

## Large self-deflection of soliton beams in LiNb03

M. Chauvet, V. Coda, H. Maillotte, E. Fazio, G. Salamo

### ▶ To cite this version:

M. Chauvet, V. Coda, H. Maillotte, E. Fazio, G. Salamo. Large self-deflection of soliton beams in LiNb03. Optics Letters, 2005, 30, n° 15, pp.1977-1979. hal-00097371

HAL Id: hal-00097371

https://hal.science/hal-00097371

Submitted on 27 Aug 2013

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Large self-deflection of soliton beams in LiNbO<sub>3</sub>

M. Chauvet, V. Coda, and H. Maillotte

Département d'Optique, Institut FEMTO-ST, UMR, CNRS, Université de Franche-Comté, 25030 Besancon, France

#### E. Fazio

Dipartimento di Energetica, Università La Sapienza and Istituto Nazionale per la Fisica della Materia, Via Scarpa 16, I-00161 Roma, Italy

#### G. Salamo

Department of Physics, University of Arkansas, Fayetteville, Arkansas 72701

Received February 15, 2005

We report the observation of large self-deflection of 2-D bright photorefractive solitons in LiNbO<sub>3</sub> crystal under a dc applied field. Beam deflection as large as 300  $\mu$ m after a 7 mm propagation distance is reported, leading to formation of curved 2-D waveguides. We attribute this large deflection to the low level of impurity acceptors present in the samples, as confirmed by numerical results from a time-dependent photorefractive model. © 2005 Optical Society of America

OCIS codes: 190.0190, 190.5330, 190.5940, 160.5320, 160.2260.

In the past decade photorefractive solitons have attracted much attention. Although the first observations 1-3 and the most advanced experiments 4-6 were realized in strontium barium niobate crystal, it was recently demonstrated that LiNbO<sub>3</sub> is an excellent candidate for forming narrow bright spatial solitons. Soliton-induced waveguides in  $LiNbO_3$  have the potential to bring about new ways to design and realize photoinduced optical components. Indeed, this mature material, which is available in good optical quality with large electro-optic, nonlinear, and acousto-optic coefficients, has already found extensive application in optical components used in the optoelectronic and telecommunication industry. However, soliton-induced waveguides could make possible novel optical components and, above all, provide access to the third spatial dimension, allowing 3-D optical circuits instead of 2-D, as achieved with standard integrated

In this Letter we show that self-focused beams in LiNbO<sub>3</sub> can give rise to curved photoinduced waveguides. Although beam bending has already been reported in the literature, it typically identifies a weak beam deflection of about  $10-20~\mu m$  for a typical 1 cm long crystal. In such experiments the deflection is essentially attributed to charge diffusion. In this Letter we report the observation of a giant deflection ( $\approx 300~\mu m$ ) of a screening soliton in LiNbO<sub>3</sub> that depends on the amplitude of the applied field. This deflection is not due to the photorefractive charge diffusion process but instead is attributed to the low concentration of acceptor impurities present in photonic-grade LiNbO<sub>3</sub> crystals.

The optical setup is similar to that in Ref. 7. The sample used for the experiment comes from an undoped z-cut photonic-grade congruent LiNbO<sub>3</sub> wafer whose absorption at 632 nm is lower than  $0.12 \text{ cm}^{-1}$ . It is 1 mm thick along the c axis (x) and 7 mm long along the beam propagation direction (y). Electrodes

are laid on the x crystal faces and the sample is placed in silicon oil to avoid arcing when an external field  $E_0$  is applied. The light beam from a He–Ne laser at 632 nm, linearly polarized along the crystal c axis, is focused with a 70 mm focal length lens at the entrance face of the crystal to a 10  $\mu$ m FWHM spot. A CCD camera in combination with an imaging lens is used to observe the beam at the exit face of the crystal.

When a positive 30 kV/cm electric field is applied along the crystal c axis, the beam diameter at the exit face gradually focuses down to 10  $\mu$ m, similarly to the report in Ref. 7, and a spatial soliton is formed. However, when the same experiment is replicated using a higher applied field, intriguing beam changes are observed at the exit face. A typical observation is depicted in Fig. 1 for a 100 µW incident beam and a 50 kV/cm external applied field  $E_0$ . In the initial stage, the beam at the exit face gradually focuses [Figs. 1(a) and 1(b)] and a 10  $\mu$ m diameter circular spot is reached after about 1 h. During this time a small beam shift (15  $\mu$ m) opposite to the c axis is also observed. Then, in a second stage, the beam is fairly stable in position and width for a few hours [Fig. 1(c)]. Thorough examination of the beam diameter, however, reveals that the beam continues to slowly self-focus during this stage. Then the entire beam shifts and diffracts [Figs. 1(d) and 1(e)]. Subsequently, a large beam shift takes place accompanied by a refocusing effect [Figs. 1(f) and 1(g)]. Finally at steady state a tightly focused beam of about  $7 \mu m$ FWHM displaced by over 200  $\mu$ m in the direction opposite to the crystal c axis is formed.

For better insight, the evolution of the beam width and the position of the beam maximum have been plotted in Fig. 2 as a function of time. The only parameter that differs from the preceding experiment is the applied field, which is now set to 40 kV/cm. The general behavior is identical, but two major differences are to be noticed. First, the anomalous beam




Fig. 1. Beam evolution at the exit face of a 7 mm long LiNbO<sub>3</sub> sample. Experimental parameters:  $E_0$  = 50 kV/cm,P=100  $\mu$ W. Images from (a) to (j) have been taken at times, respectively, equal to 0, 0.5, 2.1, 4, 4.6, 6.3, 9.6, 13, 16.3, and 19.5 h.

shift appears later in time than for the results in Fig. 1, and, second, the total beam shift is smaller. Indeed, as a general rule, we observed that the sudden defocusing will occur sooner in time and the total shift will be larger as we increase  $E_0$ . The amplitude of the shift does not increase linearly with  $E_0$  but tends to saturate at a high value. As a result, a 300  $\mu$ m maximum shift was measured experimentally for a 60 kV/cm applied field. Note that a negative  $E_0$  is not used since it gives rise to a defocusing effect. Besides, as is usually the case for photorefractive phenomena, the response time is inversely proportional to the incident intensity.

To understand the origin of the giant deflection we have analyzed theoretically the formation of the internal field E that is due to both the applied field  $E_0$  and the photorefractive space-charge field. For simplicity we make use of a 1-D model with one ionization center and one carrier for which the intensity profile I is assumed to vary along the x direction. The field E, as a function of time t and spatial coordinate x, satisfies the following differential equation t:

$$\varepsilon \frac{\partial E}{\partial x \, \partial t} = -e \mu \frac{\partial (nE)}{\partial x} - \mu k_B T \frac{\partial^2 n}{\partial x^2} - \beta_{ph} (N_D - N_A) \frac{\partial I}{\partial x}, \tag{1}$$

where e and  $\mu$  are, respectively, the charge and the mobility of the electron,  $k_B$  is the Boltzmann constant, T is the temperature,  $\varepsilon$  is the permittivity of the medium, and  $\beta_{ph}$  is the photovoltaic coefficient.  $N_D$ ,  $N_A$ , and n are, respectively, the donor, acceptor, and free-electron concentrations. Equation (1) is valid for  $N_D$  or  $N_A \gg n$ , which is satisfied when a low light intensity is used.

If we neglect the free-electron buildup time, the density of electrons is given by 12

$$n = A(I + I_d) \left( 1 + B \frac{\partial E}{\partial x} \right)^{-1}.$$
 (2)

Here  $I_d$  is the dark equivalent irradiance and A and B are constants, respectively, equal to  $s(N_D - N_A)/\gamma N_A$  and  $\varepsilon/(eN_A)$ , where s is the photoexcita-

tion cross section and  $\gamma$  is the carrier recombination rate. It is essential to note that in unintentionally doped crystals, such as the one used in our experiment,  $N_A$  is low, and, as a consequence, the term  $B \partial E_{sc}/\partial x$  cannot be neglected as is usually done for doped crystals.

Integration of Eq. (1) relative to x and substitution of Eq. (2) yields, after neglecting the second-order spatial derivative of E,

$$\begin{split} \varepsilon \frac{\partial E}{\partial t} &= -e \mu A (I + I_d) \left( 1 + B \frac{\partial E}{\partial x} \right)^{-1} E - \mu k_B T A \\ &\times \left( 1 + B \frac{\partial E}{\partial x} \right)^{-1} \frac{\partial I}{\partial x} - \beta_{ph} (N_D - N_A) I + D \,. \end{split} \tag{3}$$

Since no light is present at infinite x and a uniform field  $E_0$  is initially in place, the integration constant D is set to  $e\mu AI_dE_0$ . We solve Eq. (3) numerically using an iterative method considering a 10  $\mu$ m FWHM Gaussian beam centered at the origin. Parameters are extracted from Ref. 13, except for  $N_A$  and  $N_D$ , which are free parameters.

Numerical results are presented in Fig. 3, where the -E distribution is plotted at discrete times for two values of  $N_A$ . Since the refractive-index change is proportional to -E, we can picture the curves in Fig. 3 as the profile evolution of the photoinduced waveguide. The chosen reference time  $t_0$  is equal to  $2T_dI_d/I_{max}$ , where  $T_d = \epsilon \gamma N_A/[e\mu sI_d(N_D-N_A)]$  is the material dielectric response time in the dark.  $t_0$  is the spatial soliton formation time in a quasi-steady-state regime. In our experiment we can identify  $t_0$  as the time necessary to reach the maximum self-focusing effect. The calculation reveals that the  $N_D$  concentration has little influence on the space-charge field, whereas the  $N_A$  concentration is critical. At the beginning of the process E is described by even functions for both low [Fig. 3(a)] and higher [Fig. 3(b)]  $N_A$ concentrations. Apart from a possible weak shift due to charge diffusion, the focusing effect is symmetric and the beam deflection is consequently negligible. However, as E builds up, the index profile becomes clearly asymmetric for low  $N_A$  content [Fig. 3(a)]. Al-




Fig. 2. Beam FWHM (dots) and position of beam maximum (crosses) versus time. Experimental parameters:  $E_0$  = 40 kV/cm, P=100  $\mu$ W (the beam position curve has been arbitrarily shifted to avoid overlap).




Fig. 3. Photoinduced photorefractive field distribution produced by a 10  $\mu\mathrm{m}$  FWHM Gaussian beam versus time when (a)  $N_A=1\times10^{15}$  at. cm $^{-3}$  and (b)  $N_A=1\times10^{16}$  cm $^{-3}$ . Lower curves are at  $t=0.03t_0$ , and time is doubled for each successive curve. Dashed curve is at  $t=t_0$ . Parameters:  $I_{\mathrm{max}}/I_d=10^8,~\mu=0.74~\mathrm{cm}^2~\mathrm{V}^{-1}~\mathrm{s}^{-1},~T=290~\mathrm{K},~N_D=1.1N_A, \gamma=1.65\times10^{-8}~\mathrm{s}^{-1}~\mathrm{cm}^3,~\beta_{ph}=7\times10^{-28}~\mathrm{cm}^3~\mathrm{V}^{-1},~E_0=50~\mathrm{kV}~\mathrm{cm}^{-1}.$ 

though an accurate description of the influence of such an index profile on beam propagation necessitates solving the nonlinear Schrödinger equation, it is clear that beam bending opposite to the x axis will take place. Indeed, light will tend to follow the highindex region, which is now off center. In our experiments, we believe that the beam phase tilt due to this asymmetric index profile is large enough that after some propagation distance the light escapes from the initially formed waveguide, yielding the sudden partial defocusing. Moreover, since the beam is still experiencing focusing just before the abrupt change occurs, we can infer that  $t < t_0$ . After this stage the process is more gradual as the photoinduced waveguide adiabatically follows the light distribution change. A quasi-stable position is attained when the beam phase tilt matches the curvature of the induced waveguide. The asymmetric index profile is the direct consequence of the limited charges available to screen the applied field. It is analogous to the index grating shift observed in two-wave-mixing experiments when the applied field or the photovoltaic field is greater than the saturation field.

The validity of the model is supported by experimental evidence. First, for low  $E_0$  or at the beginning of the focusing process for higher  $E_0$ , no shift is observed because charge saturation is not reached. Second, no influence of the photovoltaic field has been noticed in our experiments, and the photovoltaic field  $E_{ph} = \beta_{ph} \gamma N_A/(e\mu s)$  leads to the conclusion that  $N_A$  is indeed low. Also note that the  $N_A$  values

( $\approx 10^{15}$  cm<sup>-3</sup>) used in the numerical calculations are realistic for unintentionally doped samples. We can even assert that the photovoltaic effect plays no role in the beam deflection. Finally, for a fixed applied field the transient defocusing appearance time is inversely proportional to the intensity. In our model, it is confirmed by the intensity dependence of  $t_0$ .

After formation of a bent soliton, the applied field and the beam can be switched off, leaving a curved waveguide in the medium. The waveguide is stored for at least several weeks in the dark and can be used to guide beams other than the original soliton beam. These low-loss bent waveguides open up new possibilities for creating complex optical circuits inside LiNbO<sub>3</sub>.

In conclusion, we have shown that self-focused beams can induce the formation of curved waveguides in photonic-grade LiNbO $_3$  crystals. The curvature arises when an external field higher than a threshold value is applied on the crystal. At steady state, a beam shift as large as 300  $\mu$ m is observed. We show that this unusual effect is due to a low concentration of acceptor impurity in the crystal. The space-charge field is consequently limited in amplitude and develops into an asymmetric distribution, causing the deflection. Numerical calculation of the space-charge field growth provides qualitative confirmation of this hypothesis.

This work was supported in part by the French Ministry of Education and Research through an Action Concertée Nanosciences 2004 (project NR137). M. Chauvet's e-mail address is mathieu.chauvet@univ-fcomte.fr.

#### References

- M. Segev, B. Crosignani, A. Yariv, and B. Fischer, Phys. Rev. Lett. 68, 923 (1992).
- G. Duree, J. L. Shultz, G. Salamo, M. Segev, A. Yariv, B. Crosignani, P. Di Porto, E. Sharp, and R. R. Neurgaonkar, Phys. Rev. Lett. 71, 533 (1993).
- M. Shih, M. Segev, G. C. Valley, G. Salamo, B. Crosignani, and P. Di Porto, Electron. Lett. 31, 826 (1995).
- J. Petter and C. Denz, Opt. Commun. 188, 55 (2001).
- J. W. Fleischer, T. Carmon, M. Segev, N. K. Efremedis, and D. N. Christodoulides, Phys. Rev. Lett. 90, 023902 (2003).
- M. Klotz, H. Meng, G. J. Salamo, M. Segev, and S. R. Montgomery, Opt. Lett. 24, 77 (1999).
- E. Fazio, F. Renzi, R. Rinaldi, M. Bertolotti, M. Chauvet, W. Ramadan, A. Petris, and V. I. Vlad, Appl. Phys. Lett. 85, 2193 (2004).
- M. F. Shih, P. Leach, M. Segev, M. Garret, G. Salamo, and G. C. Valley, Opt. Lett. 21, 324 (1996).
- M. I. Carvalho, S. R. Singh, and D. N. Christodoulides, Opt. Commun. 120, 311 (1995).
- M. Chauvet, J. Opt. Soc. Am. B 20, 2515 (2003).
- N. Fressengeas, J. Maufoy, and G. Kugel, Phys. Rev. E 54, 6866 (1996).
- D. N. Christodoulides and M. I. Carvalho, J. Opt. Soc. Am. B 12, 1628 (1995).
- L. Ren, L. Liu, D. Liu, J. Zu, and Z. Luan, J. Opt. Soc. Am. B 20, 2162 (2003).
- R. A. Rupp, R. Sommerfeldt, K. H. Ringhofer, and E. Krätzig, Appl. Phys. B 51, 364 (1990).