

Results obtained during recent flights of the LPMA balloon experiment and contribution to the Envisat validation

Y. Té, Sébastien Payan, P. Jeseck, V. Ferreira, G. Dufour, A. Butz, K. Pfeilsticker, M. Dorf, F. Weidner, C. Camy-Peyret

▶ To cite this version:

Y. Té, Sébastien Payan, P. Jeseck, V. Ferreira, G. Dufour, et al.. Results obtained during recent flights of the LPMA balloon experiment and contribution to the Envisat validation. 17th ESA Symposium on European Rocket and Balloon Programmes and Related Research., May 2005, Sanderfjord, Norway. pp.209-217. hal-00123881

HAL Id: hal-00123881

https://hal.science/hal-00123881

Submitted on 1 Mar 2022

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Results obtained during recent flights of the LPMAA balloon experiment and contribution to the ENVISAT validation

Té Y.⁽¹⁾, S. Payan⁽¹⁾, P. Jeseck⁽¹⁾, V. Ferreira⁽¹⁾, G. Dufour⁽²⁾, A. Butz⁽³⁾, K. Pfeilsticker⁽³⁾, M. Dorf⁽³⁾, F. Weidner⁽³⁾ and C. Camy-Peyret⁽¹⁾

(1) Laboratoire de Physique Moléculaire pour l'Atmosphère et l'Astrophysique Université Pierre et Marie Curie - Case 76 - 4, Place Jussieu - 75252 Paris cedex 05 - France te@ccr.jussieu.fr, phone : +33 1 44 27 96 07, Fax : +33 1 44 27 70 33

(2) Department of Chemistry

University of Waterloo - 200 University Avenue West - Waterloo, ON, Canada, N2L 3G1

(3) Institut für Umweltphysik University of Heidelberg, Heidelberg, Germany

Abstract

The LPMAA balloon experiment, based on a Fourier transform infrared (FTIR) spectrometer, has already proved its capabilities to prepare and to validate satellite missions: IASI mission, validations of ILAS and ODIN, second Atmospheric Chemistry Validation of ENVISAT (ACVE-2)...

Several flights from August 2002 to March 2004 (LPMA19, LPMA20, IASI02, LPMA22) have been dedicated to the validation of ENVISAT instruments. Results from these recent flights are presented here. This contribution to the ENVISAT validation (MIPAS, SCIAMACHY) provides high vertical resolution profiles of trace species (CH₄, N₂O, HCl, NO₂, NO, CO, O₃, HNO₃) from the upper troposphere to the lower stratosphere.

1 - Introduction

1.a - Description of the balloon-borne FTIR of the LPMAA

The Laboratoire de Physique Moléculaire pour l'Atmosphère et l'Astrophysique (LPMAA) has developed two infrared remote sensing instruments based on the same Fourier transform interferometer, a Bomem DA2.01 providing a maximum optical path difference of 50 cm. Each instrument, mounted into a stratospheric gondola with a pointing system [ref.1], is operated under large balloons (150000 m³) or 400000 m³) by CNES (Centre National d'Études Spatiales) to reach a height between 30 and 40 km. Depending on the scientific objectives, one instrument will be chosen in place of the another, allowing to study the concentration of the atmospheric trace gases located in the troposphere or in the stratosphere. For the cases discussed in this paper, flights in both configurations were dedicated to the validation of the ENVISAT satellite, launched in a sun synchronous orbit on

February 28th 2002, specially MIPAS (Michelson Interferometer for Passive Atmospheric Sounding) and SCIAMACHY (SCanning Imaging Absorption spectroMeter for Atmospheric CHartogaphY).

In its first configuration called Limb Profile Monitor of the Atmosphere (LPMA), the instrument operates in solar occultation [ref.2] and allows sounding of air masses from the upper troposphere to the middle stratosphere (tangent heights between 13 to 35 km). Figure 1 shows a schematics of the LPMA instrument and its gondola. The solar beam, after absorption by atmospheric constituents, is collected using a suntracker and is directed to the input of the interferometer. The LPMA spectrometer can observe numerous atmospheric trace gases at the same time in a large spectral range due to its dual channel output optics.




Fig.1 Schematic of the LPMA instrument and its gondola.

Three different optical configurations can be used depending of the targeted spectral regions, cf. Table 1. The long wave infrared (LWIR) configuration covers the spectral range from 650 cm⁻¹ to 4150 cm⁻¹ and is mainly used for MIPAS validation (same optical range as MIPAS), especially for trace gases like O₃, HNO₃, N₂O, CH₄,

Proceedings of the 17^{th} ESA Symposium on European Rocket and Balloon Programmes and Related Research, Sandefjord, Norway, 30 May - 2 June 2005 (ESA SP-590, August 2005)

 NO_2 , ... The short wave infrared (SWIR) configuration, from 2050 cm⁻¹ to 5320 cm⁻¹, is suitable for SCIAMACHY validation (covering the infrared channels or band 7 and band 8 of SCIAMACHY), especially for tropospheric N_2O , CO, CH₄, ... In the near infrared (NIR) configuration, the instrument covers the spectral region from 10300 cm^{-1} to 13400 cm^{-1} and has been used to validate GOMOS products in the O_2 A

band. Other scientific instruments can be accommodated in the same gondola: the DOAS (Differential Optical Absorption Spectroscopy) spectrometer from the Institut für Umweltphysik, University of Heidelberg, Germany or the Cold Atmospheric Emission Spectral Radiometer (CAESR) from Denver University.

Configuration	Detectors	Beamsplitter	Spectral range (cm ⁻¹)
LPMA(LWIR)	HgCdTe / InSb	KCl	650-1300 & 1750-2000
, ,	•		2750-3150 & 4100-4150
LPMA(SWIR)	InSb / InSb	CaF ₂	2050-2220 & 4220-4440
` ,		_	2700-3150 & 4770-5320
LPMA(NIR)	Si / Si	Quartz	10300-11000
• ,		•	12700-13400
IASI-Balloon	HgCdTe / InSb	KC1	650-2000
	2		1800-3000

Table 1: Different optical configurations of the balloon-borne instruments.

In the second configuration shown in Fig.2, the named IASI-balloon (Infrared instrument Atmospheric Sounding Interferometer), measures in the nadir viewing geometry, the thermal atmospheric emission of the surface/atmosphere system [ref.3]. This upwelling radiation is composed by several contributions as the emission of the Earth surface, the emission and absorption of atmospheric constituents, the emission of the clouds or the backscattered solar radiation. This downlooking configuration allows sounding of the low layers of the atmosphere, from the lower background surface, which could be the ground, water, forest, ..., to the actual height of the instrument.

The temperature of the sounded atmospheric scene and the operational temperature of the instrument are approximately the same at about 300 K. Therefore we have to radiometrically calibrate the measured spectra. Two well-characterised blackbodies stabilized at two different temperatures are needed to perform this absolute calibration by using the equation (1), [ref.3, ref.4]:




Fig.2 : Schematic of the IASI-balloon instrument and its gondola.

$$S_{\text{scene}}^{\text{calib}} = \frac{\varepsilon_{\text{WBB}} B_{\text{WBB}} \left(S_{\text{scene}}^{\text{meas}} - S_{\text{CBB}}^{\text{meas}} \right) - \varepsilon_{\text{CBB}} B_{\text{CBB}} \left(S_{\text{scene}}^{\text{meas}} - S_{\text{WBB}}^{\text{meas}} \right)}{S_{\text{WBB}}^{\text{meas}} - S_{\text{CBB}}^{\text{meas}}}$$
(1)

In this equation ϵ_{WBB} and ϵ_{CBB} are the emissivities of the warm and cold blackbodies and B_{WBB} and B_{CBB} are the theoretical Planck functions at the appropriate temperatures. The radiometrically calibrated spectra of the atmospheric scenes covers the spectral range from

650 cm⁻¹ to 3000 cm⁻¹. IASI-balloon is used here to validate the total columns measured by SCIAMACHY in its nadir sounding mode.

These two balloon-borne instruments LPMA and IASI-balloon, have been involved in several Announcement of Opportunities projects for validating the ENVISAT chemistry instruments.

Details for these dedicated flights are summarised in Table 2. The results retrieved (total columns or volume mixing ratio profiles) from several of these flights are presented in section 2 and 3. Some of these results have been already presented during the

ACVE-2 (Second Workshop on the Atmospheric Chemistry Validation of ENVISAT) workshop in May 2004 [ref.5] or will be published soon in scientific journals [ref.6].

Date	Flight	Location	Principal trace gases	Validation
05/08/2002	IASI02	Kiruna, Sweden	O ₃ ; CH ₄ ; N ₂ O; CO	SCIAMACHY
19/08/2002	LPMA18 (NIR)	Kiruna, Sweden	H ₂ O; O ₂ A band	GOMOS
04/03/2003	LPMA19 (LWÍR)	Kiruna, Sweden	HNO_3 , N_2O , NO_2	MIPAS
23/03/2003	LPMA20 (SWIR)	Kiruna, Sweden	CH ₄ , CO, N ₂ O, NO ₂	SCIAMACHY
09/10/2004	LPMA21 (SWIR)	Aire-sur-l'Adour, France	CH_4 , CO , N_2O , NO_2	SCIAMACHY
24/03/2004	LPMA22 (LWIR)	Kiruna, Sweden	HNO₃, N₂O	MIPAS

Table 2: Balloon flights performed during ESABC validation campaigns.

1.b - The retrieval algorithm LARA

In order to retrieve the concentration of the atmospheric trace gases from their spectral signatures observed in our spectra, we have to

model the infrared radiance at the entrance of the interferometer. This radiance can be represented by the radiative transfer equation:

$$L_{\widetilde{v}}(M) = L_{\widetilde{v}}(M_0) T_{\widetilde{v}}(M_0, M) + \int_{M_0}^{M} J_{\widetilde{v}}(s') T_{\widetilde{v}}(s', M) \alpha(s') ds'$$
(2)

where $L_{\tilde{v}}(M)$ is the radiance observed at point M (along the line of sight) by the instrument in unit of W/(cm²sr cm⁻¹), $L_{\tilde{v}}(M_0)$ is the radiance of the background (at the lower boundary $M_{\rm 0}$ of the line of $T_{\tilde{v}}(M_0, M)$ is the atmospheric transmission along the line of sight between the points M_0 and M, $J_{\tilde{v}}(s')$ is the source function at any point between M_0 and M, and $\alpha_{\widetilde{\nu}}(s')$ is the absorption coefficient. The first term gives the background emission after transmission in the atmosphere and the second term corresponds to thermal emission of different atmospheric layers along the line of sight. Table 3 gives more details about the LPMAA Atmospheric Retrieval Algorithm (LARA) [ref.7], especially the different input parameters used by LARA, as the spectroscopic data base (Hitran 2004 here), the water vapour continuum (CKD 2.4), ... The forward model is combining spectroscopic parameters (position, intensity and broadening coefficient of the absorption lines), geometric and instrument parameters (flight trajectory and profile, instrument line shape) and retrieval parameters (surface temperature, columns or vertical profiles), to calculate the theoretical spectrum. After the forward model, a minimization algorithm based on a Levensberg-Marquardt method, allows to fit this calculated spectrum to the measured one.

Forward Hitran 2004 Model: CKD 2.4 (H₂O) water vapour continuum χ factor for CO₂, collision induced absorption for N2 and O2 Water vapour self-broadening Reflected downward flux Emission / Transmission Nadir or limb viewing User defined spectral spacing Effective temperature and pressure in layers (number density weighted) Line mixing for CO₂ Convolution in the spectral domain Pre-calculated absorption cross-sections (look-up tables) Minimisation Global fit approach algorithm: Retrieved parameters Instrumental line shape Instrumental spectral shift Vertical VMR columns and/or profiles Surface temperature (nadir) Surface emissivity (nadir)

Table 3: LPMAA Atmospheric Retrieval Algorithm (LARA).

2 - Validation of SCIAMACHY in nadir looking with IASI-balloon

2.a - The second flight of IASI-balloon

The IASI-balloon instrument has flown for its second flight from Kiruna (Sweden, 68° N, 21° E), the 5th August 2002 (between 18:30 UT and 22:10 UT with 2 hours and 30 min at float). This flight was dedicated to the validation of SCIAMACHY in its nadir sounding mode. The flight took place at the end of daytime with a night transition, in rather warm conditions (in Artic summer). The background surface was either ground, lakes or rivers, forests, mountain areas, ... In order to characterise the atmospheric scene observed by IASI-balloon, a visible CCD and an infrared camera were used. These two imagers are co-aligned with the spectrometer's instantaneous field of view, which is represented by a circle in the infrared pictures of Fig.3. The dark colours, cf. Fig.3a, correspond to cold pixels like clouds, which are at higher altitude and colder than the ground. Ground surface, rivers or lakes are warmer than the clouds and appear in clearer colours, cf. Fig.3b.




Fig. 3: Night-time infrared pictures recorded during the flight IASI02 (top (Fig. 3a) - bottom (Fig. 3b)).

Figure 4 shows two radiometrically calibrated spectra of the atmosphere recorded at float around 31 km, for a clear sky case. The brightness

temperature of the background surface is around 265.45 K. The good superposition of these two spectra in the overlap region between 1850 and 1920 cm⁻¹, confirms the good performances of the IASI-balloon instrument. Several absorption bands of CO₂, O₃, N₂O, CH₄, H₂O and CO can be observed.





Fig.4: Radiometrically calibrated atmospheric spectra recorded by IASI-balloon.

2.b - Comparison between IASI02 and SCIAMACHY in nadir sounding

The total columns of CH₄ and O₃ measured during the IASI02 flight are compared to those obtained by SCIAMACHY operating in the nadir looking in the same day. Figure 5 shows the good co-location (latitude and longitude) between the IASI-balloon and SCIAMACHY footprints (less than 600 km). On Fig.5, the mean value of the total columns of CH₄ measured by IASI-balloon is represented in red and is compared to the corresponding columns obtained by SCIAMACHY from band 7 (cf. Fig.5a) and from band 8 (cf. Fig.5b). SCIAMACHY band 7 underestimates the balloon CH₄ total columns by about 25%. And the CH₄ columns derived from SCIAMACHY band 8 show strong and strange variations.

The comparison between the balloon and satellite O₃ columns is shown in Fig.6. Ozone results derived from SCIAMACHY band 1, show a positive bias of about 30% compared to the balloon ones as seen in Fig.6a. Some ozone column results from band 2 are negative as seen in the colour-coded map of Fig.6b. The official products of ESA for our balloon flight have not been reprocessed because of instrument problems with SCIAMACHY in that period.







Fig.5: Total columns of CH4 measured by IASIballoon and SCIAMACHY (top (Fig.5a) - bottom (Fig.5b)).

3 - Validation of SCIAMACHY and MIPAS with LPMA

3.a - The LPMA19 and LPMA22 flights

The LPMA19 and LPMA22 flights were performed from Esrange (Kiruna, Sweden) with take-off at 13:20 UT on March 4th 2003 and at 14:05 UT on March 23th 2004 respectively. The long wave infrared (LWIR) optical configuration was used for both flights. Fig.7 shows an example of spectra recorded during the LPMA19 flight. A dichroïc is used to split the spectral range of the spectral range is split again using optical and numerical filters in order to optimise the signal to noise ratio and the data rate. Absorption bands of several atmospheric trace gases like CO₂, O₃, N₂O, NO₂, HCl, CH₄, H₂O, HF, HNO₃, can be observed in the four windows.






Fig.6: Total columns of O₃ measured by IASI-balloon and SCIAMACHY (top (Fig.6a) - bottom (Fig.6b)).

3.b - Comparison between MIPAS and LPMA19

The satellite profiles considered here have been measured during the same day as the LPMA19 flight. The mean position is 65.7°N and 13.4°E at 21:13 UT. During sunset, data have been recorded by the LPMA instrument for locations of the tangent points between (66.7°N and 22.8°E) and (66.1°N and 15.6°E). The spatial and temporal colocation is then quite good. Figure 8 presents the comparison between balloon and satellite results for O₃. The profile (in red) obtained by version v4.61 of the ESA operational retrieval algorithm shows strong oscillations. But the IMK scientific profile is smoother with a difference less than 8% as compared to the LPMA sunset profile. The IMK profile is representative of the expected MIPAS results when a final version of the operational retrieval algorithm is available.




Fig.7: Spectra recorded by the LPMA instrument during the LPMA19 flight.




Fig. 8: O3 profile measured by LPMA19 and MIPAS.

In the comparison of CH_4 profiles, strong oscillations can be also observed in the ESA operational profile, cf. Fig.9. The IMK scientific profile of CH_4 agrees very well with the LPMA profile, within the error bars.




Fig.9: CH₄ profile measured by LPMA19 and MIPAS.

The last comparison concerns the N_2O molecule. Figure 10 shows a good agreement between the three profiles (scientific, operational and balloon). But this agreement is a little worse than for CH_4 , with maximum differences of about 30%.




Fig.10: N₂O profile measured by LPMA19 and MIPAS.

The last version of the ESA operational algorithm of MIPAS is v4.62. Data recorded by MIPAS for LPMA19, have not yet reprocessed. But generally, the reprocessed operational profiles have been improved (no or smaller oscillations).

3.c - Comparison between LPMA and SCIAMACHY in himb sounding

The flights LPMA19 and LPM22 were originally dedicated to the validation of MIPAS products, but some results can be used also for the validation of the SCIAMACHY instrument in limb sounding (the same sounding geometry as for the LPMA instrument). Results derived from the LPMA19 flight were provided by the French LPMA instrument team. Preliminary results from the LPMA22 flight were produced by the German DOAS instrument team. For the validation of O₃, Fig.11 shows (in grey diamond) the LPMA sunset profile of O₃ with its high vertical resolution, (in blue open diamond) the same profile degraded to the SCIAMACHY vertical resolution (lower) and (in red circle) the SCIAMACHY profile itself. The concentrations inferred from the satellite instrument agree with the balloon-borne results in the available altitude range from 18 km to 32 km with a maximum difference of about 20%. A slightly negative altitude offset in the satellite profile is observed.

For Fig.12, the same representation is used with the square symbol for the balloon-borne ascent profiles and the green dashed line for the O₃ sonde from Esrange. The comparison between satellite and balloon results reveals a good agreement within the

error bars, in the altitude range from 22 km to 32 km. The relative differences are smaller than 20%. But below 22 km, the agreement is poor and the difference is larger than 50%, although the coincidence of the measured air masses is quite good between 10 km and 20 km.




Fig.11: O₃ profile measured by LPMA19 and SCIAMACHY.





Fig.12: O₃ profile measured by LPMA22 and SCIAMACHY.

The NO₂ validation study is represented in Fig.13. Since the NO₂ molecule shows strong photochemical variations (between day and night time), a photochemical correction model is needed. The same symbols and colours as in previous figures are used. The only difference is that the blue open diamond represents the balloon profile convolved to the SCIAMACHY vertical resolution

but with the photochemical correction. The comparison is performed for the same air masses measured by the SCIAMACHY instrument before and after the balloon flight. For both cases, a quite good agreement between satellite and balloon results is observed (within the combined errors bars). The maximum differences are at most 30% between 18 km and 32 km.







Fig.13: NO₂ profile measured by LPMA19 and SCIAMACHY (before the balloon flight (top) - after the balloon flight (bottom)).

The comparison between SCIAMACHY and LPMA22 results is shown in Fig.14. The square symbol represents again the balloon ascent measurements. The satellite results agree very well with the balloon ones in the altitude range from

12 km to 32 km. The differences are smaller for the "satellite before balloon" case (top figure). The differences are a slightly larger for the "satellite after balloon" case (bottom figure).






Fig.14: NO₂ profile measured by LPMA22 and by SCIAMACHY before the balloon flight (top) or after the balloon flight (bottom).

4 - Conclusion

This paper has discussed the results obtained with the two versions of the LPMAA experiment that have been used for the validation of the ENVISAT instruments MIPAS and SCIAMACHY. The agreement between satellite and balloon results are encouraging. As a rough conclusion, the SCIAMACHY data for August 5th 2002 provided in the officially distributed ESA products are not reliable, because of possible calibration problem for that period. The operational algorithm of MIPAS, shows, for version v4.61 strong oscillations, which have more or less been suppressed in version v4.62.

Acknowledgements

Funding support was provided through the ESABC project by the European Space Agency (ESA), the Centre National d'Études Spatiales (CNES) and the Deutsche Luft und Raumfahrt (DLR) agency. We are grateful to the hospitality and support of the Swedish Space Corporation (SSC/Esrange). We thank the CNES team from Aire-sur-l'Adour without which all the successful balloon launches would not have been possible. Thanks are also due to the Institute of Environmental Physics and Institute of Remote Sensing (Bremen, Germany) for their results from SCIAMACHY in limb sounding, for the Institute of Meteorology in Karlsruhe (IMK) for the MIPAS «scientific profiles» and to the CNES team of « Nacelles Pointées » from Toulouse with which we have performed all our flights since several years.

5 - References

1. F. P. Wildi

New concepts and performances in azimuth control of large balloon gondolas. ESA publications, SP-317, pp. 357-361 (1991).

- 2. C. Camy-Peyret, P. Jeseck, T. Hawat, G. Durry, S. Payan, G. Berubé, L. Rochette and D. Huguenin The LPMA balloon-borne FTIR spectrometer for remote sensing of atmospheric constituents. ESA publications, SP-370, pp. 323-328 (1995).
- 3. Y. Té, P. Jeseck, C. Camy-Peyret, S. Payan, G. Perron and G. Aubertin Balloonborne calibrated spectroradiometer for atmospheric nadir sounding.

 Appl. Opt., 41, 6431-6441, 2002.

- 4. H. E. Revercomb, H. Buijs, H. B. Howell, D. D. LaPorte, W. L. Smith and L. A. Sromovsky Radiometric calibration of IR Fourier transform spectrometers: solution to a problem with the High-resolution Interferometer Sounder.

 Appl. Opt., 27, pp. 3210-3218 (1988).
- 5. G. Dufour, S. Payan, Y. Té, P. Jeseck, V. Ferreira, C. Camy-Peyret, M. Eremenko, K. Pfeilsticker, W. Gurlit, A. Butz. K. Gerilowski ENVISAT Validation results obtained with LPMA and IASI-Balloon FTIR. Atmospheric Chemistry Validation of ENVISAT, ESRIN, 3-7 May 2004 (ACVE-2 CONFERENCE PROCEEDINGS).
- 6. A. Butz, H. Bösch, C. Camy-Peyret, M. Chipperfield, G. Dufour, M. Dorfl, A. Rozanov, C. von Savigny, C. Sioris, S. Payan, F. Weidner, and K. Pfeilsticker Validation of stratospheric O3 and NO2 profiles retrieved from ENVISAT/SCIAMACHY Limb measurements by comparison with balloon-borne direct sun observations. (manuscript prepared for Atmos. Chem. Phys.).
- 7. C. Clerbaux, J. Hadji-Lazaro, S. Payan, C. Camy-Peyret and G. Mégie Retrieval of CO columns from IMG/ADEOS spectra.

 IEEE transactions on geoscience and remote sensing, 37, pp. 1657-1661 (1999).