



HAL
open science

Tree inclusion problems

Patrick Cegielski, Irene Guessarian, Yuri Matiyasevich

► **To cite this version:**

| Patrick Cegielski, Irene Guessarian, Yuri Matiyasevich. Tree inclusion problems. 2007. hal-00159125

HAL Id: hal-00159125

<https://hal.science/hal-00159125>

Preprint submitted on 3 Jul 2007

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

TREE INCLUSION PROBLEMS *

PATRICK CÉGIELSKI¹, IRÈNE GUESSARIAN² AND
YURI MATIYASEVICH³

Abstract. Given two trees (a target T and a pattern P) and a natural number w , *window embedded subtree problems* consist in deciding whether P occurs as an embedded subtree of T and/or finding the number of size (at most) w windows of T which contain pattern P as an embedded subtree.

P is an embedded subtree of T if P can be obtained by deleting some nodes from T (if a node v is deleted, all edges adjacent to v are also deleted, and outgoing edges are replaced by edges going from the parent of v (if it exists) to the children of v). Deciding whether P is an embedded subtree of T is known to be NP-complete.

Our algorithms run in time $O(|T|2^{2^{|P|}})$ where $|T|$ (resp. $|P|$) is the size of T (resp. P).

1991 Mathematics Subject Classification. 68Q25, 68W05.

For 60th birthday of Serge Grigorieff

1. INTRODUCTION

Given two trees, we study the following problems: can P be obtained from T by deleting nodes? if this holds, is P contained in a reasonably small (i.e. of a small height) subtree of T ? If P is contained in a subtree of height w (a “window”) of T , how many times can this occur?

These problem generalize in a natural way the subsequence problems for words: we proved in [BCGM01], that the problem of counting the number of w -windows

Keywords and phrases: Subtree inclusion, algorithm.

* Support from the Council for Grants of the President of the Russian Federation under grant NSh-8464.2006.1 is acknowledged by the third author.

¹ LACL, Université Paris 12, Route forestière Hurtault, F-77300 Fontainebleau, France, e-mail: cegielski@univ-paris12.fr

² LIAFA, UMR 7089 and Université Paris 6, 2 Place Jussieu, 75254 Paris Cedex 5, France; send correspondence to e-mail: ig@liafa.jussieu.fr

³ Steklov Institute of Mathematics, Fontanka 27, St. Petersburg, 191023, Russia. e-mail: yumat@pdmi.ras.ru

of a text t containing a pattern p as a subsequence (i.e. letters of p appear in the window in the same order as in p but are not necessarily consecutive and may be interleaved with other letters) can be solved in time $O(n)$ where n is the size of t . The generalization to trees can be stated as follows: P is an embedded subtree of T if P can be obtained by deleting some nodes from T (if a node v is deleted, the ingoing edge to v (if it exists) is also deleted, and outgoing edges are replaced by edges going from the parent of v (if it exists) to the children of v). P is an embedded subtree of T within a w -window if P is an embedded subtree of W , and W is a subtree of T of height w .

We cannot hope to reduce (in a simple and succinct way) the problem of finding whether P is an embedded subtree of T within a w -window to the subsequence problem for words by encoding T and P by words t and p respectively, and then solving some subsequence problem for t and p : it is known [KM95] that even the simpler problem of deciding whether P is an embedded subtree of T is NP-complete, hence the length of t and/or p would probably be exponential in the size of T and/or P .

The problem of finding embedded occurrences of a pattern in a window of a tree is important in two areas extensively studied recently:

1. retrieving information from structured documents [KM95] such as dictionaries: via a pattern embedding the user can specify the structure and content of the parts of the document she/he is interested in.
2. discovering frequent substructures in semi-structured data; most semi-structured data are modeled by colored labelled trees (e.g. itemsets in relational databases, chemical compounds, XML documents), and mining such structures is naturally done via finding tree embeddings.

The paper is organized as follows: in section 2 we define notations and problems, in section 3 we describe a new algorithm to decide whether a pattern is embedded in a target (not interesting per se, but for the generalisations given in the following section), and section 4 presents our main contribution, namely, (i) determining (and counting) the w -windows containing a pattern as an embedded subtree, and (ii) determining (and counting) the embeddings of a pattern within a w -window of text.

2. NOTATIONS

Let A be an alphabet.

Definition 2.1. (i) A **tree** T on A is a finite connected acyclic graph $T = \langle V, E, color \rangle$, where V is the set of nodes, E is the set of edges, and $color: V \mapsto A$ is a coloring function: each node (or vertex) is colored by a letter of A .

(ii) A **rooted tree** $T = \langle V, E, color, r \rangle$ is a tree where a node r has been distinguished and is called the **root** of the tree.

In a rooted tree, edges are naturally directed (from the root to the leaves): all nodes have in-degree one except for the root which has in-degree zero; if (u, v) is

an edge oriented from u to v , u is the *parent* of v and v is a *child* of u ; each node has exactly one parent, except for the root which has none; a node can have any finite number of children and childless nodes are called *leaves*. Nodes have a *depth*: the depth of the root is 0, and if the depth of node v is n , then all its children have depth $n + 1$. Two nodes having the same parent are called *siblings*. The transitive closure of the parent (resp. child) relation is called the *ancestor* (resp. *descendent*) relation.

In the case of trees, the notions similar to subword and subsequence for words exist and are called *subtree* and *embedded subtree*. Formally:

Definition 2.2. Let $T = \langle V, E, color, r \rangle$ and $T' = \langle V', E', color', r' \rangle$ be rooted trees, such that:

1. $V' \subseteq V$ and $E' \subseteq E$
2. the coloring of V' is preserved in T' , i.e. $\forall v' \in V' \ color'(v') = color(v')$

Then T' is said to be a **subtree** of T .

Moreover, if for each node v' from T' all its descendents in T are also its descendents in T' , then T' is said to be a **bottom-up subtree** of T .

Intuitively, a bottom-up subtree of T can be obtained by taking a node v of T together with all of v 's descendents and corresponding edges; a subtree of T can be obtained by taking a bottom-up subtree of T and pruning some edges together with the subtree below the pruned edge. The bottom-up subtree of T rooted at node v will be denoted by $T[v]$.

Definition 2.3. Let $T = \langle V, E, color, r \rangle$ and $T' = \langle V', E', color', r' \rangle$ be rooted trees; an **embedding** from T' into T is an injective mapping $\tau: V' \hookrightarrow V$, such that:

1. for every $v' \in V'$, $color(\tau(v')) = color'(v')$, i.e. τ preserves colors.
2. v'_1 is an ancestor of v'_2 in T' iff $\tau(v'_1)$ is an ancestor of $\tau(v'_2)$ in T , i.e. τ preserves the ancestor-descendent relationship.

T' is said to be an **embedded subtree** of T if there exists an embedding from T' into T .

Intuitively, an embedded subtree of T is obtained by deleting some nodes from T and gluing together the remaining edges in a way preserving the ancestor-descendent relationship of T .

Definition 2.4. A **window** of $T = \langle V, E, color, r \rangle$ is a subtree $W = \langle V', E', color', r' \rangle$ of T such that for any node v of T belonging to V' all siblings of v in T also belong to V' .

For $w \in \mathbb{N}^*$, a **w -window** of T is a window of T of height at most w . P is an **embedded subtree of T within a w -window** if there is an embedding from P into T and moreover the image of P is contained in a w -window of T .

Example 1. In Figure 1, T', T'', T''' are respectively a bottom-up subtree, a subtree, and an embedded subtree of T . T''' is an embedded subtree of T within a 2-window. W is a 1-window of T .




FIGURE 1. A tree T with bottom-up subtree T' , subtree T'' , embedded subtree T''' , and 1-window W .

THE PROBLEMS

- **Problem 1.** Given two trees, *target tree* T and *pattern tree* P , to decide whether P is an embedded subtree of T .
- **Problem 2.** Given two trees, *target* T and *pattern* P , to decide whether P is an embedded subtree of T within a w -window. Subsidiarily, to count the number of windows of height at most w of T containing P as an embedded subtree.
- **Problem 3.** Given two trees, *target* T and *pattern* P , to count the number of occurrences of P as an embedded subtree of T within a w -window.

RELATED RESULTS

Different versions of the first problem have been considered. Papers [K92,KM95] shows that problem 1 is NP-complete, but can be solved in time $O(ptk2^{2k})$, where $p = |P|$ (resp. $t = |T|$) is the number of nodes (size) of P (resp. T), **if** the out-degrees of the nodes of P are bounded by k .

3. EMBEDDED SUBTREE SEARCH

We study Problem 1: given target tree T and pattern tree P , to decide whether P is an embedded subtree of T .

3.1. NOTATIONS

Without loss of generality we may assume that the nodes of P are labelled: each node has a *unique* label from $\{1, \dots, p\}$, see Figure 2. This yields a labelling of the bottom-up subtrees of P : bottom-up subtree rooted at node v has the same label as node v . A bottom-up subtree of P rooted at node v is represented either by the label of v or in the form $P[v]$: the bottom-up subtree rooted at node v having label j , will thus be denoted by j or $P[v]$ according to the context.

Definition 3.1. A **forest** of P is a set of bottom-up subtrees of P . A forest will be denoted by the set of labels of its roots. Forest F is said to be a **max-forest**




FIGURE 2. A pattern P and a postorder labelling of its bottom-up subtrees.

if all its trees are incomparable, i.e. there are no $t, t' \in F$ such that t' is a proper bottom-up subtree of t .

We say that forest F **dominates** forest F' (different from F itself) if every tree from F' is a bottom-up subtree of some tree from F .

3.2. IDEA

Let T be a (big) tree (called the *target*) and let P be a (small) tree (called the *pattern*). For each node v of T we will compute a *configuration*, which will be a set of max-forests of bottom-up subtrees of P .

Intuitively, each forest of the configuration at node v represents a set of subtrees of P which can be embedded in $T[v]$ *simultaneously*, i.e. in such a way that the images of different trees wouldn't intersect.

Definition 3.2. A **configuration** is a set $C = \{F_1, F_2, \dots, F_k\}$, where each F_i is a max-forest of P , and if $i \neq j$ then F_i does not dominate F_j .

Definition 3.3. The union of two configurations $C = \{F_1, F_2, \dots, F_k\}$ and $C' = \{F'_1, F'_2, \dots, F'_{k'}\}$ is configuration D , denoted by $D = C \otimes C'$ and obtained as follows:

- (1) let $D' = \{F_i \cup F'_{i'} \mid i \in \{1, \dots, k\}, i' \in \{1, \dots, k'\}\}$
- (2) we pass from D' to D'' by removing from each $F'_j = F_i \cup F'_{i'}$ which is not a max-forest all labels of subtrees of P which are subtrees of a tree whose label is already present in F'_j
- (3) we pass from D'' to D by removing each F''_j which is dominated by some F''_i .

Note that:

- In (2), we obtain a forest F''_j such that all subtrees of P belonging F''_j are maximal in F''_j (all subtrees of F''_j are incomparable), i.e. F''_j is a max-forest.
- The resulting $D = \{F_i \mid i = 1, \dots, l\}$ is a set of max-forests of P , such that if $i \neq j$ then F_i does not dominate F_j , hence it is a configuration.

3.3. ALGORITHM

We traverse T bottom-up (from leaves to root, or in postorder): to scan a node v of T we must first have scanned all its children. With each node v of T we will associate a configuration C_v such that for every forest F from C_v all trees from F can be simultaneously embedded into $T[v]$. This leads to the following algorithm. (See Figure 3(1) for an example.)

Algorithm1


```

Let  $r :=$  the label of the root of  $P$ ; //initialization
FORALL nodes of  $T$  visited bottom-up DO
  (1) IF node  $v$  is a leaf of  $T$ , its configuration is the set of singletons  $\{i\}$  where
       $i$  is the label of a leaf  $v'$  of  $P$  such that  $color(v) = color(v') = a$ .
      //If no leaf of  $P$  is colored  $a$ , the configuration of  $v$  is the empty set.
      ENDIF
  (2) IF node  $v$  is an internal node colored  $a$ , with children  $v_1, \dots, v_n$ , THEN DO
      (a)  $\Delta := D := C_{v_1} \otimes C_{v_2} \otimes \dots \otimes C_{v_n}$ ;
      (b) FORALL nodes  $w$  of  $P$  colored  $a$  and labelled  $j$  DO //  $w$  has the same
          color as  $v$ 
          Let  $j_1, \dots, j_p$  be the children (if they exists) of  $j$  in  $P$ 
          IF there is an  $F_i \in D$  such that  $\{j_1, \dots, j_p\} \subseteq F_i$  // true if there are
          no children
          THEN
            IF  $w = r$  THEN DO
              output " $P$  is an embedded subtree of  $T$ ";
              STOP ENDDO ENDIF
            let  $\Delta^*$  be the result of deleting  $j_1, \dots, j_p$  from all forests in  $\Delta$ ;
             $\Delta := \Delta^* \cup \{\{j\}\}$ 
          ENDIF
        ENDDO
      (c) Remove from  $\Delta$  all dominated forests and take the resulting configura-
          tion for  $C_v$ 
      ENDDO
    ENDIF
  ENDDO
output " $P$  isn't an embedded subtree of  $T$ "

```

Comment: when computing Δ^* we delete every occurrence of j_1, \dots, j_p in all forests because they are used only to obtain j ; at a later stage (i) either we will choose j but it already appears, or (ii) we will choose another subtree, and in that latter case we do not need j_1, \dots, j_p .

Complexity: the number of bottom-up subtrees of P is bounded by p where p is the size of P , the number of forests is bounded by 2^p , hence the number of configurations is at most $O(2^{2^p})$.

FIGURE 3. A target T where the pattern of Figure 2 is embedded.

3.4. IMPROVEMENTS

IMPROVEMENT 1

Algorithm1 can be improved in practice by reducing the number of configurations. Let us say node v from the target and node v' from the pattern are **upward compatible**, if the path from v' to the root of P can be embedded into the path from v to the root of T . We can preprocess target T in order to precompute for each node v in T the set $c(v)$ of all nodes of P which are upward compatible with it. This is trivial for the root of T . Passing from a node v in T to its child w we just add to $c(v)$ each node u in P such that: 1) u has the same color as w , and 2) the parent of u is in $c(v)$.

The algorithm computing the set $c(w)$ of nodes of P upward compatible with w is as follows:

```

Let  $r :=$  the label of the root of  $P$ ; //initialization
FORALL nodes  $w$  of  $T$  visited top-down DO
  IF node  $w$  is the root of  $T$ ,
    - THEN  $c(w) = \begin{cases} \{r\} & \text{if } color(w) = color(r), \\ \emptyset & \text{otherwise.} \end{cases}$ 
    - ELSE DO //  $w$  has parent  $v$  whose set of upward compatible nodes is  $c(v)$ 
       $c(w) = c(v) \cup \{u \mid u \text{ is a node of } P, \text{ and } parent(u) \in c(v), \text{ and } color(u) = color(w)\}$  ENDDO
  ENDIF
ENDDO

```

The complexity of this preprocessing is $O(tp)$. Then in step 1 of algorithm1 we can demand that v' should be upward compatible with v . This could considerably reduce the number of configurations to deal with. For instance in Figure 3 the set of nodes upward compatible with the rightmost leaf of T is $\{1, 2, 6\}$, which reduces by half the set of configurations on the rightmost path of T , see Figure 3(2).

IMPROVEMENT 2

The idea of upward compatibility can be further developed as follows. Suppose that $\tau : V' \rightarrow V$ is an embedding of $P = \langle V', E', color', r' \rangle$ into $T = \langle V, E, color, r \rangle$. We can consider an *inverse embedding* σ which is a partial map from V onto $\mathcal{P}(E') \cup V'$ defined as follows:

- if $v = \tau(v')$ then $\sigma(v) = v'$;
- if v'_1 is the parent of v'_2 in P , then for every internal node v on the path from $\tau(v'_1)$ to $\tau(v'_2)$ the value of $\sigma(v)$ is equal to the edge between v'_1 and v'_2 ;
- for all other nodes of T the value of σ is left undefined.

For every v from T we can consider the set $S(v)$ of all possible values of $\sigma(v)$, for all possible embeddings τ . It is easy to check that these sets satisfy the following conditions:

- [A1] if $S(v)$ contains some v' from V' then $color(v) = color'(v')$;
- [A2] if $S(v)$ contains some v' from V' then
 - if v' has the parent v'_1 in P , then v has the parent v_1 in T and $S(v_1)$ contains either v'_1 or the the edge between v'_1 and v' ;
 - for every child v'_2 of v' in P , the node v has a child v_2 such that the set $S(v_2)$ contains either v'_2 or the edge between v' and v'_2
- [A3] if $S(v)$ contains the edge between some v'_2 and its parent v'_1 in P then
 - v has the parent v_1 in T and $S(v_1)$ contains either v'_1 or the edge between v'_1 and v'_2
 - v has a child v_2 such that $S(v_2)$ contains either v'_2 or the edge between v'_1 and v'_2

We cannot easily calculate “true” sets $S(v)$ so instead of this we calculate (and dynamically maintain during the entire work of the algorithms) some sets $\tilde{S}(v)$ such that $S(v) \subseteq \tilde{S}(v)$. Initially, we put

$$\tilde{S}(v) := \{v' | v' \in V' \text{ and } color'(v') = color(v)\} \cup E' \quad (1)$$

and then diminish these sets as long as either [A2] or [A3] is violated.

As soon as we calculated configuration C_v for some node v , we try to further trim $\tilde{S}(v)$ in the following way. The set $\tilde{S}(v)$ can be represented as the union $\tilde{S}(v) = \tilde{S}_V(v) \cup \tilde{S}_E(v)$ where $\tilde{S}_V(v) = \tilde{S}(v) \cap V(P)$ and $\tilde{S}_E(v) = \tilde{S}(v) \cap E(P)$. Now we can put

$$\tilde{S}(v) = (\tilde{S}_V(v) \cap (\cup_{w \in F \in C_v} V(P[w]))) \cup \tilde{S}_E(v). \quad (2)$$

(and then check conditions [A2] and [A3], of course).

In its turn, the calculation of $\tilde{S}(v)$ allows us to add on step (b) additional restriction on the choice of j , namely, we can demand that $j \in \tilde{S}(v)$.

Calculation of the $\tilde{S}(v)$'s can be done with only linear slow-down of the algorithm. This can be implemented as follows. Each of the two conditions in [A2]

and the two conditions in [A3] can be expressed by a logical formula of the form

$$u' \in S(v) \Rightarrow u'_1 \in S(v_1) \vee \dots \vee u'_k \in S(v_k) \quad (3)$$

where v_1, \dots, v_k are adjacent to v in T and u'_1, \dots, u'_k are either adjacent or incident to u' in P . Initially, each node v of T writes down these formulas for each elements u' from the set (1). As soon as the right hand side of the implication (3) turns out to be empty (**=false**), the node removes u' from $\tilde{S}(v)$ and then v informs its parent (if it exists) and its children (if they exist) about this removal. Having got this information, the parent and the children delete corresponding disjunctive terms in their formulas. This process can propagate by a chain but since each time at least one disjunctive term is deleted, the total complexity is bounded by the total size of initial formulas which is at most $O(tp^2)$.

4. THE WINDOW SUBSEQUENCE ALGORITHM

4.1. PROBLEM 2

We study Problem 2: Given a target tree T and a pattern tree P , to decide whether pattern P is an embedded subtree of tree T within a window of height w . We will solve an extended version of Problem 2, where we count the number of w -windows of T where P can be embedded.

The algorithm is somehow similar to Algorithm1, but the configurations contain not only the embedded bottom-up subtrees of P , but also the least possible depth of its image in T . We will thus store in configurations ordered pairs consisting of a bottom-up subtree t of P embedded in T , together with an integer n representing the length of the longest root-to-leaf path (in T) of the current embedding of t . The number n will be called a *depth-stamp*.

Moreover, for the extended version of Problem 2, a counter N will count the number of w -windows containing P .

Configurations will be replaced by *s-configurations* where each occurrence of a subtree of P will be augmented by the least possible value of the depth-stamp. We will modify accordingly the definition of union of configurations to keep track of the depth-stamps.

Definition 4.1. A **stamped subtree** is an ordered pair (t, n) where t is a bottom-up subtree of P , and $n \in \mathbb{N}$ is called a depth-stamp.

A set F of stamped trees is called an *s-forest*, and it is said to be a **min-s-forest** if the following three conditions hold

- there are no (t, n) and $(t, n') \in F$ such that $n' < n$, i.e. all its subtrees occur at the least possible depth in T ,
- there are no (t, n) and $(t', n) \in F$ such that t' is a proper bottom-up subtree of t , and
- there are no (t, n) and $(t', n') \in F$ such that $n' \geq n$ and t' is a proper bottom-up subtree of t .

An s-forest F is said to **dominate** s-forest F' if for every (t', n') from F' there is a (t, n) from F such that

- t' is a bottom-up subtree of t , and
- $n' \geq n$.

An **s-configuration** is a set $C = \{F_1, F_2, \dots, F_k\}$, where each F_i is a min-s-forest, and if $i \neq j$ then F_i does not dominate F_j .

Definition 4.2. If an s-forest F is not a min-s-forest, we can associate with F a **reduced** forest, the min-s-forest $D = \text{red}(F)$ obtained by the following algorithm:

- (1) remove all stamped subtrees $(t, n) \in F$ such that there is a $(t, n') \in F$ with $n' < n$: then all subtrees of P belonging F are affected with the minimal possible depth-stamp.
- (2) remove all stamped subtrees $(t', n) \in F$ such that there is $(t, n) \in F$ such that t' is a proper bottom-up subtree of t , and
- (3) remove all stamped subtrees $(t', n') \in F$ such that there is $(t, n) \in F$ such that $n' \geq n$ and t' is a proper bottom-up subtree of t .

Definition 4.3. A subtree T' of T is said to be a **minimal subtree** of T containing P iff P is an embedded subtree of T' , but there is no proper subtree T'' of T' such that P is an embedded subtree of T'' .

Definition 4.4. The **union** of two s-configurations $C = \{F_1, F_2, \dots, F_k\}$ and $C' = \{F'_1, F'_2, \dots, F'_{k'}\}$ is s-configuration $D = C \otimes_s C'$ obtained as follows:

- (1) let $D' = \{\text{red}(F_i \cup F'_{i'}) \mid i \in \{1, \dots, k\}, i' \in \{1, \dots, k'\}\}$
- (2) if F'_i is dominated by F'_j remove F'_i .

It is easy to see [BCGM01, K92] that a window of height w of T contains P as an embedded subtree iff it contains a minimal subtree of T containing P ; therefore, it is enough to count the number of w -windows of T containing a minimal subtree containing P .

We now present Algorithm2 for problem 2. See Figure 4 for an illustration of algorithm2 with $w = 3$.

Algorithm2

Let $r :=$ the label of the root of P ; $N := 0$; //initializations

FORALL nodes of T visited bottom-up DO

- (1) IF node v is leaf of T , THEN the configuration of v is the set of singletons $\{(i, 0)\}$ where i is the label of a leaf v' of P such that a is the color of both v and v' ,
//if no leaf of P has the same color as v the configuration of v is the empty set.
- (2) IF node v is an internal node colored a , with children v_1, \dots, v_n , whose respective configurations are C_{v_i} , $i = 1, \dots, n$, THEN DO
 - (a) FOR $i = 1, \dots, n$, DO

```

 $C'_{v_i} := \{ \{(l, d+1) | (l, d) \in F_j \text{ and } h+d+1 \leq w \text{ where } h \text{ is the}$ 
 $\text{height of } l \text{ in } P \} | F_j \in C_{v_i} \} // \text{subtree } (l, d+1) \text{ cannot contribute to any}$ 
 $\text{embedding in a } w\text{-window if } h+d+1 > w \text{ ENDDO}$ 
(b)  $\Delta := D := C'_{v_1} \otimes_s C'_{v_2} \otimes_s \dots \otimes_s C'_{v_n};$ 
(c) FORALL nodes  $w$  of  $P$  colored  $a$  and with label  $j$  DO  $//w$  has same color
as  $v$ 

- IF node  $w$  is not a leaf of  $P$ ,
 $//w$  is an internal node of  $P$  labelled  $j$ 
  - THEN Let  $j_1, \dots, j_p$  be the children of  $j$  in  $P$ ,
FOR  $\{(j_1, d_1), \dots, (j_p, d_p)\} \subseteq F_i \in D$ 
 $\Delta := \Delta \cup \{ \{(j, \max\{d_1, \dots, d_p\})\} \};$
  - ELSE  $//w$  is a leaf labelled  $j$  and colored  $a$ 
 $\Delta := \Delta \cup \{ \{(j, 0)\} \};$


ENDIF
ENDDO
(d) Reduce the forests in  $\Delta$  and remove from  $\Delta$  all dominated forests
(e) Take the resulting configuration  $\Delta$  for  $C_v$ 
(f) IF there are  $d$  and  $F \in C_v$  such that  $(r, d) \in F$ 
THEN DO let  $d_0$  be the least possible value of such a  $d$ ;
 $N := N + 1 + (w - d_0);$ 
output “ $P$  is an embedded subtree of  $T$  within  $1+(w-d_r)$   $w$ -windows
at node  $v$ ”.
ENDDO
ENDIF
ENDDO
ENDIF
ENDDO

```

4.2. Problem 3.

Given two trees, *target* T and *pattern* P , we want to count the number of occurrences of P as an embedded subtree of T within a window of height w .

In order to solve problem 3, configurations will now be replaced by *ms-configurations* which are multisets of multiforests (i.e. multisets of stamped subtrees of P). We must also modify the definition of union of configurations to keep track of the multiplicities. Note that we now neither reduce the multiforests nor remove dominated multiforests.

Definition 4.5. An **ms-configuration** is a multiset $C = \{F_1, F_2, \dots, F_k\}$, where each F_i is a multiset of bottom-up stamped subtrees of P .

Definition 4.6. The **union** of two ms-configurations $C = \{F_1, F_2, \dots, F_k\}$ and $C' = \{F'_1, F'_2, \dots, F'_{k'}\}$ is ms-configuration $D = C \otimes_{ms} C' = \{F_i \cup F'_{i'} | i \in \{1, \dots, k\}, i' \in \{1, \dots, k'\}\}$.

Algorithm3 below will count the number of embeddings of P as an embedded subtree of T within a w -window. The reader is invited to note that




FIGURE 4. Pattern P occurs in four 3-window (window of height 3 at most) in target T .




FIGURE 5. Pattern P has 2 occurrences in a window of height 2 of T .

- (1) we now must count all embedded occurrences of P within a w -window and not only the minimal ones.
- (2) we consider P as a *colored labelled tree*, that is each node has a (unique) *label* from $\{1, \dots, p\}$, and a (not necessarily unique) *color* from the alphabet: different nodes can have the same color but not the same label. For instance in Figure 5, P has 2 occurrences in a 2-window of T .

Figure 6 illustrates algorithm3 on the same P, T as in Figure 4, with $w = 2$. Figure 7 illustrates algorithm3 with thread-like trees P, T with $w = 3$.

Algorithm3

Let $r :=$ the label of the root of P ; $N := 0$; //initializations
 FORALL nodes of T visited bottom-up DO




FIGURE 6. Pattern P has 5 occurrences (which are crossed with a backslash) in a 2-window (window of height at most 2) of target T .

- (1) IF node v is leaf of T , THEN the configuration of v is the set of singletons $\{(i, 0)\}$ where i is the label of a leaf v' of P such that a is the color of both v and v' , //the configuration of v is the empty set if no leaf of P is colored a .
- (2) IF node v is an internal node colored a , with children v_1, \dots, v_n , whose respective configurations are C_{v_i} , $i = 1, \dots, n$, THEN DO
 - (a) FOR $i = 1, \dots, n$, DO

$$C'_{v_i} := \{(l, d+1) \mid (l, d) \in F_j \text{ and } h+d+1 \leq w \text{ where } h \text{ is the height of } l \text{ in } P\} \mid F_j \in C_{v_i}$$
 ENDDO
 - (b) $\Delta := D := C'_{v_1} \otimes_{ms} C'_{v_2} \otimes_{ms} \dots \otimes_{ms} C'_{v_n}$;
 - (c) FORALL nodes w of P colored a and labelled j DO // w has same color as v
 - IF node w is a not a leaf
// w is an internal node labelled j
 - THEN Let j_1, \dots, j_p be the children of j in P ; DO

$$\Delta := \Delta \cup \{(j, \max\{d_1, \dots, d_p\})\}$$
 ; ENDDO
 - ELSE $\Delta := \Delta \cup \{(j, 0)\}$; // w is a leaf labelled j
 ENDDIF
 - (d) FORALL (r, d_r) such that $(r, d_r) \in F_j \in \Delta$ DO
 output “ P is an embedded subtree of T within a w -window at node v ”.
 $N := N + 1$;
 $F_j := F_j \setminus \{(r, d_r)\}$; ENDDO
 - (e) $C_v := \Delta$




FIGURE 7. Pattern P has 7 occurrences (crossed with a backslash) in a 3-window of target T .

ENDDO
 ENDIF
 ENDDO

5. CONCLUSION

In the present paper we answered some problems about tree inclusions, namely deciding whether a pattern is an embedded subtree of a target within a w -window, counting the number of windows of height at most w of the target containing the pattern as an embedded subtree, and counting the number of occurrences of the pattern as an embedded subtree of the target within a w -window.

There are many other interesting problems concerning tree inclusions, for instance, counting the number of windows of height exactly w of the target containing the pattern as an embedded subtree, or counting in a slice of the target tree.

REFERENCES

[BCGM01] L. Boasson, P. Cegielski, I. Guessarian, Yu. Matiyasevich, Window Accumulated Subsequence Matching is linear, *Annals of Pure and Applied Logic* Vol. 113 (2001), pp. 59-80.
 [CMNK05] Y. Chi, R. Muntz, S. Nijssen, J. Kok, Frequent subtree mining – an overview, *Fundamenta Informaticae*, Volume 66 (2005), pp. 161–198.

- [K92] P. Kilpelainen, Tree matching problems with applications to structured text databases, PhD Thesis, Helsinki (1992), <http://thesis.helsinki.fi/julkaisut/mat/tieto/vk/kilpelainen/>
- [KM95] P. Kilpelainen, H. Mannila, Ordered and Unordered Tree Inclusion, SIAM Journal on Computing , Volume 24 ,B Issue 2 B (April 1995), pp. 340 - 356.

Communicated by (The editor will be set by the publisher).
today.