

Density hardening plasticity and mechanical aging of silica glass under pressure: Raman spectroscopic study

Damien Vandembroucq, Thierry Deschamps, Camille Coussa, Antoine Perriot, Etienne Barthel, Bernard Champagnon, Christine Martinet

▶ To cite this version:

Damien Vandembroucq, Thierry Deschamps, Camille Coussa, Antoine Perriot, Etienne Barthel, et al.. Density hardening plasticity and mechanical aging of silica glass under pressure: Raman spectroscopic study. 2008. hal-00258599v1

HAL Id: hal-00258599 https://hal.science/hal-00258599v1

Preprint submitted on 22 Feb 2008 (v1), last revised 13 May 2009 (v3)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Density hardening plasticity and mechanical aging of silica glass under pressure: A Raman spectroscopic study

Damien Vandembroucq¹, Thierry Deschamps², Camille Coussa², Antoine Perriot¹, Etienne Barthel¹, Bernard Champagnon² and Christine Martinet²

**Laboratoire Surface du Verre et Interfaces,

**Unité Mixte de Recherche CNRS/Saint-Gobain,

39 Quai Lucien Lefranc, F-93303 Aubervilliers, France.

² Universit de Lyon; Universit Lyon1; UMR5620 CNRS Laboratoire de Physico-Chimie des Matriaux Luminescents, Domaine Scientifique de la Doua, Bt. Kastler, 10 rue Ampre, Villeurbanne, F-69622, France. (Dated: February 22, 2008)

In addition of a flow, plastic deformation of structural glasses (in particular amorphous silica) is characterized by a permanent densification. Raman spectroscopic estimators are shown to give a full account of the plastic behavior of silica under pressure. While the permanent densification of silica has been widely discussed in terms of amorphous-amorphous transition, from a plasticity point of view, the evolution of the residual densification with the maximum pressure of a pressure cycle can be discussed as a density hardening phenomenon. In the framework of such a mechanical aging effect, we propose that the glass structure could be labelled by the maximum pressure experienced by the glass and that the saturation of densification could be associated with the densest packing of tetrahedra only linked by their vertices.

I. INTRODUCTION

The behavior of amorphous silica under high pressure has been intensively studied in the last decades^{1,2,3,4,5,6,7} and has recently motivated an increasing amount of numerical studies^{8,9,10,11,12,13,14,15,16,17}. Silica appears to be elastic up to around 10 GPa and to exhibit a plastic behavior at higher pressure. Two features can be emphasized at that level: i) in the elastic regime, the compressibility exhibits a surprising non monotonous evolution with a maximum at around 2-3 GPa^{1,18,19} ii) when unloading from the plastic regime a permanent densification up to 20 % can be observed^{1,2,3,4,5,6,7}. No clear evidence of alteration of the tetrahedral short range order in this unloaded state has been observed^{5,20}.

Above 25 GPa, a change from 4-fold to 6-fold coordination is observed⁵. This 6-fold amorphous seems not to be quenchable at zero pressure. When unloading downto zero pressure, no trace of 6-fold coordination is obtained. Performing X-ray Raman scattering experiments on oxygen K-edge, Lin et al²¹ observed a reversible electronic bonding transition between 10 and 25 GPa. The latter was attributed to a fourfold quartz-like to a sixfold stishovitelike change of configuration of silica glass. For P>25 GPa the densification process saturates and after unloading to ambient, the density level is the one obtained with a maximum pressure $P\simeq 25$ GPa^{18,19}.

Questions remain about the nature of the densified phase and the mechanism of densification. Recent studies¹⁷ have proposed the existence of an "activated" five-fold coordination at high pressure allowing reorganization toward a denser tetrahedral network. In former studies, in analogy with amorphous ice, Lacks¹² has proposed a first order transition between 2 differ-

ent tetrahedral amorphous phases of silica. This transition would be kinetically hindered at room temperature. This idea of poly-amorphism has received a lot of attention^{7,14,15,16,22,23,24}. At this stage it is important to separate the known transition at very HP between a 4-fold amorphous silica and a 6-fold amorphous silica involving a change in the short-range order^{5,9} from an additional hypothetical transition at lower P between 2 different amorphous phases of tetrahedral silica and involving the medium range order²⁵.

The most recent numerical 17 and experimental 7 works as well as the existence of a continuous range of densities for amorphous silica⁶ after return to ambient pressure seem to rule out this idea of transition between 2 different forms of amorphous tetrahedral silica. However, the original observation of Lacks remains of interest: performing molecular dynamics simulations driven in volume¹¹, he noted discontinuities in the pressure signal associated with local pressure induced mechanical instabilities. The latter are reminiscent of the shear induced mechanical instabilities previously identified in flowing liquids²⁶. Note that similar localized transitions are widely believed to be the main mechanism of shear plasticity of amorphous materials²⁷ and can be associated to the vanishing of one eigenvalue of the Hessian matrix of the interatomic potential 28,29 .

In parallel to a structural study, it may be worth considering the pressure induced densification process in silica according to a mechanical perspective. In particular, in the Raman spectroscopic measurements to be presented below, we will use cycles of pressure of increasing maxima. This protocol will help us to discriminate in the spectral patterns, modifications due to the reversible elastic deformation of the network from other ones due

to plastic structural reorganizations.

We first present the experimental methods i.e. Raman measurements of silica submitted to pressure cycles and analyze their results in terms of mechanical behavior. Two series of experiments are discussed. In series A Raman measurements are performed in situ during the loading and unloading stages of successive pressure cycles, first in the elastic range (below 10 GPa) where full reversibility is expected, then in the plastic range (up to 18 GPa) where permanent densification is expected. This first series of experiments gives a nice illustration of (densification) plasticity in the context of a silica glass. In series B Raman measurements are performed ex situ at ambient pressure before and after pressure cycles of increasing P_{max} from 9 to 25 GPa. Using a quantitative (though empirical) relation between permanent densification and the D_2 shift before/after loading cycle^{30,31}, we can extract an estimate of the residual densification after each pressure cycle. This second series of experiments thus allows us to follow the evolution of permanent densification vs the pressure maximum of the cycle i.e. the density hardening behavior of silica.

We finally give a discussion, first in terms of mechanical behavior, then in terms of amorphous structure. These results are of primary importance in the description of the mechanical properties of silica. While silica is daily used as a calibration sample for nano-indentation measurements, it appears that the mechanical behavior of this material is not fully described. It has been shown recently³¹ that the constitutive laws available^{32,33} which do not take hardening into account fail to fully describe the densification process induced by an indentation test. The above data can be used to include hardening in a simple constitutive law of silica³⁴, which gives a precise account for this behavior.

Beyond their interest in terms of mechanical behavior, these results can also be discussed in terms of amorphous structure. In particular, as detailed below, densification can be regarded as a typical glassy phenomenon, resulting from a mechanical aging process. Following this perspective, the amorphous densified structure would be associated with the quench of the structure at high pressure and could be labelled by a fictive pressure in the very same acception as a fictive temperature can be used to label a structure obtained by thermal aging.

II. EXPERIMENTAL METHODS

Bars of amorphous silica (Saint-Gobain Quartz IDD) are shattered into pieces. Splinters of characteristic length of 10 $\mu \rm m$ are submitted to cycles of pressure in a "Sidoine" Diamond Anvil Cell (DAC) with a maximum pressure in the range [1-25 GPa]. Raman spectra are collected with a Renishaw RM 1000 micro-spectrometer with a Ar⁺-ion 514 nm, 50 mW laser excitation). A small piece of ruby is introduced together with the silica splinter in order to monitor the pressure level using the shift

of the R1-luminescence band.

Two series of experiments are presented.

- In series A in situ measurements of the Raman spectrum are collected all along the compression cycle. Three cycles are presented, The first one with $P_{max} = 7.3$ GPa lies in the elastic domain, te third cycle consists of a compression up to $P_{max} = 18$ GPa followed by a decompression at 1 GPa, finally the last cycle consists of a compression up to $P_{max} = 16$ GPa and a direct return to ambient pressure induced by the breakdown of a diamond. Methanol is used as a pressure transmitting fluid in this series of experiments (quasi-hydrostatic conditions). A detailed presentation of these in situ experiments can be found in 35 .
- In series B Raman measurements are performed ex situ at ambient pressure before and after each cycle of pressure. A series of compression cycles is presented where the pressure maximum is increasing from 9 GPa for the first cycle to 25 GPa for the last cycle. In this case, the pressure transmitting fluid is a mix similar to 5:1 methanol-ethanol, which ensures hydrostaticity up to 16 to 20 GPa³⁶. The Raman spectrum is measured before loading and after unloading, the diamond-anvil-cell being emptied of the transmitting fluid.

Figure 1 contrasts the initial spectrum of a sample (plain line) and that obtained after a 18 GPa hydrostatic loading (red line).

Between 200 and 750 cm⁻¹ we can identify a main band at 440 cm⁻¹ which results from the symmetric stretching mode of bridging oxygens between two Si atoms. This band is intense, and affected by the densification process through a decrease of the inter-tetrahedral angles Si-O-Si³⁷: the band gets narrower and is shifted to higher wave numbers.

The defect lines D_1 and D_2 , at 492 and 605 cm⁻¹, are respectively attributed to the breathing modes of the




FIG. 1: Raman spectra obtain with an amorphous silica sample before (plain line) and after (dotted line) a 18 GPa hydrostatic loading.




FIG. 2: Sketch of a typical pressure/density curve expected in elastoplasticity. A reversible elastic behavior is obtained up to the elastic limit pressure P_0^Y . When loading above P_0^Y , plasticity sets in and the (elastic) unloading from P_1^Y is characterized by a residual densification. A subsequent loading at $P_2^Y > P_1^Y$ reproduces the previous unloading curve up to P_1^Y before plasticity sets in again. The elastic limit has thus evolved under loading from P_0^Y to P_1^Y and P_2^Y . The knowledge of this density hardening behavior (evolution of the limit elastic pressure with density at zero pressure) is necessary to give a proper modelling of plasticity of glasses.

four-membered and three-membered $rings^{13,38}$. Their area ratio was previously used in literature as an indicator for the variation of the "fictive temperature" 39,40,41, which is associated with a slight change of density. The effect of pressure seems to be better accounted for by the shift of the D_2 line. As discussed by Polsky *et al*⁴², this may be due to pressure induced variations of the Raman cross section. The D_2 line is of particular interest since it has almost no overlap with the main band. Sugiura et al. 30 correlated the position of the D_2 line with the ratio of the sample density ρ to its initial density ρ_0 . The residual density evaluated through this relation accounts for both irreversible and elastic densification due to residual elastic strain. However, several works 30,43,44 evidenced that the D₂ line position is only marginally sensitive to residual elastic strains. This correlation was recently used to probe the densification gradient surrounding a plastic imprint in silica obtained by indentation³¹.

III. RESULTS AND INTERPRETATION

We describe in the following the experimental results and give an interpretation in the framework of the elastoplastic response of continuous media.

A. Continuum mechanics

We first recall briefly the formalism of elasto-plasticity. Fig. 2 shows the hydrostatic stress as a function of the volumetric strain of a medium submitted to pressure. Below a threshold value of pressure P_0^Y the material remains fully elastic and the volumetric deformation is reversible. When increasing the pressure beyond threshold, plasticity sets in and an irreversible deformation adds up to the elastic reversible deformation. When unloading from $P_1^Y > P_0^Y$, the material behaves elastically and only the elastic part of deformation is recovererd. Loading again to a higher pressure $P_2^Y>P_1^Y$, we observe the same phenomenology with a crucial difference: the onset of plasticity has increased from P_0^Y to P_1^Y . In other words, the mechanical behavior depends on the history of mechanical loading. The material has experienced hardening⁴⁵ which can be regarded as a mechanical aging. Such a behavior is standard for metal shear plasticity and usually results at the structural level from the entanglement or the pinning of dislocations by impurities⁴⁶. Metals however do not exhibit any volumetric plastic deformation (dislocation motion is a volume conserving mechanism). However, irreversible changes of density are familiar in soil mechanics and granular materials (dilatancy effect) 47 . Using hydrostatic pressure p and equivalent shear stress τ as coordinates, the typical mechanical behavior of a material like silica glass can be summarized as shown on Fig. 3. Before any loading, the material is elastic up to a threshold which depends both on pressure and shear. In these coordinates this elastic threshold corresponds to a continuous curve intersecting the two axis. When reaching threshold, if the stress is increased, plasticity sets in and the elastic limit is convected to the maximum value of stress experienced by the material. At macroscopic scale, one tries to characterize this hardening behavior, relating the evolution of densification with the pressure maximum. At microscopic scale, in the present case of silica, in absence of a microscopic mechanism as well defined as the motion of dislocation, a pending question remains to identify and understand a structural signature of density hardening.

B. Elasto-plastic behavior of silica under pressure

In this section we present the results of in situ raman measurements (series **A**). Two patterns of the Raman spectra measured in situ during the pressure cycles are discussed: i) the shift of the main band ω_M ; i) the shift of the D_2 line ω_{D2} .

On Fig. 4 and 5 we show the evolution of the position of these two bands for a cycle of pressure up to $P_{max} = 7.3$ GPa (black symbols). We observe a full reversibility between loading and unloading. This result is consistent with the usual estimate $P_c \simeq 10$ GPa for the onset of permanent densification in silica. The evolution of these indicators is also plotted on the same figures for




FIG. 3: Limit of the elastic domain in the space of stresses (pressure in abscissa, equivalent shear stress in ordinate). The behavior remains elastic for any stress left or below this limit. When stress reaches this limit, plasticity sets in and the limit curve can be convected at higher stresses (hardening). Pressure cycles allow to give a quantitative account of the evolu-




FIG. 4: Raman shift of the main band ω_M in the elasticplastic regime. Successive pressure loading and unloading cycles are depicted. Filled and empty symbols correspond to loading and unloading curves respectively. For a pressure maximum $P_{max} = 7.3$ GPa, a full reversibility is obtained (elastic behavior). For a larger maximum pressure $P_{max} = 18$ GPa, a residual shift is obtained after unloading (plastic behavior). An additional loading at $P_{max} = 16$ GPa reproduces the last unloading curve, indicating the increase of the elastic limit under loading (hardening).

the second series of cycles up to $P_{max}=17.9$ GPa. We now see that below $P_c\simeq 10$ GPa, the same elastic behavior as before is recovered; then a change of slope on loading is noticeable at least for the position of the main band; then the unloading curve does not reproduce the initial loading one and there appears a permanent change of the spectrum at ambient pressure; when loading again, one follows the very last unloading curve. These two




FIG. 5: Raman shift of D2 line ω_{D2} in the elastic-plastic regime (same conditions as above).

curves appear to be very similar to the ideal case of hardening plasticity depicted in Fig. 2. This spectroscopic study allows us to closely follow the elastic-plastic behavior of silica under pressure.

We now discuss the evolution of permanent densification after cycles of increasing pressure. The latter is estimated through the shift of the D_2 line. Following Ref.³¹, the densification was estimated using the empirical relation:

$$\frac{\Delta\omega_{D2}}{\omega_{D2}} \simeq \left(\frac{\Delta\rho}{\rho}\right)^{0.14} \tag{1}$$

The results are summarized on Fig. 6. We thus obtain the evolution of the permanent densification with the pressure maximum P^Y of each pressure cycle. We obtain a continuous range of increasing densities with an apparent saturation. As shown on Fig. 6, this evolution can be approached by a sigmoidal curve. Comparable results were obtained recently on window glass using an octahedral multi-anvil apparatus⁴⁸. In mechanical terms, this allows us to give a quantitative account of the density hardening behavior of silica. In the space of stresses depicted in Fig. 3, we have obtained the evolution of the maximum pressure P_Y below which the material remains fully elastic as a function of the glass density.

IV. DISCUSSION

Raman spectroscopic estimators have been shownn to give a full account of the density hardening behavior of silica under pressure. Raman scattering measurements during a loading/unloading pressure cycle closely reproduce the elastoplastic behavior usually observed in stress/strain curves: full reversibility below a limit stress,




FIG. 6: Evolution of the residual densification vs the maximum pressure of the pressure cycle (symbols). The dashed line is an indicative sigmoidal curve corresponding to a 18% maximum densification.

appearance of a residual deformation with an elastic unloading for larger stresses. A crucial difference obviously lies in the fact that in the present study the evolution of hydrostatic pressure vs density is considered instead of shear stress vs shear strain as in usual metal plasticity. From a mechanical point of view, the detailed analysis of the density increase with the maximum pressure of the cycle allowed us to study the evolution of the residual densification with the parameter P^{Y} along the abscissa of Fig. 3. Such a knowledge is of crucial importance for the determination of constitutive equation modelling the plastic behavior of silica. It was shown in Ref.³¹ that when restricting the plastic criterion to perfect plasticity (i.e. assuming no hardening effect) it was not possible to account for the permanent densification of amorphous silica around a plastic imprint induced by indentation. Conversely, as shown in Ref. 34 the assumption of an elliptic plastic criterion coupling shear stress and pressure together with the data of density hardening extracted from the present experiments allow to describe successfully this phenomenon of indentation induced densification.

From a physical/structural point of view, the present results suggest that the description of densified silica need not the hypothesis of an amorphous-amorphous transition between two types of tetrahedral networks. simpler and alternative scenario consists of pressure induced reorganizations of the amorphous network allowing a more efficient packing of tetrahedra remaining linked by their vertices only. Such a scenario does not exclude the occurence of 5-fold or 6-fold coordinated silica in the plastic regime at high pressure. However, the latter would correspond to intermediate states between two amorphous tetrahedral structures. This occurrence of 5-fold or 6-fold coordination would thus simply denote the necessity of cutting and rebonding between the two structures. The denser structure would thus be quenched when pressure decreases down to ambient conditions. In that sense, the final structure could be labelled by the maximum pressure the material experienced. In this context of mechanical aging, the latter pressure could be thought of as a "fictive" pressure in the same acception as the fictive temperature in a more classical thermal aging experiment. Note that these denser structures may be affected by internal stresses due to the succession of localized reorganizations. Looking finally at orders of magnitude for the density of the various phases of silica, we observe that the density of the stable crystalline equivalent at zero pressure (quartz) is 2.65 while the density of the metastable coesite (stable at 2-3 GPa) is 3.01. The density of fused silica being 2.2, a 20% increase gives 2.64 i.e values close to quartz but well below coesite. In analogy with hexagonal and random close packing, an interesting question could thus be whether the maximum observed density of amorphous silica corresponds to any geometrical maximal packing of tetrahedra bonded by their vertices only i.e. the maximum density of the continuous random network. To our knowledge, though the packing of space by tetrahedra, or ellipsoids has been considered^{49,50}, this question has not been discussed yet.

V. ACKNOWLEDGMENTS

The authors acknowledge useful discussions with G. Kermouche and would like to thank CECOMO and High Pressure facilities of University Lyon1. This work has been supported by the ANR "plastiglass" contract no ANR-05-BLAN-0367-01.

¹ P. W. Bridgman and I. Simon, J. Appl. Phys **24**, 405 (1953).

² H. M. Cohen and R. Roy, J. Am. Ceram. Soc. 44, 523 (1961).

³ J. D. Mackenzie, J. Am. Ceram. Soc. **46**, 461 (1963).

⁴ A. Polian and M. Grimsditch, Phys. Rev. B 41, 6086 (1990).

⁵ C. Meade, R. J. Hemley, and H. K. Mao, Phys. Rev. Lett. 69, 1387 (1992).

⁶ Y. Inamura, M. Arai, M. Nakamura, T. Otomo, N. Kita-

mura, S. M. Bennington, A. C. Hannon, and U. Buchenau, J. Non-Cryst. Solids **293-295**, 389 (2001).

⁷ Y. Inamura, Y. Katayama, W. Utsumi, and K. I. Funakoshi, Phys. Rev. Lett. **93**, 015501 (2004).

⁸ W. Jin, R. K. Kalia, P. Vashishta, and J. P. Rino, Phys. Rev. Lett. **71**, 3146 (1993).

⁹ W. Jin, R. K. Kalia, P. Vashishta, and J. P. Rino, Phys. Rev. B **50**, 118 (1994).

 $^{^{10}\,}$ R. G. D. Valle and E. Venuti, Phys. Rev. B ${\bf 54},\,3809$ (1996).

¹¹ D. J. Lacks, Phys. Rev. Lett. **80**, 5385 (1998).

- ¹² D. J. Lacks, Phys. Rev. Lett. **84**, 4629 (2000).
- ¹³ A. Rahmani, M. Benoit, and C. Benoit, Phys. Rev. B 68, 184202 (2003).
- ¹⁴ L. P. Dávila, M. J. Caturla, A. Kubota, B. Sadigh, T. D. de la Rubia, J. F. Shackelford, S. H. Risbud, and S. H. Garofalini, Phys. Rev. Lett. **91**, 205501 (2003).
- $^{15}\,$ L. Huang and J. Kieffer, Phys. Rev. B $\mathbf{69},\,224203$ (2004).
- ¹⁶ L. Huang and J. Kieffer, Phys. Rev. B 69, 224204 (2004).
- ¹⁷ Y. Liang, C. R. Miranda, and S. Scandolo, Phys. Rev. B 75, 024205 (2007).
- ¹⁸ A. Polian and M. Grimsditch, Phys. Rev. B **47**, 13979 (1993).
- ¹⁹ C. S. Zha, R. J. Hemley, H. K. Mao, T. S. Duffy, and C. Meade, Phys. Rev. B **50**, 13105 (1994).
- ²⁰ R. J. Hemley, H. K. Mao, P. M. Bell, and B. O. Mysen, Phys. Rev. B **57**, 747 (1986).
- ²¹ J.-F. Lin, H. Fukui, D. Prendergast, T. Okuchi, Y. Q. Cai, N. Hiraoka, C.-S. Yoo, A. Trave, P. Eng, M. Y. Hu, et al., Phys. Rev. B **75**, 012201 (2007).
- ²² G. D. Mukherjee, S. N. Vaidya, and V. Sugandhi, Phys. Rev. Lett. 87, 195501 (2001).
- ²³ M. S. Shell, P. G. Debenedetti, and A. Z. Panagiotopoulos, Phys. Rev. E **66**, 011202 (2002).
- ²⁴ B. Champagnon, C. Martinet, C. Coussa, and T. Deschamps, J. Non-Cryst Solids 353, 4208 (2007).
- ²⁵ B. T. Poe, C. Romano, and G. Henderson, J. Non-Cryst. Solids **341**, 162 (2004).
- ²⁶ D. L. Malandro and D. J. Lacks, Phys. Rev. Lett. **81**, 5576 (1998).
- ²⁷ M. L. Falk and J. S. Langer, Phys. Rev. E **57**, 7192 (1998).
- ²⁸ C. E. Maloney and A. Lemaître, Phys. Rev. Lett. **93**, 195501 (2004).
- ²⁹ C. E. Maloney and A. Lemaître, Phys. Rev. E **74**, 016118 (2006).
- ³⁰ H. Sugiura, R. Ikeda, K. Kondo, and T. Yamadaya, J. Appl. Phys. 81, 1651 (1997).
- ³¹ A. Perriot, V. Martinez, C. Martinet, B. Champagnon, D. Vandembroucq, and E. Barthel, J. Am. Ceram. Soc. 89, 596 (2006).

- ³² A. Shorey, K. Xin, K. Chen, and J. Lambropoulos, Proc SPIE **3424**, 72 (1998).
- ³³ K. Xin and J. Lambropoulos, Proc. SPIE **4102**, 112 (2000).
- ³⁴ G. Kermouche, E. Barthel, D. Vandembroucq, and P. Dubujet, submitted to Acta Mat. (2007).
- ³⁵ B. Champagnon, C. Martinet, M. Boudeulle, D. Vouagner, C. Coussa, T. Deschamps, and L. Grosvalet, J. Non-Cryst Solids 354, 569 (2008).
- ³⁶ J. Besson and P. Pinceaux, Rev. Sci. Instrum. **50**, 541 (1979).
- ³⁷ S. Mochizuki and N. Kawai, Solid State Communications 11, 763 (1972).
- ³⁸ F. L. Galeneer, Solid State Communications 44, 1037 (1982).
- ³⁹ B. Champagnon, C. Chemarin, E. Duval, and R. L. Parc, J. Non-Cryst. Solids 274, 81 (2000).
- ⁴⁰ R. L. Parc, B. Champagnon, P. Guenot, and S. Dubois, J. Non-Cryst. Solids **293-295**, 367 (2001).
- ⁴¹ B. Champagnon, R. L. Parc, and P. Guenot, Phil. Mag. B 82, 251 (2002).
- ⁴² C. H. Polsky, K. H. Smith, and G. H. Wolf, J. Non-Cryst. Solids **248**, 159 (1999).
- ⁴³ Y. Hibino, H. Hanafusa, K. Ema, and S.-I. Hyodo, Appl. Phys. Lett. (1985).
- Fhys. Lett. (1985).
 T. A. Michalske, D. Tallant, and W. L. Smith, Phys. Chem. Glasses 29, 150 (1988).
- A. Khan and S. Huang, Continuum theory of plasticity (Wiley, New-York, 1995).
- 46 A. H. Cottrell, Dislocations and plastic flow in crystals
- (Oxford Univ. Press, Oxford, 1956).

 47 H. M. Jaeger, S. Nagel, and R. P. Behringer, Rev. Mod.
- Phys. 68, 1259 (1996).

 H. Ji, V. Keryvin, T. Rouxel, and T. Hammouda, Scripta
- Mat. **55**, 1159 (2006).

 49 K. Binder and W. Kob, Glassy materials and disordered
- solids (World Scientific, Singapore, 2005).
- ⁵⁰ A. Donev, F. H. Stillinger, P. M. Chaikin, and S. Torquato, Phys. Rev. Lett. **92**, 255506 (2004).