



**HAL**  
open science

# Relevant Representations for the Inference of Rational Stochastic Tree Languages

François Denis, Edouard Gilbert, Amaury Habrard, Faïssal Ouardi, Marc Tommasi

► **To cite this version:**

François Denis, Edouard Gilbert, Amaury Habrard, Faïssal Ouardi, Marc Tommasi. Relevant Representations for the Inference of Rational Stochastic Tree Languages. 2008. hal-00293511v1

**HAL Id: hal-00293511**

**<https://hal.science/hal-00293511v1>**

Preprint submitted on 21 Aug 2008 (v1), last revised 10 Sep 2008 (v3)

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Relevant Representations for the Inference of Rational Stochastic Tree Languages<sup>\*</sup>

François Denis, Édouard Gilbert, Amaury Habrard, Faïssal Ouardi, and Marc Tommasi

- 1- Laboratoire d'Informatique Fondamentale de Marseille (L.I.F.) UMR CNRS 6166.  
`{francois.denis,amaury.habrard,faissal.ouardi}@lif.univ-mrs.fr`
- 2- Laboratoire d'Informatique Fondamentale de Lille (L.I.F.L.), INRIA and  
É.N.S. Cachan  
`{edouard.gilbert,marc.tommasi}@inria.fr`

**Abstract.** Recently, an algorithm, DEES, was proposed for learning rational stochastic tree languages. Given an i.i.d. sample of trees drawn according to a rational stochastic language, DEES outputs a linear representation of a rational series which converges to the target. DEES can then be used to identify in the limit with probability one rational stochastic tree languages. However, when DEES deals with finite samples, it often outputs a rational tree series which does not define a stochastic language. Moreover, the linear representation can not be directly used as a generative model. In this paper, we show that any representation of a rational stochastic tree language can be transformed in a reduced normalised representation that can be used to generate trees from the underlying distribution. We also study some properties of consistency for rational stochastic tree languages and discuss their implication for the inference. We finally consider the applicability of DEES to trees built over an unranked alphabet.

## 1 Introduction

In this paper, we consider the problem of learning probability distribution on trees from a i.i.d sample of trees, in a given class of models. In this context, the learning process has two main objectives: finding the correct structure of the representation and estimating precisely the parameters of the model. Because we are interested in machine learning, we restrict ourselves to classes of probabilistic languages that can be somehow finitely presented. Probabilistic tree automata (PTA) is a usual representation for rational stochastic tree language (RSTL). In a PTA, each rule is equipped with a weight in  $[0, 1]$  and a per state normalisation is imposed. Nonetheless, a first drawback is that is not know whether a PTA is consistent *i.e.* whether it represents a probability distribution on trees. One difficulty comes from the fact that a RSTL may be such that the average size of trees may be undefined. A second drawback of PTA is that it admits no

---

<sup>\*</sup> This work was fund by the ARA Marmota Project

canonical representation. Thus, most of learning algorithms approaches based on grammatical inference fail for the class of PTA.

Recent approaches have proposed to work in a larger class of representation: the class of rational stochastic tree languages that can be represented under a linear form of a tree series. The models of this class can be equivalently representing by weighted tree automata with parameters in  $\mathbb{R}$  (hence with weights that can be negative and without any per state normalisation condition). This class has two interesting properties: it has a high level of expressiveness since it strictly includes the class of RSTL and it admits a canonical form with a minimal number of parameters. Based on these properties, linear representations of RSTL are a good candidate from a grammatical inference standpoint. A recent algorithm, DEES, able to identify in the limit with probability one the class of rational stochastic tree languages RSTL was proposed in [1]. However, this algorithm has two main drawbacks when working with finite samples. It often outputs a rational tree series that does not define a stochastic language, and the representation of the series can not be directly used as a generative model. This comes from the fact that the canonical representation is more adapted for finding the structure of the model and estimating the parameters. We do not obtain a representation of a probability distribution that factorises into a product of probabilities associated with each state. When we need a generative model, we claim that we have to use another representation. Our first contribution is to show that any canonical representation of a rational stochastic tree language admits a normalised reduced representation of the same size which can be easily used in a generative process. Then, we examine some conditions of consistency for rational stochastic languages. Indeed, as for probabilistic context-free grammars, the consistency can not be ensured only with syntactical properties. We discuss then the influence of these conditions to the problem of inferring rational stochastic tree languages. We finish by studying the applicability of our approach to trees that are built from an unranked alphabet. Actually, a bijection can be made between the unranked representation and a ranked one, allowing us to apply our algorithm to the unranked case.

The paper is organized as follows. Definitions and notations are presented in Section 2. Section 3 deals with the normalised reduced representation of rational stochastic tree language. The consistency conditions are evoked in Section 4. The paper terminates by Section 5 on unranked trees.

## 2 Preliminaries

In this section, we recall definitions of trees, (rational) tree series, weighted automata and (rational) stochastic tree languages. We mainly follow notations and definitions from [2] about trees and tree automata. Formal power tree series have been introduced in [3] where the main results appear.

**Trees and contexts** Let  $\mathcal{F} = \mathcal{F}_0 \cup \mathcal{F}_1 \cup \dots \cup \mathcal{F}_p$  be a ranked alphabet where the elements in  $\mathcal{F}_m$  are the function symbols of rank  $m$ . Let  $\mathcal{X}$  be a countable set of

variables. The set  $T(\mathcal{F}, \mathcal{X})$  is the smallest set satisfying:  $\mathcal{F}_0 \cup \mathcal{X} \subseteq T(\mathcal{F}, \mathcal{X})$ , for  $f \in \mathcal{F}_m$ ,  $m \geq 1$ , and  $t_1, \dots, t_m \in T(\mathcal{F}, \mathcal{X})$ ,  $f(t_1, \dots, t_m) \in T(\mathcal{F}, \mathcal{X})$ .

We call *trees*, elements in  $T(\mathcal{F}, \emptyset) = T(\mathcal{F})$ . For any tree  $t$ , let us denote by  $|t|_f$  the number of occurrences of the symbol  $f \in \mathcal{F}$  in  $t$  and by  $|t|$ , the size  $\sum_{f \in \mathcal{F}} |t|_f$  of  $t$ . The *height* of a tree  $t$  is defined by:  $\text{height}(t) = 0$  if  $t \in \mathcal{F}_0$  and  $\text{height}(t) = 1 + \max\{\text{height}(t_i) \mid i = 1..m\}$  if  $t = f(t_1, \dots, t_m)$ . We suppose given a total order  $\leq$  on  $T(\mathcal{F})$  which satisfies  $\text{height}(t) < \text{height}(s) \Rightarrow t < s$ .

*Contexts* are elements  $c$  of  $C_n(\mathcal{F}) \subset T(\mathcal{F}, \mathcal{X})$  where  $n$  distinct variables  $\$1, \dots, \$n$  appears exactly once in  $c$ . Let  $c$  be a context in  $C_n(\mathcal{F})$  and  $t, t_1, \dots, t_n$  be trees. In the following, the notation  $c[\$1 \leftarrow t_1, \dots, \$n \leftarrow t_n]$  or simply  $c[t_1, \dots, t_n]$  represents the tree that results from substituting the  $\$i$ 's by the  $t_i$ 's in  $c$ .  $C_1(\mathcal{F})$  is simply denoted by  $C(\mathcal{F})$ . We say that a set  $A$  is *prefixial* whenever for any  $c \in C(\mathcal{F})$  and any  $t \in T(\mathcal{F})$ ,  $c[t] \in A \Rightarrow t \in A$ .

**Formal power tree series** A (*formal power*) *tree series* on  $T(\mathcal{F})$  is a mapping  $r : T(\mathcal{F}) \rightarrow \mathbb{R}$ . The vector space of all tree series on  $T(\mathcal{F})$  is denoted by  $\mathbb{K}\langle\langle\mathcal{F}\rangle\rangle$ .

Let  $V$  be a finite dimensional vector space over  $\mathbb{R}$ . We denote by  $\mathcal{L}(V^p; V)$  the set of  $p$ -linear mappings from  $V^p$  to  $V$ . Let  $\mathcal{L} = \cup_{p \geq 0} \mathcal{L}(V^p; V)$ . We denote by  $V^*$  the dual space of  $V$ , *i.e.* the vector space composed of all the linear forms defined on  $V$ .

A *linear representation* of  $T(\mathcal{F})$  is a couple  $(V, \mu)$ , where  $V$  is a finite dimensional vector space over  $\mathbb{R}$ , and where  $\mu : \mathcal{F} \rightarrow \mathcal{L}$  maps  $\mathcal{F}_p$  into  $\mathcal{L}(V^p; V)$  for each  $p \geq 0$ .

Thus for each  $f \in \mathcal{F}_p$ ,  $\mu(f) : V^p \rightarrow V$  is  $p$ -linear. Function  $\mu$  extends uniquely to a morphism  $\mu : T(\mathcal{F}) \rightarrow V$  by:  $\mu(f(t_1, \dots, t_p)) = \mu(f)(\mu(t_1), \dots, \mu(t_p))$ . Let  $V_{T(\mathcal{F})}$  be the vector subspace of  $V$  spanned by  $\mu(T(\mathcal{F}))$ :  $(V_{T(\mathcal{F})}, \mu)$  is a linear representation of  $T(\mathcal{F})$ .

Let  $r$  be a tree series over  $T(\mathcal{F})$ ,  $r$  is said to be *recognizable* if there exists a triple  $(V, \mu, \lambda)$ , where  $(V, \mu)$  is a linear representation of  $T(\mathcal{F})$ , and  $\lambda : V \rightarrow \mathbb{R}$  is a linear form, such that  $r(t) = \lambda(\mu(t))$  for all  $t$  in  $T(\mathcal{F})$ . The triple  $(V, \mu, \lambda)$  is called a *linear representation for  $r$* .

It has been shown in [3] that the notions of recognizable tree series and rational tree series coincide. From now on, we shall refer to them by using the term of *rational* tree series.

**Definition 1.** A stochastic tree language over  $T(\mathcal{F})$  is a tree series  $r \in \mathbb{R}\langle\langle\mathcal{F}\rangle\rangle$  such that for any  $t \in T(\mathcal{F})$ ,  $0 \leq r(t) \leq 1$  and  $\sum_{t \in T(\mathcal{F})} r(t) = 1$ . Let  $p$  be a stochastic language, let  $c \in C(\mathcal{F})$  be such that there exists a tree  $t$  such that  $p(c[t]) \neq 0$ . We define the stochastic language  $c^{-1}p$  by  $c^{-1}p(t) = \frac{p(c[t])}{\sum_{t' \in T(\mathcal{F})} p(c[t'])}$ .

A *rational stochastic tree language* (RSTL) is a stochastic tree language which admits a linear representation. The set of rational stochastic tree languages is denoted by  $\mathcal{S}^{rat}(\mathcal{F})$ .

**Weighted Tree Automata** A *weighted tree automaton*<sup>1</sup> (WTA) over  $\mathcal{F}$  is a tuple  $\mathcal{A} = (Q, \mathcal{F}, \tau, \delta)$  where  $Q$  is a set of states,  $\tau$  is a mapping from  $Q$  to  $\mathbb{R}$  and  $\delta$  is a mapping from  $\cup_{m \geq 0} \mathcal{F}_m \times Q^m \times Q$  to  $\mathbb{R}$ . The mapping  $\delta$  can be interpreted as a set  $\Delta$  of rules which can be written in a bottom-up or a top-down way:

$f(q_1, \dots, q_m) \xrightarrow{w} q \in \Delta$  (or  $q \xrightarrow{w} f(q_1, \dots, q_m) \in \Delta$ ) iff  $\delta(f, q_1, \dots, q_m, q) = w \wedge w \neq 0$ .

The weight  $w$  of a rule  $r$  is denoted by  $w(r)$ . For any  $q \in Q$ , we denote by  $\Delta_q$  the subset of  $\delta$  composed of the (top-down) rules whose lhs is  $q$ . A series  $r_q$  can be associated with any state  $q$  by:  $r_q(f(t_1, \dots, t_n)) = \sum_{r \in \Delta_q} w(r) \prod_{i=1}^n r_{q_i}(t_i)$ .

Then the WTA  $\mathcal{A}$  computes the series  $r$  defined by:  $r(t) = \sum_{q \in Q} \tau(q) r_q(t)$ .

WTA and linear representations are two equivalent ways to represent rational series. For example, let  $(V, \mu, \lambda)$  be a linear representation of the tree series  $r \in \mathbb{R}\langle\langle\mathcal{F}\rangle\rangle$  and let  $B = (e_1, \dots, e_n)$  be a basis of  $V$ . A WTA  $\mathcal{A} = (Q, \mathcal{F}, \lambda, \delta)$  can be associated with  $(V, \mu, \lambda, B)$  where  $Q = \{e_1, \dots, e_n\}$ , and  $\delta(f, e_{i_1}, \dots, e_{i_m}, e_j) = w_j$  for any  $f \in \mathcal{F}_m$  where  $\mu(f)(e_{i_1}, \dots, e_{i_m}) = \sum_j w_j e_j$ . Conversely, an equivalent linear representation can be associated with any weighted tree automaton (see Example 1 below).

Note here that a *probabilistic tree automaton* (PTA) is a specific case of WTA  $\mathcal{A} = (Q, \mathcal{F}, \tau, \delta)$  satisfying the following conditions: (i)  $\delta$  and  $\tau$  take their values in  $[0, 1]$ , (ii)  $\sum_{q \in Q} \tau(q) = 1$ , (iii) for any  $q \in Q$ ,  $\sum_{r \in \Delta_q} w(r) = 1$ .

It can be shown that any PTA computes a rational tree series  $r$  that satisfies  $r(t) \geq 0$  for any tree  $t$  and  $\sum_t r(t) \leq 1$ . It can be shown that there exist rational stochastic tree languages that cannot be computed by any probabilistic automaton (see [4] for an example in the case of word stochastic languages).

*Example 1.* A WTA representing a rational stochastic tree language. Let  $\mathcal{A} = (Q, \mathcal{F}, \tau, \delta)$  be the WTA defined by  $Q = \{q_1, q_2\}$ ,  $\mathcal{F} = \{a, f(\cdot, \cdot)\}$ ,  $\tau(q_1) = 2, \tau(q_2) = -1$  and  $\Delta = \{q_1 \xrightarrow{2/3} a, q_1 \xrightarrow{1/3} f(q_1, q_1), q_2 \xrightarrow{3/4} a, q_2 \xrightarrow{1/4} f(q_2, q_2)\}$ .

$p_{q_1}$  and  $p_{q_2}$  are RSTL, that the series  $p = 2p_{q_1} - p_{q_2}$  computed by  $\mathcal{A}$  takes only positive values. And since  $\sum_t p(t) = 1$ ,  $p$  is an RSTL. It admits the following linear representation:  $(\mathbb{R}^2, \mu, \lambda)$  where  $e_1 = (1, 0), e_2 = (0, 1)$ ,  $\lambda(e_1) = 2, \lambda(e_2) = -1$ ,  $\mu(a) = 2e_1/3 + 3e_2/4$ ,  $\mu(f)(e_1, e_1) = e_1/3, \mu(f)(e_2, e_2) = e_2/4$  and  $\mu(f)(e_i, e_j) = 0$  if  $i \neq j$ .

## 2.1 Canonical Linear Representation of Rational Tree Series

We now define the canonical representation of a rational tree series.

<sup>1</sup> These automata are also referred to as *multiplicity tree automata* in the literature.

Let  $c \in C(\mathcal{F})$ . We define the linear mapping  $\dot{c} : \mathbb{R}\langle\langle\mathcal{F}\rangle\rangle \rightarrow \mathbb{R}\langle\langle\mathcal{F}\rangle\rangle$  by

$$\dot{c}(r)(t) = r(c[t]) .$$

Let  $r \in \mathbb{R}\langle\langle\mathcal{F}\rangle\rangle$ . Let us denote by  $W_r$  the vector subspace of  $\mathbb{R}\langle\langle\mathcal{F}\rangle\rangle$  spanned by  $\{\dot{c}r \mid c \in C(\mathcal{F})\}$ . It can be shown that  $r$  is rational if and only if the dimension of  $W_r$  is finite [1]. Let  $W_r^*$  be the dual space of  $W_r$ , i.e. the set of all linear forms on  $W_r$ . For any  $t \in T(\mathcal{F})$ , let  $\bar{t} \in W_r^*$  be defined by:  $\forall s \in W_r, \bar{t}(s) = s(t)$ . It can be shown that there exist trees  $t_1, \dots, t_m$  such that  $(\bar{t}_1, \dots, \bar{t}_m)$  forms a basis of  $W_r^*$ . Let us define the linear representation  $(W_r^*, \mu, \lambda)$  as follows:

- for any  $f \in \mathcal{F}_m$ , define  $\mu(f)(\bar{t}_1, \dots, \bar{t}_{i_m}) = \overline{f(t_1, \dots, t_{i_m})}$ .
- $\lambda \in (W_r^*)^* = W_r$  by  $\lambda(\bar{t}) = r(t)$ .

**Theorem 1.** [1]  *$(W_r^*, \nu, \tau)$  is a linear representation of  $r$  which is called the canonical linear representation of  $r$ . It can be embedded in any linear representation of  $r$ ; in particular, its dimension is minimal.*

*Example 2.* Consider the rational stochastic tree language  $p$  defined in example 1. It can easily be shown that  $p_1(t) = \frac{2^{|t|_f+1}}{3^{2|t|_f+1}}$ ,  $p_2(t) = \frac{3^{|t|_f+1}}{4^{2|t|_f+1}}$  and  $p(t) = \frac{2^{5|t|_f+4} - 3^{3|t|_f+2}}{3^{2|t|_f+1} \times 4^{2|t|_f+1}}$ . Thus, for any context  $c$  and any tree  $t$ :  $\bar{t}(\dot{c}p) = p(c[t]) = \frac{2^{5|t|_f+5|c|_f+4} - 3^{3|t|_f+3|c|_f+2}}{3^{2|t|_f+2|c|_f+1} \times 4^{2|t|_f+2|c|_f+1}}$ .

Since  $p$  has a 2-dimensional linear representation, the dimension of  $W_r^*$  is  $\leq 2$ . Let  $c_0 = \$$  and  $c_1 = f(a, \$)$ , we have:

$$\bar{a}(\dot{c}_0p) = \frac{7}{3 \times 2^2}, \bar{a}(\dot{c}_1p) = \overline{f(a, a)}(c_0) = \frac{269}{3^3 \times 2^6}, \text{ and } \overline{f(a, a)}(\dot{c}_1p) = \frac{9823}{3^5 \times 2^{10}}.$$

Since  $\bar{a}(\dot{c}_0p) \times \overline{f(a, a)}(\dot{c}_1p) \neq \bar{a}(\dot{c}_1p) \times \overline{f(a, a)}(\dot{c}_0p)$ ,  $\bar{a}$  and  $\overline{f(a, a)}$  are linearly independent. Then,  $(\bar{a}, \overline{f(a, a)})$  is a basis of  $W_r^*$ . We define  $\lambda$  and  $\mu$  by:

$$\begin{aligned} \lambda(\bar{a}) &= p(a) = \frac{7}{3 \times 2^2} \text{ and } \lambda(\overline{f(a, a)}) = p(f(a, a)) = \frac{269}{3^3 \times 2^6} \text{ and} \\ \mu(a) &= \bar{a}, \mu(f)(\bar{a}, \bar{a}) = \overline{f(a, a)} \\ \mu(f)(\bar{a}, \overline{f(a, a)}) &= \mu(f)(\overline{f(a, a)}, \bar{a}) = \frac{-54}{2^4 \times 3^4} \bar{a} + \frac{59}{2^4 \times 3^2} \overline{f(a, a)} \\ \mu(f)(\overline{f(a, a)}, \overline{f(a, a)}) &= \frac{-3186}{2^8 \times 3^6} \bar{a} + \frac{2617}{2^8 \times 3^4} \overline{f(a, a)}. \end{aligned}$$

We can justify here why the canonical form of a stochastic language  $p$  may not be relevant for generating trees according to  $p$ . Indeed, one can remark here that  $\mu(f(a, f(a, a))) = \mu(f)(\bar{a}, \overline{f(a, a)}) = \frac{-54}{2^4 \times 3^4} \bar{a} + \frac{59}{2^4 \times 3^2} \overline{f(a, a)}$ . Thus, if we consider the weights of trees according to  $\bar{a}$ ,  $f(a, f(a, a))$  has a negative weight and then  $\bar{a}$  does not define by itself a stochastic language. As a consequence, the canonical form does not have a relevant structure if one aims at using it according to a generative model.

## 2.2 DEES

DEES is an inference algorithm which identifies any rational stochastic language in the limit with probability one (see [1]). Let us show how DEES works on the previous example. Let  $S$  be a sample of trees independently drawn according to  $p$  and let  $p_S$  be the empirical distribution defined on  $T(\mathcal{F})$ :  $p_S(t)$  is the frequency of  $t$  in  $S$ . For any confidence parameter  $\delta$ , there exists  $\epsilon > 0$  such that with

probability at least  $1 - \delta$ ,  $|p(t) - p_S(t)| \leq \epsilon$  for any tree  $t$ . Statistical tests, based on this property, are used to accept or reject hypotheses of the form:  $\bar{t}$  is a linear combination of  $\bar{t}_1, \dots, \bar{t}_n$ . Parameters  $\epsilon$  and  $\delta$  can be chosen, depending on the size of the sample  $S$ , such that with probability one, the correct hypothesis will always be chosen from some sample size.

In order to find the basis of the canonical representation, the algorithm first tests whether  $\bar{a}$  and  $\overline{f(a, a)}$  are linearly independent. With probability one, this will be detected from some step:  $\bar{a}$  and  $\overline{f(a, a)}$  are elements of the canonical basis. Then, the algorithm tests whether  $\overline{f(a, f(a, a))}$  is a linear combination of  $\bar{a}$  and  $\overline{f(a, a)}$ . As this is true, this will be detected with probability one from some step. Therefore,  $\overline{f(a, f(a, a))}$  will not be added to the basis. And so on. The algorithm terminates when it has checked that no more elements can be added to the basis.

It can be proved that with probability one, there exists an integer  $N$  such that for any sample  $S$  containing more than  $N$  examples, a basis of  $W_p^*$  will be identified from  $S$ . DEES will compute a linear representation  $(W_p^*, \mu_S, \lambda_S)$ , such that  $\mu_S$  and  $\lambda_S$  converge respectively to  $\mu$  and  $\lambda$  when  $S$  tends to infinity.

Hence, DEES identifies in the limit the canonical linear representation of any rational tree stochastic language with probability one. However:

- Given the canonical linear representation of a stochastic language  $p$  does not help to generate trees according to  $p$ .
- Moreover, the series output by DEES from some sample  $S$  can be not a stochastic language. The possibility to transform it in a stochastic language is then an important issue.
- The series output by DEES converges to the target  $p$  as the size of  $S$  increases, but what is the rate of convergence?

We propose to adress of all of these questions in the present paper.

### 3 Normalised linear representation for rational stochastic tree languages

Given a rational tree series  $r$ , a linear representation  $(V, \mu, \lambda)$  of  $r$  and a basis  $B = \{e_1, \dots, e_n\}$  of  $V$ , we can consider the  $n$  rational tree series  $r_i$  for  $i = 1, \dots, n$  defined by the linear representation  $(V, \mu, \lambda_i)$ , where  $\lambda_i(e_j) = \delta_{ij}$  where  $\delta_{ij} = 1$  if  $i = j$  and 0 otherwise. Remark that the series  $r_i$  directly correspond to the series  $r_q$  defined from the WTA associated with  $(V, \mu, \lambda, B)$

Now, when  $r$  is a stochastic language, it can be asked whether there exists a linear representation  $(V, \mu, \lambda)$  of  $r$  and a basis  $B = \{e_1, \dots, e_n\}$  of  $V$  such that each  $r_i$  is also a stochastic language.

**Proposition 1.** *Let  $p$  be an RSTL over  $T(\mathcal{F})$  and let  $(W_p^*, \mu, \lambda)$  be the canonical linear representation of  $p$ . Then,  $W_p^*$  admits a basis  $B = \{e_1, \dots, e_n\}$  such that each series  $r_i$  is stochastic.*

*Proof.* See Appendix 7.1.

**Definition 2.** Let  $\mathcal{A} = (Q, \mathcal{F}, \tau, \delta)$  be a WTA. We say that  $\mathcal{A}$  is in normalised form if and only if (i)  $\sum_{q \in Q} \tau(q) = 1$ , (ii) for any  $q \in Q$ ,  $\sum_{r \in \Delta_q} w(r) = 1$  and (iii) for any  $q \in Q$  and any  $f \in \mathcal{F}$ ,  $\sum_{r \in \Delta_q} w(r) \in [0, 1]$ . Moreover, we say that  $\mathcal{A}$  is in reduced normalised form if the series  $r_q$  are linearly independent.

Any rational stochastic tree language can be represented by a normalised reduced WTA  $\mathcal{A} = (Q, \mathcal{F}, \tau, \delta)$  such that each  $r_q$  defines a stochastic language. Note also that any PTA is in normalised form (but not necessarily in reduced normalised form).

*Example 3.* Let us consider the rational stochastic tree language  $p$  presented in the previous examples and show how to compute a normalized WTA that computes it. Let  $c_0 = \$$ ,  $c_1 = f(\$ , a)$  and let  $s_0 = \alpha_0 \bar{a} + \beta_0 \overline{f(a, a)}$  and  $s_1 = \alpha_1 \bar{a} + \beta_1 \overline{f(a, a)}$  where  $s_i(c_j^{-1}p) = \delta_{ij}$ . Remarking that  $\sum_t c_0 p(t) = 1$  and  $\sum_t c_1 p(t) = \sum_t p(f(t, a)) = 2 \sum_t p_1(f(t, a)) - \sum_t p_2(f(t, a)) = 37/144$  one can check that  $\alpha_0 = \frac{-9823}{300}$ ,  $\alpha_1 = \frac{3228}{25}$ ,  $\beta_0 = \frac{9953}{300}$  and  $\beta_1 = \frac{-3108}{25}$ .

Now, by expressing,  $\bar{a}$  and  $\overline{f(a, a)}$  in the basis  $s_0, s_1$ , we get the following set of rules:

$$\begin{array}{ll} s_0 \xrightarrow{7/12} a, & s_1 \xrightarrow{269/444} a, \\ s_0 \xrightarrow{-269/50} f(s_0, s_0), & s_1 \xrightarrow{-3024/925} f(s_0, s_0), \\ s_0 \xrightarrow{259/50} f(s_0, s_1), & s_1 \xrightarrow{2664/925} f(s_0, s_1), \\ s_0 \xrightarrow{259/50} f(s_1, s_0), & s_1 \xrightarrow{2664/925} f(s_1, s_0), \\ s_0 \xrightarrow{-1369/300} f(s_1, s_1), & s_1 \xrightarrow{-23273/11100} f(s_1, s_1). \end{array}$$

It is easy to verify that this representation is in normalised form.

A generation process of trees can be done using normalized WTA as given in Algorithm 1. Each tree is built top-down. The process is different from the classical approach with PTA since instead of drawing a transition rule to apply at each step, we rather draw a symbol according to the distributions of the symbols defined by the rules.

**Comments:**

- (1)  $\Delta_{gen}$  contains  $n$  rules of the form  $q_t \xrightarrow{w_i} c[q_1^i, \dots, q_m^i]$  where  $c$  is a linear context over  $m$  variables and where  $1 \leq i \leq n$ ;
- (2) it can be proved that  $\sum_{f \in \mathcal{F}} \alpha_{f,j}^c = 1$  for any  $1 \leq j \leq m$
- (3) the numbers  $\alpha_{f,j}^c$  define a probability distribution on  $\mathcal{F}_j$
- (4) There exists a unique tree  $t$  such that all the rules of  $\Delta_{gen}$  are of the form  $q_t \xrightarrow{w_i} t$ ;  $t$  is the output of the algorithm

## 4 Learning rational stochastic tree languages

We consider the question of learning a rational stochastic tree language (RSTL)  $p$  from an i.i.d. sample of trees drawn according to  $p$ . An RSTL can be such that the average size of trees generated from  $p$  is unbounded, i.e.  $\sum_t p(t)|t| = \infty$ .



```

Data      : An WTA  $\mathcal{A} = (Q, \mathcal{F}, \tau, \delta)$  in normalised form
Result   : A tree  $t \in T(\mathcal{F})$ 
begin
  Let  $q_t$  be a new state ;
  Let  $\Delta_{gen} = \{q_t \xrightarrow{\tau(q)} q \mid q \in Q\}$  (1);
  while the rhs of some rule of  $\Delta_{gen}$  contains states do
    Let  $m$  be the number of rules in  $\Delta_{gen}$  and  $n$  be the number of states in
    each the rules;
    for  $1 \leq j \leq m$  do
      for any  $f \in \mathcal{F}$ , let  $\alpha_{f,j}^c = \sum_{i=1}^n w_i \sum_{r \in \Delta_{q_j^i, f}} w(r)$  (2);
      draw randomly  $f_j \in \mathcal{F}$  according to  $\alpha_{f_j, j}^c$  (3);
      let  $n_j$  be the rank of  $f_j$ ;
      let  $c^j = c(f_1(\$_1^1, \dots, \$_1^{n_1}), \dots, f_m(\$_m^1, \dots, \$_m^{n_m}))$  a linear context;
      in  $\Delta_{gen}$ , replace each rule  $q_t \xrightarrow{w_i} c[q_1^i, \dots, q_m^i]$  by the rules
       $q_t \xrightarrow{w_i w_{r_1} \dots w_{r_m}} c[f_1(q_{r_1}^1, \dots, q_{r_1}^{n_1}), \dots, f_m(q_{r_m}^1, \dots, q_{r_m}^{n_m})]$  ;
      where  $r_j : q_j \xrightarrow{w_{r_j}} f_j(q_{r_j}^1, \dots, q_{r_j}^{n_j}) \in \Delta_{q_j^i, f_j}$ ,  $1 \leq j \leq m$ ,  $1 \leq i \leq n$ ;
    Outputs the tree of  $\Delta_{gen}$  (4);
  end

```

**Algorithm 1:** Drawing a tree according to a RSTL

For example, this is the case for the RSTL defined by the PTA whose rules are:  $\{q \xrightarrow{1/2} a, q \xrightarrow{1/2} f(q, q)\}$ . To our knowledge, it is still unknown whether a PTA defines a RSTL and it is much better to deal with the stronger notion of *strongly consistent* stochastic language: a RSTL  $p$  is strongly consistent if  $\sum_t |t|p(t) < \infty$ . Next section investigates some properties of strongly consistent RSTL.

#### 4.1 Strongly consistent rational stochastic languages

Let  $\mathcal{A} = (Q = \{q_1, \dots, q_n\}, \mathcal{F}, \tau, \delta)$  be an WTA and let  $A = (a_{ij})_{1 \leq i, j \leq n}$  be the matrix defined by  $a_{ij} = \sum_{r \in \Delta_{q_i}} n_r(j)w(r)$  where  $n_r(j)$  is the number of occurrences of  $q_j$  in the rhs of  $r$ .

We denote by  $p_i$  the rational series defined from state  $q_i$  and we let  $\gamma_i = \sum_{t \in T(\mathcal{F})} p_i(t)|t|$  ( $\gamma_i$  may be undefined if the sum diverges),  $\gamma = (\gamma_1, \dots, \gamma_n)$  and  $B = (1, \dots, 1)^t$ .

**Proposition 2.** *Let us suppose that for any index  $i$ ,  $\sum_{t \in T(\mathcal{F})} p_i(t) = 1$  and  $\sum_{r \in \Delta_{q_i}} w(r) =$*

1. *Then  $\gamma = \sum_{n \geq 0} A^n B$ .*

*Proof.* See Appendix 7.2.

The sum  $\sum_{n \geq 0} A^n B$  converges iff  $A^n B$  converges to 0, which can be decided within polynomial time.

*Example 4.* Consider the PTA defined by the rules  $\{q \xrightarrow{1-\alpha} a, q \xrightarrow{\alpha} f(q, q)\}$  and  $\tau(q) = 1$ :  $A = (2\alpha)$  and  $A^n B$  converges iff  $\alpha < 1/2$ . The average size of trees generated from these PTA is  $1/(1 - 2\alpha)$ . When  $\alpha = 1/3$  (resp.  $1/4$ ), the PTA computes the stochastic language  $p_{q_1}$  (resp.  $p_{q_2}$ ) as previously defined in example 1. Then, the average size of trees  $\gamma_1$  (resp.  $\gamma_2$ ) generated from  $p_{q_1}$  (resp.  $p_{q_2}$ ) is 3 (resp. 2). One can deduce the average size of the stochastic language  $p = 2p_{q_1} - p_{q_2}$ ,  $\gamma = 2 \times \gamma_1 - \gamma_2 = 4$ .

Consider now the normalized form of  $p$  as presented in example 3.

The matrix  $A$  is  $\begin{pmatrix} -2/5 & 37/30 \\ -144/185 & 47/30 \end{pmatrix}$ .

It is easy to verify that  $(I - A)$  is invertible and  $(I - A)^{-1} = \begin{pmatrix} -17/5 & 37/5 \\ -864/185 & 42/5 \end{pmatrix}$ .

Thus  $(I - A)^{-1} B = (4 \ 690/185)$ . Following Prop. 2, the average size  $\gamma_0$  of trees generated by  $c_0^{-1} p$  is 4 and the average size of trees generated by  $c_0^{-1} p$  is  $690/185$ . Since  $p = c_0^{-1} p$  the average tree size of  $p$  is 4.

We show below that when  $\mathcal{A}$  is a reduced normalised representation of a strongly consistent rational stochastic language, the spectral radius  $\rho(A)$  of  $A$  is  $< 1$ . We need the following lemma (See [5] for a similar result in the case of words.)

**Lemma 1.** *Let  $p_1, \dots, p_n$  be  $n$  independent stochastic languages. Then  $\Lambda = \{(\alpha_1, \dots, \alpha_n) \in \mathbb{R}^n : \sum_{i=1}^n \alpha_i p_i \text{ is a stochastic language}\}$  is a compact convex subset of  $\mathbb{R}^n$ .*

**Proposition 3.** *Let  $A = (Q = \{q_1, \dots, q_n\}, \mathcal{F}, \tau, \delta)$ , a reduced normalised representation of a strongly consistent RSTL  $p$  such that each  $p_{q_i}$  is a stochastic language and let  $A = (a_{ij})_{1 \leq i, j \leq n}$  be the matrix defined as previously. Then the spectral radius of  $A$  satisfies  $\rho(A) < 1$ .*

*Proof.* See Appendix 7.3.

*Example 5.* The matrix  $A$  of Example 4 admits two eigen values:  $\frac{1}{2}$  and  $\frac{2}{3}$ , then  $\rho(A) = \frac{2}{3} < 1$ .

## 4.2 Effective normalisation

Let  $p$  be a strongly consistent RSTL and let  $\mathcal{B} = (\bar{t}_1, \dots, \bar{t}_n)$  be the smallest (for the order  $\leq$  on  $T(\mathcal{F})$ ) basis of the canonical linear representation  $(W_p^*, \mu, \lambda)$  of  $p$ . The main result in [1] proves that with probability one, there exists a sample size from which DEES will output a linear representation  $(W_p^*, \mu_S, \lambda_S)$  whose basis is  $\mathcal{B}$  and such that  $\mu_S$  and  $\lambda_S$  are arbitrarily close to  $\mu$  and  $\lambda$ .

According to Prop. 1, a normalised WTA  $\mathcal{A}_S$  can be computed from  $(W_p^*, \mu_S, \lambda_S)$ . But this proposition only state an existence property and we now we wish to

compute  $\mathcal{A}_S$ . Choosing a basis written as  $(\hat{c}_i)$  is easily done by recursively enumerating every context, the main technical key point relies in the ability to compute the sums  $\sum_t r(c_i[t])$  for a given rational series.

Let  $s$  be the vector defined by  $s = \sum_{t \in T(\mathcal{F})} \mu(t) = \sum_t \bar{t}$ . Then  $s_i = \sum_t r_{q_i}(t) = \sum_t r(c_i[t])$ . Moreover,  $s$  is a solution of the relation:  $s = \sum_m \sum_{f \in \mathcal{F}_m} \mu_f(s, \dots, s)$ . This is a polynomial system of degree  $m$ , which happens not to be analytically soluble. As a consequence, we will try and approximate these sums, using either a direct propagative method or Newton's method.

Let  $M$  and  $M_p$  be the endomorphisms defined by

$$M(v) = \sum_m \sum_{l=1}^m \sum_{f \in \mathcal{F}_m} \mu_f(\underbrace{s, \dots, s}_{l-1}, v, \underbrace{s, \dots, s}_{m-l})$$

$$M_p(v) = \sum_m \sum_{l=1}^m \sum_{f \in \mathcal{F}_m} \mu_f(\underbrace{s_p, \dots, s_p}_{l-1}, v, \underbrace{s, \dots, s}_{m-l}).$$

The propagative method, proposed by Stolcke[6] in the case of probabilistic context-free languages. The idea is to recursively the sequence  $s_p = \sum_{t \in T^{<p}(\mathcal{F})} t$  using the recursion:  $s_0 = 0 \quad s_{p+1} = F(s_p)$ . Obviously,  $(s_p)$  converges towards  $s$ . Let's study the rate of convergence.

By applying the multi-linearity of  $\mu_f$ ,  $s - s_{p+1}$  can be decomposed in  $s - s_{p+1} = F(s) - F(s_p) = M_p(s - s_p)$ . Taking into account that  $(\bar{t})_i = r(c_i[t]) \geq 0$  for every tree  $t$  it's easily shown that for every  $p$   $\|s - s_{p+1}\| = \|\prod_{q=0}^p M_q(s - s_0)\| \leq \|M^p\| \|s - s_0\|$ . By Gerland's formula, we have  $\|M^k\| \sim \rho(M)^k$  and thus  $\|s - s_p\| = O(\rho(M)^k \|s - s_0\|)$ .

If  $A$  is the matrix of  $M$  in the basis  $(c_i^{-1})$ , then it can be proved that it's the same matrix as defined in Section 4.1. Thanks to proposition 3 and because we made the assumption the series is strongly consistent, we know that  $\rho(M) = \rho(A) < 1$ .

When tested on the previous example, the propagative method achieved precision of  $10^6$  in approximately 30 iterations. In near future, we intend to study the use of Newton's method, which could at least theoretically achieve faster convergence.

### 4.3 Learning a strongly consistent rational stochastic language: the road map

The normalised WTA  $\mathcal{A}_S$  obtained at the end of the previous section computes an RSTL  $p_S$  such that the spectral radius  $\rho_S$  of the matrix  $A_S$  associated with  $\mathcal{A}_S$  satisfies  $\rho_S < 1$  which is a strong property. We have still some results to prove in order to complete the learning process. We present them below as conjectures.

**Conjecture 1:** It is possible to modify Algorithm 1 in order to be used to generate trees from a normalised WTA. The modified algorithm stops (and output a tree) with probability one, as soon as  $S$  is sufficiently large. Hence, it defines a stochastic language  $\hat{p}$ .

**Conjecture 2:** with probability one,  $\sum_t |p(t) - \hat{p}(t)| \cdot |t|$  converges to 0 with the size of  $S$ .

These two conjectures generalize results proved in the word case. Note that the convergence type described in Conjecture 2 is stronger than  $l_1$ -convergence.

## 5 Unranked trees

In this section we consider trees where the rank constraint has been dropped: every symbol in unranked trees may have from 0 to an unbounded but finite number of (ordered) children. Unranked trees are the common abstract representation of semi-structured data like XML.

Let  $\Sigma$  be a finite set of symbols. The set  $T(\Sigma)$  of unranked trees is the smallest set such that  $\Sigma \subseteq T(\Sigma)$ , and  $f(t_1, \dots, t_m) \in T(\Sigma)$  provided  $f \in \Sigma$  and  $t_1, \dots, t_m \in T(\Sigma)$ . An algebraic definition of unranked trees can be given by means of the extension operator  $@$  ([2]). Basically,  $@$  adds a new child at the end of the list of children of an unranked tree:  $f @ t = f(t), f(t_1, \dots, t_{n-1}) @ t_n = f(t_1, \dots, t_n)$ .

The extension operator provides a unique recursive definition of any unranked tree. It can be syntactically represented by a binary (ranked) tree over  $\mathcal{F} = \mathcal{F}_0 \cup \mathcal{F}_2$  where  $\mathcal{F}_0 = \Sigma$  and  $\mathcal{F}_2 = \{@\}$ . Let us now define the mapping  $\text{ext}$  from  $T(\Sigma)$  to  $T(\mathcal{F})$  by  $\text{ext}(f) = f$  and  $\text{ext}(f(t_1, \dots, t_n)) = @( \text{ext}(f(t_1, \dots, t_{n-1})), \text{ext}(t_n) )$ . One can show that the mapping  $\text{ext}$  is a bijection. Hedge automata [7] directly act on unranked trees in  $T(\Sigma)$ . Briefly, hedge automata rules are of the form  $f(L) \rightarrow q$  where  $L$  is a word language on the alphabet of states. It has been shown that hedge automata and ordinary tree automata on  $T(\mathcal{F})$  define the same class of recognizable languages [8]. Extension from hedge automata to weighted hedge automata (there referred to as unranked WTA) is proposed in [9]. In unranked WTA rules are of the form  $f(L) \xrightarrow{w} q$  where  $L$  is a weighted word language on the alphabet of states.


Thanks to the  $\text{ext}$  mapping, each result presented in this paper can be interpreted in the case of unranked trees. Tree series on  $T(\Sigma)$  are simply defined via tree series on  $T(\mathcal{F})$ . This mapping also suggests a notion of rational unranked tree series and stochastic languages.

**Proposition 4.** *The class of rational unranked tree series represented via the mapping  $\text{ext}$  coincide with the class of unranked tree series defined by unranked WTA.*

More precisely, let  $r$  be an unranked WTA which represents a rational unranked tree series  $r^u$ . One can build in linear time a (ranked) WTA which represents a rational tree series  $r^r$  such that  $\forall t \in T(\Sigma) r^u(t) = r^r(\text{ext}(t))$ . The converse is also true but to compute the corresponding unranked WTA, one needs to normalise rules following the method given in Section 4.2.

The following example illustrates how one can build a weighted automaton for unranked trees. Let us consider trees that represent nested lists built with the commonly used symbols `ul` and `li`. Let us consider first a stochastic hedge

automaton with two states  $q_{ul}$  and  $q_{li}$ . Final weights are given by  $F(q_{ul}) = 1$  and  $F(q_{li}) = 0$ . Rules are  $li(L_1) \xrightarrow{1} q_{li}$  and  $ul(L_2) \xrightarrow{1} q_{ul}$  where



The weight of a tree  $ul(li, li(ul(li)))$  is  $2^3/3^6$ .

The corresponding automaton on the expression with the @ operator has 4 states  $\{q_1^{li}, q_2^{li}, q_3^{ul}, q_4^{ul}\}$ ,  $\tau(q_4^{ul}) = 1$  and the set of rules:

$$\left\{ \begin{array}{l} li \xrightarrow{1} q_1^{li} \quad , \quad ul \xrightarrow{1} q_3^{ul} \quad , \quad @(q_1^{li}, q_4^{ul}) \xrightarrow{w_1} q_2^{li} \quad , \\ @(q_3^{ul}, q_1^{li}) \xrightarrow{w_2} q_4^{ul} \quad , \quad @(q_3^{ul}, q_2^{li}) \xrightarrow{w_3} q_4^{ul} \quad , \\ @(q_4^{ul}, q_1^{li}) \xrightarrow{w_4} q_4^{ul} \quad , \quad @(q_4^{ul}, q_2^{li}) \xrightarrow{w_5} q_4^{ul} \quad \end{array} \right\}$$

The weight  $w_2$  is the weight of adjoining a subtree in state  $q_1^{li}$  to a tree in state  $q_3^{ul}$ . The results gives a tree in state  $q_4^{ul}$ . It corresponds to the following computation in the hedge automaton: exit from  $L_1$  with state  $q_1^{li}$ , then apply the rule  $li(L_1) \xrightarrow{1} q_{li}$  and finally follow the transition from  $q_3^{ul}$  to  $q_4^{ul}$  in  $L_2$ . Hence  $w_2 = 2/3 \times 1 \times 1/3$ . Similarly  $w_3 = 1/3 \times 1 \times 1/3$ ,  $w_4 = 2/3 \times 1 \times 2/3$ ,  $w_5 = 1/3 \times 1 \times 2/3$  and  $w_1 = 1 \times 1 \times 1$ . The binary tree associated with  $ul(li, li(ul(li)))$  is  $@(@@ul, li), @(li, @(ul, li))$ . One can verify that its weight is also  $2^3/3^6$ .

Hence, to learn rational unranked tree series, one can simply proceed in the following way: apply ext to input trees and then apply DEES. Eventually, a representation of an unranked WTA where weights are estimated can possibly be returned.

## 6 Conclusion

In this paper, we studied the problem of learning a rational stochastic tree language  $p$  from an *i.i.d.* sample of trees drawn from  $p$ . An inference algorithm, DEES, was previously proposed for this problem. Using this algorithm leads to two main drawbacks: It often outputs linear representations that do not define stochastic languages and these representation can not be directly used to generate trees from the underlying distribution. We adressed this problem by showing that any rational stochastic tree language admits a normalised reduced representation that can be used as a generative model. We have studied the notion of strongly consistent rational stochastic languages which corresponds to the fact that the average size of trees generated from a RSTL  $p$  is bounded. We showed the relationship between this notion and the normalised reduced representation of a RSTL. We finally justified that the methods presented in this paper can be directly applied to unranked trees.

The next step of this work is to prove the conjectures that was presented for learning strongly consistent rational stochastic languages: First a probability distribution  $\hat{p}$  can be extracted in order to generate trees from a normalised WTA.

Second, that  $\sum_t |p(t) - \hat{p}(t)| \cdot |t|$  converges to zero with the size of the learning sample. Note here that this condition is stronger than the l1-convergence.

## References

1. Denis, F., Habrard, A.: Learning rational stochastic tree languages. In: Algorithmic learning theory. Volume 4754 of LNAI., 18th International Conference, ALT 2007, Springer-Verlag (2007) 242–256
2. Comon, H., Dauchet, M., Gilleron, R., Jacquemard, F., Lugiez, D., Löding, C., Tison, S., Tommasi, M.: Tree automata techniques and applications. Available on: <http://tata.gforge.inria.fr/> (2007) release October, 12th 2007.
3. Berstel, J., Reutenauer, C.: Recognizable formal power series on trees. Theoretical Computer Science **18** (1982) 115–148
4. Denis, F., Esposito, Y.: Rational stochastic languages. Technical report, LIF - Université de Provence, <http://hal.ccsd.cnrs.fr/ccsd-00019728> (2006)
5. Denis, F., Esposito, Y., Habrard, A.: Learning rational stochastic languages. In Lugosi, G., Simon, H.U., eds.: Learning theory. Lecture Notes in Computer Science, Springer-Verlag (2006) 274–288
6. Stolcke, A.: An efficient probabilistic context-free parsing algorithm that computes prefix probabilities. Computational Linguistics **21**(2) (1995) 165–201
7. Brüggemann-Klein, A., Murata, M., Wood, D.: Regular tree and regular hedge languages over unranked alphabets. Technical report, Honk-Kong University Theoretical Computer Science Center (2001) Version 1.
8. Carme, J., Niehren, J., Tommasi, M.: Querying unranked trees with stepwise tree automata. Rewriting Techniques and Applications **3091** (2004) 105–118
9. Droste, M., Vogler, H.: Weighted logics for xml. manuscript (2007)

## 7 Appendix

### 7.1 Proof of Proposition 1

**Proposition 1.** *Let  $p$  be an RSTL over  $T(\mathcal{F})$  and let  $(W_p^*, \mu, \lambda)$  be the canonical linear representation of  $p$ . Then,  $W_p^*$  admits a basis  $B = \{e_1, \dots, e_n\}$  such that each series  $r_i$  is stochastic.*

*Proof.* Let  $c_1, \dots, c_n \in C(\mathcal{F})$  such that  $\{c_1^{-1}p, \dots, c_n^{-1}p\}$  is a basis of  $W_p$ . Let  $\{\ell_1, \dots, \ell_n\}$  be a basis of  $W_p^*$  such that  $\ell_i(c_j^{-1}p) = \delta_{ij}$  for  $1 \leq i, j \leq n$ . We show below that  $\{\ell_1, \dots, \ell_n\}$  is a normalised basis of  $W^*$ . Let  $\lambda_1, \dots, \lambda_n$  be the linear forms defined on  $W^*$  by  $\lambda_i(\ell_j) = \delta_{ij}$ . Let us show that for any  $t \in T(\mathcal{F})$  and any  $1 \leq i \leq n$ ,  $\lambda_i(\mu(t)) = c_i^{-1}p(t)$ .

Let  $\{\bar{t}_1, \dots, \bar{t}_n\}$  be a basis of  $W_p^*$  and let  $\bar{t}_i = \sum_{j=1}^n \gamma_i^j \ell_j$  for any  $1 \leq i \leq n$ . We have

$$\bar{t}_i(c_j^{-1}p) = \sum_{k=1}^n \gamma_i^k \ell_k(c_j^{-1}p) = \sum_{k=1}^n \gamma_i^k \delta_{kj} = \gamma_i^j. \quad (1)$$

Let  $t \in T(\mathcal{F})$  and  $\bar{t} = \sum_{i=1}^n \beta_i \bar{t}_i$ . We have

$$\bar{t} = \sum_{i=1}^n \left( \beta_i \sum_{j=1}^n \gamma_i^j \ell_j \right) = \sum_{j=1}^n \left( \sum_{i=1}^n \beta_i \gamma_i^j \right) \ell_j . \quad (2)$$

Because  $(W_p^*, \mu, \lambda)$  is the canonical representation of  $p$ , we have  $\mu(t) = \bar{t}$  by definition. Hence,

$$\begin{aligned} \lambda_j(\mu(t)) &= \lambda_j(\bar{t}) \stackrel{(2)}{=} \sum_{i=1}^n \beta_i \gamma_i^j \stackrel{(1)}{=} \sum_{i=1}^n \beta_i \bar{t}_i (c_j^{-1} p) \\ &= \bar{t}(c_j^{-1} p) && \text{since } \bar{t} = \sum_{i=1}^n \beta_i \bar{t}_i \\ &= c_j^{-1} p(t) . \end{aligned}$$

Hence,  $(W_p^*, \mu, \lambda_i)$  represents a stochastic language for  $1 \leq i \leq n$ .  $\square$

## 7.2 Proof of Proposition 2

**Proposition 2.** *Let us suppose that for any index  $i$ ,  $\sum_{t \in T(\mathcal{F})} p_i(t) = 1$  and  $\sum_{r \in \Delta_{q_i}} w(r) = 1$ .*

1. *Then*

$$\gamma = \sum_{n \geq 0} A^n B.$$

*Proof.* Let  $1 \leq i_1, \dots, i_l \leq n$ . One can check, by induction on  $l$  that

$$\sum_{t_1, \dots, t_l} p_{i_1}(t_1) \dots p_{i_l}(t_l) = 1 \text{ and } \sum_{t_1, \dots, t_l} p_{i_1}(t_1) \dots p_{i_l}(t_l) (|t_1| + \dots + |t_l|) = \gamma_{i_1} + \dots + \gamma_{i_l}.$$

Then,

$$\begin{aligned}
 \gamma_i &= \sum_{t \in T(\mathcal{F})} p_i(t) |t| \\
 &= \sum_{r=f(q_{i_1}, \dots, q_{i_l}) \rightarrow q_i \in \Delta_{q_i}} w(r) \sum_{t_1, \dots, t_l} p_{i_1}(t_1) \dots p_{i_l}(t_l) (|t_1| + \dots + |t_l| + 1) \\
 &= \sum_{r=f(q_{i_1}, \dots, q_{i_l}) \rightarrow q_i \in \Delta_{q_i}} w(r) \left( \sum_{t_1, \dots, t_l} p_{i_1}(t_1) \dots p_{i_l}(t_l) (|t_1| + \dots + |t_l| + 1) \right) \\
 &= \sum_{r \in \Delta_{q_i}} w(r) (\gamma_{i_1} + \dots + \gamma_{i_l} + 1) \\
 &= 1 + \sum_{r \in \Delta_{q_i}} \sum_{j=1}^n w(r) n_r(j) \gamma_j \\
 &= 1 + \sum_{j=1}^n a_{ij} \gamma_j
 \end{aligned}$$

Therefore,

$$\gamma = A\gamma + B = \sum_{n \geq 0} A^n B.$$

□

### 7.3 Proof of Proposition 3

**Proposition 3.** *Let  $\mathcal{A} = (Q = \{q_1, \dots, q_n\}, \mathcal{F}, \tau, \delta)$ , a reduced normalised representation of a strongly consistent RSTL  $p$  such that each  $p_{q_i}$  is a stochastic language and let  $A = (a_{ij})_{1 \leq i, j \leq n}$  be the matrix defined as previously. Then the spectral radius of  $A$  satisfies  $\rho(A) < 1$ .*

*Proof.* For any integer  $k$ , let  $A^k = (a_{ij}^{(k)})_{1 \leq i, j \leq n}$  and for any index  $i$ , let

$$p_i^{(k)} = \sum_{j=1}^n a_{ij}^{(k)} p_j / Z_{i,k}$$

where  $Z_{i,k}$  is a normalising coefficient defined such that  $\sum_t p_j^{(k)}(t) = 1$ .

Clearly,

$$Z_{i,k} = \sum_{j=1}^n a_{ij}^{(k)} = (A^k B)_i$$

the  $i$ -th coordinate of  $A^k B$ .

The rules of  $\mathcal{A}$ , called the rules of order one, can be unfolded by independently and simultaneously applying a rule to each state in the rhs and by multiplying



the weights. The rules of order  $k + 1$  of  $\mathcal{A}$  are obtained from rules of order  $k$  by independently and simultaneously applying a rule of order one to the states in the rhs.

Let  $\mathcal{A}$  be the WTA defined in example 4. The rules of order 2 of  $\mathcal{A}$  are:  $\{q \xrightarrow{1-\alpha} a, q \xrightarrow{\alpha(1-\alpha)^2} f(a, a), q \xrightarrow{\alpha^2(1-\alpha)} f(f(q, q), a), q \xrightarrow{\alpha^2(1-\alpha)} f(a, f(q, q)), q \xrightarrow{\alpha^3} f(f(q, q), f(q, q))\}$ .

Let  $\Delta_{q_i}^{(k)}$  be the set of rules of order  $k$  of the form  $q_i \xrightarrow{w(r)} c[q_{i_1}, \dots, q_{i_l}]$  where  $c$  is a linear context with  $l$  variables, each of which being at depth  $k$  from the root. And let  $\Delta_{i,c}^{(k)}$  be the set of rules of  $\Delta_{q_i}^{(k)}$  build on context  $c$ .

We have

$$a_{ij}^{(k)} = \sum_{r \in \Delta_{q_i}^{(k)}} n_r(j)w(r) = \sum_c \sum_{r \in \Delta_{i,c}^{(k)}} n_r(j)w(r).$$

Therefore,

$$\begin{aligned} Z_{i,k} p_i^{(k)} &= \sum_{j=1}^n a_{ij}^{(k)} p_j \\ &= \sum_c \sum_{r \in \Delta_{i,c}^{(k)}} \sum_{j=1}^n n_r(j)w(r)p_j \\ &= \sum_c \sum_{r: q_i \xrightarrow{w(r)} c[q_{i_1}, \dots, q_{i_l}] \in \Delta_{i,c}^{(k)}} w(r) \sum_{j=1}^l p_{i_j} \end{aligned}$$

Now, for any linear context  $c[\$1, \dots, \$l]$  and for any term  $t$ , we can first check that

$$\sum_{i=1}^l p(c[\$i \leftarrow t, \$j \leftarrow T(\Sigma) \text{ for } j \neq i]) \geq 0$$

and that

$$\sum_{i=1}^l p(c[\$i \leftarrow t, \$j \leftarrow T(\Sigma) \text{ for } j \neq i]) = \sum_c \sum_{r: q_i \xrightarrow{w(r)} c[q_{i_1}, \dots, q_{i_l}] \in \Delta_{i,c}^{(k)}} w(r) \sum_{j=1}^l p_{i_j}(t) = Z_{i,k} p_i^{(k)}(t).$$

Hence, either  $p_i^{(k)}$  or  $-p_i^{(k)}$  is a stochastic language, depending on the sign of  $Z_{i,k}$ .

From Lemma 1, there exists a constant  $R$  that only depends on  $p_1, \dots, p_n$  such that  $|a_{ij}^{(k)}|/Z_{i,k} \leq R$ , i.e.  $|a_{ij}^{(k)}| \leq R|Z_{i,k}| = R|(A^k B)_i|$  and from Prop. 2,  $a_{ij}^{(k)} \rightarrow 0$  when  $k$  tends to infinity. Let  $v$  be a non zero eigen vector of  $A$  and let  $\lambda$  be the associated eigen value:  $\lambda^k v = A^k v \rightarrow 0$  when  $k$  tends to infinity. Hence,  $\rho(A) < 1$ .  $\square$