

Validation of the calibration of a laser-induced fluorescence instrument for the measurement of OH radicals in the atmosphere

W. J. Bloss, J. D. Lee, C. Bloss, K. Wirtz, M. Martin-Reviejo, M. Siese, D. E. Heard, M. J. Pilling

▶ To cite this version:

W. J. Bloss, J. D. Lee, C. Bloss, K. Wirtz, M. Martin-Reviejo, et al.. Validation of the calibration of a laser-induced fluorescence instrument for the measurement of OH radicals in the atmosphere. Atmospheric Chemistry and Physics Discussions, 2003, 3 (6), pp.6029-6061. hal-00303914

HAL Id: hal-00303914 https://hal.science/hal-00303914

Submitted on 18 Jun 2008

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés. Atmos. Chem. Phys. Discuss., 3, 6029–6061, 2003 www.atmos-chem-phys.org/acpd/3/6029/ © European Geosciences Union 2003



ACPD

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page			
Abstract	Introduction		
Conclusions	References		
Tables	Figures		
14			
•	•		
Back	Close		
Full Screen / Esc			
Print	Print Version		
Interactive Discussion			

© EGU 2003

Validation of the calibration of a laser-induced fluorescence instrument for the measurement of OH radicals in the atmosphere

W. J. Bloss¹, J. D. Lee¹, C. Bloss¹, K. Wirtz², M. Martin-Reviejo², M. Siese³, D. E. Heard¹, and M. J. Pilling¹

 ¹Department of Chemistry, University of Leeds, Woodhouse Lane, Leeds, LS2 9JT, UK
 ²Fundación CEAM, EUPHORE Laboratories, C/Charles Darwin 14, Parque Technológico, 46980 Paterna, Valencia, Spain
 ³Institut für Chemie und Dynamik der Geosphäre, Institut II: Troposphäre, Forschungszentrum Jülich, D-52425 Jülich, Germany

Received: 28 October 2003 – Accepted: 21 November 2003 – Published: 28 November 2003 Correspondence to: W. Bloss (w.bloss@chemistry.leeds.ac.uk)

Abstract

An assessment of the accuracy of OH concentrations measured in a smog chamber by a calibrated laser-induced fluorescence (LIF) instrument has been made, in the course of 9 experiments performed to study the photo-oxidation of benzene, toluene, 1,3,5trimethylbenzene, para-xylene, ortho-cresol and ethene at the European Photoreactor 5 facility (EUPHORE). The LIF system was calibrated via the water photolysis/ozone actinometry approach. OH concentrations were inferred from the instantaneous rate of removal of each hydrocarbon species (measured by FTIR or HPLC) via the appropriate rate coefficient for their reaction with OH, and compared with those obtained from the LIF system. Good agreement between the two approaches was found for all 10 species with the exception of 1,3,5-trimethylbenzene, for which OH concentrations inferred from hydrocarbon removal were a factor of 3 lower than those measured by the LIF system. From the remaining 8 experiments, an overall value of 1.15 ± 0.13 ($\pm1\sigma$) was obtained for [OH]_{LIF}/[OH]_{Hvdrocarbon Decay}, compared with the estimated uncertainty in the accuracy of the water photolysis/ozone actinometry OH calibration technique of 15 **26%** (1*σ*).

1. Introduction

Accurate measurements of trace gas concentrations are essential to study the chemistry of the Earth's atmosphere. Hydroxyl radicals (OH) are the principal oxidising
 species in the troposphere, and dominate the daytime removal of most volatile organic compounds (VOCs). Reaction with OH thus governs the atmospheric lifetime of many species, and hence their potential to contribute to (for example) global warming and ozone depletion. The OH-initiated oxidation of hydrocarbons and CO in the presence of oxides of nitrogen also leads to the generation of ozone, a constituent of photochemical smog. As the reactivity of OH is high, its concentration is low (of the order of 0.04–0.2 pptv in the sunlit troposphere) and chemical lifetime is short (0.1–

ACPD

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.



1 s); OH concentrations are therefore determined by local chemical processes rather than transport, and their in situ measurement can be used to validate numerical models of tropospheric chemistry. Accurate measurement of atmospheric hydroxyl radical concentrations has been a goal of atmospheric scientists for three decades, following recognition of the central importance of OH radicals in tropospheric oxidation chemistry (Levy, 1971).

In-situ measurements of OH concentrations have been performed using radiometric, wet chemical and spin trapping techniques, however most recent measurements have been performed by the techniques of DOAS (Differential Optical Absorption Spectroscopy), LIF (Laser Induced Fluorescence) and CIMS (Chemical Ionisation Mass Spectrometry) (Heard and Pilling, 2003). CIMS and LIF are not absolute measure-

ment techniques, and so require determination of the instrument response factor using an OH calibration source. The production of a well-known concentration of OH radicals at the instrument inlet under ambient atmospheric conditions presents a considerable challenge, and is critical to the accuracy of the current generation of LIF- and CIMS-

based ambient OH measurement systems.

5

10

A series of photosmog experiments has recently been performed at the European Photoreactor Facility (EUPHORE), in Valencia, Spain, to study the oxidation of selected aromatic (and related) hydrocarbon species under polluted conditions. Instrumentation

- ²⁰ deployed included FTIR and HPLC for monitoring of hydrocarbon concentrations, and LIF for direct in situ measurement of OH concentrations. Under the conditions of the experiments, the dominant chemical removal route for the primary (initial) hydrocarbon species was by reaction with OH; thus OH concentrations could be calculated throughout each experiment, from the instantaneous rate of hydrocarbon decay via the
- relevant rate coefficient for reaction with OH, and compared with those obtained from the LIF instrument. In this way the accuracy of the LIF instrument measurements may be assessed.

The water photolysis/ozone actinometry approach used to calibrate the EUPHORE LIF system is commonly used in the calibration of field instruments for the measure-

ACPD

3, 6029–6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.



ment of ambient OH by LIF (Bloss et al., 2003; Holland et al., 2003; Kanaya et al., 2001). In this paper we present an assessment of the accuracy of this calibration based upon hydrocarbon decays measured in 9 photo-oxidation studies performed upon benzene, toluene, 1,3,5-trimethylbenzene, ethene, para-xylene and ortho-cresol.

5 2. The OH LIF system: description

The LIF system installed at the EUPHORE facility has been described in detail previously (Becker, 1999; Siese et al., 2001), therefore only a brief description of the instrument is given here. OH concentrations are measured by laser induced fluorescence at low pressure – the Fluorescence Assay by Gas Expansion (FAGE) technique (Hard et al., 1984): Ambient air is drawn through a small orifice into a fluorescence chamber, maintained at low pressure. A pulsed laser beam is directed through the gas expansion, leading to excitation of OH radicals through the (0,0) band of the ($A^2\Sigma^+ \leftarrow X^2\Pi_i$) transition near 308 nm. On-resonance (308 nm) fluorescence accompanying the subsequent relaxation of the OH($A^2\Sigma^+$) is detected orthogonally to the gas expansion and excitation beam. Use of the low pressure chamber extends the OH fluorescence life-

- time beyond the duration of the laser pulse, thus retrieval of scattered laser light can be minimised through temporal gating of the detection system. A high pulse-repetitionfrequency (PRF), low pulse energy excitation beam is used to avoid optical saturation effects and minimise photolytic generation of OH from other chemical species. Exci-
- tation at 308 nm with on-resonance fluorescence monitoring is used rather than the alternative diagonal (1,0) fluorescence scheme with excitation near 282 nm in order to minimise generation of OH through the photolysis of ozone and subsequent reaction of O(¹D) atoms with water vapour (Chan et al., 1990).

The EUPHORE LIF system uses a copper vapour laser pumped dye laser system (Oxford Lasers ACL 35/Lambda Physik FL3001) to generate 308 nm radiation at a PRF of 8.5 kHz. The laser power entering the fluorescence cell is typically 10–15 mW. A 0.38 mm diameter conically shaped nozzle is used to sample air from the EUPHORE 3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page		
Abstract	Introduction	
Conclusions	References	
Tables	Figures	
I4 >1		
•	►	
Back	Close	
Full Screen / Esc		
Print Version		
Interactive Discussion		

chamber into the fluorescence cell, comprising a 100 mm aluminium cube maintained at a pressure of 1.6 mbar. Fluorescence is collimated through 75 mm optics and directed onto a micro-channel plate photomultiplier tube detector through a 308 nm bandpass interference filter and an additional solar-blind filter. A concave mirror positioned 5 opposite the detection axis approximately doubles the solid angle of fluorescence col-

lected. Photon counting is used to monitor the amplified signal from the PMT, which is subsequently normalised by measured excitation laser power.

Contributions to the measured signal arise from OH LIF, and also from scattered laser and solar light, and detector dark current. Contributions from the latter sources

are subtracted: Scattered laser light is measured by performing alternating measure-10 ments on- and off- the OH line; the latter containing no contribution from OH LIF. Scattered solar radiation is measured during a second photon counting window, several microseconds after each excitation laser pulse, at which time all OH LIF has decayed away. The on-line off-line cycle, yielding a single OH concentration measurement, typically takes 60–90 s, with variability between cycles being less than 5%. 15

25

3. The OH LIF system: calibration

LIF is not an absolute technique, thus calibration of the instrument response factor is required. The LIF signal per unit time (S) is proportional to the OH concentration and excitation laser power (P_{wr}) , with the constant of proportionality or calibration constant C dependent upon factors such as the Einstein coefficients for the particular OH transi-

20 tion in question, rotational population, the overlap of the OH Doppler and laser spectral line widths and fluorescence collection efficiency:

 $S = C \times P_{wr} \times [OH].$

While the value of C is in principle calculable (Stevens et al., 1994; Holland et al., 1995), in practice calibration with a known concentration of OH is required for accurate measurements. As noted above, during ambient measurements the total signal

ACPD

3,6029-6061,2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.



© EGU 2003

(i)

recorded contains contributions from scattered solar and laser light and detector dark current; S in Eq. (i) refers solely to the contribution from OH LIF.

The response of the EUPHORE LIF system was calibrated by the water photolysis – ozone actinometry method (Aschmutat et al., 1994). The calibration source consists of a laminar flow reactor, consisting of a 20 mm internal diameter by 600 mm length quartz tube, through which 20 slm of humidified air was flowed. The 184.9 nm radiation from a mercury pen-ray lamp was used to photolyse the water and oxygen within the tube, leading to the generation of OH, HO₂ and O₃ according to reactions (1)–(4), below:

$$H_2O+h\nu \rightarrow OH+H$$
 (1)

$$H+O_2+M \to HO_2+M \tag{2}$$

10

$$O_2 + h\nu \to O + O \tag{3}$$

$$2 \times \quad O + O_2 + M \to O_3 + M. \tag{4}$$

After passing the photolysis region the calibration flow impinges upon the nozzle of the LIF system, and a fraction of the total flow (ca. 1 slm) is drawn into the instrument. The remainder of the flow is directed to an ozone monitor and subsequently vented. As the humidity of the air entering the flow reactor is known (measured using a chilled-mirror dew-point hygrometer) the concentration of OH or HO₂ radicals formed can be calculated from the measured ozone concentration and the relevant cross sections and quantum yields.

- ²⁰ A complication arises due to the radial distribution of the axial flow velocity within the laminar flow tube: Air in the centre of the tube travels faster than air at the edges, and so spends less time in the photolysis region, and thus has lower OH, HO_2 and O_3 concentrations. The LIF nozzle samples from the centre of the flow tube, while the ozone concentration measured is the average of the remaining flow – a correction (the
- ²⁵ profile factor, *P*) must therefore be applied. For perfect laminar flow, with a parabolic velocity profile, and zero sample withdrawal by the LIF nozzle, the correction would be

a factor of 2; for the EUPHORE calibration system a value of $P = (1.85 \pm 0.09)$ has been measured (Siese et al., 2001).

The OH (or HO_2) concentration present at the LIF system sampling nozzle can then be calculated via Eq. (ii):

$$[OH] = \frac{[O_3] \times [H_2O] \times \sigma_{H_2O} \times \Phi_{OH}}{P \times [O_2] \times \sigma_{O_2} \times \Phi_{O_3}}.$$
 (ii)

where Φ_{OH} and Φ_{O_3} , the quantum yields for production of OH and (ultimately) O_3 from water and oxygen photolysis at 184.9 nm, have values of 1 and 2, respectively, P is the profile factor referred to above, and $\sigma(H_2O)$ and $\sigma(O_2)$ are absorption cross sections for water and oxygen (respectively) at 184.9 nm. A value of $(7.1\pm0.2)\times10^{-20}$ molecule⁻¹ cm² is used for $\sigma(H_2O)$, being the mean of the determinations of Cantrell et 10 al. (1997), Hofzumahaus et al. (1997) and Creasey et al. (2000). The emission spectrum of the 184.9 nm band from mercury pen-ray lamps overlaps with several features in the Schumann-Runge band of the O₂ spectrum (Lanzendorf et al., 1997). Under typical oxygen column densities employed for LIF calibration (ca. (0.5-1)×10¹⁹ molecule cm⁻²), some absorption features within the lamp spectrum are saturated while others are not; thus the appropriate value of $\sigma(O_2)$ for calculation of O_2 photolysis in Eq. (ii) is dependent upon the actual oxygen column used. Moreover, the emission spectrum varies from lamp to lamp, and is dependent upon operating conditions (e.g. temperature, power) (Lanzendorf et al., 1997; Creasey et al., 2000). For the pen-ray lamp used in the EUPHORE LIF system, a value of $\sigma(O_2) = (1.23 \pm 0.05) \times 10^{-20}$ molecule⁻¹ cm² 20 was determined under the actual operating conditions of oxygen column, lamp current and cooling flow employed in the calibration system.

Care is taken to work with sufficiently low photolysis flux that reactions between hydroxyl or hydroperoxy radicals and ozone (5–8, below) do not significantly alter their ²⁵ concentrations after generation and prior to sampling into the LIF cell:

 $OH+HO_2 \rightarrow H_2O+O_2$

5

ACPD

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page			
Abstract	Introduction		
Conclusions	References		
Tables	Figures		
14			
•	•		
Back	Close		
Full Screen / Esc			
Print \	/ersion		
Interactive Discussion			

 $\text{OH+O}_3 \rightarrow \text{HO}_2\text{+O}_2$

 $OH+OH \rightarrow H_2O+O/H_2O_2$

 $HO_2 + O_3 \rightarrow OH + 2O_2$.

Typical OH/HO₂ and O₃ concentrations generated were 7×10^8 molecule cm⁻³ and 5×10^{10} molecule cm⁻³, respectively, with a flow tube residence time of less than 65 ms (between the photolysis region and sampling nozzle). Under these conditions, the fraction of OH lost through reactions (5), (6) and (7), and formed through reaction (8), is calculated to be equivalent to 0.5, 0.04, 0.02 and 0.001% (respectively) of the initial OH concentration.

¹⁰ The OH LIF signal is expected to decrease with increasing humidity in the sampled air, as H_2O is an extremely efficient quencher of electronically excited OH radicals: Relative values of *k* for the reaction

 $OH(A^{2}\Sigma^{+}, v'=0)+X \rightarrow OH(X^{2}\Pi_{i}, v'')+X,$

where X=N₂, O₂, H₂O are 1:4:20 at 294 K (Bailey et al., 1997, 1999), which equates
to a calculated reduction in the total OH fluorescence quantum yield of approximately 7% from a totally dry atmosphere to one with 10 000 ppmv (1%) water vapour (typical of continental boundary layer air). However, the sensitivity of OH LIF systems has in some cases been observed to decrease with increasing humidity to a greater extent than can be explained by OH quenching alone (Holland et al., 1995; Hofzumahaus et al., 1996; Creasey et al., 1997a). The reduction in sensitivity (of up to 50% between 1000 ppmv (0.1%) and 10 000 ppmv (1%) H₂O) has been attributed to the formation of water clusters in the supersonic gas expansion, which scavenge OH and HO₂ (Holland et al., 1995): Temperatures in the supersonic expansion, which extends for a few tens of mm from the sampling nozzle into the fluorescence chamber, briefly dip to ca. 25 K;

however the air rapidly warms – the OH rotational temperature at the point of LIF excitation is ca. 220 K (Creasey et al., 1997b). The humidity effect can be accounted for in the

ACPD 3,6029-6061,2003 Validation of the calibration of a OH LIF instrument W. J. Bloss et al. **Title Page** Introduction Abstract Conclusions References Figures Tables ► Back Close Full Screen / Esc Print Version Interactive Discussion

© EGU 2003

(6)

(7)

(8)

(9)

case of most tropospheric measurements by performing calibrations at ambient water vapour concentrations. In the EUPHORE chambers, absolute humidity is usually main-tained at levels between 100 and 200 ppmv, much lower than ambient boundary layer values, in order to minimise interference in the FTIR spectra. Calibrations performed at

- ⁵ this humidity are noisy (due to the low [OH] formed; Eq. ii), so routine calibrations performed between photosmog experiments to check upon instrument performance were conducted at ca. 900 ppmv H₂O. In separate experiments the calibration constant was measured at water mixing ratios between 150 and 900 ppmv, and was found to be constant to within $\pm 15\%$. Holland et al. (2003) report that nozzle design and diameter
- appear to be critical factors in determining the anomalous humidity dependence to the instrument calibration; using a shaped nozzle similar to that employed at EUPHORE (0.4 mm diameter) they observed a humidity dependence to the calibration constant consistent with the H₂O quenching mechanism alone.

The overall uncertainty in the calculated OH concentration (Eq. ii) and hence the ¹⁵ instrument calibration arises from the various factors described above, and is summarised in Table 1. Addition of the various contributions in quadrature yields an overall uncertainty (1 σ) in the calculated [OH] from the calibration source of 26%, with the dominant factor being the uncertainty in the measurement of ozone concentration, in particular noise in the zero measurement of the ozone instrument (Ansyco GmbH ²⁰ model 41M) which at typical values of ±0.5 ppbv is significant compared to the measured ozone mixing ratios of 3–4 ppbv. Individual OH measurements will have a greater uncertainty, as their precision will be reduced by factors such as corrections for scattered solar and laser light, and the repeatability of excitation laser wavelength selection

tered solar and laser light, and the repeatability of excitation laser wavelength selection between on-line and off-line measurements – typically better than 5%.

25 4. Experimental

Measurements were performed in the course of the EXACT (Effects of the Atmospheric Oxidation of Aromatic Compounds in the Troposphere) programme at the European

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page		
Abstract	Introduction	
Conclusions	References	
Tables	Figures	
•	►	
Back	Close	
Full Screen / Esc		
Print Version		
Interactive Discussion		

Photoreactor facility (EUPHORE) situated in Valencia, Spain during September 2001 and July 2002. The EXACT campaign and EUPHORE facility are detailed fully in Pilling (2003), Becker (1997) and Klotz et al. (1998), respectively; only a brief overview and description of pertinent instrumentation is given here. The EXACT project aimed

- to elucidate the oxidation mechanisms for benzene, toluene, the xylenes and 1,3,5trimethylbenzene, in the light of estimates that aromatic species could account for up to 30% of the total anthropogenic hydrocarbon oxidation initiated ozone production under European conditions (Derwent et al., 1996). The project combined laboratory studies and theoretical work to generate oxidation mechanisms for the target species within the
- ¹⁰ Master Chemical Mechanism (MCM, http://www.chem.leeds.ac.uk/Atmospheric/MCM/ mcmproj.html), with subsequent smog chamber experiments to test and refine the mechanisms. The data reported in this paper were acquired in the course of these validation experiments.

The EUPHORE chambers consist of two 195 m³ volume hemi-spherical bags formed from FEP-teflon foil (with transmission greater than 80% between 280 and 640 nm) illuminated by natural sunlight. Hydraulically actuated steel housings exclude sunlight and protect the chambers from inclement weather when not in use. Chamber pressure is maintained at 100-200 Pa above ambient, and a floor cooling system is used to counteract solar heating during experiments. The chamber temperature is registered and approximately follows the ambient temperature (typically maintained at 25-20 35°C). The chambers are filled with ambient air, which is treated by an air purification and drying system to remove NO_v, H₂O (<200 ppmv) and non-methane hydrocarbons $(<0.3 \,\mu\text{g}\,\text{m}^{-3})$. Chamber mixing time is 2 min (fan assisted). Chamber A, used for all the experiments reported in this study, was equipped with the LIF system for OH radical measurement, a long-path FTIR interferometer system (Nicolet Magna 550, 25 326.8 m absorption path length; 1 cm⁻¹ resolution) and off-line RP-HPLC system (HP 1050 series isocratic pump with diode array detector (HP 1100) and fluorescence detector HP1046A). Sampling of the polar ring retaining compounds for subsequent anal3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.



© EGU 2003

vsis by HPLC was performed using a double coil stripping system directly connected

to the chamber. Additional instrumentation in chamber A included various ancillary monitors for O_3 , NO_x , $J(NO_2)$ and meteorological parameters. For all the experiments discussed in this paper, hydrocarbon concentrations were monitored by FTIR; in the case of o-cresol measurements were made by HPLC also.

- ⁵ The conditions for each experiment are outlined in Table 2. Experiments were conducted by introducing the hydrocarbon species of interest together with the required concentration of NO/NO₂, allowing 10 min for mixing to occur, and then initiating the radical oxidation chemistry by opening the chamber covers to admit sunlight. During the experiments a certain amount of air from the chamber is lost through small leaks
- ¹⁰ and withdrawal of air samples for analysis; clean air is added to compensate for this and some dilution of the reactants and products occurs as a result. To measure the dilution rate SF_6 was added to the reaction mixture as an inert tracer in each experiment and its concentration was monitored by FTIR. The average calculated loss rate of SF_6 over the course of each experiment (given in Table 2) was used as to calculate the 15 contribution of dilution to the reduction in concentration of each hydrocarbon species.
- In addition to dilution, removal of the primary hydrocarbon species (benzene, toluene, 1,3,5-trimethylbenzene, ethene, para-xylene and ortho-cresol) could in principle occur via photolysis, heterogeneous uptake and chemical reaction. Photolysis is unimportant for monocyclic aromatic hydrocarbons in the troposphere as their absorp-
- ²⁰ tion spectra do not extend into the regions of the spectrum where significant actinic flux is encountered at low altitudes (σ <1×10⁻¹⁹ molecule⁻¹ cm² at 285 nm and decreasing to higher wavelengths for all aromatic species considered here (Calvert et al., 2002; Etzkorn et al., 1999). Similar comments apply to the photochemistry of ethene (Atkinson, 1990). The particulate loading of the purified air used to fill the EUPHORE chambers is low (<50 particles cm⁻³) and aerosol yields from the monocyclic aromatic species
- considered are low under the conditions of the EXACT experiments (Pilling, 2003) thus heterogeneous losses are not expected to be a significant sink for the primary hydrocarbon species considered here; rather chemical reaction dominates their active removal.

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page		
Abstract	Introduction	
Conclusions	References	
Tables	Figures	
•	►	
■ Back	► Close	
Back Full Scre	Close een / Esc	
Back Full Scree Print \	Close een / Esc	

In the lower atmosphere, reaction with O_3 , OH, NO_3 and $O({}^3P)$ have been identified as the key processes which initiate the oxidation of aromatic hydrocarbons (Atkinson, 1994). Table 3 lists the percentage contribution to the removal of each hydrocarbon species for reaction with O_3 , OH, NO_3 and $O({}^3P)$, under the conditions of the experiments performed. Values were calculated to give a "worst case" value from the perspective of the importance of reaction with OH: While mean OH concentrations (as measured by LIF) were used, concentrations of O_3 , NO_3 and $O({}^3P)$ were all upper limits: The peak ozone concentration for each experiment is used, while in practice the mean ozone concentration is much lower. NO_3 concentrations were calculated from simple photochemical steady state (formation via NO_2+O_3 ; loss via photolysis), while in practice NO_3 concentrations will be lowered by reaction with NO, NO_2 , hydrocarbons etc. $O({}^3P)$ concentrations were calculated from measured [O_3] and calculated J(O_3), assuming that all $O({}^1D)$ was quenched to $O({}^3P)$ and that all $O({}^3P)$ only underwent reaction with O_2 .

It can be seen from Table 3 that reaction with OH accounts for more than 99.9% of the loss of each hydrocarbon species, with the exceptions of ethene and o-cresol, for which reaction with O₃ and NO₃ (respectively) is significant. In the case of the ethene experiment (4), ozone mixing ratios increased from <1 ppb to 446 ppb over the course of 5 h, thus the mean removal of ethene by ozone was rather lower than line 4
 of Table 3 suggests, at 16.4%. The contribution of ozonolysis to the removal of ethene was accounted for as detailed in Sect. 5, below.

Considering the case of o-cresol, the NO₃ concentration obtained from the simple steady-state approach (in which photolysis is the only sink for NO₃), ca. 1.8×10^8 molecule cm⁻³, is greatly overestimated as NO₃ will react with many species present, not least o-cresol itself. Inclusion of this reaction alone as an additional NO₃ sink in the steady state analysis reduces the calculated mean [NO₃] to 7.3×10^5 molecule cm⁻³, and reduces the significance of NO₃ for removal of cresol to 5%. This is also an overestimate, as the primary fate of NO₃ was reaction with products of cresol oxidation – a simulation of the cresol oxidation system, performed using

ACPD

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.



the MCM version 3.1 (Pilling, 2003) employing all relevant reactions and initiated with measured concentrations, determined that 28% of the loss of NO₃ was by reaction with cresol, less than 0.1% by photolysis and the remainder by reaction with products of cresol oxidation. The same simulation determined that, after dilution, over 98% of the removal of cresol occurred through reaction with OH.

The removal of the primary hydrocarbon species is thus overwhelmingly dominated by reaction with OH (after accounting for dilution, and the ozonolysis reaction in the case of ethene), and the hydrocarbon decay data can be used to infer the concentration of OH radicals present.

10 5. Inferred OH from hydrocarbon decays: method

For each experiment, a subset of hydrocarbon and OH data was selected corresponding to the period during which the chamber was open to sunlight (typically 3–5 h). The hydrocarbon concentration-time data were analysed using the interval method (Guggenheim, 1926) to obtain a pseudo-first-order rate coefficient (k') for hydrocarbon removal:

$$k' = \ln(c_1/c_2)/(t_2 - t_1), \tag{iii}$$

where c_1 and c_2 were the hydrocarbon concentrations measured at times t_1 and t_2 , respectively. The mean OH concentration during the time period between t_1 and t_2 was then obtained via

²⁰ [OH]_{HC} =
$$(k' - k_{dil})/k_{OH+HC}$$
,

15

where k_{dil} is a first-order rate coefficient for the effect of dilution and k_{OH+HC} is the rate coefficient for the reaction between OH radicals and the hydrocarbon species in question, at the appropriate temperature (Table 2) and atmospheric pressure.

The treatment of the ethene data (experiment 4) was an exception to the above procedure: In this system, reaction with ozone accounts for between 1 and 30% of

ACPD

3, 6029–6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.



(iv)

the chemical loss of ethene, depending upon the time-point considered. Equation (iv) were therefore modified to include a term accounting for the ozonolysis reaction, and the ethene data were analysed to return $[OH]_{HC}$ according to Eq. (v):

 $[OH]_{HC} = (k' - k_{dil} - k_{C_2H_4 + O_3}[O_3]) / k_{OH + HC}$

⁵ A value of 1.87×10^{-18} molecule⁻¹ cm³ s⁻¹ was used for $k_{C_2H_4+O_3}$ (Atkinson et al., 2002). Analysis of the ethene data was otherwise identical to that for the other hydrocarbon species, as described below.

Each inferred OH concentration was compared with the mean value for [OH] obtained by the LIF instrument, $[OH]_{LIF}$, over the same time period (t_1 to t_2). The overall agreement for each species/experiment was quantified by calculating the ratio, R, of the sum of the values of [OH] obtained from the averaged LIF measurements to the equivalent from the hydrocarbon decay data:

 $R = \Sigma[OH]_{LIF} / \Sigma[OH]_{HC}$

20

Thus a value of unity for *R* indicates perfect agreement, values greater than 1 indicate that OH concentrations measured by the LIF system were greater than those inferred from the hydrocarbon decay and suggest that the calibration constant *C* (Eq. i) may be too small, and values less than 1 suggest the converse.

Random noise in the hydrocarbon concentrations obtained from the FTIR data leads to a high degree of variability in the inferred OH concentrations, as can be seen in Fig. 1a, showing the results for benzene (experiment 8); in some cases negative OH concentrations are returned. This variability can be reduced by increasing the time

- interval between each pair of hydrocarbon concentrations analysed. In this work a 5-hydrocarbon measurement point interval (ca. 40 min) gave a reasonable balance between reducing the noise in the inferred OH concentrations and maintaining a signif-
- icant number of data points in the analysis; thus the first inferred OH concentration was obtained from hydrocarbon concentrations c_1 and c_5 , the second from c_2 and c_6 , and so forth. The OH concentrations obtained from the LIF system were averaged

ACPD 3,6029-6061,2003 Validation of the calibration of a OH LIF instrument W. J. Bloss et al. **Title Page** Introduction Abstract Conclusions References Figures Tables ► Back Close Full Screen / Esc Print Version Interactive Discussion © EGU 2003

(v)

(vi)

over the same time interval, i.e. t_1 to t_5 , t_2 to t_6 etc., corresponding typically to 15– 20 individual OH measurements (each taken at 90–120 s intervals) for each value of $[OH]_{LIF}$. Figure 1b shows the reduced variability in inferred OH concentration with a 5-point interval between benzene concentrations. The value of *R* obtained is equal (to ⁵ within 1%) in each case; however the reduction in scatter accompanying adoption of the 5-point interval greatly facilitates visual comparison of the values of $[OH]_{HC}$ and $[OH]_{LIF}$.

Rate coefficients for the reaction of OH with the various hydrocarbon species, k_{OH+HC} , as given in Table 4, were taken from Calvert et al. (2002), with the exception of ethene, for which the mean of the values recommended by the IUPAC (Atkinson et al., 2002) and NASA/JPL (Sander et al., 2003) panels was used. Uncertainty in the individual values is discussed further below.

6. Inferred OH from hydrocarbon decays: results

The hydrocarbon decay data, individual measured LIF OH concentrations, inferred OH concentrations $[OH]_{HC}$ and averaged LIF OH concentrations $[OH]_{LIF}$ are shown in Fig. 2. Table 4 lists the value of the OH + hydrocarbon rate coefficient used to evaluate each dataset, and gives the values of *R*, the ratio of $[OH]_{LIF}$ to $[OH]_{HC}$, obtained. The uncertainty quoted in Table 4 reflects the uncertainty in the rate coefficient, k_{OH+HC} only – the value of *R* is directly proportional to k_{OH+HC} via Eqs. (iv) and (vi). Figure 3 compares the values of *R* obtained for each experiment, with two confidence intervals shown – the inner limits reflecting solely uncertainty in k_{OH+HC} , as given in Table 4, and the outer limits reflecting the propagation of this with the uncertainty (26%) in the LIF system calibration. The results for each individual species are discussed below.

ACPD

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page			
Abstract	Introduction		
Conclusions	References		
Tables	Figures		
	_		
	►I		
•	►		
Back	Close		
Full Screen / Esc			
Print V	ersion		
Interactive Discussion			

6.1. Toluene

Experiments 1 and 3 show excellent agreement between the LIF and hydrocarboninferred (HC) values for OH, with values for R of (0.96±0.19) and (1.06±0.21) obtained, respectively.

5 6.2. 1,3,5-Trimethylbenzene

The OH concentrations obtained from the LIF and HC analyses are not in agreement for 1,3,5-TMB, with the LIF data considerably higher than the hydrocarbon decay giving R=(3.0±0.6). The quality of the hydrocarbon decay data is poor (reflecting the lower 1,3,5-TMB concentrations used in this experiment) which contributes to the variability in the [OH]_{HC} values, but cannot explain the discrepancy between the absolute values, possible reasons for which are discussed in Sect. 7.

6.3. Ethene

10

The OH concentrations inferred from the decay of ethene are in good agreement with those measured by the LIF system throughout the experiment, giving a value of $R = (0.87 \pm 0.21)$. The correlation in the shape of the OH profiles indicates that the modified analysis to account for the ozonolysis reaction (Eq. v) is correct, as the contribution to chemical loss of ethene from this reaction ranges from 1.5% for the first point to 39.6% for the final point.

6.4. o-Cresol

²⁰ The cresol experiments show good agreement between OH concentrations measured directly by LIF and inferred from the hydrocarbon decays, with values of $R = (0.83 \pm 0.25)$ and (0.93 ± 0.28) for the FTIR and HPLC analyses, respectively. The HPLC data are smoother than those from the FTIR, reflected in reduced noise in the values of $[OH]_{HC}$ in Fig. 2f. Differences in the $[OH]_{LIF}$ data between Figs. 2e and 2f reflect the FTIR and

6044

ACPD

Title Page		
Abstract	Introduction	
Conclusions	References	
Tables	Figures	
I	►I	
•	Þ	
Back	Close	
Full Screen / Esc		
Print Version		
Interactive	Interactive Discussion	
© EGU 2003		

HPLC data being acquired on different timescales, and thus different averaging of the individual LIF data points being applied.

6.5. para-Xylene

The data from the first p-xylene experiment (6) is limited due to a partial power failure, which interrupted OH data acquisition at approximately 12:30 pm. While data acquisition resumed 90 min later, confidence in the validity of the OH calibration was low as the dye laser beam alignment had to be completely reoptimised, and no check of the instrument calibration was possible until the next day; therefore only data acquired prior to the power failure are considered. Agreement between $[OH]_{HC}$ and $[OH]_{LIF}$ is poor for experiment 6, $R = (1.69 \pm 0.42)$, better for experiment 9, $R = (1.45 \pm 0.36)$ considering just the uncertainty in the OH + p-xylene rate coefficient, and $R = (1.45 \pm 0.52)$ if the uncertainty in the LIF calibration is factored in (as shown in Fig. 3). Again, possible reasons for the disagreement are considered below.

6.6. Benzene

The contribution of chemical loss (reaction with OH) to the total loss of benzene is the least of all the species considered (Table 2); dilution dominates due to the low rate coefficient for the benzene + OH reaction. Accordingly the values of [OH]_{HC} obtained are noisier, as scatter in the FTIR retrievals has a greater influence. The absolute agreement between the LIF and HC [OH] is good for experiment 7 (Fig. 2i) and excellent for experiment 8 (Fig. 1), with values of *R*=(1.29±0.26) and (1.04±0.21) obtained, although inspection of the plot indicates that the confidence interval, reflecting uncertainty in *k*(OH+benzene), is probably underestimated for experiment 7.

ACPD

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.



7. Discussion

5

The principal factor affecting the value of R, the measure of absolute agreement between HC and LIF values for [OH], is the rate coefficient used for the hydrocarbonhydroxyl reaction (Eq. iv). Studies of the relevant rate coefficients have been reviewed by Calvert et al. (2002), recommended values from which are used in this work; however the discrepancies observed in the cases of 135-TMB and p-xylene merit further attention.

Measurements of k(OH+1, 3, 5-TMB) at 298 K range from $(3.78\pm0.52)\times10^{-11}$ molecule⁻¹ cm³ s⁻¹ (Ohta and Ohyama, 1985) to $(6.24\pm0.75)\times10^{-11}$ molecule⁻¹ cm³ s⁻¹ (Perry et al., 1977), with a recommended value 10 (Calvert et al., 2002) of k(OH+1, 3, 5–TMB)=(5.67±1.13)×10⁻¹¹ molecule⁻¹ cm³ s⁻¹. Adoption of the lowest measured value $(3.78 \times 10^{-11} \text{ molecule}^{-1} \text{ cm}^3 \text{ s}^{-1})$ would reduce the value of R obtained from this experiment by 33%, to (2.01±0.59) (confidence interval reflects combined uncertainty in k and the LIF calibration). Uncertainty in the kinetic data can thus account for some, but not all, of the discrepancy between $[OH]_{HC}$ and $[OH]_{IIF}$ in the 1,3,5-TMB experiment. For p-xylene, measurements of k(OH+p-xylene)exhibit significant scatter, ranging from $(1.05\pm0.1)\times10^{-11}$ molecule⁻¹ cm³ s⁻¹ (Ravishankara et al., 1978) to $(1.82\pm0.22)\times10^{-11}$ molecule⁻¹ cm³ s⁻¹ (Perry et al., 1977) with the recommendation of Calvert et al. (2002), of $(1.43\pm0.36)\times10^{-11}$ molecule⁻¹ cm³ s⁻¹ being a straight average of a subset of the recent determinations. Were the lower 20 measurement of 1.05×10^{-11} molecule⁻¹ cm³ s⁻¹ to be adopted, the values of R for the p-xylene experiments would be reduced by 27% to (1.24 ± 0.35) and (1.06 ± 0.30) for experiments 6 and 9, respectively, in good agreement with the values from the other

species considered (again, confidence interval reflects combined uncertainty in k and the LIF calibration). The results of this work therefore suggest that the true value for k(OH+p-xylene) may be somewhat lower than the value recommended by Calvert et al. (2002).

If the values for the rate constants (k_{OH+HC}) used are correct, the sense of discrep-

ACPD

3, 6029–6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page		
Abstract	Introduction	
Conclusions	References	
Tables	Figures	
14	►I	
•	►	
Back	Close	
Full Screen / Esc		
Print Version		
Interactive Discussion		

ancy which might be anticipated in this work (assuming all other factors to be correct) is $[OH]_{HC}>[OH]_{LIF}$ – which could arise if processes other than dilution and reaction with OH contributed to the removal of the hydrocarbon species. Disagreement in the opposite sense (as observed for 1,3,5-TMB and p-xylene) implies either regeneration of the primary hydrocarbon (for which no mechanism can be envisaged) or a problem with the values of $[OH]_{HC}$ or $[OH]_{LIF}$. Other sources of loss of the hydrocarbon species have been discussed (Sect. 4); however two potential systematic errors in the values of $[OH]_{HC}$ and $[OH]_{LIF}$ are considered below: Errors in the FTIR retrievals of the hydro-

carbon concentrations, and generation of artefact OH radicals, through photolysis of sampled compounds by the excitation laser pulse.

The pseudo-first order nature of the analysis leads to the inferred OH concentrations, [OH]_{HC}, being independent of the absolute hydrocarbon concentrations, and hence of the cross sections used to analyse the FTIR data, and standards adopted to calibrate the HPLC instrument. Errors in the retrieved hydrocarbon concentrations, for exam-¹⁵ ple due to overlap with absorption spectra of photo-oxidation products, could however lead to incorrect values for [OH]_{HC}. Such spectral contamination would be expected to vary (and worsen) over the course of the experiments, as the complexity of the analyte increased and the primary hydrocarbon concentration decreased, and thus any deviation between [OH]_{HC} and [OH]_{LIF} would be expected to increase. This trend is observed in the case of 1,3,5-TMB (experiment 2), and to a lesser extent in the case of p-xylene. In the case of 1,3,5-TMB however no spectral overlap occurs between

- of p-xylene. In the case of 1,3,5-TMB however no spectral overlap occurs between the trimethybenzene and the two major photo-oxidation products, methylglyoxal and PAN. Moreover, the 1,3,5-TMB concentrations obtained from the FTIR analysis are in good agreement with those obtained from GC-FID measurements performed during the same experiment.
 - The photolysis of ambient ozone, generating $O(^{1}D)$ which could react with ambient water vapour to form OH radicals, was a problem for some early measurements of OH by LIF, in which 282 nm excitation was used (Zeng et al., 1998). Use of 308 nm excitation, combined with high PRF – low pulse energy excitation, reduces the

ACPD

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.



contribution to returned [OH] from this source to less than 10³ molecule cm³ under conditions of the EUPHORE experiments ([O3], [H2O], laser fluence). Hydrocarbon photolysis by the excitation laser beam could also lead to artefact OH generation; however no significant levels of OH were detected ($<1 \times 10^6$ molecule cm³) at the start of each experiment, when the hydrocarbon species had been introduced to the chamber but prior to opening of the covers to admit sunlight (Fig. 2). Photolysis of products of the oxidation of each primary hydrocarbon could contribute to artefact OH generation; however considering the case of 1,3,5-TMB, the three principal observed products were methyl glyoxal, PAN and HCHO. If direct production of OH radicals with unit quantum yield following 308 nm photolysis of each of these species were possible, the

- maximum concentrations of OH radicals produced inside the FAGE cell would be ca. 2500, 75 and 1500 molecule cm^{-3} , respectively (calculated for the maximum concentration of each species observed, using the appropriate operating parameters for the EUPHORE LIF system). These values can be compared to a concentration of ca. 17 000 molecule cm⁻³ of OH within the FAGE cell which results from sampling ambient 15
- air containing $[OH] = 8 \times 10^6$ molecule cm⁻³ (typical of the levels found during the 1,3,5-TMB experiment). When the further requirements for any such OH to be generated in the correct rovibronic state, and to be both generated and excited within the same laser pulse are considered, the contribution of photolytic artefacts to the returned [OH] is clearly minimal.

20

25

Variation in the calibration of the LIF system between experiments could account for the discrepancies in the results for 1,3,5-TMB – calibration of the LIF system requires entry into the EUPHORE chamber, which must be purged of experimental gases prior to calibration, and of water vapour etc. afterwards. Therefore, it was not possible to perform calibration checks between every experiment during the EXACT campaigns. Calibrations performed at the start and end of the first exact campaign were within 6% of each other; similarly for the second campaign, 17 individual calibrations performed

on three different days at the start, middle and end of the campaign exhibited a standard deviation of 9%. It is therefore unlikely that variation in the instrument calibration 3,6029-6061,2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.



(arising for example from variations in laser linewidth due to changed oscillator alignment) can explain the large discrepancies obtained for 1,3,5-TMB and p-xylene. This conclusion is supported by the excellent agreement between the two toluene experiments, 1 and 3, performed prior and subsequent to the 1,3,5-TMB run, and by the consistency in the result from the two p-xylene runs, which were conducted 15 days apart.

No single reason can be identified for the disagreement between values of $[OH]_{LIF}$ and $[OH]_{HC}$ in the case of 1,3,5-TMB; uncertainty in the rate constant for reaction with OH can account for some, but not all of the discrepancy. In the case of p-xylene, agree-¹⁰ ment (within 1 s.d. uncertainty) is achieved for experiment 9, and nearly for experiment 6 (Fig. 3); as discussed above, k(OH+p-xylene) may be somewhat smaller than that used to obtain these values. The confidence interval in the values of *R* listed in Table 4 reflect only the uncertainty in k(OH+hydrocarbon), and those plotted in Fig. 3 show also the combined uncertainty in the calculated [OH] from calibration. The true ¹⁵ uncertainty in these values is larger, as no contribution from data scatter is included – for example, inspection of Fig. 2 indicates clearly that the value of *R* obtained from

experiment 7 will be less precise than that from experiment 1.

We discount the results from experiment 2 (1,3,5-TMB) from our final comparison between the LIF-measured and hydrocarbon-inferred OH, on the basis that the deviation in this case is much greater than indicated by the remaining studies, and is likely

- ²⁰ tion in this case is much greater than indicated by the remaining studies, and is likely to be due to some other systematic factor. Averaging results from the remaining 8 experiments gives a mean value for $[OH]_{LIF}/[OH]_{HC}$ of (1.15 ± 0.13) , where the range indicates combined (1 s.d.) uncertainty in the values of k(OH+hydrocarbon) and the LIF calibration methodology. This result thus indicates that OH concentrations retrieved
- ²⁵ from LIF systems calibrated using the water-photolysis ozone-actinometry calibration approach are accurate to within the stated calibration uncertainty (\pm 26%), but suggests a slight bias to overestimate the true ambient OH concentration. The possibility of counterbalancing errors in the various calibration factors (e.g. oxygen and water cross sections) is not precluded, so the same conclusion cannot necessarily be drawn

ACPD

3, 6029–6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page			
Abstract	Introduction		
Conclusions	References		
Tables	Figures		
•	•		
Back	Close		
Full Screen / Esc			
Print	Print Version		
Interactive Discussion			

for the analogous calibration approach in which photolysis of water vapour is quantified through measurement of the UV flux by a calibrated photodiode.

The results of this work indicate that OH concentrations measured by an LIF instrument calibrated using the water photolysis-ozone actinometry method are accurate to within the stated calibration uncertainty of ±26%, with a mean value of [OH]_{LIF}/[OH]_{hydrocarbon decay} of (1.15±0.13) obtained. Continuing development of calibration techniques, for example via the ozonolysis of alkenes (Hard et al., 2002), and further intercomparisons of ambient OH measurements performed using different approaches and calibration techniques, such as the comparison between LIF and DOAS techniques reported by Brauers et al. (1996), are essential to further our understanding of the accuracy and precision of the current generation of hydroxyl radical measurements.

Acknowledgements. Fundación CEAM is supported by Generalidad Valenciana and BAN-CAIXA. Financial support for this work was provided through the EU programme "Effects of the Oxidation of Aromatic Compounds in the Troposphere" (EXACT), Contract #EVK2-CT-1999-00053, and Ministerio de Ciencia y Tecnologia (REN2000-3277-CE/CLI, REN2001-4600-E/CLI).

References

Aschmutat, U., Hessling, M., Holland, F. and Hofzumahaus, A.: A tunable source of hydroxyl

- ²⁰ (OH) and hydroperoxy (HO₂) radicals: In the range between 10⁶ and 10⁹ cm⁻³, Physico-Chemical Behaviour of Atmospheric Pollutants, edited by Angeletti, G. and Restelli, C., Proc. EUR, 15 609, 811–816, 1994.
 - Atkinson, R.: Gas-phase Tropospheric Chemistry of Organic Compounds: A review, Atmos. Environ., 24A, 1, 1–41, 1990.
- Atkinson, R.: Gas Phase Tropospheric Chemistry of Organic Compounds, J. Phys. Chem. Ref. Data, Monograph No. 2, 1–216, 1994.

Atkinson, R., Baulch, D. L., Cox, R. A., Crowley, J. N., Hampson, R. F., Kerr, J. A., Rossi, M.

3, 6029–6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page		
Abstract	Introduction	
Conclusions	References	
Tables	Figures	
I	►I	
•	Þ	
Back	Close	
Full Screen / Esc		
Print Version		
Interactive Discussion		

6051

J., and Troe, J.: Summary of Evaluated Kinetic and Photochemical Data for Atmospheric Chemistry, http://www.iupac-kinetic.ch.cam.ac.uk, 2002.

- Bailey, A. E., Heard, D. E., Paul, P. H., and Pilling, M. J.: Collisional Quenching of OH ($A^2\Sigma^+$, $\nu'=0$) by N₂, O₂ and CO₂ between 204 and 294 K, Implications for atmospheric measure-
- 5 ments of OH by laser-induced fluorescence, J. Chem. Soc. Faraday Trans., 93, 16, 2915– 2920, 1997.
 - Bailey, A. E., Heard, D. E., Henderson, D. A., and Paul, P. H.: Collisional quenching of OH $(A^2\Sigma^+, \nu'=0)$ by H₂O between 211 and 294 K and the development of a unified model for quenching, Chem. Phys. Lett., 302, 132–138, 1999.
- ¹⁰ Becker, K. H.: EUPHORE: Final Report to the European Commission, Contract #EV5V-CT92-0059, Bergische Universität Wuppertal, Germany, 1996.
 - Becker, K. H.: In Situ Euphore Radical Measurement (EUPHORAM): Final Report to the European Commission, Contract #ENV4-CT95-0011, Bergische Universität Wuppertal, Germany, 1999.
- ¹⁵ Bloss, W. J., Gravestock, T. J., Heard, D. E., Ingham, T., Johnson, G. P., and Lee, J. D.: Application of a compact all-solid-state laser system to the in situ detection of atmospheric OH, HO₂, NO and IO by laser-induced fluorescence, J. Environ. Monit., 5, 21–28, 2003a.
 - Brauers, T., Aschmutat, U., Brandenburger, U., Dorn, H. P., Hausmann, M., Hessling, M., Hofzumahaus, A., Holland, F., Plass-Dulmer, C., Ehhalt, D. H.: Intercomparison of tropo-
- ²⁰ spheric OH radical measurements by multiple folded long-path laser absorption and laserinduced fluorescence, Geophys. Res. Lett., 23, 18, 2545–2548, 1996.
 - Cantrell, C. A., Zimmer, A., and Tyndall, G. S.: Absorption cross sections for water vapour from 183 to 193 nm, Geophys. Res. Lett., 24, 17, 2195–2198, 1997.

Calvert, J. G., Atkinson, R., Kerr, J. A., Madronich, S., Moortgat, G. K., Wallington, T. J., and

- ²⁵ Yarwood, G.: The Mechanisms of Atmospheric Oxidation of the Alkenes, OUP, New York, 2000.
 - Calvert, J. G., Atkinson, R., Becker, K. H., Kamens, R. M., Seinfeld, J. H., Wallington, T. J., and Yarwood, G.: The Mechanisms of Atmospheric Oxidation of Aromatic Hydrocarbons, OUP, New York, 2002.
- ³⁰ Chan, C. Y., Hard, T. M., Mehrabzadeh, A. A., George, L. A., and O'Brien, R. A.: Third-Generation FAGE Instrument for Tropospheric Hydroxyl Radical Measurement, J. Geophys. Res., 95, D11, 18569–18576, 1990.

Creasey, D. J., Halford-Maw, P. A., Heard, D. E., Pilling, M. J., and Whitaker, B. J.: Imple-

ACPD

3, 6029–6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page		
Abstract	Introduction	
Conclusions	References	
Tables	Figures	
•	•	
Back	Close	
Full Screen / Esc		
Drint V	laraian	
Print V	ersion	



mentation and initial deployment of a field instrument for the measurement of OH and HO_2 in the troposphere by laser-induced fluorescence, J. Chem. Soc., Faraday Trans., 93, 16, 2907–2913, 1997a.

Creasey, D. J., Heard, D. E., Pilling, M. J., Whitaker, B. J., Berzins, M., and Fairlie, R.: Visu-

- alisation of a supersonic free-jet expansion using laser-induced fluorescence spectroscopy: Application to the measurement of rate constants at ultralow temperatures, App. Phys. B, 65, 375–391, 1997b.
 - Creasey, D. J., Heard, D. E., and Lee, J. D.: Absorption cross-section measurements of water vapour and oxygen at 185 nm. Implications for the calibration of field instruments to measure OH, HO₂ and RO₂ radicals, Geophys. Res. Lett., 27, 11, 1651–1654, 2000.
- Derwent, R. G., Jenkin, M. E., and Saunders, S. M.: Photochemical ozone creation potentials for a large number of reactive hydrocarbons under European conditions, Atmos. Environ., 30, 181–199, 1996.

Etzkorn, T., Klotz, B., Sørensen, S., Patroescu, I. V., Barnes, I., Becker, K. H., and Platt, U.:

- Gas-phase absorption cross sections of 24 monocyclic aromatic hydrocarbons in the UV and IR spectral ranges, Atmos. Environ., 33, 525–540, 1999.
 - Guggenheim, E. A.: On the determination of the Velocity Constant of a Unimolecular Reaction, Philos. Mag., 2, 9, 538–543, 1926.

Hard, T. M., O'Brien, R. J., Chan, Y. C., and Mehrabzadeh, A. A.: Tropospheric Free Radical

²⁰ Determination by FAGE, Environ. Sci. Technol., 18, 768–777, 1984.

Hard, T. M., George, L. A., and O'Brien, R. J.: An Absolute Calibration for Gas-Phase Hydroxyl Measurements, Environ. Sci. Tech., 36, 1783–1790, 2002.

Heard, D. E. and Pilling, M. J.: Measurement of OH and HO₂ in the troposphere, Chemical Reviews, in press, 2003.

²⁵ Hofzumahaus, A., Aschmutat, U., Heßling, M., Holland, F., and Ehhalt, D. H.: The measurement of tropospheric OH radicals by laser-induced fluorescence spectroscopy during the POPCORN field campaign, Geophys. Res. Lett., 23, 18, 2541–2544, 1996.

Holland, F., Hessling, M., and Hofzumahaus, A.: In Situ Measurement of Tropospheric OH Radicals by Laser-Induced Fluorescence – A Description of the KFA Instrument, J. Atmos.

³⁰ Sci., 52, 19, 3393–3401, 1995.

10

Holland, F., Hofzumahaus, A., Schäfer, J., Kraus, A., and Pätz, H.: Measurements of OH and HO₂ radical concentrations and photolysis frequencies during BERLIOZ, J. Geophys. Res., 108, D4, 8246, doi:10.1029/2001JD001393, 2003.

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page		
Abstract	Introduction	
Conclusions	References	
Tables	Figures	
•	►	
Back	Close	
Full Screen / Esc		
Full Scre	en / Esc	
Full Scre	en / Esc	
Full Scre	en / Esc /ersion	

Kanaya, Y., Sadanaga, Y., Hirokawa, J., Kajii, Y., and Akimoto, H.: Development of a Ground-Based LIF Instrument for Measuring HO_x Radicals: Instrumentation and Calibrations, J. Atmos. Chem., 38, 1, 73–110, 2001.

Klotz, B., Sørensen, S., Barnes, I., Becker, K.H., Etzkorn, T., Volkamer, R., and Platt, U.: Atmospheric Oxidation of Toluene in a Large-Volume Outdoor Photoreactor: In Situ Determination

spheric Oxidation of Toluene in a Large-Volume Outdoor Photoreactor: In Situ Determination of Ring-Retaining Product Yields, J. Phys. Chem. A, 102, 10289–10299, 1998.

Lanzendorf, E. J., Hanisco, T. F., Donahue, N. M., and Wennberg, P. O.: Comment on "The measurement of tropospheric OH radicals by laser-induced fluorescence spectroscopy during the POPCORN field campaign" by Hofzumahaus et al. and "Intercomparisons of tropo-

- ¹⁰ spheric OH radical measurements by multiple folded long-path laser absorption and laser induced fluorescence" by Brauers et al., Geophys, Res. Lett., 24, 23, 3037–3038, 1997.
 - Lee, J. D.: Development and Deployment of the FAGE instrument for measurement of HO_x in the troposphere, PhD Thesis, University of Leeds, 2000.

Levy II, H.: Normal Atmosphere: Large Radical and Formaldehyde Concentrations Predicted, Science, 173, 141–143, 1971.

Ohta, T. and Ohyama, T.: A set of rate constants for the reactions of hydroxyl radicals with aromatic hydrocarbons, Bull. Chem. Soc. Jpn., 58, 3029–3030, 1985.

Pilling, M. J.: Effects of the Oxidation of Aromatic Compounds in the Troposphere (EXACT): Final Report to the European Commission, Contract #EVK2-CT-1999-00053, University of Leeds, UK, 2003.

Perry, R. A., Atkinson, R., and Pitts Jr., J. N.: Kinetics and mechanism of the gas phase reaction of OH radicals with aromatic hydrocarbons over the temperature range 296–473 K, J. Phys. Chem., 81, 296–304, 1977.

Ravishankara, A. R., Wagner, S., Fishcer, S., Smith, G., Schiff, R., Watson, R. T., Tesi, G.,

and Davis, D. D.: A kinetics study of the reactions of OH with several aromatic and olefinic compounds, Int. J. Chem. Kinet., 10, 783–804, 1978.

- Sander, S. P., Friedl, R. R., Golden, D. M., Kurylo, M. J., Huie, R. E., Orkin, V. L., Moortgat, G. K., Ravishankara, A. R., Kolb, C. E., Molina, M. J., and Finlayson-Pitts, B. J.: Chemical Kinetics and Photochemical Data for use in Atmospheric Studies, Evaluation #14, NASA-JPL
- ³⁰ Publication 02–25, Jet Propulsion Laboratory, Pasadena, CA 91109, 2003.

15

20

Siese, M., Becker, K. H., Brockmann, K. J., Geiger, H., Hofzumahaus, A., Holland, F., Mihelcic, D., and Wirtz, K.: Direct Measurement of OH Radicals from Ozonolysis of Selected Alkenes: A EUPHORE Simulation Chamber Study, Environ. Sci. Technol., 35, 4660–4667, 2001.

ACPD

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page			
Abstract Introduction			
Conclusions References			
Tables	Figures		
I< ►I			
< >			
Back	Close		
Full Scre	een / Esc		
Full Scre	een / Esc		
Full Scree	een / Esc /ersion		

Stevens, P. S., Mather, J. H., and Brune, W. H.: Measurement of tropospheric OH and HO₂ by laser-induced fluorescence at low pressure, J. Geophys. Res., 99, D2, 3543–3557, 1994.

ACPD

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page			
Abstract	Introduction		
Conclusions	References		
Tables	Figures		
I∢ ►I			
•	•		
■	► Close		
■ Back Full Scr	Close		
■ Back Full Scr	Close reen / Esc		
 Back Full Scr Print 	Close reen / Esc Version		

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Table 1. Contributions to overall uncertainty in the OH calibration.

Contributing factor	Fractional uncertainty (1 s.d.)
H ₂ O 184.9 nm cross section	0.03
O ₂ 184.9 nm cross section	0.11 ^{<i>a</i>}
Flow profile <i>P</i> -factor	0.05
Humidity dependence	0.15
Measurement of [H ₂ O]	0.02
Measurement of $[O_3]$	0.17

^{*a*} Combined statistical uncertainty in the measurement of $\sigma(O_2)$ for the particular lamp used (4%), and estimated accuracy of the cross-section measurement procedure (10%) from Siese et al. (2001) and Creasey et al. (2000).



3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page						
Abstract Introduction						
Conclusions References						
Tables Figures						
I∢ ►I						
▲ ►						
Back Close						
Full Screen / Esc						
Print Version						
Interactive Discussion						

© EGU 2003

Table 2. Conditions for the photo-oxidation experiments and importance of chemical loss relative to dilution.

Run ^a	Hydrocarbon species	Chamber Temp./K ^b	$k_{\text{Dilution}}/10^{-5}\mathrm{s}^{-1c}$	Percentag value ±1	ge chemical loss ^d s.d. uncertainty
1	Toluene	302.3	1.61	74.6	7.7
2	1,3,5-TMB ^e	300.0	1.35	87.8	19.2
3	Toluene	302.3	1.58	66.0	11.9
4	Ethene	303.8	1.64	78.7	5.7
5	o-Cresol	299.2	1.37	92.9	2.9
6	p-Xylene	308.9	1.97	79.2	6.4
7	Benzene	305.2	1.96	17.9	41.4
8	Benzene	307.1	1.99	42.0	9.2
9	p-Xylene	304.9	1.97	85.0	2.6

 a Chronological order in which experiments were performed, No.'s 1–5 during campaign 1, 6–9 during campaign 2.

^b Mean air temperature inside the chamber during the sunlit period.

^c Derived from SF₆ decay.

^{*d*} Fraction of the total hydrocarbon removal which arose from chemical reaction (balance from dilution)

^e Trimethylbenzene.

3, 6029-6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

Title Page			
Abstract Introduction			
Conclusions References			
Tables	Figures		
•			
Back Close			
Full Screen / Esc			
Print Version			
Interactive Discussion			

© EGU 2003

 Table 3. Breakdown of chemical loss for each hydrocarbon species.

,

Run	Hydrocarbon	Peak ozone/ppb ^b	Percentage of hydrocarbon loss by reaction with			
	species		OH	O ₃	NO_3	O(³ P)
1	Toluene	416	99.96	0.02	0.01	0
2	1,3,5-TMB	396	99.95	0.02	0.02	0.01
3	Toluene	255	99.97	0.02	0.02	0
4	Ethene	446	69.28	30.72	0	0
5	o-Cresol	107	12.04	0.05	87.91	0
6	p-Xylene	319	99.91	0.05	0.04	0
7	Benzene	177	99.92	0.05	0.03	0
8	Benzene	222	99.95	0.03	0.02	0
9	p-Xylene	362	99.92	0.05	0.03	0
а	Ethene	446	83.55	16.45	0	0
b	o-Cresol	107	98.30	0.04	1.67	0

Notes: Rate constants for ethene taken from Atkinson et al. (2002); for all other species from Calvert et al. (2002).

^a Correcting for the time-dependent growth in $[O_3]$ rather than using the peak value.

^b Correcting [NO₃] for effect of reaction with cresol and other oxidation products via MCM simulation; see text.

3, 6029–6061, 2003

Validation of the calibration of a OH LIF instrument

W. J. Bloss et al.

ion				
Conclusions References				
S				
• •				
Full Screen / Esc				
Print Version				
Interactive Discussion				

© EGU 2003

Run	Hydrocarbon	k(OH+hydrocarbon)/	H+hydrocarbon)/ $R = \Sigma[OH]_L$	
	species	$10^{-12} \mathrm{molecule}^{-1} \mathrm{cm}^3 \mathrm{s}^{-1a}$	value ^b	± uncertainty ^c
1	Toluene	5.51	0.96	0.19
2	1,3,5-TMB	56.7	3.02	0.60
3	Toluene	5.51	1.06	0.21
4	Ethene	8.04 ^{<i>d</i>}	0.87	0.21
5 ^a	o-Cresol (FTIR)	40.7	0.83	0.25
5^b	o-Cresol (HPLC)	40.7	0.93	0.28
6	p-Xylene	14.3	1.69	0.42
7	Benzene	1.24	1.29	0.26
8	Benzene	1.24	1.04	0.21
9	p-Xylene	14.3	1.45	0.36

Table 4. Literature values for k(OH+HC) and ratio of LIF-measured to hydrocarbon-inferred

^a Recommended values from Calvert et al. (2002).

^b R defined as in Eq. (vi).

OH concentrations.

^c Uncertainty quoted here derived from uncertainty in k(OH+Hydrocarbon) only.

^d Mean of values from Atkinson et al. (2002) and Sander et al. (2003).





Fig. 1. Effect of lengthening the analysis period from successive hydrocarbon measurement points (1-point, top panel) to every fifth hydrocarbon measurement point (5-point, lower panel). Scatter and noise are greatly reduced in the latter instance. Data for benzene, experiment 8. Key: Benzene mixing ratio, blue diamonds; individual [OH] from LIF, small red circles; [OH] inferred from benzene decay; blue circles; average LIF [OH] over the corresponding interval between benzene measurements, black/red squares.





Title PageAbstractIntroductionConclusionsReferencesTablesFiguresI<</td>►II►IBackCloseFull Screen / EscPrint VersionInteractive Discussion

© EGU 2003

Fig. 2. Data from each experiment showing comparison between measured and inferred OH concentrations. Key: Individual [OH] from the LIF measurements, small red circles; [OH] from LIF averaged over interval between hydrocarbon measurements used for analysis, black/red squares; [OH] inferred from hydrocarbon decay, blue circles; hydrocarbon mixing ratio, blue diamonds (right hand abscissa; vmr = volume mixing ratio).

3, 6029-6061, 2003



Fig. 3. Ratio (R) of OH concentrations measured by the LIF system and those obtained from hydrocarbon decay data. Outer (light blue) confidence interval indicates combined uncertainty in FAGE calibration (26%) and k(OH+Hydrocarbon) (Table 4); inner confidence interval reflects uncertainty in k(OH+Hydrocarbon) only.

Full Screen / Esc

Figures

►

Close