



**HAL**  
open science

# On the stabilizing and destabilizing effects of damping in a non-conservative pin-disc system

Jean-Jacques Sinou, Louis Jézéquel

► **To cite this version:**

Jean-Jacques Sinou, Louis Jézéquel. On the stabilizing and destabilizing effects of damping in a non-conservative pin-disc system. *Acta Mechanica*, 2008, 199, pp.43-52. 10.1007/s00707-007-0565-2 . hal-00322892

**HAL Id: hal-00322892**

**<https://hal.science/hal-00322892>**

Submitted on 1 Oct 2018

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# On the stabilizing and destabilizing effects of damping in a non-conservative pin-disc system

J.-J. Sinou, L. Jezequel

Laboratoire de Tribologie et Dynamique des Systèmes, Equipe Dynamique des Structures et des Systèmes, Ecole Centrale de Lyon, Ecully, France

**Summary.** Friction-induced vibration due to mode coupling is a major concern in a wide variety of mechanical systems. Though there are numerous papers on both linear and non-linear stability analyses of dynamical systems with friction-induced vibrations, the effects of damping on the evolution of the stable–unstable regions is not yet fully understood. The purpose of this work is to study a pin-disc model describing a typical friction-induced vibration due to a geometric constraint in order to illustrate the effects of damping on linear stability analyses. The results not only illustrate the influence of damping for determining the stable and unstable zones, but they also indicate that the “most efficient damping factor of the coupling modes” is an important factor to be taken into account. The physical mechanism causing this change in instability as a consequence of the damping factor is also suggested to help avoid bad design.

## 1 Introduction

Recently, the effect of damping on the stability of distributed non-conservative systems with friction has been investigated by some researchers [1], [2] by considering theoretical systems with 2 *dof*. For example, Hoffmann and Gaul [1] studied the effects of damping on mode coupling or coalescence between two modes in friction induced oscillations. They demonstrated that linear viscous structural damping changes the mode coupling and that an imperfect merging of modes may be observed. They developed a feedback-loop formalism in order to allow a more detailed understanding of the underlying mechanical processes. Nevertheless, they concluded that viscous instability in the field of friction-induced oscillations is in itself a surprising phenomenon. Moreover, Sinou and Jézéquel [2] indicated that neglecting damping in a stability analysis or adding damping on only one part of the system may lead to a misunderstanding of the phenomenon referred to as mode coupling or coalescence between two modes. This effect of damping, called the destabilization paradox, was previously described and theoretically explained by Kirillov and Seyranian [3], [4].

---

Correspondence: Jean-Jacques Sinou, Laboratoire de Tribologie et Dynamique des Systèmes UMR CNRS 5513, Equipe Dynamique des Structures et des Systèmes, Ecole Centrale de Lyon, Bâtiment E6, 36 Avenue Guy de Collongue, 69134 Ecully, France  
e-mail: jean-jacques.sinou@ec-lyon.fr

Despite these previous works, problems generated by the destabilization paradox have not yet been considered for physical–mechanical systems subjected to friction-induced vibration such as pin-disc systems. However, friction-induced oscillations due to mode coupling (i.e. coalescence between modes) occur in a wide variety of mechanical systems and are known to lead to very annoying phenomena such as brake squeal [5]–[11].

Given this fact, we will seek to describe the effects of damping on a pin-disc system in order to avoid bad design in mechanical systems subject to flutter instability. The main objective of this paper will be to clarify the influence of structural damping for the well-known pin-disc system because this system includes all the essential features for generating friction-induced vibrations due to geometric constraint and for showing the role of damping. First, the mechanical system will be presented and the associated equations of motion will be described. Second, the effects of damping on the size of the stable and unstable regions will be investigated. It will be shown that the “most efficient damping factor of the coupled modes” is one of the most important parameters to be taken into account for pin disc systems and mechanical systems subject to flutter instability.

## 2 Description of the mechanical model

In this study, a dynamic model of a beam rubbing against a rotating disc with a constant friction coefficient is considered, as indicated in Fig. 1. In this case, flutter instability is governed by modal interaction between the cantilever and disc bending modes and variations of normal and tangential contact forces, due to the configuration of the system based on “geometrically-induced vibrations” (sprag-slip mechanism [10], [12]). This mechanical system [13] is composed of a disc, rubbed by a flexible beam, inclined at angle  $\theta$  in relation to the plane of the disc. As illustrated in Fig. 1, this dynamic system is composed of only three vibration modes: the flexure of the disc (defined by the physical parameters  $(m_3, c_3, k_3)$  and the associated displacement  $X_3$ ), the stretching–compressing of the beam (defined by the physical parameters  $(m_1, c_1, k_1)$  and the associated displacement  $X_1$ ), and the flexure of the beam (defined by the physical parameters  $(m_2, c_2, k_2)$  and the associated displacement  $X_2$ ). The governing equations of motion of this system may be written as follows:




Fig. 1. Mechanical model of a beam rubbing against a disc

$$\begin{aligned}
m_1\ddot{X}_1 + c_1\dot{X}_1 + k_1X_1 &= N \sin \theta + T \cos \theta, \\
m_2\ddot{X}_2 + c_2\dot{X}_2 + k_2X_2 &= N \cos \theta - T \sin \theta, \\
m_3\ddot{X}_3 + c_3\dot{X}_3 + k_3X_3 &= -N.
\end{aligned} \tag{1}$$

Assuming constant pin and disc contact, the following geometric constraint may be obtained:  $X_3 = X_1 \sin \theta + X_2 \cos \theta$ . Eliminating  $X_3$  and  $N$  and assuming Coulomb's law  $T = \mu N$ , the equations of motion (1) may be reduced to the form

$$\mathbf{M}\ddot{\mathbf{X}} + \mathbf{C}\dot{\mathbf{X}} + \mathbf{K}\mathbf{X} = \mathbf{0} \tag{2}$$

with  $\mathbf{X} = (X_1 \ X_2)^T$ .  $\ddot{\mathbf{X}}$ ,  $\dot{\mathbf{X}}$  and  $\mathbf{X}$  are the acceleration, velocity, and displacement response two-dimensional vectors of the degrees-of-freedom, respectively. The mass matrix  $\mathbf{M}$ , the damping matrix  $\mathbf{C}$ , the stiffness matrix  $\mathbf{K}$  are given by

$$\mathbf{M} = \begin{bmatrix} m_1 + m_3 \sin \theta \cdot f(\theta, \mu) & m_3 \cos \theta \cdot f(\theta, \mu) \\ m_3 \sin \theta \cdot g(\theta, \mu) & m_2 + m_3 \cos \theta \cdot g(\theta, \mu) \end{bmatrix}, \tag{3}$$

$$\mathbf{C} = \begin{bmatrix} c_1 + c_3 \sin \theta \cdot f(\theta, \mu) & c_3 \cos \theta \cdot f(\theta, \mu) \\ c_3 \sin \theta \cdot g(\theta, \mu) & c_2 + c_3 \cos \theta \cdot g(\theta, \mu) \end{bmatrix}, \tag{4}$$

$$\mathbf{K} = \begin{bmatrix} k_1 + k_3 \sin \theta \cdot f(\theta, \mu) & k_3 \cos \theta \cdot f(\theta, \mu) \\ k_3 \sin \theta \cdot g(\theta, \mu) & k_2 + k_3 \cos \theta \cdot g(\theta, \mu) \end{bmatrix} \tag{5}$$

with  $f(\theta, \mu) = \sin \theta + \mu \cos \theta$  and  $g(\theta, \mu) = \cos \theta - \mu \sin \theta$ . The base parameters are [13]: pin masses  $m_1 = 0.177$  kg and  $m_2 = 0.088$  kg; disc mass  $m_3 = 2$  kg; natural frequency of the stretching–compressing mode of the beam  $\omega_1 = 2\pi \times 8820$  rad s<sup>-1</sup>, natural frequency of the first flexible mode of the beam  $\omega_2 = 2 \times 658$  rad s<sup>-1</sup>, natural frequency of the first flexible mode of the disc  $\omega_3 = 2\pi \times 440$  rad s<sup>-1</sup> (i.e.  $k_i = m_i \omega_i^2$ ). The damping ratios are chosen to be the same in the two perpendicular directions of the beam  $\zeta_1 = 0.01$  (i.e.  $c_i = 2\zeta_1 \sqrt{m_i k_i}$  for  $i = 1, 2$ ); and  $\zeta_2 = 0.01$  for the disc (i.e.  $c_3 = 2\zeta_2 \sqrt{m_3 k_3}$ ); angle between the disc and the beam  $\theta = 1.4$  rad.

### 3 Stability analysis and effect of damping on unstable regions

To investigate the effects of physical parameters on the stability of the equilibrium point that is equal to zero for the pin-disc system, the eigenvalues  $\lambda$  of the system can be found by solving the standard equation

$$\det(\lambda^2 \mathbf{M} + \lambda \mathbf{C} + \mathbf{K}) = 0. \tag{6}$$

If we denote one or more eigenvalues  $\lambda$  having a positive real part, the mechanical system is unstable and the associated imaginary part of this eigenvalue defines the frequency of the unstable mode. Moreover, it may be noted that numerical methods for bifurcation analysis [14] and bifurcation software available for such systems [15] should be used for the interactive bifurcation analysis of dynamical systems.

Figures 2, 4 and 5 illustrate some general, well-known information by varying parameters; an increase of the friction coefficient  $\mu$  may induce instability and increases the unstable regions; within a certain range of the angle  $\theta$  of orientation between the beam and the disc, we observe that flutter instability occurs. Increasing the friction coefficient increases this range of the angle  $\theta$ .


Table 1 indicates the value of the Hopf bifurcation point, defined by  $\text{Re}(\lambda(\mu))|_{\mu=\mu_0} = 0$  and  $\frac{d}{d\mu}(\text{Re}(\lambda(\mu)))|_{\mu=\mu_0} \neq 0$ , and the value of the associated unstable frequency for various damping ratios

**Table 1.** Determination of the Hopf bifurcation point and the unstable associated frequency versus the friction coefficient

Damping ratio coefficients		Hopf bifurcation point $\mu_0$	Unstable frequency (Hz)
$\zeta_1$	$\zeta_2$		
0	0	0.474	1,197
0.01	0.01	0.468	1,491
0.001	0.01	0.44	1,974
0.01	0.001	0.407	688

$\zeta_1$  and  $\zeta_2$ . It appears that damping may increase the unstable zone, and if we use only the undamped mechanical system for determining the stable and unstable regions, the information about the stability of the equilibrium point of the mechanical system may be erroneous.

To further understanding the effects of damping, Fig. 2 shows the stable and unstable regions for various damping ratios  $\zeta_1$  and  $\zeta_2$  and various friction coefficients while keeping the angle  $\theta$  at its




**Fig. 2.** Instability region (with regard to variables  $\zeta_1$ ,  $\zeta_2$  and  $\mu$ , with  $\theta = 1.2$  rad)

base value. It clearly appears that increasing damping in both the disc and the beam have beneficial effect and increase the stable region. Moreover, Fig. 2 suggests that adding damping in only the beam or the disc may induce flutter instability.


Figure 3 illustrates the influence of the factor  $\zeta_1/\zeta_2$  for various values of the friction coefficient  $\mu$  and the angle  $\theta$ . Considering only these results, the varying effects of  $\zeta_1/\zeta_2$  show that the predictions of stable and unstable regions are complex; increasing or decreasing  $\zeta_1/\zeta_2$  may increase the unstable region. However, it may be observed that the smallest unstable region is obtained for the ratio damping  $\zeta_1/\zeta_2$  near 1.5.

To better assess the influence of the damping factor  $\zeta_1/\zeta_2$ , Fig. 4 shows the effects of varying  $\zeta_1/\zeta_2$  and friction coefficient  $\mu$  while keeping the angle  $\theta$  at its base value. Figure 5 then illustrates the effects of varying  $\zeta_1/\zeta_2$  and angle  $\theta$  while keeping the friction coefficient  $\mu$  at its base value. The general observations from these parametric studies are:

- for all values of  $\zeta_1/\zeta_2$ , we note the existence of a critical value of the friction coefficient  $\mu$  below which the system becomes unconditionally stable,



**Fig. 3.** Instability region (with regard to variables  $\mu$ ,  $\theta$  and  $\zeta_1/\zeta_2$ , with  $\zeta_1 = 0.01$ )




**Fig. 4.** Instability region (with regard to variables  $\mu$ ,  $\zeta_1/\zeta_2$  and  $\theta$ , with  $\zeta_1 = 0.01$ )

- for all the values of  $\zeta_1/\zeta_2$ , within a certain range of the angle  $\theta$ , the system is unstable,
- increasing or decreasing only the damping ratio  $\zeta_1$  or  $\zeta_2$  may increase the unstable region.

These results indicate an additional significant fact: there exists a value of  $\zeta_1/\zeta_2$  for which the smallest unstable region is observed, regardless of the values of the friction coefficient  $\mu$  and the angle  $\theta$ . This value is estimated near  $\zeta_1/\zeta_2 = 1.5$ . As explained previously, Fig. 3 also describes values of  $\zeta_1/\zeta_2$  near 1.5 for the largest stable region. Throughout various computational simulations, it has been observed that the value of the most efficient damping factor  $\zeta_1/\zeta_2$  appears to be the same for various values of  $\zeta_1$  or  $\zeta_2$ .

Finally, we have shown the importance of the damping ratio in order to predict the stable and unstable regions. The effects of damping appear to be a key factor for flutter instability. These results not only indicate that increasing or decreasing damping of either the disc or the beam alone may have dangerous effects on the stability of the equilibrium point of the pin-disc system, but also show




**Fig. 5.** Instability region (with regard to variables  $\theta$ ,  $\zeta_1/\zeta_2$  and  $\mu$ , with  $\zeta_1 = 0.01$ )

the important fact that the system is more stable when a particular value of the damping factor  $\zeta_1/\zeta_2$  is used ( $\zeta_1/\zeta_2 \approx 1.5$  for this mechanical model).

In order to identify the physical mechanics, which are causing instability as a consequence of the damping ratio  $\zeta_1/\zeta_2$  in the study above, we recall that the effect of damping depends on whether energy dissipation occurs in the different parts of the mechanical system. This is a very well-known phenomenon observed in the field of rotor-dynamics where the non-rotating damping is always stabilizing, while the damping associated with the rotating parts has a destabilizing effect [16]. In this study, the introduction of unequal damping coefficients for each part of the mechanical system changes the merging motion for the mechanical system, as illustrated in Fig. 6. We recall that flutter instability is composed of two modes of which only one is unstable. By adding unequal damping, the lesser-damped mode defines the potentially unstable mode and the other mode corresponds to the stable one. Therefore, by introducing various damping ratios, the merging scenario and the unstable mode may change, as indicated in Fig. 6 where the





**Fig. 6.** Evolution of the stable and unstable modes versus the damping ratio  $\zeta_1/\zeta_2$

merging phenomenon is observed for  $\zeta_1/\zeta_2$  near 1.25 and 1.5. Effectively, if the damping ratio  $\zeta_1/\zeta_2$  is lower than 1.5, the unstable mode is the mode that has the higher frequency. If the damping ratio  $\zeta_1/\zeta_2$  is bigger than 1.5, the unstable mode is the mode that has the lower frequency.

Moreover, the results that have been previously shown in Fig. 2 are due to this phenomenon. When the damping factor  $\zeta_1$  is much weaker than the damping factor  $\zeta_2$ , the stretching–compressing of the beam [defined by the physical parameters  $(m_1, c_1, k_1)$ ] corresponds to the unstable mode whereas if the damping factor  $\zeta_2$  is much lower than the damping factor  $\zeta_1$ , the unstable mode becomes the flexure of the beam [defined by the physical parameters  $(m_2, c_2, k_2)$ ]. Moreover, Fig. 2 indicates that the system is always stable if the damping ratio  $\zeta_1/\zeta_2$  is approximately 1.5. It may be noted that this optimal value of the damping ratio  $\zeta_1/\zeta_2 = 1.5$  corresponds physically to the case of adding equal structural damping (i.e.  $c_1 = c_2$  with  $c_i = 2\zeta_1\sqrt{m_i k_i}$  for  $i = 1, 2$ ). This last

observation is also shown in Figs. 3, 4 and 5 where the largest stable area is obtained approximately for  $\zeta_1/\zeta_2 = 1.5$ .

Physically speaking, when the damping ratio  $\zeta_1/\zeta_2$  reaches the value 1.5, the unstable mode becomes stable (and the stable mode becomes unstable). So before the damping ratio  $\zeta_1/\zeta_2$  exceeds a certain value (approximately  $\zeta_1/\zeta_2 = 1.5$ ), adding damping has the effect of delaying the energy source driving instability (i.e. damping is added on the unstable mode). After the damping ratio  $\zeta_1/\zeta_2$  has exceeded this optimal value, the system becomes more unstable again (i.e. the unstable area grows again). This is only due to the fact that the stable and unstable modes are reversed. Now, damping is added to the stable mode and the system becomes comparable to a less constrained system (i.e. damping gives the mechanical system additional freedom to extract the energy source driving instability).

## 4 Conclusion

A dynamic model describing elementary mechanisms of friction-induced vibrations due to a geometric constraint is used to investigate the effects of damping on flutter instability. This study illustrates that damping is one of the most important parameters for friction-induced vibrations. Moreover, neglecting damping in a stability analysis may result in worse design and a misunderstanding of flutter instability in a mechanical system. Therefore, if too much damping is added to only one part of the mechanical system, instability may occur. Throughout the computational simulations, it has been found that there exists a damping factor  $\zeta_1/\zeta_2$  which allows us to obtain the largest stable region with regard to the effects of damping.

## References

- [1] Hoffmann, N., Gaul, L.: Effects of damping on mode-coupling instability in friction induced oscillations. *Z. Angew. Math. Mech. (ZAMM)* **83**, 524–534 (2003)
- [2] Sinou, J.-J., Jézéquel, L.: Mode coupling instability in friction induced vibrations and its dependency on system parameters including damping. *J. Eur. Mech. A/Solids* **26**, 106–122 (2007)
- [3] Kirillov, O.N.: Destabilization paradox. *Dokl. Phys.* **49**, 239–245 (2004)
- [4] Kirillov, O.N., Seyranian, A.O.: The effect of small internal and external damping on the stability of distributed non-conservative systems. *J. Appl. Math. Mech.* **69**, 529–552 (2005)
- [5] Crolla, D.A., Lang, A.M.: Brake noise and vibration – state of art. In: *Proc. 17th Leeds-Lyon Symposium on Tribology*, vol. 18, pp. 165–174 (1991)
- [6] North, M.: A mechanism of disk brake squeal. In: *14th FISITA Congress*, paper 1/9 (1972)
- [7] Ibrahim, R.A.: Friction-induced vibration, chatter, squeal and chaos: part II – dynamics and modeling. *ASME Appl. Mech. Rev.* **47**, 227–253 (1994)
- [8] Jarvis, R.P., Mills, B.: Vibrations induced by dry friction. *Proc. Inst. Mech. Engng.* **178**, 847–866 (1963/1964)
- [9] Earles, S.W.E., Chambers, P.W.: Disc brake squeal noise generation: predicting its dependency on system parameters including damping. *Int. J. Veh. Des.* **8**, 538–552 (1987)
- [10] Sinou, J.-J., Thouverez, F., Jézéquel, L.: Analysis of friction and instability by the center manifold theory for a non-linear sprag-slip model. *J. Sound Vib.* **265**, 527–559 (2003)
- [11] Sinou, J.-J., Thouverez, F., Jézéquel, L.: Stability and non-linear analysis of a complex rotor/stator contact. *J. Sound Vib.* **278**, 1095–1129 (2004)
- [12] Spurr, R.T.: A theory of brake squeal. *Proc. Auto. Div. Inst. Mech. Engng.* **1**, 33–40 (1961/1962)
- [13] Chambrette, P., Jézéquel, L.: Stability of a beam rubbed against a rotating disc. *Eur. J. Mech. A/Solids* **11**, 107–138 (1992)
- [14] Kuznetsov, Y.A.: *Elements of applied bifurcation theory*. Applied Mathematical Sciences. Springer, New York (2004)

- [15] Kuznetsov, Y.A., Govaerts, W., Doedel, E.J., Dhooge, A.: Numerical periodic normalization for codim 1 bifurcations of limit cycles. *SIAM J. Numer. Anal.* **43**, 1407–1435 (2005)
- [16] Childs, D.: *Turbomachinery rotor dynamics: phenomena, modeling, and analysis*. Wiley, London (1993)