



**HAL**  
open science

## Computer Graphics & Geometric Modeling

Paul Zsombor-Murray, Paul O'Leary

► **To cite this version:**

Paul Zsombor-Murray, Paul O'Leary. Computer Graphics & Geometric Modeling. 2006. hal-00365582

**HAL Id: hal-00365582**

**<https://hal.science/hal-00365582>**

Preprint submitted on 5 Mar 2009

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# CRN 148 MECH 576

## Computer Graphics & Geometric Modeling

October 24, 2006

### The Inertia Matrix in Least-Squares Linear Fitting

**ABSTRACT** Least squares fitting of point sets to lines, planes, curves and surfaces is carried out using eigenvalues and eigenvectors to find the major principal moment of inertia axis of a point set taken as representing the mass distribution of a rigid body. This engineering geometric approach produces identical results when compared to methods of conventional minimization using partial derivatives with respect to linear equation coefficients. Extending the approach to the fitting of conics and quadrics achieves great computational advantage over conventional least-squares optimization of *Euclidean*, as opposed to *algebraic* distance. The results, though imperfect, provide a starting point for iterations that will converge rapidly. Often, if enough points are given and these do not deviate wildly from the fit shape type selected, the result is satisfactory without resorting to further improvement.

**Keywords:** Fitting, Curves, Surfaces, Linear, Algebra, Inertia, Moment, Grassmann, Geometry

## 1 INTRODUCTION

The importance and utility of extracting underlying simple functional relations and geometric shape features from experimental data, acquired either as images or numbers, are evident. So it is deemed unnecessary to give examples and reasons in this regard. Rather, fitting a line to three given planar points by means of first partial derivatives of the sum of points' squared distances to a line  $y = ax + b$ , where  $a$  and  $b$  are unknown, will be compared to the novel method exposed herein where the moments and products of inertia of the points about Cartesian axes lead to principal moment of inertia axes, in the plane, via the eigenvalues and eigenvectors of the inertia matrix. The line of best fit will be seen to lie on the centroid of the point triangle and normal to the eigenvector associated with the larger eigenvalue of the planar inertia matrix. This latter concept will then be applied to fitting a plane to spatial points and finally to fitting a conic, using the inertia notion in the context of a five dimensional Euclidean point space of quadratic forms. A special conic, a circle fit to four points, is used to illustrate a preliminary result and to point out the essential shortcoming of our pseudo-linear approach. Although familiarity with elementary calculus, linear algebra and mechanics is assumed, [1], [2] and [3], respectively, provide all the relevant background necessary.

## 2 A LINE TO THREE POINTS

The proposed inertia matrix method, elaborated upon in Section 4, will now be introduced using the numerical example in Fig. 1 with points

$${}_1P(1, 2), {}_2P(3, 4), {}_3P(5, 3)$$

The first moment is calculated to yield  $G$  the centroid on the fit line.

$$[(1 + 3 + 5)/3, (2 + 4 + 3)/3] \rightarrow G(3, 3)$$

The inertia matrix is referred to this origin so

$${}_1P'(-2, -1), {}_2P'(0, 1), {}_3P'(2, 0)$$

replaces  ${}_iP$  above. Then the second moments and product are obtained as

$$I_{xx} = (-1)^2 + 1^2 + 0^2 = 2, \quad I_{yy} = (-2)^2 + 0^2 + 2^2 = 8$$

$$I_{xy} = (-2)(-1) + 0(1) + 2(0) = 2$$

Eigenvalues are found as follows.

$$\begin{bmatrix} I_{xx} - \lambda & -I_{xy} \\ -I_{xy} & I_{yy} - \lambda \end{bmatrix} \begin{bmatrix} e_x \\ e_y \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \end{bmatrix} \quad (1)$$

$$\rightarrow \begin{vmatrix} 2 - \lambda & -2 \\ -2 & 8 - \lambda \end{vmatrix} = 0 \rightarrow \lambda^2 - 10\lambda + 12 = 0$$

$$\lambda = 5 \pm \sqrt{13}$$

Then the eigenvector  $\mathbf{e}$  associated with the *greater* eigenvalue is given by *either* one of Eq. 1. *E.g.*, this eigenvector, *normal* to the sought line on  $G$ , has a slope of  $e_y/e_x$ , *i.e.*, given by

$$[2 - (5 + \sqrt{13})]e_x - 2e_y = 0$$

This line on  $G$  represents the axis *in the plane* about which the moment of inertia of the three points is greatest. The line on  $G$  parallel to the other eigenvector is the axis of *minimum inertia*. One must not confuse these axes with  $I_{zz}$ , encountered in elementary planar mechanics, which is mutually orthogonal to them. The inertia matrix approach clearly reveals the underlying geometric structure of this simple fitting problem. Now consider a conventional alternative. Examining the upper diagram in Fig. 1 one may easily formulate the sum of the three squared normal distances  $\Delta n_i$  in terms of line coefficients  $a$  and  $b$ . By induction and taking first partial derivatives with respect to  $a$  and  $b$  one quickly arrives at a quadratic in  $a$  and a linear equation relating  $b = b(a)$ .

$$a^2 + \frac{[\sum_{ik}(x_i^2 - x_k^2)] - [\sum_{ik}(y_i^2 - y_k^2)]}{\sum_{ik}[(x_i - x_k)(y_i - y_k)]} a - 1 = 0 \quad (2)$$

$$nb = \sum_i y_i - \left(\sum_i x_i\right)a \quad (3)$$

Note that  $n$  is the number of points and that all possible differences and differences of squares must be taken in the sums. Two solutions for  $a$ , the slope of the fitted line, appear. One is the actual slope the other is its normal. Eq. 3 provides the corresponding values of  $b$ . The lines intersect on  $G$ , the centroid of the given points. There is no way *a-priori* to tell which line is which . . . unless one is prepared to examine second derivatives; a procedure that becomes quite inconvenient in problems of higher dimension.




Figure 1: Three Point Line Fit

### 3 A PLANE TO SIX POINTS

This time an example where six given random points will be fit to a plane is presented and the singular matrix appears in Eq. 4.

$$\begin{bmatrix} I_{xx} - \lambda & -I_{xy} & -I_{xz} \\ -I_{xy} & I_{yy} - \lambda & -I_{yz} \\ -I_{xz} & -I_{yz} & I_{zz} - \lambda \end{bmatrix} \begin{bmatrix} e_x \\ e_y \\ e_z \end{bmatrix} = \begin{bmatrix} 0 \\ 0 \\ 0 \end{bmatrix} \quad (4)$$

The six given points  ${}_iP(p_{x,i} p_{y,i} p_z)$  appear below.

$$\begin{aligned} &{}_1P(4, 3, 2), \quad {}_2P(7, 1, 4), \quad {}_3P(2, 8, 1), \\ &{}_4P(9, 6, 7), \quad {}_5P(1, 4, 6), \quad {}_6P(12, -3, -5) \end{aligned}$$

The homogeneous coordinates of the centroid are  $G\{g_0 : g_1 : g_2 : g_3\} \equiv \{6 : 35 : 19 : 15\}$ . To obtain the elements of the inertia matrix  ${}_iP$  are first multiplied by 6 and  $g_1, g_2, g_3$  are subtracted from  ${}_iP$  to produce

$$\begin{aligned} &{}_1P'(-11, -1, -3), \quad {}_2P'(7, -13, 9), \quad {}_3P'(-23, 29, -9), \\ &{}_4P'(19, 17, 27), \quad {}_5P'(-29, 5, 21), \quad {}_6P'(37, -37, -45) \end{aligned}$$

Notice that all six of the following sums of products contain the common divisor 6. Inertia matrix element magnitude is irrelevant because we seek only the *direction* of eigenvector  $\mathbf{e}$  associated with greatest eigenvalue  $\lambda$ .

$$\begin{aligned}
I_{xx} &= \{[(-1)^2 + (-3)^2] + [(-13)^2 + 9^2] \\
&+ [29^2 + (-9)^2] + [17^2 + 27^2] + [5^2 + 21^2] \\
&+ [(-37)^2 + (-45)^2]\}/6 = 1010 \\
I_{yy} &= \{[(-3)^2 + (-11)^2] + [9^2 + 7^2] \\
&+ [(-9)^2 + (-23)^2] + [27^2 + 19^2] \\
&+ [21 + (-29)^2] + [(-45)^2 + 37^2]\}/6 = 1106 \\
I_{zz} &= \{[(-11)^2 + (-1)^2] + [7^2 + (-13)^2] \\
&+ [(-23)^2 + 29^2] + [19^2 + 17^2] + [(-29)^2 + 5^2] \\
&+ [37^2 + (-37)^2]\}/6 = 994 \\
I_{xy} &= \{[(-11)(-1)] + [(7)(-13)] + [(-23)(9)] \\
&+ [(19)(17)] + [(-29)(5)] + [(37)(-37)]\}/6 = 323 \\
I_{xz} &= \{[(-3)(-11)] + [(9)(7)] + [(-9)(23)] \\
&+ [(27)(19)] + [(21)(-29)] + [(-45)(37)]\}/6 = 243 \\
I_{yz} &= \{[(-1)(-3)] + [(-13)(9)] + [(29)(-9)] \\
&+ [(17)(27)] + [(5)(21)] + [(-37)(-45)]\}/6 = -309
\end{aligned}$$

The cubic characteristic equation becomes

$$\lambda^3 - 3110\lambda^2 + 2961505\lambda - 796404408 = 0$$

which has three real roots, ignoring small imaginary residues returned by numerical solution.

$$\lambda = 453.1092563, \quad 1244.042205, \quad 1412.84854$$

Using the third, greatest one in the expansion of Eq. 4 yields a set of three linearly dependent equations in the elements of  $\mathbf{e}$ , the associated eigenvector.

$$\begin{aligned}
(1010 - 1412.84854)e_x + 323e_y + 243e_z &= 0 \\
323e_x + (1106 - 1412.84854)e_y - 309e_z &= 0 \\
243e_x - 309e_y + (994 - 1412.84854)e_z &= 0
\end{aligned}$$

Solving, say, the first two homogeneously produces three direction numbers normal to the desired plane.

$$e_x = -25242.80478, \quad e_y = -45991.1989, \quad e_z = 19284.4863$$

These, together with the homogeneous coordinates of  $G$ , yield the plane equation.

$$\begin{aligned}
G_1x + G_2y + G_3z + G_0 &= 0 \rightarrow \\
g_0e_x x + g_0e_y y + g_0e_z z - (g_1e_x + g_2e_y + g_3e_z) &= 0 \\
\rightarrow \\
(6)(-25242.80478)x + (6)(-45991.1989)y \\
(6)(19284.4863)z - [(35)(-25242.80478) \\
+ (19)(-45991.1989) + (15)(19284.4863)] &= 0
\end{aligned}$$

Fig. 2 shows top and front view of the array of six spatial points as well as *all three* mutually orthogonal eigenvector *directions*. The remaining two were computed with the other two eigenvalues. The one labelled  $\lambda_3$  is associated with the greatest eigenvalue. It does not *appear* as the longest because the direction numbers were plotted as calculated. Vectors were not normalized and assigned inertial magnitudes represented by the respective eigenvalues.




Figure 2: Six Point Plane Fit

## 4 CONIC GRASSMANNIAN

The coefficients of a conic on five given points are provided by the top row minor  $5 \times 5$  determinants of the singular matrix, Eq. 5.

$$\left| \begin{bmatrix} w^2 & wx & wy & x^2 & xy & y^2 \\ w_1^2 & w_1x_1 & w_1y_1 & x_1^2 & x_1y_1 & y_1^2 \\ w_2^2 & w_2x_2 & w_2y_2 & x_2^2 & x_2y_2 & y_2^2 \\ w_3^2 & w_3x_3 & w_3y_3 & x_3^2 & x_3y_3 & y_3^2 \\ w_4^2 & w_4x_4 & w_4y_4 & x_4^2 & x_4y_4 & y_4^2 \\ w_5^2 & w_5x_5 & w_5y_5 & x_5^2 & x_5y_5 & y_5^2 \end{bmatrix} \right| = 0 \quad (5)$$

Therefore the conic is represented in a six dimensional homogeneous vector space of quadratic point form variables  $q_i$ , derived from point coordinates  $p_i$ , Eq. 6.

$$\begin{aligned} P\{p_0 : p_1 : p_2 : p_3\} &\equiv \{w : x : y : z\} \rightarrow \\ &Q\{q_0 : q_1 : q_2 : q_3 : q_4 : q_5\} \\ &\equiv \{w^2 : wx : wy : x^2 : xy : y^2\} \end{aligned} \quad (6)$$

For a brief but excellent introduction relating homogeneous coordinates and projective geometry to modern linear algebra a recent text by Pottmann and Wallner [4] is highly recommended. When fitting a conic to more than five given points, for the purpose of pattern recognition, *e.g.*, in unsupervised automated inspection of industrial production [5], digital image pixels often constitute the point set. Hence, after pre-processing, the spatial point set  $P$  is assumed to lie in the Euclidean plane of the curve it must represent. For this reason Eq. 5 contains only six planar quadratic forms (columns) rather than ten needed to define a three dimensional quadric surface in space. One may set  $p_0 = w = 1$  for points in the Euclidean plane to obtain the usual Cartesian coordinates

$$\begin{aligned} P(p_1, p_2) &\equiv (x, y) \rightarrow Q(q_1, q_2, q_3, q_4, q_5) \\ &\equiv (x, y, x^2, xy, y^2) \end{aligned} \quad (7)$$

Now first moments (centres of “gravity”) and second moments (moments and products of “inertia”) of the numerous given points, assumed to be of equal unit weight, in a five dimensional Euclidean space, will be defined. But first, consider what is in hand and what will be done with it.

- There are  $n$  given points

$${}_iQ(iq_1, iq_2, iq_3, iq_4, iq_5), \quad i = 1, \dots, n$$

- The first moment is defined with respect to a point  $G$  about which the sum of all point moments vanishes. Conversely  $G$  is the point where all  $n$  points may concentrate their weight so as to exert the same moment, anywhere, as do the  $n$  points in their actual position.

$$\begin{aligned} G\{g_0 : g_1 : g_2 : g_3 : g_4 : g_5\} &\equiv \left\{ n : \sum_{i=1}^n iq_1 : \right. \\ &\left. \sum_{i=1}^n iq_2 : \sum_{i=1}^n iq_3 : \sum_{i=1}^n iq_4 : \sum_{i=1}^n iq_5 \right\} \end{aligned} \quad (8)$$

- A hyperplane  $g\{G_0 : G_1 : G_2 : G_3 : G_4 : G_5\}$  on  $G$  is sought such that the sum of the squares of the normal “distances” from  ${}_iQ$  to  $g$  is minimized.
- This will occur, at least in the context of this geometric model, when the hyperplane normal direction numbers  $G_1 : G_2 : G_3 : G_4 : G_5$  are in the same ratio as those of the point cloud inertia matrix eigenvector  $e\{0 : E_1 : E_2 : E_3 : E_4 : E_5\}$  associated with the eigenvalue of greatest magnitude, say,  $\lambda_{max} = \lambda_5$ . The reason for this choice is evident. The sum of the squares of the distances to unit mass points in all directions normal to an axis is maximized if that axis is the principal axis of greatest inertia of a rigid body whose mass is composed exclusively of unit masses on  ${}_iQ$ . This observation proceeds directly from the definition of mass moment of inertia about an axis of rotation.

- $G_0 = 0$  if  $G \in g$ . *I.e.*, if one chooses  $G$  as origin. Then  $g$  is identical to  $e$ , except for some non-zero real multiplier.
- A little thought experiment may help to clarify the two arguments above.
  1. Imagine a massless rectangular wire-frame “box” with edge lengths  $a > b > c$ . On each of the eight vertices is located a unit point mass. Since  $8 > 3$ , these points are redundant in defining a unique plane. However it is obvious that  $G$  is at the centre of the box,  $g$  bisects the four edges of length  $c$  and the normal to  $g$  on  $G$  is the principal axis of greatest inertia. Finally,  $2c^2$  is the sum, of the distances squared, from vertex points  ${}_iP$  to  $g$ . It is obviously minimal.
  2. It must be pointed out that, as regards fitting planes to points, this geometric model is perfect . However the analogy between points and quadratic point forms is not and neither is the fit it produces.

This “point cloud” then, for a conic, is in five dimensional Euclidean space. The inertia matrix can be written as a symmetric array of sums of squares (along the diagonal) and negative product (off diagonal) terms in Eq. 9.

$$\mathbf{I} = \begin{bmatrix} I_{11} & -I_{12} & -I_{13} & -I_{14} & -I_{15} \\ -I_{12} & I_{22} & -I_{23} & -I_{24} & -I_{25} \\ -I_{13} & -I_{23} & I_{33} & -I_{34} & -I_{35} \\ -I_{14} & -I_{24} & -I_{34} & I_{44} & -I_{45} \\ -I_{15} & -I_{25} & -I_{35} & -I_{45} & I_{55} \end{bmatrix} \quad (9)$$

Rather than fitting six or more points to a general conic an example to fit four points to a circle is chosen because the simpler calculation can be demonstrated in detail and this special case will illustrate some intricacy not otherwise evident.

## 5 CIRCLE ON FOUR POINTS

Fitting a circle to an over-determined system of four given points  ${}_iP\{{}_ip_0 : {}_ip_1 : {}_ip_2\} \equiv \{w : x : y\}$  begins with a table of their homogeneous point coordinates.

$w$	$x$	$y$
1	4	2
1	9	5
1	14	5
1	18	4

This is represented in a table containing only *four* quadratic point forms, rather than six of a general conic, because the circle’s invariance under rotation would fill the column under  $xy$  with zeros. Similarly, another circle characteristic, identical coefficients of  $x^2$  and  $y^2$ , require that these two columns be combined as a sum. Thus these four appear in a  $5 \times 5$  matrix, of rank deficiency two, whose determinant expresses the circle equation. Additional given points would simply add



more zero columns on the left, further increasing rank deficiency, *i.e.*, expanding the null space of the matrix.

$$\left[ \begin{array}{cccccc} 0 & w^2 & wx & wy & x^2 + y^2 \\ 0 & 1p_0^2 & 1p_0 1p_1 & 1p_0 1p_2 & 1p_1^2 + 1p_2^2 \\ 0 & 2p_0^2 & 2p_0 2p_1 & 2p_0 2p_2 & 2p_1^2 + 2p_2^2 \\ 0 & 3p_0^2 & 3p_0 3p_1 & 3p_0 3p_2 & 3p_1^2 + 3p_2^2 \\ 0 & 4p_0^2 & 4p_0 4p_1 & 4p_0 4p_2 & 4p_1^2 + 4p_2^2 \end{array} \right] = 0$$

These quadratic point forms

$$\begin{aligned} \{w^2 : wx : wy : x^2 + y^2\} &\equiv \{ip_0^2 : ip_0 ip_1 : ip_0 ip_2 : ip_1^2 + ip_2^2\} \\ &\equiv \{iq_0 : iq_1 : iq_2 : iq_3\} \end{aligned}$$

and their sum and their average are tabulated below.

	$q_0$	$q_1$	$q_2$	$q_3$
	1	4	2	20
	1	9	5	106
	1	14	5	221
	1	18	4	340
$\Sigma$	4	45	16	687
$G = \bar{q}$	1	11.25	4	171.75

## 5.1 Centroid, Inertia Matrix & Elements

Subtracting the coordinates of  $G$ , the “centre of gravity”, produces the next table.

	$q'_1$	$q'_2$	$q'_3$
	-7.25	-2	-151.75
	-2.25	1	-65.75
	2.75	1	49.25
	6.75	0	168.25

Now the inertia matrix characteristic equation is given by

$$\begin{vmatrix} I_{11} - \lambda & -I_{12} & -I_{13} \\ -I_{12} & I_{22} - \lambda & -I_{23} \\ -I_{13} & -I_{23} & I_{33} - \lambda \end{vmatrix} = 0$$

where

$$\begin{aligned} I_{11} &= \sum_{i=1}^4 (iq_2'^2 + iq_3'^2), & I_{12} &= \sum_{i=1}^4 (iq_1' iq_2') \\ I_{13} &= \sum_{i=1}^4 (iq_1' iq_3'), & I_{22} &= \sum_{i=1}^4 (iq_1'^2 + iq_3'^2) \\ I_{23} &= \sum_{i=1}^4 (iq_2' iq_3'), & I_{33} &= \sum_{i=1}^4 (iq_1'^2 + iq_2'^2) \end{aligned}$$

So

$$\begin{array}{ccc}
 q_2'^2 + q_3'^2 & q_1'q_2' & q_1'q_3' \\
 23032.0625 & 14.5 & 1100.1875 \\
 4324.0625 & -2.25 & 147.9375 \\
 2426.5625 & 2.75 & 135.4375 \\
 28308.0625 & 0 & 1135.6875 \\
 \\ 
 q_1'^2 + q_3'^2 & q_2'q_3' & q_1'^2 + q_2'^2 \\
 23080.625 & 303.5 & 56.5625 \\
 4328.125 & -65.75 & 6.0625 \\
 2433.125 & 49.25 & 8.5625 \\
 28353.625 & 0 & 45.5625
 \end{array}$$

and

$$\begin{array}{lll}
 I_{11} = 58090.75, & I_{12} = 15, & I_{13} = 2519.25 \\
 I_{22} = 58195.5, & I_{23} = 287 & I_{33} = 116.75
 \end{array}$$

## 5.2 Eigenvalues and Eigenvectors

The characteristic equation determinant yields the following cubic

$$\lambda^3 - 116403\lambda^2 + 3387767447\lambda - 20536062200 = 0$$

with eigenvalues

$$\lambda = 58201.40932, \quad 58195.52759, \quad 6.063090633$$

The greatest, first eigenvalue produces the following three dependent equations when it is substituted into the matrix that pre-multiplies column eigenvector  $\mathbf{e}$ .

$$\begin{array}{lll}
 110.65932e_1 + & 15e_2 + & 2519.25e_3 = 0 \\
 15e_1 + & 5.90932e_2 + & 287e_3 = 0 \\
 2519.25e_1 + & 287e_2 + & 58084.65932e_3 = 0
 \end{array}$$

Solving the first two equations homogeneously reveals the eigenvector normal to the “best” fitting “plane”.

$$\mathbf{e} = \begin{bmatrix} e_1 \\ e_2 \\ e_3 \end{bmatrix} = \begin{bmatrix} -10582.05441 \\ 6029.52516 \\ 428.9213329 \end{bmatrix}$$

## 5.3 The “Plane” & the Circle

Recall the centroid

$$G\{g_0 : g_1 : g_2 : g_3\} = \{1 : 11.25 : 4 : 171.75\}$$

on which  $g$  the pseudo-plane of best fit must lie.

$$\begin{aligned}
 & g\{G_0 : G_1 : G_2 : G_3\} \\
 = & \{-(g_1e_1 + g_2e_2 + g_3e_3) : g_0e_1 : g_0e_2 : g_0e_3\} \\
 = & g\{21262.77253 : -10582.05441 : \\
 & 6029.52516 : 428.9213329\}
 \end{aligned} \tag{10}$$

Recall, also, the circle equation whose coefficients are the elements of  $g$ , thus.

$$21262.77253w^2 - 10582.05441wx + 6029.52516wy + 428.9213329(x^2 + y^2) = 0$$

Rearranging this in more familiar, Euclidean form and dividing by  $G_3$  produces something that looks like a circle equation

$$(x^2 + y^2) - 24.67131755x + 14.05741496y + 49.57266263 = 0$$

that can easily be interpreted as

$$(x^2 + y^2) - 2x_c x - 2y_c y + (x_c^2 + y_c^2 - r^2) = 0$$

Solving for centre coordinates  $C(x_c, y_c)$  and radius  $r$  gives the following circle parameters.

$$x_c = 12.33565878, \quad y_c = -7.02870748, \quad r = 12.32876895$$

Examine Fig. 3. This result is quite encouraging when compared to a rigorous least squares distance fit described below. However the downward-convex circular arc centred on  $C'$  is the result of invoking the second eigenvalue, less than the greatest by only 0.01%! This inertial fit appears to be very sensitive in this regard.




Figure 3: Four Point Circle Fit

## 5.4 Least Squares Distance

Consider the minimization of the following sum.

$$D = \sum_{i=1}^4 \left[ \sqrt{(x_c - x_i)^2 + (y_c - y_i)^2} - r \right]^2$$

Taking the derivatives

$$\frac{\partial D}{\partial x_c} = 0, \quad \frac{\partial D}{\partial y_c} = 0, \quad \frac{\partial D}{\partial r} = 0$$

Removing the common factor 2 from all three derivatives and the common reciprocal factor

$$\prod_{i=1}^4 \sqrt{(x_c - x_i)^2 + (y_c - y_i)^2}$$

from the first two yields three simultaneous equations. Note that  $u = x, y$  to account for the first two of similar form.

$$\begin{aligned} (4u_c - \sum u_i)a_{1234} - [(u_c - u_1)a_{234} \\ + (u_c - u_2)a_{134} + (u_c - u_3)a_{124} \\ + (u_c - u_4)a_{123}]r = 0 \\ a_1 + a_2 + a_3 + a_4 - 4r = 0 \end{aligned} \tag{11}$$

Multiple subscripts indicate products, *e.g.*,  $a_{1234} = a_1a_2a_3a_4$  and

$$a_i = \sqrt{(x_c - x_i)^2 + (y_c - y_i)^2}$$

Eliminating  $r$  leaves the two following equations.

$$\begin{aligned} & 3(4u_c - \sum u_i)a_{1234} \\ & -a_1^2[(u_c - u_2)a_{34} + (u_c - u_3)a_{24} + (u_c - u_4)a_{23}] \\ & -a_2^2[(u_c - u_1)a_{34} + (u_c - u_3)a_{14} + (u_c - u_4)a_{13}] \\ & -a_3^2[(u_c - u_1)a_{24} + (u_c - u_2)a_{14} + (u_c - u_4)a_{12}] \\ & -a_4^2[(u_c - u_1)a_{23} + (u_c - u_2)a_{13} + (u_c - u_3)a_{12}] = 0 \end{aligned}$$

Solving these explicitly seems impractical. However inserting the exact values obtained with the inertial model leaves residues of about -695 and -97, respectively. After a few iterative perturbations these are reduced to about 2.1 and -3.8. To achieve still greater precision is probably not worthwhile. The centre coordinates of  $C$  are now

$$x_c = 12.32503412, \quad y_c = -7.02685$$

Substituting these into the third partial derivative, Eq. 11, produces  $r = 12.32552238$ . When these improved values are used to construct a circle in Fig. 3 this and the original arc are virtually coincident.

## 6 CONCLUSION

It is anticipated that the novel geometric approach, based on a moment of inertia interpretation, described here could, with further development, become a powerful image processing and pattern recognition tool. The immediate extension of its currently modest capacities will be focused on recognition of other shapes which can be represented by quadratic forms, *i.e.*, other specific conics as well as quadric surfaces.

## References

- [1] Peterson, T.S. (1950): *Elements of Calculus*, Harper & Bros., pp.30-37.
- [2] Strang, G. (1980): *Linear Algebra & Its Applications*, 2<sup>nd</sup> Ed., Academic Press, ISBN 0-12-673660-X, pp.179-242.
- [3] Meriam, J.L. & Kraige, L.G. (2003): *Engineering Mechanics, Vol. 2, Dynamics*, 5<sup>th</sup> Ed., Wiley, ISBN 0-1471-26606-x, pp.651-678.
- [4] Pottmann, H. & Wallner, J. (2000): *Computational Line Geometry*, Springer, ISBN 3-540-42058-4, pp.1-158.
- [5] O’Leary, P. & Zsombor-Murray, P.J. (2004): “Direct & Least-Square Fitting of Hyperbolæ & Ellipses”, *J. Electronic Imaging*, (to appear 04-03), 26pp.

## ABOUT THE AUTHORS

Paul Zsombor-Murray is an associate professor of Mechanical Engineering in the Department of Mechanical Engineering in McGill University. His research interests are Theoretical Kinematics, Robotics and Applications of Geometry in Mechanics. He can be reached by e-mail: paul@cim.mcgill.ca, by phone: +1-514-398-6311, by fax: +1-514-398-7348 or through the postal address: McGill University Centre for Intelligent Machines/ 817r. Sherbrooke o./ Montréal (Québec) Canada/ H3A 2K6. Web site: <http://www.cim.mcgill.ca/paul/>

Paul O’Leary is a professor of automation in the Institute for Automation in The University of Leoben. His research interests are Industrial Automation, Optical Measurement and Calibration and Autonomous Inspection through Image Processing. He can be reached by e-mail: oleary@unileoben.ac.at, by phone: +43-3842-402-9030, by fax: +43-3842-402-9032 or through postal address: Institute for Automation/ University of Leoben/ A-8700 Leoben Austria. Web site: <http://automation.unileoben.ac.at/>