

Semi-empirical dissipation source functions for ocean waves: Part I, definition, calibration and validation

Fabrice Ardhuin, Erick Rogers, Alexander Babanin, Jean-François Filipot, Rudy Magne, Aron Roland, Andre van Der Westhuysen, Pierre Queffeulou, Jean-Michel Lefevre, Lotfi Aouf, et al.

▶ To cite this version:

Fabrice Ardhuin, Erick Rogers, Alexander Babanin, Jean-François Filipot, Rudy Magne, et al.. Semiempirical dissipation source functions for ocean waves: Part I, definition, calibration and validation. 2009. hal-00407184v2

HAL Id: hal-00407184 https://hal.science/hal-00407184v2

Preprint submitted on 25 Jul 2009 (v2), last revised 1 Jan 2010 (v3)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Semi-empirical dissipation source functions for ocean waves: Part I, definition, calibration and validation.

FABRICE ARDHUIN¹, ERICK ROGERS², ALEXANDER BABANIN³, JEAN-FRANÇOIS FILIPOT¹, RUDY MAGNE¹, AARON ROLAND⁴, ANDRE VAN DER WESTHUYSEN⁵, PIERRE QUEFFEULOU⁶, JEAN-MICHEL LEFEVRE, LOTFI AOUF⁷, AND FABRICE COLLARD⁸

¹Service Hydrographique et Océanographique de la Marine, Brest, France
 ²Oceanography Division, Naval Research Laboratory, Stennis Space Center, MS, USA
 ³Swinburne University, Hawthorn, VA, Australia
 ⁴Technological University of Darmstadt, Germany
 ⁵Delft Hydraulics
 ⁶Ifremer, Laboratoire d'Océanographie Spatiale, Plouzané, France
 ⁷UMR GAME, Météo-France - CNRS, Toulouse, France
 ⁸CLS, Division Radar, Plouzané, France

(Manuscript received , in final form)

ABSTRACT

New parameterizations for the spectra dissipation of wind-generated waves are proposed. The rates of dissipation have no predetermined spectral shapes and are functions of the wave spectrum and wind speed and direction, in a way consistent with observation of wave breaking and swell dissipation properties. Namely, the swell dissipation is nonlinear and proportional to the swell steepness, and dissipation due to wave breaking is non-zero only when a non-dimensional spectrum exceeds the threshold at which waves are observed to start breaking. An additional source of short wave dissipation due to long wave breaking is introduced to represent the dissipation of short waves due to longer breaking waves. Several degrees of freedom are introduced in the wave breaking and the wind-wave generation term of Janssen (J. Phys. Oceanogr. 1991). These parameterizations are combined and calibrated with the Discrete Interaction Approximation of Hasselmann et al. (J. Phys. Oceangr. 1985) for the nonlinear interactions. Parameters are adjusted to reproduce observed shapes of directional wave spectra, and the variability of spectral moments with wind speed and wave height. The wave energy balance is verified in a wide range of conditions and scales, from gentle swells to major hurricanes, from the global ocean to coastal settings. Wave height, peak and mean periods, and spectral data are validated using in situ and remote sensing data. Some systematic defects are still present, but the parameterizations yield the best overall results to date. Perspectives for further improvement are also given.

1. Introduction

a. On phase-averaged models

Spectral wave modelling has been performed for the last 50 years, using the wave energy balance equation (Gelci et al. 1957). This description radiation of the spectral density of the surface elevation variance F distributed over frequencies f and directions θ can be put in the form

$$\frac{\mathrm{d}F(f,\theta)}{\mathrm{d}t} = S_{\mathrm{atm}}(f,\theta) + S_{\mathrm{nl}}(f,\theta) + S_{\mathrm{oc}}(f,\theta) + S_{\mathrm{bt}}(f,\theta),$$
(1)

where the Lagrangian derivative is the rate of change of the spectral density when following a wave packet at its group speed in physical and spectral space. The source functions on the right hand side are separated into an atmospheric source function $S_{\rm atm}$, a nonlinear scattering term $S_{\rm nl}$, an ocean source $S_{\rm oc}$, and a bottom source $S_{\rm bt}$.

This separation, like any other, is largely arbitrary. For example, waves that break are highly nonlinear and thus the effect of breaking waves that is contained in $S_{\rm oc}$ is intrisically related to the non-linear evolution term contained in $S_{\rm nl}$. Yet, compared to the usual separation of deep-water evolution in input, non-linear interactions, and dissipation, it has the benefit of identifying where the energy and momentum is going to or coming from, which is a necessary feature when ocean waves are used to drive or are coupled with atmospheric or ocean cir-

Corresponding author address: Fabrice Ardhuin, Service Hydrographique et Océanographique de la Marine, 29609 Brest, France E-mail: ardhuin@shom.fr

culation models (e.g. Janssen et al. 2004; Ardhuin et al. 2008b).

 $S_{\rm atm}$, which gives the flux of energy from the atmospheric non-wave motion to the wave motion, is the sum of a wave generation term $S_{\rm in}$ and a wind-generation term $S_{\rm out}$ (often referred to as negative wind input, i.e. a wind output). The nonlinear scattering term $S_{\rm nl}$ represents all processes that lead to an exchange of wave energy between the different spectral components. In deep and intermediate water depth, this is dominated by cubic interactions between quadruplets of wave trains, while quadratic nonlinearities play an important role in shallow water (e.g. WISE Group 2007). The ocean source $S_{\rm oc}$ may accomodate wave-current interactions¹ and interactions of surface and internal waves, but it will be here restricted to wave breaking and wave-turbulence interactions.

The basic principle underlying equation (1) is that waves essentially propagate as a superposition of almost linear wave groups that evolve on longer time scales as a result of weak-in-the-mean processes (e.g. Komen et al. 1994). Recent reviews have questioned the possibility of further improving numerical wave models without changing this basic principle (Cavaleri 2006). Although this may be true in the long term, we demonstrate here that it is possible to improve model results significantly by including more physical features in the source term parameterizations. The main advance proposed in the present paper is the adjustment of a shape-free dissipation function based on today's knowledge on the breaking of random waves (Banner et al. 2000; Babanin et al. 2001) and the dissipation of swells over long distances (Ardhuin et al. 2009b). The present formulations are still semiempirical, in the sense that they are not based on a detailed physical model of dissipation processes, but they demonstrate that progress is possible. This effort opens the way for completely physical parameterizations (e.g. Filipot et al. 2008) that will eventually provide new applications for wave models, such as the estimation of statistical parameters for breaking waves, such as whitecap coverage and foam thickness. Other efforts, less empirical in nature, are also under way to arrive at better parameterizations (e.g. Banner and Morison 2006; Babanin et al. 2007; Tsagareli 2008), but they yet have to produce a practical alternative for wave forecasting and hindcasting.

b. Shortcomings of existing parameterizations

All wave dissipation parameterizations up to the work of van der Westhuysen et al. (2007) had no quantitative relationship with observed features of wave dissipation, and the parameterizations were generally used as set of tuning knobs to close the wave energy balance. The parameterization of the form proposed by Komen et al. (1984) have produced a family loosely justified by the so-called 'random pulse' theory of (Hasselmann 1974). These take a generic form

$$S_{\rm oc}(f,\theta) = C_{\rm ds} g^{0.5} k_r^{4.5} H_s^4 \left[\delta_1 \frac{k}{k_r} + \delta_2 \left(\frac{k}{k_r} \right)^2 \right],$$
(2)

in which $C_{\rm ds}$ is a negative constant, and k_r is an energyweighted mean wavenumber defined from the entire spectrum, and H_s is the significant wave height. In the early and latest parameterizations, the following definition was used

$$k_r = \left[\frac{16}{H_s^2} \int_0^{f_{\max}} \int_0^{2\pi} k^r E\left(f,\theta\right) \mathrm{d}f\mathrm{d}\theta\right]^{1/r},\qquad(3)$$

where r is a chosen real constant, typically r = 0.5.

These parameterizations are still widely used in spite of inconsistencies in the underlying theory. Indeed, if whitecaps do act as random pressure pulses, their average work on the underlying waves only occurs because of a phase correlation between the vertical orbital velocity field and the moving whitecap position, which travels with the breaking wave. In reality the horizontal shear is likely the dominant mechanism (Longuet-Higgins and Turner 1974), but the question of correlation remains the same. For any given whitecap, such a correlation cannot exist for all spectral wave components: a whitecap that travels with one wave leads to the dissipation of spectral wave components that propagate in the same direction with comparable phase velocities waves propagating in one direction will give (on average) a zero correlation for waves propagating in the opposite direction because the crest of those waves relative to that of the whitecap are completely random. As a result, not all wave components are dissipated by a given whitecap (others should even be generated) and the dissipation function cannot take the form later given by Komen et al. (1984). This is also true for all waves shorter than about 1 m wavelength, which provide a significant portion of the dissipation and do not produce whitecapping (e.g. Longuet-Higgins 1990; Jessup et al. 1997; Tulin and Landrini 2001).

In particular, a strict interpretation of the pressure pulse model gives a zero dissipation for swells in the open ocean because the swell wave phases are uncorrelated to those of the shorter breaking waves. There is only a negligible dissipation due to short wave modulations by swells and preferential breaking on the swell crests (Phillips 1963; Hasselmann 1971; Ardhuin and Jenkins 2005). Still, the Komen et al. (1984) type dissipation terms are applied to the entire spectrum, including swells, without any physical justification.

In spite of its successful use for the estimation of the significant wave height H_s and peak period T_p , these fixed-shape dissipation functions, from Komen et al. (1984) up to Bidlot et al. (2007a), have built-in defects.

¹In the presence of variable current, the source of energy for the wave field, i.e. the work of the radiation stresses, is generally hidden when the energy balance is written as an action balance (e.g. Komen et al. 1994).

Most conspicuous is the spurious amplification of wind sea growth in the presence of swell (e.g. van Vledder and Hurdle 2002), which is contrary to all observations (Dobson et al. 1989; Violante-Carvalho et al. 2004; Ardhuin et al. 2007). Associated with that defect also comes an underestimation of the energy level in the inertial range, making these wave models ill-suited for remote sensing studies, as will be exposed below.

Also, these parameterizations typically give a decreasing dissipation of swell with increasing swell steepness, contrary to all observations from Darbyshire (1958) to Ardhuin et al. (2009b). This effect is easily seen by taking a sea state composed of a swell of energy E_1 and mean wavenumber k_1 and a windsea of energy E_2 and mean frequency k_2 , with $k_2 > k_1$. The overall mean wavenumber is

$$k_r = \left(k_1 E_1 + k_2 E_2\right)^{1/r} / (E_1 + E_2), \qquad (4)$$

and the low frequency dissipation for a given value of k is proportional to $k_r^{3.5}(E_1 + E_2)$. Now, if we keep k_1, k_2 an E_2 constant and only increase the swell energy E_1 , the relative change in dissipation is proportional to $3.5[(k_1/k_r)^r - 1]/r + 2$. For r = 0.5, as used in BAJ, and $k_1/k_r < 0.51$, this is negative (i.e. the dissipation decreases with increasing swell energy). For equal energy in sea and swell, this occurs when $k_1/k_2 < 0.3$, which is generally the case with sea and swell in the ocean. This erroneous decrease of swell dissipation with increasing swell steepness is reduced when the model frequency range is limited to maximum frequency of 0.4 Hz, in which case the lowest winds (less than 5 m/s) are unable to produce a realistic wind sea level, hence limiting the value of k_r to relatively small values.

An alternative and widely used formulation has been proposed by Tolman and Chalikov (1996), and some of its features are worth noting. It combines two distinct dissipation formulations for high and low frequencies, with a transition at two times the wind sea peak frequency. Whereas Janssen et al. (1994) introduced the use of two terms, k and k^2 in eq. (2), in order to match the very different balances in high and low frequency parts of the spectrum, they still had a common fixed coefficient, δ . In Tolman and Chalikov (1996) these two dissipation terms are completely distinct, the low frequency part being linear in the spectrum and proportional to wind friction velocity u_{\star} , the high frequency part is also linear and proportional to u_{\star}^2 . In this formulation the frequency dependence of the two terms is also prescribed. Tolman and Chalikov (1996) further included swell attenuation by the wind, based on numerical simulations of the airflow above waves (Chalikov and Belevich 1993), here noted S_{out} . At relatively short fetches, these source terms are typically a factor 2 to 3 smaller than those of Janssen et al. (1994), which was found to produce important biases in wave growth and wave directions at short fetch (Ardhuin et al. 2007). Another successful set of parameterizations, for high winds conditions, is the combination by Makin and Stam (2003), but it does not produce accurate results in moderate sea states (Lefèvre et al. 2004)

rate results in moderate sea states (Lefèvre et al. 2004). Polnikov and Inocentini (2008) have also proposed new source term formulations, but the accuracy of their results appears generally less than with the model presented here, in particular for mean periods.

Considering the observed strong wave height gradients in rapidly varying currents Phillips (1984) proposed a dissipation rate proportional to the non-dimensional spectrum, also termed 'saturation spectrum'. Banner et al. (2000) indeed found a correlation of the directionintegrated saturation B with the breaking probability of dominant waves. IN particular they found that breaking occurs when B exceeds a threshold B_r . Alves and Banner (2003) proposed to define the dissipation $S_{\rm oc}$ by B/B_r to some power, multiplied by a Komen-type dissipation term. Although this approach avoided the investigation of the dissipation of non-breaking waves, it imported all the above mentionned defects of that parameterization. Further, these authors used a value for B_r that is much higher than suggested by observations, which tends to disconnect the parameterization from the observed effects (Babanin and van der Westhuysen 2008).

The use of a saturation parameter was taken up again by van der Westhuysen et al. (2007), hereinafter WZB, who integrated the saturation spectrum over directions, giving

$$B(f) = \int_0^{2\pi} k^3 F(f,\theta') C_g/(2\pi) \mathrm{d}\theta'.$$
 (5)

From this, they defined the source function

$$S_{\rm oc,WZB}\left(f,\theta\right) = -C\sqrt{gk} \left[\frac{B(f)}{B_r}\right]^{p/2},\qquad(6)$$

where C is a positive constant, B_r is a constant saturation threshold and and p is a coefficient that varies both with the wind friction velocity u_{\star} and the degree of saturation $B(f)/B_r$ with, in particular, $p \approx 0$ for $B(f) < 0.8B_r$. For non breaking waves, when $p \approx 0$, the dissipation is too large by at least one order of magnitude, making the parameterization unfit for oceanic scale applications with wave heights in the Atlantic underpredicted by about 50% (Ardhuin and Le Boyer 2006). Further, the increase of pwith the inverse wave age u_{\star}/C , tends to increase $S_{\rm oc}$ at high frequency, and was needed to obtain a balance with the S_{atm} term in equation (1). This indicates that, besides the value of the saturation B_r , other factors may be important, such as the directionality of the waves (Banner et al. 2002). Other observations clearly show that the breaking rate of high frequency waves is much higher for a given value of B, probably due to cumulative effects by which the longer waves are modifying the dissipation of shorter waves.

Banner et al. (1989) and Melville et al. (2002) have shown how breaking waves suppress the short waves on the surface, and we will show here that a simple estimation of the dominant breaking rates based on the observations by Banner et al. (2000) suggests that this effect is dominant for wave frequencies above three times the windsea peak frequency. Young and Babanin (2006) arrived at the same conclusion from the examination of wave spectra, and even proposed a parameterization for $S_{\rm oc}$. Yet, their estimate was only obtained for a single wind-forcing condition (quite strong). Further, their interpretation of the differences in parts of a wave record with breaking and non-breaking waves implies an underestimation of the dissipation rates because the breaking waves have already lost some energy when they are observed and the non-breaking waves are not going to break right after they have been observed. Also, since the spectra are different, nonlinear interactions must be different, even on this relatively small time scale (e.g. Young and van Vledder 1993, figure 5), and the differences in spectra may not be the result of dissipation alone.

Finally, the recent measurement of swell dissipation by Ardhuin et al. (2009a) has revealed that the dissipation of non-breaking waves is essentially a function of the wave steepness, and a very important process for ocean basins larger than 1000 km. Because of the differences in coastal and larger scale sea states (e.g. Long and Resio 2007), it is paramount to verify source function parameterizations at all scales, in order to provide a robust and comprehensive parameterization of wave dissipation.

It is thus time to combine the existing knowledge on the dissipation of breaking and non-breaking waves to provide an improved parameterization for the dissipation of waves. Our objective is to provide a robust parameterization that improves existing wave models. Further work will be needed to replace the arbitrary choices made here with physically-motivated expressions. We will first present one general form of the dissipation terms that can be made consistent with observed wave dissipation features, and the impact of the different parameters on the resulting wave spectra. The degrees of freedom in the parameterization will then be used to adjust the resulting wave parameters to observations using field experiments and a one year hindcast of waves at the global and regional scale, in which all possible wave measurements are considered, with significant wave heights ranging from 0 to 17 m. The model is further validated with independent data at regional and global scales. Tests and verification in the presence of currents, and using a more realistic parameterizations of wave-wave interactions will be presented in parts II and III.

2. Parameterizations

Several results will be presented, obtained by a numerical integration of the energy balance. Because numerical choices can have important effects (e.g. Tolman 1992; Hargreaves and Annan 2000), a few details should be given. Most calculations are performed with the WAVEWATCH III^{TM} modelling framework (Tolman

2008, 2009), hereinafter WWATCH, including modifications of the source terms described here, and, for some coastal simulations, the the use of advection schemes on unstructured grids (Roland 2008). In all cases ran with WWATCH, the source terms are integrated with the fully implicit scheme of Hargreaves and Annan (2000), combined with the adaptative time step and limiter method of Tolman (2002), in which a minimum time step of 10 s is used. The diagnostic tail, proportional to f^{-5} is only imposed at a cut-off frequency f_c of 10 times the mean frequency $f_m = 1/T_{m01}$. Here f_c is generally above the maximum model frequency that we fixed at 0.72 Hz. Hence the high frequency tail is left to evolve freely and the limiter on wind-wave growth is almost never activated. Some comparison tests are also done with other parameterizations using a lower value of f_c , typically set at 2.5 f_m (Bidlot et al. 2007a). In such calculations, the net source term may be non-zero even if there is no spectral evolution due to the imposed tail.

a. Nonlinear wave wave interactions

All the results discussed and presented in this section are obtained with the Discrete Interaction Approximation of Hasselmann et al. (1985). The coupling coefficient that gives the magnitude of the interactions is $C_{\rm nl}$. Based on comparisons with exact calculations, Komen et al. (1984) adjusted the value of $C_{\rm nl}$ to 2.78×10^7 , which is the value used by Bidlot et al. (2005). Here this constant will be allowed to vary slightly. This parameterization is well known for its shortcomings (Banner and Young 1994), and the adjustment of other parameters probably compensates for some of these errors. This matter will be fully discussed in Part III.

b. Swell dissipation

Observations of swell dissipation are consistent with the effect of friction at the air-sea interface (Ardhuin et al. 2009a), resulting in a flux of momentum from the wave field to the wind (Harris 1966). We thus write the swell dissipation as a negative contribution $S_{\rm out}$ which is added to $S_{\rm in}$ to make the wind-wave source term $S_{\rm atm}$.

Using the method of Collard et al. (2009), a systematic analysis of swell observations by Ardhuin et al. (2009a) showed that the swell dissipation is non-linear, possibly related to a laminar-to-turbulent transition of the oscillatory boundary layer over swells. Defining the boundary Reynolds number Re= $4u_{orb}a_{orb}/\nu_a$, where u_{orb} and a_{orb} are the significant surface orbital velocity and displacement amplitudes, and ν_a is the air viscosity, we take, for Re less than a critical value Re_c

$$S_{\text{out}}(f,\theta) = -C_{\text{dsv}} \frac{\rho_a}{\rho_w} \left\{ 2k\sqrt{2\nu\sigma} \right\} F(f,\theta), \quad (7)$$

where the constant C_{dsv} is equal to 1 in Dore (1978)'s laminar theory.

When the boundary layer is expected to be turbulent,

for $\text{Re} \geq \text{Re}_c$, we take

$$S_{\text{out}}(f,\theta) = -\frac{\rho_a}{\rho_w} \left\{ 16 f_e \sigma^2 u_{\text{orb}}/g \right\} F(f,\theta) \,. \tag{8}$$

A few tests have indicated that $\text{Re}_c = 10^5$ provides reasonable result, although it may be a function of the wind speed. Here we shall use $C_{\text{dsv}} = 1.2$, but the result are not too sensitive to variations in the range 0.8 to 1.5.

The parameterization of the turbulent boundary layer is a bit more problematic, and in the absence of direct measurements in the boundary layer, leaves room for speculations. From the analogy with an oscillatory boundary layer over a fixed bottom (Jensen et al. 1989), the values of f_e inferred from the swell observations, in the range 0.004 to 0.013 (Ardhuin et al. 2009b), correspond to a surface with a very small roughness. Because, we also expect the wind to influence f_e , the parameterization form includes adjustable effects of wind speed on the roughness, and an explicit correction of f_e . This latter correction takes the form of a Taylor expansion to first order in u_*/u_{orb} ,

$$f_e = s_1 \left\{ f_{e,GM} + [|s_3| + s_2 \cos(\theta - \theta_u)] \frac{u_{\star}}{u_{\text{orb}}} \right\}, \quad (9)$$

where $f_{e,GM}$ is the friction factor given by Grant and Madsen's (1979) theory for rough oscillatory boundary layers without a mean flow. Adequate swell dissipation is obtained with constant values of f_e in the range 0.004 to 0.007, but these do not necessarily produce the best results when comparing wave heights to observations. Based on the simple idea that most of the air-sea momentum flux is supported by the pressure-slope correlations that give rise to the wave field (Donelan 1998; Peirson and Banner 2003), we have taken the surface roughness z'_0 to be a fixed small proportion r_{z0} , here set to 0.04, of the roughness for the wind. We thus give the more generic equation (9) for f_e , with $f_{e,GM}$ of the order of 0.003 for values of a_{orb}/z'_0 of the order of 2×10^5 .

The coefficients s_2 and s_3 of the $O(u_*/u_{\rm orb})$ correction have been adjusted to -0.018 and 0.015, respectively, the former negative value giving a stronger dissipation for swells opposed to winds, when $\cos(\theta - \theta_u) < 0$. This gives a range of values of f_e consistent with the observations, and reasonable hindcasts of swell decay (Fig. 1), with a small underestimation of dissipation for steep swells. An increase of s_1 from 0.8 to 1.1 produces negative biases on H_s of the order of 30% at all oceanic buoys (40% for a partial wave height estimated from a spectrum restricted to periods around 15 s), so that the magnitude of the swell dissipation cannot be much larger than chosen here. Further discussion and validation of the swell dissipation 4.

c. Wave breaking

Observations show that waves break when the orbital velocity at their crest U_c comes close to the phase speed



FIG. 1. Comparison of modelled swell significant heights, following the propagation of the two swells shown by Ardhuin et al. (2009) with peak periods of 15 s and high and low dissipation rates. Known biases in the level 2 data have been corrected following Collard et al. (2009).

C, with a ratio $U_c/C > 0.8$ for random waves (Tulin and Landrini 2001; Stansell and MacFarlane 2002; Wu and Nepf 2002). It is nevertheless difficult to parameterize the breaking of random waves, since the only available quantity here is the spectral density. This density can be related to the orbital velocity variance in a narrow frequency band. Yet, a proper threshold has to be defined for this quantity, and the spectral rate of energy loss associated to breaking has to be defined. Also, breaking is intricately related to a complex non-linear evolution of the waves (e.g. Banner and Peirson 2007).

These difficulties will be ignored here. Following the more detailed analysis presented in Filipot et al. (2009), we shall parameterize the spectral dissipation rate directly from the wave spectrum, in a way similar to WZB. Essentially we distiguish between spontaneous and induced breaking, the latter being caused by large scale breakers overtaking shorter waves, and causing them to be dissipated. For the spontaneous breaking we parameterize the dissipation rate directly from the spectrum, without the intermediate step of estimating a breaking probability.

We started from the simplest possible dissipation term formulated in terms of the direction-integrated spectral saturation B(f) given by eq. (5), with a realistic threshold $B_{0r} = 1.2 \times 10^{-3}$ corresponding to the onset of wave breaking (Babanin and Young 2005). This saturation parameter corresponds exactly to the α parameter defined by Phillips (1958). The value $B_0 = 8 \times 10^{-3}$, given by Phillips, corresponds to a self-similar sea state in which waves of all scales have the same shape, limited by the breaking limit.

This view of the sea state, however, ignores completely wave directionality. Early tests of parameterizations based on this definition of *B* indicated that the spectra were too narrow (Ardhuin and Le Boyer 2006). This effect could be due to many errors. Because Babanin et al. (2001) introduced a directional width in their saturation to explain some of the variability in observed breaking probabilities, we similarly modify the definition of *B*. Expecting also to have different dissipation rates in different directions, we define a saturation *B'* that would correspond, in deep water, to a normalized velocity variance projected in one direction (in the case sB = 2), with a further restriction of the integration of directions controlled by Δ_{θ} ,

$$B'(f,\theta) = \int_{\theta-\Delta_{\theta}}^{\theta+\Delta_{\theta}} k^3 \cos^{\mathrm{sB}}(\theta-\theta') F(f,\theta') \frac{C_g}{2\pi} \mathrm{d}\theta',$$
(10)

Here we shall always use $\Delta_{\theta} = 80^{\circ}$. As a result, a sea state with two systems of same energy but opposite direction will typically produce much less dissipation than a sea state with all the energy radiated in the same direction.

We finally define our dissipation term as the sum of the saturation-based term of Ardhuin et al. (2008a) and a cumulative breaking term $S_{\rm bk,cu}$,

$$S_{\rm oc}(f,\theta) = \sigma \frac{C_{\rm dat}^{\rm cas}}{B_r^2} \left[\delta_d \max \left\{ B\left(f\right) - B_r, 0 \right\}^2 + (1 - \delta_d) \max \left\{ B'\left(f,\theta\right) - B_r, 0 \right\}^2 \right] F(f,\theta) + S_{\rm bk,cu}(f,\theta) + S_{\rm turb}(f,\theta).$$
(11)

where

$$B(f) = \max \{ B'(f, \theta), \theta \in [0, 2\pi] \}.$$
 (12)

The combination of an isotropic part (the term that multiplies δ_d) and a direction-dependent part (the term with $1 - \delta_d$) was intended to allow some control of the directional spread in resulting spectra. This aspect is illustrated in figure 2 with a hindcast of the November 3 1999 case during the Shoaling Waves Experiment (Ardhuin et al. 2007; Zhang et al. 2009). Clearly, the isotropic saturation in the TEST442 dissipation (with the original



FIG. 2. Wave spectra on 3 November 1999 at buoy X3 (fetch 39 km, wind speed $U_{10} = 9.4 \text{ m s}^{-1}$), averaged over the time window 1200-1700 EST, from observations and model runs, with different model parameterizations (symbols): BAJ stands for Bidlot et al. (2007a). (a) Energy, (b) mean direction (c) directional spread. This figure is analogue to the figures 10 and 11 in Ardhuin et al. (2007), the model forcing and setting are identical. It was further verified that halving the resolution from 1 km to 500 m does not affect the results. All parameters for BAJ, TEST441 and TEST443 are listed in tables A1 and A2. Input parameters for TEST441 and TEST443 are identical to those for TEST441, and TEST442 differs from TEST441 only in its isotropic direct breaking term, given by sB= 0, $\Delta_{\theta} = 180^{\circ}$, and $B_{T} = 0.0012$. It should be noted that the overall dissipation term in TEST443 is made anisotropic due to the cumulative effect, but this does not after much the underestimation of directional spread.

threshold $B_r = 0.0012$) produces very narrow spectra, even though it is known that the DIA parameterization for nonlinear interactions tends to broaden the spectra. The same behaviour is obtained with the isotropic parameterization by van der Westhuysen et al. (2007), as demonstrated by Ardhuin and Le Boyer (2006). Further, using an isotropic dissipation at all frequencies yields an energy spectrum that decays faster towards high frequencies than the observed spectrum (Fig. 2.a). On the contrary, a fully directional dissipation term (TEST443 with $\delta_d = 0$) gives a better fit for all parameters. With sB = 2, we reduce B_r to 0.0009, a threshold for the onset of breaking that is consistent with the observations of Banner et al. (2000) and Banner et al. (2002), as discussed byBabanin



FIG. 3. Fetch-limited growth of the windsea energy in as a function of fetch on 3 November 1999, averaged over the time window 1200-1700 EST, from observations and model runs, with different model parameterizations (symbols): BAJ stands for Bidlot et al. (2007a). This figure is analogue to the figure 8 in Ardhuin et al. (2007), the model forcing and setting are identical. All parameters for BAJ, TEST441 and TEST443 are listed in tables A1 and A2. Input parameters from TEST441 only in its isotropic direct breaking term, given by sB= 0, $\Delta_{\theta} = 180^{\circ}$, and $B_r = 0.0012$.

and van der Westhuysen (2008).

The dissipation constant $C_{\rm ds}^{\rm sat}$ was adjusted to 2.2 \times 10^{-4} with the input constant $\beta_{\rm max}$ in order to give acceptable time-limited wave growth and good directional fetch-limited growth as described by Ardhuin et al. (2007). As noted in this previous work, although similar fetch-limited growth are possible with almost any value of $\beta_{\rm max}$, a reasonable mean direction in slanting fetch conditions (Fig. 2.b) essentially selects the range of possible values of β_{max} . Here the mean directions at the observed peak frequency are still biassed by about 25° towards the alongshore direction with parameterizations proposed here, which is still less that the 50° obtained with the weaker Tolman and Chalikov (1996) source terms (Ardhuin et al. 2007, figure 11). A relatively better fit is obtained with the parameterization by Bidlot et al. (2005), hereinafter BAJ. This is likely due due to either the stronger wind input or the weaker dissipation at the peak. It is likely that both features of the BAJ parameterization are more realistic.

An equilibrium sea-state, achieved by most models for long durations with steady wind and infinite fetch, and often compared with the Pierson and Moskowitz (1964) spectrum, is largely controlled by the balance between the non-linear flux of energy to low frequencies and the wind output term, as discussed below. Figure 3 shows the fetch-limited growth in wave energy of various parameterizations. We repeat here the sensitivity test to the presence of swell, already displayed in Ardhuin et al. (2007). Whereas the 1 m swell causes an unrealistic doubling of the wind sea energy at short fetch in the BAJ parameterization, the new parameterizations, just like the one by van der Westhuysen et al. (2007), are by design insensitive to swell (not shown).

The dissipation S_{turb} due to wave-turbulence interactions is expected to be much weaker (Ardhuin and Jenkins 2006) and will be neglected here.

Finally, following the analysis by Filipot et al. (2009), the threshold B_r is corrected for shallow water, so that B'/B_r in different water depths corresponds to the same ratio of the root mean square orbital velocity and phase speed. For periodic and irrotational waves, the orbital velocity increases much more rapidly than the wave height as it approaches the breaking limit. Further, due to nonlinear distortions in the wave profile in shallow water, the height can be twice as large as the height of linear waves with the same energy. In order to express a relevant threshold from the elevation variance, we consider the slope $kH_{lin}(kD)$ of an hypothetical linear wave that has the same energy as the wave of maximum height. In deep water, $kH_{\rm lin}(\infty) \approx 0.77$, and for other water depths we thus correct B_r by a factor $(kH_{\rm lin}(kD)/H_{\rm lin}(\infty))^2$. Using streamfunction theory (Dalrymple 1974), a polynomial fit as a function of $Y = \tanh(kD)$ gives

$$B'_{r} = B_{r}Y\left[M_{4}Y^{3} + M_{3}Y^{2} + M_{2}Y + M_{1}\right].$$
 (13)

such that $B'_r = B_r$ in deep water. The fitted constants are $M_4 = 1.3286$, $M_3 = -2.5709$, $M_2 = 1.9995$ and $M_1 = 0.2428$. Although this behaviour is consistent with the variation of the depth-limited breaking parameter γ derived empirically by Ruessink et al. (2003), the resulting dissipation rate is not yet expected to produce realistic results for surf zones because no effort was made to verify this aspect. This is the topic of ongoing work, outside of the scope of the present paper.

The cumulative breaking term $S_{\rm bk,cu}$ represents the smoothing of the surface by big breakers with celerity C' that wipe out smaller waves of phase speed C. Due to uncertainties in the estimation of this effect in the observations of Young and Babanin (2006), we use the theoretical model of Ardhuin et al. (2009b). Briefly, the relative velocity of the crests is the norm of the vector difference, $\Delta_C = |\mathbf{C} - \mathbf{C}'|$, and the dissipation rate of short wave is simply the rate of passage of the large breaker over short waves, i.e. the integral of $\Delta_C \Lambda(\mathbf{C}) d\mathbf{C}$, where $\Lambda(\mathbf{C}) d\mathbf{C}$ is the length of breaking crests per unit surface that have velocity components between C_x and $C_x + dC_x$, and be-tween C_y and $C_y + dC_y$ (Phillips 1985). Because there is no consensus on the form of Λ (Gemmrich et al. 2008), we prefer to link Λ to breaking probabilities. Based on Banner et al. (2000, figure 6, $b_T = 22 (\varepsilon - 0.055)^2$), and taking their saturation parameter ε to be of the order of $1.6\sqrt{B'(f,\theta)}$, the breaking probability of dominant

waves waves is approximately

$$P = 56.8 \left(\max\{\sqrt{B'(f,\theta)} - \sqrt{B'_r}, 0\} \right)^2.$$
(14)

However, because they used a zero-crossing analysis, for a given wave scale, there are many times when waves are not counted because the record is dominated by another scale: in their analysis there is only one wave at any given time. This tends to overestimate the breaking probability by a factor of 2 (Filipot et al. 2009), compared to the present approach in which we consider that several waves (of different scales) may be present at the same place and time. We shall thus correct for this effect, simply dividing P by 2.

With this approach we define the spectral density of crest length (breaking or not) per unit surface $l(\mathbf{k})$ such that $\int l(\mathbf{k}) dk_x dk_y$ is the total length of all crests per unit surface, with a crest being defined as a local maximum of the elevation in one horizontal direction. In the wavenumber vector spectral space we take

$$l(\mathbf{k}) = 1/(2\pi^2 k) \tag{15}$$

which is equivalent to a constant in wavenumberdirection space $l(k, \theta) = 1/(2\pi^2)$. This number was obtained by considering an ocean surface full of unidirectional waves, with one crest for each wavelength $2\pi/k$ for each spectral interval $\Delta k = k$, e.g. one crest corresponding to spectral components in the range 0.5 k to 1.5 k. This potential number of crests is doubled by the directionality of the sea state. These two assumptions have not been verified and thus the resulting value of $l(\mathbf{k})$ is merely an adjustable order of magnitude.

Thus the spectral density of breaking crest length per unit surface is $\Lambda(\mathbf{k}) = l(\mathbf{k})P(\mathbf{k})$. Assuming that any breaking wave instantly dissipates all the energy of all waves with frequencies higher by a factor r_{cu} or more, then the cumulative dissipation rate is simply given by the rate at which these shorter waves are taken over by larger breaking waves, times the spectral density, namely

$$S_{\mathrm{bk,cu}}(f,\theta) = -C_{\mathrm{cu}}F(f,\theta) \int_{f' < r_{\mathrm{cu}}f} \Delta_C \Lambda(\mathbf{k}') \mathrm{d}\mathbf{k}',$$
(16)

where r_{cu} defines the maximum ratio of the frequencies of long waves that will wipe out short waves.

We now obtain Λ by extrapolating eq. (14) to higher frequencies, gives the source term,

$$S_{\rm bk,cu}(f,\theta) = -C_{\rm cu}F(f,\theta)\int_{0}^{r_{\rm cu}f}\int_{0}^{2\pi}\frac{28.4}{\pi} \times \max \left\{\sqrt{B(f',\theta')} - \sqrt{B_{r}},0\right\}^{2} \frac{\Delta_{C}}{C'_{g}}\mathrm{d}\theta'\mathrm{d}f',$$
(17)

We shall take $r_{\rm cu} = 0.5$, and $C_{\rm cu}$ is a tuning coefficient expected to be of order 1, which also corrects for errors in the estimation of l.

This generic form of the source terms produces markedly different balances for both mature and fully developped seas. For mature seas, without cumulative ef-



FIG. 4. Academic test case over a uniform ocean with a uniform 10 m s⁻¹ wind starting from rest, after 8 hours of integration, when $C_p/U_{10} \approx 1$. Source term balances given by the parameterization BAJ, and the parameterizations proposed here with the successive introduction of the cumulative breaking and the wind sheltering effects with the parameters C_{cu} and s_u . For BAJ, a diagnostic f^{-5} tail is applied above 2.5 the mean frequency. In order to make the high frequency balance visible, the source terms are multiplied by the normalization function $M(f) = \rho_w C/(\rho_a E(f)\sigma U_{10})$. The result with the parameterization of Tolman and Chalikov (1996) is also given for reference.

(17) fect, figure (4) shows that a balance is possible that gives roughly the same energy level and wind input term up to 0.4 Hz as the BAJ parameterization. However, the balance in the tail results in energy level decreasing slower than f^{-4} as the dissipation is too weak compared to the input, and thus the nonlinear energy flux is reversed, pumping energy from the tail to higher frequencies.

The introduction of a strong cumulative term (TEST437) allows a balance at roughly the same energy level. However, with the present formulation this will lead to too strong a dissipation at high frequency for higher winds. The introduction of the sheltering effect via the parameter s_u (details in section 2d) is designed to get a balance with a weaker cumulative effect. Clearly, for relatively young waves the energy levels at the spectral peak are lower with $s_u = 0.4$ (TEST441) than in other runs, this is largely due to a reduced feedback of the wave age on the wind stress via the τ_w/τ term in eq. (22).

The most important qualitative feature is the lack of a regular predefined shape for the normalized dissipation term $S_{oc}(f)/E(f)$. Whereas the shape given by $\delta k + (1 - \delta)k^2$ is clearly visible in BAJ (with extremely high dissipation rates if one considers high frequencies), and the low to high frequency dissipation transition at 2 f_p is evident in TC, the shape of the new dissipation rates are completely dictated by the local spectral saturation level. This leads to a relatively narrow peak of dissipation right above the spectral peak, where saturation is strongest.

This feature helps to produce the realistic spectral shapes near the peak, with a steeper low frequency side and and a more gentle high frequency side, contrary to the backward facing spectra produced by BAJ and TC. However, this localized strong relative dissipation is hard to reconcile with time and spatial scales of breaking events of the order of the wave period and a fraction of the wavelength: each single wave that breaks contains the same spectral components over a frequency range that is inversely proportional to its lifetime. There is no physical reason why a breaking event would take much more energy, relatively speaking, from the spectral band 1.1 to $1.2f_p$ than from 1.2 to $1.3f_p$. The factor 2 difference in the relative dissipation rates found here thus appears unrealistic. This strong relative dissipation at the peak (50% higher than in BAJ) is one important factor that gives a slower growth of the wave spectrum in TEST441 compared to BAJ.

Now considering the fully developped conditions illustrated by figure 5, a reasonable balance is obtained for $C_{\rm cu} = 1$. Compared to the source term balance with BAJ. Figure 6 shows that the nonlinear interactions are much smaller at high frequency, essentially because the spectrum approaches a f^{-4} shape, for which S_{nl} goes to zero, whereas it decreases even faster than f^{-5} with BAJ when the tail is left to evolve freely. However, for strongly forced conditions, the dominant waves break frequently, and $C_{\rm cu} = 1$ reduces the energy level in the tail below observed levels. This effect can be seen by considering satellite-derived mean square slopes (Fig. 8), or high moments of the frequency spectrum derived from buoy data.

That effect can be mitigated by decreasing C_{cu} or increasing r_{cu} , so that dominant breaking waves will only



FIG. 5. Same as figure (4) but after 48 h of integration and without normalization of the source terms. Source term balances given by the parameterization BAJ, and the parameterizations proposed here with the successive introduction of the cumulative breaking and the wind sheltering effects with the parameters C_{cu} and s_u . For BAJ, a diagnostic f^{-5} tail is applied above 2.5 the mean frequency.

wipe out much smaller waves. Instead, and because the wind to wave momentum flux was apparently too high in high winds, we chose to introduce one more degree of freedom, allowing a reduction of the wind input at high frequency.



FIG. 6. Values of the spectral saturation B_0 for the cases presented in figure 5.

d. Wind input

The wind input parameterization is thus adapted from Janssen (1991) and the following adjustments performed by Bidlot et al. (2005, 2007a). The full wind input source term reads

$$S_{\rm in}(f,\theta) = S_{\rm in}^{\rm up}(f,\theta) + \frac{\rho_a}{\rho_w} \frac{\beta_{\rm max}}{\kappa^2} e^Z Z^4 \left(\frac{u_\star}{C}\right)^2 \\ \times \max\left\{\cos(\theta - \theta_u), 0\right\}^p \sigma F(f,\theta)$$

where β_{max} is a non-dimensional growth parameter (constant), κ is von Kármán's constant. In the present implementation the air/water density ratio is constant. The power of the cosine is taken constant with p = 2. We define the effective wave age $Z = \log(\mu)$ where μ is given by Janssen (1991), and corrected for intermediate water depths, so that

$$Z = \log(kz_1) + \kappa / \left[\cos\left(\theta - \theta_u\right) \left(u_\star / C + z_\alpha \right) \right], \quad (19)$$

where z_1 is a roughness length modified by the wavesupported stress τ_w , and z_α is a wave age tuning parameter. z_1 is implicitly defined by

$$U_{10} = \frac{u_{\star}}{\kappa} \log\left(\frac{z_u}{z_1}\right) \tag{20}$$

$$z_0 = \min\left\{\alpha_0 \frac{\tau}{g}, z_{0,\max}\right\}$$
(21)

$$z_1 = \frac{z_0}{\sqrt{1 - \tau_w/\tau}}.$$
 (22)

The maximum value of z_0 was added to reduce the unrealistic stresses at high winds that are otherwise given by the standard parameterization. For example, $z_{0,\text{max}} = 0.0015$ is equivalent to setting a maximum wind drag coefficient of 2.5×10^{-3} . For the TEST441 parameterization, we have adjusted $z_{\alpha} = 0.006$ and $\beta_{\text{max}} = 1.52$ (Fig. 7).

An important part of the parameterization is the calculation of the wave-supported stress τ_w , which includes the resolved part of the spectrum, as well as the growth of an assumed f^{-5} diagnostic tail beyond the highest frequency. This parameterization is highly sensitive to the high frequency part of the spectrum since a high energy level there will lead to a larger value of z_1 and u_{\star} , which gives a positive feedback and reinforces the energy levels.

In order to allow a balance with the saturation-based dissipation, an ad hoc and optional reduction of u_{\star} is implemented in order to allow a balance with a saturation-based dissipation. This correction also reduces the drag coefficient at high winds. Essentially, the wind input is reduced for high frequencies and high winds, loosely following Chen and Belcher (2000). This is performed by replacing u_{\star} is eq. (18) with a frequency-dependent $u'_{\star}(f)$ defined by

$$(u'_{\star})^{2} = u_{\star}^{2} (\cos \theta_{u}, \sin \theta_{u}) - |s_{u}| \int_{0}^{k} \int_{0}^{2\pi} \frac{S_{in} (f', \theta)}{C} (\cos \theta, \sin \theta) \, \mathrm{d}f' \mathrm{d}\theta,$$
(23)

where the sheltering coefficient $|s_u| \sim 1$ can be used to tune the stresses at high winds, which would be largely overestimated for $s_u = 0$. For $s_u > 0$ this sheltering is also applied within the diagnostic tail, which requires the estimation of a 3-dimensional look-up table for the high frequency stress. The shape of the new wind input is illustrated in figure 7 for fully developped seas.

3. Consequences of the source term shape

The presence of a cumulative dissipation term allows a different balance in the spectral regions above the peak, where an equilibrium range with a spectrum proportional to f^{-4} develops (Long and Resio 2007), and in the high frequency tail were the spectrum decays like f^{-5} or possibly a little faster. The spectral level in the range 0.2 to 0.4 Hz was carefully compared against buoy data, and was found to be realistic. In particular we have investigated the systematic variation of spectral moments

$$m_n(f_c) = \int_0^{f_c} f^n E(f) \mathrm{d}f.$$
 (24)

with n = 2,3 and 4, and cut-off frequencies in the range 0.2 to 0.4 Hz. Such moments are relevant to a variety of applications. Ardhuin et al. (2009b) investigated the third moment, which is proportional to the surface Stokes drift in deep water, and found that buoy data are very well represented by a simple function, which typically explains 95% of the variance,

$$m_{3}(f_{c}) \simeq \frac{5.9gU_{10}}{(2\pi)^{3}} \times 10^{-4} \left[1.25 - 0.25 \left(\frac{0.5}{f_{c}} \right)^{1.3} \right] \\ \times \min \{ U_{10}, 14.5 \} + 0.027 \left(H_{s} - 0.4 \right),$$
(25)



FIG. 7. Incremental adjustements to the wind-wave interaction source term S_{atm} , going from the BAJ form to the one used in TEST441. The effect of modifying a new parameter are clearly seen. The reduction of z_{α} from 0.011 to 0.006 strongly reduces the low frequency input, which is probably overestimated in BAJ when average (20%) levels of gustiness are considered: now the wind input goes to zero for f = 0.13, which corresponds to $C/U_{10} = 0.83$, whereas it is still significant at that wave age in the BAJ parameterization. As a result the much lower input level need a readjustment, bu increasing β_{max} to 1.52. Yet, this high value of β_{max} produces very high wind stress values and thus a very strong high frequency input. This is where the sheltering term $s_u = 1$ allows a decent balance at high frequency. Finally, the addition of the air-sea friction term that gives swell dissipation produces a significant reduction of the input to the widn sea at f = 0.25 Hz. It is questionable whether this mechanism also applies in the presence of the critical layer for those waves. This matter clearly requires more theoretical and experimental investigation.

where f_c is in Hertz, U_{10} is in meters per second, and H_s is in meters.

This relationship is well reproduced in hindcasts using $C_{cu} = 0.4$ and $s_u = 1$, while the BAJ source terms give almost a a constant value of m_3 when H_s varies and U_{10} is fixed (Ardhuin et al. 2009b). Here we also consider the fourth moment m_4 which, for linear waves, is proportional to a surface mean square slope filtered at the frequency f_c . Figure 8 shows that for any given wind speed mss_C increases with the wave height (Gourrion et al. 2002), whereas this is not the case of m_4 in the BAJ parameterization, or, for very high winds, when $C_{\rm cu}$ is too strong. In the case of BAJ, this is due to the $(k/k_r)^2$ part in the dissipation term (eq. 2), which plays a role similar to the cumulative term in our formulation. For $C_{cu} = 1$ and $s_u = 0$, the cumulative effect gets too strong for wind speeds over 10 m s⁻¹, in which case m_4 starts to decrease with increasing wave height, whereas for high winds and low (i.e. young) waves, the high frequency tail is too high and m_4 gets as large as 6%, which is unrealistic. It thus appears, that the high frequency tail, for $s_u = 0$, responds too much to the wind, hence our use of $s_u = 1$ in the TEST441 combination.

This interpretation of the model result assumes that

the high frequency part of the spectrum can be simply converted to a wavenumber spectrum, using linear wave theory. This is not exactly the case as demonstrated by Banner et al. (1989). Also, there is no consensus on the nature of the spectrum modelled with the energy balance equation but, since non-resonant nonlinearities are not represented, the modelled spectra are expected to be more related to Lagrangian buoy measurements, rather than Eulerian measurements. This matter is left for further studies, together with a detailed interpretation of altimeter radar cross sections. Although it covers much less data, the analysis of m_4 obtained from buoy heave spectra produces results similar to figure 8.



FIG. 8. Variation of the surface mean square slope estimated as either $0.64/\sigma_0$ using the C-band altimeter on board JASON-1, after the correction of a 1.2 dB bias in the JASON data, or by integration of modelled spectra from 0 to 0.72 Hz, with either the $C_{\rm cu} = 0.4$ and $s_u = 1$ parameterization (TEST441) or the parameterization by BAJ. For modelled values a constant 0.011 is added to account for the short waves that contribute to the satellite signal and that are not resolved in the model. This saturated high frequency tail is consistent with the observations of Vandemark et al. (2004). The original 1 Hz data from JASON is subsampled at 0.5 Hz and averaged over 10 s, namely 58 km along the satellite track. The same averaging is applied to the wave model result, giving the 393382 observations reported here, for the first half year of 2007.

4. Verification

In order to provide simplified measures of the difference between model time series X_{mod} and observations X_{obs} we use the following definitions for the normalized root mean square error (NRMSE),

$$NRMSE(X) = \sqrt{\frac{\sum (X_{obs} - X_{mod})^2}{\sum X_{obs}^2}} \qquad (26)$$

the normalized bias,

$$NB(X) = \sqrt{\frac{\sum X_{obs} - X_{mod}}{\sum X_{obs}}},$$
 (27)

and Pearson's linear correlation coefficient,

$$r(X) = \frac{\sum \left(X_{\rm obs} - \overline{X}_{\rm obs}\right) \left(X_{\rm mod} - \overline{X}_{\rm mod}\right)}{\sqrt{\sum \left(X_{\rm obs} - \overline{X}_{\rm obs}\right)^2 \left(X_{\rm mod} - \overline{X}_{\rm mod}\right)^2}},$$
(28)

where the overbar denotes the arithmetic average.

The normalisation of the errors allows a quantitative comparison between widely different sea state regimes. Because previous studies have often used (nonnormalized) RMSE we also provide RMSE values. In addition to the coastal fetch-limited case of SHOWEX, presented above, the parameterizations are calibrated on at the global scale and validated in two other cases.

a. Global scale results

We present here results for the entire year 2007, using a stand-alone 0.5° resolution grid, covering the globe from 80° south to 80° north. The model has actually been adjusted to perform well over this data set, but the very large number of observations (over 2 million altimeter collocation points) makes the model robust, and an independent validation on 2008 gives identical results. The interested reader may also look at the monthly reports for the SHOM model (e.g. Bidlot 2008), generated as part of the model verification project of the IOC-WMO Joint Commission on Oceanography and marine Meteorology (JCOMM), in which the TEST441 parameterization ($C_{cu} = 0.4$ and $s_u = 1$) is used, except for the Mediterranean where, the TEST405 has been preferred for its superior performance for younger seas. These SHOM models are ran in a combination of two-way nested grids (Tolman 2007). The monthly JCOMM reports include both analysis and forecasts, but, since they are produced in a routine setting, many SHOM calculations from December 2008 to June 2009 have been affected by wind field transfer problems.

Comparing model results for H_s to well-calibrated (Queffeulou and Croizé-Fillon 2008) altimeter-derived measurements provides a good verification of the model performance in a number of different wave climates. Figure (9) shows that, as expected, the important positive bias in the swell-dominated regions when using the BAJ parameterization, has been largely removed. This is essentially the signature of the specific swell dissipation that is parameterized in S_{out} . The largest bias pattern now appears in the southern ocean, reaching 30 cm in the Southern Atlantic. Although this bias is small compared to the local averaged wave height, it is rather strange when the model errors are plotted as a function of wave height in figure (10). Why would the model overestimate the Southern ocean waves but understimate the very large waves?

The structure of the large bias, also seen in model results with BAJ, is reminiscent of the observed pattern in iceberg distribution observed by Tournadre et al. (2008). These observed iceberg distributions are enough to give a cross-section for incoming waves of the order of 1 to 10% for a 250 km propagation length. Taking icebergs into account could actually reverse the sign of the bias. This matter will be investigated further elsewhere.

Also noticeable is a significant negative bias in the equatorial south Pacific, amplified from the same bias obtained with the BAJ parameterization. It is possible that the masking of subgrid islands (Tolman 2003) introduces a bias by neglecting shoreline reflections. This model defect could be exacerbated in this region by the very large ratio of shoreline length to sea area. This will also require further investigation. Finally, the negative biases for H_s on mid-latitude east coasts are reduced but still persist. It is well known that these areas are also characterized by strong boundary currents (Gulf Stream, Kuroshio, Agulhas ...) with warm waters that is generally conducive to wave amplification and faster wind-wave growth (e.g. Vandemark et al. 2001). Neither effect is included in the present calculation because the accuracy of both modelled surface currents and air-sea stability parameterizations are likely to be insufficient (Collard et al. 2008; Ardhuin et al. 2007).

The reduction of systematic biases clearly contributes to the reduction of r.m.s. errors, as evident in the equatorial east Pacific (Fig. 11). However, the new parameterization also brings a considerable reduction of scatter, with reduced errors even where biases are minimal, such as the trade winds area south of Hawaii, where the NRMSE for H_s can be as low as 5%. When areas within 400 km from continents are excluded, because the global model resolution may be inadequate, significant errors (> 12.5%), in yellow to red) remain in the northern Indian ocean, on the North American and Asian east coasts, the Southern Atlantic. The parameterizations TEST405, TEST437 and TEST441 produce smaller errors on average than BAJ. It is likely that the model benefits from the absence of swell influences on wind seas: swell in BAJ typically leads to a reduced dissipation and stronger wind wave growth. As models are adjusted to average sea state conditions, this adjustement leads to a reduced wind sea growth on east coasts where there is generally less swell.

Although much more sparse than the altimeter data, the in situ measurements collected and exchanged as part as the JCOMM wave model verification is much needed to constrain other aspects of the sea state. This is illustrated here with mean periods T_{m02} for data provided by the U.K. and French meteorological services, and peak periods T_p for all other sources. It is worth noting that the errors on H_s for in situ platforms are comparable to the errors against altimeter data.

With the BAJ parameterizations, the largest errors in the model results are the large biases on peak periods on the U.S. West coast (Fig. 12), by 1.2 to 1.8 s for most locations, and the understimation of peak periods



FIG. 9. Bias for the year 2007 in centimeters. The global 0.5 WWATCH model is compared to altimeters JASON, ENVISAT and GFO following the method of Rascle et al. (2008). The top panel is the result with the BAJ parameterization, and the bottom panel is the result with the $C_{cu} = 0.4$ and $s_u = 1$ (TEST441) parameterization.

on the U.S. East Coast. However, peak and mean periods off the European coasts were generally very well predicted. When using the TEST441 parameterization, the explicit swell dissipation reduces the bias on periods on the U.S. West coast, but the problem is not completely solved, with residual biases of 0.2 to 0.4 s. This is consistent with the validation using satellite SAR data (Fig. 1), that showed a tendency to underpredict steep swells near the storms and overpredict them in the far field. A simple increase of the swell dissipation was tested but it tended to deteriorate the results on other parameters. On European coasts, despite a stronger bias, the errors on T_{m02} are particularly reduced. Again, this reduction of the model scatter can be largely attributed to the decoupling of swell from windsea growth.

The general performance of the parameterizations is synthetized in table 1. It is interesting to note that the parameterization TEST405 that uses a diagnostic tail for 2.5 times the mean frequency gives good results in terms of scatter and bias even for parameters related to short waves (m_3, m_4) . This use of diagnostic tail is thus a good pragmatic alternative to the more costly explicit resolution of shorter waves, which requires a smaller adapatative timestep. The diagnostic tail generally mimics the effect of the cumulative effect. Yet, the parameterization TEST441 demonstrates that it is possible to obtain slightly better results with a free tail. The normalized biases indicated for the mean square slopes are only relative because of the approximate calibration of the radar cross section. They show that the BAJ parameterization, and to a lesser extent the use of a f^{-5} tail, produce energy levels that are relatively lower at high frequency.

b. Lake Michigan

At the global scale, the sea state is never very young,



FIG. 11. Normalized RMSE for the year 2007 in percents. The global 0.5 WWATCH model is compared to altimeters JASON, ENVISAT and GFO following the method of Rascle et al. (2008). The top panel is the result with the BAJ parameterization, and the bottom panel is the result with the $C_{cu} = 0.4$ and $s_u = 1$ (TEST441) parameterization.

and it is desirable to also verify the robustness of the parameterization in conditions that are more representative of the coastal ocean. We thus follow the analysis of wave model performances by Rogers and Wang (2007), hereinafter RW2007, and give results for the Lake Michigan, representative of relatively young waves. The model was ran with parameterizations BAJ, TC, TEST437 and TEST441 over the same time frame as investigated by RW2007 (fall 2002). The model setting and forcing fields are identical to the one defined by (Rogers et al. 2003), with a 2 km resolution grid, a 10° directional resolution, and a wind field defined from in situ observations.



FIG. 12. Statistics for the year 2007 based on the JCOMM verification data base (Bidlot et al. 2007b). Bais (a,d) and NRMSE (b,c) for T_p or T_{m02} at in situ locations using the BAJ or the proposed TEST441 (T_p is shown at all buoys except U.K. and French buoys for which T_{m02} is shown). The different symbols are only used to help distinguish the various colors and do not carry extra information.

The models are run from September 1 to November 14, 2002. The results at the National Data Buoys Center's buoy 45007 are compared to the measurements.

Using the directional validation method proposed by these authors, the TC parameterization understimates the directional spread σ_{θ} by 5° degrees in the range 0.9 to 1.8 f_p , and even more at higher frequencies. The understimation with BAJ is about half, and the TEST441 and TEST437 overpredict the directional spread by about 5 and 8° in the range 1 to $1.6f_p$, and less so for higher frequencies. It thus appears that the broadening introduced to fit the SHOWEX 1999 observations is not optimal for other situations. A similar positive bias on directional spread is also found in global hindcasts.



FIG. 10. Wave model errors as a function of H_s . All model parameterizations are used in a global WWATCH model settings using a 0.5° resolution. The model output at 3h intervals is compared to JASON, ENVISAT and GFO following the method of Rascle et al. (2008). Namely, the altimeter 1 Hz Ku band estimates of H_s are averaged over 1^circ. After this averaging, the total number of observations is 2044545. The altimeter estimates are not expected to be valid for H_s larger than about 12 m, due to the low signal level and the fact that the waveform used to estimate H_s is not long enough in these cases.

In terms of H_s , the TEST441 and TEST437 yield minor understimations, but give generally better results compared to observations than the other parameterizations (table 2). It thus appears that for such young seas, the directional spreading of the parameterization could be improved, but the energy content of various frequency

Table 1. Model accuracy for measured wave parameters over the oceans in 2007. mss data from JASON 1 corresponds to January to July 2007 (393382 co-located points). Unless otherwise specified by the number in parenthesis, the cut-off frequency is take to be 0.4 Hz, C stands for C-band. The normalized bias (NB) is defined as the bias divided by the r.m.s. observed value, while the scatter index (SI) is defined as the r.m.s. difference between modeled and observed values, after correction for the bias, normalized by the r.m.s. observed value, and r is Pearson's correlation coefficient. These global averages are area-weighted, and the SI and NRMSE are the area-weighted averages of the local SI and NRMSE

	BAJ	TEST	TEST	TEST
		405	437	441
H_s				
NB(%)	-2.1	-0.8	0.2	-1.23
SI(%)	11.8	10.5	10.6	10.4
NRMSE(%)	13.0	11.5	11.6	11.3
$m_4(C)$				
NB(%)	-16.1	-4.9	-2.3	-2.5
SI(%)	10.7	9.1	9.1	9.1
r	0.867	0.925	0.931	0.939
T_p				
NRMSE(%)	24.1	19.0	19.4	18.2
T_{m02}				
NRMSE(%)	7.6	6.9	6.6	6.7
m_3				
NB(%)	-14.6	1.7	-2.3	-2.4
SI(%)	20.6	12.6	14.8	12.6
NRMSE(%)	25.3	13.1	13.1	12.8
r	0.934	0.971	0.961	0.973

bands, and as a result the mean period, are reproduced with less scatter than with previous parameterizations.

c. Hurricane Ivan

Although the global hindcast does contain quite a few extreme events, with significant wave heights up to 17 m, these were obtained with a relatively coarse wave model grid and wind forcing $(0.5^{\circ}$ resolution and 6-h timestep) that is insufficient to resolve small storms such as tropical cyclones (Tolman and Alves 2005). Hurricane waves do share many similarities with more usual sea states (Young 2005), but the high winds and their rapid rotation are particularly challenging for numerical wave models. It is thus necessary to verify that the new source functions perform adequately under extreme wind conditions. A simulation of Hurricane Ivan (Gulf of Mexico, September 2004) is chosen for this purpose because it was extensively measured (e.g. Wang et al. 2005) and hindcasted.

Winds for this simulation are based on gridded surface wind analyses created by NOAA's Hurricane Research Division (HRD). These analyses are at three hour intervals, which for a small, fast-moving weather system is temporally too coarse to provide directly to the wave model. Therefore, as an intermediate step, fields are reprocessed to 30 minute intervals, with the storm position updated at each interval (thus, semi-Lagrangian

Table 2. Model-data comparison at buoy 46005, for four frequency bands. Statistics are given for equivalent significant wave heights in the bands $0.5f_p < f < 0.8f_p$ (band1), $0.8f_p < f < 1.2f_p$ (band2), $1.2f_p < f < 2f_p$ (band3) $2f_p < f < 3f_p$ (band4). The KHH n = 2 run corresponds to the dissipation parameterization defined by (Rogers et al. 2003) based on (Komen et al. 1984) and ran in the SWAN code. For the peak frequency band, statistics are also given for the directional spread σ_{θ} .

	BAJ	TC	TEST	TEST	KHH
			437	441	n=2
band 1					
SI(%)	76	71	77	82	84
band 2 H_s					
SI(%)	16	19	15	15	15
band 2 σ_{θ}					
SI(%)	22	24	30	30	25
bias (°)	-0.4	-1.6	2.3	2.6	1.2
band 3 H_s					
SI(%)	18	26	17	17	16
band 4 H_s					
SI(%)	20	32	18	17	19
H_s bias (m)	-0.03	-0.11	-0.02	-0.02	0.02
r	0.95	0.94	0.96	0.96	0.96
SI(%)	19	25	18	18	18
T_{m02}					
bias (s)	0.02	39	-0.05	-0.05	0.11
r	0.89	0.87	0.90	0.90	0.90
SI(%)	0.10	0.14	9	9	10

interpolation). The wind speeds are reduced by factor 1/1.11 to convert from maximum sustained gust to hourly mean. The HRD winds do not cover the entire computational domain. For areas falling outside the domain, the nearest NDBC buoy wind observation is used. This produces some non-physical spatial discontinuities in the wind field, but these are smoothed in the wave model integration, and in any event, only affect weaker wind seas far from the storm center.

Bathymetry is taken from the Naval Research Laboratory's 2 minute resolution database, DBDB2, coarsened to the computational grid resolution (0.1 deg). The directional resolution is 10°, and the frequency range is limited to 0.0418-0.4117 Hz. The model was ran from September 13 to September 16 2004. Model results are illustrated by figure 13.

Model runs with parameterizations BAJ, TEST437 and TEST441 give very similar results close to the observations, except for the highest waves ($H_s > 13$ m at buoy 42040) where TEST437 and TEST441 give slightly smaller values. Results with the TC parameterization are generally lower in terms of H_s than all these parameterizations that share a Janssen-type input. It appears that the new source term perform similarly to BAJ and are able to reproduce such young waves and severe sea states.

Because the wind forcing enters the wave model through a wind stress parameterized in a way that may not apply to such conditions, it is worthy to re-examine some



FIG. 13. Time series of model and buoy significant wave height (top) and partial wave height (bottom, for f < 0.06 Hz), during the passage of Hurrican Ivan, at buoy 42040. The 10-m discus buoy was capized by waves and could not record waves after 16 September.

choices made above. In particular the surface roughness was allowed to exceed 0.002 in TEST441b, which resulted in better estimates of H_s . Lifting this constraint shows that, for these very high winds, the wind sheltering effect plays a similar role to the limitation of the roughness to $z_{0 \max}$, with the difference that it tends narrow the wind input spectrum (Fig. 7). This narrower wind input has a limited effect of the wind stress and H_s , but is has a noticeable effect on the spectral shape. This is illustrated by the low frequency energy that appears to be strongly overestimated before the peak of the storm for TEST441b. In general the new parameterizations provide results that are as reasonable as those of previous parameterizations, given the uncertainty of the wind forcing. Further validation for this and other cases will certainly require a careful verification

5. Conclusions

A set of parameterization for the dissipation source terms of the wave energy balance equation have been proposed, based on know properties of swell dissipation and wave breaking statistics. This dissipation includes an explicit nonlinear swell dissipation and a wave breaking parameterization that contains a cumulative term, representing the dissipation of short waves by longer breakers, and different dissipation rates for different directions. These dissipation parameterizations have been combined with a modified form of the wind input proposed by Janssen (1991), in which the questionable gustiness parameter z_{α} has been reduced, and the general shape of the wind input has been significantly modified. The resulting source term balance is thus markedly different from the previous proposed forms, with a near-balance for very old seas between the air-sea friction term, that dissipates swell, and the nonlinear energy flux to low frequencies. Also, the

wind input is concentrated in a narrower range of frequencies.

For younger seas the wind input is relatively weaker than given by Janssen (1991) but stronger than given by Tolman and Chalikov (1996) (TC). However, the dissipation at the peak is generally stronger because it is essentially based on a local steepness and these dominant waves are the steepest in the sea state. As a result the short fetch growth is relatively weaker than with the source term combination proposed by Bidlot et al. (2007a) (BAJ). The choice of parameters tested here tend to produce broader directional spectra than observed in the Lake Michigan and global hindcasts, and slanting fetch directions that are too oblique relative to the wind (Fig. 2). In this respect the new source terms are intermediate between BAJ and TC.

Another likely defect comes from the definition of the saturation level used to define the breaking-induced dissipation. Here, as in the work by van der Westhuysen et al. (2007), the saturation is local in frequency space, whereas wave breaking is naturally expected to have a relatively broad impact due to its localization in space and time(Hasselmann 1974). This is expected to produce an overestimaton of the energy just below the peak, and an understimation at the peak of the saturation spectrum. These effects likely contribute to the persistent overestimation of low frequency energy in the model.

In spite of these defects, the new parameterization produces robust results and clearly outperform the Bidlot et al. (2007a) parameterization in global hindcasts, whether one considers dominant wave parameters, H_s , T_{m02} and T_p or parameters sensitive to the high frequency content, such as the surface Stokes U_{ss} drift or the mean square slope. At global scales, errors on H_s , T_p and U_{ss} are - on average - reduced by 15, 25 and 50% relative to those obtained with the parameterization by Bidlot et al. (2007a).

Because our intention was only to demonstrate the capability of new dissipation parameterizations and the resulting source term balances, we have not fully adjusted the 18 parameters that define the deep water parameterizations, compared to about 9 with Bidlot et al. (2007a). The results presented here are thus preliminary in terms of model performance, which is why the parameterizations are still given temporary names like TEST441. As illustrated by the hurrican Ivan hindcast, some parameters, such as $z_{0 \text{ max}}$, may turn out to be unnecessary.

Because 5 of the extra parameters define the air-sea friction term that produces swell dissipation, and 2 define the cumulative breaking term, it is feasible to define a systematic adjustement procedure that should produce further improvements by separately adjusting swell, wind sea peak, and high frequency properties. In particular the directional distribution may be improved by making the dissipation term more isotropic (i.e. taking $\delta_d > 0.3$) or modifying the definition of the saturation parameter B' in equation (10). In part II we shall further investigate the response of the wave field to varying currents, from

global scales to regional tidal currents. It is particularly expected that the steepening will produce more more dissipation due to breaking as envisaged by Phillips (1984).

Obviously, it is well known that the Discrete Interaction Approximation used here to compute the non-linear interactions is the source of large errors, and further calculations, will be performed using a more accurate estimation of these interactions in part III.

Acknowledgments. This research would not have been possible without the dedication of Hendrik Tolman, Henrique Alves, and Arun Chawla in putting together the core of the WAVEWATCH-IIITM code. Florent Birrien performed the integration of Aaron Roland's routines into the WWATCH framework. Wind and wave data were kindly provided by ECMWF, Météo-France, and the French Centre d'Etudes Techniques Maritimes Et Fluviales (CETMEF). The SHOM buoy deployments were managed by David Corman with precious help from Guy Amis. Wave data were kindly provided by the U.S. Navy, ESA and CNES, and the many *in situ* contributors to the JCOMM (WMO-IOC) exchange program coordinated by Jean-Raymond Bidlot.

APPENDIX A Parameter settings

All parameters defining the dissipation source function and their numerical values are listed in table A1 for the wind-wave interaction term S_{atm} and table A2 for the wave-ocean interaction term $S_{\rm oc}$. We also recall that the nonlinear coupling coefficient (variable NL-PROP in WWATCH) is set to 2.78×10^7 in all cases, except for the two parameterizations mostly used here, with $C_{\rm nl} = 2.5 \times 10^7$ in TEST437 and TEST441. Although the best performance for most parameters is obtained with the TEST441 settings, its underestimation of extreme sea states may be a problem in some applications for which the TEST437 may be preferred. A full tuning of the model has not been tried yet and it is possible that a simple adjustment of $\beta_{\max} C_{cu}$, r_{cu} and s_u may produce even better results. Finally, these parameters have been mostly adjusted for deep water conditions using ECMWF winds. Using other sources of winds for large scale applications may require a retuning of the wind source function, which can be best performed by a readjustment of $\beta_{\rm max}$.

REFERENCES

- Alves, J. H. G. M. and M. L. Banner, 2003: Performance of a saturationbased dissipation-rate source term in modeling the fetch-limited evolution of wind waves. J. Phys. Oceanogr., 33, 1274–1298.
- Ardhuin, F., B. Chapron, and F. Collard, 2009a: Observation of swell dissipation across oceans. *Geophys. Res. Lett.*, 36, L06607.
- Ardhuin, F., F. Collard, B. Chapron, P. Queffeulou, J.-F. Filipot, and M. Hamon, 2008a: Spectral wave dissipation based on observations: a global validation. *Proceedings of Chinese-German Joint Symposium on Hydraulics and Ocean Engineering, Darmstadt, Germany*, 391–400. http://www.comc.ncku.edu.tw/joint/joint2008/papers/69.pdf

Parameter	variable in WWATCH.	WAM-Cycle4	BAJ	TEST405	TEST437	TEST441
α_0	ALPHA0	0.01	0.0095	idem	idem	idem
β_{\max}	BETAMAX	1.2	1.2	1.55	1.52	idem
z_{lpha}	ZALP	0.0110	0.0110	0.006	idem	idem
$z_{0 \max}$	ZOMAX	N.A.	N.A.	0.002	idem	idem
s_u	TAUWSHELTER	0.0	0.0	0.0	0.0	1.0
s_0	SWELLFPAR	0	0	3	idem	idem
s_1	SWELLF	0.0	0.0	0.8	idem	idem
s_2	SWELLF2	0.0	0.0	-0.018	idem	idem
s_3	SWELLF3	0.0	0.0	0.015	idem	idem
Re_{c}	SWELLF4	0.0	10^{5}	idem	idem	idem
$C_{\rm dsv}$	SWELLF5	0.0	0.0	1.2	idem	idem
z_r	ZORAT	0.0	0.0	0.04	idem	idem

Table A1. Wind-wave interaction parameters as implemented in version 3.14-SHOM of the WAVEWATCH III code, and values used in the tests presented here. In WWATCH, all parameters are accessible via the SIN3 namelist. All of these parameters are included in version 3.14 of WWATCH. s_0 is a switch that, if nonzero, activates the calculation of S_{out} .

Parameter	variable in WWATCH	WAM4	BAJ	TEST405	TEST437	TEST441	TEST443
$C_{\rm ds}$	SDSC1	-4.5	-2.1	0.0	idem	idem	idem
p	WNMEANP	-0.5	0.5	0.5	idem	idem	idem
$p_{\rm tail}$	WNMEANPTAIL	-0.5	0.5	0.5	idem	idem	idem
$f_{\rm FM}$	FXFM3	2.5	2.5	2.5	9.9	idem	idem
δ_1	SDSDELTA1	0.5	0.4	0.0	idem	idem	idem
δ_2	SDSDELTA2	0.5	0.6	0.0	idem	idem	idem
$C_{\rm ds}^{\rm sat}$	SDSC2	0.0	0.0	-2.2×10^{-5}	-2.2×10^{-5}	idem	idem
$C_{ m lf}$	SDSLF	1.0	1.0	0.0	idem	idem	idem
$C_{ m hf}$	SDSHF	1.0	1.0	0.0	idem	idem	idem
Δ_{θ}	SDSDTH	0.0	0.0	80	idem	idem	idem
B_r	SDSBR	0.0	0.0	1.2×10^{-3}	9×10^{-4}	idem	idem
p^{sat}	SDSP	0.0	0.0	2.0	idem	idem	idem
$r_{\rm cu}$	SDSBRF1	0.0	0.0	0.0	0.5	idem	idem
$2 * C_{cu}$	SDSC3	0.0	0.0	0.0	2.0	0.8	idem
$C_{ m turb}$	SDSC5	0.0	0.0	0.0	0.0	0.0	0.0
sB	SDSCOS	0.0	0.0	0.0	2.0	idem	idem
δ_d	SDSDC6	0.0	0.0	1.0	0.3	0.3	0.0
M_0	SDSBM0	0.0	0.0	1.0	idem	idem	idem
M_1	SDSBM1	0.0	0.0	0.2428	idem	idem	idem
M_2	SDSBM2	0.0	0.0	1.9995	idem	idem	idem
M_3	SDSBM3	0.0	0.0	-2.5709	idem	idem	idem
M_4	SDSBM4	0.0	0.0	1.3286	idem	idem	idem

Table A2. Dissipation parameter as implemented in version 3.14-SHOM of the WAVEWATCH III code, and values used in the tests presented here. In WWATCH, all parameters are accessible via the SDS3 namelist. Most of these are also included in version 3.14, except for C_{cu} which is needed for the TEST437 and TEST441 with results described here. The TEST405 can be ran with version 3.14. The parameter M_0 is a switch for the correction or not of B_r into B'_r , when $M_0 = 1$, as is the case here, the correction is not applied.

- Ardhuin, F., T. H. C. Herbers, K. P. Watts, G. P. van Vledder, R. Jensen, and H. Graber, 2007: Swell and slanting fetch effects on wind wave growth. J. Phys. Oceanogr., 37, 908–931.
- Ardhuin, F. and A. D. Jenkins, 2005: On the effect of wind and turbulence on ocean swell. Proceedings of the 15th International Polar and Offshore Engineering Conference, June 19–24, Seoul, South Korea, ISOPE, volume III, 429–434.
- 2006: On the interaction of surface waves and upper ocean turbulence. J. Phys. Oceanogr., 36, 551–557.
- Ardhuin, F. and A. Le Boyer, 2006: Numerical modelling of sea states: validation of spectral shapes (in French). *Navigation*, 54, 55–71.
- Ardhuin, F., L. Marié, N. Rascle, P. Forget, and A. Roland, 2009b: Observation and estimation of Lagrangian, Stokes and Eulerian currents induced by wind and waves at the sea surface. *J. Phys. Oceanogr.*, in press, available at http://hal.archivesouvertes.fr/hal-00331675/.
- Ardhuin, F., N. Rascle, and K. A. Belibassakis, 2008b: Explicit waveaveraged primitive equations using a generalized Lagrangian mean. *Ocean Modelling*, **20**, 35–60.
 Babanin, A., I. Young, and M. Banner, 2001: Breaking probabilities for
- Babanin, A., I. Young, and M. Banner, 2001: Breaking probabilities for dominant surface waves on water of finite depth. J. Geophys. Res., 106, 11659–11676.

- Babanin, A., K. Tsagareli, I. Young, and D. Walker, 2007: Implementation of new experimental input/dissipation terms for modelling spectral evolution of wind waves. *Proceedings of the 10th International workshop on wave hindcasting and forecasting, Oahu, Hawaii.*
- Babanin, A. V. and A. J. van der Westhuysen, 2008: Physics of saturation-based dissipation functions proposed for wave forecast models. J. Phys. Oceanogr., 38, 1831–1841.
- Babanin, A. V. and I. R. Young, 2005: Two-phase behaviour of the spectral dissipation of wind waves. *Proceedings of the 5th In*ternational Symposium Ocean Wave Measurement and Analysis, Madrid, june 2005, ASCE, paper number 51.
- Banner, M. L., A. V. Babanin, and I. R. Young, 2000: Breaking probability for dominant waves on the sea surface. J. Phys. Oceanogr., 30, 3145–3160.
- Banner, M. L., J. R. Gemmrich, and D. M. Farmer, 2002: Multiscale measurement of ocean wave breaking probability. J. Phys. Oceanogr., 32, 3364–3374.
- Banner, M. L., I. S. F. Jones, and J. C. Trinder, 1989: Wavenumber spectra of short gravity waves. J. Fluid Mech., 198, 321–344.
- Banner, M. L. and W. L. Peirson, 2007: Wave breaking onset and strength for two-dimensional deep-water wave groups. J. Fluid Mech., 585, 93–115.
- Banner, M. L. and I. R. Young, 1994: Modeling spectral dissipation in the evolution of wind waves. part I: assessment of existing model performance. J. Phys. Oceanogr., 24, 1550–1570.
- Banner, M. L. and R. P. Morison, 2006: On modeling spectral dissipation due to wave breaking for ocean wind waves. *Proceedings of* the 9th International workshop on wave hindcasting and forecasting, Victoria, Canada.
- Bidlot, J., S. Abdalla, and P. Janssen, 2005: A revised formulation for ocean wave dissipation in CY25R1. Technical Report Memorandum R60.9/JB/0516, Research Department, ECMWF, Reading, U. K.
- Bidlot, J., P. Janssen, and S. Abdalla, 2007a: A revised formulation of ocean wave dissipation and its model impact. Technical Report Memorandum 509, ECMWF, Reading, U. K.
- Bidlot, J.-R., 2008: Intercomparison of operational wave forecasting systems against buoys: data from ECMWF, MetOffice, FNMOC, NCEP, DWD, BoM, SHOM and JMA, September 2008 to November 2008. Technical report, Joint WMO-IOC Technical Commission for Oceanography and Marine Meteorology, available from http://preview.tinyurl.com/7bz6jj.
- Bidlot, J.-R., J.-G. Li, P. Wittmann, M. Fauchon, H. Chen, J.-M. Lefèvre, T. Bruns, D. Greenslade, F. Ardhuin, N. Kohno, S. Park, and M. Gomez, 2007b: Inter-comparison of operational wave forecasting systems. *Proceedings, 10th Int. WOrkshop of Wave Hindcasting and Forecasting, Hawaii.*
- Cavaleri, L., 2006: Wave modeling where to go in the future. *Bull. Amer. Meterol. Soc.*, **87**, 207–214.
- Chalikov, D. V. and M. Y. Belevich, 1993: One-dimensional theory of the wave boundary layer. *Boundary-Layer Meteorol.*, 63, 65–96.
- Chen, G. and S. E. Belcher, 2000: Effects of long waves on windgenerated waves. J. Phys. Oceanogr., 30, 2246–2256.
- Collard, F., F. Ardhuin, and B. Chapron, 2009: Monitoring and analysis of ocean swell fields using a spaceborne SAR: a new method for routine observations. J. Geophys. Res., in press, available at http://hal.archives-ouvertes.fr/hal-00346656/.
- Collard, F., A. A. Mouche, B. Chapron, C. line Danilo, and J. Johannessen, 2008: Routine high resolution observation of selected major surface currents from space. *Proceedings of SEASAR 2008, SP-*656, ESA, ESA - ESRIN, Frascati, Italy.
- Dalrymple, R. A., 1974: A finite amplitude wave on a linear shear current. J. Geophys. Res., 79, 4498–4504.
- Darbyshire, J., 1958: The generation of waves by wind. *Phil. Trans. Roy. Soc. London A*, **215**, 299–428.
- Dobson, F., W. Perrie, and B. Toulany, 1989: On the deep water fetch laws for wind-generated surface gravity waves. *Atmosphere Ocean*, 27, 210–236.
- Donelan, M. A., 1998: Air-water exchange processes. *Physical Processes in Lakes and Oceans*, J. Imberger, ed., American Geophysical Union, Washington, D.C., pages 18–36, iSBN 0-87590-268-5.
- Dore, B. D., 1978: Some effects of the air-water interface on gravity

waves. Geophys. Astrophys. Fluid. Dyn., 10, 215-230.

- Filipot, J.-F., F. Ardhuin, and A. Babanin, 2008: Paramétrage du déferlement des vagues dans les modèles spectraux : approches semi-empirique et physique. Actes des Xèmes journées Génie côtier-Génie civil, Sophia Antipolis, Centre Français du Littoral.
- 2009: A unified deep-to-shallow-water spectral wave breaking dissipation formulation. Part 1. Breaking probability. J. Geophys. Res., submitted, April 2009.
- Gelci, R., H. Cazalé, and J. Vassal, 1957: Prévision de la houle. La méthode des densités spectroangulaires. Bulletin d'information du Comité d'Océanographie et d'Etude des Côtes, 9, 416–435.
- Gemmrich, J. R., M. L. Banner, and C. Garrett, 2008: Spectrally resolved energy dissipation rate and momentum flux of breaking waves. J. Phys. Oceanogr., 38, 1296–1312.
- Gourrion, J., D. Vandemark, S. Bailey, and B. Chapron, 2002: Investigation of C-band altimeter cross section dependence on wind speed and sea state. *Can. J. Remote Sensing*, 28, 484–489.
- Grant, W. D. and O. S. Madsen, 1979: Combined wave and current interaction with a rough bottom. J. Geophys. Res., 84, 1797–1808.
- Hargreaves, J. C. and J. D. Annan, 2000: Comments on –improvement of the short-fetch behavior in the wave ocean model (WAM)–. J. Atmos. Ocean Technol., 18, 711–715.
- Harris, D. L., 1966: The wave-driven wind. J. Atmos. Sci., 23, 688-693.
- Hasselmann, K., 1971: On the mass and momentum transfer between short gravity waves and larger-scale motions. J. Fluid Mech., 4, 189–205.
- 1974: On the spectral dissipation of ocean waves due to white capping. *Boundary-Layer Meteorol.*, 6, 107–127.
- Hasselmann, S., K. Hasselmann, J. Allender, and T. Barnett, 1985: Computation and parameterizations of the nonlinear energy transfer in a gravity-wave spectrum. Part II: Parameterizations of the nonlinear energy transfer for application in wave models. J. Phys. Oceanogr., 15, 1378–1391.
- Janssen, P. A. E. M., 1991: Quasi-linear theory of wind wave generation applied to wave forecasting. J. Phys. Oceanogr., 21, 1631–1642, see comments by D. Chalikov, J. Phys. Oceanogr. 1993, vol. 23 pp. 1597–1600.
- Janssen, P. A. E. M., K. Hasselmann, S. Hasselmann, and G. J. Komen, 1994: Parameterization of source terms and the energy balance in a growing wind sea. *Dynamics and modelling of ocean waves*, G. J. Komen et al., ed., Cambridge University Press, pages 215– 238.
- Janssen, P. A. E. M., O. Saetra, C. Wettre, and H. Hersbach, 2004: Impact of the sea state on the atmosphere and ocean. *Annales Hy*drographiques, 6e série, vol. 3, 3–1–3–23.
- Jensen, B. L., B. M. Sumer, and J. Fredsøe, 1989: Turbulent oscillatory boundary layers at high Reynolds numbers. J. Fluid Mech., 206, 265–297.
- Jessup, A. T., C. J. Zappa, and H. Yeh, 1997: Defining and quantifying microscale wave breaking with infrared imagery. J. Geophys. Res., 102, 23145–23153.
- Komen, G. J., L. Cavaleri, M. Donelan, K. Hasselmann, S. Hasselmann, and P. A. E. M. Janssen, 1994: *Dynamics and modelling of ocean* waves. Cambridge University Press, Cambridge, 554 pp.
- Komen, G. J., K. Hasselmann, and S. Hasselmann, 1984: On the existence of a fully developed windsea spectrum. J. Phys. Oceanogr., 14, 1271–1285.
- Lefèvre, J.-M., S. E. Ştefănescu, and V. Makin, 2004: Implementation of new source terms in a third generation wave model. *Preprints* of the 3th International workshop on wave hindcasting and forecasting, Montreal, Quebec, 19-22 May, Environment Canada.
- Long, C. E. and D. T. Resio, 2007: Wind wave spectral observations in Currituck Sound, North Carolina. J. Geophys. Res., 112, C05001.
- Longuet-Higgins, M. S., 1990: Flow separation near the crests of short gravity waves. J. Phys. Oceanogr., 20, 595–599.
- Longuet-Higgins, M. S. and J. S. Turner, 1974: An 'entraining plume' model of a spilling breaker. J. Fluid Mech., 63, 1–20.
- Makin, V. K. and M. Stam, 2003: New drag formulation in NEDWAM. Technical Report 250, Koninklijk Nederlands Meteorologisch Instituut, De Bilt, The Netherlands.
- Melville, W. K., F. Verron, and C. J. White, 2002: The velocity field under breaking waves: coherent structures and turbulence. J. Fluid Mech., 454, 203–233.

- Peirson, W. L. and M. L. Banner, 2003: Aqueous surface layer flows induced by microscale breaking wind waves. J. Fluid Mech., 479, 1–38.
- Phillips, O. M., 1958: The equilibrium range in the spectrum of windgenerated waves. J. Fluid Mech., 4, 426–433.
- 1963: On the attenuation of long gravity waves by short breaking waves. J. Fluid Mech., 16, 321–332.
- 1984: On the response of short ocean wave components at a fixed wavenumber to ocean current variations. J. Phys. Oceanogr., 14, 1425–1433.
- 1985: Spectral and statistical properties of the equilibrium range in wind-generated gravity waves. J. Fluid Mech., 156, 505–531.
- Pierson, W. J., Jr and L. Moskowitz, 1964: A proposed spectral form for fully developed wind seas based on the similarity theory of S. A. Kitaigorodskii, J. Geophys. Res., 69, 5,181–5,190.
- A. Kitaigorodskii. J. Geophys. Res., 69, 5,181–5,190.
 Polnikov, V. G. and V. Inocentini, 2008: Comparative study of performance of wind wave model: Wavewatch?modified by new source function. Engineering Applications of Computational Fluid Mechanics, 2, 466–481.
- Queffeulou, P. and D. Croizé-Fillon, 2008: Global altimeter SWH data set, version 4, october 2008. Technical report, Ifremer.
- Rascle, N., F. Ardhuin, P. Queffeulou, and D. Croizé-Fillon, 2008: A global wave parameter database for geophysical applications. part 1: wave-current-turbulence interaction parameters for the open ocean based on traditional parameterizations. *Ocean Modelling*, 25, 154–171.
- Rogers, W. E., P. A. Hwang, and D. W. Wang, 2003: Investigation of wave growth and decay in the SWAN model: Three regional-scale applications. J. Phys. Oceanogr., 33, 366–389.
- Rogers, W. E. and D. W. C. Wang, 2007: Directional validation of wave predictions. J. Atmos. Ocean Technol., 24, 504–520.
- Roland, A., 2008: Development of WWM II: Spectral wave modelling on unstructured meshes. Ph.D. thesis, Technische Universität Darmstadt, Institute of Hydraulic and Water Resources Engineering.
- Ruessink, B. G., D. J. R. Walstra, and H. N. Southgate, 2003: Calibration and verification of a parametric wave model on barred beaches. *Coastal Eng.*, 48, 139–149.
- Stansell, P. and C. MacFarlane, 2002: Experimental investigation of wave breaking criteria based on wave phase speeds. J. Phys. Oceanogr., 32, 1269–1283.
- Tolman, H. L., 1992: Effects of numerics on the physics in a third-generation wind-wave model. J. Phys. Oceanogr., 22, 1095–1111.
 2002: Limiters in third-generation wind wave models. Global Atmos.
- Decean Syst., 8, 67–83.
 2003: Treatment of unresolved islands and ice in wind wave models.
- Ocean Modelling, 5, 219–231. — 2007: The 2007 release of WAVEWATCH III. Proceedings, 10th Int.
- Workshop of Wave Hindcasting and Forecasting, Hawaii.
- 2008: A mosaic approach to wind wave modeling. Ocean Modelling, 25, 35–47.
- 2009: User manual and system documentation of WAVEWATCH-IIITM version 3.14. Technical Report 276, NOAA/NWS/NCEP/MMAB.
- Tolman, H. L. and J.-H. G. M. Alves, 2005: Numerical modeling of wind waves generated by tropical cyclones using moving grids. *Ocean Modelling*, 9, 305–323.

- Tolman, H. L. and D. Chalikov, 1996: Source terms in a thirdgeneration wind wave model. J. Phys. Oceanogr., 26, 2497–2518.
- Tournadre, J., K. Whitmer, and F. Girard-Ardhuin, 2008: Iceberg detection in open water by altimeter waveform analysis. J. Geophys. Res., 113, C08040.
- Tsagareli, K., 2008: Numerical Investigation of Wind Input and Spectral Dissipation in Evolution of Wind Waves. Ph.D. thesis, University of Adelaide, Faculty of Engineering, Computer and Mathematical Sciences School of Civil and Environmental Engineering, Australia.
- Tulin, M. P. and M. Landrini, 2001: Breaking waves in the ocean and around ships. Proceedings of the 23rd ONR symposium on naval hydrodynamics, Val de Reuil, France, Naval Studies Board, 713– 745.
- van der Westhuysen, A. J., M. Zijlema, and J. A. Battjes, 2007: Saturation-based whitecapping dissipation in SWAN for deep and shallow water. *Coastal Eng.*, 54, 151–170.
- van Vledder, G. P. and D. P. Hurdle, 2002: Performance of formulations for whitecapping in wave prediction models. *Proceedings of* OMAE.02 21st International Conference on Offshore Mechanics and Artic Engineering June 23-28, 2002, Oslo, Norway, number OMAE2002-28146.
- Vandemark, D., B. Chapron, J. Sun, G. H. Crescenti, and H. C. Graber, 2004: Ocean wave slope observations using radar backscatter and laser altimeters. J. Phys. Oceanogr., 34, 2825–2842.
- Vandemark, D., P. D. Mourad, S. A. Bailey, T. L. Crawford, C. A. Vogel, J. Sun, and B. Chapron, 2001: Measured changes in ocean surface roughness due to atmospheric boundary layer rolls. J. Geophys. Res., 106, 4639–4654.
- Violante-Carvalho, N., F. J. Ocampo-Torres, and I. S. Robinson, 2004: Buoy observations of the influence of swell on wind waves in the open ocean. *Appl. Ocean Res.*, 26, 49–60.
- Wang, D. W., D. A. Mitchell, W. J. Teague, E. Jarosz, and M. S. Hulbert, 2005: Extreme waves under hurricane Ivan. Science, 309, 896.
- WISE Group, 2007: Wave modelling the state of the art. Progress in Oceanography, 75, 603–674.
- Wu, C. H. and H. M. Nepf, 2002: Breaking criteria and energy losses for three-dimensional wave breaking. J. Geophys. Res., 107, 3177.
- Young, I. R., 2005: Directional spectra of hurricane wind waves. J. Geophys. Res., 111, C08020.
- Young, I. R. and A. V. Babanin, 2006: Spectral distribution of energy dissipation of wind-generated waves due to dominant wave breaking. J. Phys. Oceanogr., 36, 376–394.
- Young, I. R. and G. P. van Vledder, 1993: A review of the central role of nonlinear interactions in wind-wave evolution. *Phil. Trans. Roy. Soc. London A*, 342, 505–524.
- Zhang, F. W., W. M. Drennan, B. K. Haus, and H. C. Graber, 2009: On wind-wave-current interactions during the shoaling waves experiment. J. Geophys. Res., 114, C01018.

Fabrice's Draft: July 25, 2009

Generated with ametsocjmk.cls.

Written by J. M. Klymak

mailto:jklymak@ucsd.edu

http://opg1.ucsd.edu/ jklymak/WorkTools.html