



HAL
open science

A discussion on Neumann-Kelvin model for progressive water waves

Philippe Destuynder, Caroline Fabre

► **To cite this version:**

Philippe Destuynder, Caroline Fabre. A discussion on Neumann-Kelvin model for progressive water waves. 2009. hal-00429737

HAL Id: hal-00429737

<https://hal.science/hal-00429737>

Preprint submitted on 4 Nov 2009

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

A discussion on Neumann-Kelvin model for progressive water waves

Philippe Destuynder¹ and Caroline Fabre²

¹Department of Mathematics,
Conservatoire National des Arts et Métiers,
292, rue Saint Martin, 75003, Paris, France
philippe.destuynder@cnam.fr

²Laboratoire de Mathématiques CNRS-UMR 8628,
Université de Paris sud, bat. 425, 91400 Orsay, France
caroline.fabre@u-psud.fr

May 24, 2009

Abstract

This paper focus on the role of the capillary in the modelling and the analysis of progressive waves at the surface of the sea. It is proved that the classical Neumann-Kelvin model is fully instable and should be modified in order to be mechanically reliable. It is shown that the easiest way to take the capillary into account is to use a formulation where the normal displacement of the free surface appears as a main unknown variable.

AMS Subject Classification: Primary: 74F10, 35L85, 35R35; Secondary: 76B15, 35L70, 35Q35

Key words: water waves, unstabilities, wave equations, spectral theory, non-linear models

1 Introduction

Since the work of Kelvin [KEL 87], many contributions have been published for modelling progressive waves at the surface of the sea. In most of them, the authors consider that the capillary is neglectible [STO 57], [DOU 95]. This is a well founded hypothesis as far as one compares the forces in presence at the surface of the sea. Unfortunately, as it has been pointed out by several authors [CHEN 01] [IOS 96] [DIKH 99], the model is ill posed in a sense that is made precise in the following. In this paper, an extension of classical models is presented which takes into account the surface energy of the sea. A mathematical

analysis of it is given, and it is explained why it should be numerically more stable than the usual one. The discussion is governed by the value of the stationary flow's velocity. Comparisons with the regular Neumann-Kelvin model enable one to understand the limits of the classical progressive wave theory. Before detailing the context of our work, let us precise that the literature on water waves is very plentiful. Let us mention three works which seem to us particularly interesting in our context: the work of B. Alvarez-Samaniego and D. Lannes [ALLA 08], based on Zakharov's model, presents and justifies the main asymptotic models such as shallow water equations, Boussinesq's systems (and some more) and its references. Let us note that their framework neglects the capillary and the free surface of the water is unbounded (which enables one to use Fourier transform). Capillary-gravity waves on the free surface of a two dimensional inviscid fluid of *infinite depth* are studied in [IOS 96] and [DIKH 99] (and their references) where they prove the existence of solitary waves.

In this paper, one uses two functions in order to describe the wave phenomenon occurring at the surface of a water pool which is moving forwards at a given permanent velocity U . The fluid is assumed to be incompressible and the ordinary waves are due to the gravity and the capillary on the free surface. The mathematical models that are analyzed in the following can be used in a very general framework as soon as the fluid is assumed to be inviscid. Furthermore it is also necessary to assume that if the boundary is not connected, the flow velocity has a zero circulation around each connected component of the boundary of the pool. For instance, there can be a moving submarine under the free surface of the water but its rotation should be zero. Then the two functions which enable to describe the movement of the water are a velocity potential function -say Φ - and the normal displacement -say η - of a geometrical point of the free surface. Let us underline that this is not the displacement of the water particle at this point. In our case, the kinematical continuity on the free surface which will be considered as a separated media from the interior of the sea, has to be written for a material point. The coupling between the two media (the surface of the sea and the interior of the sea) requires as usual two sets of relations: one for the kinematical continuity and the other for the equilibrium of the stresses. But let us notice that the two waves (gravity waves and capillary waves) are essentially surface waves. The model that is discussed is based on the Neumann-Kelvin formulation [STO 57] [MOA 81] [DOU 95] [KEL 87] [STOE 92] [CAM 02]. It is different because the capillary is taken into account. Furthermore, in the Neumann-Kelvin model, one eliminates the normal displacement η in order to obtain a model where the only unknown is Φ . In the present analysis it is suggested that the formulation with respect to η is more appropriate as far as numerical simulations are concerned. Our discussion is based on mathematical arguments and more precisely on the spectral theory of the involved operators. The dominating result is that the wave model by Neumann- Kelvin is ill-posed and one can't neglect the capillary effect on

the free surface. A consequence is that a numerical simulation of the classical model is meaningless unless an artificial numerical cut-off of the high frequencies is used. The capillary is the right physical method for defining this cut-off. There are other artificial methods used by engineers for instance by considering a larger mesh of the free surface or by averaging the solution on a larger area than the one used for the solution method. The theoretical results given in this paper can be extended to the hydrodynamic behavior of a ship for the modelling of the whipping and the slamming phenomenae [DCF 08] [DCF 09] [HAC 02] [HOL 04] [GAZZ 05][GAZ 07].

Our plan is the following: in section 2, the interior fluid model is presented and the added mass operator is defined. Its mathematical properties are discussed in section 3. This operator is a corner stone in order to analyze the model of the free surface which is given in section 4, where the steady state is also studied. In section 5, the mathematical analysis of the full linearized coupled model is done when it is expressed in terms of the normal displacement of the free surface. It is proved that the model used in this paper is more stable than the one suggested by Neumann and Kelvin. Let us split our analysis into two main cases according to a small or a large value of the velocity of the flow. In section 6, the formulation based on the velocity potential is discussed for the Neumann-Kelvin's model. In section 8, few remarks on the non linear case are given and the section 9 concerns the numerical schemes.

Finally, let us mention that the main geometrical notations are explicated on figure 1 and that constant c may change from one line to another.

2 The interior fluid model

The pool containing the water occupies in \mathbb{R}^d ($d = 2$ or 3) a non empty, open, bounded and connected set denoted by Ω , the boundary of which is denoted by $\Gamma = \partial\Omega$. Three parts of this boundary are distinguished and they are assumed to be with non empty interiors: one denoted by Γ_0 corresponds to the bottom of the pool and the boundary of a submarine (see figure 1); a second one -say Γ_f - is the free surface and the last one Γ_1 , contains the intake and the exit through which the water is entering and exhausting from the pool. It is assumed that $\Gamma = \Gamma_0 \cup \Gamma_1 \cup \Gamma_f$ and that Γ_f is open. Let us denote by ν the unit outwards normal to the boundary Γ .

In all the paper, the following boundary conditions are used :

- On Γ_1 , the normal velocity of the steady flow is prescribed equal to $U(e_1, \nu)$ where $(,)$ denotes the scalar product of two vectors in \mathbb{R}^d . The transient pressure is assumed to vanish on Γ_1 . This leads to an homogeneous Dirichlet boundary condition for the transient component of the velocity potential.




Figure 1: Main notations

- On Γ_f , one assumes that the normal velocity of the steady flow is zero. Let us remark that this is not the only possibility. Indeed, another one, may be more realistic, would be to assume that the free surface Γ_f is a stream surface for the steady flow (or a stream line in 2D). Let us suppose that the free surface Γ_f is initially located in the space $x_3 = 0$, whereas the coordinates (x_1, x_2) are varying in the plane containing Γ_f (see figure 1).

The velocity potential which describes the steady flow is denoted by Φ_0 . It is solution of the following system :

$$\begin{cases} -\Delta\Phi_0 = 0 \text{ in } \Omega, \\ \frac{\partial\Phi_0}{\partial\nu} = 0 \text{ on } \Gamma_0, \quad \frac{\partial\Phi_0}{\partial\nu} = U(e_1, \nu) \text{ on } \Gamma_1, \\ \frac{\partial\Phi_0}{\partial\nu} = 0 \text{ on } \Gamma_f, \quad \int_{\Gamma_f} \Phi_0 = 0. \end{cases} \quad (1)$$

It is known that there is a unique solution in the space $H^1(\Omega)$ to (1) as soon as the following Fredholm's condition (see for instance [NEC 67]) is satisfied:

$$\int_{\Gamma_1} (e_1, \nu) = 0. \quad (2)$$

It is assumed to be valid. Let us remark that the hypothesis (2) is not restrictive and is satisfied in each physical case because it is a consequence of the incompressibility of the fluid. If Ω is a parallelepiped, the condition (2) is true and one can easily prove that $\Phi_0(x) = U(x_1 + c)$ with some constant c . It satisfies $\Delta_s \Phi_0 = 0$ on Γ_f where Δ_s is the inplane Laplace operator on Γ_f . In other cases, one can write $\Phi_0 = U(x_1 + \Phi_1)$ where:

$$\begin{cases} -\Delta \Phi_1 = 0 \text{ in } \Omega, \\ \frac{\partial \Phi_1}{\partial \nu} = -(e_1, \nu) \text{ on } \Gamma_0, \quad \frac{\partial \Phi_1}{\partial \nu} = 0 \text{ on } \Gamma_1 \cup \Gamma_f \\ \int_{\Gamma_f} \Phi_1 = - \int_{\Gamma_f} x_1. \end{cases}$$

Let us assume that $\Phi_1|_{\Gamma_f} \in C^3(\bar{\Gamma}_f)$ and thus $\Phi_0|_{\Gamma_f} \in C^3(\bar{\Gamma}_f)$. This hypothesis is fulfilled if $\bar{\Gamma}_0 \cap \bar{\Gamma}_f = \emptyset$ and if the boundary of Ω is smooth enough (see [GRI 86] or [KON 06]).

As usual, the last relation on Γ_f enables to fix the constant, Φ_0 depends on as far as a Neumann's boundary condition is prescribed on all the boundary of Ω . Let us write $\Phi_0 = U\tilde{\Phi}_0$ where $\tilde{\Phi}_0$ is solution of (1) with $U = 1$.

Let us now consider the dynamic behaviour of the water. The total velocity potential Φ is written as the summ of two contributions: one is the steady state defined previously and the other one is the dynamic state:

$$\Phi = \Phi_0 + \varphi = U\tilde{\Phi}_0 + \varphi. \quad (3)$$

The unit normal to the deformed boundary Γ_f is denoted by ν' . It is different from ν when there is a rotation of this free surface, which is clearly the case for waves and the coupling between the rotation of ν and the velocity of a geometrical point of the free surface leads to gyroscopic forces as it is shown in the following.

The boundary condition on the deformed free surface is

$$\frac{\partial \Phi}{\partial \nu'} = \frac{\partial \eta}{\partial t}(\nu, \nu'),$$

where $\frac{\partial \eta}{\partial t}(\nu, \nu')$ is the velocity on the (deformed) free surface in the direction ν' . The displacement of the free surface is neglected but not its rotation. In fact, the gradient of η appears in the first order term and therefore, it is kept.

Finally, the dynamic velocity potential φ satisfies the following set of equations:

$$\begin{cases} -\Delta\varphi = 0 \text{ in } \Omega, \\ \frac{\partial\varphi}{\partial\nu} = 0 \text{ on } \Gamma_0, \varphi = 0 \text{ on } \Gamma_1, \\ \frac{\partial\Phi}{\partial\nu'} = \frac{\partial\eta}{\partial t}(\nu, \nu') \text{ on } \Gamma_f \text{ (which is the velocity on } \Gamma_f \text{ in the direction } \nu'). \end{cases} \quad (4)$$

The last relation is a non-linear one. It is one of the main difficulty in progressive wave modelling. Let us make it more explicit. From a classical computation, one has at the first order in η :

$$\nu' = \nu - \nabla_s \eta$$

where ∇_s is the inplane gradient operator on Γ_f . This boundary condition can be written as follows up to the second order (let us keep in mind that $\frac{\partial\Phi_0}{\partial\nu} = 0$ and $(\nabla_s \eta, \nu) = 0$ on Γ_f):

$$\frac{\partial\varphi}{\partial\nu} - \nabla_s \eta \cdot \nabla_s \Phi_0 - \nabla_s \eta \cdot \nabla_s \varphi = \frac{\partial\eta}{\partial t}.$$

The linearized version of this relation around $\eta = 0$ and $\varphi = 0$ is:

$$\frac{\partial\varphi}{\partial\nu} = \frac{\partial\eta}{\partial t} + \nabla_s \eta \cdot \nabla_s \Phi_0. \quad (5)$$

If one considers an initial deformation of the free surface described by a function η_0 , one would obtain:

$$\frac{\partial\varphi}{\partial\nu} = \frac{\partial\eta}{\partial t} + \nabla_s \eta \cdot \nabla_s \Phi_0 + \nabla_s \eta_0 \cdot \nabla_s \varphi. \quad (6)$$

This is the case for instance if one considers the digging effect which is discussed later on.

Several possibilities could occur for the boundary condition satisfied by φ on Γ_1 . The one used in (4) traduces a vanishing acoustic pressure. Another possibility would be to prescribe the total pressure (linearized expression) to zero (assuming also that the steady velocity is normal to Γ_1):

$$\frac{\partial\varphi}{\partial t} + U \frac{\partial\varphi}{\partial\nu} = 0. \quad (7)$$

Clearly there are many other possibilities in the definition of the boundary condition that should be satisfied by φ on this part of the boundary $\partial\Omega$. Furthermore it is certainly validate to use different boundary conditions at the flow-intake and at the exit.

In many cases, the solution Φ_0 , in the neighbourhood of the free surface, is very close to $Ux_1 + c$. Hence, the steady velocity on Γ_f is almost uniform and close to Ue_1 . This enables one to write approximately:

$$\frac{\partial \Phi}{\partial \nu'} = \nabla \Phi \cdot \nu' \simeq (Ue_1 + \nabla \varphi, \nu') = \frac{\partial \varphi}{\partial \nu} - U \frac{\partial \eta}{\partial x_1}, \quad (8)$$

or else:

$$\frac{\partial \varphi}{\partial \nu} \simeq \frac{\partial \eta}{\partial t} + U \frac{\partial \eta}{\partial x_1}, \quad (9)$$

which is the formula used in most publications on progressive wave theory (see J.J. Stoker [STO 57]). But for the general cases, the right linearized boundary condition is:

$$\frac{\partial \varphi}{\partial \nu} = \frac{\partial \eta}{\partial t} + U \nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta. \quad (10)$$

This is the one that is considered in this paper. The difference between these two expressions occurs for instance if a submarine is close to the free surface or if the depth of the sea is small and if the bottom is not flat (shore effect). It is worth noting that one needs an additional regularity on the term $\nabla_s \tilde{\Phi}_0$ in order to be able to make sense to the previous boundary condition. The point is that $\tilde{\Phi}_0$ is a smooth function excepted occasionally near corners of the boundary $\partial\Omega$. For instance one can assume that as far as the angles between Γ_1 and Γ_f are near from $\pi/2$ then $\tilde{\Phi}_0 \in C^1(\Omega)$ and therefore the restriction on Γ_f of the gradient of $\tilde{\Phi}_0$ is continuous. But, as mentionned, we assume more regularity on $\tilde{\Phi}_0$. Details concerning the regularity of the solution to elliptic partial differential equations can be found in [KON 06] or [GRI 86]. This regularity property is used in the following. Let us underline that if a surface ship is considered, the singularities which can appear at the junction between the free surface of the water and the hull of the boat can induce singularities which can change the analysis that is suggested in this paper. This is widely discussed in [DCF 09]. Let us give a formal variational formulation of the previous model. Let us set:

$$W_0 = \{\psi \in H^1(\Omega), \psi = 0 \text{ on } \Gamma_1\}. \quad (11)$$

At any time, the function $\varphi = \varphi(t, x)$ should be solution of:

$$\left\{ \begin{array}{l} \varphi \in W_0, \\ \forall \psi \in W_0, \int_{\Omega} \nabla \varphi \cdot \nabla \psi = \int_{\Gamma_f} \frac{\partial \eta}{\partial t} \psi + U \nabla \tilde{\Phi}_0 \cdot \nabla_s \eta \psi. \end{array} \right. \quad (12)$$

Hence, φ appears as a linear function of η . More precisely, there are two contributions: one is a linear function of $\frac{\partial \eta}{\partial t}$ and the other one is a linear

function of $U\nabla_s\tilde{\Phi}_0.\nabla_s\eta$. This operator, which maps the right hand side of (12) into φ is named the added mass operator and is denoted by G . It plays a crucial role in our analysis and this is why the next section gives a description and few properties of G which are useful in all what follows. Having in mind these properties related to G , we will then be able to introduce the model of equilibrium related to the free surface.

3 Definition and properties of G

Let us first state some mathematical notations and let us introduce functional spaces that will be used in the following.

3.1 The spaces $\tilde{H}^{1/2}(\Gamma_f)$ and its dual

Standard notations are used for Sobolev spaces and their norms; $\|\cdot\|_{s,X}$ denotes the norm in $H^s(X)$ where X is an open set of \mathbb{R}^d ($d \geq 1$). For instance for $s = 0$ one has: $H^0(X) = L^2(X)$. Let us consider the functional space W_0 defined at (11) equipped with the norm:

$$\|\psi\|_{W_0} = \|\nabla\psi\|_{0,\Omega}.$$

Let us define the following closed subspace of $H^{1/2}(\Gamma_f)$:

$$\tilde{H}^{1/2}(\Gamma_f) = \{v \in L^2(\Gamma_f), \exists \psi \in W_0, v = \psi|_{\Gamma_f}\}. \quad (13)$$

The space $\tilde{H}^{1/2}(\Gamma_f)$ is equipped with its natural norm which induces on it, an Hilbert's structure :

$$\|v\|_{1/2} = \inf_{\psi \in W_0, v = \psi|_{\Gamma_f}} \|\psi\|_{W_0} = \min_{\psi \in W_0, v = \psi|_{\Gamma_f}} \|\psi\|_{W_0}. \quad (14)$$

Obviously, $\mathcal{D}(\Gamma_f) \subset \tilde{H}^{1/2}(\Gamma_f)$, $\tilde{H}^{1/2}(\Gamma_f)$ is continuously embedded in $H^{1/2}(\Gamma_f)$ and we have

$$\forall v \in \tilde{H}^{1/2}(\Gamma_f), \|v\|_{1/2,\Gamma_f} \leq \|v\|_{1/2} \quad (15)$$

Remark 1. The space $\tilde{H}^{1/2}(\Gamma_f)$ can be $H^{1/2}(\Gamma_f)$ or $H_{00}^{1/2}(\Gamma_f)$ (see [LM 68]) in particular cases depending on the geometry of the open set Ω and the conditions prescribed on Γ_1 in the space W_0 . For instance it is $H^{1/2}(\Gamma_f)$ if Γ_1 is disconnected from Γ_f and: $H_{00}^{1/2}(\Gamma_f)$ if Γ_1 is connected to Γ_f and $\bar{\Gamma}_0 \cap \bar{\Gamma}_f = \emptyset$ (as on figure 1).

The dual space of $\tilde{H}^{1/2}(\Gamma_f)$ is denoted by $\tilde{H}^{-1/2}(\Gamma_f)$, its norm is denoted by $\|\cdot\|_{-1/2}$. and the duality bracket between $\tilde{H}^{1/2}(\Gamma_f)$ and its dual is denoted by $\langle\langle \cdot, \cdot \rangle\rangle$.

For regular functions $\eta \in L^2(\Gamma_f)$ and $v \in \tilde{H}^{1/2}(\Gamma_f)$, one has

$$\langle\langle \eta, v \rangle\rangle = \int_{\Gamma_f} \eta v = \langle \eta, v \rangle_{-1/2, 1/2}$$

where $\langle, \rangle_{-1/2, 1/2}$ denotes the duality between $H^{-1/2}(\Gamma_f)$ and $H^{1/2}(\Gamma_f)$. The space $H^{-1/2}(\Gamma_f)$ is continuously embedded into $\tilde{H}^{-1/2}(\Gamma_f)$ and

$$\forall \eta \in \tilde{H}^{-1/2}(\Gamma_f), \quad \|\eta\|_{-1/2} \leq \|\eta\|_{-1/2, \Gamma_f} \quad (16)$$

Let us now turn to the study of the added mass operator G .

3.2 Analysis of the operator G .

The definition of the linear operator G is :

$$g \in \tilde{H}^{-1/2}(\Gamma_f) \rightarrow G(g) = \Phi|_{\Gamma_f} \in \tilde{H}^{1/2}(\Gamma_f), \quad (17)$$

where $\Phi = \Phi(g) \in W_0$ is the unique solution of :

$$\forall \psi \in W_0, \quad \int_{\Omega} \nabla \Phi \cdot \nabla \psi = \langle\langle g, \psi|_{\Gamma_f} \rangle\rangle. \quad (18)$$

On the one hand Φ is uniquely as a function of W_0 and on the other hand the trace on Γ_f of a function in W_0 is in the space $\tilde{H}^{1/2}(\Gamma_f)$. Therefore G is well defined. Furthermore, this operator satisfies the following properties.

Theorem 2. *Let G be the operator defined at (17). G is a self-adjoint positive operator from $\tilde{H}^{-1/2}(\Gamma_f)$ onto $\tilde{H}^{1/2}(\Gamma_f)$ and there exist two constants $c_1 > 0$ and $c_0 > 0$ such that:*

$$\forall g \in \tilde{H}^{-1/2}(\Gamma_f), \quad c_1 \|g\|_{-1/2} \leq \|G(g)\|_{1/2} \leq c_0 \|g\|_{-1/2},$$

$$\|G(g)\|_{1/2}^2 \leq \langle\langle g, G(g) \rangle\rangle.$$

Hence, the operator G is an isomorphism between $\tilde{H}^{-1/2}(\Gamma_f)$ and $\tilde{H}^{1/2}(\Gamma_f)$.

Proof. For $(g, h) \in \tilde{H}^{-1/2}(\Gamma_f)^2$, let us set $\psi = \Phi(h)$ in (18). One obtains

$$\int_{\Omega} \nabla \Phi(g) \cdot \nabla \Phi(h) = \langle\langle g, G(h) \rangle\rangle = \langle\langle h, G(g) \rangle\rangle \quad (19)$$

which proves that G is self adjoint. Furthermore, (19) implies that

$$\|\Phi(g)\|_{1, \Omega}^2 \leq \|g\|_{-1/2} \|G(g)\|_{1/2},$$

and from the definition of the norm in $\tilde{H}^{1/2}(\Gamma_f)$,

$$\|G(g)\|_{1/2}^2 \leq \|\Phi(g)\|_{1,\Omega}^2 \leq \|g\|_{-1/2} \|G(g)\|_{1/2}$$

which proves the right hand side of the first inequality of theorem 2. The operator G maps continuously $\tilde{H}^{-1/2}(\Gamma_f)$ into $\tilde{H}^{1/2}(\Gamma_f)$ and it is clearly one to one because $G(g) = 0$ implies that Φ solution of (18) satisfies $\nabla\Phi = 0$ in Ω and also $\Phi = 0$ on Γ_1 . Thus $\Phi = 0$ and therefore $g = \frac{\partial\Phi}{\partial\nu} = 0$.

The onto character of G is a consequence of its closed range. Let us prove it. Let $g \in \tilde{H}^{-1/2}(\Gamma_f)$ and let $\psi_0 \in \tilde{H}^{1/2}(\Gamma_f)$ be such that

$$\|g\|_{-1/2} = \frac{\langle\langle g, \psi_0 \rangle\rangle}{\|\psi_0\|_{1/2}}.$$

Let $\psi \in W_0$ whose trace on Γ_f is ψ_0 and such that $\|\psi\|_{W_0} = \|\psi_0\|_{1/2}$. One has (with (19))

$$\|g\|_{-1/2} \leq \frac{\|\Phi(g)\|_{W_0} \|\psi\|_{W_0}}{\|\psi_0\|_{1/2}} \leq \|\Phi(g)\|_{W_0}. \quad (20)$$

Let us now consider a continuous extension operator from $H^{1/2}(\Gamma)$ into $X = \{u \in H^1(\Omega), \Delta u \in L^2(\Omega)\}$ -say R - with (see J.L. Lions et E. Magenes [LM 68]):

$$-\Delta R(v) \in L^2(\Omega) \text{ in } \Omega, \quad \frac{\partial R(v)}{\partial\nu} = 0 \text{ on } \Gamma, \quad R(v) = v \text{ on } \Gamma.$$

Let $v \in \tilde{H}^{1/2}(\Gamma_f)$. From the definition of this space there exists $w \in W_0$ such that $w|_{\Gamma_f} = v$ and $\|v\|_{1/2} = \|w\|_{W_0}$. Let $v_1 = w|_{\Gamma}$. There exists $c > 0$ such that for any $v \in \tilde{H}^{1/2}(\Gamma_f)$, one gets:

$$\|v_1\|_{1/2,\Gamma} \leq c \|v\|_{1/2}. \quad (21)$$

Applying this result with $v = \Phi(g)|_{\Gamma_f} = G(g)$, one obtains $\Phi(g) = R(v_1) + \Phi_1$ where $\Delta\Phi_1 = -\Delta R(v_1)$ in Ω , $\Phi_1 = 0$ on $\Gamma_f \cup \Gamma_1$ and $\frac{\partial\Phi_1}{\partial\nu} = 0$ on Γ_0 . One also has

$$\|\Phi(g)\|_{1,\Omega} \leq \|R(v_1)\|_{1,\Omega} + \|\Phi_1\|_{1,\Omega} \leq \|v_1\|_{1/2,\Gamma} + \|\Delta R(v_1)\|_{0,\Omega}$$

thus (20) and (21) lead to the existence of a constant $c > 0$ such that (constant c might change from a line to another) for any $g \in \tilde{H}^{-1/2}(\Gamma_f)$,

$$\|g\|_{-1/2} \leq c \|v_1\|_{1/2,\Gamma} \leq c \|\bar{v}\|_{1/2,\Gamma_f \cup \Gamma_1} \leq c \|v\|_{1/2}.$$

Recalling that $v = G(g)$, one has proved that G has a closed range in $\tilde{H}^{1/2}(\Gamma_f)$. Thanks to the fact that it is a self adjoint operator, one deduces that it is an isomorphism from $\tilde{H}^{-1/2}(\Gamma_f)$ onto $\tilde{H}^{1/2}(\Gamma_f)$.

Finally, let us prove the second relation in theorem 2. We have

$$c_1 \|g\|_{-1/2}^2 \leq \|G(g)\|_{1/2}^2 \leq c \|\Phi(g)\|_{W_0}^2 = \langle g, G(g) \rangle$$

hence G is positive the proof of theorem 2 is complete. \square

Let us now notice few properties of the operator L_s defined on $H^{1/2}(\Gamma_f)$ by

$$L_s(v) = \nabla_s \tilde{\Phi}_0 \cdot \nabla_s v. \quad (22)$$

Since $\tilde{\Phi}_0 \in C^1(\bar{\Gamma}_f)$, one has $L_s(v) \in H^{-1/2}(\Gamma_f)$ and there exists $c > 0$, depending on $\tilde{\Phi}_0$ such that

$$\|L_s(v)\|_{-1/2, \Gamma_f} \leq c \|v\|_{1/2, \Gamma_f}. \quad (23)$$

As a consequence, one deduces :

Corollary 3. *There exists $c > 0$ such that the following estimates hold : for every $u, v \in H^{1/2}(\Gamma_f)$,*

$$|\langle L_s(v), G \circ L_s(u) \rangle| \leq c \|v\|_{1/2, \Gamma_f} \|u\|_{1/2, \Gamma_f}$$

and for every $u, v \in \tilde{H}^{1/2}(\Gamma_f)$,

$$|\langle L_s(v), G \circ L_s(u) \rangle| \leq c \|v\|_{1/2} \|u\|_{1/2}$$

Proof. Since $\nabla_s \tilde{\Phi}_0 \cdot \nabla_s v \in H^{-1/2}(\Gamma_f)$, one has $\nabla_s \tilde{\Phi}_0 \cdot \nabla_s v \in \tilde{H}^{-1/2}(\Gamma_f)$ and the term $G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s v)$ makes sense. Applying Theorem 2, (16) and (15), it leads to

$$\forall u, v \in H^{1/2}(\Gamma_f),$$

$$\begin{aligned} |\langle L_s(v), G \circ L_s(u) \rangle| &\leq c_0 \|L_s(v)\|_{-1/2} \|L_s(u)\|_{-1/2}, \\ &\leq c \|L_s(v)\|_{-1/2, \Gamma_f} \|L_s(u)\|_{-1/2, \Gamma_f} \\ &\leq c \|v\|_{1/2, \Gamma_f} \|u\|_{1/2, \Gamma_f} \end{aligned} \quad (24)$$

which ends the corollary's proof since the embedding from $\tilde{H}^{1/2}(\Gamma_f)$ in $H^{1/2}(\Gamma_f)$ is continuous and thus the second part follows. \square

Notice that the kernel of L_s plays an important role in the following.

The set of equations (4) and (10) is the dynamic fluid model. One can express φ in terms of η and its derivatives as follows, but η is also an unknown. In the case of boundary conditions on Γ_f stated in (10), we have

$$\varphi|_{\Gamma_f} = G\left(\frac{\partial \eta}{\partial t}\right) + UG(L_s(\eta))$$

whereas with boundary conditions (6), one has

$$\varphi|_{\Gamma_f} = G\left(\frac{\partial\eta}{\partial t}\right) + UG(L_s(\eta)) + UG(\nabla_s\eta_0 \cdot \nabla_s\varphi).$$

In this paper, we only consider boundary condition (10) on the free surface. The case of (6) would require a different definition of operator G . This will be studied in forthcoming papers.

An equation is still lacking: it is the one which traduces the equilibrium of the free surface under the combine effects of the gravity, the water pressure and the capillary forces. By eliminating φ as a function of η in this equilibrium equation, one obtains the surface model which is an up-dated version of Neuman-Kelvin's model. This is explicited in the next section.

4 The equilibrium of the free surface

4.1 The model

Let us denote by p the pressure in the fluid. From Bernoulli theorem (see for instance G. Duvaut [DUV 90] or L. Landau-E. Lipschitz [LAL 71]), one obtains on the free surface of the water -say Γ_f ($x_3 = 0$)- by considering only the linearized expression in η and φ of the pressure (p_0 is the pressure in the air over the free surface):

$$p = p_0 - \varrho \frac{\partial\varphi}{\partial t} - \frac{\varrho}{2} |\nabla\varphi|^2 - \varrho U \nabla_s \tilde{\Phi}_0 \cdot \nabla_s \varphi - \varrho \frac{U^2}{2} |\nabla_s \tilde{\Phi}_0|^2 - \varrho g \eta + \sigma \Delta_s \eta. \quad (25)$$

In this expression $\sigma > 0$ is the capillary constant, $\varrho > 0$ is the mass density of the fluid and g is the gravity (let us recall that the notation Δ_s is the Laplace operator restricted to the free surface). One can linearize this formula by cancelling the term $|\nabla\varphi|^2$. But one can also introduce a stationary solution η_0 named the digging effect. It corresponds a stationary solution for the velocity potential in the fluid denoted by φ_0 . Finally it is possible to linearize the non linear term $\frac{\varrho}{2} |\nabla\varphi|^2$ around this new stationary terms. The linearized pressure at 0 is given by:

$$p = p_0 - \varrho \frac{\partial\varphi}{\partial t} - \varrho U \nabla_s \tilde{\Phi}_0 \cdot \nabla_s \varphi - \varrho \frac{U^2}{2} |\nabla_s \tilde{\Phi}_0|^2 - \varrho g \eta + \sigma \Delta_s \eta \quad (26)$$

Let us adopt for instance homogeneous Dirichlet boundary conditions for η on $\partial\Gamma_f$ (but many other possibilities exist). The equilibrium of the free surface is therefore governed by (p_0 which acts on both side of Γ_f is eliminated):

$$-\sigma \Delta_s \eta + \varrho g \eta + \varrho \frac{\partial\varphi}{\partial t} + \varrho U \nabla_s \tilde{\Phi}_0 \cdot \nabla_s \varphi = -\varrho \frac{U^2}{2} |\nabla_s \tilde{\Phi}_0|^2 \text{ on } \Gamma_f. \quad (27)$$

with :

$$\varphi = G\left(\frac{\partial\eta}{\partial t}\right) + UG(L_s(\eta)) \quad \text{on } \Gamma_f. \quad (28)$$

The term $-\frac{\rho}{2}U^2|\nabla_s\tilde{\Phi}_0|^2$ is a Venturi effect which induces the digging effect. It means that even for a stationary case, one hasn't exactly $\eta = 0$. The solution of the previous model where the transient terms have been cancelled is η_0 . Considering that both G and L_s are linear, system (27) and (28) is linear and one has $\eta = \eta_0 + \tilde{\eta}$ (and $\varphi = \varphi_0 + \tilde{\varphi}$) where $\tilde{\eta}$ is the solution of (27)-(28) with a null right hand side.

In the next subsection, an analysis of the steady state of system (27)-(28) is given and several concepts which will be useful in the following are introduced. Without loss of generality, the digging effect is omitted concerning the dynamic behavior of the surface.

4.2 On the digging effect

The digging component η_0 is solution of:

$$\begin{cases} \eta_0 \in H_0^1(\Gamma_f), \\ -\sigma\Delta_s\eta_0 + \rho g\eta_0 + \rho U^2\nabla_s\tilde{\Phi}_0 \cdot \nabla_s G(\nabla_s\tilde{\Phi}_0 \cdot \nabla_s\eta_0) = -\frac{\rho U^2}{2}|\nabla_s\tilde{\Phi}_0|^2, \end{cases} \quad (29)$$

where $UG(\nabla_s\tilde{\Phi}_0 \cdot \nabla_s\eta_0)$ is the solution φ of the model (4)-(10) but where the term $\frac{\partial\eta}{\partial t}$ is cancelled. For example, if $\tilde{\Phi}_0 = x_1$ which is a classical case, and if one restricts the preceding model to the one dimensional case (see section 7), one obtains the following model for the digging effect:

$$\begin{cases} \eta_0 \in H_0^1(\Gamma_f), \\ -\sigma\Delta_s\eta_0 + \rho g\eta_0 + \rho U^2 \frac{\partial G\left(\frac{\partial\eta_0}{\partial x_1}\right)}{\partial x_1} = -\frac{\rho U^2}{2}. \end{cases} \quad (30)$$

The expression of the digging effect η_0 depends on the steady flow which is described by $\tilde{\Phi}_0$. For instance it could be much more meaningful for shallow water and with different boundary condition on Γ_1 . But the analysis given here-after still works.

In order to explain the difficulties which will be encountered in the transient analysis, let us discuss the model (29) assuming the properties of G stated in

theorem 2 and in section 3. It can be written in a variational form as follows:

$$\left\{ \begin{array}{l} \text{find } \eta_0 \in H_0^1(\Gamma_f) \text{ such that } \forall v \in H_0^1(\Gamma_f) : \\ \int_{\Gamma_f} \sigma \nabla_s \eta_0 \cdot \nabla_s v + \varrho g \eta_0 v - \varrho U^2 G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta_0) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s v \\ - \varrho U^2 \int_{\Gamma_f} \Delta_s \tilde{\Phi}_0 G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta_0) v = - \frac{\varrho U^2}{2} \int_{\Gamma_f} |\nabla_s \tilde{\Phi}_0|^2 v. \end{array} \right. \quad (31)$$

We first prove the

Theorem 4. *There exists a critical velocity -say $U_c > 0$ - such that for every $0 \leq U < U_c$, the bilinear form:*

$$\begin{aligned} (\eta, v) \in H_0^1(\Gamma_f) &\rightarrow \sigma \int_{\Gamma_f} \nabla_s \eta \cdot \nabla_s v + \varrho g \int_{\Gamma_f} \eta v \\ &- \varrho U^2 \int_{\Gamma_f} G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s v - \varrho U^2 \int_{\Gamma_f} \Delta_s \tilde{\Phi}_0 G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta) v, \end{aligned}$$

is $H_0^1(\Gamma_f)$ elliptic. The operator:

$$v \in H_0^1(\Gamma_f) \rightarrow -\sigma \Delta_s v + \varrho g v + \varrho U^2 \nabla_s \tilde{\Phi}_0 \cdot \nabla_s G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s v),$$

satisfies the maximum principle (for $0 \leq U < U_c$) and one has $\eta_0 \leq 0$. The precise characterization of U_c is given in section 5.3.

Proof. From the properties satisfied by the operator G , one has (see theorem 2):

$$c_0 \| |\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta| \|_{-1/2} \leq \| |G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta)| \|_{1/2} \leq c_1 \| |\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta| \|_{-1/2}.$$

On the one hand, with (16) and (23), (let us recall that $\tilde{\Phi}_0 \in \mathcal{C}^3(\bar{\Gamma}_f)$) one gets:

$$\| |\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta| \|_{-1/2} \leq \| |\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta| \|_{-1/2, \Gamma_f} \leq c_2 \| |\eta| \|_{1/2, \Gamma_f},$$

and on the other hand:

$$\left| \int_{\Gamma_f} \Delta_s \tilde{\Phi}_0 G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta) v \right| \leq c_3 \| |\eta| \|_{1/2, \Gamma_f} \| |v| \|_{1/2, \Gamma_f}.$$

Hence, from the natural continuous inclusion of the space $H_0^1(\Gamma_f)$ into $H^{1/2}(\Gamma_f)$

one can claim that there exists a constant c such that for any $\delta \in]0, 1[$:

$$\left\{ \begin{array}{l} \forall v \in H_0^1(\Gamma_f), \\ \int_{\Gamma_f} [\sigma |\nabla_s v|^2 + \varrho g v^2 - \varrho U^2 G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s v) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s v] \\ - \varrho U^2 \int_{\Gamma_f} \Delta_s \tilde{\Phi}_0 G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s v) v \\ \geq (\delta \inf(\sigma, \varrho g) - c \varrho U^2) \|v\|_{1/2, \Gamma_f}^2 + (1 - \delta) \inf(\sigma, \varrho g) \|v\|_{1, \Gamma_f}^2. \end{array} \right. \quad (32)$$

The inequality (32) ensures that for U small enough, the bilinear form which appears in the variational equation (31) is elliptic on the space $H_0^1(\Gamma_f)$ and (31) has a unique solution. It is worth noting that even if the bilinear form which appears in (31) is not symmetrical, the Lax-Milgram's theorem still applies. \square Let us extend the existence result to any velocity U with a Fredholm's alternative. Let us first assume that the term $\Delta_s \tilde{\Phi}_0$ can be neglected which is the case in most applications (see remark 9 below for general cases).

Theorem 5. *Let us assume that $\Delta_s \tilde{\Phi}_0 = 0$ on Γ_f . There exists a countable sequence $\{\lambda_p\}$ with*

$$0 < \lambda_1 \leq \lambda_2 \leq \lambda_3 \leq \dots \leq \lambda_p \leq \lambda_{p+1} \leq \dots$$

and there exists finite dimensional subspaces S_p such that

1 If $\lambda_p < U^2 < \lambda_{p+1}$.

Then the model (31) has a unique solution.

2 If $U^2 = \lambda_p$ then

• If:

$$\forall v \in S_p, \int_{\Gamma_f} |\nabla_s \tilde{\Phi}_0|^2 v = 0$$

there is a solution to (31) which is defined up to an arbitrary element of S_p .

• If :

$$\exists v \in S_p \text{ such that: } \int_{\Gamma_f} |\nabla_s \tilde{\Phi}_0|^2 v \neq 0,$$

there is no solution to (31).

Proof. Let us make few preliminary remarks which will also be helpful in the the following. The bilinear form:

$$u, v \in H_0^1(\Gamma_f) \rightarrow a(u, v) = \int_{\Gamma_f} \sigma \nabla_s u \cdot \nabla_s v + \varrho g u v,$$

is symmetrical continuous and coercive on the space $H_0^1(\Gamma_f)$. From theorem 2 and its corollary, the bilinear form:

$$u, v \in H_0^1(\Gamma_f) \rightarrow b(u, v) = \varrho \int_{\Gamma_f} G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s u) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s v,$$

is symmetrical positive and continuous on the space $H_0^1(\Gamma_f)$ and defines a seminorm equivalent to $\|\nabla_s \tilde{\Phi}_0 \cdot \nabla_s v\|_{-1/2, \Gamma_f}$ on this space. But it is not always a norm excepted if $v \in H_0^1(\Gamma_f)$, $\nabla_s \tilde{\Phi}_0 \cdot \nabla_s v = 0$ implies that $v = 0$. Therefore one sets:

$$K_0 = \{v \in H_0^1(\Gamma_f), \forall q \in H_0^1(\Gamma_f), b(v, q) = 0\} \quad (33)$$

which is the same than the kernel of b . It is a closed subspace of $H_0^1(\Gamma_f)$ and a partial description of it is given in remark 7. The mapping:

$$v \in H_0^1(\Gamma_f) \rightarrow \sqrt{b(v, v)}, \quad (34)$$

is a norm on the quotient space $H_0^1(\Gamma_f)/K_0$ which is isomorphic to the orthogonal of K_0 in $H_0^1(\Gamma_f)$. The completed space with respect to this norm is denoted by $H^\#$. It is also an Hilbert space.

From (24), $H^\#$ contains the space $H^{1/2}(\Gamma_f)$ and thus $\tilde{H}^{1/2}(\Gamma_f)$. Hence the embedding from $H_0^1(\Gamma_f)/K_0$ into $H^\#$ is compact. Finally, the spectral theorem (see for instance [RATO 83]) can be applied to the following variational model:

$$\left\{ \begin{array}{l} \text{find } \lambda \in \mathbb{R}^{+*}, w \in H_0^1(\Gamma_f)/K_0 \text{ such that:} \\ \forall v \in H_0^1(\Gamma_f)/K_0, a(w, v) = \lambda b(w, v), \\ \text{with (one can use the norm on the space } H_0^1(\Gamma_f)/K_0): \\ \inf_{v_0 \in K_0} b(w + v_0, w + v_0) = 1. \end{array} \right. \quad (35)$$

The result of the spectral theorem is stated in the following:

Lemma 6. *There is a countable family of solutions $(\lambda_n, w_n) \in \mathbb{R}^{+*} \times H_0^1(\Gamma_f)/K_0$ such that the multiplicity of each eigenvalue λ_n is finite, the only accumulation point is ∞ , the family of the eigenvectors $\{w_n\}$ is an Hilbert's basis in the space $H^\#$ and $\{\frac{w_n}{\sqrt{\lambda_n}}\}$ is an Hilbert's basis in the space $H_0^1(\Gamma_f)/K_0$. Finally, the sequence λ_n is ordered such that:*

$$0 < \lambda_1 \leq \lambda_2 \leq \lambda_3 \leq \dots \leq \lambda_p \leq \lambda_{p+1} \leq \dots$$

and tends to infinity.

Theorem 5 is a direct consequence of Lemma 6 and of the Fredholm's alternative.

Remark 7. The description of K_0 is clearly related to a unique continuation property. In particular, it is necessary to have information on the nature of the zero set of $\nabla_s \tilde{\Phi}_0$ where $\tilde{\Phi}_0$ is solution of (1).
Let $\gamma \subset \Gamma_f$ be the set

$$\gamma = \{x \in \Gamma_f, \nabla_s \tilde{\Phi}_0(x) = 0\}.$$

It is a classical unique continuation result that γ has empty interior.
Let us prove that in the two dimensional case, $K_0 = \{0\}$.

We have : $v \in K_0$ implies that $\nabla_s v$ is null on the supplementary of γ . Since $\frac{\partial \tilde{\Phi}_0}{\partial \nu} = 0$ on Γ_f , γ is the set where the gradient of $\tilde{\Phi}_0$ is null. Since $\tilde{\Phi}_0$ is a real and harmonic function, γ has no accumulation point in Γ_f . There then exists a nonempty and open interval where v is constant. Let us consider a maximal interval I with this property and let us suppose that $b = \sup I \notin \partial\Gamma_f$. Since $\tilde{\Phi}_0$ is regular, in both case $\nabla_s \tilde{\Phi}_0(b) = 0$ (and then b is an isolated point in γ) or $\nabla_s \tilde{\Phi}_0(b) \neq 0$, there exists $\alpha > 0$ such that $]b, b + \alpha[\cap \gamma = \emptyset$. This implies that v is constant on $]b, b + \alpha[$ and since v is continuous, $v = v(b)$ and $]b, b + \alpha[\subset I$ which contradicts the maximal character of I . One easily get that v is constant on Γ_f and since $v \in H_0^1(\Gamma_f)$, v is null.

In three dimensionnal case, let us notice that there are several examples where $K_0 = \{0\}$. The first case which is mostly important corresponds to $\tilde{\Phi}_0 = x_1 + c$ (parallelepiped case). In this case one has:

$$v \in K_0 \Leftrightarrow \frac{\partial v}{\partial x_1} = 0,$$

which implies that v only depends on the coordinates x_2 transverse to x_1 in the plan containing Γ_f . But the only function in $H_0^1(\Gamma_f)$ which is constant with respect to the coordinate x_1 and null on $\partial\Gamma_f$ is $v = 0$ and thus $K_0 = \{0\}$.

More generally, as far as one can ensure that if for instance $\frac{\partial \tilde{\Phi}_0}{\partial x_1} \neq 0$ (excepted at isolated point) the result is still true. But this would be different if there was a surface boat on Γ_f that we do not consider in this paper.

Remark 8. Let us consider the case where:

$$\exists v \in S_p \text{ such that: } \int_{\Gamma_f} |\nabla_s \tilde{\Phi}_0|^2 v \neq 0.$$

When $\lambda_p < U^2 < \lambda_{p+1}$ there is a unique solution to (31). When $U^2 \rightarrow \lambda_p$ the solution tends to infinity (in norm). One has a stiff problem which can be interpreted physically by a an explosion of the progressive wave solution of (31).

Remark 9. In the case where $\Delta_s \tilde{\Phi}_0 \neq 0$ on Γ_f , one must consider a bilinear form b which is no more symmetrical and therefore the spectral theory is much more complicated and not so well known. One can say that if U^2 is not an eigen value then the system is still well posed. In other cases, the right hand side should be conjugate with respect to the eigenvectors of the transposed operators in order to ensure existence of solutions.

Remark 10. If the digging effect leads to a term η_0 which can't be neglected, it is necessary to modify the definition of G as follows. Instead of (18), let us introduce $\Phi \in W_0$ solution of (G is the restriction of Φ on Γ_f) :

$$\forall \psi \in W_0, \int_{\Omega} \nabla \Phi \cdot \nabla \psi - \int_{\Gamma_f} \nabla_s \eta_0 \cdot \nabla_s \Phi \psi = \int_{\Gamma_f} g \psi. \quad (36)$$

This is a non-symmetrical variational model. The only point which is not straightforward is that the bilinear form implied in the preceding model is elliptic. In fact one has:

$$\int_{\Omega} |\nabla \Phi|^2 - \int_{\Gamma_f} \nabla_s \eta_0 \cdot \nabla_s \Phi \Phi = \|\Phi\|_{1,\Omega}^2 - \frac{1}{2} \int_{\partial \Gamma_f} \frac{\partial \eta_0}{\partial \nu} \Phi^2 + \int_{\Gamma_f} \Delta_s \eta_0 \Phi^2. \quad (37)$$

But $\Phi = 0$ on $\partial \Gamma_f$ because $\Phi = 0$ on Γ_1 . The bilinear form implied in (36) is therefore strictly coercive on W_0 as soon as $\Delta_s \eta_0 \geq 0$ or is small enough.

5 Formulation of the model in η without digging effect

5.1 The model

In this section, let us consider dynamical part of system (27) and (28) neglecting η_0 but having in mind that it should be added to the solution η that is discussed hereafter in a numerical simulation. Let us consider the functional space in which η is looked for:

$$V = H_0^1(\Gamma_f). \quad (38)$$

By multiplying equation (27) by an arbitrary element of the space V , one obtains:

$$\forall v \in V, \sigma \int_{\Gamma_f} \nabla_s \eta \cdot \nabla_s v + \rho g \int_{\Gamma_f} \eta v + \rho \int_{\Gamma_f} \frac{\partial \varphi}{\partial t} v + \rho U \int_{\Gamma_f} \nabla_s \tilde{\Phi}_0 \cdot \nabla_s \varphi v = 0. \quad (39)$$

Using the map G which has been introduced in section 3, one can eliminate the velocity potential φ . When $U = 0$ it leads to an inertia term on the free surface of the water. But when $U \neq 0$ it gives new terms including gyroscopic

and hydrodynamic negative stiffness contributions. Let us explain how. Let us recall that the potential φ is solution of:

$$\begin{cases} \varphi \in W_0, \\ \forall \psi \in W_0, \int_{\Omega} \nabla \varphi \cdot \nabla \psi = \int_{\Gamma_f} \frac{\partial \eta}{\partial t} \psi + U \nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta \psi, \end{cases} \quad (40)$$

which can be written (28) as

$$\varphi|_{\Gamma_f} = G\left(\frac{\partial \eta}{\partial t}\right) + UG(\nabla_s \eta \cdot \nabla_s \tilde{\Phi}_0). \quad (41)$$

By introducing this expression into the equation (39) which traduces the equilibrium of the free surface, one obtains formally:

$$\begin{cases} \forall t \in [0, T], \eta = \eta(t) \in H_0^1(\Gamma_f), \\ \forall v \in H_0^1(\Gamma_f), m_s\left(\frac{\partial^2 \eta}{\partial t^2}, v\right) + 2Uc\left(\frac{\partial \eta}{\partial t}, v\right) + a(\eta, v) = 0, \end{cases} \quad (42)$$

with the notations for η and v smooth enough :

$$\begin{cases} m_s(\eta, v) = \varrho \int_{\Gamma_f} G(\eta)v, \\ c(\eta, v) = \frac{\varrho}{2} \int_{\Gamma_f} [G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta)v - \nabla_s \tilde{\Phi}_0 \cdot \nabla_s v G(\eta) - \Delta_s \tilde{\Phi}_0 G(\eta)v], \\ a(\eta, v) = \int_{\Gamma_f} [\sigma \nabla_s \eta \cdot \nabla_s v + \varrho g \eta v] \\ \quad - \varrho U^2 \int_{\Gamma_f} [G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s v + \Delta_s \tilde{\Phi}_0 G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta)v]. \end{cases} \quad (43)$$

Of course, one must add given initial data (η^0, η^1) to equation (42). Let us present some properties of the bilinear forms involved by (42) which will

be usefull in what follows. Let us set $a = a_s + a_r$ and $c = c_s + c_r$ with

$$\left\{ \begin{array}{l} c_s(\eta, v) = \frac{\varrho}{2} \int_{\Gamma_f} [G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta)v - \nabla_s \tilde{\Phi}_0 \cdot \nabla_s v G(\eta)] \\ c_r(\eta, v) = -\frac{\varrho}{2} \int_{\Gamma_f} \Delta_s \tilde{\Phi}_0 G(\eta)v, \\ a_s(\eta, v) = \int_{\Gamma_f} [\sigma \nabla_s \eta \cdot \nabla_s v + \varrho g \eta v] - \varrho U^2 \int_{\Gamma_f} G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s v \\ a_r(\eta, v) = -\varrho U^2 \int_{\Gamma_f} \Delta_s \tilde{\Phi}_0 G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta)v. \end{array} \right. \quad (44)$$

One has $a = a_s$ and $c = c_s$ when the term $\Delta_s \tilde{\Phi}_0$ can be neglectible which is the case in many examples.

The first step is to check few useful properties of the bilinear forms m_s , c and a . Let us notice that they are well defined if η and v are functions lying in the space $H_0^1(\Gamma_f)$. The bilinear form m_s and a_s are symmetrical and the bilinear form c_s is anti-symmetrical. This is due to the fact that it represents a gyroscopic coupling, in fact, $\nabla_s \eta$ is a rotation of the unit normal ν . The main properties are the coerciveness properties which are summarized hereafter. Nevertheless the additional terms which would appear in the expression of c and a can be easily handled as soon as one assumes that $\tilde{\Phi}_0 \in \mathcal{C}^2(\Gamma_f)$, (see P. Grisvard [GRI 86] or M. Borsuk and V. Kondratiev [KON 06] for the justification) because one has in this case:

$$\left\{ \begin{array}{l} |c_r(\eta, v)| \leq c \|\eta\|_{-1/2, \Gamma_f} \|v\|_{-1/2, \Gamma_f}, \\ \text{and:} \\ |a_r(\eta, v)| \leq c \|v\|_{1/2, \Gamma_f} \|\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta\|_{-1/2, \Gamma_f} \\ \leq c' \|\eta\|_{1/2} \|v\|_{1/2, \Gamma_f} \end{array} \right. \quad (45)$$

Theorem 11. *Let us assume that $\min(\varrho g, \sigma) > 0$. There exists constants $c_i > 0$ such that for every η and v in $H_0^1(\Gamma_f)$, one has*

(i) *Concerning a and a_s :*

$$\left| \begin{array}{l} |a_s(\eta, v)| + |a(\eta, v)| \leq c_3 \|\eta\|_{1, \Gamma_f} \|v\|_{1, \Gamma_f} \\ a(v, v) \geq c_0 \|v\|_{1, \Gamma_f}^2 - c_6 U^2 \|v\|_{1/2, \Gamma_f}^2 \end{array} \right.$$

(ii) Concerning m_s :

$$c_1 \|v\|_{-1/2}^2 \leq m_s(v, v) \leq c_2 \|v\|_{-1/2, \Gamma_f}^2 \leq c_2 \|v\|_{-1/2}^2.$$

(iii) Concerning c and c_s :

$$\left| \begin{array}{l} |c_s(\eta, v)| + |c(\eta, v)| \leq c_7 \|\eta\|_{1/2, \Gamma_f} \|v\|_{1/2, \Gamma_f} \\ c_s(v, v) = 0, \quad \forall v \in H_0^1(\Gamma_f). \end{array} \right.$$

Proof. Notice first that $H_0^1(\Gamma_f) \subset \tilde{H}^{1/2}(\Gamma_f)$ thus Theorem 9 makes sense. Theorem 2 proves that the bilinear form m_s induces a scalar product on $\tilde{H}^{-1/2}(\Gamma_f)$ which is equivalent to the usual one. Furthermore, the continuity of m_s with respect to the $H^{-1/2}(\Gamma_f)$ norm is a consequence of (16) and thus assertion (ii) is proved.

Concerning a_s , let us notice that:

$$\forall \eta \in H_0^1(\Gamma_f),$$

$$\begin{aligned} a_s(\eta, \eta) &= \sigma \int_{\Gamma_f} |\nabla_s \eta|^2 + \varrho g \int_{\Gamma_f} \eta^2 - \varrho U^2 \int_{\Gamma_f} G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta \\ &\geq \min(\sigma, \varrho g) \|\eta\|_{1, \Gamma_f}^2 - \varrho U^2 \int_{\Gamma_f} G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta. \end{aligned}$$

But, from the definition of the operator G and using again theorem 2 and its corollary :

$$\int_{\Gamma_f} G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta \leq c'_0 \|\eta\|_{1/2, \Gamma_f}^2$$

and assertion (i) is proved.

Assertion (ii) is clear with (i) and the second part of (45). Finally, (iii) is an easy consequence of (23). The theorem 11 is now proved. \square

Remark 12. *A natural question is to obtain the best constants which appears in the previous theorem. This is discussed in a section 5.3 in the case where $\Delta_s \tilde{\Phi}_0 = 0$.*

5.2 Well-posedness of (42) ($\sigma > 0$) for small velocity

Let us prove the following result:

Theorem 13. *There exists $U_c > 0$ such that for every $0 \leq U < U_c$ and every $(\eta_0, \eta_1) \in V \times \tilde{H}^{-1/2}(\Gamma_f)$, there exists a unique solution to (42) in $C^0([0, T]; V) \times C^1([0, T]; \tilde{H}^{-1/2}(\Gamma_f))$ with $\eta(0) = \eta_0$ and $\dot{\eta}(0) = \eta_1$.*

Proof. Let us consider a basis -say $\{w_n\}$ - of the space $H_0^1(\Gamma_f)$ and let us denote by V^N the finite dimensional subspace of $H_0^1(\Gamma_f)$ spanned by the N first basis vectors w_n . Furthermore η_0^N and η_1^N are approximations of $\eta_0 = \eta(0)$ and $\eta_1 = \frac{\partial \eta}{\partial t}(0)$ in the space V^N . They are such that :

$$\begin{cases} \lim_{N \rightarrow \infty} \|\eta_0^N - \eta_0\|_{1, \Gamma_f} = 0, \\ \lim_{N \rightarrow \infty} \|\eta_1^N - \eta_1\|_{-1/2, \Gamma_f} = 0. \end{cases} \quad (46)$$

Let us now consider the approximate models (for any N):

$$\begin{cases} \text{find } \eta^N \in V^N \text{ such that:} \\ \forall v \in V^N, m_s(\frac{\partial^2 \eta^N}{\partial t^2}, v) + 2Uc(\frac{\partial \eta^N}{\partial t}, v) + a(\eta^N, v) = 0, \\ \eta^N(0) = \eta_0^N, \quad \frac{\partial \eta^N}{\partial t}(0) = \eta_1^N. \end{cases} \quad (47)$$

This is a finite dimensional linear differential equation with initial conditions and constant coefficients. Therefore there is a unique solution to (46). Furthermore the time dependence is as smooth as one wishes because one has:

$$\eta^N = \sum_{k=1, N} \alpha_k^N(t) w_k,$$

and the time derivatives only imply the coefficients α_k^N .

Let us set $U_c = \sqrt{\frac{c_0}{c_6}}$ where the constants c_0 and c_6 are introduced in theorem

11. Let us assume that $U < U_c$. The bilinear form a is coercive on the space $H_0^1(\Gamma_f)$ (non symmetrical) and one obtains an *a priori* estimate for the approximate solution by setting $v = \dot{\eta}_N$ in the variational equation (47). From the symmetry of the bilinear forms m_s and a_s , the anti-symmetry of c_s , one obtain with $E(t) = \frac{1}{2}[m_s(\frac{\partial \eta}{\partial t}, \frac{\partial \eta}{\partial t}) + a_s(\eta, \eta)](t)$,

$$\text{if } \Delta_s \tilde{\Phi}_0 = 0, \quad E(t) = E(0) \quad (48)$$

and in others cases,

$$E(t) \leq c[E(0) + \int_0^t (c_r(\eta, \frac{\partial \eta}{\partial t}) + a_r(\eta, \frac{\partial \eta}{\partial t}))]. \quad (49)$$

Thanks to (45), Theorem 11 and Gronwall's Lemma, the previous estimate enables one to extract from η^N , a subsequence denoted by $\eta^{N'}$ which converges to η^* in the following topology:

$$\left\{ \begin{array}{l} \eta^{N'} \rightharpoonup \eta^* \text{ in } L^\infty(]0, T[; H_0^1(\Gamma_f)) \text{ weak}^*, \\ \frac{\partial \eta^{N'}}{\partial t} \rightharpoonup \frac{\partial \eta^*}{\partial t} \text{ in } L^\infty(]0, T[; \tilde{H}^{-1/2}(\Gamma_f)) \text{ weak}^*. \end{array} \right. \quad (50)$$

In order to take the limit for $N' \rightarrow \infty$, one uses the equivalent variational formulation which makes sense to the second order time derivative of η^* :

$$\left\{ \begin{array}{l} \forall \Psi = \sum_{k=1, N_0} \beta_k(t) w_k, \text{ with } \beta_k(t) \in \mathcal{D}([0, T]), N_0 \leq N, \\ -m_s \left(\frac{\partial \eta^N}{\partial t}, \frac{\partial \Psi}{\partial t} \right) - 2Uc(\eta^N, \frac{\partial \Psi}{\partial t}) + a(\eta^N, \Psi) \\ = -\{m_s(\eta_1^N, \Psi) + 2Uc(\eta_0^N, \Psi)\}. \end{array} \right. \quad (51)$$

But the result is true for any $N_0 \leq N$ and the approximate initial conditions converge to the one of the continuous model; hence one can claim that η^* is a solution to the weak (variational) model (42). The last point concerns the uniqueness. The proof is slightly different from the usual one as far as there is a gyroscopic term. First of all let us point out that the result is straightforward for smooth enough solutions. If $m_s(\frac{\partial^2 \eta}{\partial t^2}, \frac{\partial \eta}{\partial t})$ and $a_s(\eta, \frac{\partial \eta}{\partial t})$ can be defined, the result is derived from the energy conservation property. In fact one can introduce the difference between two solutions which satisfy the same initial conditions and therefore the energy -which is constant with respect to the time variable- is always zero. Let us now consider the general case for which the regularity condition of the weak solution is not necessarily satisfied. Let us set (following an idea given in J.L Lions [JLL 69]):

$$h = \int_0^t \eta \quad (52)$$

One can check that:

$$\left\{ \begin{array}{l} h \in L^\infty(]0, T[; H_0^1(\Gamma_f) \cap W^{1, \infty}(]0, T[; H^{1/2}(\Gamma_f))), \\ \forall v \in H_0^1(\Gamma_f), \\ m_s \left(\frac{\partial^2 h}{\partial t^2}, v \right) + 2Uc \left(\frac{\partial h}{\partial t}, v \right) + a(h, v) = m_s(\eta_1, v) + 2Uc(\eta_0, v). \end{array} \right. \quad (53)$$

But h has also to satisfy the initial conditions:

$$h(0) = 0 \text{ et } \frac{\partial h}{\partial t} = \eta_0. \quad (54)$$

This enables one to ensure the uniqueness of h because the regularity assumption is now satisfied. The uniqueness of η is a consequence of the one of h .

It has been proved that for small velocity $U < U_c$, the system is well-posed. \square
The value of U_c given by Theorem (11) is not optimal and we precise it in the next section.

5.3 About the static instabilities

Let us discuss the best value for the constant U_c in the particular case where the term $\Delta_s \tilde{\Phi}_0$ is neglected. One has in this case $a = a_s$. Two possibilities have to be considered depending if there is a capillary term or not ($\sigma > 0$ and $\sigma = 0$).

Let us introduce the eigenvalue model which has already been used in the analysis of the digging effect (31):

$$\left\{ \begin{array}{l} \text{find } (\lambda, w) \in \mathbb{R}^+ \times H_0^1(\Gamma_f) \text{ such that:} \\ \forall v \in H_0^1(\Gamma_f), \\ \lambda \varrho \int_{\Gamma_f} G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s w) \nabla_s \tilde{\phi}_0 \cdot \nabla_s v = \sigma \int_{\Gamma_f} \nabla_s w \cdot \nabla_s v + \varrho g \int_{\Gamma_f} wv. \end{array} \right. \quad (55)$$

It is a non-classical formulation because the bilinear form:

$$(\eta, v) \in H_0^1(\Gamma_f), \rightarrow \varrho \int_{\Gamma_f} G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta) \nabla_s \tilde{\phi}_0 \cdot \nabla_s v, \quad (56)$$

is not always definite. One has from corollary 2:

$$\left\{ \begin{array}{l} \exists c > 0, \text{ s.t. } \forall \eta \in H_0^1(\Gamma_f) : \\ \int_{\Gamma_f} G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta) \nabla_s \tilde{\phi}_0 \cdot \nabla_s \eta \geq c \|\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta\|_{-1/2}^2. \end{array} \right. \quad (57)$$

The kernel of the bilinear form (56) has been defined at (33) as the subspace of $H_0^1(\Gamma_f)$ such that:

$$K_0 = \{v \in H_0^1(\Gamma_f), \nabla_s \tilde{\Phi}_0 \cdot \nabla_s v = 0 \text{ on } \Gamma_f\}. \quad (58)$$

It is a closed subspace of $H_0^1(\Gamma_f)$ and few properties of it are given in the remark 7 where it has been proved that in 2D and in many cases in 3D, one has $K_0 = \{0\}$.

In what follows and in order to simplify, let us assume that $K_0 = \{0\}$ which is the most realistic case. Notice that our results can be easily adapted to the case where $K_0 \neq \{0\}$ using the quotient space $H_0^1(\Gamma_f)/K_0$ as in subsection 4.2.

Since $K_0 = \{0\}$, the mapping:

$$\eta \in \tilde{H}^{1/2}(\Gamma_f) \rightarrow \|\eta\|_{\#} = \|\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta\|_{-1/2, \Gamma_f}, \quad (59)$$

is a norm on the space $\tilde{H}^{1/2}(\Gamma_f)$ and with Theorem 2 :

$$\left\{ \begin{array}{l} \exists c, c' > 0, \text{ s.t. } \forall \eta \in \tilde{H}^{1/2}(\Gamma_f) : \\ c \|\eta\|_{\#}^2 \leq \int_{\Gamma_f} G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s \eta \leq c' \|\eta\|_{\#}^2. \end{array} \right. \quad (60)$$

Let $H^{\#}(\Gamma_f)$ be the completed space of $\tilde{H}^{1/2}(\Gamma_f)$ equipped with the norm $\|\cdot\|_{\#}$. Using (16) and (23) then (15), we get the existence of a constant $c > 0$ such that for every $v \in \tilde{H}^{1/2}(\Gamma_f)$,

$$\|v\|_{\#} \leq c \|L_s(v)\|_{-1/2, \Gamma_f} \leq c \|v\|_{1/2, \Gamma_f} \leq c \|v\|_{1/2, \Gamma_f},$$

thus $\tilde{H}^{1/2}(\Gamma_f) \subset H^{\#}(\Gamma_f)$.

Remark 14. The space $H^{\#}(\Gamma_f)$ is larger than $\tilde{H}^{1/2}(\Gamma_f)$. An interesting case (see theorem 15) corresponds to the inclusion: $H^{\#}(\Gamma_f) \subset L^2(\Gamma_f)$. Let us first consider the two dimensionnal case with $\tilde{\Phi}_0 = x_1 + c$. One has:

$$\nabla_s \tilde{\Phi}_0 \cdot \nabla_s v = \frac{\partial v}{\partial x_1} \in \tilde{H}^{-1/2}(\Gamma_f) \text{ hence } v \in H^{1/2}(\Gamma_f) \subset L^2(\Gamma_f).$$

Therefore $H^{\#}(\Gamma_f) \subset L^2(\Gamma_f)$. In the three dimensionnal case, $\frac{\partial v}{\partial x_1} \in \tilde{H}^{-1/2}(\Gamma_f)$ and there is no reason to hope the previous inclusion.

From general spectral theory of linear operators one can deduce the following theorem:

Theorem 15. Let us assume that $K_0 = \{0\}$. Two cases are considered in which the results are inverted.

1 • If $\sigma > 0$, there exists a countable set of elements denoted by (λ_n, w_n) in $\mathbb{R}^{+*} \times H_0^1(\Gamma_f)$ solution of (55). Each term of the sequence (ordered by increasing values) λ_n has a finite multiplicity and $+\infty$ is the only accumulation point. The family $\{w_n\}$ is an Hilbert basis of the space $H^{\#}(\Gamma_f)$. Furthermore, the family $\{\frac{w_n}{\sqrt{\lambda_n}}\}$ is an Hilbert basis of the space $H_0^1(\Gamma_f)$. The smallest eigenvalue denoted by λ_1 will be the best constant in theorem 11.

2 • If $\sigma = 0$ the result is different. Let us assume that $H^{\#}(\Gamma_f) \subset L^2(\Gamma_f)$ and that the inclusion is compact. There exists a countable set of solutions $(\lambda_n, w_n) \in \mathbb{R}^{+*} \times H^{\#}(\Gamma_f)$ and the terms of the sequence λ_n are ordered by

decreasing values (the largest value is denoted by λ_1). The multiplicity of each term is finite and 0 is the only accumulation point. The family $\{w_n\}$ is an Hilbert basis of the space $L^2(\Gamma_f)$ while the family $\{\frac{w_n}{\sqrt{\lambda_n}}\}$ is an Hilbert basis of the space $H^\#(\Gamma_f)$.

Proof. Let us begin with $\sigma > 0$. The result is a direct consequence of the spectral theory for linear operator as it is presented P.A. Raviart and J.M. Thomas [RATO 83]. In fact the bilinear form :

$$(\eta, v) \rightarrow \sigma \int_{\Gamma_f} \nabla_s \eta \cdot \nabla_s v + \varrho g \int_{\Gamma_f} \eta v,$$

is symmetrical, continuous and coercive on the space $H_0^1(\Gamma_f)$. Furthermore the bilinear and symmetrical form:

$$(\eta, v) \rightarrow \int_{\Gamma_f} G(\nabla_s \Phi_0 \cdot \nabla_s \eta) \nabla_s \Phi_0 \cdot \nabla_s \eta,$$

is continuous and elliptic on the space $H^\#(\Gamma_f)$. The assumptions of the spectral theory formulated in [RATO 83] are satisfied and the result is proved.

Let us consider the second case: $\sigma = 0$. Now the bilinear and symmetrical form:

$$(\eta, v) \rightarrow \varrho g \int_{\Gamma_j} \eta v,$$

is only equivalent to the square of the norm in the space $L^2(\Gamma_f)$. The variational eigenvalue problem is inverted. The compact embedding is from the space $H^\#(\Gamma_f)$ into $L^2(\Gamma_f)$. This completes the proof of theorem 15. \square

Remark 16. *In the first case where $\sigma > 0$, one can characterize the constant λ_1 which appears in theorem 11 as the smallest eigenvalue of the model (55). Therefore there are no confusion in the notation. Let us underline that λ_1 which is the smallest eigenvalue solution of (55) satisfies for every $v \in H_0^1(\Gamma_f)$:*

$$\lambda_1 \varrho \int_{\Gamma_f} G(\nabla_s \Phi_0 \cdot \nabla_s v) \nabla_s \Phi_0 \cdot \nabla_s v \leq \sigma \int_{\Gamma_f} |\nabla_s v|^2 + \varrho g \int_{\Gamma_f} v^2. \quad (61)$$

Hence:

$$\begin{cases} \forall \delta \in [0, 1], \forall v \in H_0^1(\Gamma_f), & a_s(v, v) \geq \inf(\sigma, \varrho g)(1 - \delta) \|v\|_{1, \Gamma_f}^2 \\ & + \varrho(\delta \lambda_1 - U^2) \int_{\Gamma_f} G(\nabla_s \Phi_0 \cdot \nabla_s v) \nabla_s \Phi_0 \cdot \nabla_s v. \end{cases} \quad (62)$$

Thus λ_1 is the best constant in theorem 11 and it enables to characterize the critical velocity U_c corresponding to the instability of the linear wave model in which the term $\Delta_s \tilde{\Phi}_0$ is neglected, by:

$$U_c = \sqrt{\lambda_1}. \quad (63)$$

If $U \geq U_c$ the coerciveness of the stiffness bilinear form on the space $H_0^1(\Gamma_f)$ is lost. But it is still true for the complementary of the first eigenvectors in this space.

Remark 17. *Let us assume that $\sigma = 0$, the coerciveness of a_s is no more true on the space $H_0^1(\Gamma_f)$ but only on the space $L^2(\Gamma_f)$ which is not contained in $H^\#(\Gamma_f)$ in most cases. In fact, the contrary is very often true which is a so-called mathematical inversion of the compactness.*

Furthermore, for any velocity $U > 0$, there exists an infinite number of instable eigenmodes. They are more and more local (the wave length is smaller and smaller). Therefore, in a numerical approximation, the more the mesh is refined, the larger is the number of instabilities. This remark which has already formulated in a different numerical framework by Xiao-bo Chen [CHEN 02], condemns the Neuman-Kelvin without capillary. In fact, the variational model (42) is fully instable excepted for a finite number of eigenmodes (see theorem 15) the eigenvalues of which -say λ_n solution of (55) with $\sigma = 0$ - would satisfy:

$$\lambda_n \geq U^2. \quad (64)$$

One can draw a strange conclusion: if U is small enough and if the mesh size in a numerical approximation is large enough, the Neumann-Kelvin is stable. This is really disturbing because the true model is not. One has a numerical filtering of the instabilities due to mesh size which would be too large.

The conclusion of this section is that the Neumann-Kelvin model is non physical (instable) as far as the capillary is not taken into account (excepted if $U = 0$). This result is obviously in contradiction with the usual argument that the capillary is very small and can be neglected compared to the gravity effect. A simple analytical example is discussed in section 6.

5.4 Extension of the existence and uniqueness result when

$$U \geq U_c = \sqrt{\lambda_1} \text{ and } \sigma > 0$$

First of all, let us note that the assumption $\sigma > 0$ is essential in this section where the well-posedness of the system for large velocity is studied. For sake of simplicity, it is assumed that $\Delta_s \tilde{\Phi}_0 = 0$ is neglectible. For a given velocity U ,

there is only a finite number of instable eigenmodes for which the stiffness operator (the static one) is negative. All the norms on the finite dimensional space spanned by these eigenmodes are equivalent. This enables one to overcome the lack of postivity. But it would be false for $\sigma = 0$ for which the instable space is not finite dimensional. Our goal in this section is to prove an existence result for the instable wave model.

Theorem 18. *For every $(\eta_0, \eta_1) \in V \times \tilde{H}^{-1/2}(\Gamma_f)$, there exists a unique solution to (42) in $C^0([0, T]; V) \times C^1([0, T]; \tilde{H}^{-1/2}(\Gamma_f))$ with $\eta(0) = \eta_0$ and $\dot{\eta}(0) = \eta_1$.*

Proof. Let κ be a strictly positive constant which is specified latter on depending on the largest eigenvalue λ_n solution of the model (55) and such that:

$$\lambda_n \leq U^2 < \lambda_{n+1}.$$

Let us set:

$$\eta = e^{\kappa t} z. \quad (65)$$

A simple formal calculus enables one to characterize z as a formal solution of:

$$\begin{cases} \forall v \in H_0^1(\Gamma_f) \cap L_0^2(\Gamma_f), \\ m_s(\frac{\partial^2 z}{\partial t^2}, v) + 2U c_s(\frac{\partial z}{\partial t}, v) + a_s(z, v) + \kappa^2 m_s(z, v) \\ = -2\kappa m_s(\frac{\partial z}{\partial t}, v) - 2U \kappa c_s(z, v). \end{cases} \quad (66)$$

In order to obtain an *a priori* estimate on the solution z^N of the approximate model (analogous to (47)) let us choose $v = \frac{\partial z^N}{\partial t}$ for the test function in the variational formulation. This leads to:

$$\begin{aligned} \frac{1}{2} \frac{d}{dt} [m_s(\frac{\partial z^N}{\partial t}, \frac{\partial z^N}{\partial t}) + a_s(z^N, z^N) + \kappa^2 m_s(z^N, z^N)] \leq \\ c \|\frac{\partial z^N}{\partial t}\|_{-1/2, \Gamma_f}^2 + 2U \kappa c_s(z^N, \frac{\partial z^N}{\partial t}) \end{aligned}$$

Let us now examine the term $c_s(z^N, \frac{\partial z^N}{\partial t})$. It is the summ of two terms. The first one is:

$$\varrho \int_{\Gamma_f} G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s z^N) \frac{\partial z^N}{\partial t},$$

which is bounded as follows: (as usual with (15), (16) and Theorem 2)

$$\begin{aligned}
\varrho \left| \int_{\Gamma_f} G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s z^N) \frac{\partial z^N}{\partial t} \right| &\leq c_0 \| \| G(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s z^N) \| \|_{1/2, \Gamma_f} \| \| \frac{\partial z^N}{\partial t} \| \|_{-1/2, \Gamma_f} \\
&\leq c_1 \| \| \nabla_s \tilde{\Phi}_0 \cdot \nabla_s z^N \| \|_{-1/2, \Gamma_f} \| \| \frac{\partial z^N}{\partial t} \| \|_{-1/2, \Gamma_f} \\
&\leq c_1 \| \| \frac{\partial z^N}{\partial t} \| \|_{-1/2, \Gamma_f} \| \| \nabla_s \tilde{\Phi}_0 \cdot \nabla_s z^N \| \|_{-1/2, \Gamma_f} \\
&\leq \frac{c_1}{2} [\| \| z^N \| \|_{1/2, \Gamma_f}^2 + \| \| \frac{\partial z^N}{\partial t} \| \|_{-1/2, \Gamma_f}^2].
\end{aligned}$$

The second term is:

$$-\varrho \int_{\Gamma_f} G(z^N) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s \left(\frac{\partial z^N}{\partial t} \right).$$

It can be written as follows:

$$-\frac{d}{dt} \left[\varrho \int_{\Gamma_f} G(z^N) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s z^N \right] + \varrho \int_{\Gamma_f} G \left(\frac{\partial z^N}{\partial t} \right) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s z^N.$$

Let us summarize the previous results. One has:

$$\begin{aligned}
&\frac{d}{dt} \left[m_s \left(\frac{\partial z^N}{\partial t}, \frac{\partial z^N}{\partial t} \right) + a_s(z^N, z^N) + \kappa^2 m_s(z^N, z^N) + \right. \\
&\left. + 2U\kappa\varrho \int_{\Gamma_f} G(z^N) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s z^N \right] \leq c_2 [\| \| z^N \| \|_{1, \Gamma_f}^2 + \| \| \frac{\partial z^N}{\partial t} \| \|_{-1/2, \Gamma_f}^2].
\end{aligned} \tag{67}$$

But one has also for any $\alpha > 0$:

$$\begin{aligned}
2U\kappa\varrho \int_{\Gamma_f} G(z^N) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s z^N &\leq 2U\kappa\varrho \| \| G(z^N) \| \|_{1/2, \Gamma_f} \| \| \nabla_s \tilde{\Phi}_0 \cdot \nabla_s z^N \| \|_{-1/2, \Gamma_f} \\
&\leq \varrho c_3 \left[\alpha \kappa^2 \| \| z^N \| \|_{-1/2, \Gamma_f}^2 + \frac{U^2}{\alpha} \| \| z^N \| \|_{1/2, \Gamma_f}^2 \right],
\end{aligned}$$

which enables one to derive the estimates required for the *a priori* estimate on z^N for κ large enough. Let us explain how. From the previous inequality, one has (the norm on $\tilde{H}^{-1/2}(\Gamma_f)$ can be chosen equal to $\sqrt{m_s(\cdot)}$ or equivalently to $\| \| \cdot \| \|_{-1/2, \Gamma_f}$):

$$\begin{aligned}
&a_s(z^N, z^N) + \kappa^2 m_s(z^N, z^N) + 2U\kappa\varrho \int_{\Gamma_f} G(z^N) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s z^N \\
&\geq \kappa^2 (1 - \alpha c_3 \varrho) \| \| z^N \| \|_{-1/2, \Gamma_f}^2 + a_s(z^N, z^N) - \frac{\varrho c_3 U^2}{\alpha} \| \| z^N \| \|_{1/2, \Gamma_f}^2
\end{aligned}$$

In order to lower bound the previous quantity, let us consider a splitting of the space $H_0^1(\Gamma_f)$ into two subspaces as describe in the following lemma (let us denote by $((\cdot, \cdot))$ the natural scalar product on $H^{1/2}(\Gamma_f)$).

Lemma 19. *Let $\zeta > 0$ and let $A_\zeta(w, v) = a_s(w, v) - \zeta((w, v))$. There exists a finite dimensionnal subspace E_ζ and a real number $\delta_\zeta > 0$ such that the bilinear form $\delta_\zeta m_s(w, v) + A_\zeta(w, v)$ is coercive on $H_0^1(\Gamma_f)$.*

Proof of Lemma 19. Applying the spectral theorem to the eigenvalue problem

$$a_s(\tilde{w}, v) = \tilde{\mu}((\tilde{w}, v)),$$

there exists an Hilbert basis of eigenvectors \tilde{w}_k ($k > 0$) corresponding to a non negative increasing sequence of eigenvalues $\tilde{\mu}_k$ which tends to the infinity. The bilinear form A_ζ is a non negative one except on a finite dimensionnal subspace of $H_0^1(\Gamma_f)$ denoted by E_ζ . On that space E_ζ , norms m_s and $\|\cdot\|_{1/2, \Gamma_f}$ are equivalent. For some $c_0 > 0$,

$$\forall v \in E_\zeta, \quad \delta_\zeta m_s(v, v) + A_\zeta(v, v) \geq c_0 \delta_\zeta((v, v)) + A_\zeta(v, v) \geq a_s(v, v).$$

Therefore, there exists $\delta_\zeta > 0$ such that $\delta_\zeta m_s(v, v) + A_\zeta(v, v)$ is coercive on $H_0^1(\Gamma_f)$ which proves Lemma 19. \square

Let $\zeta > 0$ be fixed. The classical spectral theorem can be applied to the eigenvalue problem $\delta_\zeta m_s(w, v) + A_\zeta(w, v) = \mu m_s(w, v)$ which is equivalent to:

$$\begin{cases} \text{find } \mu \in \mathbb{R}, w \in H_0^1(\Gamma_f) \text{ such that: } \forall v \in H_0^1(\Gamma_f), \\ \mu m_s(w, v) = a_s(w, v) - \zeta((w, v)). \end{cases} \quad (68)$$

There exists a non decreasing sequence $\{\mu_k\}$ in \mathbb{R} with only the infinity as accumulation point and an Hilbert basis $\{w_k\}$ in $\tilde{H}^{-1/2}(\Gamma_f)$ equipped with norm $\sqrt{m_s}$ of eigenvectors solution of (68) which are orthogonal for A_ζ . Furthermore, it has been proved in the previous lemma that the space spanned by the eigenvectors w_k , $k = 1, P$ corresponding to negative eigenvalues of the model (68) is a finite dimensional one. It is denoted by V_P . Let us choose $\zeta = \varrho \frac{c_3 U^2}{\alpha}$. This enables one to derive the following lower bound on the space V_P :

$$\forall v \in V_P, \quad \kappa^2(1 - \alpha c_3 \varrho) m_s(v, v) + a_s(v, v) - \frac{\varrho c_3 U^2}{\alpha} \|v\|_{1/2, \Gamma_f}^2$$

$$\geq [\kappa^2(1 - \alpha c_3 \varrho) + \mu_1] m_s(v, v).$$

But on the finite dimensional space V_P all the norms are equivalent. Thus choosing

$$\alpha < \frac{1}{c_3 \rho} \quad \text{and} \quad \kappa^2 > -\frac{\mu_1}{1 - \alpha c_3 \varrho} > 0,$$

one can conclude that there exists a positive constant \tilde{c}_P such that:

$$\begin{aligned} \forall v \in V_P, \quad & \kappa^2(1 - \alpha c_3 \varrho) m_s(v, v) + a_s(v, v) - \frac{\varrho c_3 U^2}{\alpha} \|v\|_{1/2, \Gamma_f}^2 \\ & \geq \tilde{c}_P \|v\|_{1, \Gamma_f}^2. \end{aligned} \quad (69)$$

On the orthogonal complementary space V_P^\perp of V_P in $H_0^1(\Gamma_f)$ equipped with the scalar product a_0 , the previous inequality is also satisfied and there exists $d_P > 0$ such that :

$$\begin{aligned} \forall v \in V_P^\perp, \quad & \kappa^2(1 - \alpha c_3 \varrho) m_s(v, v) + a_s(v, v) - \frac{\varrho c_3 U^2}{\alpha} \|v\|_{1/2, \Gamma_f}^2 \\ & \geq d_P \|v\|_{1, \Gamma_f}^2. \end{aligned} \quad (70)$$

Since the basis $\{w_k\}$ is orthogonal for the entire bilinear form $\kappa^2(1 - \alpha c_3 \varrho) m_s(v, v) + a_s(v, v) - \frac{\varrho c_3 U^2}{\alpha} \|v\|_{1/2, \Gamma_f}^2$, one easily gets with $c_P = \min(\tilde{c}_P, d_P) > 0$,

$$\begin{aligned} \forall v \in V_P, \quad & \kappa^2(1 - \alpha c_3 \varrho) m_s(v, v) + a_s(v, v) - \frac{\varrho c_3 U^2}{\alpha} \|v\|_{1/2, \Gamma_f}^2 \\ & \geq c_P \|v\|_{1, \Gamma_f}^2 \end{aligned} \quad (71)$$

and thus there exists $c_P > 0$ and $\kappa > 0$ such that :

$$\begin{aligned} \forall v \in V_P, \quad & \kappa^2 m_s(v, v) + a_s(v, v) + 2\rho U \int_{\Gamma_f} G(v) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s v \\ & \geq c_P \|v\|_{1, \Gamma_f}^2 \end{aligned} \quad (72)$$

Finally, it has been proved that for any velocity U , there exists a constant $\kappa \geq 0$ and another one c_P such that :

$$\begin{aligned} & m_s\left(\frac{\partial z^N}{\partial t}, \frac{\partial z^N}{\partial t}\right) + a_s(z^N, z^N) + \kappa^2 m_s(z^N, z^N) \\ & + 2U \kappa \varrho \int_{\Gamma_f} G(z^N) \nabla_s \tilde{\Phi}_0 \cdot \nabla_s z^N \\ & \geq c_P [\|z^N\|_{-1/2, \Gamma_f}^2 + \|z^N\|_{1, \Gamma_f}^2]. \end{aligned} \quad (73)$$

The *a priori* estimate on z^N is then derived from the Gronwall's lemma (see for instance [JLL 69]) on the inequality (67). It is obtained in the space

$$L^\infty(]0, T[; H_0^1(\Gamma_f)) \cap W^{1, \infty}(]0, T[; \tilde{H}^{-1/2}(\Gamma_f)),$$

and one can conclude to the existence and the uniqueness of a solution to the instable model exactly as in the case where $U < \sqrt{\lambda_1}$. The theorem 18 is proved. \square

Remark 20. *One can consider several kind of boundary conditions on $\partial\Gamma_f$ concerning η . For instance, one can set:*

$$\frac{\partial\eta}{\partial\nu} + \alpha\eta = 0 \text{ sur } \partial\Gamma_f, \quad (74)$$

which is a Robin's boundary condition. If $\alpha = 0$ there is a perfect gliding of the water, if $\alpha = \infty$ there is an adhesion of the water. But one can also consider a condition as:

$$\frac{\partial\eta}{\partial t} + \gamma \frac{\partial\eta}{\partial\nu} + \delta\eta = 0, \quad (75)$$

and so on.

The most suitable boundary condition for η is certainly a transparency one (L Halpern [Hal 06]) in order to avoid reflection. But it would also be useful to use such a condition for φ on Γ_1 . This will be discussed in a future work.

6 The model formulated with φ

The elimination of η is quite easy from the theoretical point of view, but much more complicated in the practical applications as far as the capillary is kept. In fact the goal is to transform a Lagrangian formulation into an Euler one using advective derivation:

$$D_t(\cdot) = \frac{\partial}{\partial t}(\cdot) + U\nabla_s\tilde{\Phi}_0 \cdot \nabla_s(\cdot)$$

Thus, one has on $\Gamma_f \times]0, T[$:

$$\left\{ \begin{array}{l} \text{on the one hand:} \\ \frac{\partial\varphi}{\partial\nu} = D_t\eta, \\ \text{and on the other hand:} \\ -\sigma\Delta_s D_t\eta + g\rho D_t\eta = \\ -[\rho \frac{\partial^2\varphi}{\partial t^2} + 2\rho U\nabla_s\tilde{\Phi}_0 \cdot \nabla_s \frac{\partial\varphi}{\partial t} + \rho U^2\nabla_s\tilde{\Phi}_0 \cdot \nabla_s(\nabla_s\tilde{\Phi}_0 \cdot \nabla_s\varphi)]. \end{array} \right. \quad (76)$$

Furthermore, φ satisfies the relations (4) in Ω and on $\Gamma_0 \cup \Gamma_1$.

Let us begin with the usual -but physically wrong- case where $\sigma = 0$ (no capillary term). Let us consider $\psi \in W_0$ and multiplying (4) by ψ , and integrating by parts, one obtains (let us recall that $\varphi = 0$ on $\partial\Gamma_f$ and therefore boundary terms disappear in an integration by parts):

$$\left\{ \begin{array}{l} \forall \psi \in W_0, \int_{\Omega} \nabla \varphi \cdot \nabla \psi + \frac{1}{g} \int_{\Gamma_f} \frac{\partial^2 \varphi}{\partial t^2} \psi \\ + U \int_{\Gamma_f} \nabla_s \tilde{\Phi}_0 \cdot \nabla_s \left(\frac{\partial \varphi}{\partial t} \right) \psi - (\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \psi) \frac{\partial \varphi}{\partial t} - \Delta_s \tilde{\Phi}_0 \frac{\partial \varphi}{\partial t} \psi \\ - U^2 \int_{\Gamma_f} (\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \varphi) (\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \psi) - U^2 \int_{\Gamma_f} \Delta_s \tilde{\Phi}_0 (\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \varphi) \psi = 0. \end{array} \right. \quad (77)$$

This variational equation which corresponds to the local equation (4) is the wellknown Neumann-Kelvin model [STO 57]. Let us point out again that its numerical implementation is fully instable excepted for $U = 0$.

Let us now go to the case $\sigma > 0$. Let Z_0 be the distribution space on Γ_f defined by (it would be different for other boundary condition on $\partial\Gamma_f$):

$$Z_0 = H^{-1}(\Omega). \quad (78)$$

Let us define by A the operator which maps Z_0 onto $H_0^1(\Gamma_f)$ defined by:

$$A = \left[-\frac{\sigma}{\rho} \Delta_s + g I_d \right]^{-1}. \quad (79)$$

This is a regularizing operator which enables to define the up-graded (with capillary) Neumann-Kelvin variational model by:

$$\left\{ \begin{array}{l} \forall \psi \in W_0, \int_{\Omega} \nabla \varphi \cdot \nabla \psi + \frac{1}{g} \int_{\Gamma_f} A \left[\frac{\partial^2 \varphi}{\partial t^2} \right] \psi \\ + 2U \int_{\Gamma_f} A [\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \left(\frac{\partial \varphi}{\partial t} \right)] \psi + U^2 \int_{\Gamma_f} A [(\nabla_s \tilde{\Phi}_0 \cdot \nabla_s (\nabla_s \tilde{\Phi}_0 \cdot \nabla_s \varphi))] \psi = 0. \end{array} \right. \quad (80)$$

Remark 21. *The mathematical analysis of Neumann-Kelvin model upgraded with the capillary term is not necessary because it is equivalent to the one in η . But the numerical approximation is easier for the model in η because the order of the tangential derivatives are smaller.*

7 A simple analytical example

Let us consider the open set $\Omega =]0, L[\times]0, H[$ which is represented on figure 2. It is a rectangle the width of which is L and the height H . In order to simplify the computation let us consider an homogeneous Neumann's boundary condition




Figure 2: Geometry used for the analytical example

for φ on Γ_1 . Let us choose for sake of simplicity Neumann's boundary condition on Γ_1 . The eigenvalue model (55) can be written:

$$\left\{ \begin{array}{l} -\Delta\varphi = 0 \text{ in } \Omega, \\ \frac{\partial\varphi}{\partial\nu} = 0 \text{ on } \Gamma_0 \cup \Gamma_1, \\ -\sigma\Delta_s\eta + \varrho g\eta + \lambda\varrho \frac{\partial\varphi}{\partial x_1} = 0 \text{ and } \frac{\partial\varphi}{\partial\nu} = \frac{\partial\eta}{\partial x_1} \text{ on } \Gamma_f, \\ \eta = 0 \text{ on } \partial\Gamma_f. \end{array} \right. \quad (81)$$

One can solve it using a separation of the variables x_1 et x_2 (see figure 2). Thus, one obtains a sequence of solutions depending on the integer n :

$$\left\{ \begin{array}{l} \eta_n(x_1, x_2) = \sqrt{\frac{2}{L}} \sin\left(\frac{n\pi x_1}{L}\right), \\ \varphi(x_1, x_2) = \sqrt{\frac{2}{L}} \cos\left(\frac{n\pi x_1}{L}\right) \coth\left(\frac{n\pi(x_2 + H)}{L}\right), \\ \lambda_n = \left[gH + \frac{n^2\pi^2\sigma H}{L^2\varrho} \right] \frac{\tanh\left(\frac{n\pi H}{L}\right)}{\frac{n\pi H}{L}} \underset{\approx}{\overset{H \text{ large}}{\simeq}} \frac{g}{k} + \frac{\sigma k}{\varrho}, \quad k = \frac{n\pi}{L}. \end{array} \right. \quad (82)$$

Let us introduce the minimizer $x_0 = \sqrt{\frac{g\rho}{\sigma}} \frac{L}{\pi}$ of the function $f(x) = \frac{gL}{\pi x} + \frac{\sigma\pi x}{\rho L}$. Let us define the integer $[x_0]$ as the entire part of x_0 . One can easily prove that

$$U_c = \min(\sqrt{f([x_0])}, \sqrt{f([x_0] + 1)})$$

$$= \begin{cases} \sqrt{f([x_0])} & \text{if } x_0 \leq \sqrt{[x_0]^2 + [x_0]} \\ \sqrt{f([x_0] + 1)} & \text{if } x_0 > \sqrt{[x_0]^2 + [x_0]} \end{cases} \quad (83)$$

In the same context than J. Lighthill, we obtain a value close to (corresponding to $f(x_0)$) $\sqrt{\frac{2g}{k}} = \sqrt{2}(\frac{g\sigma}{\rho})^{1/4}$, which is a value given by J. Lighthill [LIH 78] but from a different formulation (using a Fourier's transform in the x_1 direction). One can find the same expression which is discussed in the paper by D. Richard and de P. G. Gennes [RIC 96]. Their framework is also the one of J. Lighthill. For instance, for $g = 9.81 \text{ m/s}^2$, $\sigma = 7,5 \cdot 10^{-2} \text{ N/m}$, $\rho = 1000 \text{ kg/m}^3$, one obtains: $x_0 = 361.67$ and thus

$$U_c = f(362) = 0.233 \text{ m/s}, \quad (84)$$

which is a well known value by engineers. It is worth to comment it. If the flow velocity is smaller than U_c , there are no instability on the surface. Engineers are used to say that there is no wave on the surface in this case. But the formulation given here enables to have a complete explanation of the phenomenon and can be applied to any geometry. In particular, this enables to take into account the shape of the bottom of the sea in shallow-water or the influence of a submarine under the surface.

The evolution of the eigenvalues λ_n have been plotted for different values of σ with respect to the wave length number $k = \frac{n\pi}{L}$. In particular, one can observe that for $\sigma = 0$ the sequence of eigenvalues tends to zero as $n \rightarrow \infty$. The point is that this result is true for arbitrary geometry and not only the particular one used by Lighthill.

In case of Dirichlet boundary conditions on Γ_1 , computations are much more complicated and not so explicit.

8 Remark on the non linear behaviour for the solution given at section 7

Let us consider that the velocity U is larger than the critical value U_c of the system (55). There exists a single eigenmode which is instable. It is denoted by: (λ_1, w_1) .




Figure 3: First eigenvalue of (55) versus k for several values of σ

The model in φ is assumed to be still valid and it is up-graded by the addition of the quadratic term containing the gradient of φ in the expression of the pressure.

Let us recall that this term is $|\nabla\varphi|^2 = \frac{\partial\varphi^2}{\partial\nu} + |\nabla_s\varphi|^2$. Another non-linear term should be considered see (4) but is omitted for sake of simplicity. Thus, one obtains the new wave model in the example of section 7:

$$\left\{ \begin{array}{l} -\sigma\Delta_s\eta + \varrho g\eta + \varrho G\left(\frac{\partial^2\eta}{\partial t^2}\right) + \varrho U\left[\frac{\partial G\left(\frac{\partial\eta}{\partial t}\right)}{\partial x_1} + \frac{\partial G\left(\frac{\partial\eta}{\partial x_1}\right)}{\partial t}\right] \\ + \varrho U^2 \frac{\partial G\left(\frac{\partial\eta}{\partial x_1}\right)}{\partial x_1} + \frac{\varrho}{2}\left[\left|\frac{\partial G\left(\frac{\partial\eta}{\partial t} + U\frac{\partial\eta}{\partial x_1}\right)}{\partial x_1}\right|^2 + \left|\frac{\partial\eta}{\partial t} + U\frac{\partial\eta}{\partial x_1}\right|^2\right] = 0, \end{array} \right. \quad (85)$$

where the operator G is the one defined at (17). The variational formulation of this non-linear model is (the functional space V_{NL} should be defined in order

to make sense to the non-linear terms):

$$\left\{ \begin{array}{l} \text{find } \eta(t) \in V_{NL} \text{ such that:} \\ \forall v \in V_{NL} \quad m_s(\frac{\partial^2 \eta}{\partial t^2}, v) + 2Uc_s(\frac{\partial \eta}{\partial t}, v) + a_s(\eta, v) \\ + \frac{\rho}{2} \int_{\Gamma_f} [|\frac{\partial \eta}{\partial t} + U \frac{\partial \eta}{\partial x_1}|^2 + |\frac{\partial G(\frac{\partial \eta}{\partial t} + U \frac{\partial \eta}{\partial x_1})}{\partial x_1}|^2] v = 0. \end{array} \right. \quad (86)$$

Let us look for an approximate solution which has the simple expression:

$$\eta = \xi(t)w_1.$$




Figure 4: Non-linear oscillations of the linear instability

Choosing the test function v in the one dimensional space spanned by w_1 , one obtains a non-linear differential equation (c_s is anti-symmetrical and thus $c_s(w_1, w_1) = 0$):

$$\ddot{\xi} + (\lambda_1 - U^2)\xi + A\dot{\xi}^2 + B\xi\dot{\xi} + C\xi^2 = 0 \text{ où } A > 0 \text{ et } C > 0. \quad (87)$$

In order to illustrate our discussion, the numerical solutions of this equation (87) are plotted on figures 4 and 5. In the first case there is an oscillation of




Figure 5: Instability of the non linear model

the linear instability and in the second one the non-linear solution is instable (both are instable for the linearized model). But, one has to be careful concerning the validity of such simulation because only one eigenmode is used and furthermore the stable components which are coupled with the instable eigenmode is omitted. Furthermore a non-linear term contained in the kinematical relation(4) has been omitted. A much more complete discussion on non-linear waves including more realistic models is given in G. Ioss and P. Kirrmann [?]. A mechanical analysis of these non-linear waves in shallow water is explicated in R. Timman, A.J. Hermans and G.C. Hisao [TIM 85].

9 Remark on the time step numerical scheme for η

Let us just give few remarks (in the case where $\Delta_s \tilde{\Phi}_0 = 0$ on Γ_f) for solving the progressive wave model which can generate instabilities. First of all, let us underline that the finite element method is certainly more appropriate as far as the non-linear term should be taken into account in case of an instability and the eigenvalues of several model should be computed. The difficulty is to use a time-step scheme which remains stable until the physical instability (at least). One criterion is to check the energy conservation for the numerical

approximation. One trap to avoid is to transform the gyroscopic effect into a negative damping which would generate an artificial instability. Therefore, a centered scheme in time for this term is better. An up-wind scheme would delayed the apparition of the critical velocity but increase the stability of the scheme. It is obtained for instance by writting the approximate equation at the middle between $n\Delta t$ and $(n+1)\Delta t$ where Δt is the time step. Let η^n be the approximation of η at time $t = n\Delta t$. A first possible scheme is:

$$m_s \left(\frac{\eta^{n+1} - 2\eta^n + \eta^{n-1}}{\Delta t^2}, v \right) + 2Uc_s \left(\frac{\eta^{n+1} - \eta^n}{\Delta t}, v \right) + a_s \left(\frac{\eta^{n+1} + \eta^n}{2}, v \right) = 0.$$

By choosing the test function v equal to $\eta^{n+1} - \eta^n$ and making use of Cauchy-Schwarz's inequality one deduces that:

$$\begin{aligned} \frac{1}{2} m_s \left(\frac{\eta^{n+1} - \eta^n}{\Delta t}, \frac{\eta^{n+1} - \eta^n}{\Delta t} \right) + \frac{1}{2} a_s(\eta^{n+1}, \eta^{n+1}) \\ \leq \frac{1}{2} m_s \left(\frac{\eta^n - \eta^{n-1}}{\Delta t}, \frac{\eta^n - \eta^{n-1}}{\Delta t} \right) + \frac{1}{2} a_s(\eta^n, \eta^n) \end{aligned} \quad (88)$$

which proves that the scheme is stable as far as a_s (defined in (44)) is strictly positive (the energy is decreasing which suggests that a numerical damping is introduced). This is the case if $U \leq \sqrt{\lambda_1}$. But if an instability occurs, it is more appropriate to center the scheme around the time $n\Delta t$ in order to avoid an upward glidding of the critical velocity due to the artificial damping. Therefore one can consider the following scheme which can be stable even if the critical velocity is delayed:

$$m_s \left(\frac{\eta^{n+1} - 2\eta^n + \eta^{n-1}}{\Delta t^2}, v \right) + 2Uc_s \left(\frac{\eta^{n+1} - \eta^{n-1}}{2\Delta t}, v \right) + a_s \left(\frac{\eta^{n+1} + \eta^{n-1}}{2}, v \right) = 0.$$

By choosing for the test function $v = \eta^{n+1} - \eta^{n-1}$ one obtains now an energy conservation property which ensure that no artificial damping is introduced. But the expression which ensure the stability is different from the energy. It is the next one (which contains twice the kinetical energy):

$$\begin{aligned} m_s \left(\frac{\eta^{n+1} - \eta^n}{\Delta t}, \frac{\eta^{n+1} - \eta^n}{\Delta t} \right) + \frac{1}{2} a_s(\eta^{n+1}, \eta^{n+1}) \\ = m_s \left(\frac{\eta^n - \eta^{n-1}}{\Delta t}, \frac{\eta^n - \eta^{n-1}}{\Delta t} \right) + \frac{1}{2} a_s(\eta^{n-1}, \eta^{n-1}) \end{aligned} \quad (89)$$

This result is a useful indicator which proves that the scheme doesn't introduce any artificial damping and therefore the instability can only occur when the bilinear form a_s is no more strictly positive. This a strong argument for this scheme even if the physical energy of the numerical scheme is not constant with respect to the time variable.

10 Conclusion

In this paper a modification of the Neumann-Kelvin's wave model for the unstable progressive wave is discussed and analyzed. Let us underline the main points:

1 The role of the capillary is explained in mathematical framework for the physical equations for progressive waves. It is proved that the classical Neumann-Kelvin's model is fully unstable and should be modified in order to be mechanically reliable.

2 It is shown that the best way to take into account the capillary is to use a formulation where the normal displacement η of the free surface appears as a main unknown variable. Thus one can eliminate the velocity potential φ making use of the added mass operator. This operator plays a basic role in the equilibrium energy between the gravity and the capillary. On simple examples the first instability due to the velocity U occurs when the energy of the capillary reach the same level as the one of the gravity (see the example treated in section 7). This critical velocity is characterized by an eigenvalue problem.

3 As far as one has to consider a coupling of the sea with a ship, the formulation in η is much more appropriate than the one in φ . For instance the slamming between the shell of the ship and the surface of the water can be formulated with respect to η . Furthermore the mathematical model of progressive waves formulated in η -even if it is equivalent to the one in φ - has better properties for the numerical implementation.

There are other physical mechanisms which should be added to the progressive wave model. For instance the vortex have been eliminated in the potential model, but the viscosity should play a role in the damping of wave and the characterization of the critical velocity U_c . The compressibility of the water is certainly acceptable inside the water, but much less for the surface waves. The coupling with the atmosphere is a fundamental problem and it can change a lot the behaviour of the progressive waves, mainly if temperature gradient are meaningful.

Our goal was to focus on the validity (in fact the non-validity) of the Neumann-Kelvin model) for which a modification is suggested in order to overcome classical difficulties mentioned in many scientific contributions.

Acknowledgments The authors thank Th. Gazzola and X.B. Chen from Bureau Veritas for their judicious remarks and valuable comments during this work.

References

- [ADA 75] R. Adams, *Sobolev spaces*, Academic press, New York, (1975).
- [ALLA 08] B. Alvarez-Samaniego and D. Lannes, *Large Time Existence for 3D water-waves and asymptotics*, *Inventiones Mathematicae*, **171**, p. 485–541, (2008).
- [KON 06] M. Borsuk and V. Kondratiev, *Elliptic Boundary Value Problems of Second Order in Piecewise Smooth Domains*, North Holland, Mathematical Library, Amsterdam, (2006).
- [BRE 83] H. Brezis, *Analyse Fonctionnelle*, edition Masson, Paris, (1983).
- [CAM 02] E. F. Campana and A. Iafrati, Direct numerical simulation of surface tension dominated and non-dominated breaking waves, 24th symposium on Naval hydrodynamics, Fukuoka Japan, July (2002).
- [CHEN 01] Xiao-bo Chen, On the singular and highly oscillatory properties of the Green function for ship motions, *J. Fluid Mechs.*, vol. 445, pp. 77-91, (2001).
- [CHEN 02] Xiao-bo Chen, Role of the surface tension in modelling ship waves, Proc. of the 17th Inter. Workshop on water Waves and floating bodies, edited by R. C. Rayney and S. F. Lee, Peterhouse Cambridge, UK 14-17 april, pp. 25-28, (2002).
- [DCF 08] Ph Destuynder, C. Fabre, A modelling of springing, whipping and slamming for ships, *Communications on Pure and Applied Analysis*, vol. 8, n^o1, pp. 209-228, (2008).
- [DCF 09] Ph. Destuynder, C. Fabre, Whipping phenomenon for surface ship coupled with instable waves, Internal research report CNAM-Université d’Orsay, (2009).
- [DIKH 99] F. Dias and C. Kharif *Nonlinear Capillary and Capillary-gravity waves*, *Annu. Rev. Fluid Mech*, **31**, p. 301–46 (1999).
- [DOU 95] Y. Doutréleau, Résonances pour le problème de Neumann-Kelvin tridimensionnel dans le cas d’un corps immergé, 5th journées de l’hydrodynamique, , Rouen, mars (1995).
- [DUV 90] G. Duvaut, *Mécanique des milieux continus*, Dunod, Paris, (1990).
- [GAZZ 05] Th. Gazzola, A. Korobkin, Sime Malenica and Yves-Marie Scolan, Three- dimensional Wagner problem using variational inequalities, in “Proceedings of the 20th International Workshop on Water Waves and Floating Bodies,” (2005).

- [GAZ 07] Th. Gazzola, Modélisation du phénomène de tossage pour les bateaux, Thèse de l'Ecole Centrale de Paris, (2007).
- [GRI 86] P. Grisvard, *Singularities In Boundary Value Problems*, Masson, Paris, (1992).
- [HAC 02] J. P. Hackett, G. K. Kapsenberg and A. P. van Veer, *Whipping loads due to aft body slamming*, 24th Symposium on Naval Hydrodynamics, Fukuoka Japan, July, (2002).
- [Hal 06] L. Halpern. Absorbing Boundary Conditions and Optimized Schwarz Waveform Relaxation. BIT, vol. 46, November 2006, pp 21-34, (2006).
- [TIM 85] A.J Hermans, G.C Hsiao and R. Timman, *Water waves and ship hydrodynamics*, Delft University Press, The Netherlands, (1985).
- [HOL 04] D. S. Holloway, G. A. Thomas and M. R. Davis, Added mass of whipping modes for ships at high Froude number by a free surface boundary element method coupled with strip theory, ANZIAM J., **45** (2004), C831-C844.
- [IOKI 92] G. Iooss and K. Kirchgessner, *Water waves for small surface tension: an approach via normal form*, Proc. Roy. Soc. Edin. **122A**, p. 267–299, (1992).
- [IOS 96] G. Ioss P and Kirrmann, *Capillary Gravity Waves on the Free Surface of an Inviscid Fluid of Infinite Depth, Existence of Solitary Waves*, Arch. Rational Mech. Anal. vol. 136, pp. 1-19, Springer-Verlag, (1996).
- [KEL 87] Kelvin Lord (Sir Thomson), On the waves produced by a single input in water of any depth, or in a dispersive medium, In: *Proceedings of the Royal Society of London*, series A, vol. 42, pp. 80-85, (1887).
- [KOR 07] A. Korobkin, *Second-order Wagner theory of wave impact*, J. Engineering Mathematics, **58**, p. 121–139, (2007).
- [LAL 71] L. Landau, E. Lipschitz, *Mécanique des fluides*, Editions de Moscou, (1971).
- J. Engineering Mathematics, **58**, p. 121–139, (2007).
- [LIH 78] J. Lighthill, *Waves in fluids*, Cambridge university press, (1978).
- [LM 68] J. L. L. Lions and E. Magenes, *Problèmes aux limites non homogènes et applications, Tome 1*, Dunod, Paris, (1968).
- [JLL 69] J. L. Lions, *Quelques méthodes de résolution des problèmes aux limites non-linéaires*, Dunod, Paris, 1969.

- [MOA 81] D.S. Moak, The q -analogue of the Laguerre polynomials, *J. Math. Anal. Appl.*, **81**, pp. 20-47, (1981).
- [MRO 92] J. P. Morand and R. Ohayon, *Interactions fluides-structures*, RMA n^o23, Masson, Paris, 1992.
- [NEC 67] J. Necas, *Les méthodes directes en théorie des équations elliptiques*, Masson, Paris, 1967.
- [RATO 83] P. A. Raviart and J. M. Thomas, *Introduction à l'analyse numérique des équations aux dérivées partielles*, Masson, Paris, 1983.
- [RIC 96] D. Richard and P. G. de Gennes, Capillary gravity waves caused by a moving disturbance wave resistance, *J. Phys. Rev. E.*, vol. 53, pp. 3448-3455, (1996).
- [STOE 92] C. Van der Stoep, 'A three dimensional method for the calculation of the unsteady ship wave pattern using a Neumann-Kelvin approach, Thesis university of technology of Delft, February 6th 1992.
- [STO 57] J. J. Stoker, *Water waves*, Pure and applied mathematics, vol. IV, Interscience publishers, Inc., New York (1957).
- [STO 07] G. Storhaug, Experimental investigation of wave induced vibrations and their effect on the fatigue loading of ships, Thesis Oslo, Department of Marine Technology Faculty of Engineering Science and Technology Norwegian University of Science and Technology, 2007.
- [TIM 85] R. Timman, A.J. Hermans and G.C. Hsiao, *Water waves and ship hydrodynamics*, Delft university-press, the Netherlands, (1985).
- [TRU 01] K. Trulsen and C. T. Stansberg, Spatial evolution of water surface waves: Numerical simulation and experiment of bichromatic waves, Proceedings of the eleventh international offshore and polar engineering conference, Stavanger, Norway, June 17-22, 2001.
- [Yan 00] C. Yang, R. Lohner, F. Noblesse and Th. T. Huang, Calculation of ship sinkage and trim using unstructured grids, ECCOMAS 2000, Barcelona, 11-14 September, (2000).
- [WAG 32] H. Wagner, Über Stoss und Gleitvorgänge an der Oberfläche von Flüssigkeiten, *ZAMM.*, **12** (1932), pp. 193-215.