



Central European Olympiad in Informatics
Tîrgu Mureş, România
July 8 – 14, 2009
Contest Day 2

tri

100 points

Source code: `tri.c`, `tri.cpp`, `tri.pas`
Input files: `tri.in`
Output files: `tri.out`
Time limit: `2 s`
Memory limit: `64 MB`

Task

You are given K points with positive integer coordinates. You are also given M triangles, each of them having one vertex in the origin and the other 2 vertices with non-negative integer coordinates.

You are asked to determine for each triangle whether it has at least one of the K given points inside. (None of the K points are on any edge of any triangle.)

Input

The first line of the input file `tri.in` will contain K and M . The following K lines will contain 2 positive integers x y separated by one space that represent the coordinates of each point. The next M lines have 4 non-negative integers separated by one space, (x_1, y_1) and (x_2, y_2) , that represent the other 2 vertices of each triangle, except the origin.

Output

The output file `tri.out` should contain exactly M lines. The k -th line should contain the character Y if the k -th triangle (in the order of the input file) contains at least one point inside it, or N otherwise.

Constraints

- $1 \leq K, M \leq 100\ 000$
- $1 \leq$ each coordinate of the K points $\leq 10^9$
- $0 \leq$ each coordinate of the triangle vertices $\leq 10^9$
- Triangles are not degenerate (they all have nonzero area).
- In 50% of the test cases, all triangles have vertices with coordinates $x_1=0$ and $y_2=0$. That is, one edge of the triangle is on the x -axis, and another is on the y -axis.



Central European Olympiad in Informatics
Tîrgu Mureş, România
July 8 – 14, 2009
Contest Day 2

Example

tri.in	tri.out	Explanation
<pre> 4 3 1 2 1 3 5 1 5 3 1 4 3 3 2 2 4 1 4 4 6 3 </pre>	<pre> Y N Y </pre>	

tri.in	tri.out	Explanation
<pre> 4 2 1 2 1 3 5 1 4 3 0 2 1 0 0 3 5 0 </pre>	<pre> N Y </pre>	