

Central European Olympiad in Informatics

28 July – 4 August 2005 Sárospatak, Hungary
<http://ceoi.inf.elte.hu>

Ticket Office

We provide an algorithm using greedy method. The algorithm works in three steps.

The first step allocates as many full-price orders as possible. The greedy method processes the orders in decreasing order of the seat number and allocates it if possible. Denote the resulted schedule by $S1$.

The second step modifies the schedule $S1$ to minimize the wastage. It means that it replaces $p1$ with an order p for which $p < p1$ and $p \bmod L$ is minimal (where L is the number of seats in the bunch).

The third step fills in the gaps between full-price orders with half-price orders resulting the schedule $S3$.

We prove that $S3$ is an optimal schedule.




Figure 1:

Let S be an optimal schedule, that is a schedule resulting maximal income. We apply usual method of proving correctness of greedy algorithm. We modify S step by step to obtain $S3$ while the total income remains the same.

Let k be the number of scheduled full-price orders in $S1$. First we prove that there is an optimal schedule with k full-price orders. The number of full-price orders in S is at most k . Assume that the number of full-price orders in S is less than k . If there is an order p_i in $S1$ that does not collide with full-price order in S then p_i collides with at most 2 half-price order in S , therefore removing them from S and including p_i in S the total income does not decrease. See figure 2-a. Repeat this procedure until each order in $S1$ collides with at least one full-price order in S . If the number of full-price orders in S still less than k , then there is a situation shown in figure 2-b. Remove the orders from S that collide with either of the two orders in $S1$ and include the two orders of $S1$ in S .

We may assume that the half-price orders in the schedules are shifted on the left as much as possible. Let p_1 be the first seat




Figure 2:

number of the leftmost full-price order in $S1$, q_1 in $S3$ and r_1 in S . Notice that the full-price order at q_1 must collide with the full-price order at r_1 .

If $q_1 < r_1$ then the order at q_1 can not collide with half-price order in S , because in this case the waste would be less than for the first full-price order in $S3$ and the second step of our algorithm would choose it. Therefore we can remove the order at r_1 and include the order at q_1 in S . See figure 3.

Now consider the case $r_1 < q_1$.

Let k be the largest integer such that $a = k \cdot L < r_1$. Moreover, let b the smallest integer such that $a < b$ and the first half-price order in the S end at b . If there is no such half-price order then $b = m$ (m is the largest seat number). See figure 4. It is clear that the number of full-price orders in $S3$ between a and b equals the number of full-price orders in S between a and b . Moreover, if there is a half-price order in S ending at b that there is a half-price order in $S3$ at $a + 1$ and conversely. Therefore we can replace the orders of S located between a and b with the orders of $S3$ located between a and b without affecting the total income.

Consider the reduced problem when the available seats are $q_u \dots m$ and the orders are those that are not scheduled up to b .



Central European Olympiad in Informatics

28 July – 4 August 2005 Sárospatak, Hungary
<http://ceoi.inf.elte.hu>



Figure 3:



Figure 4:

Complexity:

Time: $O(n+m)$

Memory: $O(n+m)$

Implementation

```

Program ticket;
Const
  MaxN=100000;
  MaxM=30000;
Var
  N,m:longint;
  L:longint;
  Start,R:Array[0..MaxN] of longint;
  S:Array[0..MaxM] of longint;
  Sch:Array[0..MaxM] of longint;
  i,ii,k,x:longint;
  Lend,fn,gap,free:longint;
  Sol:longint;
  OutF:Text;

procedure ReadIn;
var
  InFile:Text;
  i,x:longint;
begin
  assign(InFile,'ticket.in'); reset(InFile);
  readln(InFile,m, L);
  readln(InFile, N);
  for i:=1 to N do begin
    read(InFile, x);
    Start[i]:=x;
    R[i]:=i;
  end {for i};
  Start[0]:=0;

```



Central European Olympiad in Informatics

28 July – 4 August 2005 Sárospatak, Hungary
<http://ceoi.inf.elte.hu>

```

    Start[n+1]:=m+1;
end {ReadIn};

procedure Sort;
var
    Nox:array[0..MaxM] of longint;
    i,ii,j,x:longint;
begin
    Nox[0]:=0;
    for x:=1 to m do Nox[x]:=0;
    for i:=1 to n do inc(Nox[Start[i]]);
    for x:=1 to m do Nox[x]:=Nox[x]+Nox[x-1];
    for i:=1 to n do begin
        ii:=Start[i];
        j:=Nox[ii];
        R[j]:=i;
        dec(Nox[ii]);
    end;
    R[0]:=0;
    R[n+1]:=n+1;
end {Sort};

Begin {Prog}
    ReadIn;
    Sort;
    fn:=0;
    Lend:=m+1;
{1. step: allocate full-price orders}
    for i:=N downto 1 do begin
        ii:=R[i];
        if Start[ii]+L<=Lend then begin
            inc(fn);
            S[fn]:=ii;
            Lend:=Start[ii];
        end;
    end {for i};

    for i:=1 to fn div 2 do begin
        x:=S[i]; S[i]:=S[fn-i+1];
        S[fn-i+1]:=x;
    end;
{2. step: modify the schedule to minimize the wastage }
    S[fn+1]:=n+1;
    free:=1;
    k:=1;
    gap:=m;
    Sol:=0;
    Lend:=Start[S[1]];
    for i:=1 to n do begin
        if Start[R[i]]>Lend then begin
            Sol:=Sol+(Start[S[k]]-free) div L+1;

```



Central European Olympiad in Informatics

28 July – 4 August 2005 Sárospatak, Hungary
<http://ceoi.inf.elte.hu>

```

    free:=Start[S[k]]+L;
    inc(k);
    Lend:=Start[S[k]];
    gap:=m;
end;
if (free<=Start[R[i]])and((Start[R[i]]-free) mod L<gap) then begin
    gap:=(Start[R[i]]-free) mod L;
    S[k]:=R[i];
end;
end {for i};

Sol:=Sol+(Start[S[fn]]-free) div L;
Sol:=Sol+(m-(Start[S[fn]]+1) div L;
if Sol>n then Sol:=n;
assign(OutF, 'ticket.out'); rewrite(OutF);
writeln(OutF, Sol+fn);
writeln(OutF, Sol);
{3. step: fill in the gaps with half-price orders}
for i:=1 to m do Sch[i]:=0;
for i:=1 to fn do
    for k:=Start[S[i]] to Start[S[i]]+L-1 do
        Sch[k]:=S[i];

free:=1; i:=1;
while i<=n do begin
    if free+L-1>m then break;
    if Sch[Start[R[i]]]=R[i] then begin
        inc(i); continue;
    end;
    k:=Sch[free+L-1];
    if (Sch[free]=0)and(k=0) then begin
        Sch[free]:=R[i];
        free:=free+L;
        inc(i);
    end else
        free:=Start[k]+L;
end {while i};
k:=1;
while k<=m do begin
    if Sch[k]>0 then begin
        writeln(OutF, Sch[k], ' ',k);
        k:=k+L;
    end else begin
        inc(k);
    end;
end;
close(OutF);
End.

```