



Central European Olympiad in Informatics

28 July – 4 August 2005 Sárospatak, Hungary

<http://ceoi.inf.elte.hu>

Depot Rearrangement

Let n be the number of shops and m be the number of products.

Consider the directed multi-graph $G = (V, E)$, where

$$V = \{p_1, \dots, p_n\} \cup \{q_1, \dots, q_m\}$$

For each i and for each j the edge set E of G contains (p_i, q_j) k -times iff the number of containers labeled by j in the container positions $[m * (i - 1) + 1, m * i]$ is $k + 1$ and $k > 0$.

A pair (q_j, p_i) is in E iff there is no container labeled by j in the container positions $[m * (i - 1) + 1, m * i]$. There is no other edge in G .

It is clear that for each node the number of incoming edges is equal to the number of outgoing edges. Consequently, each component of G has an Eulerian circuit. The number of moves is at least $\sum_{j=1}^m \text{Outdegree}(q_j)$. Moreover, for every component of the graph at least one container must be moved to the free position. Therefore the minimal number of moves is at least

$$c + \sum_{j=1}^m \text{Outdegree}(q_j)$$

where c is the number of components of G . The following algorithm uses this number of moves by performing the moves according to the Eulerian circuits.

Complexity:

Time: $O(|E| + n * m)$

Memory: $O(|E| + n * m)$

Implementation

```
program Depot;
Const
  MaxN=1000;      {max # shops}
  MaxM=1000;      {max # products}
  MaxNM=MaxN*MaxM; {max input length}
Type
  List=^Cell;
  Cell=record elem:integer; link:List end;

Var
  n,                {# shops}
  m:longint;       {# products}
  Pl:array[1..MaxNM+1] of longint;
  Poz:array[1..MaxN,1..MaxM] of longint;
  G,G0:array[boolean, 1..MaxN] of List;
  fromp,top,freep,i:longint;
  Nmove:longint;
  outFile:Text;

procedure ReadIn;
Var
  inFile:Text;
```



Central European Olympiad in Informatics

28 July – 4 August 2005 Sárospatak, Hungary

<http://ceoi.inf.elte.hu>

```

x, i, j: longint;
node: List;
begin
  assign(inFile, 'depot.in'); reset(inFile);
  readln(inFile, n, m);
  for i:=1 to MaxN do begin
    G[true, i]:=nil;
    G[false, i]:=nil;
  end;
  for i:=1 to n*m do Pl[i]:=0;
  for i:=1 to n do begin
    for j:=1 to m do
      Poz[i, j]:=0;
    end;
    for i:=1 to n*m do begin
      read(inFile, x);
      j:=(i-1) div m+1;
      if Poz[j, x]=0 then
        Poz[j, x]:=i
      else begin{add x to list of j}
        new(node);
        Pl[i]:=Poz[j, x];
        Poz[j, x]:=i;
        node^.elem:=x;
        node^.link:=G[true, j];
        G[true, j]:=node;
      end;
    end{for i};

    for i:=1 to n do
      for j:=1 to m do
        if Poz[i, j]=0 then begin{add i to list of j}
          inc(Nmove);
          new(node);
          node^.elem:=i;
          node^.link:=G[false, j];
          G[false, j]:=node;
        end;
      end;
    close(inFile);
  end{ReadIn};

  function FromPoz(v, t: longint): longint;
  Var p: longint;
  begin
    p:=Poz[v, t];
    Poz[v, t]:=Pl[p];
    FromPoz:=p;
  end;

```



Central European Olympiad in Informatics

28 July – 4 August 2005 Sárospatak, Hungary

<http://ceoi.inf.elte.hu>

```

end{FromPoz};

Procedure DFS(t:boolean; pre,p:integer; domove:boolean);
  Var q:integer;
begin{DFS}
  While G[t,p]<>Nil Do Begin{visiting all edge p->q }
    q:=G[t,p]^elem;
    G[t,p]:=G[t,p]^link;
    DFS(not t,p,q, domove);
  End{while};
  if domove and not t then begin
    fromp:=FromPoz(pre,p);
    writeln(outFile, fromp, ' ',top);
    top:=fromp;
  end;
end{DFS};

begin{program}
  Nmove:=0;
  ReadIn;
  assign(outFile, 'depot.out'); rewrite(outFile);
  G0:=G;
  for i:=1 to n do {increase NMove by the number of components}
    if G[true,i]<>nil then begin
      inc(NMove);
      DFS(true,G[true,i]^elem,i, false);
    end;
  writeln(outFile, NMove);

  G:=G0;
  freep:=n*m+1;
  for i:=1 to n do
    if G[true,i]<>nil then begin
      top:=freep;
      DFS(true,G[true,i]^elem,i, true);
      writeln(outFile, freep, ' ',fromp);
    end;
  close(outfile);
end.

```