



Day 2 – Task 2

Boats

The task can be solved using the following greedy algorithm. During the process we will maintain the set of tied boats S . At each step we try to insert one boat into the set, going from left to right, relative to the ring positions. We initialize S with boat tied to the leftmost ring, so that it is positioned maximally to the left. Let l and r be the coordinates of the endpoints of the last inserted boat and l_i and p_i the length and the ring position of the boat we are currently processing. If $p_i = r$, then we insert i^{th} boat to the set, positioning it to the leftmost possible position. If $p_i < r$ then we check if $l_i < r - l$ and if it holds then we delete last inserted boat from the set and insert the i^{th} boat, at the leftmost possible position. If it does not hold then we just skip the i^{th} boat. This solution is optimal, which can easily be proved by induction.

There are also other solutions based on dynamic programming approach.

Example solution in Pascal:



1st Junior Balkan Olympiad in Informatics Belgrade 2007

Day 2 – Task 2

```
const
    maxN = 10000;

type
    TBoat = record
        p, l : Longint;
    end;

var
    n, m : Integer;
    c : array[1..maxN] of TBoat;

procedure Sort;
var
    tmp : TBoat;

    procedure QuickSort(l, r : Integer);
    var
        i, j : Integer;
        p : Longint;
    begin
        i := l;
        j := r;
        p := c[(l + r) div 2].p;
        repeat
            while c[i].p < p do inc(i);
            while p < c[j].p do dec(j);
            if i <= j then
                begin
                    tmp := c[i];
                    c[i] := c[j];
                    c[j] := tmp;
                    inc(i);
                    dec(j);
                end;
            until i > j;
            if l < j then QuickSort(l, j);
            if i < r then QuickSort(i, r);
        end;
    end;

begin
    QuickSort(1, n);
end;

function Max(a, b : Longint) : Longint;
begin
    if a > b then
        Max := a
    else
        Max := b
    end;
end;

procedure Solve;
var
    i : Integer;
    l, r, t : Longint;
begin
    Sort;

    m := 1;
    r := c[1].p;

    for i := 2 to n do
        if c[i].p >= r then
            begin
```



1st Junior Balkan Olympiad in Informatics
Belgrade 2007

Day 2 – Task 2

```
    l := r;  
    r := Max(c[i].p, r + c[i].l);  
    inc(m);  
end else  
begin  
    t := Max(c[i].p, l + c[i].l);  
    if t < r then  
        r := t;  
    end;  
end;  
  
begin  
    Readln(n);  
    for i := 1 to n do  
        Readln(c[i].l, c[i].p);  
    Solve;  
    Writeln(m);  
end.
```