

Poisson point processes applied to sensors networks

Laurent Decreusefond, Eduardo Ferraz, Hugues Randriambololona

▶ To cite this version:

Laurent Decreusefond, Eduardo Ferraz, Hugues Randriambololona. Poisson point processes applied to sensors networks. Spatial Networks Models for Wirelles Communications, Apr 2010, Cambridge, United Kingdom. hal-00472487

HAL Id: hal-00472487 https://hal.science/hal-00472487

Submitted on 12 Apr 2010

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Poisson Point Processes Applied to Sensor Networks

{eduardo.ferraz, laurent.decreusefond, randriam}@telecom-paristech.fr





Motivation

The development of wireless ad hoc networking capability together with the decreasing costs and sizes of the electronical circuits allow an increasing using of sensor networks in building, utilities, industrial, home, agriculture, defense and many other contexts. The topology of such networks, particularly the connectiveness and coverage area, are important and, sometimes, critical factors. Recently, many works dealing with topology give interpretations and techniques capable to be applied on sensor networks. Besides, it is not possible to control the positions and number of sensors in many of those networks, which lead us to study the topology of random sensor networks by using the Poisson point processes.

Simplicial Homology

Simplicial complexes are structures composed by elements named simplices, which can be seen by *d*-dimensional filled spaces. Exemples of simplexes are given below:



 β_d denotes the number of *d*-dimensional holes. Particularly, β_0 , β_1 and β_2 measure, respectively, the connectiveness, the number of holes and the number of voids of a complex.

Interpreting a Sensor Network

We can represent the topology of a sensor network by its Rips complex, which is obtained when we consider that whenever k + 1 points are 2 by 2 closer than ϵ between them, they create a *k*-simplex.



Problem Formulation

The principal idea of the problem is that sensors $\{S_1, S_2, ..., S_n\}$ have a power suply allowing them to transmit theirs ID's and maybe some environmental information (such as temperature, pression, presence/absence of an element etc). At the same time, the sensors have receivers which can identify the transmitted ID's of other sensors above a threshold power. The sensors, knowing theirs ID's and the ID's of the close neighbors, create an information network.

Physical Features of the System

• The sensors lie over a *d*-torus \mathbb{T}_a^d and the dimensions of the sensor are considered too reduced compared to the system, so the position of the sensor S_i is given by $x_i \in \mathbb{T}_a^d = (u_{i,1}, ..., u_{d,i}), u_{d,k} \in [0, a];$



Results: Mean of k-simplexes, $\overline{s_k}$, and Euler's Characteristic, $\overline{\chi}$

It is possible to calculate the mean of k-simplices given the size of individual coverage ϵ , the density of sensors λ , the dimension *d* and the sizes of the d-torus, *a*:

 $\overline{s_{k-1}} = \frac{\lambda^k a^d}{k!} k^d \left(\epsilon^{k-1}\right)^d, \quad \epsilon < a/3$

Below, we present the variation of $\overline{s_k}$ in function of ϵ for a = 100 and $\lambda = 0.10$ in two dimensions.

/		L	_		_		
Compari	son bet	ween the	calcul	ations a	and the si	mulation	ns
	$\frac{1}{S_1}$	imulated	I	I	I		

Comparison between the calculations and the simulations

Comparison between the calculations and the simulations 0.25 r

- A sensor receives the ID's from all other sensors closer then a deterministic distance ϵ , so if $||x_i - x_j|| \leq \epsilon$, sensors S_i and S_j are directly connected;
- We use the maximum norm, i.e.,

 $||x_i - x_j|| = \max_k (u_{i,k} - u_{j,k})$

Random Features of the System

• The number of sensors lying over on $\mathbb{T}_{a'}^d$, $\Phi(t)$, is distributed as poisson with mean λa^d , where λ is a constant in the model. Indeed, λ represent the density of sensors;



Let B_d be the Bell's polynomial. Using the mean of k-simplexes, we can calculate the mean of the Euler's Characteristic χ :



The variation of $\overline{\chi}$ in function of λ is presented following, for d = 1, d = 2 and d = 3:



• The distribution of the position of each sensor is independent of the other sensors and given by



References

- [1] R. Ghrist, A. Muhammad. Coverage and Hole-Detection in Sensor Networks Via Homology In Fourth International Conference on Information Processing in Sensor Networks (IPSN'05), UCLA, 2005.
- [2] C. Houdré, N. Privault. Concentration and deviation inaqualities in infinite dimensions via covariance representations Bernoulli, 2002.

Conjecture: β_i dominance region

Based on simulations and analytical expressions, we can conjecture that, given a density of points, there are at most two dominating types of holes.



Results: Concentration Inequality

Since a compensated Poisson point process can be seen as a martingale, we can use a concentration inequality to find a superior limit for $P(\beta_0 \ge c)$ in two dimensions

