



HAL
open science

A systemic criterion of sustainability in agile manufacturing

Roque Calvo, Rosario Domingo, M A Sebastian

► **To cite this version:**

Roque Calvo, Rosario Domingo, M A Sebastian. A systemic criterion of sustainability in agile manufacturing. *International Journal of Production Research*, 2008, 46 (12), pp.3345-3358. 10.1080/00207540601096957 . hal-00512961

HAL Id: hal-00512961

<https://hal.science/hal-00512961>

Submitted on 1 Sep 2010

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



A systemic criterion of sustainability in agile manufacturing

Journal:	<i>International Journal of Production Research</i>
Manuscript ID:	TPRS-2006-IJPR-0291.R2
Manuscript Type:	Original Manuscript
Date Submitted by the Author:	25-Oct-2006
Complete List of Authors:	Calvo, Roque; National Distance University of Spain, Manufacturing Engineering Domingo, Rosario; National Distance University of Spain, Manufacturing Engineering Sebastian, M A; National Distance University of Spain, Manufacturing Engineering
Keywords:	FLEXIBILITY, AGILE MANUFACTURING, DECISION SUPPORT SYSTEMS
Keywords (user):	Complexity, Sustainability



A systemic criterion of sustainability in agile manufacturing

R. CALVO^{*}, R. DOMINGO[†] and M.A. SEBASTIÁN[‡]

Department of Manufacturing Engineering, National Distance University of Spain
(UNED), C/ Juan del Rosal 12, E-28040 Madrid, Spain

Abstract. Agile manufacturing systems work in a constant change in a global market, in particular, assembly systems at the last stage of product differentiation. Meanwhile, sustainability is becoming a key issue for manufacturing strategy. This paper formulates a systemic criterion of sustainability in agile manufacturing and computes it through flexibility and complexity. It is defined a ratio of utility and entropy as a sustainability measurement. Under a unified framework, utility allows to quantify the contributions to agility, in particular system flexibility. Complexity is measured by entropy. Thus, it is proposed an original complementary role of flexibility and the complexity of the system. Developed from the distribution of system states, the systemic approach to sustainability in terms of output evolution is enriched. Based on a simple assembly line integer model simulation, a first quantitative analysis illustrates the concepts introduced.

Keywords: agility manufacturing, decision support systems, complexity, flexibility, sustainability

^{*} Tel.: +34 91 398 64 55; Fax: +34 91 398 82 28; E-mail: rcalvo@recol.es

[†] Corresponding author. Tel.: +34 91 398 64 55; Fax: +34 91 398 82 28; E-mail: rdomingo@ind.uned.es

[‡] Tel.: +34 91 398 64 45; Fax: +34 91 398 82 28; E-mail: msebastian@ind.uned.es

1. Nomenclature

C_r reduced cost, in the hybrid lines assembly model.

F flexibility.

H system entropy, metric of system complexity.

H_s structural complexity by Frizelle and Efstathiou (2002).

O_t output vector evaluated at t , in Gallopin (1996) sustainability definition.

p_{ij} probability of resource (machine or line) i being in state j .

Q_r reduced quality, in the hybrid lines assembly model.

$S, S(x)$ sustainability, sustainability as a function of a state variable.

v utility value (Calvo *et al.* 2003), utility prospect of a utility vector (Abbas 2006)

$v(x)$ density function of the probability distribution $V(x)$.

$V, V(x)$ expected utility or valuation (sustainability definition), cumulative distribution function of utility to respect the x state parameter.

ΔV utility-increment vector.

Δv_i discrete utility increment, i element of the discrete utility-increment vector ΔV .

ΔV_j discrete utility value. Correspond to the component j of the utility-increment vector.

T_r reduced delivery or makespan of the daily production.

t time.

x, x_t scalar state parameter, state parameter at the time t .

x_1, x_2, \dots, x_n scalar state parameters, variables that define productive factors.

2. Introduction

Nowadays manufacturing systems have to respond to continuous changes and sustainability requirements. Agile manufacturing has been identified as a broad concept to face it. Based on flexibility and the response to customer, agility also includes cost reduction, high quality of products and the delivery conditions and service (Goldman and Nagel 1991). Moreover agile manufacturing is a response to complexity brought about by constant change (Sanchez and Nagi 2001). Therefore, we find two relevant features of agility: flexibility and complexity. Flexibility has been identified as a key productive factor for success or competitive advantage (Suarez *et al.* 1995). It is required to handle a high variety of products. However, the variety of products increases the complexity (Wiendahl and Scholtissek 1994). Thus, complexity in a manufacturing system plays a counter-weighting role in the use of flexibility. Conversely, we live a trend towards an increasing product variety in a product life-cycle framework, including the evolution of manufacturing reorganisation towards simplicity, sustainability and the dynamic flexibility of subsystems (Wiendahl and Scholtissek 1994). Beyond the analysis of product end-of-life, a reference point is to consider sustainability from system capacity of maintaining performance under acceptable standards.

According to Alford *et al.* (2000), an effective approach must be developed to support decisions in order to promote customisation, but preventing complexity in manufacturing. We extend this approach to reach system sustainability. Some metrics have been given to flexibility assessment (Filippini *et al.* 1998, Ward *et al.* 1998, Calvo *et al.* 2003, Domingo *et al.* 2005), complexity (Deshmukh *et al.* 1992, Frizelle and Efstathiou 2002, Calvo *et al.* 2006) and sustainability (Gallopín 1996, Wall and Gong 2001).

1
2
3
4
5 However, literature lacks in providing an integrated metric. The original contribution of the
6
7 paper includes formulating a criterion of sustainability in agile systems and quantifying its
8
9 measure though flexibility and complexity.
10

11 We adopt the utility theory (Keeney and Ruiffa 1976) to quantify of flexibility.
12
13 Authors have taken this approach (Calvo *et al.* 2003), using it in other manufacturing
14
15 systems (Domingo *et al.* 2005, Calvo *et al.* 2006). Utility for the decision-maker allows
16
17 quantifying the contributions of productive factors to agility. This theory permits to
18
19 consider that the factors (e.g. cost, quality or delivery) are mutually preferentially
20
21 independent. This is of a particular interest and easy application in industrial manufacturing
22
23 systems. The complexity is measured by means of entropy by Frizelle and Efstathiou
24
25 (2002). We proposed an original complementary role of flexibility and the complexity of
26
27 the system. In this sense, **entropy represents** an estimation of uncertainty level. In addition,
28
29 this paper takes in account the classic systemic sustainability by Gallopín (1996), but
30
31 developing a new systemic approach to sustainability in terms of output evolution from the
32
33 distribution of system states. Sustainability involves the ability to generate variety in a
34
35 dissipative process that admits a decrease of entropy. It is proposed the ratio of utility and
36
37 entropy as a sustainability measurement, interesting for the dynamic evolutions of agile
38
39 systems.
40
41
42
43
44
45
46
47
48
49

50 **3. Quantification of flexibility in manufacturing systems**

51
52 Flexibility is the main differential productive factor of agility, compare to former
53
54 manufacturing systems. Moreover, it is countermeasure against uncertainty. Nevertheless,
55
56 most of the success assigned to flexibility could have been actually got through flexible
57
58
59
60

1
2
3
4 technology, instead of a flexible management of the system. Consequently, the provision of
5
6 flexible manufacturing systems (FMS) could not currently be enough to face scaling
7
8 uncertainties. Manufacturing flexibility should be considered as a strategic and operative
9
10 factor of production for decision-making (Hill and Chambers 1991). Therefore, it must be
11
12 tightly integrated in the assessment of system performance along cost, quality and delivery.
13
14 In their literature review about manufacturing flexibility, Beach *et al.* (2000) indicate that
15
16 flexibility definitions include two common features: Response to change and uncertainty.
17
18 The change of flexibility can be expressed as a short-term or a long-term operative
19
20 decision. In this process, uncertainty can be managed to avoid negative impacts, or to
21
22 improve system performance through strategic planning.
23
24
25
26
27

28 Flexibility quantification has not consolidated a group of measures widely accepted.
29
30 The attempts to formulate a consistent generic schema of flexibility types and measures
31
32 have had a limited success. Flexibility quantification cannot be independent from the
33
34 performance measures, in particular in agile, complex and dynamic systems (Grubbström
35
36 and Olhager 1997, Filippini *et al.* 1998, Ward *et al.* 1998). Decision-making can determine
37
38 a radically opposite system behaviour, proper of complex systems evolution under different
39
40 initial conditions. So, the compatibility between the strategic and the operational use of
41
42 flexibility should be determined directly by the time scale and the outstanding parameters
43
44 of the system. Therefore, a flexibility generic measure should allow including every
45
46 relevant feature of the system for decision-making, in order to be a concept applicable to
47
48 different manufacturing systems.
49
50
51
52
53

54 Decision-maker preferences can be introduced by the utility theory. A structure of
55
56 priorities among different contributions to the utility is quantified by this function, and the
57
58
59
60

1
2
3
4 objective of maximum utility is pursued to get the better combination of factors: Cost,
5
6 quality and delivery. They can be considered mutually preferentially independent, so the
7
8 level of each one does not depend on the level of the rest in the structure of decision-maker
9
10 preference (Keeney and Ruiffa 1976). This assumption can be maintained since they
11
12 represent complementary concepts. Although, the operative management of cost, quality or
13
14 delivery is based on tradeoffs between them, because productive factors interact through
15
16 the group of significant magnitudes that define the system state. The mutual preferential
17
18 independence among factors facilitates the formulation of the utility function. Each mutual
19
20 independent contributor can be aggregated as an additive function into the complete utility
21
22 expression. The coefficients of each additive function can be interpreted as the scale factor
23
24 or weights in the contribution of each factor. Every factor has its own unit of measurement,
25
26 so in order to aggregate those different effects into the same function; it is proposed the
27
28 addition of each contribution dimensionless. That is, dividing cost, quality and delivery
29
30 contributions into significant reference values of the system. For sustainability purposes,
31
32 environmental issues in decision-making can also be included in the utility function through
33
34 its parameters of influence. In the operational field could include energy consumption, cost
35
36 of recycling or disposal, costs of emission rights, etc. In a strategic perspective, the
37
38 intangible values of a responsible and clean integration of activities can be evaluated
39
40 through new metrics (Funk 2003).
41
42
43
44
45
46
47
48

49 In this approach, manufacturing flexibility, F , can be defined as the temporal ratio of
50
51 incremental utility between two states (Calvo *et al.* 2003). Equation (1) quantifies this
52
53 definition.
54
55
56
57
58
59
60

$$F = \frac{\Delta v}{\Delta t} = \frac{\Delta v(x_1, x_2, \dots, x_n)}{\Delta \text{time}} \Bigg|_{\text{state1}}^{\text{state2}} = \frac{v_2 - v_1}{t_2 - t_1} \quad (1)$$

The utility function, v , depends on productive factors and represents the structure of choice and trade-offs for the decision-maker (Keeney and Ruiffa 1976), by equation (2).

$$\text{utility} = v(\text{cost}, \text{quality}, \text{delivery}) = v(x_1, x_2, \dots, x_n) \quad (2)$$

Noted x_1, x_2, \dots, x_n as the scalar state parameters, they are the set of metrics that define a system status. Reminiscent from the theory of control, they are among the variables of the function of transference for system control. They can frequently take only integer values, e.g. product-to-line assignation. Discrete variations on manufacturing systems could be considered in an approximation under a continuous analysis by taking average values in convenient time intervals. So the utility function could be rewritten as a function of the state parameters of the manufacturing system

$$F = \frac{d v}{d t} = \frac{d v [x_1(t), x_2(t), \dots, x_n(t)]}{d t} = \frac{\partial v}{\partial x_1} \cdot \frac{d x_1}{d t} + \frac{\partial v}{\partial x_2} \cdot \frac{d x_2}{d t} \dots + \frac{\partial v}{\partial x_n} \cdot \frac{d x_n}{d t} \quad (3)$$

This definition quantifies production flexibility as the result of a change in the system and it can cover most of the metrics applicable to an agile manufacturing system. A positive variation of utility yields positive flexibility. Null flexibility corresponds with an interchange of productive factors, keeping overall utility. A negative evolution of utility yields negative flexibility. Flexibility is compatible with negative and positive evolutions, allowing the conciliation of two controversial aspects in manufacturing systems: World-Class Manufacturing efforts of agile manufacturing and the productive factors interchange. While the first one requires a positive change of flexibility, the second one is represented

1
2
3
4 by evolutions of null flexibility. Moreover, this definition of flexibility permits the
5
6 mathematical and conceptual decomposition into the potential flexibility and the rate of
7
8 flexibility. The temporal ratio of each state parameter represents the rate and the utility
9
10 increment to respect the state parameter evaluates a potential flexibility. Based on potential
11
12 and rate flexibility, we can understand the existence of manufacturing systems including
13
14 flexible technology, but showing low flexible performance. They have potential flexibility
15
16 but a very low rate, resulting in rather low flexibility. This definition of flexibility allows
17
18 comparing two different manufacturing systems based on the same utility function defined
19
20 by the decision-maker, but containing different state parameters, which belongs to each
21
22 specific system. In addition, this flexibility definition covers also its dual nature. From an
23
24 operational perspective, flexibility results from little variations of utility between two
25
26 states, but at a significant rate (short-term). Besides, the strategic use of flexibility results
27
28 from significant variation of utility with respect to state parameters at a low rate (long-
29
30 term). Partial derivatives of utility with respect to state parameters in (3) represent the
31
32 additive contribution to variation of each factor *ceteris paribus*. They can be identified
33
34 among the classical operational types of flexibility (Calvo *et al.* 2003).
35
36
37
38
39
40
41

42 Focused on agility, product flexibility represents the capability of introducing new
43
44 products for manufacturing without affecting overall performance, directly related to the
45
46 temporal dimension of changes that agility imposes. Modular product designs and final
47
48 customised assembly will help to support it.
49
50
51
52
53
54
55
56
57
58
59
60

4. Complexity quantification in manufacturing systems

Some indicators of manufacturing system complexity growth can be found in the increasing number of variants of products from a basic model, the shorting time of design and production lead-time of new products, the increasing effort in information transactions, the management of materials processing or the rising rate of fixed costs (Wiendahl and Scholtissek 1994). Although, literature does not show a unique approach about its definition and measure. We have adopted a systems quantitative approach. In this sense, a complexity definition is the variety of states in the system (Beer 1970). More dynamic, McCarthy (1995) defines complexity as a system attribute that increases when the number and variety of elements and their relationships increase, at the time the level of predictability and understanding of the system as a whole decreases. Noteworthy, while complexity can create uncertainty, flexibility is a reaction against it. General features of complexity include uncertainty associated with a high number of states, irreversibility and non-linear response. These initial clues of manufacturing complexity make interesting its reduction. In order to face it, a first step is to establish the complexity concept boundaries and its measurement methods. Based on the concept of informational entropy (Shannon 1948), a set of measures has been developed and received broad attention. According to Calinescu *et al.* (2001), the approach of static complexity by Deshmukh *et al.* (1992), can be used for decision-making complexity. It is an entropy-based measurement of system states: Possible combination of operations and machines for every part. This metric can also represent the complexity of the decision tree of the production planning. Therefore, we consider that decision-making from an industrial implementation must enclose a global priority on the whole system. This requires a model including only the main influences and

1
2
3
4 the objectives assessment, as well as uncertainty or risk estimation. A drawback of model
5
6 simplification is a cut-off of sensitiveness of a complex emergent behaviour. Nevertheless,
7
8 manufacturing complexity has been identified as scale dependent, so the simulation model
9
10 can catch system complexity at the scale it represents the system behaviour.
11

12
13
14 Similarly, for structural complexity, H_s , it can be used the static complexity (Frizelle
15
16 and Efstathiou 2002), representing the assignation part-to-machine or part-to-line in
17
18 assembly schedules. Let p_{ij} be the probability of the i resource, out of L lines, being in state
19
20 j , of K_i possible configurations, so the structural complexity is
21
22

$$H_s = - \sum_{i=1}^L \sum_{j=1}^{K_i} p_{ij} \cdot \log p_{ij} \quad (4)$$

23
24
25
26

27
28 Noteworthy, the assessment of states probabilities in the system does not anticipate its
29
30 predictability or the transition from one state to another. For equal probability of their
31
32 states, flexible systems will yield greater complexity than dedicated systems, because the
33
34 number of possible states will be higher. Thus, higher levels of complexity could represent
35
36 higher flexibility in a system under control.
37

38
39 This entropy-based measure considers two dimensions of complexity: The number of
40
41 states and its probability. Nevertheless, the interdependence between variables is not taken
42
43 into account directly. This should be established through the system performance.
44

45
46 Considering a manufacturing model under the technical and operational sufficient validity
47
48 by Schellenberger (1974), H_s calculated from the simulation output might incorporate the
49
50 interdependence among variables that such a manufacturing model establishes. Thus, the
51
52 structural complexity of output states could approach system complexity, as the system
53
54 simulation approaches system behaviour under decision-maker control.
55
56
57
58
59
60

1
2
3
4 Probabilities are *a priori* arrangements of events based on their expectation of
5 occurrence. From this point of view, states are events recognized from system monitoring.
6
7 That is, the system works mainly in a controlled path. When the process deviates in a
8
9 random way, decision-maker will try to control the deviations, actuating through the state
10 parameters of the system in order to correct the evolution. Therefore, states probabilities
11
12 can be considered conditioned by the decision-maker and his/her structure of utility.
13
14
15
16
17
18
19
20

21 **5. Decision-making on agile and complex systems**

22
23 Some conceptual and formal connections between flexibility and complexity will help
24 to integrate both for decision-making. A systemic meeting point of flexibility and
25 complexity is the states set that the system can reach. It was remarked before that system
26 complexity is associated with a large number of possible states. If all of them are equally
27 probable, entropy presents a maximum for that number of states. In the other hand, an agile
28 manufacturing system requires choosing options among all possible different states.
29
30 Flexibility is perceived high when the set of states allows decision-making towards the
31 performance goal.
32
33
34
35
36
37
38
39
40
41

42 A conceptual neighbourhood of flexibility and complexity is alike. The basic utility
43 idealisation theory and the fundamental laws of thermodynamics can be interpreted
44 isomorphs, on a macroscopic view of the system (Smith and Foley 2002). In particular in a
45 closed system, entropy will never decrease almost-surely, while in the utility field a
46 decision-maker will never voluntary accept a reduction of utility. The informational
47 connection of flexibility and complexity seems to be uncertainty. Flexibility has always
48
49 been considered an operative and strategic countermeasure against uncertainty. Complexity
50
51
52
53
54
55
56
57
58
59
60

1
2
3
4 grows along uncertainty in its entropy-based approach, since states of equal probability
5
6 give little information to make a decision. In addition, flexibility and complexity are
7
8 additive by the definitions adopted. Flexibility is additive, as temporal incremental ratio of
9
10 utility, for mutual preferential independent contributions to the utility function, as exposed
11
12 above. Similarly, entropy-based view of complexity is additive as entropy is additive by its
13
14 logarithmic formulation. Therefore, a convenient complementary role of flexibility and
15
16 complexity is proposed: Decision-making on agile manufacturing through the utility and
17
18 complexity evaluation of the system states. State outputs and their utility based on
19
20 simulation could be considered a tool of the decision-maker. Utility evolution (flexibility)
21
22 comes from the aggregation of cost, quality or delivery factors, so it is close to the real
23
24 system. In addition, complexity can be felt across the system. Frizelle and Efstathiou (2002)
25
26 point out that the queues and bottlenecks are clear signs in relationship with complexity
27
28 inside a manufacturing system.
29
30
31
32
33
34

35 The set of all possible state utilities can be interpreted under a statistical analogy as a
36
37 probability distribution. Castagnoli and LiCalzi (1996) interpret the expected utility as a
38
39 procedure to rank lotteries based on their probability to outperform an independent
40
41 stochastic benchmark. Lotteries are random variables that take their values in the domain of
42
43 utility distribution and they are exogenously given to the decision-maker, added to the
44
45 utility structure. Among other interpretations, the stochastic benchmark is the expected
46
47 probability that outperform a deterministic threshold or target. This threshold is imperfectly
48
49 known (probabilistic distribution), and the state utility distribution represents the
50
51 uncertainty about the right (deterministic) target to apply. These approach by Castagnoli
52
53 and LiCalzi (1996), allows us to include utility and its external target in the decision-
54
55
56
57
58
59
60

1
2
3
4 making process, instead of utility and some lotteries. In manufacturing system seems to be
5
6 more intuitive the goal under uncertainty than the decision-making process based on
7
8 lotteries. Under these premises, the set of possible states and their utility values can be
9
10 interpreted as a probability distribution, which represents the uncertainty of reaching a
11
12 deterministic target of utility, independent of the lotteries the decision-maker is facing to
13
14 take a decision (expected utility based on those lotteries). At this point, flexibility gains
15
16 significance as the temporal ratio of incremental utility between two states. The utility
17
18 distribution of the possible states is an assessment of the uncertainty to reach or surpass a
19
20 target of utility. Passing from one state to another of greater utility is an act (*versus* a
21
22 lottery) of reducing the uncertainty of reaching a target of utility. Thus, a flexible change is
23
24 an uncertainty countermeasure in the decision-making process.
25
26
27
28
29

30 This distribution of probability or uncertainty could represent the probability of
31
32 occurrence of the states, so the complexity of the system can be estimated through its
33
34 entropy-based (informational) measurement, H . For a continuous utility distribution (Abbas
35
36 2006)
37
38
39

$$40 \quad V(x) = \int_{x_{min}}^x v(y) dy; \text{ and } \int_{x_{min}}^{x_{max}} v(y) dy = 1, \text{ by definition } v(x) = \frac{dV(x)}{dx} \quad (5)$$

$$41 \quad H(x) = - \int_{x_{min}}^x v(y) \ln(v(y)) dy \text{ and } H = - \int_{x_{min}}^{x_{max}} v(y) \ln(v(y)) dy \quad (6)$$

42
43
44
45
46
47
48
49 Where, in general, the scalar utility function by (2) is a non-decreasing function of the
50
51 state variables. And $V(x)$, $H(x)$ note the increments of utility and entropy taking decision on
52
53 the evolution of one of them, the variable $x \in \{x_1, x_2, \dots, x_n\}$, that take values in the interval
54
55
56
57
58
59
60

x_{min} and x_{max} , ranking states from less to most preferred. In addition, for a discrete set of events the same formulation can be rewrite (Abbas 2006):

$$\Delta V_j = \sum_{i=1}^j \Delta v_i \quad \text{and} \quad \sum_l^L \sum_k^K v_{kl} = 1 \quad (7)$$

$$H_j = - \sum_{i=1}^j \Delta v_i \ln(\Delta v_i) \quad (8)$$

Let ΔV_j be the discrete utility value that correspond with the component j of the utility-increment vector. Its components, Δv_i are equal to the difference between the consecutive elements in the utility vector, which ranks in order the $L \times K$ utility prospect values (states) from null to one, for L assembly lines with K configuration of each line.

With no loss of generality, except a constant of proportionality, we formulate (8) in natural logarithms, convenient for easier integration in the case of the continuous approach. From (3), (5) and (6) or (8), we can express complexity variation as a function of utility

$$\frac{dH(x)}{dV(x)} = -\ln[v(x)] \quad \text{or} \quad \frac{\Delta H_j}{\Delta V_j} = \frac{\sum_{i=1}^{j-1} \Delta v_i \ln(\Delta v_i) - \sum_{i=1}^j \Delta v_i \ln(\Delta v_i)}{\sum_{i=1}^j \Delta v_i} \quad (9)$$

Where $V(x)$ is the cumulative distribution function of utility of x state parameter and $v(x)$ the density function of the probability distribution $V(x)$. From (9) and (5), we could interpret the sign of variation of complexity and expected utility should be the same, so an increase of complexity supports greater flexibility under uncertainty. In other terms, in order to contain uncertainty, increments of complexity and increments of utility compensate each other. From (9), the temporal incremental ratio of complexity to flexibility could be an estimation of the uncertainty level, considering the $v(x)$ relationship with the probability of

1
2
3
4 events, by (7). Obviously, situations of low complexity and high utility are preferred.
5
6 Reducing initially uncertainty through contractual mechanisms could allow it. Current
7
8 competitive industrial environments seem to make it difficult.
9
10

14 6. Systemic sustainability of manufacturing

16 Agile systems are open, flexible and complex. The thermodynamic principle of non-
17
18 decreasing entropy for a close system is not directly applicable to the evolution of a
19
20 manufacturing system. From raw materials to energy, from information to engineered
21
22 products, manufacturing systems are open systems. This is an important reason to consider
23
24 their sustainability. A general definition of sustainability in elementary terms can be
25
26 formulated (Gallopín 1996), from V as a valuation function of the system outputs and O_t as
27
28 **output vector at time t** , as follows:
29
30
31

$$32 V(O_{t+1}) \geq V(O_t) \quad (10)$$

33
34 That is, for Gallopín (1996) a sustainable system is a system of non-decreasing
35
36 ‘worth’ in time. In this sense, we have intentionally noted it like the former utility function.
37
38 It represents the same concept of expected utility of the system, in a broad sense for the
39
40 society. A first identification of the utility function with the worth to the society of the
41
42 system can yield this first sustainability criterion. Nevertheless, this approach lacks the
43
44 organisational objectives of survival or goal-setting evolution for the system.
45
46
47
48

49 From a systemic perspective, the principle of requisite of variety establishes that the
50
51 variety in the control of the system must be equal to or larger than the variety of the
52
53 perturbations in order to maintain stability (Ashby 1958). Thus, variety generation
54
55
56
57
58
59
60

1
2
3
4 (entropy) is necessary to survive. Considering the increasing uncertainty of manufacturing
5
6 systems in a global market, we could conclude that a manufacturing system under control
7
8 can only evolve increasing its complexity. Note that the process of controlling a system
9
10 becomes harder as its possible states increase. In fact, controlling is a process of variety
11
12 destruction to maintain the system in the assigned work-point. Although, a complementary
13
14 perspective can be adopted, interpreting agile systems as adaptive self-organized entities.
15
16
17 The survival of a manufacturing system through agility can be view as the dynamic stability
18
19 of a dissipative entity of asymmetric transitions (Heylighen 1992), where state of energy
20
21 emission are more probable of those where energy is absorbed. Former author affirms that
22
23 this hypothesis is equivalent to the law of maximum entropy production, so the system can
24
25 reduce its internal complexity. In this view, systems configurations tend to become more
26
27 stable emitting energy in the process, conversely to the most common interpretation of the
28
29 second law for close systems, namely that disorder and homogeneity tend to increase. This
30
31 is an interpretation of manufacturing systems as open, dissipative and complex structures.
32
33 Its evolution can be recognised in some features of current manufacturing systems.
34
35
36 Manufacturers seek differentiation from competitors, product variety and sales increases,
37
38 instead of product homogeneity and activity reduction. This fact is compatible in an open
39
40 system to the decrease of its entropy through a continuous interchange of energy and goods,
41
42 obtaining stability (future or survival) as a dissipative entity. In this approach of agile
43
44 manufacturing as a dissipative system, sustainability is viewed as the long-term survival of
45
46 the system in its environment and it concerns the ability to generate variety interacting with
47
48 its environment in a dissipative process that allows a decrease of entropy (complexity)
49
50 inside the system.
51
52
53
54
55
56
57
58
59
60

1
2
3
4 Good manufacturing systems are imagined offering goods at a high quality, low cost
5
6 and produced quickly under schemas of continuous variety change for customer
7
8 satisfaction. Meanwhile, we aim an internal configuration based on simple processes and a
9
10 big effort of commonality of parts that do not yield many possible alternatives, because
11
12 many state options usually come from overdimensioned systems. Therefore, a sustainable
13
14 manufacturing system interchanges its goods, energy and disposals with the market and its
15
16 environment at low internal entropy. Thus, we propose to define sustainability for a
17
18 manufacturing system as
19
20
21
22

$$23 \text{ Sustainability}(t) = S(O_t) = \frac{\Delta V(O_t)}{\Delta H(O_t)} \quad (11)$$

24
25
26
27

28 A utility increase and/or internal complexity reduction enhance sustainability of the
29
30 system itself. In addition to the constructivist modelling of flexibility and complexity from
31
32 utility, a thermodynamic analogy as a dissipative system arises. The worthiness (utility of
33
34 manufacturing output for the society) can be seen as the energy the system interchanges.
35
36 The complexity or entropy of the system assumes the same role than the thermal entropy as
37
38 a macroscopic measure of microstates. The ratio of energy transfer at a level of entropy
39
40 (utility change at an internal complexity) is the macroscopic temperature at equilibrium, the
41
42 sustainability in this analogy. Note that under a thermodynamic criterion, a system is more
43
44 capable of developing a cyclic work when its temperature is higher. This approach connects
45
46 to the exergy approach to sustainability (Wall and Gong 2001). Likewise, sustainability of a
47
48 manufacturing system increases when the ratio of incremental utility *versus* incremental
49
50 complexity increases.
51
52
53
54
55
56
57
58
59
60

When we compare this criterion (11) with the former decision-making ratio between utility and complexity (9), a new connection of concepts appears. The criterion of sustainability represents the reverse of the uncertainty of utility to respect the state parameter x at a point time, that is its certainty. Thus, sustainable systems are those that evolve in evolutions towards greater certainty, so towards higher order under-control or predictable system. In addition, in a continuous approach the temporal probability distribution of utility to respect the state parameter x is directly related to sustainability.

$$S(x_t) = -\frac{1}{\ln[v(x_t)]} \quad \text{or} \quad S_j = \frac{\sum_{i=1}^j \Delta v_i}{\sum_{i=1}^{j-1} \Delta v_i \ln(\Delta v_i) - \sum_{i=1}^j \Delta v_i \ln(\Delta v_i)} \quad (12)$$

Note in (12) that sustainability is evaluated at time t . For a continuous analysis through a state parameter, x_t . For a discrete approach, states are arranged in increasing utility through the index j , and the associated utility vectors are evaluated at time t . From (5) and (12), sustainability is positive, increasing as the probability of the utility (function of density) v increases.

7. A case simulation analysis

Final assembly represents the last step of postponement of final variety. A simple model of product-to-line assignation in a hybrid (semiautomatic) assembly system is used. Authors have applied this model to analyse flexibility and complexity (Domingo *et al.* 2005, Calvo *et al.* 2006). In this model, the state parameters include products definition by manufacturing standard time per part and its daily demand. Assembly lines are defined by its layout,

1
2
3
4 machines, operators and processes established for the products they can process. Layout,
5
6 machines or processes are established during line design. Therefore, the capability of a line to
7
8 produce a product is initially determined by design. The incidence matrix between products
9
10 and lines is an input that establishes that possibility. Significant line operative parameters
11
12 include the number of operators and cycle time. Production is managed just-in-time and zero
13
14 stock, so every day planning is to produce the day after deliveries. Different utility functions
15
16 and goals can be used to maximize utility: Minimizing reduced cost (C_r), noise-to-signal
17
18 ratio of parts work content in the lines (reduced quality, Q_r), makespan of the daily
19
20 production (reduced delivery, T_r) or a weighted addition of them, that represents the relative
21
22 importance of the different productive factors to the decision-maker. In addition to the pure
23
24 individual factors, for illustration we use also $(0.2C_r+0.3Q_r+0.5T_r)$. In order to evaluate
25
26 the variety effect, from an initial portfolio of 30 products we reduce the variety (suppressing
27
28 products from the bottom of product listing) maintaining the workload in total hours
29
30 (proportional for each product to the relative volume in the original table of 30 products). Note
31
32 that the reduced cost represents the hour cost per hour of standard load, so it can be seen as a
33
34 unitary cost or efficiency. In the same sense, reduced delivery T_r measures makespan of the
35
36 daily production rated by the average load of the assembly lines. In both cases, the relative
37
38 measure maintains its reference, since the total workload is constant for different number of
39
40 products (Figure 1).
41
42
43
44
45
46
47
48

49
50 **(Figure 1 about here)**

51
52 The maximum, v_{max} , and mean, v_{mean} , utility reached in the set of system states, as
53
54 well as complexity H , both are represented for a weighted criterion of utility function,
55
56 $0.2C_r+0.3Q_r+0.5T_r$. At a first glance, we appreciate that v_{max} and v_{mean} approximate
57
58
59
60

1
2
3
4 each other as the number of product increases. That means a dispersion reduction in the
5
6 distribution of solutions, so towards system stability, that constitutes an internal variety
7
8 decrease indicator. Even when the number of solution increases, complexity H can decrease
9
10 when the number of products increases. Therefore, a higher number of states is possible, but
11
12 under less uncertainty. Noteworthy, this criterion represents the consumption of resources that
13
14 exhausts internal performance of the agile assembly lines, in a decreasing or constant
15
16 evolution of flexibility. In the other hand, we can interpret that a greater variety offered to the
17
18 customer for the same workload can yield an increase of product sales or a better part price.
19
20 These benefits, not included in the model, could probably compensate or overpass that effort
21
22 of utility reduction.
23
24
25
26

27
28 Next, we can calculate sustainability from (12), based on the statistical approach of each
29
30 utility distribution. When it is followed an aggressive criterion of maximizing utility (v_{max}),
31
32 the system loses sustainability when increasing variety. The number of states that maximize
33
34 utility are ordinary infrequent. According to Heylighen (1992), under a systemic perspective,
35
36 the principle of selective retention establishes that stable configurations are retained, while
37
38 unstable ones are eliminated. Consequently, system evolution through states of higher
39
40 likelihood, v_{mean} , plays in favour of sustainability. Like the principle of selective retention,
41
42 this statement seems to be tautological, but it is not so evident for manufacturing system where
43
44 the maximum performance at any time seems to be the path for survival. In particular, when
45
46 adopting a simple definition like (10) that anticipates a maximization of utility for
47
48 sustainability increase.
49
50
51
52

53
54 **(Figure 2 about here)**
55
56
57
58
59
60

1
2
3
4
5 The more probable and numerous working points at mean utility v_{mean} , Figure 2,
6
7 presents greater sustainability and a positive evolution than v_{max} , for an increasing variety.
8
9 This alerts about the path of a manufacturing system for sustainability. System performance
10
11 (utility) can improve but the complexity of the system should be contained, in order to
12
13 increase sustainability. Very complex manufacturing systems can collapse when are not
14
15 properly controlled. This trade-off between complexity and performance suggest that
16
17 sustainability from an equilibrium state could be closer related to system stability. The
18
19 likelihood of temporal equilibrium of an open system in its environment seems to be more
20
21 influent for sustainability than with the optimisation of the performance.
22
23
24
25
26
27

28 **8. Concluding remarks**

29
30 We have presented a new and general integrated framework for flexibility and
31
32 complexity join measurement based on utility and its distribution. Both are related each
33
34 other through the uncertainty of changes and the decision-making processes on the system.
35
36 Useful for decision support systems, flexibility and complexity could become some
37
38 remarkable factors for decision-making, in particular for very dynamical systems of agile
39
40 manufacturing. We have revised sustainability of agile manufacturing systems considering
41
42 them as dissipative open systems. The sustainability criterion proposed is based on previous
43
44 decision-maker key drivers of flexibility and complexity (utility and entropy). Nowadays,
45
46 the emergent behaviour of complex systems is object of intense research. This systemic
47
48 approach to sustainability could be useful for systems research and it can easily incorporate
49
50 engineering, business or environmental factors through the utility function. Including not
51
52 only the classical approach to performance, but also the evaluation of the system internal
53
54
55
56
57
58
59
60

1
2
3
4 complexity. This general approach is independent of the system and the additive property
5
6 of flexibility and complexity will allow the partial or detailed quantitative analysis on
7
8 subsystems. Therefore, the study of some concrete complexity and flexibility sources and
9
10 sinks in the manufacturing system can help to improve it effectively. Quantification based
11
12 on the utility distribution of the possible states the system can reach, function of the system
13
14 state parameters, so finally close to practitioners and potential industrial application.
15
16
17
18
19

20 21 **References**

- 22
23 Abbas, A.E. Maximum entropy utility, *Operations Research*, 2006, **54** (2), 277-290.
24
25 Alford, D., Sackett, P. and Nelder, G. Mass customization – an automotive perspective.
26
27 *International Journal of Production Economics*, 2000, **65**, 99-110.
28
29 Ashby, W.R. Requisite variety and implications for control of complex systems.
30
31 *Cybernetica*, 1958, **1**, 83-99.
32
33 Beach, R., Muhlemann, A.P., Price, D.H.R., Paterson, A. and Sharp, J.A. A review of
34
35 manufacturing flexibility. *European Journal of Operational Research*, 2000, **122**, 41-57.
36
37 Beer, S. Managing Modern Complexity. *Futures*, 1970, **2**, 245-257.
38
39 Calinescu, A., Efstathiou, J., Huaccho Huatuco, L. and Sivadasan, S., Classes of
40
41 complexity in manufacturing, in *17th National Conference on Manufacturing Research*
42
43 (NCMR 2001): Advances in Manufacturing Technology XV, University of Cardiff, UK,
44
45 2001, pp. 351-356.
46
47 Calvo, R., Domingo, R. and Sebastián, M.A. An integrated assessment of manufacturing
48
49 flexibility. *International Journal for Manufacturing Science and Production*, 2003, **5**,
50
51 151-161.
52
53
54
55
56
57
58
59
60

- 1
2
3
4 Calvo, R., Domingo, R. and Rubio, E.M. A heuristic approach for decision-making on
5
6 flexible assembly lines for mass customization. *Materials Science Forum*, 2006, **526**, 1-
7
8 6.
9
10
11 Castagnoli, E. and Licalzi, M. Expected utility without utility. *Theory Decision*, 1996, **41**,
12
13 281-301.
14
15
16 Deshmukh, A.V., Talavae, J.J. and Barash, M.M., Characteristics of part mix complexity
17
18 measure for manufacturing systems, in *IEEE International Conference on Systems, Man*
19
20 *and Cybernetics*, New York, 1992, pp. 1348-1349.
21
22
23 Domingo, R., Calvo, R. and Sebastián, M.A. Analysis of a quantitative approach of routing
24
25 flexibility in manufacturing. In *Manufacturing, Modelling, Management and Control*
26
27 *2004*, edited by G. Chryssolouris and D. Mourtzis, pp. 63-68, 2005 (Elsevier).
28
29
30 Filippini, R., Forza, C. and Vinelli A. Trade-off and compatibility between performance:
31
32 Definitions and empirical evidence. *International Journal of Production Research*, 1998,
33
34 **36**, 3379-3406.
35
36
37 Frizelle, G. and Efstathiou, J. Seminar notes on measuring complex systems, London
38
39 School of Economics, 2002.
40
41
42 Funk, K. Sustainability and performance. *MIT Sloan Management Review*, 2003, **44**, 65-70.
43
44
45 Gallopin, G. Environmental and sustainability indicators and the concept of situational
46
47 indicators. A systems approach. *Environmental Modelling & Assessment*, 1996, **1**, 101-
48
49 117.
50
51
52 Goldman, S.L. and Nagel, R.N. (eds.) 21st century manufacturing enterprise strategy: An
53
54 industry-led view. Iacocca Institute, Lehigh University, Bethlehem, PA, 1991.
55
56
57
58
59
60

- 1
2
3
4 Grubbström, R. and Olhager J. Productivity and flexibility: Fundamental relations between
5 two major properties and performance measures of the production system. *International*
6
7 *Journal of Production Economics*, 1997, **52**, 73-82.
8
9
10
11 Heylighen, F. Principles of systems and cybernetics: An evolutionary perspective. In
12
13 *Cybernetics and Systems '92*, edited by R. Trappl, pp. 3-10, 1992 (World Science,
14
15 Singapore).
16
17
18 Hill, T. and Chambers, S. Flexibility – a manufacturing conundrum. *International Journal*
19
20 *of Operations and Production Management*, 1991, **11**, 5-10.
21
22
23 Keeney, R.L. and Ruiffa, H. *Decisions with multiple objectives: Preferences and value*
24
25 *tradeoffs*. John Wiley and Son, Inc., New York 1976.
26
27
28 McCarthy, I.P. Manufacturing classification: lessons from organisational systematic and
29
30 biological taxonomy. *Integrated Manufacturing Systems*, 1995, **6**, 37 – 49.
31
32
33 Sanchez, L.M. and Nagi, R. A review of agile manufacturing systems. *International*
34
35 *Journal of Production Research*, 2001, **39**, 3561-3600.
36
37
38 Schellenberger, R.E. Criteria for assessing model validity for managerial purposes.
39
40 *Decision Sciences*, 1974, **5**, 644-653.
41
42
43 Shannon, C.E. A Mathematical Theory of Communication. *The Bell System Technical*
44
45 *Journal*, 1948, **27**, 379-423.
46
47
48 Smith, E. and Foley, D.K. Is utility theory so different from thermodynamics? Working
49
50 paper, Santa Fe Institute, 2002.
51
52
53 Suarez, F.F., Cusumano, M.A. and Fine C.H. An empirical study of flexibility in
54
55 manufacturing. *Sloan Management Review*, 1995, Fall, 25-32.
56
57
58
59
60

1
2
3
4 Wall, G. and Gong, M. On exergy and sustainable development – Part 1: Conditions and
5
6 concepts. *Exergy, An International Journal*, 2001, 1(3), 128-145.
7
8

9 Ward, P.T., McCreery, J.K., Ritzmin, L.P. and Sharma, D. Competitive Priorities in
10
11 operations Management. *Decision Sciences*, 1998, **29**, 1035-1046.
12
13

14 Wiendahl, H.P. and Scholtissek, P. Management and control of complexity in
15
16 manufacturing. *CIRP Annals-Manufacturing Technology*, 1994, **43**, 533-540.
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60




Figure 1. Utility and complexity evolution vs. variety increase

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60




Figure 2. System sustainability evolution vs. variety increase