



**HAL**  
open science

## Liquid Cooling of Bright LEDs for Automotive Applications

Yan Lai, Nicolás Cordero, Frank Barthel, Frank Tebbe, Jörg Kuhn, Robert Apfelbeck, Dagmar Würtenberger

► **To cite this version:**

Yan Lai, Nicolás Cordero, Frank Barthel, Frank Tebbe, Jörg Kuhn, et al.. Liquid Cooling of Bright LEDs for Automotive Applications. Applied Thermal Engineering, 2009, 29 (5-6), pp.1239. 10.1016/j.applthermaleng.2008.06.023 . hal-00516159

**HAL Id: hal-00516159**

**<https://hal.science/hal-00516159>**

Submitted on 9 Sep 2010

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

## Accepted Manuscript

Liquid Cooling of Bright LEDs for Automotive Applications

Yan Lai, Nicolás Cordero, Frank Barthel, Frank Tebbe, Jörg Kuhn, Robert Apfelbeck, Dagmar Würtenberger


PII: S1359-4311(08)00281-0  
DOI: [10.1016/j.applthermaleng.2008.06.023](https://doi.org/10.1016/j.applthermaleng.2008.06.023)  
Reference: ATE 2551

To appear in: *Applied Thermal Engineering*

Received Date: 6 February 2008  
Revised Date: 11 June 2008  
Accepted Date: 12 June 2008

Please cite this article as: Y. Lai, N. Cordero, F. Barthel, F. Tebbe, J. Kuhn, R. Apfelbeck, D. Würtenberger, Liquid Cooling of Bright LEDs for Automotive Applications, *Applied Thermal Engineering* (2008), doi: [10.1016/j.applthermaleng.2008.06.023](https://doi.org/10.1016/j.applthermaleng.2008.06.023)

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.



## Liquid Cooling of Bright LEDs for Automotive Applications

Yan Lai <sup>a</sup>, Nicolás Cordero <sup>a,\*</sup>, Frank Barthel <sup>b</sup>, Frank Tebbe <sup>b</sup>, Jörg Kuhn <sup>b</sup>, Robert Apfelbeck <sup>b</sup>, Dagmar Würtenberger <sup>b</sup>

<sup>a</sup> Tyndall National Institute, Cork, Ireland

<sup>b</sup> Odelo GmbH, Schwaikheim, Germany

### Abstract

With the advances in the technology of materials based on GaN, high brightness white light emitting diodes (LEDs) have flourished over the past few years and have shown to be very promising in many new illumination applications such as outdoor illumination, task and decorative lighting as well as aircraft and automobile illuminations. The objective of this paper is to investigate an active liquid cooling solution of such LEDs in an automotive headlights application. The thermal design from device to board to system level has been carried out in this research. Air cooling and passive liquid cooling methods were investigated and excluded as unsuitable, and therefore an active liquid cooling solution was selected. Several configurations of the active liquid cooling system were studied and optimisation work was carried out to find an optimum thermal performance.

### Keywords

Liquid cooling, bright LEDs, white LEDs, thermal management, automotive.

---

\* Corresponding author. Address: Tyndall National Institute, Lee Maltings, Prospect Row, Cork, Ireland. Tel. +353-21-490 4073, fax: +353-21-427 0271. e-mail: nicolas.cordero@tyndall.ie

## 1. Introduction

Due to the small package size, styling flexibility and superior performance over incandescent light sources, LEDs are widely used in many automobile exteriors nowadays, such as brake lights, turn indicators and tail lights. With the development of higher light output packages, the use of white LED sources for vehicle forward lighting applications is beginning to be considered. Although many properties of LEDs have made them a very promising light source for vehicle forward lighting, the use of white LEDs as automobile headlamps is still in its infancy. Currently, LEDs have appeared as forward lighting only in some concept cars, and there are no LEDs customised for headlight applications.

The widespread introduction of LED headlamps in Europe is dependent on legal regulations, which are enacted in all specifications. One important specification of a LED headlamp is the required luminous flux per lamp (low beam) of 1,000 lm. At present, LEDs offer a high cost solution with insufficient lumen output for production vehicles. However, since the average current bright LED output is only 40 lm/W, more LEDs and higher driving powers are needed to meet this standard [1]. In order to attain the required flux of an LED headlamp, the optics must be customised. As the demand for light output increases, the driving power of the LED increases continuously. The thermal management of LED packaging, which has great effect on their efficiency, performance and reliability, has become more and more important for these devices.

An increase in diode junction temperature leads to a decrease in the LED efficiency and a shift in the emission wavelength. Therefore, the LED operating temperature must be kept well below its maximum operating temperature (e.g.  $< 125\text{ }^{\circ}\text{C}$ ) for optimum efficiency operation and small colour variation. To achieve this, the thermal solution must be all-inclusive and must address thermal issues at all levels—device, package, board and system level. Commercially available bare die (unpackaged chip) bright LEDs are used in this application. Thermal simulations using Computational Fluid Dynamics (CFD) were carried out at all levels to support the search for a suitable thermal management solution. The design of the thermal management solution was supported using the commercial CFD software FloTherm [2] which calculates the temperature distribution and the pressure and velocity for the surrounding fluids (air, cooling liquid, etc.).

## 2. Choice of active liquid cooling

### 2.1. From device to board level

The chosen LED for this application is a Cree XBright900. This LED is a  $900 \times 900 \mu\text{m}$  chip that is commercially available as bare die [3]. It generates light of wavelengths between 460 and 470 nm in 2.5 nm range bins, which gives the colour of blue. With appropriate thermal management it can operate generating up to 2.7 W of heat per LED. The system proposed here consists of 15 LEDs mounted on 5 boards with 3 LEDs each [4]. Therefore the whole system dissipates 40.5 W.

To simplify the mounting process, the LEDs had to be individually packaged. Furthermore, the LEDs need to incorporate a layer of phosphor to convert the blue light from the GaN based LED to a white (visible spectrum) light emitter. The heat is dissipated directly from the active region of the device to the package. Therefore, a high thermal conductivity ceramic must be chosen to provide the package with a low resistance thermal path and electrical insulation simultaneously. Aluminium nitride ( $k=200 \text{ W/mK}$ ), was chosen in this case as it fits the role very well in providing thermal conduction and heat spreading for high power operation. The calculated thermal resistance between the LED and the bottom of the AlN package is less than  $2 \text{ }^\circ\text{C/W}$  [5][6].

The AlN package is then mounted on an insulated metal substrate (IMS) (Figure 1). Adopting IMS provides both heat spreading and a good thermal path to the heat sink or cold plate and greatly simplifies the system design. IMS consists of three layers: a copper foil circuitry layer bonded together with a thin dielectric layer, and a metal base plate made of aluminium [7].

Several different materials making up the dielectric layer as well as different combinations of the thickness of the three layers of IMS have been compared. The thermal simulations show that the optimum board should have a thick circuitry layer to spread the heat while a very thin dielectric layer made of a material with higher thermal conductivity to reduce the thermal resistance. The thicknesses of these layers are therefore only limited by the manufacturability of the IMS. The chosen structure of IMS includes a  $70 \mu\text{m}$  copper layer, a  $75 \mu\text{m}$  dielectric layer with thermal conductivity of  $2.2 \text{ W/mK}$  and a  $1 \text{ mm}$  Al core board (Table 1) [5][6].

## 2.2. System level thermal management – Air cooling

The headlight application requires forward light emission. The optical design is based on a reflective mirror and therefore requires the IMS boards to be mounted at 45° facing the mirror placed at the back of the headlight assembly. For passive air-cooling, the heat sink has to be mounted directly behind the IMS board. In the actual application, the whole system is placed inside the headlamp enclosure, which reduces the heat dissipation to the surrounding ambient by convection. Furthermore, due to the space constraints inside the headlamp, the size of the heat sink is limited. Figure 2 shows a cross section of the modelled air-cooled headlight, where the LED junction temperature (hottest point) far exceeds its maximum permitted value of 125°C.

Active air cooling was also investigated here. However, it is not a feasible cooling solution since the space and enclosure constraints would necessitate a large number of high flow fans. This is impractical from reliability, cost and assembly viewpoints. Therefore, liquid cooling solutions were chosen for further analysis.

## 2.3. System level – Passive liquid cooling

Two possible passive liquid cooling configurations were investigated: passive closed-loop and heat pipe.

The close-loop configuration is based on indirect cooling (fluid is not in contact with the LEDs or any other electrically active components), and therefore any liquid with good heat transfer properties, such as water, can be used [8]. Thermal simulations showed that a passive closed-loop could achieve the required cooling levels to keep the LED junction temperatures well below their maximum operation temperature. However, in passive systems the motion of the fluid is achieved by buoyancy forces. Therefore, these systems require the heat exchanger to be placed above the heat source, so that the hotter and lighter cooling fluid (water) will travel upwards against gravity to be cooled. However, although feasible from the thermal point of view, it is not a suitable solution for the cooling of headlamps, as the headlight design requires the heat exchanger to be positioned below the LED modules.

For the heat pipe solution, a loop heat pipe system was considered in order to transfer the heat from the IMS boards to the heat exchanger. However, since in this application each individual LED board needs to be mechanically adjustable for proper light beam alignment, the heat pipe is therefore required to be bendable, which significantly increases the cost of the cooling solution. From the commercially available flexible heat pipe products (e.g. Thermotek, [9], Dau [10]), the price could be as expensive as \$1,000 per unit. Again, although feasible from the thermal point of view, the flexible heat pipe system is not a suitable solution due to engineering and cost considerations.

Therefore, the cooling solution of high brightness LEDs in the automotive application turns to active liquid cooling.

### **3. Active liquid cooling**

#### **3.1. System structure**

The chosen liquid cooling system consists of a pump, cold plates thermally connected to the heat sources (IMS boards), a liquid reservoir, and a heat exchanger. The cold plates and the heat exchanger are connected using flexible silicone hoses which create a closed loop. See [11] for a more detailed description of the complete headlight system.

As each board has to be individually mechanically adjustable, a separate cold plate is attached to each board. In automotive headlights heat should be available near the front lenses to defrost them and to prevent them steaming up. Therefore, the heat exchanger is placed directly behind the front lens without shadowing the luminous flux. Due to the weight and volume limitations, and the fact that the high and low beam are never on at the same time, a single heat exchanger can be shared by both the high beam (HB) and low beam (LB) LEDs. The heat exchanger consists of a heat sink with a liquid-cooled base. Due to its good thermal properties and availability, the most suitable liquid for the cooling solution is water with a number of additives (e.g. antifreeze -glycol-, anti-algae, anti-fungal, etc.).

Several configurations for the closed loop were considered. To reduce damage to the pump and therefore improve its reliability, the pump only sees 'cold' liquid. First a solution with five LB-HB circuits in parallel (Figure 3) was investigated. Although optimal from the thermal point of view (all cold plates

cooled at the same temperature and lower pressure head), this solution requires two manifolds plus two different hose sections, which makes the system far too complicated and therefore, not the best option in this case.

A second solution consists of the same five LB-HB cold plate circuits but connected in series on a single loop. The circuit is longer and therefore the pressure drop is higher. Furthermore the last cold plate has higher temperature than the first one. However, CFD simulations show that a) the temperature difference between the first and the last boards is less than 5°C; and b) the pressure drop in the circuit is well below the pressure head of standard pumps and should not have a detrimental effect on the thermal performance of the liquid cooling solution.

Finally, as the LB and the HB LEDs are never on (generating heat) at the same time, an alternative design is proposed, consisting of a liquid loop through all the LB cold plates in series followed by the HB in series and then into the heat exchanger (Figure 4). This design presents the advantages of having a smaller number of hoses than the previous one (14 instead of 17), shorter hoses which allows the separate mechanical adjustment of both beams, and being simpler to mount. Again the thermal simulations show that the junction temperature of the last set of three LEDs (last board in the loop) is less than 5°C higher than those in the first set.

The system configuration as modelled using Flotherm is shown in Figure 5. The model only includes a set of 15 LEDs (5 boards with 3 LEDs each) because only one of the beams (either HB or LB) is turned on at the same time. Furthermore, the heat exchanger (heat sink plus cold plate) was modelled at a 45° angle, while in the actual system (Figure 4) it is horizontal, to simplify the finite volume mesh.

### **3.2. Thermal optimisation**

#### *3.2.1. Liquid flow optimisation*

Figure 6 shows the calculated LED junction temperature as a function of the nominal (zero pressure) pump flow. As the nominal pump flow increases the LED junction temperature decreases. However, for flows higher than 0.12 l/s, the reduction is less significant.



Figure 7 shows the calculated relation between the nominal and the actual flows for the chosen closed loop circuit. For low nominal flows the effect of the pressure drop is insignificant. However, as the flow increases, the pressure drop in the liquid cooling loop limits the actual flow. Figure 8 shows the relation between pressure drop and flow for the loop and the characteristics of a linear pump with a nominal flow of 0.12 l/s and a nominal pressure head (no flow) of 25 kPa. The results show that the chosen pump will be operating within its recommended operation range.

### 3.2.1. Heat exchanger (heat sink) optimisation

The heat sink design relies on the external condition of the heat sink, such as the airflow type and the operating environment that determines the components placement and the air flow rate [12]. In this application, since the heat sink is placed horizontally, there is no preferential flow direction, and therefore, in order to reduce the total weight, a heat sink with pins was preferred to one with fins.

There are a number of parameters to be considered in the design of the optimal heat sink, such as pin length, pin numbers, base thickness, etc. Due to the conflicting effects of some of the parameters on the LED temperature, investigation of these parameters is undertaken through an iterative procedure.

The parameters studied in this case include the following (see Figure 9):

- 1) Heat sink base thickness ( $t$ ). Since the cold plate underneath has already spread the heat over the whole area, the base thickness has very small influence on the LED temperature. Due to the weight constraints, it should be as thin as mechanically possible. For the rest of the optimisation, it was set to 5 mm.
- 2) Heat sink height ( $H$ ). The total height of the heat sink is equal to the base thickness ( $t$ ) plus the pin height ( $h$ ). The pin height is the dominant parameter in the optimisation. Therefore, from the thermal point of view, it should be as high as possible within the limitation that the heat sink should not block the out-coming light.
- 3) Pin length ( $l$ ). The calculated optimum value is 4.5 mm. However, the sensitivity of the LED temperature on pin length is small for values around this optimum. According to the simulations, the

values between 3.5 and 6 mm only contribute to an increase of less than 1 °C in the LED junction temperature. Therefore, any value in this range is suitable in this application.

- 4) Pin width ( $w$ ). The calculated optimum value is 9mm. As the same with the case of pin length, small variations in the range between 7.5 and 10 mm only produce a small increase in temperature.
- 5) Number of pins in the X direction ( $N_x$ ). The calculated optimum value is 40, which corresponds to spacing between pin of 5.1 mm. Again, from the thermal simulations, any number falls in the range between 35 and 45 works in this case.
- 6) Number of pins in the Y direction ( $N_y$ ). Due to the limited space in the headlamp, the maximum number referred to here is on the widest edge, the number will be smaller in the narrow end. The calculated optimum value is 7, which corresponds to a spacing of 4 mm. Values from 7 up are also feasible.
- 7) The total weight of this optimum heat sink realised in aluminium is less than 800 grams.

The optimisation of some parameters depends on others (e.g. pin length and pin width). Therefore, they had to be considered simultaneously during the optimisation process (see Figure 10).

Other parameters (e.g. pin number) are independent and can therefore be optimised separately (Figure 11).

In summary, the dimensions of the optimised heat sink for this application are as follows (all dimensions in mm).

- Optimised design

$$t = 5 \text{ mm}, H > 30 \text{ mm}, h > 25 \text{ mm}, l = 4.5 \text{ mm}, w = 9 \text{ mm}, N_x=8, N_y=7$$

- Allowable design margins ( $< 1^\circ\text{C}$  increase in junction T)

$$3.5 < l < 6 \text{ mm}, 5 < w < 10 \text{ mm}, 35 < N_x < 45, 7 < N_y$$

#### 4. Experimental results

The optimised headlight was realised and thermally characterised. The headlight, together with its front lens, was placed in a heat chamber with an ambient temperature of 30°C. At first, the temperature measurements were carried out only with the LB in operation, as set in the simulations. However, the

LEDs were driven with a lower forward current, so their heat dissipation was half of that considered in the CFD simulations. Since LED heat generation with the chosen electrical parameter was much lower than originally assumed in the simulation, the HB and the LB were operated simultaneously in order to match the heat input into the real system.

Fourteen thermal test points were set inside the enclosure along the thermal path, between the LEDs and the heat exchanger. After approximately two hours, the temperature in all the 14 test points inside the enclosure reached steady-state values. The measured thermal resistances between the different test points along the thermal path are in good agreement with the simulated results (see Figure 12. For more details, please refer to [11]). The only discrepancy encountered was between the heat exchanger and ambient. This was due to the fact that the enclosure was considered as an ideal insulator in the thermal simulations while in the actual system there was some heat dissipation by conduction.

## 5. Conclusions

This paper demonstrates the procedure for selection and optimisation of an active liquid cooling solution for high brightness LEDs customised for novel headlight applications.

It was found that air and passive liquid cooling were either insufficient to maintain LED junction temperature below its maximum allowable levels or unpractical in the actual application. While some of these solutions would be suitable from a purely thermal point of view, this is not the case when the optical and mechanical designs are taken into account. Therefore all aspects of the headlight design must be taken into account when seeking a suitable thermal management solution.

Therefore active liquid cooling is selected as the optimum cooling solution under these circumstances. Several different system structures of active liquid cooling are studied and compared in this paper. And thermal optimisations of the liquid flow and heat sink are carried out in order to maximise the thermal performance. During the search for the optimum thermal solution, thermal management is not the only factor to focus on; all related issues such as manufacturability and product specifications are also taken into account.

With the development of brighter white LEDs, the driving power required for a certain light output will be decreasing continuously in the future. Therefore heat dissipation will also decrease. With the reduced power requirements for the system and lower heat dissipation, the cooling solution can once again be simplified to only passive air-cooling.

### **Acknowledgements**

This work was partly supported by the European Commission through the FP6-Transport project ISLE (Contract TST3-CT03-506316). The authors would like to thank Rafael Jordan (TU Berlin) and Jochen Kunze (Global Light Industries GmbH) for fruitful discussions and their support of this work.

### **Appendix**

### **References**

- [1] T. Pearson, E. Mounier, J.C. Eloy, D. Jourdan, Solid-state lighting in the automobile: concept, market timing and performance, *EDs Magazine* 2005, 25-27.
- [2] Flomerics Ltd., FloTherm™ 6.1 Instruction Manual, 2005.
- [3] Cree LED Lighting Website [Online]: <http://www.cree.com>.
- [4] O. Dross, A. Cvetkovic, P. Benítez, J.C. Miñano, J. Chaves, Novel LED headlamp architectures that create high quality patterns independent of LED shortcomings, *Proc. ISAL 2005*, 117-127.
- [5] Y. Lai, N. Cordero, Thermal management of bright LEDs for automotive applications, *Proc. of the 7<sup>th</sup> EuroSimE Conference*, 2006, 390-394.
- [6] Y. Lai, N. Cordero, F. Barthel, F. Tebbe, J. Kuhn, R. Apfelbeck, D. Würtenberger, Liquid Cooling of Bright LEDs for Automotive Applications, *Proc. Thermic 2006*, 80-85.
- [7] J. Stratford, A. Musters, Insulated metal printed circuits – a user-friendly revolution in power design, *Electronics Cooling*, 2004 (10) 30-34.
- [8] F.P. Incropera, *Liquid Cooling of Electronic Devices by Single-Phase Convection*, John Wiley & Sons, 1999.

- [9] [www.thermotekusa.com](http://www.thermotekusa.com)
- [10] [www.dau-at.com](http://www.dau-at.com)
- [11] D. Würtenberger, F. Barthel, J. Kuhn, F. Tebbe, R. Apfelbeck, N. Cordero, Y. Lai, Investigation of an active liquid cooling system for an LED headlamp, International Symposium on Automotive Lighting, Proc. ISAL 2007, 532-540
- [12] B. Karimpourian, J. Mahmoudi, Some important considerations in heatsink design, Proc. of the 6<sup>th</sup> EuroSimE Conference, 2005, 406-413.

ACCEPTED MANUSCRIPT

**Captions**

**Figure 1.** Insulated Metal Substrate assembly. (a) AlN cup with wire-bonded LED, (b) Circuit layer, (c) Dielectric layer and (d) Aluminum substrate.

**Figure 2.** Temperature profile across the headlight assembly for passive air cooling ( $T_j=200^\circ\text{C}$ ).

**Figure 3.** Cold plates and heat exchanger design and their hose connections.

**Figure 4.** Active liquid cooling configuration—the liquid loop connects all the LB cold plates in series followed by the HB in series and then into the heat exchanger.

**Figure 5.** Full model of active liquid cooling of complete low beam system inside the headlamp enclosure (shown in Figure 4).

**Figure 6.** Calculated LED junction temperature (top) and IMS board temperature (bottom) as a function of the nominal flow (with a nominal pressure head of 25 kPa)

**Figure 7.** Calculated actual flow through the cooling loop as a function of the nominal (zero pressure) flow.

**Figure 8.** Pressure vs. flow characteristics for the liquid cooling loop and linear pump characteristics

**Figure 9.** Heat sink parameters and dimensions

**Figure 10.** LED temperature as a function of pin length and pin width. A) 3D view and B) Contour plot.

**Figure 11.** LED temperature as the function of pin number in the X (diamonds) and Y (squares) directions.

**Figure 12.** Measured and simulated temperatures at different points of the assembly shown in Figure 4.

**Table 1.** IMS board structure and materials used in thermal modelling.

**Tables**

| Layer      | Material        | Thickness        | k (W/mK) |
|------------|-----------------|------------------|----------|
| Circuit    | Cu              | 70 $\mu\text{m}$ | 385      |
| Dielectric | Ceramic/Polymer | 75 $\mu\text{m}$ | 2.2      |
| Metal      | Al              | 1 mm             | 200      |
| Substrate  |                 |                  |          |

Table 1. IMS board structure and materials used in thermal modelling.

ACCEPTED MANUSCRIPT

## Figures




Figure 1. Insulated Metal Substrate assembly. (a) AlN cup with wire-bonded LED, (b) Circuit layer, (c) Dielectric layer and (d) Aluminum substrate.




Figure 2. Temperature profile across the headlight assembly for passive air cooling ( $T_j=200^\circ\text{C}$ ).




Figure 3. Cold plates and heat exchanger design and their hose connections.






Figure 4. Active liquid cooling configuration—the liquid loop connects all the LB cold plates in series followed by the HB in series and then into the heat exchanger.




Figure 5. Full model of active liquid cooling of complete low beam system inside the headlamp enclosure (shown in Figure 4).




Figure 6. Calculated LED junction temperature (top) and IMS board temperature (bottom) as a function of the nominal flow (with a nominal pressure head of 25 kPa)




Figure 7. Calculated actual flow through the cooling loop as a function of the nominal (zero pressure) flow.




Figure 8. Pressure vs. flow characteristics for the liquid cooling loop and linear pump characteristics




Figure 9. Heat sink parameters and dimensions




Figure 10. LED temperature as a function of pin length and pin width. A) 3D view and B) Contour plot.




Figure 11. LED temperature as the function of pin number in the X (diamonds) and Y (squares) directions.




Figure 12. Measured and simulated temperatures at different points of the assembly shown in Figure 4.