

A note on: An optimal batch size for an imperfect production system with quality assurance and rework

Udo Buscher, Steffen Rudert, Christian Schwarz

▶ To cite this version:

Udo Buscher, Steffen Rudert, Christian Schwarz. A note on: An optimal batch size for an imperfect production system with quality assurance and rework. International Journal of Production Research, 2009, 47 (24), pp.7063-7067. 10.1080/00207540802317723. hal-00530218

HAL Id: hal-00530218 https://hal.science/hal-00530218

Submitted on 28 Oct 2010

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



A note on: An optimal batch size for an imperfect production system with quality assurance and rework

Journal:	International Journal of Production Research
Manuscript ID:	TPRS-2008-IJPR-0173.R1
Manuscript Type:	Technical Note
Date Submitted by the Author:	19-Jun-2008
Complete List of Authors:	Buscher, Udo; Dresden University of Technology, Faculty of Business Management and Economics, Department of Industrial Management Rudert, Steffen; Dresden University of Technology, Faculty of Business Management and Economics, Department of Industrial Management Schwarz, Christian; Dresden University of Technology, Faculty of Business Management and Economics, Department of Industrial Management
Keywords:	LOT SIZING, RE-MANUFACTURING, QUALITY ASSURANCE
Keywords (user):	LOT SIZING, RE-MANUFACTURING



RESEARCH NOTE

A note on: An optimal batch size for an imperfect production system with quality assurance and rework

Udo Buscher^{a*}, Steffen Rudert^a and Christian Schwarz^a

^aFaculty of Business Management and Economics, Department of Industrial Management, Dresden University of Technology, 01062 Dresden, Germany

In Ojha *et al.* 2007 three models are introduced in the context of imperfect production systems. By analysing the proposed models we identify some problems. In particular we focus on six issues of the models developed in Ojha *et al.* and propose some modifications. All corrections are presented in detail and the numerical example of Ojha *et al.* is used to show the influence of the issues addressed in this paper.

Keywords: Imperfect production, Lot sizing, Remanufacturing

*Corresponding author. Email: udo.buscher@tu-dresden.de

Analysis

In Ojha *et al.*, a static deterministic model with imperfect production is considered. Raw materials are received from a supplier, processed and delivered to the customer. Three scenarios are distinguished. Within the most complex one, multiple lots using a batch of raw material and each production lot is delivered to the customer in multiple instalments. Furthermore, two special cases of this model are considered. In the second and third model all produced items of a lot are delivered in a single instalment. The third model additionally applies a lot-for-lot policy, i.e. the raw material is ordered in quantity Q_r that is required for one production run. In spite of the contribution of Ojha *et al.* understanding imperfect production in the context of inventory-production-delivery systems, some issues addressed in their paper remain unclear. In the following we discuss six issues in more detail.

Firstly, Ojha *et al.* assume merely that production rate P must be higher than demand rate D_f . However, when dealing with imperfect production, this does not necessarily avoid shortages in the system. Using the same equipment, rework is done directly after production. Since sequential movement is assumed additionally, the sum of production and rework time $(t_1 + t_2)$ must not exceed the cycle time $T = Q_f/D_f$. Recall that production uptime t_1 is defined as Q_f/P and the rework time t_2 is given by $(\beta Q_f)/P$, the aforementioned condition only holds if $P \ge (1 + \beta)D_f$ is valid. Since this is a general condition, it affects all three models developed by Ojha *et al.*

Secondly, the price for an item of raw material in Ojha *et al.* is C. In addition, the conversion factor f_0 specifies how many finished goods can be made out of one raw material item. It should be noted that C is used as raw material price for a raw material part as well as for the raw material price of a finished product. This is only true for the special case of $f_0 = 1$. Therefore, we have to differentiate between C_r , the price for one unit raw material, and C_f , the effective value of raw material for a finished product. The relation of C_r and C_f is obviously $C_f = C_r/f_0$. In this context, the inventory carrying cost for reworkable items I_{RE} and for finished products I_F are affected.

Thirdly, we address the finished goods inventory carrying cost where a production lot is distributed to the customer in multiple instalments. In this case the finished goods inventory carrying cost consists of those costs which are incurred during production and those which are incurred during delivery: $I_F = I_{F, prod} + I_{F, del}$. While $I_{F, prod}$ is calculated correctly, we examine $I_{F, del}$. Following Ojha *et al.* the values of non-defective items and reworked items are $C_f + V$ and $C_f + 2V$, respectively. Unfortunately, this fact is ignored while calculating $I_{F, del}$. The average cost per unit of the finished product is

$$\frac{(C_f + V)(1 - \beta)Q_f + (C_f + 2V)\beta Q_f}{Q_f} = C_f + V(1 + \beta).$$
(1)

Thus, the correct finished goods inventory carrying costs are

$$I_F = i(C_f + V) \frac{D_f Q_f}{2P} \left[1 + \beta (1 - \beta) \right] + i[C_f + V(1 + \beta)] \frac{x}{2} (m - 1);$$
(2)

or

$$I_F = i(C_f + V) \left(\frac{D_f Q_f}{2P} \left[1 + \beta(1 - \beta) \right] + \frac{x}{2} (m - 1) \right) + \frac{\beta i x V}{2} (m - 1).$$

Fourthly, usually in static deterministic inventory-models the cost function is formulated in \$ per year. However, Ojha *et al.* specify inspection, late delivery and lost production costs as cycle cost. The corresponding expressions have to be divided by the cycle length T. The correct expressions are $C_I = C_i D_f$; $C_L = (\beta C_I D_f)/P$; $C_{LP} = \beta D_f V$. In consequence, these cost components have no impact on the optimal values of the decision variables. In the following the issues described above are incorporated into the total cost functions. As a consequence the functions of Q^* , n^* and m^* need to be adjusted slightly.

$$TC^{I}(m,n) = \frac{imxC_{f}}{2} \left[\frac{D_{f}}{P} + n - 1 \right] + \frac{D_{f}}{mx} \left(\frac{A_{r}}{n} + A_{f} \right) + i(C_{f} + V) \frac{mxD_{f}}{2P} \left[1 + \beta(1 - \beta) \right] + i \left(C_{f} + V(1 + \beta) \right) \frac{x}{2} (m - 1) + VD_{f} \left(1 + \beta \right) + \frac{imx\beta D_{f}}{2P} (1 + \beta)(C_{f} + V) + \frac{imx\beta^{2} D_{f} V}{2P} + C_{i}D_{f} + \frac{\beta C_{i}D_{f}}{P} + \beta D_{f} V$$
(3)

$$m^{I^*} = \sqrt{\frac{A_f D_f}{\Delta_1 x}} \tag{4}$$

$$n^{I^*} = \sqrt{\frac{2\Delta_1 A_r}{ixA_f C_f}} \tag{5}$$

$$\Delta_{1} = \frac{ixC_{f}}{2} \left(\frac{D_{f}}{P} - 1 \right) + \frac{ixD_{f}}{2P} (C_{f} + V) \left[1 + \beta (1 - \beta) \right] + \frac{ix}{2} \left(C_{f} + V (1 + \beta) \right) + \frac{\beta ixD_{f}}{2P} (1 + \beta) (C_{f} + V) + \frac{\beta^{2} ixD_{f} V}{2P}$$
(6)

$$TC^{II}(Q_{f},n) = \frac{iC_{f}Q_{f}}{2} \left[\frac{D_{f}}{P} + n - 1 \right] + \frac{D_{f}}{Q_{f}} \left(\frac{A_{r}}{n} + A_{f} \right) + \frac{iQ_{f}D_{f}}{2P} \left[1 + \beta(1-\beta) \right] (C_{f} + V) + VD_{f} \left(1 + \beta \right) + \frac{i\beta Q_{f}D_{f}}{2P} (1+\beta)(C_{f} + V) + \frac{i\beta^{2}Q_{f}D_{f}V}{2P} + C_{i}D_{f} + \frac{\beta C_{l}D_{f}}{P} + \beta D_{f}V$$

$$(7)$$

$$Q_f^{II*}(n) = \sqrt{\frac{D_f \left(\frac{\Delta_f}{n} + A_f\right)}{\frac{inC_f}{2} + \Delta_2}}$$
(8)

$$Q_f^{II*} = \sqrt{\frac{A_f D_f}{\Delta_2}} \tag{9}$$

$$n^{II*} = \sqrt{\frac{2\Delta_2 A_r}{iA_f C_f}} \tag{10}$$

$$\Delta_{2} = \frac{iC_{f}}{2} \left(\frac{D_{f}}{P} - 1 \right) + i(C_{f} + V) \frac{D_{f}}{2P} \left[1 + \beta(1 - \beta) \right] + \frac{\beta^{2} i D_{f} V}{2P} + \frac{\beta i D_{f}}{2P} (1 + \beta) (C_{f} + V)$$
(11)

$$TC^{III}(Q_f) = \frac{iQ_f D_f C_f}{2P} + \frac{D_f}{Q_f} (A_r + A_f)$$

$$+ \frac{iQ_f D_f}{2P} [1 + \beta(1 - \beta)] (C_f + V) + VD_f (1 + \beta)$$

$$+ \frac{i\beta Q_f D_f}{2P} (1 + \beta) (C_f + V) + \frac{i\beta^2 Q_f D_f V}{2P}$$

$$+ C_i D_f + \frac{\beta C_i D_f}{P} + \beta D_f V$$

$$Q_f^{III*} = \sqrt{\frac{2D_f}{\Delta_3}} (A_r + A_f)$$
(13)

$$\Delta_{3} = \frac{iC_{f}D_{f}}{P} + i(C_{f} + V)\frac{D_{f}}{P}[1 + \beta(1 - \beta)] + \frac{\beta iD_{f}}{P}(1 + \beta)(C_{f} + V) + \frac{\beta^{2}iD_{f}V}{P}$$
(14)

Fifthly, taking the first derivative of $TC^{I}(m,n)$ with respect to m we see that the optimal value of m depends on the given n, thus $m^{*}(n)$. Conversely, the optimal value of n is also a function of m. Therefore, it is not sufficient to verify only the four combinations $TC^{I}(m^{*}|_{n^{*}})$, $TC^{I}(m^{*}|_{$

$$n(m) = \frac{1}{m} \sqrt{\frac{2A_r D_f}{ix^2 C_f}}$$

Substituting of this formula into (3) provides

$$TC(m) = \Delta_1 m + \frac{A_f D_f}{xm} + \Delta_4$$
(15)

with

$$\Delta_4 = -i \left(C_f + V \left(1 + \beta \right) \right) \frac{x}{2} + D_f V + \beta D_f V + C_i D_f + \frac{\beta C_l D_f}{P} + \beta D_f V + \sqrt{2iC_f A_r D_f}.$$

Since (3) is convex in m, we are able to establish a lower bound m_l and an upper bound m_u within which the optimal integer value of m is located. To compute both boundary values, we equate the costs C_b with the right-hand side of (15) and solve the resulting expression for m. In doing so, we obtain a quadratic equation which provides the following two integer values:

$$m_1 = max(1; \lceil \alpha_1 - \alpha_2 \rceil)$$
 and $m_u = max(1; \lfloor \alpha_1 + \alpha_2 \rfloor)$

with

$$\alpha_1 = -\frac{\Delta_4 - C_b}{2\Delta_1}$$
 and $\alpha_2 = \sqrt{\left(\frac{\Delta_4 - C_b}{2\Delta_1}\right)^2 - \frac{A_f D_f}{\Delta_1}}$.

Due to the convexity of *TC* in *n*, it is possible to calculate the optimal integer *n*-value for a given m by $\lfloor n(m) \rfloor$ or $\lceil n(m) \rceil$. For all *m*-values between the lower and upper bound the optimal *n*-value is determined by comparing the resulting costs. Each time a new temporary optimal solution is found, we update the bounds m_i and m_u by using cost TC^I as the new C_b -value. This successive tightening of these bounds offers - in contrast to using static bounds - the potential to considerably reduce the solution effort needed to ascertain the cost minimizing solution. After examining all relevant pairs (m, n), the best solution so far represents the optimal solution for the underlying planning problem.

Sixthly, in the second model of Ojha *et al.* the lot size Q_f and the number *n* of production lots have to be determined. Obviously, n_{opt} has to be an integer value. Therefore, Ojha *et al.* compare $TC^{II}(Q^*, \lfloor n^* \rfloor)$ and $TC^{II}(Q^*, \lceil n^* \rceil)$ to find n_{opt} . However, it would be favorable to calculate the optimal Q_f for a given value of *n* and compare the resulting cost afterwards, i.e. $TC^{II}(Q(\lfloor n^* \rfloor), \lfloor n^* \rfloor)$ and $TC^{II}(Q(\lceil n^* \rceil), \lceil n^* \rceil)$.

Numerical example

For better understanding the impact of the issues described above, we use the numerical example of Ojha *et al.* The problem parameters are: $\beta_1 = 0.05$; $E_1 = 0.1$; $E_2 = 0.1$; $A_f = 50$ [\$ per setup]; $A_r = 150$ [\$ per order]; $C_r = 2$ [\$ per unit raw material]; $C_i = 0.2$ [\$ per unit]; $C_l = 0.1$ [\$ per year]; $D_f = 2000$ [units per year]; $f_0 = 0.95$; i = 0.18 [per year]; P = 3000 [units per year]; V = 1 [\$ per unit]; x = 20 [units]; $C_f = C_r/f_0 = 2.11$. The procedure to get the optimal solution for model I is shown in the following table.

**** Place table 1 here ****

The procedure proposed by Ojha *et al.* does not consider the combination m = 22 and n = 3, which is the optimal solution.

The results using the formulation presented in this paper and those of Ojha *et al.* are given in table 2. Whereas a plus sign is used to indicate the results obtained in this note, a hash marks the results of Ojha *et al.* It should be noted that $TC^{\#}$ is calculated by inserting the production policy derived in Ojha *et al.* into the cost functions derived in this note to get an impression of the induced cost deviations for the given example.

**** Place table 2 here ****

Due to the corrected total cost function, the optimal expressions of the decision variables m, n and Q_f show significant differences. Finally, it is important to point out that the main idea and contribution of the paper of Ojha *et al.* have a great value.

References

Ojha, D., Sarker, B.R., and Biswas, P., 2007. An optimal batch size for an imperfect production system with quality assurance and rework. *International Journal of Production Research*, 45 (14), 3191-3214.

iteration	т	п	$TC^{I}(m,n)$	C	b	range of <i>m</i>		current m_{opt} ; n_{opt} 23; 3
start	23	3	3865.97	386	3865.97		$n \le 25$	
1	21	2	3905.37	386	3865.97		$n \le 25$	23; 3
2	21	3	3865.90	386	3865.90		$n \le 25$	21; 3
3	22	2	3895.26	386	3865.90		$n \le 25$	21; 3
4	22	3	3864.99	3864	3864.99		$m \le 24$	22; 3
5	23	2	3887.51	3864	3864.99		$m \le 24$	22; 3
6	23	3	3865.97	3864	3864.99		$m \le 24$	22; 3
7	24	2	3881.81	3864.99		$22 \le m \le 24$		22; 3
8	24	3	3868.59	3864.99		$22 \le m \le 24$ $22 \le m \le 24$		22; 3
Table 2 Co	$\frac{\text{mparison}}{Q_f^+}$	$\frac{\text{of result}}{Q_f^{\#}}$	$\frac{s}{n^+}$	<i>n</i> [#]	<i>m</i> ⁺	<i>m</i> [#]	TC ⁺	TC [#]
Ι	$\frac{\mathcal{Q}_f}{440}$	$\frac{\mathcal{Q}_f}{340}$			m 22	17		
I	440 671	540 443	3 2	4 3		17	3864.99 3705.29	3885.87 3741.48
III	1045	443 757	-	- -	_		3705.29	3765.45