

# MARSIS surface reflectivity of the south residual cap of Mars

Jeremie Mouginot, W. Kofman, A. Safaeinili, C. Grima, A. Null Herique, J.J.

Plaut

#### ► To cite this version:

Jeremie Mouginot, W. Kofman, A. Safaeinili, C. Grima, A. Null Herique, et al.. MARSIS surface reflectivity of the south residual cap of Mars. Icarus, 2009, 201 (2), pp.454. 10.1016/j.icarus.2009.01.009 . hal-00533497

# HAL Id: hal-00533497 https://hal.science/hal-00533497v1

Submitted on 7 Nov 2010

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Accepted Manuscript

MARSIS surface reflectivity of the south residual cap of Mars

Jeremie Mouginot, W. Kofman, A. Safaeinili, C. Grima, A. Herique, J.J. Plaut

PII:S0019-1035(09)00031-1DOI:10.1016/j.icarus.2009.01.009Reference:YICAR 8891



To appear in: Icarus

Received date:1 July 2008Revised date:16 October 2008Accepted date:9 January 2009

Please cite this article as: J. Mouginot, W. Kofman, A. Safaeinili, C. Grima, A. Herique, J.J. Plaut, MARSIS surface reflectivity of the south residual cap of Mars, *Icarus* (2009), doi: 10.1016/j.icarus.2009.01.009

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

# 1 MARSIS surface reflectivity of the south residual cap

# 2 of Mars

- 3 Mouginot J.<sup>1</sup>, (jeremie.mouginot@obs.ujf-grenoble.fr)
- 4 Kofman W.<sup>1</sup>, (wlodek.kofman@obs.ujf-grenoble.fr)
- 5 Safaeinili A.<sup>2</sup>, (ali.safaeinili@jpl.nasa.gov)
- 6 Grima C.<sup>1</sup>, (cyril.grima@obs.ujf-grenoble.fr)
- 7 Herique A.<sup>1</sup>, (alain.herique@obs.ujf-grenoble.fr)
- 8 Plaut J. J.<sup>2</sup> (plaut@jpl.nasa.gov)
- 9
- 10
- <sup>11</sup>Laboratoire de Planétologie de Grenoble, CNRS/UJF 38041 Grenoble Cedex, France
- <sup>12</sup> <sup>2</sup>Jet Propulsion Laboratory, California Institute of Technology, Pasadena, CA 91109.
- 13
- 14
- 15
- 16
- 17
- 18
- 19
- 20 Manuscript : 13 pages
- 21 Figures : 5 pages
- 22 Tables : 1 page

#### 24 **Proposed running head:**

- 25 MARSIS surface reflectivity of the South Residual Cap.
- 26
- 27 The name and address to which editorial correspondence and proofs should be
- 28 directed:
- 29 Jeremie MOUGINOT
- 30 122 rue de la piscine
- 31 38000 Grenoble
- 32 FRANCE
- 33 Jeremie.mouginot@obs.ujf-grenoble.fr

#### 35 (Abstract)

The south residual cap of Mars is commonly described as a thin and bright layer of CO<sub>2</sub>-ice. The Mars Advanced Radar for Subsurface and Ionospheric Sounding (MARSIS) is a low-frequency radar on board Mars Express operating at the wavelength between 55 and 230 m in vacuum. The reflection of the radar wave on a stratified medium like the residual cap can generate interferences, causing weaker surface reflections compared to reflections from a pure water ice surface.

42 In order to understand this anomalous low reflectivity, we propose a stratified 43 medium model, which allows us to estimate both the thickness and the dielectric 44 constant of the optically thin slab. First, we consider the residual cap as single unit 45 and show that the decrease in the reflected echo strength is well explained by a mean 46 thickness of 11 m and a mean dielectric constant of 2.2. This value of dielectric 47 constant is close to the experimental value 2.12 for pure  $CO_2$ -ice. Second, we study 48 the spatial variability of the radar surface reflectivity. We observe that the reflectivity 49 is not homogeneous over the residual cap. This heterogeneity can be modeled either 50 by variable thickness or variable dielectric constant. The surface reflectivity shows 51 that two different units comprise the residual cap, one central unit with high reflectivity and surrounding, less reflective units. 52

53 KEYWORD: RADAR OBSERVATIONS, MARS, POLAR CAPS, ICES

#### 54

#### 55 **1. Introduction**

56

#### 57 **1.1. South residual cap**

58

59 The south polar plateau of Mars is partially covered by a perennial thin layer of 60 carbon dioxide  $(CO_2)$  ice, which is easily visible from Earth and spacecraft due to its 61 high albedo compared to the surrounding regions. Astronomers have observed this 62 layer over a century [Flammarion 1892], but the composition (CO<sub>2</sub>-ice) was 63 determined using Viking orbiter thermal data [Kieffer, 1979; Paige et al. 1990]. It has 64 been shown that this  $CO_2$  layer directly lies above water ice (H<sub>2</sub>O-ice), which 65 comprises the major part of the plateau [Plaut et al. 2007] in the form of South Polar 66 Layered Deposits (SPLD).

Thermal data from Thermal Emission Imaging System (THEMIS) revealed the presence of small exposures of  $H_2O$ -ice adjacent to the  $CO_2$ -ice, based on temperature signatures [Titus *et al.* 2003]. The Observatoire pour la Minéralogie, l'Eau, les Glaces, et l'Activité (OMEGA) observed spectral signatures of both  $CO_2$ -ice and trace amounts of  $H_2O$ -ice within the residual ice cap [Bibring *et al.* 2004, Douté *et al.* 2007]. OMEGA also confirmed the identification of  $H_2O$ -ice-rich surfaces near the CO<sub>2</sub>-ice cap

The perennial  $CO_2$  deposit consists of numerous layers. Using Mars Global Surveyor Mars Orbiter Camera (MOC) images, Thomas *et al.* [2005] showed that the south residual cap consists of two distinct layered units, which were deposited at different

0/	
88	MARSIS is a decameter-wave sounding radar, which can penetrate kilometers below
89	the icy surface. It has provided important results on the Martian subsurface [Picardi et
90	al. 2005; Plaut et al. 2007; Watters et al. 2007] and ionosphere [Gurnett et al. 2005;
91	Duru et al. 2006; Safaeinili et al. 2007; Espley et al. 2007]. The radar uses four
92	frequency bands, which are centered at 1.8, 3, 4 and 5 MHz (166, 100, 75, and 60 m
93	wavelength). Each band has a width of 1 MHz.
94	The data have been corrected for the distortion (phase shift) [Safaeinili et al. 2003;
95	Mouginot et al. 2008a] and absorption [Mouginot et al. 2008b] due to the ionosphere.
96	The radar frequency is close to the plasma frequency (up to4 MHz) of the ionosphere
97	[Nagy et al. 2004; Gurnett et al. 2005] and as a result the signal is broadened
98	significantly in addition to being delayed. This broadening of the pulses can cause
99	smearing of the resulting radargram. Correction for ionospheric effects is performed
100	to re-sharpen the pulses and compensate for the absorption effects as described in
101	Mouginot et al. [2008a].

times, separated by a period of degradation. The older unit, about 10 m thick, has
layers approximately 2 m thick. The younger unit has variable numbers of layers,
each about 1 m thick.

An estimate of the quantity of  $CO_2$  in the slab, which can be compared to the total CO<sub>2</sub> content of the atmosphere, was made by Byrne and Ingersoll [2003]. They showed that a CO<sub>2</sub> residual ice cap with 10 m thickness, an area of 87,000 km<sup>2</sup>, and a density of 1.6 g.cm<sup>-3</sup>, constitutes only about 5% of the average atmospheric mass.

- 84
- 85

#### 1.2. Surface Reflectivity measured by MARSIS

87

102

We quantify the echo returned by the surface from MARSIS radargrams by localizing the position in the radargram corresponding to the surface echo and measuring the amplitude. The position corresponds to the surface elevation given by Mars Orbiter Laser Altimeter (MOLA).

107 This surface echo amplitude (i.e., surface reflectivity) allows us to build reflectivity 108 maps in each MARSIS frequency band (map at 4 MHz in Fig. 1a; maps at other 109 frequencies show the same type of features). The map resolution is 14.7 km per pixel 110 (about the MARSIS footprint width). For bands centered at 3, 4 and 5 MHz, we used 111 305, 464 and 539 orbits, respectively, to construct reflectivity maps. For crossing 112 tracks, we average the data from multiple measurements from MARSIS is a nadir-113 looking radar and the Mars Express polar orbit does not allow us to sound the surface 114 poleward of about 87°N and 87°S; this lack of data results in a gap centered at the 115 pole.

To first order, the reflectivity is inversely correlated with the surface roughness, because the power reflected by a surface at nadir decreases with its roughness. Thus the topographic variations at lateral scales comparable to and/or larger than the MARSIS wavelength are affecting the signal. This is normal behavior due to the loss of coherency of the radar signal.

121 A simulator of returned radar echoes from Mars was developed by Nouvel et al. 122 [2004]. This computationally efficient radar signal simulation is based on the use of 123 the Facet Method as surface modeling scheme. The slope and the large-scale 124 roughness effects are simulated using MOLA topography to predict the surface echo 125 amplitude in each point [Nouvel et al. 2004]. In this simulation, the reflectivity

variability is only due to surface slopes, with an assumption of a single fixed surfacedielectric constant. It allows distinguishing dielectric and topographic effects.

For each MARSIS radargram, we generate the corresponding radar simulation and extract the surface amplitude from simulated radargrams to obtain a simulated reflectivity map (Fig. 1b). We use identical procedures to generate both the simulated map and the data map (Fig. 1a).

132 With such a simulated map, we can correct for any reflectivity variations that are due 133 to topographic effects. Indeed, the reflection coefficient (backscattering coefficient) R134 can be written as the product of a dielectric constant function and a roughness 135 function [Ulaby et al. 1986], which is independent of the dielectric constant. By 136 normalizing the reflectivity map by the simulated one, we obtain a map proportional 137 to the dielectric constant (Fig. 1c). This normalization consists of the difference of the 138 power logarithms between data and simulated map. This normalized map reveals 139 variations of surface reflectivity across our area of interest. Indeed, one can see that 140 the region of the residual cap has very low reflectivity values (black box in Fig. 1c) 141 compared to the other parts of the SPLD.

142

## 143 **2. Wave propagation in a stratified medium**

We built a first order model to describe reflectivity in the south residual cap. This model allows us to compute the radar wave propagation in a stratified medium and then obtain a corresponding reflectivity.

147 Previous work indicates that the south residual cap consists of a thin perennial slab of

148  $CO_2$ -ice overlapping H<sub>2</sub>O-ice. So we model the south residual cap reflectivity using

149 three layers: the atmosphere, the  $CO_2$ -ice and the  $H_2O$ -ice (Fig. 2).

150 In a two-layer medium with refractive indices  $n_i$  and  $n_j$ , the reflection coefficient for 151 normal incidence is given by the equation:

152 
$$r_{ij} = \frac{n_j - n_i}{n_j + n_i} (1)$$

In a stratified medium (i.e., with three layers in our case), the reflection coefficient equation may be conveniently expressed in terms of the corresponding coefficients  $r_{12}$ and  $r_{23}$  associated with the reflection coefficients at the first and the second interface, respectively [Born and Wolf 1959]:

157 
$$r = \frac{r_{12} + r_{23}e^{2i\beta}}{1 + r_{12}r_{23}e^{2i\beta}} (2)$$

where  $\beta = \frac{2\pi}{\lambda} n_2 h$ , h is the thickness of the intermediate layer and  $\lambda$  is the 158 wavelength of the incident wave.  $r_{12}$ ,  $r_{23}$  may be obtained by substituting equation 1 159 with the corresponding subscripts. This notation implies that  $n_1$ ,  $n_2$  and  $n_3$  are 160 161 respectively, the refractive index for the upper (atmosphere), intermediate (CO<sub>2</sub> slab) 162 and lower ( $H_2O$ -ice) layers (see Fig. 2). This model does not include any losses in the 163 media, which, we believe, is a good approximation because for CO<sub>2</sub>- and H<sub>2</sub>O-ice 164 losses are known to be weak. In addition polar MARSIS measurements typically 165 show low losses [*Plaut et al., 2007*]. The refractive index  $n_i$  corresponds to the square root of the real part of dielectric constant:  $n_i = \sqrt{\varepsilon_i}$ . 166

167

As the MARSIS radar signal has a bandwidth of 1 MHz and therefore is not
monochromatic, we cannot limit ourselves to equation 2 to obtain the reflectivity.
Instead, we have to calculate the reflectivity as:

171 
$$R = \max\left(\left\|\operatorname{IFFT}(S(f)r(f)S^*(f)\|^2\right)(3)\right)$$

where f is the frequency, r is the reflection coefficient defined in equation 2 and S is the linearly modulated chirp signal of MARSIS. Equation 3 describes our method to model the amplitude of the surface echo: we apply to an ideal transmitted signal (chirp) the reflection coefficient r(f). The Inverse Fast Fourier Transform (IFFT) gives a time dependent signal that corresponds to the output of the matched filter of the receiver.

178 In our model, we describe the  $H_2O$ -ice as compact pure water ice, which corresponds 179 to a dielectric constant  $\varepsilon_3$  equal to 3.15. This value of pure water ice for the dielectric 180 constant is probably a good assumption, as previous workers have shown that the 181 deposits of the south polar-layered deposits are composed of relatively clean water ice 182 [Plaut et al. 2007; Zuber et al. 2007]. Moreover laboratory experiments have shown 183 that the real component varies between 3.14 and 3.19 [Ulaby et al. 1986] for various 184 types of "dirty ices". In case of porous ice, the dielectric constant decreases. For 185 example, if the porosity of ice were equal to 10%, then, using Maxwell Garnett 186 mixing formulas [Sihvola, 1999], the dielectric constant would be 2.87. The dielectric 187 constant of the atmosphere is set to 1.

Fig. 3 presents the model of reflectivity *R* as function of the CO<sub>2</sub> thickness, *h*, for different values of CO<sub>2</sub> dielectric constant. The two free parameters in our model are *h* and the dielectric constant of the central layer  $\varepsilon_2$  (the CO<sub>2</sub>-ice). Both have an impact on the inferred reflectivity. The CO<sub>2</sub> thickness in the plot is limited to the 0-20 m range because previous studies have shown that the global thickness is around 10 m.

First, we see on Fig. 3 that the reflectivity is minimal for a layer whose optical thickness  $n_2h$  is close to  $\lambda_0/4$  ( $\lambda_0$  is the central wavelength) and the reflectivity is maximal when optical thickness is close to  $\lambda_0/2$  (Born and Wolf 1979).

197 Second, the reflectivity is minimum or strictly equal to zero when the dielectric 198 constant of the intermediate layer is equal to  $\sqrt{n_1 n_3}$ . In our case, this corresponds with 199 a dielectric constant of  $\varepsilon_2 \approx 1.77$ .

200

#### 3. Data Analysis

#### 201 **1.3.** Comparison to $H_2O$ -ice

As the reflectivity measured by MARSIS is not absolutely calibrated, we have to compare the reflectivity in the south residual cap to a reference region of known composition.

We have chosen a reference region in the SPLD around the position 82°S and 150°W in a 2° by 2° box. It was chosen because of its flatness, so that we can expect that the only parameter that plays a role on the reflectivity is the dielectric constant. We know that the radar waves in the region are reflected by pure water ice, overlain by an optically thin soil layer [*Plaut et al. 2007*]. In this case, the reflection coefficient of the reference region is estimated as  $r_{air/H_2O-ice} = 0.279$  with  $\varepsilon_{H_2O-ice} = 3.15$  (see

equation 1), which corresponds to a reflectivity  $R = |r_{air/H_2O-ice}|^2 = 0.078$ .

In our modeling effort, we consider the south residual cap according to the geological unit defined by Skinner *et al.* [2006] in the Mars geologic maps. MARSIS measurements cover about 60% of the 87,000 km<sup>2</sup> the south residual cap (to 87°S). We select all MARSIS reflectivity measurements that are either within the south residual cap or in the reference region. We obtain a distribution (see Fig. 4) of the reflectivity for both regions and for each of the three MARSIS frequency bands. The band 1 centered at 1.8 MHz is not used because of the low amount of data.

In order to find the most probable reflectivity values that characterize each region, we fit this distribution by a Gaussian function. Best-fit parameters are summarized in Table 1. Results show that for all frequencies, the reflectivity is much lower in the south residual cap than in the reference region.

In order to find the best values for model parameters ( $\varepsilon$ , thickness) that reproduce the observations, we use the model described previously. We fix a range for these parameters, which are from 0 to 20 m for the thickness and from 1.0 to 3.15 for the dielectric constant. The limits for the dielectric constant are the dielectric constant of the upper and lower media (i.e. respectively the atmosphere and the water ice). The procedure consists of a minimization between the model of reflectivity in a stratified medium and the MARSIS measurements for all frequency bands simultaneously.

Application of this procedure gives the best value in our model of a mean thickness of 11 m and a mean dielectric constant of 2.3. This  $CO_2$  dielectric constant is close to the value measured by Pettineli *et al.* [2003] of 2.12. It confirms that the thin bright slab in the south residual cap is primarily  $CO_2$ -ice. The formal 1-sigma errors on each parameter, computed from the covariance matrix in the minimization, are 1 m for the thickness and 0.2 for the dielectric constant.

236

#### 237 **1.4. Local Study**

In this section, we are not considering the south residual cap as a single unit, but we try to evaluate, locally, (with a resolution of about 14.7 km) the properties of the  $CO_2$ slab. One can see in Fig. 1c that there is a large variability of reflectivity in the residual cap.

242 Within our model representation, these variations can be explained as a change in 243 thickness or change in the dielectric constant. In the previous section, we use all the 244 data in the residual cap and so the statistics are robust. This allows us to easily extract 245 the mean behavior. However, in the local study, the statistics for each bin are poor and 246 it is difficult to invert the two parameters at the same time because they play a similar 247 role in reducing the reflectivity of the surface. Alternatively, we can fix one parameter 248 and solve for the other one. Thus for each pixel, we try to describe the reflectivity 249 variation as a change in dielectric constant only, or as a change in CO<sub>2</sub>-ice thickness 250 only.

#### **1.1.1. Spatial Variability of the dielectric constant?**

252 First, we fix the thickness at 10 meters and look at the changes in the dielectric 253 constant due to variation of the reflectivity. The resulting dielectric map is shown in 254 Fig. 5a. One can see that the low reflectivity regions (Fig. 1c) correspond to areas 255 where the dielectric constant is close to the value of pure CO<sub>2</sub>-ice (2.12) [Pettineli et 256 al. 2003]. The central part of the residual cap corresponds to higher values of the 257 dielectric constant, between the  $CO_2$ -ice (2.12) and H<sub>2</sub>O-ice (3.15) reflectivity values, 258 which means in this case a mixture between H<sub>2</sub>O-ice and CO<sub>2</sub>-ice. This mixture could 259 be intimate (at the grain size level) or, because MARSIS has a large footprint,  $CO_2$ 260 residual cap and water outcrop reflectivity can be mixed in the returned signal. Using 261 the Maxwell Garnett mixing formula [Sihvola, 1999] and supposing that the effective 262 dielectric constant is only due a mixing between  $H_2O$ - and  $CO_2$ -ice, we obtain the 263 percentage of  $CO_2$ -ice compared to  $H_2O$ -ice. Fig. 5a shows that the ice content in the 264 central part could be up to 50% of  $H_2O$ , whereas surrounding terrains would contain 265 less than 20%.

#### 266 **1.1.2. Spatial Variability of the thickness?**

Next, we fix the  $CO_2$  dielectric constant at 2.12 and estimate the thickness with our model. This  $CO_2$  dielectric constant is close to the previously found value and corresponds to the value measured by Pettineli *et al.* 2003.

Fig. 5b shows the CO<sub>2</sub> thickness computed by our reflectivity model. In this hypothesis, we observe on the Fig. 4b two types of terrains: terrains with relatively low thickness in the central part (less than 6-7m thick) and higher thickness in the surrounding terrains (about 12 m thick). As it is difficult to measure a 1 dB decrease, thicknesses under 4 m cannot be extracted from our analysis.

275

#### **4. Discussion**

#### 277 **1.5.** *Errors*

278 In this section, we discuss possible errors in our method.

279 In the first part of the analysis, where we study the general reflectivity of the residual

280 cap, we make an assumption of the constant dielectric of the reference region. For

example, if there is a porosity in the shallow subsurface of the ice sheet, the dielectric

constant of the reference would decrease and so the reflectivity. For 10% porosity,

283  $\varepsilon_{H_{2}O-ice}$  would be 2.87 and the corresponding reflectivity would be R = 0.066. A

porosity of 10% in water ice would thus reduce the reflectivity less than 1 dB.

Our model assumes no porosity for water ice (i.e.  $\varepsilon_{H_2O-ice} = 3.15$ ) and we think that the assumption does not have a significant effect on our results. Our model is not particularly sensitive to this parameter. For the 10%-porosity case, the output values of the model would be still 11 m for the thickness and 2.2 for the dielectric constant of

the CO2. This change is inside the uncertainties given by the 1-sigma errors on eachparameter.

In the second part, where we study the spatial variability in the south residual cap, we cannot exclude that the effect of roughness at about tens of meters scale could explain the reflectivity variability. However we think that the geologic features in the residual cap (depressions of few meters) are small compared to the MARSIS wavelength and are not responsible for the decrease in reflectivity.

296

297

#### 298 **1.6.** Conclusions

299

The multi-layered reflection model proposed in this paper allows us to estimate a  $CO_2$ slab thickness for a portion of the south residual cap of Mars. The mean  $CO_2$ thickness measured by MARSIS seems to be in agreement with the thickness estimated by Thomas *et al.* 2005.

304 It is interesting to note that the reflectivity detected by MARSIS is not homogenous 305 across the residual cap. Indeed we observe that the central part of the residual cap has 306 higher reflectivity than surrounding areas.

We have proposed an interpretation of this heterogeneity in terms of dielectricconstant and thickness of the CO<sub>2</sub>-ice slab.

309 Firstly, supposing that the thickness is constant across the residual cap and solving for

310 dielectric variations, we would conclude that the central part is a mixture of  $CO_2$  and

 $H_2O$  ices, and the surrounding terrains are mainly pure CO2-ice.

312

313 Alternatively, supposing that the residual cap composition is homogeneously pure

314 CO2-ice and solving for thickness variations, it appears that the central terrains are 315 thinner that the surrounding terrains. In this case, the volume of CO<sub>2</sub>-ice contained in the mapped part of the residual cap is about  $4.1 \times 10^{11}$  m<sup>3</sup>. As MARSIS measurements 316 cover 60% of the residual cap, we can estimate that the total volume  $6.85 \times 10^{11} \text{ m}^3$ , 317 318 which corresponds to about 5% (0.27 mbar) of atmospheric surface pressure (5.6 319 mbar) if we assume that the  $CO_{2}$ -ice density is about 1.6 g.cm<sup>3</sup>. This estimation is 320 consistent with previous works that predict that the amount of CO2 in the residual cap 321 is small compared to the mass of the atmosphere [Prettyman et al. 2004; Byrne and 322 Ingersoll, 2003]. 323 In both cases, our model shows that the central part of the mapped portion of the 324 residual cap, which shows lower surface reflectivity, contains less CO<sub>2</sub>-ice than the 325 surrounding parts of the residual cap. 326 A similar analysis could be conducted with the SHAllow subsurface RADar 327 (SHARAD), which operates at 20 MHz (i.e., a wavelength of 15 m in vacuum). The 328 SHARAD horizontal resolution is 300 m, which would allow description of the 329 surface features at a better resolution. SHARAD may also be sensitive to the seasonal 330  $CO_2$  deposits when the thickness is 1-2 m as described by Nunes and Phillips 2006., 331 although this study is probably more difficult because SHARAD is more sensitive to 332 meter-scale roughness.

333

# 334 Acknowledgments

335

336	The authors acknowledge the French space agency (CNES) for support of these
337	studies in Laboratoire de Planétologie de Grenoble. Operations of the Mars Express
338	spacecraft by the European Space Agency (ESA) are gratefully acknowledged. Lynn
339	Carter and an anonymous reviewer provided helpful suggestions for this paper.

340

#### 341 **References**

342

- 343 Bibring, J., and 13 colleagues, 2004. Perennial water ice identified in the south polar
- 344 cap of Mars , Nature 428, 627-630.
- 345
- Born M. and Wolf E., 1979. Principles of Optics: Electromagnetic theory of
  propagation, interference and diffraction of light, Cambridge Univ. Press, Cambridge,
  UK.

349

- Byrne, S. and Ingersoll, A. P., 2003. A Sublimation Model for Martian South Polar
  Ice Features, Science 299, 1051-1053.
- 352
- Douté, S. Schmitt, B., Langevin, Y., Bibring, J.-P., Altieri, F., Bellucci, G., Gondet,
  B., Poulet, F. & the MEX OMEGA team, 2007. South Pole of Mars: Nature and
  composition of the icy terrains from Mars Express OMEGA observations, Planetary
  And Space Science 55, 113-133.

- Duru, F.; Gurnett, D. A.; Averkamp, T. F.; Kirchner, D. L.; Huff, R. L.; Persoon, A.
  M.; Plaut, J. J. & Picardi, G., 2006. Magnetically controlled structures in the
  ionosphere of Mars, J. Geophys. Res. 111, A12204.
- 361
- 362 Espley, J. R., Farrell, W. M., Brain, D. A., Morgan, D. D., Cantor, B., Plaut, J. J.,
- 363 Acuña, M. H., Picardi, G., 2007. Absorption of MARSIS radar signals: Solar
- 364 energetic particles and the daytime ionosphere, Geoph. Res. Let. 34, 9101-+.
- 365

2	6	6
Э	υ	υ

Flammarion, C., 1892. La planète mars et ses conditions d'habitabilité, v. 1.
Gauthier–Villars et Fils, Paris.

369

- 370 Gurnett, D.A. and 11 colleagues, 2005. Radar soundings of the ionosphere of Mars,
- 371 Science 310, 1929–1933.

372

- 373 Kieffer, H.H., 1979. Mars south polar spring and summer temperatures: a residual
- 374 CO2 frost, J. Geophys. Res. 84, 8263–8288.

375

Mouginot, J.; Kofman, W.; Safaeinili, A.; Herique, 2008a. A Correction of the
ionospheric distortion on the MARSIS surface sounding echoes, Planetary and Space
Science 56, 917-926.

379

380 Mouginot, J.; Kofman, W.; Safaeinili, A.; Herique, A.; Plaut, J. J.; Picardi, G., 2008b.

381 Calibration of MARSIS Surface Echoes LPSC XXXIX, No. 1391, p. 1716

382

383 Nouvel, J. F.; Herique, A.; Kofman, W., Safaeinili, A., 2004. A. Radar signal

384 simulation: Surface modeling with the Facet Method, Radio Science 39, RS1013.

385

Nunes, D. C., Phillips, R. J., 2006. Radar Subsurface Mapping of the Polar Layered
Deposits on Mars J. Geophys. Res. 111, 6+-.

388

Paige, D., Herkenhoff, K., Murray, B., 1990. Mariner 9 observations of the south
polar cap of Mars: evidence for residual CO2 frost. J. Geophys. Res. 95, 1319–1335.

391	
392	Pettinelli, E.; Vannaroni, G.; Cereti, A.; Paolucci, F.; Della Monica, G.; Storini, M. &
393	Bella, F., 2003. Frequency and time domain permittivity measurements on solid $CO_2$
394	and solid CO <sub>2</sub> -soil mixtures as Martian soil simulants, J. Geophys. Res. 108, 10-+
395	
396	Picardi, G. and 12 colleagues, 2004. Performance and surface scattering models for
397	the Mars Advanced Radar for Subsurface and Ionosphere Sounding (MARSIS)
398	Planet. and Space Science 52, 149-156.
399	
400	Plaut, J. J.and 23 colleagues, 2007. Subsurface Radar Sounding of the South Polar
401	Layered Deposits of Mars, Science 316, 92
402	
403	Prettyman, T. H. and 12 colleagues, 2004. Composition and structure of the Martian
404	surface at high southern latitudes from neutron spectroscopy, J. Geophys. Res. 109,
405	5001-+
406	
407	Safaeinili, A.; Kofman, W.; Nouvel, J.; Herique, A., Jordan, R. L., 2003. Impact of
408	Mars ionosphere on orbital radar sounder operation and data processing, Planetary
409	and Space Science 51, 505-515.
410	
411	Safaeinili, A.; Kofman, W.; Mouginot, J.; Gim, Y.; Herique, A.; Ivanov, A. B.; Plaut,
412	J. J., Picardi, G., 2007. Estimation of the total electron content of the Martian

ionosphere using radar sounder surface echoes, Geophysical Reseach Letters 34,

- 414 23204-+.
- 415

- 416 Skinner, J.A., Jr., Hare, T.M., Tanaka, K.L., 2006, Digital Renovation of the Atlas of
- 417 Mars 1:15,000,000-Scale Global Geologic Series Maps, LPSC XXXVII, abstract
  418 #2331
- 419
- 420 Sihvola A., 1999. Electromagnetic mixing formulas and applications, IEE

421 Electromagnetic waves series 47, The institution of Electrical Engineers.

422

- 423 Ulaby, F.T., Moore, R.K., Fung, A.K., 1986. Microwave Remote Sensing Active and
- 424 Passive, Artech House, Volume II.

425

- 426 Watters, T. R. and 12 colleagues, 2007. Radar Sounding of the Medusae Fossae
- 427 Formation Mars: Equatorial Ice or Dry, Low-Density Deposits?
  428 Science, 318, 1025.

- 430 Zuber, M. T.; Phillips, R. J.; Andrews-Hanna, J. C.; Asmar, S. W.; Konopliv, A. S.;
- 431 Lemoine, F. G.; Plaut, J. J.; Smith, D. E. & Smrekar, S. E., 2007. Density of Mars
- 432 South Polar Layered Deposits, Science 317, 1718-.

#### 433 **Tables**

434

Center of the Gaussian	3 MHz	4 MHz	5 MHz
South residual cap	-13.1	-14.1	-15.5
Surface reference [H <sub>2</sub> O-ice]	-7.5	-8.5	-8.3
Reflectivity decrease	5.6	5.5	7.2

435

## 436 **Table Captions**

437

438 Table 1: The table summarizes the result of the Gaussian fit made on the distribution

439 presented in Fig. 4. The two first lines show the reflectivity (in dB) of the central

440 position of the Gaussian (for the residual cap and for the reference region,

441 respectively). The last line corresponds to the difference (in dB) between reference

442 and residual cap.

443

#### 444 **Figure Captions**

445

446 Fig. 1: (a) Surface reflectivity map from MARSIS using the radar frequency centered 447 at 4 MHz. The projection is polar stereographic. The reflectivity is represented in 448 decibel scale. (b) Simulated reflectivity map using MOLA topography. The 449 simulation is performed with a constant  $\mathcal{E}_{surface}$ . (c) Surface reflectivity map at 4 MHz 450 normalized by the simulated reflectivity map. (d) Mars Orbiter Camera (MOC) wide-451 angle mosaic map of the south polar region of Mars. The map resolution is about 14.7 452 km per pixel. 453 454

454 Fig. 2: Schematic view of a vertical ground section of the south residual cap, as455 described in our model.

456

Fig. 3: Reflectivity *R* of the layered surface (see Fig. 2) as a function of the thickness *h* for different values of the dielectric constant  $\varepsilon_{CO_2}$ . The dielectric constants of the upper and lower medium are 1 and 3.15, respectively.

460

461 Fig. 4: The distribution of surface reflectivity in the reference region (dark grey) and
462 the south residual cap (light grey). The black dashed lines are the Gaussian fit made
463 on the distribution. The results of the fit are summarized in Table 1.

464

Fig. 5: Maps of the south residual cap region. (a) Map of the dielectric constant found
by our reflectivity model with the thickness fixed at 10 meters. Using the Maxwell
Garnett mixing formula [Sihvola, 1999] and assuming that the effective dielectric

- 468 constant is only due to mixing between H<sub>2</sub>O- and CO<sub>2</sub>-ice, we give the percentage of
- 469 CO<sub>2</sub>-ice and H2O-ice. (b) Map of the  $CO_2$  thickness found by our model with
- 470 dielectric constant fixed at 2.12.
- 471

15

10

5

0



Simulated surface reflectivity (b)



MOC mosaic map (d)











Count

