

Fate of the fusarium mycotoxins fumonisins B1, B2 and B3, deoxynivalenol and zearalenone in maize flour and maize grits during extrusion cooking.

Keith Scudamore, Robin C, E Guy, Brian Kelleher, Susan Macdonald

► To cite this version:


Keith Scudamore, Robin C, E Guy, Brian Kelleher, Susan Macdonald. Fate of the fusarium mycotoxins fumonisins B1, B2 and B3, deoxynivalenol and zearalenone in maize flour and maize grits during extrusion cooking.. Food Additives and Contaminants, 2008, 25 (11), pp.1374-1384. 10.1080/02652030802136188 . hal-00577399

HAL Id: hal-00577399 https://hal.science/hal-00577399

Submitted on 17 Mar 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Food Additives and Contaminants



Fate of the fusarium mycotoxins fumonisins B1, B2 and B3, deoxynivalenol and zearalenone in maize flour and maize grits during extrusion cooking.

Journal:	Food Additives and Contaminants
Manuscript ID:	TFAC-2007-429.R1
Manuscript Type:	Original Research Paper
Date Submitted by the Author:	14-Apr-2008
Complete List of Authors:	Scudamore, Keith; KAS Mycotoxins Guy, Robin; Campden Food RA Kelleher, Brian; CSL MacDonald, Susan; CSL
Methods/Techniques:	Chromatographic analysis
Additives/Contaminants:	Mycotoxins - fumonisins, Mycotoxins - fusarium, Mycotoxins - trichothecenes, Mycotoxins - zearalenone
Food Types:	Cereals and grain, Processed foods, Snack products



http://mc.manuscriptcentral.com/tfac Email: fac@tandf.co.uk

Fate of the *fusarium* mycotoxins fumonisins B_1 , B_2 and B_3 , deoxynivalenol and zearalenone in maize flour and maize grits during extrusion cooking.

KEITH A. SCUDAMORE¹, ROBIN C. E. GUY², BRIAN KELLEHER³, & SUSAN J. MACDONALD³

¹KAS Mycotoxins, 6 Fern Drive, Taplow, Maidenhead SL6 0JS, UK; ²Campden and Chorleywood Food Research Association, Chipping Campden, GL55 6LD, UK; ³Central Science Laboratory, Sand Hutton, York, YO41 1LZ

Abstract

Extrusion technology is used widely to manufacture a range of breakfast cereals and snacks for human consumption and animal feeds. Deoxynivalenol (DON) and zearalenone (ZON) in cereals and cereal products and fumonisins B₁ and B₂ (FB₁ and FB₂) in maize are controlled in the European Union by legislation with the objective of minimising consumer exposure to these mycotoxins. Relatively few studies have examined the losses of *fusarium* mycotoxins during processing. The behaviour of FB₁, FB₂ and fumonisin B₃ (FB₃), DON and ZON during extrusion of naturally contaminated maize flour and maize grits has been examined here using pilot scale equipment. Studies of these ingredients show that DON and ZON are mostly stable during extrusion cooking and that the fumonisins are lost to varying degrees. There does however appear to be some loss of ZON when present in low concentration and extruded at higher moistures. The presence of additives such as reducing sugars and sodium chloride can also affect mycotoxin levels. Moisture content of the cereal feed

during extrusion is an important factor and has a greater effect than temperature, particularly on the loss of fumonisins at the lower moistures. The effects appear complex and not always easy to explain although more energy input to the extruder is required for drier materials. However, on the basis of these studies, the relationship between the concentration of *fusarium* toxins in the raw product and the finished product vary depending on the toxin present and the process undertaken.

Keywords: Fumonisins, deoxynivalenol, zearalenone, fusarium mycotoxins, maize, flour, grits, processing, extrusion

Introduction

Extrusion cooking technologies are used to manufacture many forms of foodstuff from cereals and other ingredients. The range of products includes breakfast cereals, snack foods, pregels (modified starches used in food products) and breading crumbs and also animal feeds. Ingredients such as maize flour and grits, wheat flour and other food components are passed through an extrusion cooker under pressure, mechanical shearing stresses and elevated temperature, and expand rapidly as they are forced through the outlet die (Riaz 2000, Guy 2001). During this process, mechanical energy is transformed into heat by viscous dissipation in the starch paste. This causes chemical bonds in the polymers to break and free radicals to form. Mycotoxins are naturally occurring contaminants and compounds such as FB1, FB2 and FB3, DON and ZON are subjected both to high temperatures and pressures and to chemical reactions by free radical and other mechanisms and might thus be susceptible to breakdown or interaction with other components in the mixture. Temperatures inside

Food Additives and Contaminants

the barrel of an extruder can range from 100°C to 200°C and moisture content can be used from 13 % to 30 % depending on the characteristics of the end product required.

Extrudates can be designed with different physical properties and characteristics ranging from highly expanded products, which are used without further processing, to high-density pellets that are subsequently fried in oil for a very short time during which they expand rapidly. Extrudates are used as the basis for a wide range of retail products

Results reported in the literature are limited and sometimes conflicting but this may be because all the conditions used are either not reported or not carefully controlled. For example, if chemical breakdown occurs during the extrusion process the extent of any loss will be related to time, so that the reduction in mycotoxin content will depend on the residence time of the material in the extruder, in turn dependant on the material feed rate. The presence of minor ingredients, or additives, may also have a significant effect (Accerbi et al. 1999). When sugars such as fructose and glucose are present in corn-based foods they may react with the amino group of FB₁ during cooking to form the N-(deoxy-D-fructos-yl-) FB₁ (Lu et al. 1997; Howard et al. 1998). These details are often missing from reports.

Extrusion cooking has been shown to have variable effects on mycotoxins and this has been reviewed recently (Castells et al. 2005, Scudamore et al. 2007). Approximately 15 % of aflatoxins B_1 and B_2 survived extrusion at 150°C when spiked corn dough was treated (Martinez and Monsalve, 1989). However, in a study by Cazzaniga, et al. (2001) in which the effects of flour moisture content, temperature and addition of sodium metabisulphite were examined, the reduction of aflatoxin B_1 was only between 10 and 25 % for samples of corn flour experimentally contaminated with aflatoxin B_1 at 50 µg kg⁻¹. Some loss of ochratoxin A, a mycotoxin formed in grain after harvest, was found during pilot scale extrusion, although loss below 150°C was relatively small (Scudamore et al. 2004). Saunders et al. (2001) showed that extrusion of dry-milled maize products reduced fumonisin concentrations by 30–90 % for mixing type extruders and by 20–50 % for non-mixing extruders. Katta et al. (1998) examined the extrusion of corn grits on the stability of FB₁ using different temperatures and screw speeds. Both the barrel temperature and screw speed affected the loss of fumonisin in the extruded product with losses ranging from 34 to 95 %. However, the loss ranged from 46–76 % in those products with expansion and colour acceptable for commercial use. Wolf-Hall et al. (1999) showed DON to be quite stable in heat-treated foods when the effects of high temperature and high pressure processing of foods spiked with DON were examined.

Reports from other workers have shown that the *fusarium* mycotoxins can also degrade at high temperatures. The review by Castells et al. (2005) suggested that FB₁ was degraded with increasing temperatures from 100°C to give losses of 50 to 92 % at temperatures above 160°C. The temperatures were only approximate measures of the barrel temperatures in most cases and the effects of moisture were not separated from the frictional effects. FB₂ was degraded in a similar manner to FB₁ with high losses at 160°C and up to 100 % at 180°C. Experiments with DON were more extensive, and results complicated by the use of metabisulphite and problems with the analytical procedures.

The current study continues work by the authors examining the fate of *fusarium* mycotoxins during milling and selected food processing over a wide range of possible extrusion cooking conditions. The fate of DON, NIV and ZON in wheat flour during extrusion showed earlier that temperature and moisture were important variables for degrading mycotoxins (Scudamore et al. 2008). Here we examine the

 loss of mycotoxins from maize grits when extruded to form directly expanded products and in maize flour either directly expanded or under conditions that produce solid pellets that are then subsequently fried in oil when they rapidly expand. This study concentrates on snack food-like products (Guy 2001) made from a basic feedstock of maize grits, and maize flour.

Materials and methods

Maize grits and maize flour containing mycotoxins

Two commercial consignments identified as containing mycotoxins suitable for carrying out the current studies were obtained from UK maize mills. One consisted of 250 kg of maize grits and the other 400 kg of maize flour. The grits had been milled from Argentine maize and consisted of a product with mean particle size between 500 and 600 μ m (micron). The maize flour had been milled from French maize giving a product with approximately 70 % of the particles between 150 and 500 μ m and about 30% finer particles.

Mycotoxin concentrations found in maize grits are usually low in comparison to those in the whole maize because they are formed in the starchy endosperm of the maize seed that make up the grits on milling. Several consignments of grits from commercial mills were examined before a suitable 1 tonne consignment was found to contain more than 100 μ g kg⁻¹ DON and 250 μ g kg⁻¹ of fumonisins, but no ZON. In the same way a number of consignments of maize flour were examined before one with a relatively high level of fumonisins (~3000 μ g kg⁻¹ of FB₁ + FB₂), a low level of ZON and no DON was intercepted. Because the quantity of the naturally contaminated test materials exceeded the capacity of the blender available, each sample was divided into several lots, blended for two hours and placed in a series of polythene bags each containing about 20 kg as described previously for a study on milling and baking (Scudamore et al. 2003). The maize ingredients in these bags were individually mixed again and a series of random samples of about 250 g were taken for mycotoxin analysis for FB₁, DON and ZON. The contents of all the individual bags were finally recombined and re-mixed (in several lots) and then stored in batches of 65-70 kg for convenient handling and eventual transfer to the extruder during the study. Individual batches of maize were re-blended and sampled as necessary. After a final blending, samples from each batch of either grits or flour were analysed again for mycotoxin content to determine the values for % standard deviation (SD) of the replicate samples.

The moisture content of the grits was about 13.2 and 13.5 % for maize flour. Additional mixes were prepared to examine the effect of common food additives on mycotoxin stability. These were 2 % added salt (sodium chloride) and 2 % sugar (sucrose) added to the maize grits and 1 % or 2 % salt and 5 % and 10 % dextrose (glucose) added to the maize flour.

Extruder and processing conditions

A pilot-scale twin-screw extrusion cooker model MPF 50D (supplied by Baker Perkins, Peterborough, UK) was prepared to reproduce conditions simulating commercial manufacturing processes. Within the extruder body, an arrangement of screws comprised of small elements formed sections for conveying cereal, mixing in water to achieve the required moisture conditions, reverse pumping in a shear zone

Food Additives and Contaminants

and final high pressure pumping. The extruder was calibrated for flow rate and moisture prior to setting up each condition required for extrusion cooking.

There are a number of possible different combinations of parameters that can be examined during extrusion cooking. To reduce the number of these, the feed rate of the material was standardised to 700 g min⁻¹. except when examining pellet formation in which case it was 550 g min⁻¹. Conditions using combinations of up to 3 temperatures and 4 moisture conditions were examined. In an initial trial, the effect of screw speed was determined and this then subsequently standardised to 300 rpm so limiting the number of combinations required for study.

Each extrusion run involved a sequential change in extruder conditions, The extruder was run up to a steady state at each change over and held for 2 minutes to stabilise the extrusion before a sample was collected over 2.5 minutes thus representing about 1.5 to 2 kg of extrudate. This was allowed to cool before packing. Logging data was taken to confirm the target settings. Data were recorded (but not all shown here) for temperature, °C, feed rate, g min⁻¹, SME (specific mechanical energy), kJ kg⁻¹, pressure, MPa, extrudate moisture content, %, extrudate specific volume,

 $L kg^{-1}$.

Direct extrusion cooking

The arrangement of the screw elements for direct extrusion cooking has been given previously (Scudamore et al. 2007). There is a section of feed screws conveying the maize feedstock into a short mixing section of paddles where water is injected. A second conveying section forces the mixture into a reversing paddles section. Resistance from the reversing paddles causes the section to fill and generate a pressure via the twin start screws. This in turn generates heat and melts the crystalline structures in the starch granule so that a melt fluid forms. In the final screw section the hot fluid is sealed under pressure and the water superheated to > 140° C and as it forced through a die it returns to atmospheric pressure outside the barrel when the water vaporises rapidly with the immediate expansion of the extrudate.

In this work, the die plate contained two circular dies of 4 mm diameter and 4 mm land length. At the start of the extrusion cooking run the barrel heaters were set at $0/50/70/120/140^{\circ}$ C and adjusted to obtain a mass temperature of $140 \pm 5^{\circ}$ C in the shear zone and final pumping section. Subsequently the barrel temperature was raised in the last two sections to obtain mass temperatures of 160° C and then $180 \pm 5^{\circ}$ C. The powder feed rates and water were adjusted to the computed settings required to run at 700 ±5 g/min and moisture levels from that of the raw material up to $21 \pm 1 \%$ w/w. In an initial trial the screw speed was adjusted from 200 to 400 ± 1 rpm but subsequently standardised at 300 rpm.

Pellet extrusion cooking

A different configuration was used for extrusion cooking with pellet formation. This comprised a conveying section of feed screws leading to a water injection point and a short cooking section with reversing paddles to heat the flour to 110-120°C and to melt the crystalline structures in the starch. After this heating section, cooling was applied gradually to reduce the mass temperature to 90-95°C before extrusion through the 6mm dies. The extrudate was cut with a 4-blade knife at 1100 rpm into disc of approximately 1.5mm thickness. After drying at 60°C for 1-2h, samples (500 g) were ground for analysis. A second portion (500 g) of dried extrudate was fried in vegetable oil at 185 \pm 5°C for 20 seconds, drained and ground for analysis.

Food Additives and Contaminants

Here, die plates contained two circular dies of 6mm diameter and 4mm land length. At the start of the extrusion cooking run the barrel heaters were set at $20/90/120/50/30^{\circ}$ C and adjusted to heat and then cool the feedstock using the six sections and circulating water set at 10° C. The exit temperatures were varied from 90 ± 2 to 95 ± 2 %. The powder and water feed rates were adjusted to the computed settings on the plan to run at 550 ± 5 % g/min for 28 ± 1 % moisture w/w. The screw speed was held at 250 ± 1 rpm for all runs.

Analysis

The methods of analysis used were as described for studies on the extrusion of wholemeal wheat flour (Scudamore et al 2007) with the addition of a method for the determination of fumonisins. The methods used are UKAS (ISO 17025) accredited, inhouse validated, published in AOAC, being processed as CEN standards and follow the UK Food Standards Agency Requirements of External Contracts (Thompson and Wood, 1995). The methods for DON and ZON are summarised below. All reagents were purchased from commercial sources and were of analytical grade. Solvents were of HPLC grade. FUMONIPREP® columns, TRICHOTHECENE P columns and EASI-EXTRACT® Zearalenone columns were supplied by R-Biopharm Rhone (Glasgow, Scotland). Mycotoxin standards of DON and ZON were purchased from Sigma-Aldrich Company Ltd., Gillingham, Dorset, UK. DON and ZON were quantified prior to use by UV spectrometry, prepared 3-monthly. FB₁, FB₂ and FB₃ were obtained from PROMEC Unit, MRC Cape Town, PO Box 19070, Tygerberg 7505, Cape Town. Prior to analysis, all samples were ground to 1µm particle size in a laboratory mill and mixed for 1 hour on a Winkworth cone blender and Winkworth paddle mixer.

Fumonisins

25 g of the ground sample were extracted with 125 ml of acetonitrile:methanol:water 25:25:50 (v/v/v) by homogenising using an Ultra Turrax on slow speed for 30 seconds, to ensure the sample was mixed with the solvent, and then at high speed for 5 minutes. The sample was filtered and 10 ml of filtrate was transferred into a flask containing 40 ml of phosphate buffered saline solution (PBS). This was mixed well and then filtered through micro fibre filter paper. 10 ml of the filtered aqueous extract was transferred onto a fumonisin immunoaffinity column. The extract was passed completely through the column at a rate of about 1 drop per second under gravity. The column was washed with 10 ml of PBS and dried to remove all excess PBS by pushing approximately 5 - 10 ml of air through it. The fumonisins were eluted from the column with 1.5 ml of methanol at a rate of no more than 1 drop per second and collected in a 4 ml amber vial. The column was washed with 1.5 ml of water and added to the methanol eluate.

Automated pre-column derivatisation was carried out using ortho phthaldialdehyde (OPA) derivatisation reagent. This was prepared by dissolving 0.12 g OPA in 3 ml of methanol. 15 ml of 0.1 M disodium tetraborate solution and 150 μ l of 2-mercaptoethanol was added and the vial was capped and shaken and kept in the dark. The HPLC system transferred 50 μ l sample/standard to a clean vial, added 450 μ l OPA reagent, mixed the solutions, and then injected 50 μ l of the derivatised solution onto the HPLC column. HPLC used an automatic sample injector (Gilson 231) with dilutor (Gilson 401). A Phenomenex ODS3-Prodigy (15 cm x 4.6 mm i.d.), 5 μ m particle size, 250 A pore size HPLC column and guard column, C18 (Anachem, C752), 2.5 cm x 4.6 mm i.d. heated at 32 °C was used with a mobile phase -

Food Additives and Contaminants

methanol:0.1 M sodium dihydrogen phosphate solution (76:24, v/v) adjusted to pH 3.35 by addition of phosphoric acid. Detection was by fluorescence (Jasco FP-1520) set at excitation 335 nm and emission 440 nm.

DON and other trichothecenes

In summary, a ground sample (20 g) was extracted with 100 ml acetonitrile/water 84:16 by shaking for 2 hours on a wrist action shaker. A 5 ml aliquot of the extract was applied to a pre-washed charcoal/alumina column and 2 ml of clean-ed up extract was transferred to a vial and evaporated to dryness. The residue was derivatised to form the trichothecene -trimethyl silyl (TMS) derivatives and determined by GC/MS operating in selected ion mode, using 4 ions for confirmation. Trichothecenes detected by this method are DON, 3AcDON, 15AcDON, nivalenol, diacetoxyscirpenol, fusarenon-X, T2 toxin and HT2 toxin.

ZON

The method used was that of MacDonald et al. (2005) and is summarised here. A ground sample (25 g) was extracted with 125 ml of acetonitrile/water 75:25 by blending for 3-5 minutes and the extract was filtered. 15 ml of the extract was diluted with 85 ml of PBS. 50 ml of the diluted extract was passed through an EASI-EXTRACT ZON immunoaffinity column under gravity and the column was washed with 20 ml water. ZON was eluted under gravity with 1.5 ml of acetonitrile. 2 ml of water was added to 1 ml of eluate and mixed well. ZON was detected by HPLC. Liquid chromatography was performed on a Phenomenex ODS3-Prodigy 150 x 4.6 mm, 5 μ particle size, operated at 1 ml min⁻¹ with acetonitrile: water 55:45 as mobile phase. The excitation wavelength of the fluorescence detector was set at 274 nm and the emission wavelength was 440 nm. Sample volumes of 400 μ l were injected.

Determination, Recovery and Limit of Detection of mycotoxins

Samples were analysed in batches and each batch included a blank maize flour sample spiked with a known amount of mycotoxin to allow assessment of recovery, with 70-110 % being the acceptable range. The spiking levels were 250 μ g kg⁻¹ FB₁, 125 μ g kg⁻¹ FB₂ and FB₃, 200 μ g kg⁻¹ DON and 50 μ g kg⁻¹ ZON. The recovery and % SD for 10 replicate determinations are given in table 1

LODs were typically 4, 10 and 9 μ g kg⁻¹ for FB₁, FB₂ and FB₃ respectively (based on 3 x signal to noise of the lowest concentration calibration standard of 100/50/50 μ g kg⁻¹) while LOQ were 14, 34 and 31 μ g kg⁻¹ (based on 10 x signal to noise of the lowest concentration calibration standard), 5 μ g kg⁻¹ and 10 μ g kg⁻¹ respectively for each trichothecene and 3 and 6 μ g kg⁻¹ for ZON. For DON and ZON, the limit of detection is defined as 3 times the electronic baseline noise and the limit of determination as 6 times baseline noise. After analysis samples were retained and stored at -20°C.

Results from check trials

Acceptable results have been achieved in the FAPAS Scheme (www.fapas.co.uk/fapas.cfm) for fumonisins, DON and ZON in cereals during the period August 2000 to April 2007 and were consistently within the limits for Z scores of ± 2 considered acceptable.

Moisture content determination

The moisture content of grits, flour and each extrudate was measured by taking a 5 g sample and heating in an oven at 105°C for 16 hours.

Results and Discussion

All analytical results were corrected for recovery and all extrudates were corrected for changes in moisture.

Homogeneity of maize grits and maize flour

After initial mixing and blending the % SD between samples from individual bags of maize grits was 17.3 % for FB₁ and 8.3 % for DON using replicate pairs of samples from up to 10 bags. After further mixing prior to extrusion, the bags were re-sampled and the % SD improved to 8.8 % for FB₁ but not for DON (12.1 %). Mean concentrations of mycotoxins in the maize grits were then 274 μ g kg⁻¹ for FB₁, 66 μ g kg⁻¹ for FB₂, 22 μ g kg⁻¹ for FB₃ and 143 μ g kg⁻¹ for DON.

After thorough mixing of the maize flour, 10 pairs of random samples from the bags gave % SD values of 13.5 %, 14.3 %, 14.0 % and 14.1 % for FB₁, FB₂, FB₃ and ZON respectively. Mean concentrations were then 2009 μ g kg⁻¹ for FB₁, 409 μ g kg⁻¹ for FB₂, 285 μ g kg⁻¹ for FB₃ and 22.0 μ g kg⁻¹ for ZON. The precision of the replicate samples which is a combination of a sampling variability factor and analytical precision is quite similar to that for the analytical methods alone, table 1, so that most of the variability is probably due to the analysis and rather than inhomogeneity

In addition, in carrying out each study, a sample was taken from the feed hopper for analysis immediately before processing and compared with the corresponding extrudate sample after extrusion. This was carried out by timing the flow of material through the extruder. The result for every set of conditions examined in this work was the combined result from separate runs thus based on two replicates. The mean % SD for all the replicate pairs of results is given at the foot of each table of results. This represents the combined variability due to sample in-homogeneity and to the analysis. The values for grits and flour are mostly between 1% and 4% that compares very favourably with values usually expected from trace analysis alone at these levels, table 1. A wide range of conditions have been examined, not all of which may be used in commercial operations. Thus, in assessing the likely behaviour of mycotoxins in a particular process the manufacturer should ensure that the appropriate conditions in this study are referred to.

Maize Grits

Effect of extruder screw speed

An initial study was carried out to determine whether the screw speed of the extruder feed shaft affected the results obtained. To do this the barrel temperature was set to 160°C and moisture contents of 17 % and 21 % were used. The results obtained for FB₁ and DON are shown in table 2. Once each extrudate condition had stabilised, a sample of grits was taken from the feed hopper and the corresponding sample of extrudate as described earlier. The mean values from two separate runs are given. Extrusion of maize grits of 17 % moisture content showed that there was a loss of FB₁ that increased as screw speed increased from 200 to 400 rpm. A similar higher loss occurred at 21 % moisture content as the screw speed increased from 300 to 400 rpm. Results show that losses of the fumonisins are consistently greater at lower moistures. More energy is applied to the extrusion system under drier conditions and this may be the reason for an increased breakdown of the thermally labile fumonisins. However, there was no significant effect on DON concentrations as the screw speed was changed. These findings are consistent with the relative thermal stability of the two

Food Additives and Contaminants

compounds. As a result of this initial study, it was decided thereafter to standardise screw speed at 300 rpm and thus reduce the number of variables.

Effect of extruder temperature and maize moisture content

Table 3 shows the loss of FB₁ during direct extrusion of maize grits at different temperatures and extruder moistures. Results for FB₂ and FB₃ (not shown here) were very similar but subject to greater variability probably because their concentrations were lower. The loss of fumonisins was greater at 17 % moisture content than at 21 %. The loss also increased slightly as the temperature was raised as might be expected with a thermally labile compound although the moisture of the extruded product had a more significant effect than temperature. In contrast, temperature had little or no effect on the survival of DON suggesting it is heat stable under the conditions used. However there was a small loss under all conditions that might be due to reduced extractability during analysis or to some binding with the extrudate material. The % SD for each pair of results was between 3 and 4 % that showed that the variability in analysis and sampling was very small and that the effects shown are significant. The Specific Volume of the products (s.v) are given and this indicates how greatly the density of the products formed can change depending on the conditions of extrusion.

The presence of small amounts of certain other ingredients added to the cereal extruder feed has been shown previously to affect the stability of some mycotoxins during processing. The effect of two commonly used additives were examined here, 2 % w/w sodium chloride (salt) and 2 % w/w sucrose. These additives were each added to a separate batches of the maize grit feed and examined in separate extruder runs.

Salt

Table 4 shows the result on concentrations of FB_1 and DON of adding 2 % NaCl to the maize grits. The loss of fumonisin B_1 is less in the presence of sodium chloride at both temperatures although the overall loss is less at the higher moisture content. The reason for this is unclear but higher extraction efficiency is sometimes obtained when salt is present in analytical extraction solvent mixtures and suggests that it may be an extractability effect. Less pronounced results were obtained for DON which is less susceptible to breakdown.

Sucrose

Table 5 shows that the addition of 2 % sucrose has no effect on the levels of FB₁ or DON when compared with samples without sucrose processed under similar conditions although losses were consistently greater under the drier conditions as discussed earlier..

Maize Flour

The flour fraction from maize milling is composed of smaller particles than those comprising the grits and has a higher oil content of about 2-3 %. There are commercial processes that use both direct expansion in which the extruder operates with lower moisture content material and higher temperatures and pellet formation that is used with higher moisture extrudate (28-30 %) and lower temperatures (~100°C). The dense pellets that are formed are then fried in oil at high temperature for about 20 seconds and as a result they expand rapidly to form the end product. Both processes were examined here.

Food Additives and Contaminants

The mycotoxin concentrations in the maize flour were 2009 μ g kg⁻¹ for FB₁, 409 μ g kg⁻¹ for FB₂, 285 μ g kg⁻¹ for FB₃, 22 μ g kg⁻¹ for ZON. The DON concentration was too low to obtain quantitative results.

Direct extrusion

The losses of FB₁, FB₂ and FB₃ shown in table 6 were all >39 % under all conditions studied. Loss also increased as temperature was raised but this effect was much less than that caused by changes in moisture content. However, the effect of temperature became more marked at lower moisture contents. Each fumonisin was affected in the same way. The loss of ZON was unexpected as it is usually regarded as a very thermally stable mycotoxin and moisture content had the opposite effect when compared to the fumonisins. This is difficult to explain although the concentration of ZON was low (22 μ g kg⁻¹) and this might play a role.

Unfortunately no study of the effect on ZON in maize grits was possible in the absence of this mycotoxin from that ingredient. However, in a previous study of ZON in wholemeal wheat, a much higher concentration was present ($300 \ \mu g \ kg^{-1}$). In that study, there was a tendency for more than 100 % of ZON to be measured although this was less marked at the higher moisture contents. Limited studies of the effects of extrusion have been carried out but some loss of ZON has been reported previously (Ryu et al. 1999).

Our study with maize grits showed that the addition of sodium chloride produced higher recovery of fumonisins. Here in table 7, the addition of 1 % sodium chloride also similarly reduced the apparent loss of fumonisin under each of the conditions examined. We reported a similar result with wholemeal wheat in which the presence of added salt also reduced the levels of mycotoxin lost. Food manufacturers are under pressure to reduce salt levels in food so it is important that the effect of salt and other ingredients is noted. It was not possible to decide whether this is an analytical artefact due to better extractability or whether thermal breakdown or binding to the maize structure is reduced. This study was repeated with maize flour and the results in table 7 confirm the effect of salt. Higher values for mycotoxins are found consistently in the presence of salt.

Studies with maize grits showed that the addition of sucrose had no effect on either fumonisins or DON so that it was decided to examine whether reducing sugars affect concentrations of some mycotoxins. Table 8 shows the effect of adding 5 % and 10 % of dextrose (glucose) to maize flour under the same conditions as tested for salt. Levels of FB₁ recovered were much reduced under all conditions by the addition of only 5 % of dextrose. The higher 10 % addition further increased the loss but clearly even a small addition of reducing sugar has a significant effect. However, fumonisins are known to bind with glucose.

It was observed that extrudate expansion of grits was similar to normal snack products at 17 % moisture but denser and more like breakfast cereals at 21 % moisture.

The results for ZON, Table 8 shows that its loss does not appear to be affected by the presence of dextrose at either moisture at 180°C although there was some loss under all concentrations. However, the loss appears to be reduced by the presence of dextrose at 160°C. ZON is much less polar than DON and this may be a factor. It is difficult to explain some of the results for both of these *fusarium* mycotoxins. However, they are both relatively resistant to loss during extrusion compared with the fumonisins. The apparent increase under some conditions requires further confirmatory studies. The trend for residual ZON values to increase going from 140°C

Food Additives and Contaminants

to 180°C in table 7 is contrary what would be expected from chemical degradation. The answer to these changes may lie with the efficiency of the extraction solvent used for removing mycotoxins in the extruded materials or that bound mycotoxins are being released by the extrusion conditions- or a combination of both.

It has already been established that DON is very stable under the conditions studied but the presence of 2 % sodium chloride seems to result in an even higher survival. This may be that sodium chloride assists in the extraction, as has been noted and used in some analytical extraction procedures for several mycotoxins. This effect also seems to occur for FB₁ although the overall survival is less than for DON. There appears to be no such effect with sucrose, where the presence of 2 % does not appear to cause any significant difference under any conditions tested.

Reduction of salt content by processors in line with current requirements may apparently reduce fumonisins concentrations because recovery is affected. The extent of this will much depend on the physical properties of the extrudate. This factor needs to be examined in detail. On the other hand, the addition of sucrose under these conditions did not significantly lower fumonisin concentrations.

Extruded pellets

Conditions used to produce extruded pellets are very different from those needed for direct expansion. The moisture of the material in the extruder is about 30 % and only a little lower at the point when forced through the die. Barrel temperature was set to 110°C or 120°C but this fell to 90°C and 95°C respectively at the die face. The pellets were then dried to about 9-10 % and stored until required. In the final frying stage the pellets are dropped into hot cooking oil for a short time during which they expand

rapidly. At the same time the moisture content falls to between 2 and 4 % depending on the pellet, table 9.

The results in table 9 show that there appears to be an increase in FB₁ level during pellet formation after correction for the change in moisture content. This was the same for pellets formed at both 110°C and 120°C. However in the same samples there was more loss for ZON at the lower temperature. Throughout this study each value is the mean of 2 samples taken from different runs. The variability is small for the fumonisin results but rather larger for the lower levels of ZON. During the subsequent frying, there was a substantial reduction in FB₁, particularly in the higher temperature pellets. In contrast the loss of ZON was much less. Changes over the whole process are very similar for FB₁, FB₂ and FB₃ and this further suggests that these differences are real and not artefacts or analytical problems. The degree of expansion of the pellets from the 110°C and 120°C material is quite different giving products of specific volume of 2.1 and 3.2 respectively and this suggests that the composition of the pellets plays a significant part in determining the loss of mycotoxins.

The loss of each fumonisin from the pellet to the fried product might be due to dissolution of the mycotoxin in the frying oil. However this seems unlikely as little loss of ZON occurred during the frying. This compound is less polar and would be expected to dissolve more readily in the oil. It thus suggests that the fumonisins, but not ZON, were partially degraded in the oil.

The effect of salt was examined again in this process by adding 1 % and 2 % to the maize feed recipe. In contrast to studies on direct expansion, salt did not produce any clear effect during pellet formation although the high loss of fumonisins from the 120°C pellets was subsequently reduced during frying and for the overall

process recovery. Recoveries of ZON were also improved overall in the expanded product in the presence of salt.

Conclusions

Extrusion cooking technology is complex and can affect mycotoxin concentrations in different ways. Some factors can produce apparently opposite effects in different mycotoxins. Moisture content has been found to be a more important factor than temperature. Operation of the extruder with low moisture ingredients requires a higher energy input and tends to result in higher losses of fumonisins at all temperatures although the opposite effect has been found for ZON. Temperature alone does not appear to significantly degrade any of the fumonisins, DON or ZON under the extrusion conditions studied.

Because loss is less affected by temperature than by moisture content it seems likely that binding to cereal components and/or solvent extractability are also significant factors. Current EC legislation (EC, 2007) sets limits for FB₁ + FB₂ concentrations of 2000 μ g kg⁻¹ in flour (milling fraction with particles \leq 500 μ) or 1400 μ g kg⁻¹ (particles >500 μ) and 1000 μ g kg⁻¹ in maize-based foods for direct human consumption or 800 μ g kg⁻¹ in breakfast cereals and 200 μ g kg⁻¹ in processed maize-based foods and baby foods for infants and young children. Similar catagories apply to limits for DON and ZON (EC, 206). Thus processes using extrusion need to be carefully considered to ensure that mycotoxins in the appropriate consumer end product will meet legislative limits.

Acknowledgement

These studies were supported by the UK DEFRA Food Safety LINK Programme and UK Food Standards Agency. Maize flour and maize grits were supplied by UK maize millers Initial mixing and blending was carried by RHM Technology, High Wycombe and analysis of *fusarium* mycotoxins at the Central Science Laboratory, York, UK. Extrusion cooking was carried out at the Campden and Chorleywood Food Research Association, Chipping Campden, UK.

References

- Accerbi M, Rinaldi VEA, Ng PKW. 1999. Utilization of highly deoxynivalenolcontaminated wheat via extrusion processing. Journal of Food Protection 62: 1485–1487.
- Axford DWE, Chamberlain N, Collins TH, Elton GAH. 1963. The Chorleywood Process. Cereal Science Today 8:265–270.
- Boudra H, Le Bars P, Le Bars J. 1995. Thermostability of ochratoxin A in wheat under two moisture conditions. Applied and Environmental Microbiology 61:1156–1158.
- Castells M, Marin S, Sanchis V, Ramos AJ. 2005. Fate of mycotoxins in cereals during extrusion cooking: A review. Food Additives and Contaminants 22:150-157.
- Cazzaniga D, Basilico JC, Gonzalez RJ, Torres RL, Degreef DM. 2001. Mycotoxins inactivation by extrusion cooking of corn flour. Letters in Applied Microbiology 33:144–147.
- Chamberlain N, Collins TH, Elton GAH. 1962. The Chorleywood Bread Process. Bakers' Digest 36:52–53.

2	
3	
4	
5	
6	
7	
8	
9	
10	
11	
12	
13	
14	
10 11 12 13 14 15 16 17	
16	
17	
11	
18	
19	
20	
21	
22	
23	
24	
25	
26	
20	
27	
28	
29 30	
30	
31	
32	
33	
34	
35	
36	
37	
38	
39	
40	
41	
42	
43	
44	
45	
46	
47	
48	
49	
50	
51	
52	
53	
54	
55	
56	
57	
58	

- EUROPEAN COMMISSION, 2006, Commission Regulation (EC) No 1881/2006, of 10 December 2006 setting maximum levels for certain contaminants in foodstuffs. Official Journal of the European Union L364: 5-24.
- EUROPEAN COMMISSION, 2007, Commission Regulation (EC) No 1126/2007, of 28 September 2007 amending Regulation (EC) No 1881/2006 setting maximum levels for certain contaminants in foodstuffs as regards *Fusarium* toxins in maize and maize products. Official Journal of the European Union L255: 14-17.
- Guy RCE. 2001. Extruded snack foods. In Extrusion cooking: Technologies and applications, RCE Guy, ed. (Cambridge: Woodhead Publishing), pp.161-181.
- Katta S, Jackson L, Summer S, Hanna M, Bullerman LB. 1998. Screw speed and temperature effects on stability of fumonisin B1 (FB₁) in extrusion cooked grits. Revue du Medicine Veterinaire 149:534.
- MacDonald SJ, Anderson S, Brereton P, Wood, R. 2005. Determination of Zearalenone in Cereals and Cereal Products by Immunoaffinity Column Cleanup with Liquid Chromatography: Interlaboratory Study, Journal of the Association of Official Analytical Chemists International 88:1733-1740.
- Martinez AJ, Monsalve C. 1989. Aflatoxin occurrence in 1985–86 corn from Venezuela and its destruction by the extrusion process. Biodeterioration Research 2, edited by C. E. O'Rear and G. C. Llewellyn (New York: Plenum), pp. 251–259.
- Riaz MN. 2000. Extruders in Food Applications (Lancaster: Technomic).
- Ryu D, Hanna MA, Bullerman LB. 1999. Stability of zearalenone during extrusion of corn grits, Journal of Food Protection 62:1482-1484.
- Saunders DF, Meredith FI, Voss KA. 2001. Control of fumonisin: effects of processing. Environmental Health Perspectives 109:333–336.
- Scudamore KA, MacDonald SJ. 1998. A collaborative study of an HPLC method for the determination of ochratoxin A in wheat using immunoaffinity column clean-up. Food Additives and Contaminants 15:401–410.

- Scudamore KA, Banks JN, MacDonald SJ. 2003. The fate of ochratoxin A in the processing of whole wheat grains during milling and bread production. Food Additives and Contaminants 20:1153–1163.
- Scudamore KA, Banks JN, Guy RCE. 2004. The fate of ochratoxin A in the processing of whole wheat grains during extrusion. Food Additives and Contaminants 21:488-497.
- Scudamore KA, Guy RCE, Kelleher B, MacDonald SJ. 2008. Fate of the fusarium mycotoxins deoxynivalenol, nivalenol and zearalenone during extrusion of wholemeal wheat grain. Food Additives and Contaminants 25:331-337.

Wolf-Hall CE, Hanna MA, Bullerman LB. 1999. Stability of

deoxynivalenol in heat-treated foods. Journal of Food Protection 62:962-964.



1 2	
3	
4	
5	
6 7	
7	
8 0	
9 10	
11	
12	
13	
14	
15	
17	
18	
9 10 11 12 13 14 15 16 17 18 19	
20	
21	
22	
20 21 22 23 24 25 26	
25	
27 28 29	
28	
29	
30 31	
32	
33	
33 34 35 36 37 38 39	
35	
36	
37 38	
39	
40	
41	
42	
43	
44 45	
40	
47	
48	
49	
50	
51 52	
ว∠ 53	
54	
55	
56	
57	
58 50	
59 60	
00	

			ta (n=10) xin, μ g/kg	
Parameter	DON	ZON	FB1	FB2
Spike level	500	50	250	125
Mean recovery	104	95	104	99
RSD, %	7	16	9	7

Table 2. The effect of screw speed on FB₁ (mean concentration 274 μ g kg⁻¹) and DON (mean concentration 143 μ g kg⁻¹) in maize grits at constant feed rate and two temperatures

nperatures								
screw	mc,		FB_1			DON		
speed, rpm	%	values	mean	loss, %	values	mean	loss, %	
200	17	189	100	27.2	132	127	4.2	
200	17	209	199	27.3	142	137	4.3	
300	17	*	100	21.2	128	100	107	
300	17	189	189	31.2	128	128	10.7	
400	17	178	170	24.0	130	105		
400	17	180	179	34.8	141	135	5.5	
300	21	234	235	14.4	141	137	4.7	
300	21	235	233	14.4	132	157	4./	
400	21	217	200	22.0	125	100	10.7	
400	21	201	209	23.8	130	128	10.7	
9	6 SD		3.37	5		3.75		
outlier value exc	luded							

* outlier value excluded

http://mc.manuscriptcentral.com/tfac Email: fac@tandf.co.uk

Food Additives and Contaminants

Table 3. Effect of extruder temperature and maize moisture content on FB_1 (mean
concentration 274 $\mu g~kg^{\text{-1}})$ and DON (mean concentration 143 $\mu g~kg^{\text{-1}})during$
extrusion of maize grits

	mc	,%	sp. v		FB_1		DON		
T,⁰C	grits	ext	L kg ⁻¹	value	mean	loss, %	values	mean	loss, %
				S					
140	17	7.00	7.0	219	202	0(1	128	120	0.6
		7.88	7.60	186	203	26.1	131	130	9.6
160	17			*			128		
		7.78	9.12	189	189	31.2	128	128	10.7
180	17			177			129		
		7.70	8.21	172	174	36.5	119	124	13.4
140	21	12.4	0.51	246		11.0	146	100	
140	21	3	2.51	240	243	11.2	132	139	3.3
160	21	12.1		234			141		
160	21	8	2.24	235	235	14.4	132	136	4.8
180	21	11.9		230			134		2.9
180	21	6	3.06	236	233	233 15.1		139	
(% SD fo	or the same	mple pair	ſS	4.13			3.94	

1
2
3
4 5
5 6
7
8
9
10
12
13
14
15
16
18
$\begin{array}{c}1\\2\\3\\4\\5\\6\\7\\8\\9\\10\\1\\12\\13\\14\\15\\16\\17\\8\\9\\20\\21\\22\\3\\4\\25\\6\\7\\8\\9\\30\\1\\32\\3\\3\\4\\5\\6\\7\\8\\9\end{array}$
20
21
22
24
25
26
27
20 29
30
31
32
33 34
35
36
37
38 39
40
41
42
43 44
44 45
46
47
48 49
49 50
50 51
52
53
54 55
56
57
58
59 60

Table 4	. Effect	on F	B_1 (mean	concentration	274	μg	kg^{-1})	and	DON	(mean
concentr	ation 143	µg kg	⁻¹)concentr	ations of adding	g NaC	l to	maize	grits		

NaCl	T, ⁰C	mc, %		FB_1 , µg kg ⁻¹				ON, μg k	
		grits	Ext.	value	mean	loss,	value	mean	loss, %
0	180	17	7.70	1767	174	36.5	129	124	13.4
	180	17		172	_		119	_	
+2%	180	17	7.80	210	205	25.2	137	140	2.0
	180	-17		200	_		144	_	
0	180	21	11.9	230	233	15.1	134	139	2.9
	180	21	6	236	_		144		
+2%	180	21	12.1	231	_ 244	10.9	143	143 141	
	180	21	3	257			139		
% SI) for the	sample	pairs		3.67			4.1	4

Table 5. Effect	t on F	$^{2}B_{1}$ (mean	concentration	274	μg	kg^{-1})	and	DON	(mean
concentration 1	13 µg kg	g ⁻¹)concentra	ations of adding	g sucro	ose t	o maiz	ze gri	ts	

sucrose	T, ⁰C	mc, %		FB ₁ , µg kg ⁻¹			DON, µg kg ⁻¹		
	-	grits	ext.	value	mean	loss,	value	mean	loss, %
	180	17		177	15.	265	129	10.1	10 /
0	100	17	7.70	170	174	36.5	119	124	13.4
	180	1/		172			119		
	180	17		177			129		
+2%	100		7.26	1 = =	177	35.5		122	15.0
	180	17		177			115		
	180	21		230			134		
0			11.96		233	15.1		139	2.9
	180	21		236		-	144		
	180	21		217			131		
+2%	100	<i>4</i> 1	11.61	<u>~</u> 1/	221	19.2	1.51	135	5.8
	180	21		226			139		
01 00	for 11 -		aina C		1.6	2		= ==	,
% SD	for the sa	ampie p	airs		1.6	3		5.73)

Table 6: Reduction in FB₁, FB₂ and FB₃ (mean concentrations 2009, 409 and 285 μ g kg⁻¹ respectively) and ZON (22 μ g kg⁻¹) content during direct extrusion of maize flour at constant screw speed and feed rate

	mc, %	sp.v.	barrel		loss of m	ycotoxin, %	0
flour	extrudate	L kg ⁻¹	T., ℃	FB_1	FB ₂	FB ₃	ZON
21	10.1	4.0	140	39	46	44	54
21	9.7	5.8	160	42	46	45	45
21	8.9	6.7	180	43	45	47	42
17	7.5	7.5	140	45	48	51	46
17	6.2	8.0	160	55	56	60	40
17	5.6	8.8	180	60	57	60	23
15	5.3	8.7	140	56	55	61	40
15	5.8	8.8	160	54	52	60	34
15	4.4	9.2	180	71	68	70	16
13.5	3.2	9.5	140	75	70	74	15
13.5	3.4	8.9	160	78	73	76	21
13.5	3.2	9.0	180	85	81	85	6
% SD for the sample pairs				1.45	2.03	5.10	2.76

Food Additives and Contaminants

Table 7. Effect of NaCl on the loss of FB₁ (2009 μ g kg⁻¹) and ZON (22 μ g kg⁻¹)

content during direct extrusion of maize flour.

m	nc, %		NaC	Cl, %
flour	extrudate	Barrel T,°C	0	2
	FB_1		los	s, %
17	6.20/5.25	160	51	41
17	5.60/6.33	180	58	49
15	5.80/4.93	160	53	48
15	4.40/5.79	180	68	40
	% SD f	for the sample pairs	5	2.03
	ZON		los	s, %
17	6.20/5.25	160	40	24
17	5.60/6.33	180	23	10
15	5.80/4.93	160	34	15
15	4.40/5.79	180	16	16
	% SD f	for the sample pairs	8	1.27
_				2

Table 8. Change in FB₁ (2009 μ g kg⁻¹) and ZON (22 μ g kg⁻¹) content during direct extrusion of maize flour, effect of dextrose

m	ic, %		Dextrose, %				
flour	extrudate*	barrel T,°C	0	5	10		
	FB_1			loss, %			
17	6.20/4.57	160	51	80	88		
17	5.60/4.62	180	58	84	88		
15	5.80/4.80	160	53	87	93		
15	4.40/4.59	180	68	90	93		
	% SD for the s	ample pairs	1.45				
	ZON			loss, %			
17	6.20/4.57	160	40	23	18		
17	5.60/4.62	180	23	19	26		
15	5.80/4.80	160	34	20	18		
15	4.40/4.59	180	16	12	20		
	% SD for the s	ample pairs		3.71			
* = 0/10 %	dextrose						

Table 9. Change in FB₁, FB₂ and FB₃ (mean concentrations 2009, 409 and 285 μ g kg⁻¹ respectively) and ZON (22 μ g kg⁻¹) during pellet production and frying of maize flour and effect of NaCl.

			loss of	mycotoxir	n, %		
	NaCl,	flour:	pellet:	flour			mc, %,
Т, ℃	%	pellet	fried	:fried	flour	:fried	after
							frying,
			FB_1		FB ₂	FB ₃	
110	0	13+	22	12	11	12	4.00
120	0	13+	60	46	46	50	2.41
110	1	7+	20	14	20	12	3.73
120	1	8+	33	28	34	24	2.53
110	2	11+	25	17	31	21	3.12
120	2	0	21	21	31	25	2.89
	% SD	4	1.43 3	3.93	6		
			ZON				
110	0	31	5	34			
120	0	8	13	18			
110	1	14	10	9			
120	1	5	+1	5			
110	2	12	+3	10			
120	2	14	4	18			
	% SD	8.	84 6.	.01			

⁺ Apparent increase

http://mc.manuscriptcentral.com/tfac Email: fac@tandf.co.uk