



**HAL**  
open science

## Added mass for wave motion in density-stratified fluids

Bruno Voisin

► **To cite this version:**

Bruno Voisin. Added mass for wave motion in density-stratified fluids. 24th International Workshop on Water Waves and Floating Bodies, Apr 2009, Zelonogorsk, Russia. pp.189-192. <hal-00583073>

**HAL Id: hal-00583073**

**<https://hal.science/hal-00583073v1>**

Submitted on 4 Apr 2011

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



HAL Authorization

## Added mass for wave motion in density-stratified fluids

Bruno Voisin

LEGI, CNRS–UJF–GINP, BP 53, 38041 Grenoble, France

[bruno.voisin@hmg.inpg.fr](mailto:bruno.voisin@hmg.inpg.fr)

In a density-stratified fluid the existence of a restoring force – buoyancy – alters fundamentally the dynamics of submerged bodies. This effect can be described as a modification of their added mass. We investigate it in the simplest possible configuration – the small-amplitude motion of an unbounded Boussinesq uniformly stratified fluid – and for the simplest possible bodies – a horizontal circular cylinder in two dimensions and a sphere in three dimensions.

**General case** The concept of added mass pertains to the irrotational flow of a homogeneous fluid<sup>1</sup>. It follows from the linearity of the flow, such that the translation of a rigid body at the velocity  $\mathbf{U}$  creates a velocity potential  $\phi = \phi_i U_i$ . By defining the added mass tensor  $m_{ij}$  according to

$$m_{ij} = \rho \oint_S n_i \phi_j \, d^2S,$$

with  $\rho$  the density of the fluid,  $S$  the surface of the body and  $\mathbf{n}$  the inward normal to  $S$ , we may express the pressure force on the body as

$$F_i = \oint_S p n_i \, d^2S = -\rho \frac{d}{dt} \oint_S \phi n_i \, d^2S = -m_{ij} \frac{dU_j}{dt},$$

the impulse and (kinetic) energy of the fluid as, respectively,

$$I_i = \rho \oint_S \phi n_i \, d^2S = m_{ij} U_j, \quad E = \frac{1}{2} \rho U_i \oint_S \phi n_i \, d^2S = \frac{1}{2} m_{ij} U_i U_j,$$

and the dipole strength of the body through

$$\rho \mathcal{D}_i = \rho \oint_S \left( n_i \phi - x_i \frac{\partial \phi}{\partial n} \right) \, d^2S = (m_f \delta_{ij} + m_{ij}) U_j,$$

with  $V$  the volume of the body and  $m_f = \rho V$  the mass of the displaced fluid. Accordingly, added mass characterizes the flow fully, being involved in the dynamics of the body through  $\mathbf{F}$ , in the dynamics of the fluid as a whole through  $\mathbf{I}$  and  $E$ , and in the dynamics of the distant fluid through  $\mathcal{D}$ .

The small-amplitude Boussinesq motion of a uniformly stratified fluid of buoyancy frequency  $N$  can similarly be described<sup>2–4</sup> in terms of a scalar function  $\chi$ , satisfying the internal wave equation

$$\left( \frac{\partial^2}{\partial t^2} \nabla^2 + N^2 \nabla_h^2 \right) \chi = 0,$$

with the  $z$ -axis directed vertically upwards and the subscript  $_h$  denoting a horizontal projection. The velocity  $\mathbf{u}$  and the disturbances  $p$  in pressure and  $\rho$  in density are related to the wave function through

$$\mathbf{u} = \left( \frac{\partial^2}{\partial t^2} \nabla + N^2 \nabla_h \right) \chi, \quad p = -\rho_0 \left( \frac{\partial^2}{\partial t^2} + N^2 \right) \frac{\partial \chi}{\partial t}, \quad \rho = \rho_0 \frac{N^2}{g} \frac{\partial^2 \chi}{\partial t \partial z},$$

with  $g$  the acceleration due to gravity, while the pressure  $p_0$  and density  $\rho_0$  at rest satisfy  $dp_0/dz = -\rho_0 g$  and  $d\rho_0/dz = -\rho_0 N^2/g$ . As for irrotational flow, the linearity of the wave equation implies a linear relation between the velocity  $\mathbf{U}$  of a translating rigid body and the wave function that it creates, in the form of a temporal convolution  $\chi = \chi_i * U_i$ .

The pressure force on the body follows immediately as

$$F_i = \oint_S p n_i d^2S = -\rho_0 \frac{\partial}{\partial t} \left( \frac{\partial^2}{\partial t^2} + N^2 \right) \oint_S n_i \chi d^2S.$$

Equations of conservation may be derived for the momentum and total (kinetic and potential) energy of the fluid, of respective densities  $\rho_0 u_i$  and  $\frac{1}{2}\rho_0 u_i^2 + \frac{1}{2}\rho_0 N^2 \zeta^2$ , with  $\zeta = \partial^2 \chi / \partial t \partial z$  the vertical displacement of fluid particles. By integrating the associated fluxes over the surface of the body, we obtain the momentum and energy outputs of the body as, respectively,

$$I_i = \rho_0 \oint_S \left( n_i \frac{\partial^2}{\partial t^2} + n_{hi} N^2 \right) \chi d^2S, \quad E = \rho_0 U_i \left( \frac{\partial^2}{\partial t^2} + N^2 \right) \oint_S n_i \chi d^2S.$$

Introduction of the Green's function of the wave equation<sup>5</sup> combined with application of standard techniques<sup>6,7</sup> yields a Kirchhoff–Helmholtz integral equation for internal waves, which corrects<sup>8</sup> and generalizes<sup>9</sup>. By expanding this equation at large distances from the body, we obtain the dipole strength of the body, such that

$$\rho_0 \mathcal{D}_i = \rho_0 \oint_S \left[ \left( n_i \frac{\partial^2}{\partial t^2} + n_{hi} N^2 \right) \chi - x_i \left( \frac{\partial^2}{\partial t^2} \frac{\partial}{\partial n} + N^2 \frac{\partial}{\partial n_h} \right) \chi \right] d^2S.$$

Accordingly, two distinct definitions of the added mass tensor may be proposed. One,

$$m_{ij}^{(1)} = \rho_0 \left( \frac{\partial^2}{\partial t^2} + N^2 \right) \oint_S n_i \chi_j d^2S,$$

involved in pressure and energy through

$$F_i = -m_{ij}^{(1)} * \frac{dU_j}{dt}, \quad E = U_i \left[ m_{ij}^{(1)} * U_j \right],$$

and the other

$$m_{ij}^{(2)} = \rho_0 \oint_S \left( n_i \frac{\partial^2}{\partial t^2} + n_{hi} N^2 \right) \chi_j d^2S,$$

involved in momentum and dipole strength through

$$I_i = m_{ij}^{(2)} * U_j, \quad \rho_0 \mathcal{D}_i = \left[ m_{if} \delta_{ij} \delta(t) + m_{ij}^{(2)} \right] * U_j.$$

The relation between the two is simplified in the monochromatic case, when the excitation  $\mathbf{U}$  and the responses  $\mathbf{u}$ ,  $p$  and  $\rho$  depend on time through the factor  $e^{-i\omega t}$  which is suppressed in the following. The time-dependent added masses are replaced by their temporal Fourier transforms and the above relations assume the more familiar forms

$$F_i = i\omega m_{ij}^{(1)} U_j, \quad \langle E \rangle = \frac{1}{2} \text{Re} \left[ \overline{U_i} m_{ij}^{(1)} U_j \right], \quad I_i = m_{ij}^{(2)} U_j, \quad \rho_0 \mathcal{D}_i = \left[ m_{if} \delta_{ij} + m_{ij}^{(2)} \right] U_j,$$

where  $\bar{\phantom{x}}$  denotes a complex conjugate and  $\langle \phantom{x} \rangle$  a time average. The two added mass tensors are related anisotropically through

$$m_{ij}^{(1)} = \left( 1 - \frac{N^2}{\omega^2} \delta_{i3} \right) m_{ij}^{(2)}.$$

As did<sup>10–12</sup>, in the following we will consider the first definition only and omit the superscript<sup>(1)</sup>.




Figure 1 – Coefficients of (a) added mass and (b) damping for an oscillating circular cylinder (—) and a sphere oscillating horizontally (---) or vertically (.....).

**Oscillating bodies** We illustrate these results for two particular oscillating bodies, a horizontal circular cylinder and a sphere, represented as source terms  $q = \sigma \delta_S$  on the right-hand side of the wave equation, namely as surface distributions of singularities of density  $\sigma$ . The condition of fixed normal velocity  $U_n$  on  $S$  becomes an integral equation for  $\sigma$ , solved by use of stretched orthogonal curvilinear coordinates<sup>13</sup> and expansion into circular or spherical harmonics<sup>14</sup>. For rigid oscillation at the velocity  $\mathbf{U}$  the solution is found for the cylinder, of radius  $a$ , as

$$q(\mathbf{x}) = \left\{ \left[ 1 + \left( 1 - \frac{N^2}{\omega^2} \right)^{1/2} \right] U_x \frac{x}{a} + \left[ 1 + \left( 1 - \frac{N^2}{\omega^2} \right)^{-1/2} \right] U_z \frac{z}{a} \right\} \delta(r - a),$$

with  $r = |\mathbf{x}|$ , and for the sphere, also of radius  $a$ , as

$$q(\mathbf{x}) = \left[ \frac{2}{1 + B(\omega/N)} \mathbf{U}_h \cdot \frac{\mathbf{x}_h}{a} + \frac{1}{1 - B(\omega/N)} U_z \frac{z}{a} \right] \delta(r - a),$$

with

$$B\left(\frac{\omega}{N}\right) = \frac{\omega^2}{N^2} \left[ 1 - \left( \frac{\omega^2}{N^2} - 1 \right)^{1/2} \arcsin\left(\frac{N}{\omega}\right) \right].$$

Complex square roots are fixed, in accordance with causality, by replacing  $\omega$  by  $\omega + i0$ , in other words by adding to the real frequency  $\omega$  a positive imaginary part which is later allowed to tend to zero.

The associated added mass coefficients  $C_{ij} = m_{ij}/(\rho_0 V)$ , such that  $\mathcal{D}_i = \int x_i q(\mathbf{x}) d^3x = V[\delta_{ij} + C_{ij}/(1 - \delta_{i3} N^2/\omega^2)]U_j$ , are complex. Their real part represents added inertia and their imaginary part, only present when  $\omega < N$  namely when propagative waves are generated, represents wave damping. They are given for the cylinder by

$$C_h = C_z = \left( 1 - \frac{N^2}{\omega^2} \right)^{1/2},$$

and for the sphere by

$$C_h = \frac{1 - B(\omega/N)}{1 + B(\omega/N)}, \quad C_z = \left( 1 - \frac{N^2}{\omega^2} \right) \frac{B(\omega/N)}{1 - B(\omega/N)}.$$

Their variations, consistent with direct calculations<sup>10,12,15,16</sup> and measurements<sup>17</sup>, are represented in figure 1. In the limit  $\omega/N \rightarrow \infty$  the values  $C_\infty = 1$  for the cylinder and  $\frac{1}{2}$  for the sphere in a homogeneous fluid are recovered.




Figure 2 – For a circular cylinder (continuous line) and a sphere (dashed lines), (a) power output of forced oscillations, normalized by  $P_0 = \rho_0 N^3 a^2 A^2$  for the cylinder and  $\rho_0 N^3 a^3 A^2$  for the sphere, and (b) free buoyant oscillations.

**Two applications** A first application of the above is the average power output  $\langle P \rangle$  of a body oscillating with amplitude  $A$  at the angle  $\alpha$  to the vertical. This output, given by

$$\langle P \rangle = \frac{1}{2} \rho_0 V \omega^3 A^2 \operatorname{Im} [C_h^2 \sin^2 \alpha + C_z^2 \cos^2 \alpha],$$

is represented in figure 2(a) for the cylinder and sphere. For  $\omega > N$ , the waves are evanescent and no output is observed. For  $\omega < N$ , the waves are propagative and the output at given  $A$  is maximum at  $\omega/N = \sqrt{2/3} \approx 0.82$  for the cylinder, and at  $\omega/N$  varying weakly, between 0.84 and 0.85, with  $\alpha$  for the sphere.

A second application is the oscillation  $Z(t)$  of a body displaced slightly by  $Z_0$  from its neutral buoyancy level then released at  $t = 0$ . The temporal Fourier transform of the oscillation is

$$\frac{Z(\omega)}{Z_0} = \frac{i}{\omega} \frac{1 + C_z(\omega)}{1 + C_z(\omega) - N^2/\omega^2},$$

yielding  $Z(t)/Z_0 = J_0(Nt)$  for the cylinder and  $\frac{1}{2}\pi \mathbf{E}_1(Nt)$  for the sphere, with  $J_\nu$  a Bessel function and  $\mathbf{E}_\nu$  a Weber function. The oscillation, represented in figure 2(b), is consistent with direct calculation and measurement<sup>18</sup>. Experiments for larger initial displacements<sup>19,20</sup> have pointed out the importance of viscous damping, and the topic remains an area of active research<sup>21–23</sup>.

## REFERENCES

1. J. N. Newman, *Marine Hydrodynamics*, MIT Press (1977), §§4.12–16.
2. V. A. Gorodtsov and E. V. Teodorovich, *Izv. Atmos. Ocean. Phys.* **16**, 699–704 (1980).
3. R. W. Hart, *Phys. Fluids* **24**, 1418–1420 (1981).
4. B. Voisin, *J. Fluid Mech.* **496**, 243–293 (2003).
5. B. Voisin, *J. Fluid Mech.* **231**, 439–480 (1991).
6. J. E. Ffowcs Williams and D. L. Hawkings, *Phil. Trans. R. Soc. Lond. A* **264**, 321–342 (1969).
7. F. Farassat, *J. Sound Vibr.* **55**, 165–193 (1977).
8. Yu. Z. Miropol'skii, *Izv. Atmos. Ocean. Phys.* **14**, 673–679 (1978).
9. S. L. Simakov, *J. Fluid Mech.* **248**, 55–65 (1993).
10. R. Y. S. Lai and C.-M. Lee, *Int. J. Engng Sci.* **19**, 1411–1420 (1981).
11. V. A. Vladimirov and K. I. Il'in, *J. Appl. Mech. Tech. Phys.* **32**, 194–200 (1991).
12. E. V. Ermanyuk, *Exps. Fluids* **32**, 242–251 (2002).
13. J. C. Appleby and D. G. Crighton, *Q. J. Mech. Appl. Maths* **39**, 209–231 (1986); *J. Fluid Mech.* **183**, 439–450 (1987).
14. V. A. Gorodtsov and E. V. Teodorovich, *Fluid Dyn.* **17**, 893–898 (1982).
15. D. G. Hurley, *J. Fluid Mech.* **351**, 105–118 (1997).
16. I. V. Sturova, *Fluid Dyn.* **36**, 478–488 (2001).
17. E. V. Ermanyuk and N. V. Gavrilov, *J. Fluid Mech.* **451**, 421–443 (2002); *J. Fluid Mech.* **494**, 33–50 (2003).
18. L. H. Larsen, *Deep-Sea Res.* **16**, 587–603 (1969).
19. C. D. Winant, *Deep-Sea Res.* **21**, 445–450 (1974).
20. J. Cairns, W. Munk and C. Winant, *Deep Sea Res. A* **26**, 369–381 (1979).
21. Yu. V. Prikhod'ko and Yu. D. Chashechkin, *Fluid Dyn.* **41**, 545–554 (2006).
22. A. Yu. Vasil'ev, A. V. Kistovich and Yu. D. Chashechkin, *Dokl. Phys.* **52**, 596–599 (2007).
23. I. Biró, K. G. Szabó, B. Gyüre, I. M. Jánosi and T. Tél, *Phys. Fluids* **20**, 051705 (2008).