

Fate of Fusarium mycotoxins in cereal product supply chain: the DON case within industrial bread-making technology

Elena Bergamini, Dante Catellani, Chiara Dall'Asta, Gianni Galaverna, Arnaldo Dossena, Rosangela Marchelli, Michele Suman

▶ To cite this version:

Elena Bergamini, Dante Catellani, Chiara Dall'Asta, Gianni Galaverna, Arnaldo Dossena, et al.. Fate of Fusarium mycotoxins in cereal product supply chain: the DON case within industrial bread-making technology. Food Additives and Contaminants, 2010, 27 (05), pp.677-687. 10.1080/19440041003660117. hal-00591171

HAL Id: hal-00591171 https://hal.science/hal-00591171

Submitted on 7 May 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Food Additives and Contaminants



Fate of Fusarium mycotoxins in cereal product supply chain: the DON case within industrial bread-making technology

Journal:	Food Additives and Contaminants
Manuscript ID:	TFAC-2009-335.R1
Manuscript Type:	Special Issue
Date Submitted by the Author:	26-Jan-2010
Complete List of Authors:	Bergamini, Elena; Barilla SpA, Food Science & Research Labs Catellani, Dante; Barilla SpA, Food Science & Research Labs Dall'Asta, Chiara; University of Parma, Department of Organic and Industrial Chemistry Galaverna, Gianni; University of Parma, Department of Organic and Industrial Chemistry Dossena, Arnaldo; University of Parma, Department of Organic and Industrial Chemistry Marchelli, Rosangela; University of Parma, Department of Organic and Industrial Chemistry Suman, Michele; Barilla SpA, Food Science & Research Labs
Methods/Techniques:	Chemometrics, Chromatography - LC/MS, Statistical analysis
Additives/Contaminants:	Mycotoxins - fusarium, Mycotoxins - trichothecenes
Food Types:	Bread, Bakery products

SCHOLARONE[™] Manuscripts

Fate of Fusarium mycotoxins in the cereal product supply chain: the DON case within industrial bread-making technology.

E. Bergamini*, D. Catellani*, C. Dall'Asta**, G. Galaverna**, A. Dossena**,

R. Marchelli**, M. Suman*

*Barilla Food Research Labs, via Mantova 166, 43100 Parma, Italy **Department of Organic and Industrial Chemistry, University of Parma, 43100, Parma, Italy

Corresponding Author e-mail: m.suman@barilla.it

Abstract

Fusarium mycotoxins are a relevant problem in the cereal supply chain at a worldwide level, being wheat, maize and barley the main contaminated crops; mould growth could happen in the preharvest phase and also during transport and storage due to ineffective drying conditions. Among Fusarium toxins, deoxynivalenol (DON) is considered the most important contaminant in wheat, due to its wide-spread occurrence. In the last years the European Food Safety Authority and the European Commission had frequently expressed opinions on Fusarium toxins, setting limits, regulations and guidelines in order to reduce their levels in raw materials and food commodities: in particular European legislation (Reg. 1881/2006) sets the maximum limit for deoxynivalenol in flour and bread as 750 μ g/kg and 500 μ g/kg respectively. Relatively few studies have taken into account the loss of trichothecenes during processing, focusing on how processing factors may influence their degradation. In particular, the description of DON behavior during bread-making is very difficult, since complex physic-chemical modifications occur during the transformation of raw ingredients into the final product. In the present study, we studied how DON concentration may be influenced by modifying bread-making parameters, with a special emphasis on the fermentation and baking stages, starting from a naturally contaminated flour at both pilot and industrial scales. Exploiting the power of a Design of Experiments (DoE) approach to consider the high complexity of the studied system, the obtained model shows satisfying goodness of fit and prediction, suggesting that the baking step (time/temperature ranges) is crucial for minimizing native DON level in bread.

Keywords:- bread; fermented dough; mycotoxins; industrial process; processed food; design of experiments; deoxynivalenol degradation; deoxynivalenol binding

Introduction

Trichothecene mycotoxins, which frequently occur in cereals and cereal-based products, are secondary metabolites produced mainly by *Fusarium* ear blight pathogens, which are widely distributed in the temperate zone of all continents (D'Mello and Macdonald 1997; Creppy 2002). The incidence of these mycotoxins in food crops can vary considerably from year to year depending on many factors, such as weather conditions and agricultural practices (Edwards 2004). Since these toxins can never be completely removed by processing (Kuiper-Goodman 2004), preventive measures should be adopted at all stages of the production chain to prevent contamination of final food products.

Among trichothecenes, deoxynivalenol (DON) is the most important for wheat and derived products, on account of its widespread diffusion and of its implication in animal and human toxicoses (Hussein and Brasel, 2001), including feed refusal, decrease in body weight, immunomodulation and reduction of host resistance against infection. Natural occurrence of DON in wheat and in derived products has been reported world-wide.

To protect consumers from unacceptably high dietary intake of trichothecenes, maximum levels have been set in EU legislation (European Commission 2006). Currently, maximum levels for deoxynivalenol are regulated in cereals (1250 μ g/kg), flour (750 μ g/kg) and bread (500 μ g/kg). The fate of DON and other trichothecenes during processing has been documented in several studies. Experiments concerned with the distribution of DON among the milling fractions in naturally *Fusarium*-contaminated wheat showed that the highest concentration of this mycotoxin is in the bran layer; while in white flour, compared with the whole grain, it is reasonably lower (Abbas et al. 1985; Tanaka et al. 1986).

The first stage of cereals processing consists into removal of dust, broken grains and other foreign material. This action can significantly reduce mycotoxin concentrations, since most mycotoxins tend to concentrate in the bran fractions or outer layers. Whole grains are then milled to produce flour and other fractions, used to prepare bread, biscuits, cakes, etc. Most mycotoxins are quite stable at room temperature and under neutral conditions; however, many factors (e.g. temperature,

pH, enzymatic activities, food macro- and microconstituents) must be considered during processing, since mycotoxin modification and breakdown may be induced (Scott. 1998).

The occurrence of mycotoxins in the raw material, such as common wheat, should be therefore carefully studied, as well as the effect of processing and food manufacturing on their concentration in the correspondent retail products (Hazel and Patel, 2004).

Bakery processing has been reported to reduce DON contamination by some authors (Abbas et al. 1985, Seitz et al. 1986) while others suggested that DON is highly stable in this process (El-Banna et al. 1983, Scott et al. 1983, 1984). Moreover DON appeared to be very stable at 100°C at the pH of bread (Wolf and Bullerman, 1998).

The influence of various ingredients added to dough before baking on DON levels in bread was studied by Boyacioglu et al. (1993). In particular, a reduction of DON as high as 40% seemed to be due to the addition of several additives such as sodium bisulphite, L-cysteine and ammonium phosphate in dough. Other additives such as potassium bromate and L-ascorbic acid were ineffective.

Samar et al (2001) indicated that DON reduction during bread-making might be due not only to the thermal decomposition of the toxin, but also to the fermentation process exerted by yeasts. However, the effect of yeast on DON levels in dough during the baking fermentation step are rather contradictory. Neira et al. (1997) documented a 20% mean reduction of DON in fermented dough, Valle Algarra et al. (2009) indicate stability during the fermentation and reduction in the baking phase, whereas Young et al. (1984) observed an increase of DON in yeasted products. The latter authors suggested that perhaps the wheat used was also contaminated with a DON precursor which was converted in DON by active yeast. This fact is a crucial point to be considered and might explain somewhat the diversity of results found in the literature, as recently pointed out also by Lancova et al (2008). Technological processes, indeed, could also play an important role in the masking mechanism: mechanical or thermal energy during the transformation process (Scudamore, 2008) may cause modification, inducing reactions with macromolecular components such as sugars, proteins or lipids as well as release of native forms.

Published data on milling and bread-making processing appear thus conflicting. This may be in part due to the failure in understanding the complexity of milling technology or to very different approaches (handmade, pilot scale/lab trials), often far from achieving an edible and satisfying product for consumers. It is also evident that the behaviour of mycotoxins in laboratory\handmade studies could not adequately reflect what occurs in industrial scale operations such as in mills or bakery plants using naturally contaminated cereals (Scudamore et al., 2009). Last but not least, it is not always made clear whether values quoted are "as is" or corrected for moisture content (usually around 30-40%) and formulation (addition of other ingredients, additives etc.).

The aim of the present study was to verify how the DON concentration in final bread is influenced by modifications of technological parameters during the fermentation and baking steps, starting from naturally contaminated wheat flour and using firstly a pilot-scale bread-making plant and then a real industrial production line. The experiments were performed using statistical Design of Experiment (DoE) schemes which allow, when multiple parameters may influence the desired outputs, to explore the relationship between the analytical responses and independent variables conducting to an optimization of the process. In particular, in our case this approach was chosen in order to consider only those modifications which can really be applied to industrial scale to obtain a final product which can be considered appreciable by the consumer.

Materials and methods

Chemicals

Deoxynivalenol (DON) as well as internal standard ${}^{13}C_{15}$ -deoxynivalenol (${}^{13}C_{15}$ -DON) were purchased by Biopure GmbH (Tulln, Austria). Acetonitrile (HPLC grade), methanol (HPLC grade), ammonium acetate (puriss. p.a.) was obtained from Merck (Darmstadt, Germany). Acetic acid was also an HPLC gradient-grade reagent obtained from BDH VWR International Ltd (Poole, England). MycoSep® 226 Trichothecene columns (Romer Labs Inc., Union, MO) were purchased from Orsell Srl (Modena, Italy). Deionized water was used for all procedures.

Samples

For the baking experiments conducted within the first part of the study, 16 batches of wheat naturally infected with *Fusarium* spp. were analysed with a focus on DON contamination levels. Among the analysed batches, three flour batches were established, according to DON contamination level and technological characteristics for bread-making (e.g. quality and quantity of the gluten-forming proteins content, grain conformation etc.). In particular, three different levels of DON contamination were selected; the whole wheat batches were milled using a pilot-scale mill (BONA, B0430) to obtain three flour batches (212 μ m granulometry) with a different DON level

contamination (flour A 160 ± 15 μ g/kg, flour B 100 ± 14 μ g/kg, flour C 967 ± 49 μ g/kg), which was evaluated in triplicate on dry matter.

Moisture content determination

The moisture contents of flour and bread were measured by taking 10g of ground sample and heating in a thermostatic oven at 105°C for more than 6 hours. The moisture content of fermented dough was measured by taking a 15g of sample and heating in an oven at 105°C for 3h; after a milling step, the sample was again heated at 105°C for 6 hours.

All the results were corrected and compared on dry matter basis.

Experimental Design

Design of Experiments (DoE) is the design of all information-gathering exercises where variation is present, whether under the full control of the analysis or not: the analyst is interested in investigating of phenomena and studying the synergistic effect of some interventions (the "treatments") for a final process optimization.

The present study is organised on a Screening Design of Experiments (SDoE) with the aim to identify which predictors are most influential as well as what are their appropriate ranges for minimizing DON levels in bread-making. Among the bread-making parameters, several conditions were varied during the experiments according to the technological requirements: in particular, DON contamination level on wheat flour, fermentation rate, fermentation temperature, baking rate and baking temperature were included as treatments in the experimental design. Each selected treatment was varied within a range defined according to the technological requirements to obtain an organoleptically appreciable loaf for the consumer, as described in Table 1 for the pilot-scale plant and for the industrial-scale plant.

To describe in a synergic way all these variables, enabling a screening interaction model to be estimated taking into account of balancing and orthogonality for each factor, it was adopted a full factorial central composite design (CCD). Three replicates of the central points were performed to estimate the experimental error.

Experimental data were then analysed by a multivariate analysis approach based on the Partial Least Square technique, using a dedicated statistical-package (MODDE software, vers. 8.0, Umetrics; Umea, Sweden).

Dough preparation and bread-making

Different doughs were prepared starting from selected flours in order to get a final loaf of about 120g; the ingredients were wheat flour (59%), water (30%), yeasts (Saccharomyces cerevisiae), bread-making promoting agents, malted barley flour, dextrose, sourdough powder, fractionated palm oil and salt (11% overall).

The process consists substantially of the following steps: firstly, flour is mixed with all solid powders ingredients (2 min) then moistened with salt suspended in water and oil (3 min). Dough is mixed with baking test kneader. Water optimal amount for each flour as well as reference baking conditions is established on the basis of previous experiments and internal technological knowledge. The overall bread-making process is summarized in Figure 1.

Since the experimental plan involved randomized changes in condition of bread fermentation and baking, 24 different baking tests for the pilot plant and 19 for the industrial plant were performed (see Tables 2 and 3). Two identical doughs were used for each single experiment: one was analysed for DON after the fermentation step and the other was analysed for DON after the baking process. Thus, rounded pieces of about 10 cm diameter (~140 gr) were obtained from each dough and let rest for 10 min at room temperature. Concerning the pilot plant, fermentation step was performed in a leaven cell (Fermalievita, Alaska) at a relative humidity (RU%) of 70%, while baking step was performed in a pilot scale oven (Pollin, Verona, Italy); concerning the industrial line, fermentation step was performed in an indirect-radiating-cyclotherm-5 zones industrial oven (Imaforni, Verona, Italy). For each baking test, fermentation parameters (time and temperature) as well as baking parameters (time and temperature) were set according to the Experimental Pilot Design (DoE).

Prior to analysis, samples were stored at -18°C. Each sample was extracted in duplicate and each extract was measured in duplicate.

Extraction and clean-up for DON

According to a previously published procedure (Suman et al., 2008), a total of 20g of bread or dough sample was extracted with 100ml of a mixture acetonitrile/water (84:16, v/v) by homogenization at medium-high speed for 2 min. The extract was filtered and 6ml of the filtrate was poured into a 10ml vial previously prepared in the following way: 100 μ l of an internal standard ($^{13}C_{15}$)-DON solution (1200 μ g/l in acetonitrile) was added and immediately evaporated to dryness

Food Additives and Contaminants

under a nitrogen stream. This final solution was acidified by 30 μ l of acetic acid and then slowly pressed trough a Mycosep® 226 column. A total of 2 ml of the eluate was evaporate using a gentle stream of nitrogen and the residue was reconstituted in 0.2 ml of starting mobile phase (phase B) and used for LC-MS/MS analysis (injection volume: 20 μ l aliquot).

LC-MS/MS analysis

The samples were analysed in duplicate in the Mass Spectrometry Laboratory of Barilla Food Research Labs and in the Food Chemistry Laboratory of Department of Organic and Industrial Chemistry, University of Parma.

The pump used for reversed-phase high-performance liquid chromatography (RP-HPLC) was a Surveyor LC Pump (Thermo Finnigan, San Jose, CA, USA). The chromatographic separation was performed using a Supelcosil LC-18 3µm 33x4.6 mm (Supelco, Bellefonte, PA, USA) column with a flow rate of 0.2 mL/min. Injections were made using a Surveyor Autosampler (Thermo Finnigan).

The electrospray ionization (ESI) experiments were carried out in a Linear-Ion-Trap LXQ (Thermo Scientific) mass spectrometer either in positive or negative scan mode.

Linear Ion Trap LC-MS/MS conditions were determined following the method of Suman et al. (2008). Briefly, a linear binary gradient was applied changing from 100% solvent A [20% methanol + 80% water (5 mM ammonium acetate)] to 100% solvent B [65% methanol + 35% water (5 mM ammonium acetate)] and to 100% solvent C [80% methanol + 20% water (5 mM ammonium acetate)] within a total run time of 25 minutes.

The capillary temperature was set to 220 °C; the sheath gas set to 20 units; the spray voltage was kept at 4000 V; the capillary voltage was kept at -11 V; multiple Reaction Monitoring (MRM) experiments were performed according to parameters reported in Table 4. All parts of the equipment and data processing were performed by the computer software Xcalibur (Thermo Scientific).

Concerning the experiments performed at the Food Chemistry laboratory, University of Parma, the instrumental conditions were reported below. The LC-MS/MS system consisted of a 2695 Alliance (Waters, Milford, MA, USA) equipped with a QuattroTM triple quadrupole mass spectrometer with an electrospray source (Micromass, Waters, Manchester, UK). Chromatographic conditions were the following: column, Phenomenex Synergi 2.5 μ m Fusion-RP 100A (50 x 2.00 μ m) equipped with a C18 precolumn cartridge (Phenomenex); flow rate, 0.25 mL/min; column temperature, 30°C; injection volume, 5 μ l. Gradient elution was performed using CH₃COOH 5 mM(eluent A) and methanol (eluent B): 0–1 min, isocratic step 5% B; 1–9 min to 70% B; 9–20 min isocratic step 70%

B; 20-21 min to 5% B; finally, a re-equilibration step at 5% B (initial conditions) for 9 min was performed (total analysis time, 30 min). The MS parameters were the following: ESI- (negative ion mode); capillary voltage, 2.5 kV; cone voltage 10 V; extractor voltage, 3 V; source block temperature, 150°C; desolvation temperature, 350°C; desolvation and cone gas (nitrogen) 500 and 50 L/h, respectively. Detection was performed using a multiple reaction monitoring (MRM) mode, by monitoring three transitions for each analyte, as reported in Table 4. The main transition was used for quantification, while two more transitions were chosen as qualifiers.

All parts of the equipment and data processing were performed by the computer software MassLynx (Waters).

Results and discussion

Design of Experiments (DoE) is a statistical technique quite used by the industry today, mainly in the development and optimization of manufacturing processes. The main objectives of this approach are screening, optimization and robustness testing in the laboratory, in the pilot-plant or in the full-scale production plant. Therefore DoE involves making a set of experiments representative with regards to a given question in a problem-dependent way.

In particular, the objectives of the Screening Design of Experiment were: (i) to explore many factors in order to reveal whether they have an influence on the responses, and (ii) to identify their appropriate ranges.

In this study, the influence of four factors on the final DON level in bread was investigated on a pilot-plant scale. The four factors were fermentation rate, fermentation temperature, baking rate and baking temperature. For each rate\temperature parameters a well-defined variation range was assessed, as reported in Table 2: this variation range was established according to the technological requirements in order to get an acceptable final product. Moreover, three flour batches containing different initial DON amount were chosen, in order to simulate a medium-low contamination (level A and level B, 100 μ g/kg and 160 μ g/kg respectively) and a high contamination (level C, 967 μ g/kg) in raw material.

The statistical model required 24 single experiments; for each experiment DON level was measured by LC-MS/MS after the fermentation step and after the baking step.

At the end of the screening design, the software was able to extract an answer concerning the influence of a particular factor. This is done by fitting a polynomial model to the data and

calculating the regression coefficient for each factor. These values, plotted in the Variable Importance Plot (VIP, Figure 2) indicated how the four factors influence the response and their relative interactions. Moreover, the construction of a response contour plot is also useful for decision making and result interpretation (Figure 3): information is thus gained about how to modify the settings of the important factors, to possible minimize DON content in ready-to-eat bread.

Afterwards, the validity of the established model was evaluated also on a full-scale plant, in order to check whether the observation obtained for pilot plant could be applied also for industrial bread. Finally, the prediction power of the model was tested by preparing and analysing a model loaf and comparing the expected and the found DON level in final bread.

Bread-making pilot plant study: DON trend during processing.

Samples obtained from the application of the bread-making DoE were extracted in duplicate and then analysed using a linear ion trap LC/MS/MS in the Mass Spectrometry Laboratory of Barilla Food Research Labs, and using a triple quadrupole LC/MS/MS in the laboratory of Food Chemistry Labs, Department of Organic and Industrial Chemistry-University of Parma, as reported in the Material and Method Section. For each DoE experiment, two identical samples were prepared: the first was analysed after the fermentation step and the latter after baking, in order to check the effect exerted by the processing conditions during each step on the DON level.

The data were expressed on dry matter and corrected according to the recipe formulation and reported in Table 3.

As shown in Table 3, the DON level seems to be influenced by the processing and an increase (Tukey test, $\alpha = 0.05$, p < 0.01) is recorded after the fermentation step for the medium-low level contaminated samples, whereas negligible changes were recorded for high level contaminated samples. The DON contamination was averagely increased of 46% for group A samples (initial contamination: 100 µg/Kg) and of 31% for group B samples (initial contamination: 160 µg/Kg); this trend could be due to the release of DON from some bound form occurring in the flour, which might be cleaved or solubilised during fermentation. The same phenomenon was not observed for highly contaminated flour (group C): in this case, the DON release from bound forms may be negligible when compared to high level of free DON occurring in the matrix (960 µg/Kg).

Since the aim of this study was the minimization of DON in industrial bread by means of statistical DoE, this phenomenon will be further studied by our group in the next future.

Bread-making pilot plant study: statistical evaluation of the prediction model

Predictive modeling is the process by which a model is created to best predict the probability of an outcome: the model is chosen on the basis of detection theory to try to guess the probability of a signal, given a set amount of input data. In this work, the data sets obtained from the execution of the DoE planned trials, were treated to build a prediction model in order to describe the bread-making process. In particular, replicates values for DON concentration in each experiment were averaged and computed as initial dataset. Partial Least Square (PLS) based on three components was chosen as statistical regression treatment.

The statistical model efficacy was evaluated by means of two main parameters: fitting (R^2) and prediction (Q^2) values. In particular, "explained variation" R^2 measures the proportion to which the statistical model accounts for the variation of a given dataset, while "predictive power" Q^2 refers to its ability to generate testable predictions. The generated statistical model starting from the dataset gave a high fitting value ($R^2 \gg 0.8$) and a correspondent good prediction value ($Q^2 > 0.5$), referring to the MODDE software output settings.

Variable Importance Plot (VIP) explains consistently the importance of a variable within the measurements of a process\phenomena. It generates also information on the most important interactions and represents the most condensed way of expressing the PLS model output as a weighted summary of all loadings and across all responses.

This statistical algorithm elaboration applied to our bread-making DoE recorded dataset, indicates the different incidence, within the technological range, of the selected predictors on the possibility to control and influence the DON evolution during the industrial process: the baking phase seems to be particularly relevant with respect to the fermentation phase, as shown in Figure 2.

Although the most important variable indicated by the plot is the initial DON contamination of flour, this value can't be obviously regarded as a variable for our model, since it is already known at the beginning of the industrial process and can be out-line carefully controlled by raw material analysis.

On the other hand, when only an acceptable technological range is considered, fermentation process cannot be changed in order to obtain a significant minimization of the DON level in final loaf, as deducible from the prediction model output.

Starting from this observation, a contour map can be obtained in order to outline the influence of the selected variables (baking rate and baking temperature) on the DON level in low-medium contaminated and in high DON-level containing flours, as reported in Figure 3a and 3b, respectively.

As shown by the contour maps, increasing the baking rate/temperature can determine a reduction of the free DON concentration in the final bread. The correspondence with the time/temperature domain that can really be applied in the industrial bread-making is illustrated in Figure 3: this is a crucial point, since many studies suggested that major DON decreases can be achieved by applying higher temperature and longer baking rate, but these conditions do not allow the production of acceptable bread.

In particular, temperature higher than 210°C may induce a significative decrease in DON concentration in bread, although this effect seemed to be remarkable only in case of medium-high contamination of the flour used as raw material. On the other hand, when low contaminated flour is used, negligible changes in DON level is predicted by the model.

Bread-making pilot-plant study: evaluation of the DoE predictive power.

Further pilot-plant bread-making trials were aimed to directly verify the predictive power showed by the statistical model by comparing the DON level predicted by the model and measured in final bread (obtained starting from a naturally contaminated flour) and applying the optimized bread-making conditions previously described. Since the minimization effect due to the baking stage seemed to be significative for highly contaminated flour, an initial DON level closed to the legal limit for raw material was chosen, namely 717±32 μ g/kg.

For the fermentation stage, the optimal processing parameters were set at 35°C for 65 min. The final moisture in bread required to reach a satisfying level was set at 35%. Baking step was performed at 215°C for 10 min: baking temperature was chosen above 210°C, as suggested by the statistical model, and the baking rate was chosen by monitoring bread browning and target moisture, in order to obtain an acceptable final product. The experiment was performed in triplicate

and each sample was analysed after the fermentation step and after the baking step, as previously reported.

Starting from set conditions (initial DON concentration, baking temperature and baking time), the statistical model returned a predicted final DON level in bread of $440 - 460 \ \mu g/kg$ d.m. The DON concentration found in final bread and reported on dry matter was $430\pm25 \ \mu g/kg$, showing thus a very good agreement with the DON predicted value.

Industrial line trials: evaluation of the prediction model.

The DoE model optimized for pilot plant was then tested also on the industrial line. As first, the predictor parameters range was adapted to the industrial plant requirements: for bread-making experiment a wheat flour containing $333\pm24 \ \mu g/kg$ of DON was chosen; also fermentation stage parameters were fixed (fermentation temperature: 32° C: fermentation rate: 56 min), in order to better investigate the influence of baking parameters on the DON concentration in final bread. In particular, the baking temperature was varied among 170° C and 225° C and baking time was varied among 0 and 13 min.

The comparison of the average DON levels in flour and in the final bread sample are reported in Figure 4.

The slight increase of deoxynivalenol concentration, related to the fermentation stage, during the processing already recorded in the pilot plant trials was confirmed also on the industrial line. Obviously, the industrial line experiments could be performed only using flour with a DON concentration significantly lower than the legally permitted limit, thus the data obtained on the pilot plant for high level of DON cannot be verified. Crumb temperature was checked carefully during the baking process and the collected values were related to the oven temperature, as reported in Figure 5.

As shown in Figure 5, the changes in DON concentration during the baking step is negligible: this can be explained taking into account the slight temperature changes recorded inside the loaf. Moreover, although the oven temperature was varied among 170° and 225°C, bread crumb experienced a maximum of 86°C at the final stage of the baking step: thus, relative low temperature inside the loaf combined with medium-low levels of the toxin in the starting flour may justify here

the lack of DON degradation or re-binding (reversing the process that happened during fermentation).

Conclusions

In the present study, the influence exerted by bread-making parameters on the DON concentration in bread was investigated, starting from a naturally contaminated flour and using both pilot and industrial-scale equipments. The results were then used for the development of a statistical predictive model, which was finally tested on an industrial production line. Exploiting the power of a Design of Experiments (DoE) approach to consider the high complexity of the studied system, the obtained prediction model provided the following useful information: (i) the fermentation phase induce a DON increase, (ii) increasing time\Temperature in the baking phase, even staying in an acceptable technological range, could reduce the native DON content in bread only starting from high naturally contaminated flour.

The fermentation stage seemed to be a crucial step in the bread-making process, since a significative DON increase was recorded in fermented dough obtained on both pilot-scale and industrial-scale plants. This increase may be due to the enzymatic release of native DON from bound forms occurring in the raw material and will be further investigated in order to highlight the involved phenomena. On the other hand, a careful control of the time/temperature combination during the baking step may lead to a minimization of the DON level in the final bread, especially when the DON concentration in flour is closed to the EU legal limit.

In conclusion, this study represents a concrete example of how a planned sequence of production experiments combined with a reliable LC-MS/MS method, may generate potential strategies for minimizing consumer exposure to DON through appropriate management of the industrial cereals processing technologies.

Acknowledgements

Part of the present work has been performed within a project (SITEIA) partially financed by the Emilia-Romagna Region (Italy). The financial support from Spinner Consortium (Spinner 2013, Emilia-Romagna Region together with the European Social Fund and the Italian Ministry for Welfare) is also acknowledged. Finally, authors would like to thanks the following colleagues for time, help and fruitful discussions: C. Cauzzi, L. De Vito, A. Garulli, E. Grignafini, A. Leporati, U. Tanzi.

References

Abbas, H.K., Mirocha, C.J., Pawlosky, R.J., Pusch D.J., 1985. Effect of cleaning, milling and baking on deoxynivalenol in wheat. Applied and Environmental Microbiology, 50, 482 – 486.

Boyacioğlu D., Hettiarachchy N.S., D'Appolonia B.L., 1993. Additives affect deoxynivalenol (vomitoxin) flour during breadbaking. Journal of Food Science, 56, 416 - 418.

Creppy EE 2002. Update of survey, regulation and toxic effect of mycotoxins in Europe. Toxicological Letters 127, 19 – 28

D'Mello JPF, Macdonald AMC. 1997. Mycotoxins. Animal feed science and Technology, 69, 155 – 166

Edwards SG, 2004. Influence of agricultural practices on Fusarium infection of cereals and subsequent contamination of grain by trichothecene mycotoxins. Toxicologicy Letters, 153, 29 – 35

El-Banna A.A., Lau P-Y., Scott P.M., 1983. Fate of mycotoxins during processing of foodstuffs II – deoxynivalenol (vomitoxin) during making of Egyptian bread. Journal of Food Protection, 46, 484 – 486

European Commission. 2006. Commission Regulation (EC) No. 1881/2006 of 19 December 2006. Official Journal of the European Union L 364, 7 – 8

Hazel C.M., Patel S. 2004. Influence of processing on trichothecene levels. Toxicology Letters, 153, 51–59

Hussein H.S., Brasel J.M. 2001. Toxicity, metabolism and impact of mycotoxins on humans and animals. Toxicology, 167, 101 – 134.

Kuiper-Goodman, T. 2004. Risk assessment and risk management of mycotoxins in food. In: *Mycotoxins in food, detection and control.* Magan, N. and Olsen, M. (eds.). Woodhead Publishing Ltd., Cambridge, UK, 6.

Lancova K., Hajslova J., Kostelanska M., Kohoutkova J., Nedelnik J., Moravcova H., Vanova M. 2008, Fate of trichothecene mycotoxins during the processing: milling and baking. Food Additives and Contaminants Part A, 25, 650 – 659

Neira M.S., Pacin A.M., Martinez E.J., Molto G. Resnik S.L. 1997. The effects of bakery processing on natural deoxynivalenol contamination. International Journal of Food Microbiology, 37, 21 – 25

Samar M.M., Neira M.S., Resnik S.L., Pacin A. 2001, Effect of fermentation on naturally occurring deoxynivalenol (DON) in Argentinean bread processing technology. Food Additives and Contaminants, 18, 1004 – 1010

Scott P.M. 1998. Industrial and farm detoxification processes for mycotoxins. Revue de Medicine Veterinaire, 149, 543 – 548

Food Additives and Contaminants

Scott P.M., Kanhere S.R., Dexter J.E., Brennan P.W., Trenholm H.L., 1984. Distribution of the trichothecene mycotoxin deoxynivalenol (vomitoxin) during the milling of naturally contaminated hard red spring wheat and its fate in baked products. Food Additives and Contaminants, 1, 313 – 323

Scott P.M., Kanhere S.R., Lau P.Y., Dexter J.E., Greenhalgh R., 1983. Effect of experimental flour milling and breadmaking on retention of deoxynivalenol (vomitoxin) in hard red winter wheat and its fate in baked products. Cereal Chemistry, 60, 421 – 424

Scudamore K.A. 2008. Fate of fusarium mycotoxins in the cereal industry: recent UK studies. World Mycotoxin Journal, 1(3), 315-325

Scudamore K.A., Hazel C.M., Patel S., Scriven F., 2009. Deoxynivalenol and other Fusarium mycotoxins in bread, cake and biscuits produced from UK-grown wheat under commercial and pilot scale conditions. Food Additives and Contaminants, 26(8), 1191 – 1198.

Seitz L.M., Eustace W.D., Mohr H.E., Shogren M.D., Yamazaki W.L. 1986. Cleaning, milling and baking tests with hard red winter wheat containing deoxynivalenol. Cereal Chemistry, 63, 146 – 150

Suman M., Catellani D. 2008. Ion trap IC-MS/MS as a valid multi-method to determine trichothecenes and zearalenone in the food industry. World Mycotoxin Journal, 1(3), 255-263

Tanaka T., Hasegawa A., Yamamoto S., Matsuki Y., Ueno Y. 1986. Residues of *Fusarium* mycotoxins, nivalenol, deoxynivalenol and zearalenone, in wheat and processed food after milling and baking. Journal of Food Hygienic Society of Japan, 27, 653 - 655.

Valle-Algarra F.M., Mateo E.M., Medina A., Mateo F., Gimeno-Adelantado J.V., Jimenez M. 2009. Changes in ochratoxin A and type B trichothecenes contained in wheat flour during dough fermentation and bread-baking. Food Additives and Contaminants Part A, 26(6), 896-906

Wolf C.E., Bullerman L.B. 1998. Heat and pH alter the concentration of deoxynivalenol in an aqueous environment. Journal of Food Protection, 61, 365 – 367

Young J.C., Fulcher G.R., Hayoe J.H., Scott P.M., Dexter J.F. 1984. Effect of milling and baking on deoxynivalenol (vomitoxin) content in eastern Canadian wheats. Journal of Agricultural and Food Chemistry, 32, 659 – 664

Table 1 – Bread-making conditions assumed during experiments in the pilot-scale plant (Levels: a,b,c) and in the industrial-scale plant.

Treatment	Bread-m	aking co	onditions	Bread-making conditions		
	in pilot-scale plant			in industrial-scale plant		
Fermentation temperature $(T_{f,}^{\circ}C)$	30 (a)		40 (c)	32	Fixed value	
Fermentation rate (t _f , min)	45 (a)	65 (b)	85 (c)	56	Fixed value	
Baking temperature (T _b ,°C)	180 (a)		210 (c)	170 (min)	225 (max)	
Baking rate (t _b , min)	8 (a)		16 (c)	0 (min)	13 (max)	

Table 2. Full factorial central composite design of experiments dataset and correspondent analytical results for screening variables effects on DON levels within the bread-making process steps
- pilot scale plant -

			Fermentation stage			Baking stage			
Experiment	DON in flour	Rate	Temperature	DON in fermented Ra		Temperature	DON in bread		
Number	(µg/Kg d.m.)	(min)	(°C)	dough (µg/Kg d.m.)	(min)	(°C)	(µg/Kg d.m.)		
1	160 ± 15	85	30	187 ± 11	8	180	211 ± 15		
2	967 ± 49	45	30	851 ± 53	8	180	963 ± 40		
3	160 ± 15	45	40	223 ± 23	8	180	216 ± 18		
4	100 ± 14	65	40	152 ± 17	8	180	159 ± 14		
5	967 ± 49	85	40	998 ± 40	8	180	931 ± 90		
6	160 ± 15	65	30	186 ± 16	8	210	198 ± 31		
7	100 ± 14	45	30	129 ± 26	8	210	145 ± 14		
8	967 ± 49	85	30	927 ± 70	8	210	1004 ± 137		
9	160 ± 15	85	40	221 ± 20	8	210	241 ± 23		
10	967 ± 49	45	40	919 ± 33	8	210	960 ± 42		
11	967 ± 49	65	40	820 ± 55	8	210	754 ± 57		
12	160 ± 15	45	30	235 ± 22	16	180	243 ± 16		
13	100 ± 14	85	30	167 ± 24	16	180	166 ± 15		
14	967 ± 49	85	30	899 ± 62	16	180	1000 ± 121		
15	160 ± 15	85	40	224 ± 31	16	180	246 ± 10		
16	967 ± 49	45	40	875 ± 95	16	180	980 ± 111		
17	160 ± 15	85	30	215 ± 20	16	210	227 ± 13		
18	967 ± 49	45	30	940 ± 21	16	210	951 ± 69		
19	160 ± 15	45	40	186 ± 14	16	210	208 ± 15		
20	100 ± 14	65	40	167 ± 13	16	210	192 ± 22		
21	967 ± 49	85	40	993 ± 47	16	210	981 ± 43		
22	100 ± 14	65	40	128 ± 22	16	210	134 ± 12		
23	100 ± 14	65	40	148 ± 12	16	210	159 ± 12		
24	100 ± 14	65	40	136 ± 13	16	210	140 ± 13		

Table 3. Design of experiments dataset and correspondent analytical results for screening variables effects on DON levels within the bread-making process steps

- industrial scale plant -

		Fermentation stage		Baking stage		
Experiment	DON in flour	Rate	Temperature	Rate Temperature		DON in bread
Number	(µg/Kg d.m.)	(min)	(° C)	(min)	(°C)	(µg/Kg d.m.)
1	333 ± 24	56	32	0	30	275±13
2	333 ± 24	56	32	3	200	270±18
3	333 ± 24	56	32	3	225	302±19
4	333 ± 24	56	32	3	170	308±23
5	333 ± 24	56	32	6	200	299±18
6	333 ± 24	56	32	6	225	307±18
7	333 ± 24	56	32	6	170	318±17
8	333 ± 24	56	32	9	200	276±16
9	333 ± 24	56	32	9	225	287±18
10	333 ± 24	56	32	9	170	291±17
11	333 ± 24	56	32	11	200	274±10
12	333 ± 24	56	32	11	225	306±18
13	333 ± 24	56	32	11	170	313±17
14	333 ± 24	56	32	13	200	304±16
15	333 ± 24	56	32	13	225	314±18
16	333 ± 24	56	32	13	170	293±19
17	333 ± 24	56	32	9	225	303±15
18	333 ± 24	56	32	9	225	289±17
19	333 ± 24	56	32	9	225	312±22

Table 4. LC-MS/MS parameters for detection and quantification of DON and (¹³C₁₅)-DON, adducts and internal standard in ESI-MRM mode.

		Retention	Parent ion	Fragments	Normalized
Barilla Food		time (min)	m/z	monitored m/z	Collision Energy (%)
Research Labs	[DON+CH ₃ COO] ⁻	5.7	355	295, 265	24
	$[(^{13}C_{15})$ -DON +CH ₃ COO] ⁻	5.7	370	310, 290	24
		Retention	Parent ion	Fragments	Collision Energy
Food Chemistry Labs		time (min)	m/z	monitored m/z	(eV)
University of Parma	[DON+CH ₃ COO] ⁻	6.4	355	295, 265, 59	12, 15, 15
	$[(^{13}C_{15})-DON + CH_3COO]^{-1}$	6.4	370	310, 279, 59	12, 15, 15

нъу-иом +CH₃COO][•] 6.4 <u>370</u> 310, 279, 59



Figure 1: Scheme of the bread-making process.



Figure 2: Variable Important Plot (VIP) obtained for the DoE dataset in pilot-scale bread-making experiments. The labeling of the X axis reports abbreviations for the terms "baking" (bak), fermentation (ferm) and "Temperature" (Temp).



Figure 3: Contour maps obtained for pilot-scale bread-making experiments performed using a high level DON contaminated flour (a) or a medium-low DON contaminated flour (b).



Figure 4: Comparison of the average DON levels (standard deviation is represented by the error bars in the graph) found in the raw flour, in the fermented dough and in the final bread produced either in the pilot-scale (left side) or industrial-scale (right side) experiments: (**) indicates a significative difference (Tukey test, $\alpha = 0.05$, p < 0.01).



Figure 5: Changes in DON concentration during the industrial baking stage (a) and temperature variation recorded in the oven and in the loaf crumb during the baking process (b).