



HAL
open science

Radiation damage in diopside and calcite crystals from uranothorianite inclusions.

Anne-Magali Seydoux-Guillaume, Jean-Marc Montel, Richard Wirth, Bernard Moine

► **To cite this version:**

Anne-Magali Seydoux-Guillaume, Jean-Marc Montel, Richard Wirth, Bernard Moine. Radiation damage in diopside and calcite crystals from uranothorianite inclusions.. *Chemical Geology*, 2009, 261 (3-4), pp.318-332. 10.1016/j.chemgeo.2008.04.013 . hal-00606536

HAL Id: hal-00606536

<https://hal.science/hal-00606536v1>

Submitted on 6 Jul 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Table 1. Compositions (in wt%) of uranothorianite (UTh), diopside (Cpx), calcite (Cc) and sheet silicate (φ) from figure 2A obtained by EMP.

# (Fig. 2A)	Uranothorianite (UTh)					Sheet silicate (φ)				Diopside (Cpx)				Calcite (Cc)
	1	2	12	13	14	3	4	5	6	7	8	9	10	11
Na ₂ O	0.00	0.00	0.08	0.00	0.00	0.07	0.00	0.00	0.00	0.12	0.22	0.21	0.29	0.00
MgO	0.00	0.00	0.00	0.01	0.00	10.56	14.02	15.50	13.75	13.79	13.72	14.05	13.99	0.66
Al ₂ O ₃	0.00	0.00	0.00	0.00	0.00	19.05	18.42	18.75	19.06	8.22	8.19	8.38	8.35	0.00
SiO ₂	0.00	0.39	0.00	0.01	0.00	43.58	39.52	33.68	43.81	48.73	48.70	49.27	48.67	0.04
K ₂ O	0.10	0.03	0.05	0.04	0.11	0.21	0.10	0.03	0.20	0.00	0.02	0.00	0.00	0.00
CaO	0.19	0.25	0.16	0.11	0.16	2.26	1.87	1.94	2.34	25.03	25.38	25.00	25.07	55.95
TiO ₂	0.00	0.00	0.00	0.00	0.00	0.25	0.18	0.09	0.24	0.74	0.72	0.83	0.68	0.00
Cr ₂ O ₃	0.04	0.00	0.07	0.00	0.01	0.00	0.04	0.02	0.00	0.00	0.00	0.00	0.02	0.02
MnO	0.00	0.07	0.07	0.05	0.02	0.13	0.01	0.23	0.10	0.11	0.05	0.00	0.04	0.02
FeO	0.12	0.00	0.00	0.01	0.01	6.28	7.55	14.45	7.25	2.36	2.26	2.23	2.50	0.19
PbO	3.77	3.74	4.10	4.33	3.92	0.06	0.17	0.14	0.00	0.25	0.00	0.00	0.05	0.18
ThO ₂	66.37	64.80	66.33	66.12	66.99	0.04	0.68	0.10	0.00	0.03	0.00	0.06	0.08	0.00
UO ₂	29.24	28.50	30.27	29.76	28.92	0.10	0.00	0.00	0.00	0.00	0.06	0.00	0.01	0.00
Total	99.83	97.78	101.14	100.44	100.15	82.57	82.56	84.93	86.75	99.38	99.31	100.03	99.75	57.06

EMP operating at 15 kV, 20 nA. Standards are : albite (NaK α), periclase (MgK α), corundum (AlK α), wollastonite (Si and CaK α), sanidine (KK α), perovskite (Ti and MnK α), Cr₂O₃ (CrK α), Hematite (FeK α), synthetic Pb-glass (PbM β), synthetic ThO₂-ceramic (ThM α) and synthetic UO₂-ceramic (UM β).