

The Interdisciplinary Role of Space Geodesy - Revisited Reiner Rummel

▶ To cite this version:

Reiner Rummel. The Interdisciplinary Role of Space Geodesy - Revisited. Journal of Geodynamics, 2010, 49 (3-4), pp.112. 10.1016/j.jog.2009.10.006 . hal-00615309

HAL Id: hal-00615309 https://hal.science/hal-00615309

Submitted on 19 Aug 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Accepted Manuscript

Title: The Interdisciplinary Role of Space Geodesy - Revisited

Author: Reiner Rummel

PII:	S0264-3707(09)00117-3
DOI:	doi:10.1016/j.jog.2009.10.006
Reference:	GEOD 944
To appear in:	Journal of Geodynamics
Received date:	26-1-2009
Revised date:	4-8-2009
Accepted date:	6-10-2009



Please cite this article as: Rummel, R., The Interdisciplinary Role of Space Geodesy – Revisited, *Journal of Geodynamics* (2008), doi:10.1016/j.jog.2009.10.006

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting proof before it is published in its final form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

1 The Interdisciplinary Role of Space Geodesy – Revisited

- 2 Reiner Rummel
- 3 Institute of Astronomical and Physical Geodesy (IAPG)
- 4 Technische Universität München
- 5 80290 München
- 6 Germany
- 7 <u>rummel@bv.tum.de</u>
- 8

Abstract. In 1988 the interdisciplinary role of space geodesy has been discussed by 9 a prominent group of leaders in the fields of geodesy and geophysics at an 10 international workshop in Erice, (Mueller I I, S Zerbini, 1989). The workshop may be 11 viewed as the starting point of a new era of geodesy as a discipline of Earth 12 13 sciences. Since then enormous progress has been made in geodesy in terms of satellite and sensor systems, observation techniques, data processing, modelling 14 15 and interpretation. The establishment of a Global Geodetic Observing System 16 (GGOS) which is currently underway is a milestone in this respect. We gener served as an important role model for the definition of GGOS. In turn, Wegener will benefit 17 18 from becoming a regional entity of GGOS.

What are the great challenges of the realisation of a 10⁻⁹ global integrated observing system? Geodesy is potentially able to provide – in the narrow sense of the words – "metric and weight" to global studies of geo-processes. It certainly can meet this expectation if a number of fundamental challenges, related to issues such as the international embedding of GGOS, the realisation of further satellite missions and some open scientific questions can be solved. Geodesy is measurement driven. This is an important asset when trying to study the Earth as a system. However its

26 guideline must be: "What are the right and most important observables to deal with27 the open scientific questions?"

28

Key words: geodesy, satellite geodesy, global observing system, global geodetic
observing system

- 31
- 32

Historical introduction. Since about 150 years geodesy can be regarded as an 33 independent discipline of science. BAEYER's memorandum about the size and figure 34 35 of the Earth "Über die Größe und Figur der Erde" (1861) may be seen as a starting point, even though important geodetic work had been done before by famous 36 37 scientists such as NEWTON, LAPLACE, GAUSS, BESSEL. But their work was not referred 38 to as geodesy and they did not regard themselves as geodesists. BAEYER's initiative 39 resulted in an extension and unification of existing triangulation and levelling 40 networks covering central Europe. This work was then expanded to the whole of 41 Europe, before its transition to an international effort with the aim to determine the global figure of the Earth. It was one of the first international projects in science and 42 43 the root of what is today the International Association of Geodesy (IAG), cf. (TORGE, 2001). 44

Last year, in 2007, 50 years of space age was celebrated. With the launch of Sputnik 1 on October 4, 1957 (and shortly after of Sputnik 2) modern space age began. Already these two satellites had a fundamental effect on geodesy. Almost instantaneously a large part of 100 years of diligent geodetic work dedicated to the determination of the figure of the Earth became out-dated. From measuring the precession of satellite orbits the Earth's flattening could be determined much more accurately than with classical astro-geodetic work, compare e.g. King-Hele, 1992.

52 Satellites opened new horizons for geodesy and no other discipline is known to me 53 that has benefited more profoundly from space techniques. Positioning, gravity field determination, Earth rotation monitoring and geodetic remote sensing can be done 54 55 much more accurately, completely and efficiently from space. Geodesy became truly global and three dimensional. Oceans, a "terra incognita" of the classical times 56 57 turned with satellites into an area of great geodetic activity. Classical geodetic 58 techniques did not allow the accurate measurement of zenith angles, due to 59 atmospheric refraction. From space the vertical dimension of the Earth's surface can be determined almost as accurately as the horizontal components. Progress of space 60 61 geodesy was fast and had a great impact. Hand in hand with the rapid development of geodetic space techniques geosciences became more and more interested in 62 geodetic work. 63

64 The Erice workshop about the interdisciplinary role of space geodesy. Twenty years ago some of the most outstanding geodesists, Earth scientists and physicists 65 were invited to a workshop in Erice/Sicily. It dealt with the interdisciplinary role of 66 space geodesy and was organized by Ivan I MUELLER and Susanna ZERBINI (1989). 67 68 At this workshop the role of space geodesy for Earth sciences was carefully analysed 69 and recommendations formulated for the future. The introductory chapter to the book by W M KAULA is especially worthwhile to read. He discusses five selected fields of 70 71 Earth science and the possible role of space geodetic techniques for them. The five 72 fields are (1) Earth rotation and core-mantle interaction, (2) mantle convection, (3) 73 regional tectonics and earthquakes, (4) ocean dynamics and (5) Venus-Earth 74 differences. The workshop in Erice marks the beginning of the era of space geodesy 75 as being a discipline of Earth sciences.

76 **Developments of the recent past.** In recent years the general emphasis of Earth 77 sciences has moved towards Climate Change and Earth System Science.

78 Awareness grew that we need a much better understanding of the Earth as a system, 79 of solar radiation as its driving force, of the thermal back radiation and how it is affected by even tiny changes in chemical composition of the atmosphere, and last 80 81 not least of the impact of man. One fundamental deficiency became particularly evident in the course of the preparation of the last report of the Intergovernmental 82 Panel on Climate Change (Climate Change, 2007) and has been addressed in 83 84 several articles in Science and Nature, see (Hogan, 2005) and the articles quoted 85 there: There is a clear lack of observations (ibid, 2005). Space geodesy is able to provide important new and unique data to Global Change research by measuring 86 87 mass and energy transport processes in the Earth system. Ben CHAO (2003) wrote:" After three decades and three orders of magnitude of advances, space geodesy is 88 89 poised for prime time in observing the integrated mass transports that take place in 90 the Earth system, from the high atmosphere to the deep interior of the core. As such 91 space geodesy has become a new remote sensing tool, in monitoring climatic and 92 geophysical changes with ever increasing sensitivity and resolution." One can claim 93 that geodesy, by merging geometry, Earth rotation, gravity and geoid, is in a position to provide "metric and weight" to Earth system research. Before this background the 94 95 establishment of the Global Geodetic Observing System (GGOS) is the right step at the right time. The underlying concept is simple and well described by the scheme 96 97 shown in figure 1 and due to ROTHACHER, see (RUMMEL et al., 2005; see also PLAG & 98 PEARLMAN, 2007).

99

100 Figure 1

101

102 GGOS will combine the three fundamental pillars of geodesy: the measurement of 103 the shape of the Earth, Earth rotation and the Earth's gravity field and geoid. The

objective is to realize this with a relative precision level of 10⁻⁹ in one unified Earth 104 105 fixed reference system and to keep this system stable over decades. Where does 106 such a demanding requirement come from? In geosciences one usually deals with 107 estimates accurate to only a few percent. Global change parameters are small und 108 their temporal changes are slow and even smaller. In general they cannot be observed directly but have to be derived from a combination of several measurement 109 110 systems and models. In order to be able to analyze them as a global process they 111 have to be scaled relative to the dimension of the Earth. Let us take an example. Sea level at an arbitrary tide gauge may vary by a few meters, due to tides and storm 112 113 surges. Measurement of sea level change with a precision of a few mm requires therefore a relative precision of 10⁻³ at this particular station. Local sea level 114 monitoring can be transformed into a global monitoring system by satellite systems 115 116 such as altimetry and GPS. Only then a global process can be deduced from local 117 tide gauge records. In order to achieve cm- or mm-precision with satellite systems 118 globally, orbit determination and altimetric measurements have to be delivered with a 119 relative precision of 1 ppb.

120 In order to meet the goals set for GGOS a series of rather fundamental geodetic 121 problems have to be dealt with. The three pillars of geodesy, geometry, Earth rotation 122 and gravity have to be expressed in one and the same Earth fixed reference system 123 with millimetre precision and stability (of the frame) has to be guaranteed over 124 decades. This requires the space as well as the ground segments to function as one 125 homogeneous entity as if all observations were done in one observatory 126 encompassing the Earth. Each observation contains a superposition of a variety of 127 effects, related to ionosphere, atmosphere, oceans, ice shields and solid Earth. In 128 order to employ them for Earth system research strategies have to be developed for 129 their separation and quantification by analysing their spatial, temporal and spectral

130 characteristics. Satellite measurements represent time series along their orbit. Via 131 the Earth's rotation and the choice of the satellite orbit elements these time series are 132 related to a spatial and temporal sampling of the Earth. The reconstruction of the 133 temporal and spatial geophysical phenomena poses a complicated problem of 134 aliasing and inversion. The current investigations of the global water cycle or of the 135 ice mass balance in Greenland and Antarctica from GRACE gravimetry are exactly 136 problems of this type. The inclusion of terrestrial and airborne data, such as surface 137 loading, ocean bottom pressure, tide gauges, gravimetry or altimetry may certainly help. However, this step is not easy either, because terrestrial measurements are 138 139 affected by local influences and exhibit a spectral sensitivity quite different from that of satellite observations. Probably the most effective support to de-aliasing and 140 141 separation of geophysical phenomena is the inclusion of prior information, such as 142 models of solid Earth and ocean tides, atmosphere, oceans, ice, hydrology or glacial 143 isostatic adjustment, however only if they are introduced consistently for all 144 techniques of the observing system. Important work towards these goals is currently 145 underway and we see geodetic techniques used much more widely in the various Earth disciplines. 146

WEGENER developed over the years from an almost mono-disciplinary project to regional multi-disciplinary activity combining a large variety of geodetic and nongeodetic measurements techniques and involving all geo-disciplines relevant to its objectives. It is therefore an excellent example on how GGOS could operate on a global scale.

A look into the future. With an enormous pace space geodesy has made fantastic progress over the past 50 years. Do we have to fear this development to slow down in the near future? Let me try to look into the future..

155 Firstly, under what general boundary conditions will space geodesy have to operate 156 in the years to come? Global Change activities are mostly organized on an 157 intergovernmental level in international programs such as INSPIRE, IGOS or CEOS. 158 GGOS must therefore strive to be integrated into such programs in order to attain the 159 necessary impact and recognition. It is advisable that geodesy tries to activate its 160 national governmental agencies towards this goal, in particular those agencies 161 supporting already for years the geodetic scientific services under the umbrella of the 162 International Association of Geodesy (IAG). Global Change is discussed nowadays in terms of so-called essential climate variables (ecv's). GGOS has to analyze in what 163 164 way it can contribute to the determination and monitoring of the identified ecv's. To a large extent the major Earth oriented satellite programs of NASA and ESA are 165 166 defined already for the next 5 to 10 years. If missions are missing which are essential 167 for the progress of space geodesy, GGOS has to develop a strategy on how to get 168 such missing elements approved by one of the space agencies.

169 What are the geodetic priorities and how can geodesy take advantage of non-170 geodetic space activities? Let me formulate a number of questions.

171 Several GNSSs will be available in parallel in the near future, the GPS, GLONASS, 172 GALILEO, COMPASS and the associated augmentation systems. What can we gain 173 from their combined use, what for example from their improved clocks? If one could 174 establish inter-satellite ranging, one would get an orbiting precision polyhedron. What 175 would we gain from such a constellation?

Let us assume geodesy would push for a third LAGEOS (e.g. counter rotating as proposed by Professor BERTOTTI a long time ago). Would it further strengthen our terrestrial reference system, e.g. its long term stability and the low gravity harmonics? It would certainly be an important bridge to gravitational physics.

180 After the great success of GRACE further gravimetric satellite missions are urgently 181 needed to secure continuity of the measured time series, if mass transport should 182 remain a central gravimetric theme. How should such missions look like? Compare 183 also, KOOP and RUMMEL, 2006. In parallel the development of significantly improved 184 geophysical "background" models of ocean tides, and coupled atmosphere-ocean 185 circulation must have high priority on the geodetic agenda. They would serve the de-186 aliasing and separation of geophysical effect. Only then one could fully benefit from 187 improved technological concepts such as inter-satellite laser link, drag free system, proof mass-to-proof mass measurement and satellite configuration flights. 188

189 Would mini-satellites be useful, e.g. for atmospheric sounding or for a satellite based 190 synchronization of two or several techniques, such as GPS, DORIS, VLBI and laser 191 ranging?

The GNSS signal emitters and receivers are distributed over three spatial layers: the GNSS satellites at high altitude, a large number of low Earth orbiters (LEO's) equipped with GNSS receivers between 300 and 1000 km altitude and many permanent receiving stations on ground. Could this add, literally, a further dimension to GNSS atmospheric sounding and to the modeling of the wet troposphere?

Several space agencies are preparing missions to our moon. A lander mission could be used to deploy geodetic laser transponders. This would greatly facilitate and improve lunar laser ranging and strengthen its role among the geodetic space techniques and for gravitational physics. In addition, the far-side gravity field of the moon is still not known very well; thus any mission opportunity for satellite lunar gravimetry would be welcome.

What are the technological building blocks of future space geodetic missions? A new generation of ultra-high-precision clocks in space and on ground, such as optical clocks, active transponders for tracking systems, GNSS reflectometry and new types

of accelerometers may soon become available for space geodesy. These could havea tremendous impact on the development of geodesy.

This leads to the question about the challenges and opportunities of future space geodesy. The three traditional enemies are non-gravitational forces acting on satellites, atmospheric refraction and local ties.

211 Uncertainties and gross errors in local ties between measurements systems sound 212 like a trivial question of diligence and organisation but strangely enough this problem 213 is not yet globally resolved. Great progress has been made in measuring and 214 modelling local tropospheric effects for the various ground receiver systems. 215 However a uniform and consistent approach for all techniques is still not routine and 216 should be pursued with high priority. Modelling of the satellite environment (residual 217 air drag and solar radiation) is still far from solved and should also be given high 218 priority. Possibly, low Earth orbiters without accelerometers might be used for gravity 219 field monitoring in the future.

220 What about clocks, time measurement, synchronisation and transfer? The great 221 progress of the past in space geodesy can be intimately linked to a corresponding progress in the measurement of travel times and time keeping. Important new 222 developments have lead to optical clocks (and counters) at a precision level of 10⁻¹⁸ 223 in the laboratory. Precisions better than 10⁻¹⁶ can and will have important implications 224 225 for geodesy. The materialisation of a global unified height system could be achieved using the relativistic dependence of time on the gravitational potential. Time 226 227 synchronisation at this level of precision via satellites would open several new 228 perspectives for geodesy. Time measurements made by satellites might be 229 considered as real observables and not only as a device for "tick marking" 230 measurements. One could start dreaming of the direct measurement of gravitational

potential differences between satellites as well as between satellites and groundstations.

During the pioneering days of satellite geodesy direction measurement with cameras to satellites against the stellar background was one of the primary techniques. With the advent of laser and radio tracking range and range rate replaced angular measurements which always suffered from the effect of atmospheric refraction. But are angular measurements really obsolete for ever? Should one not think about new concepts of angular measurement, e.g. with synchronised twin laser telescopes, and about what their impact would be?

Finally, considering all this amazing progress one can wonder whether there is not a natural limit of precision beyond which further progress of geodetic space techniques does not make sense anymore because the ever increasing precisions cannot anymore be reproduced in nature. Is 10⁻⁹ already such a limit or 10⁻¹⁰?

244 Concluding remarks. In the quoted book "The interdisciplinary role of space 245 geodesy" (MUELLER and ZERBINI, 1999), KAULA wrote on page 9: "... Theoreticians 246 get the impression that experimenters operate according to problem definitions that are a decade or more obsolete, while experimenters probably think that theoreticians 247 248 are sporadic in their attention and underestimate technical difficulties. Better 249 communication is particularly important now that measurement capabilities can yield 250 valuable constraints, provided that they are applied in sufficient detail". This is a 251 remark about the relationship between theory and experiment. KAULA, being both an 252 outstanding geodesist and geophysicist, saw that there was a problem in this 253 relationship at that time. Traditionally geodesy is very "measurement and technique 254 driven". Even during the definition phase of GGOS the underlying rationale started 255 from the observing system and not so much from the Earth science problems that 256 could be addressed with such a system. Such an approach may be logical but it is

essentially wrong. Experiments have to be derived from theory and new hypotheses from the experiments; to be successful an intimate relationship between the two must exist. From this I conclude that geodesy and geodesists have to get much deeper into Earth sciences. Geodesists have to have a profound understanding of the geophysical problems. Only then the fantastic tools of modern space geodesy will develop their full potential for the understanding of our Earth as a system. This poses a great challenge to geodetic education and science.

Acknowledgement: Several coffee time discussions with Gerhard Beutler and Urs
Hugentobler are gratefully acknowledged.

266

267 References.

- 268 Baeyer, J.J. : Über die Größe und Figur der Erde. Georg Reiner Verlag, Berlin, 1861
- 269 Chao, B. F.: Geodesy is not Just for Static Measurements Anymore, EOS
- 270 Transactions, American Geophysical Union, 84, 16, 145, 2003.
- 271 *Climate Change 2007* The Physical Science Basis, Contribution of Working Group
- 1 to the Fourth Assessment Report of the IPCC, Cambridge University Press, 2007.
- Hogan, J.: Warming Debate Highlights Poor Data, Nature, 436, 896, 2005.
- King-Hele, D.: A tapestry of orbits, Cambridge University Press, 1992.
- 275 Koop, R., R. Rummel (Eds.): The Future of Satellite Gravimetry, report of the
- workshop on the future of satellite gravimetry on April 12-13, 2007 at ESTEC
- 277 Noordwijk, TUM Institute for Advanced Study, München, 2008
- 278 Mueller, I.I., S. Zerbini (Eds.): *The Interdisciplinary Role of Space Geodesy*, Lecture
- 279 Notes in Earth Sciences, 22, Springer, Berlin, 1989
- 280 Plag, H-P., M. Pearlman (Eds.): *The Global Geodetic Observing System: Meeting the*
- 281 Requirements of a Global Society on a Changing Planet in 2020 Reference
- 282 *Document*, International Association of Geodesy, 2007

- 283 Rummel, R., M. Rothacher, G. Beutler: Integrated Global Geodetic Observing
- 284 System (IGGOS) Science Rationale, Journal of Geodynamics 40, 357-362, 2005
- 285 Torge, W.: *Geodesy*, 3rd edition, de Gruyter, Berlin, 2001
- 286
- 287

Figure 1: Geodetic space techniques determine the shape of the Earth, Earth rotation and the Earth's gravity field and geoid. From these three geodetic entities a large variety of Earth system parameters are derived. In turn, any improvement of Earth parameters serves a better modeling of geometry, Earth rotation and gravity and a more accurate modeling of space geodetic measurements.

CeR

293



- 1
- 2
- 3

Figure 1: Geodetic space techniques determine the shape of the Earth, Earth rotation and the Earth's gravity field and geoid. From these three geodetic entities a large variety of Earth system parameters are derived. In turn, any improvement of Earth parameters serves a better modeling of geometry, Earth rotation and gravity and a more accurate modeling of space geodetic measurements.

9