



Modeling the cerebral activity with dynamic probabilistic networks

**Vincent Labatut
Josette Pastor
Inserm *unité 455***

Context

- cognitive/ sensorimotor functions implemented by large-scale cerebral networks
- networks identified with activation studies and neuroimaging data
- how the activation derives from the function performance is still largely unknown

Goals

- answer **how** activation derives from information processing in large-scale networks
- provide an explicit **modeling tool** for the **interpretation** of neuroimaging data

Method



activation



simulation

Methods

activation



simulation

stimulation


**stimuli
perception**

**information
processing**


**observed
activity**

Methods

activation




simulation



stimulation

stimuli perception





information processing





observed activity

Methods

activation



simulation



stimulation

**stimuli
perception**

**information
processing**

**observed
activity**




Modeling tool

- based on **dynamic Bayesian networks**
- specific **information** representation
- specific **propagation** and **learning** mechanisms


Modeling tool: information representation

- **information** = abstraction of the neural population able to process it




- **magnitude** : global activation **level**
- **type : pattern** of activated neurons

Modeling tool: DBN




- **directed** networked structure

Modeling tool: DBN




- **directed** networked structure
- **probabilistic, causal** and **nonlinear** relationships

Modeling tool: DBN




- **directed** networked structure
- **probabilistic, causal** and **nonlinear** relationships
- **differentiated** nodes

Modeling tool: DBN




- **directed** networked structure
- **probabilistic, causal** and **nonlinear** relationships
- **differentiated** nodes
- **explicit** and **discrete** representation of **time**

Modeling tool: DBN




- **directed** networked structure
- **probabilistic, causal** and **nonlinear** relationships
- **differentiated** nodes
- **explicit** and **discrete** representation of **time**

Modeling tool: LSAN




Modeling tool: LSAN




A cognitive application: description

- **PET** study by Fox & Raichle (1985)
- **Visual** stimulus rate modulates visual cortex activation: activation grows until 7,8 Hz, then fades and becomes stable
 > why ?
- Model involving the **striate cortex** (primary visual cortex) and the **thalamus**
- Hypotheses implemented in the model : **habituation** and **refractory period** at the regional level


A cognitive application: model




A cognitive application: model




A cognitive application: model




A cognitive application: model




A cognitive application: model




A cognitive application: model




A cognitive application: model




A cognitive application: model




A cognitive application: model



A cognitive application: results



A cognitive application: results




A clinical application: description

- **fMRI** study by Ruff *et al.* (2001)
- **Phonemic categorization** process between two phonetically close syllables /pa/ and /ta/: differences between **normal** and **dyslexic** subjects activations > why ?
- Model of the **right temporal superior gyrus** (early processing of auditory stimuli)
- Hypothesis implemented in the model :
 - existence of **specialized** phonemic processors
 - near no **lateral inhibitions** in **dyslexic** subjects

A clinical application: results


normal subjects



/pa/: /pa/: /pa/: /pa/: /pa/:
62% 53% 44% 35% 26%

A clinical application: results


normal subjects



runs

A clinical application: results

normal subjects




runs


/pa/: /pa/: /pa/: /pa/: /pa/:
62% 53% 44% 35% 26%

A clinical application: results

normal subjects




dyslexic subjects




— Theoretical
rest
— Experiment

runs


A clinical application: normal model




A clinical application: normal model



A clinical application: normal model




A clinical application: dyslexic model




A clinical application: results

normal subjects



dyslexic subjects




— Theoretical
rest
— Experiment


runs

A clinical application: results

normal subjects



dyslexic subjects



- . Theoretical rest
- Experiment
- Simulation

runs

/pa/: /pa/: /pa/: /pa/: /pa/:
62% 53% 44% 35% 26%

/pa/: /pa/: /pa/: /pa/: /pa/:
62% 53% 44% 35% 26%

Perspectives

- Inclusion of more **biological plausibility**
- Make the models **independent** of the used data acquisition **technique** by using **interface** models able to translate cerebral information processing variables into neuroimaging results