



Refactoring Composite to Visitor and Inverse Transformation in Java

Akram Ajouli, Julien Cohen

► To cite this version:

Akram Ajouli, Julien Cohen. Refactoring Composite to Visitor and Inverse Transformation in Java. 2012. hal-00652872v2

HAL Id: hal-00652872

<https://hal.science/hal-00652872v2>

Submitted on 30 Nov 2012 (v2), last revised 1 Jul 2013 (v3)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Refactoring Composite to Visitor and Inverse Transformation in Java*

Akram Ajouli¹ & Julien Cohen²

1: INRIA – ASCOLA team (EMN - INRIA - LINA)

2: Université de Nantes – LINA (UMR 6241, CNRS, Univ. Nantes, EMN)

We describe how to use refactoring tools to transform a Java program conforming to the Composite design pattern into a program conforming to the Visitor design pattern with the same external behavior. We also describe the inverse transformation. We use the refactoring tools provided by IntelliJ IDEA and Eclipse.

Contents

1	Introduction	2
2	General Approach	3
2.1	Guidelines in the Literature	3
2.2	Automation	4
3	Composite↔Visitor Transformation Scheme	7
3.1	Composite→Visitor Transformation	7
3.2	Visitor→Composite Transformation	9
3.3	Result after Round Trip Transformation	13
4	Variants of Transformations for Various Pattern Instances	16
4.1	Methods with Parameters	16
4.1.1	Composite→Visitor Transformation	16
4.1.2	Visitor Program	17
4.1.3	Visitor→Composite Transformation	17
4.2	Methods Returning Values	17
4.2.1	Composite→Visitor Transformation	18
4.2.2	Visitor Program	18
4.2.3	Visitor→Composite Transformation	18
4.3	Interface instead of Abstract class in the Composite structure	18
4.3.1	Composite→Visitor Transformation	18
4.3.2	Visitor Program	22
4.3.3	Visitor→Composite Transformation	22
4.4	Class Hierarchies with Several Levels	22
4.4.1	Composite→Visitor Transformation	22
4.4.2	Visitor Program	23
4.4.3	Visitor→Composite Transformation	23
5	Application to JHotDraw	26
6	Related work	26
6.1	Refactoring to Patterns	26
6.2	Building Complex Refactoring Operations	27
6.3	Design Patterns Discovery	27
7	Conclusion	27
References		27

*This is the version 2 of the report. The main difference with the version 1 is the description of the computation of the minimum precondition for the base round-trip transformation (see App. B).

A Refactoring Operations	28
A.1 CreateEmptyClass	28
A.2 CreateIndirectionInSuperClass	31
A.3 AddParameter	34
A.4 AddParameterWithReuse	34
A.5 AddParameterWithDelegate	35
A.6 MoveMethod	35
A.7 MoveMethodWithDelegate	35
A.8 RenameMethod	36
A.8.1 RenameInHierarchyNoOverloading	37
A.8.2 RenameOverloadedMethodInHierarchy	38
A.8.3 RenameDelegatorWithOverloading	39
A.9 ExtractSuperClass	41
A.9.1 ExtractSuperClassWithoutPullUp	42
A.10 GeneraliseParameter	42
A.11 MergeDuplicateMethods	44
A.12 ReplaceMethodcodeDuplicatesInverter	45
A.13 SafeDeleteDelegatorOverriding	45
A.14 PullUpAbstract	46
A.15 PullUpImplementation	47
A.16 PullUpWithGenerics	48
A.17 InlineAndDelete	49
A.18 InlineMethodInvocations	50
A.19 AddSpecializedMethodInHierarchy (Composed)	50
A.20 DuplicateMethodInHierarchy	51
A.21 DeleteMethodInHierarchy	53
A.22 PushDownAll	55
A.23 PushDownImplementation	57
A.24 PushDownNotRedefinedMethod	58
A.25 ReplaceMethodDuplication	59
A.26 DeleteClass	59
A.27 ExtractGeneralMethod	61
A.28 InlineClass	61
A.29 SpecialiseParameter	61

B Preconditions composition	62
------------------------------------	-----------

1 Introduction

Composite and Visitor patterns have dual properties with respect to modularity: while the Composite pattern (as well as the Interpreter pattern and classic class hierarchies) provides modularity along subtypes and leaves operation definitions crosscut, the Visitor pattern provides modularity along operations and leaves behavior definitions crosscutting with respect to subtypes [GHJV95].

One solution to have modularity along operations *and* subtypes would be to be able to transform automatically a program conforming to the Composite pattern into a program with the same behavior, but which structure would conform to the Visitor pattern, and vice-versa [CDA12].

Chains of elementary refactorings can be used to make design patterns appear [OCN99, Ker04], for instance to introduce the Visitor pattern [MT04, Ker04], or to replace the Visitor pattern by the Interpreter pattern [HKVDSV11]. However, such transformations are not fully automated yet, and our proposal of navigation between several architectures for a same program [CDA12] is not currently workable.

In this report we do preliminary work before automating refactoring based Composite↔Visitor transformations:

1. We give chains of refactoring operations that provide Composite→Visitor and Visitor→Composite transformations for a simple Java program. Each refactoring operation is supported by at least one refactoring tool.
2. We explain how to use the refactoring tools IntelliJ IDEA and Eclipse to perform the needed refactoring operations (composition of several operations of the tools, specific options, applying some operations before being able to perform another one, bugs to overcome, missing operations...).
3. We study variants of the transformations for several variations in the implementation of the patterns.

Our algorithms are validated on a running toy example and on the JHotDraw program [GI].

2 General Approach

We consider the Java program of Fig. 1. It contains a classic class hierarchy: the abstract class *Graphic* has two subclasses, *Square* and *Ellipse*, and two methods, *print* and *prettyprint* implemented in the subclasses. We also consider that two classes *Printer* and *PrettyPrinter* already exist in the program: they will become visitor subclasses.




Figure 1: Base Program (classic class hierarchy)

In the following algorithms, we make abstraction of the class and method names and number: let LM be the set of traversal functions, LC the set of *concrete* classes in the composite structure, and S the superclass of the composite structure.

Here, $\text{LM} = \{\text{print}, \text{prettyprint}\}$, $\text{LC} = \{\text{Ellipse}, \text{Square}\}$ and $\text{S} = \text{Graphic}$.

We also define a function V that maps a name of visitor class to a name of method. We consider here $V(\text{print}) = \text{Printer}$ and $V(\text{prettyprint}) = \text{PrettyPrinter}$. We also define $\text{LV} = V(\text{LM}) = \{V(m)\}_{m \in \text{LM}}$.

2.1 Guidelines in the Literature

We start by considering some guidelines given in the literature for introducing an instance of the Visitor pattern into a typical object-oriented class hierarchy. We consider the guidelines of Mens and Tourwé [MT04], rephrased in Fig. 2.

1. ForAll m in LM, c in LC do
 Let visitorname = $V(m)$ in
 MoveMethodWithDelegate(c, m, visitorname)
 RenameMethod(visitorname, m, "visit")
 done
2. AddAbstractSuperClass("Visitor", LV)
3. ForAll c in LC do
 PullUpAbstract(LV, "visit", c, "Visitor")
4. ForAll c in LC do
 ExtractMethod(c, LM, "accept")
5. ForAll m in LM do
 PullUpConcrete(LC, m, S)

Figure 2: Simple Class Hierarchy → Visitor transformation [MT04].

To introduce a visitor pattern, the first obvious step is to move the business code¹ from the class hierarchy to visitor classes (in this section, we consider the target classes for the moved methods already exist in the project). This is done in step 1 (Fig. 2). We move the business code but, in order not to change the interface of the class hierarchy, we keep in the class hierarchy some methods with the same profiles as the original ones, which will be delegators to visitor's methods (see *Move Method* in Fowler [Fow99]).

The new methods in visitor classes are named *visit* so that the visitor classes will all be able to implement the abstract class *Visitor*, which is added afterward (step 2). In visitor classes, there is one method *visit* for each concrete class of the class hierarchy LC (with overloading). They are introduced as abstract methods in the *Visitor* class (step 3).

To introduce the double dispatch which is typical of the visitor pattern without changing the interface of the class hierarchy, another delegation is introduced inside the concrete classes of LC (step 4). The delegate method is named *accept*.

Since the initial methods are now delegators to *accept*, the overriding bodies are the same in the concrete classes of LC, and it can be defined once for all in the super class (step 5).

The refactoring results in the program given in Figs. 3 and 4.

2.2 Automation

If we refer to Fowler [Fow99], a refactoring is manual with checks under the responsibility of the programmer. In the same way, the general guidelines given in Fig. 2 must be *interpreted* by someone which will adapt them to his particular program.

We now consider that the programmer uses a refactoring tool. We consider IntelliJ IDEA but the same is also possible with Eclipse with small variations.

Prepare the move. A first problem occurs with the *Move Method* operation. The refactoring tool cannot move instance methods to a class if there is no reference of the destination class in that method (in parameters or in body). The reason is that the receiver object cannot be inferred otherwise (we consider *instance* methods).

Before moving the methods, we have to create delegates for these methods (to keep the initial interface), then add a parameter of the convenient visitor type to the delegates, then move them (see Fig. 5, step 1).

Restore object type after move. In our example, the pretty-print method does not access to any instance variables or methods (see Fig. 1) of the receiver object. In this case, when the *prettyprint* delegate methods are moved, the tool does not make a parameter of type *Ellipse* or *Square* appear in the resulting method.

This is problematic because we want overloaded *visit* methods (it's a design choice, here we could also use different method names) but the lack of these parameters introduces a name clash.

To solve this, it is sufficient to apply the *Add Parameter* refactoring to the methods which have been moved. We do not make this appear into the algorithm of Fig. 5 because we encapsulate this behavior into the *Move Method* operation. We consider *Move Method* is an abstract operation, which can be implemented by a refactoring tool with a single operation or with a composition/chain of several basic operations. We make the correspondence between abstract operation and tool operations in App. A (see App. A.6).

¹We call business code the code that defines the operations, here the bodies of *print* and *prettyprint*, which are spread over several classes (by the means of overriding).

```

abstract class Graphic {

    public void print() {
        accept(new PrintVisitor());
    }

    public void prettyprint() {
        accept(new PrettyPrintVisitor());
    }

    public abstract void accept(Visitor v);
}

```

```

class Square extends Graphic {

    int l;

    public void accept(Visitor v) {
        v.visit(this);
    }
}

```

```

class Ellipse extends Graphic{

    int l1, l2;

    public void accept(Visitor v) {
        v.visit(this);
    }
}

```

Figure 3: Program with Visitor (classic class hierarchy)

```

public abstract class Visitor {
    public abstract void visit(Square square);

    public abstract void visit(Ellipse ellipse);
}

```

```

public class PrintVisitor extends Visitor {
    public void visit(Square square) {
        System.out.print("Square(" + square.l + ")");
    }

    public void visit(Ellipse ellipse) {
        System.out.print("Ellipse: (" + ellipse.l1 + "," + ellipse.l2 + ")");
    }
}

```

```

public class PrettyPrintVisitor extends Visitor {
    public void visit(Square s){
        System.out.print("Square.");
    }

    public void visit(Ellipse e){
        System.out.print("Ellipse.");
    }
}

```

Figure 4: Program with Visitor (classic class hierarchy – visitor part)

1. ForAll (m,param) in LM, c in LC do
 Let visitorname = $V(m)$ in
 AddParameterWithDelegate(c,m,param,visitorname)
 MoveMethod(c, m, param+visitorname, visitorname)
 RenameMethod(visitorname, m,param+c, "visit")
 done
2. ExtractSuperClass(LV, "Visitor") // with *visit* abstract methods
3. ForAll c in LC do
 ExtractGeneralMethod(c, LM, "accept", "Visitor")
4. PullUpAbstract(LC, "accept", "Visitor", S)
5. ForAll m in LM do
 PullUpConcrete(LC, m, S)

Figure 5: Simple Class Hierarchy → Visitor transformation (adapted to IntelliJ IDEA)

ExtractSuperClass. Introducing a new superclass and pulling up methods (steps 2 and 3 of Fig. 2) is known as *Extract Superclass* in Fowler [Fow99]. That composite operations is also available in IntelliJ IDEA and Eclipse. For that reason, we use it in Fig. 5 (step 2).

However, in IntelliJ IDEA, we have had to provide an extension of that operation that applies to several classes simultaneously² (it was already possible in Eclipse).

Extract Method Accept. In the following code (from *Square* or *Ellipse*), the instruction $o.visit(this)$ occurs twice (with a different object o).

```
public void print() {
    new PrintVisitor().visit(this);
}

public void prettyprint() {
    new PrettyPrintVisitor().visit(this);
}
```

That instruction has to be extracted into a method *accept* with o as a parameter, and the occurrences of that expression will be replaced by $accept(o)$.

The tool IntelliJ IDEA will accept to extract a same method for the two instances only after we introduce a same type for the receiver objects. In practice, we first introduce a new local variable for *new PrintVisitor()* (resp. *new PrettyPrintVisitor()*), then change the type of that variable from *PrintVisitor* (resp. *PrettyPrintVisitor*) to *Visitor*, and then the extraction of the method successes (the two instances are replaced by invocations of that method). The operations used in IntelliJ IDEA are *Introduce Variable* and *Type Migration* (as many other refactoring operations *Type Migration* checks that the change is type safe). One would may also find useful to rename the local variables or the parameter of *accept* to *v* or *visitor* (operation *Rename*).

The local variables can be inlined afterward (operation *Inline*).

Note that the task of making *accept* act on *Visitors* is left implied in the guidelines of Mens and Tourwé (Fig 2). This task is not explained either by Fowler (*Extract Method* [Fow99]).

Again, we encapsulate these elementary changes in the *ExtractGeneralMethod* refactoring operation, defined in App. A.27.

Pull Up. Note that when *accept* is pulled up (step 4 of Fig. 5), IntelliJ IDEA does not add the *@Override* annotation to all the subclasses, but only in the one the operation is called on.

Also, when *print* and *prettyprint* are pulled up (step 5 of Fig. 5), the tool cannot take several classes simultaneously into account, so that the pull up does not verifies that the code are the same in all the concrete classes (in fact they are). Note that for *Pull Up*, Eclipse can take several classes into account (it allows to remove overriding methods in these classes) but it does not checks that the behavior is preserved by this change.

²Pull up method refactoring extension plugin: http://plugins.intellij.net/plugin/?idea_ce&id=6889

Visibility. In the example program, instance variables are public (package). If they were private or protected, we would have had to make them public so that the moved methods can access them. This does not depend on the way we implement the transformation, but rather to the nature of the Visitor pattern. Note that Eclipse *Move* makes the change automatically while with IntelliJ IDEA you have to do it after or before the *Move*.

Conclusion. We have seen that as soon as we consider a refactoring tool,

1. the guidelines have to be adapted and
2. an algorithm can be defined (and automated).

We have seen also that some steps are implied in the guidelines, and that, on the opposite, some chains of operations of the guidelines can be done with a single tool's operation.

Finally, we have seen that we also have to adapt the chain of operation to characteristics of the initial program. In the following, after having studied a reverse transformation to get the program back to its initial structure, we will see how the algorithm is adapted to variations in the initial program.

3 Composite↔Visitor Transformation Scheme

We now consider an instance of the Composite pattern as the initial program (Fig. 6). The difference between the classic object structure considered before and the Composite structure is *recursion*: the data type is recursive (subclasses make references to the superclass) and the operations are recursive (to traverse trees of that datatype which depth is unknown).

In this section, all the business methods we handle take no parameter and do not return any result, and the traversal process is stateless. These constraints are relaxed in Sec. 4.

We also consider that the visitor classes are not part of the project in the Composite state (unlike in previous section).

3.1 Composite→Visitor Transformation

Let us consider this part in the code of the CompositeGraphic class:

```
public void print() {
    System.out.print("Composite: " + this + " with: ());
    for (Graphic graphic : childGraphics) {
        graphic.print();
    }
    System.out.println(")");
}
```

If we apply the previous transformation algorithm (Fig. 5), after the operation *AddParameterWithDelegate* (step 1), we get the following (with IntelliJ IDEA):

```
public void print() {
    print(new PrintVisitor());
}

public void print(PrintVisitor v) {
    System.out.print("Composite: " + this + " with: ());
    for (Graphic graphic : childGraphics) {
        graphic.print();
    }
    System.out.println(")");
}
```

We observe that the recursive invocation to *graphic.print()* in the *for* loop has been left unchanged. The code is still functionally correct, but it is problematic for the following reason: if we look at the definition of *Graphic.print()* (in the program at that moment of the transformation, you cannot tell which instance of *print()* will be invoked because *print()* is abstract in the class *Graphic*, but we know that *print()*, as a delegator, will be pulled up to the class *Graphic*), we can see that each invocation of *print()* will result in the construction of a new *PrintVisitor* object.

Here, if possible, one would choose to use a single *PrintVisitor* object instead of creating useless new ones. In fact, there is a means to do this with the IntelliJ IDEA refectorer, but, in order to do that, the *print()* delegator method must be pulled up,³ which impacts the rest of the algorithm (for instance, the pull-up of step 1 is already done).

³The trick is to first introduce an indirection (directly in the superclass), then inline the delegator invocation inside the loop, then add the parameter to the delegate, so that the tool is able to insert as new parameter in invocations existing objects instead of using a default value.

```

abstract class Graphic {

    abstract public void print();

    abstract public void prettyprint();

}

class Ellipse extends Graphic{

    public void print() {
        System.out.println("Ellipse :" + this);
    }

    public void prettyprint(){
        System.out.println("Ellipse corresponding to the object " + this + ".");
    }
}

class CompositeGraphic extends Graphic {

    private ArrayList<Graphic> mChildGraphics = new ArrayList<Graphic>();

    public void print() {
        System.out.println("Composite:");
        for (Graphic graphic : mChildGraphics) {
            graphic.print();
        }
    }

    public void prettyprint(){
        System.out.println("Composite " + this + " composed of:");
        for (Graphic graphic : mChildGraphics) {
            graphic.prettyprint();
        }
        System.out.println("(end of composite)");
    }

    public void add(Graphic graphic) {
        mChildGraphics.add(graphic);
    }

    public void remove(Graphic graphic) {
        mChildGraphics.remove(graphic);
    }
}

```

Figure 6: Base Program (class hierarchy)

1. ForAll m in \mathbb{M} do $\text{CreateEmptyClass}(V(m))$
2. ForAll m in \mathbb{M} do
 $\text{CreateIndirectionInSuperClass}(S, m, aux(m))$
3. ForAll m in \mathbb{M} , c in \mathbb{C} do
 $\text{InlineMethodInvocations}(c, m, aux(m))$
4. ForAll m in \mathbb{M} do
 $\text{AddParameterWithReuse}(S, aux(m), V(m))$
5. ForAll m in \mathbb{M} , c in \mathbb{C} do
 $\text{MoveMethodWithDelegate}(c, aux(m), V(m),$
 $"visit")$
6. ExtractSuperClass(\mathbb{V} , "Visitor")
7. ForAll m in \mathbb{M} do
 $\text{GeneraliseParameter}(S, aux(m), V(m), "Visitor")$
8. MergeDuplicateMethods($S, \{ aux(m) \}_{m \in \mathbb{M}}$, "accept")

Figure 7: Base Composite→Visitor transformation

This shows that, as soon as we rely on a refactoring tool, the chain of refactoring operations depends on the characteristics of the tool.

For this reason, here we cannot encapsulate the small change in the transformation into a variation of one of the steps of the algorithm, but we have to adapt the whole algorithm. Our algorithm for basic Composite→Transformation is given in Fig. 7.

In Fig. 7, to generate temporary names, we consider a function aux that takes a method name and returns a method name. Here, $aux(\text{print}) = \text{printAux}$ and $aux(\text{prettyprint}) = \text{prettyprintAux}$.⁴

Note that two bugs were encountered with IntelliJ IDEA at the beginning of our work, but were solved by JetBrains, so that no manual intervention is needed now.

The result of this transformation is given in Figs. 8 and 9.

3.2 Visitor→Composite Transformation

Composite→Visitor transformation is based on moving business code from the data-type class hierarchy to the visitor classes. Now we do the opposite (move business code from visitor classes to composite classes). We proceed with three coarse steps (Fig 10):

- i. Replace dynamic dispatch with static dispatch.
- ii. In-line the business code from the *visitor* structure to the *composite* structure.
- iii. Make some small changes to get the initial Composite pattern structure back.

Remove Dynamic Dispatch (Fig. 10, steps 1 and 2). We replace the $accept(Visitor)$ method by some overloaded methods $accept$, one for each subtype of *Visitor*. This removes all dynamic dispatch in *visit* method invocations, so that their invocations can be inlined afterward. The *visit* methods can also be removed from the *Visitor* class (but not from the concrete visitor classes before they are inlined).

The result of this is given in Figs. 11 and 12.

Move Business Code (Fig. 10, step 3). The business code in the *visitor* classes is inlined: invocations of the *visit* methods in the *composite* classes are replaced by the corresponding body (the business code) and the *visit* methods are deleted.

The result of this step is given in Fig. 13 (visitor classes are empty).

⁴Of course, we should ensure that these names are not clashing with other names in the project.

```

abstract class Graphic {

    public void print() {
        accept(new PrintVisitor());
    }

    public void prettyprint() {
        accept(new PrettyPrintVisitor());
    }

    public abstract void accept(Visitor v);
}

```

```

class Ellipse extends Graphic{

    public void accept(Visitor v) {
        v.visit(this);
    }
}

```

```

class CompositeGraphic extends Graphic {

    ArrayList<Graphic> mChildGraphics = new ArrayList<Graphic>();

    public void accept(Visitor v) {
        v.visit(this);
    }

    public void add(Graphic graphic) {
        mChildGraphics.add(graphic);
    }

    public void remove(Graphic graphic) {
        mChildGraphics.remove(graphic);
    }
}

```

Figure 8: Program with Visitor (data classes)

```

public abstract class Visitor {

    public abstract void visit(Ellipse ellipse);

    public abstract void visit(CompositeGraphic compositeGraphic);

}

```

```

public class PrintVisitor extends Visitor {

    public void visit(CompositeGraphic compositeGraphic) {
        System.out.println("Composite :");
        for (Graphic graphic : compositeGraphic.mChildGraphics) {
            graphic.accept(this);
        }
    }

    public void visit(Ellipse ellipse) {
        System.out.println("Ellipse :" + ellipse);
    }
}

```

```

public class PrettyPrintVisitor extends Visitor {

    public void visit(CompositeGraphic compositeGraphic) {
        System.out.println("Composite " + compositeGraphic + " composed of:");
        for (Graphic graphic : compositeGraphic.mChildGraphics) {
            graphic.accept(this);
        }
        System.out.println("(end of composite)");
    }

    public void visit(Ellipse ellipse) {
        System.out.println("Ellipse corresponding to the object " + ellipse + ".");
    }
}

```

Figure 9: Program with Visitor (visitor classes)

1. ForAll v in \mathbb{V} do
 $\text{addSpecializedMethodInHierarchy}(S, \text{"accept"}, \text{"Visitor"}, v)$
 $\text{deleteMethodInHierarchy}(S, \text{accept}, \text{"Visitor"})$
2. ForAll c in \mathbb{C} do $\text{pushDownAll}(\text{"Visitor"}, \text{"visit"}, c)$
3. ForAll v in \mathbb{V} , c in \mathbb{C} do $\text{InlineMethod}(v, \text{"visit"}, c)$
4. ForAll m in \mathbb{M} do
 $\text{renameMethod}(S, \text{accept}, V(m), aux(m))$
5. ForAll m in \mathbb{M} do $\text{removeParameter}(S, aux(m), V(m))$
6. ForAll m in \mathbb{M} do $\text{replaceMethodDuplication}(S, m)$
7. ForAll m in \mathbb{M} do $\text{pushDownImplementation}(S, m)$
8. ForAll m in \mathbb{M} do $\text{pushDownAll}(S, aux(m))$
9. ForAll m in \mathbb{M} , c in \mathbb{C} do $\text{inlineMethod}(c, aux(m))$
10. ForAll v in \mathbb{V} do $\text{deleteClass}(v)$
11. $\text{deleteClass}(\text{"Visitor"})$

Figure 10: Base Visitor \rightarrow Composite transformation

```

abstract class Graphic {

    public void print() {
        accept(new PrintVisitor());
    }

    public void prettyprint() {
        accept(new PrettyPrintVisitor());
    }

    public abstract void accept(PrintVisitor v);

    public abstract void accept(PrettyPrintVisitor v);
}

```

```

class Ellipse extends Graphic{

    public void accept(PrettyPrintVisitor v) {
        v.visit(this);
    }

    public void accept(PrintVisitor v) {
        v.visit(this);
    }
}

```

```

class CompositeGraphic extends Graphic {

    ArrayList<Graphic> mChildGraphics = new ArrayList<Graphic>();

    public void accept(PrettyPrintVisitor v) {
        v.visit(this);
    }

    public void accept(PrintVisitor v) {
        v.visit(this);
    }

    public void add(Graphic graphic) {
        mChildGraphics.add(graphic);
    }

    public void remove(Graphic graphic) {
        mChildGraphics.remove(graphic);
    }
}

```

Figure 11: Reverse-State 1 (data classes)

```
public abstract class Visitor {
}
```

```
public class PrintVisitor extends Visitor {

    public void visit(CompositeGraphic compositeGraphic) {
        System.out.println("Composite:");
        for (Graphic graphic : compositeGraphic.mChildGraphics) {
            graphic.accept(this);
        }
    }

    public void visit(Ellipse ellipse) {
        System.out.println("Ellipse :" + ellipse);
    }
}
```

```
public class PrettyPrintVisitor extends Visitor {

    public void visit(CompositeGraphic compositeGraphic) {
        System.out.println("Composite " + compositeGraphic + " composed of:");
        for (Graphic graphic : compositeGraphic.mChildGraphics) {
            graphic.accept(this);
        }
        System.out.println("(end of composite)");
    }

    public void visit(Ellipse ellipse) {
        System.out.println("Ellipse corresponding to the object " + ellipse + ".");
    }
}
```

Figure 12: Reverse-State 1 (visitor classes)

Remove Visitors and Recover Initial Structure (Fig. 10, steps 4 to 11). Once the business code has been moved into the convenient classes, the rest of the refactoring operations are common refactoring operations allowing to recover the composite structure (the important part is done before).

The result of this step is given in Fig. 14.

3.3 Result after Round Trip Transformation

After this transformation, the program conforms to the Composite pattern (Fig. 14).

A few more refactorings are necessary to recover exactly the original program: make private the fields that were made public during the Composite→Transformation, reorder method definitions.

Note also that some comments are altered or lost during the transformation (which is not shown by our example).

```

abstract class Graphic {

    public void print() {
        accept(new PrintVisitor());
    }

    public void prettyprint() {
        accept(new PrettyPrintVisitor());
    }

    public abstract void accept(PrintVisitor v);

    public abstract void accept(PrettyPrintVisitor v);
}

```

```

class Ellipse extends Graphic{

    public void accept(PrettyPrintVisitor v) {
        System.out.println("Ellipse corresponding to the object " + this + ".");
    }

    public void accept(PrintVisitor v) {
        System.out.println("Ellipse :" + this);
    }
}

```

```

class CompositeGraphic extends Graphic {

    ArrayList<Graphic> mChildGraphics = new ArrayList<Graphic>();

    public void accept(PrettyPrintVisitor v) {
        System.out.println("Composite " + this + " composed of:");
        for (Graphic graphic : mChildGraphics) {
            graphic.accept(v);
        }
        System.out.println("(end of composite)");
    }

    public void accept(PrintVisitor v) {
        System.out.println("Composite:");
        for (Graphic graphic : mChildGraphics) {
            graphic.accept(v);
        }
    }

    public void add(Graphic graphic) {
        mChildGraphics.add(graphic);
    }

    public void remove(Graphic graphic) {
        mChildGraphics.remove(graphic);
    }
}

```

Figure 13: Reverse-State 2 (data classes)

```

abstract class Graphic {

    public abstract void print();

    public abstract void prettyprint();

}

```

```

class Ellipse extends Graphic{

    public void print() {
        System.out.println("Ellipse :" + this);
    }

    public void prettyprint() {
        System.out.println("Ellipse corresponding to the object " + this + ".");
    }
}

```

```

class CompositeGraphic extends Graphic {

    ArrayList<Graphic> mChildGraphics = new ArrayList<Graphic>();

    public void add(Graphic graphic) {
        mChildGraphics.add(graphic);
    }

    public void remove(Graphic graphic) {
        mChildGraphics.remove(graphic);
    }

    public void print() {
        System.out.println("Composite :");
        for (Graphic graphic : mChildGraphics) {
            graphic.print();
        }
    }

    public void prettyprint() {
        System.out.println("Composite " + this + " composed of:");
        for (Graphic graphic : mChildGraphics) {
            graphic.prettyprint();
        }
        System.out.println("(end of composite)");
    }
}

```

Figure 14: Result after Back Transformations

4 Variants of Transformations for Various Pattern Instances

In this section we consider some variants of either Composite pattern or Visitor pattern and we adapt the algorithm of transformation.

4.1 Methods with Parameters

In this section we consider that methods of interest have parameters. We consider a method `setColor` with an integer as parameter in the Composite hierarchy (see Fig. 15).

```
abstract class Graphic {  
    public abstract void print();  
    public abstract void setColor(int c);  
}  
  
class Ellipse extends Graphic{  
    protected int color ;  
    public void print() {  
        System.out.println(" Ellipse with color:"+ color);  
    }  
    public void setColor(int c){  
        this.color = c;  
    }  
}  
  
class CompositeGraphic extends Graphic{  
    private ArrayList<Graphic> mChildGraphics = new ArrayList<Graphic>();  
    public void print() {  
        System.out.println(" Composite:");  
        for (Graphic graphic : mChildGraphics) {  
            graphic.print();  
        }  
    }  
    public void setColor(int c){  
        for (Graphic graphic : mChildGraphics) {  
            graphic.setColor(c);  
        }  
    }  
    public void add(Graphic graphic) {  
        mChildGraphics.add(graphic);  
    }  
    public void remove(Graphic graphic) {  
        mChildGraphics.remove(graphic);  
    }  
}
```

Figure 15: Composite with methods having parameters.

4.1.1 Composite→Visitor Transformation

At the step 4 of the Composite→Visitor algorithm of Fig. 7, replace the application of the operation `addParameterWithReuse` with parameters by the operation *Introduce Parameter Object*. This operation is offered by refactoring tools (Eclipse and IntelliJ IDEA). If we consider a method `m(A a, B b, C c)`, it replaces the parameters by an object of a new class `P` it creates and which contains instances variables `a`, `b` and `c`. Invocations `m(a,b,c)` are replaced by `m(new P(a,b,c))`.

```

abstract class Graphic {
    public void print(){
        accept(new PrintVisitor());
    }
    public void setColor(int c) {
        accept(new SetColorVisitor(c));
    }
    public abstract void accept(Visitor v);
}

```

```

class Ellipse extends Graphic {
    protected int color ;
    void accept(Visitor v) {
        v.visit(this);
    }
}

```

```

class CompositeGraphic extends Graphic{
    ArrayList<Graphic> mChildGraphics =
        new ArrayList<Graphic>();
    public void accept(Visitor v){
        v.visit(this);
    }
    public void add(Graphic graphic) {
        mChildGraphics.add(graphic);
    }
    public void remove(Graphic graphic) {
        mChildGraphics.remove(graphic);
    }
    ArrayList<Graphic> getmChildGraphics() {
        return mChildGraphics;
    }
}

```

Figure 16: Visitor with methods having parameters (data classes)

4.1.2 Visitor Program

The result program is shown by the figures 16 and 17.

4.1.3 Visitor→Composite Transformation

After performing the step 9 of the basic algorithm (Fig. 10) perform the following tasks :

1. Delete the superclass *Visitor* structure.
2. *InlineClass(v)* (for each visitor class *v* that corresponds to the business method with parameter).

After having performed the rest of the transformation of Fig. 10, we get the following code in the *Ellipse* class:

```

public void setColor(int c) {
    final int c1 = c;
    color = new Object() {
        private final int c = c1;

        public int getC() {
            return c;
        }
    }.getC();
}

```

Here, we have to replace *new Object(){...c1...}.getC()* by *c1*. The reason is that we have replaced a parameter by an object containing the parameter with *Add Object Parameter* during the Composite→Transformation, and now we have to do the inverse, extract a component from an object. The same has to be done in *CompositeGraphic*. At the moment, we do this manually.

4.2 Methods Returning Values

In this section we consider that methods of interest return results, for instance we consider a method *perimeter* that returns an *Integer* and *toString* that returns a *String* (see Fig. 18).

```

public class PrintVisitor extends Visitor {
    public void visit(CompositeGraphic compositeGraphic) {
        System.out.println("Composite:");
        for (Graphic graphic : compositeGraphic.mChildGraphics) {
            graphic.accept(this);
        }
    }
    public void visit(Ellipse ellipse) {
        System.out.println("Ellipse with color:" + ellipse.color);
    }
}

```

```

public class SetColorVisitor extends Visitor{
    private final int c;
    public SetColorVisitor(int c) {
        this.c = c;
    }
    public int getC() {
        return c;
    }
    public void visit(CompositeGraphic compositeGraphic) {
        for (Graphic graphic : compositeGraphic.mChildGraphics) {
            graphic.accept(this);
        }
    }
    public void visit(Ellipse ellipse) {
        ellipse.color = getC();
    }
}

```

Figure 17: Visitor with methods having parameters (visitor classes)

This would require to have one accept method for each return type. To avoid this, we use generic types (see the visitor structure in Figs. 19 and 20). Note that the use of Java generic types is only possible with object types (such as *Integer*), not with raw types (such as *int*).

4.2.1 Composite→Visitor Transformation

In the step 6 of the base algorithm of Fig. 7, we use the operation *ExtractSuperClassWithoutPullUp* (see App. A.9.1) and then the operation *PullUpWithGenerics* (see App. A.16). The last operation is used to pull up methods having different return types and create the right generic types.

4.2.2 Visitor Program

The result program is shown by the figures 19 and 20.

4.2.3 Visitor→Composite Transformation

At the step 1 of the base algorithm of the Fig. 10, we must specify the return type of each *accept* method and replace the parameter type by the corresponding type (the operation *addSpecializedMethodInHierarchy* must change the return type in addition to the parameter type).

4.3 Interface instead of Abstract class in the Composite structure

In this section we consider that the top of the Composite hierarchy in an interface instead of abstract class (see Fig. 21). As we have to put some code in the superclass, we just introduce an abstract class in the hierarchy.

4.3.1 Composite→Visitor Transformation

Before performing the base algorithm of Fig. 7, create an abstract class that implements the interface of the Composite hierarchy. This is done as the following :

1. Extract a super-Class from composite classes.
2. Pull up the business methods as abstract methods to the super-Class.
3. Make the super-class implementing the interface of the Composite structure.
4. Change any use of type Interface to type super-Class (use *Type Migration* in IntelliJ IDEA to perform this operation).
5. Push down business method from the interface of composite structure (this will help to avoid any confusion or complexity of manipulating business methods in the abstract class).

```

abstract class Graphic{
    public abstract Integer perimeter ();
    public abstract String toString ();
}

```

```

class Ellipse extends Graphic{
    int perimeter;

    public Ellipse (int perimeter){
        this.perimeter=perimeter ;
    }

    public Integer perimeter () {
        return (perimeter);
    }

    public String toString () {
        return ("Ellipse : " + Integer.toString(perimeter));
    }
}

```

```

class CompositeGraphic extends Graphic {

    private ArrayList<Graphic> mChildGraphics = new ArrayList<Graphic>();

    public Integer perimeter() {
        int acc = 0 ;
        for (Graphic graphic : mChildGraphics) {
            acc += graphic.perimeter ();
        }
        return acc;
    }

    public String toString(){
        String s ;
        s = new String ("Composite with: ");
        for (Graphic graphic : mChildGraphics) {
            s = s.concat(graphic.toString() + ", ");
        }
        System.out.println("(end)");
        return s;
    }

    public void add(Graphic graphic) {
        mChildGraphics.add(graphic);
    }

    public void remove(Graphic graphic) {
        mChildGraphics.remove(graphic);
    }
}

```

Figure 18: Composite with methods returning types

```

abstract class Graphic{
    public Integer perimeter() {
        return accept(new PerimeterVisitor());
    }
    public String toString() {
        return accept(new ToStringVisitor());
    }
    public abstract <T> T accept(Visitor<T> v);
}

```

```

class Ellipse extends Graphic{
    int perimeter;
    public Ellipse (int perimeter){
        this.perimeter=perimeter ;
    }

    public <T> T accept(Visitor<T> v) {
        return v.visit(this);
    }
}

```

```

class CompositeGraphic extends Graphic {
    ArrayList<Graphic> mChildGraphics =
        new ArrayList<Graphic>();
    public void add(Graphic graphic) {
        mChildGraphics.add(graphic);
    }
    public void remove(Graphic graphic) {
        mChildGraphics.remove(graphic);
    }
    ArrayList<Graphic> getmChildGraphics() {
        return mChildGraphics;
    }
    public <T> T accept(Visitor<T> v) {
        return v.visit(this);
    }
}

```

Figure 19: Visitor with generics (data classes)

```

public class TotalPerimeterVisitor extends Visitor <Integer>{
    public Integer visit(CompositeGraphic compositeGraphic) {
        int acc = 0 ;
        for (Graphic graphic : compositeGraphic.mChildGraphics) {
            acc += graphic.accept(this);
        }
        return acc;
    }
    public Integer visit(Ellipse ellipse) {
        return (ellipse.perimeter);
    }
}

```

```

public class ToStringVisitor extends Visitor <String> {
    public String visit(CompositeGraphic compositeGraphic) {
        String s ;
        s = new String ("Composite with: ");
        for (Graphic graphic : compositeGraphic.mChildGraphics) {
            s = s.concat(graphic.accept(this) + ", ");
        }
        System.out.println("(end)");
        return s;
    }
    public String visit(Ellipse ellipse) {
        return ("Ellipse : " + Integer.toString(ellipse.perimeter));
    }
}

```

Figure 20: Visitor with generics (visitor classes)

```
interface Graphic {
    abstract public void print();
    abstract public void prettyprint();
}
```

```
class Ellipse implements Graphic{
    public void print() {
        System.out.println("Ellipse :" + this);
    }
    public void prettyprint(){
        System.out.println("Ellipse corresponding to the object " + this + ".");
    }
}
```

```
class CompositeGraphic implements Graphic {
    private ArrayList<Graphic> mChildGraphics = new ArrayList<Graphic>();
    public void print() {
        System.out.println("Composite :");
        for (Graphic graphic : mChildGraphics) {
            graphic.print();
        }
    }
    public void prettyprint(){
        System.out.println("Composite " + this + " composed of:");
        for (Graphic graphic : mChildGraphics) {
            graphic.prettyprint();
        }
        System.out.println("(end of composite)");
    }
    public void add(Graphic graphic) {
        mChildGraphics.add(graphic);
    }
    public void remove(Graphic graphic) {
        mChildGraphics.remove(graphic);
    }
}
```

Figure 21: Composite with Interface

```

interface Graphic {
    void print();
    void prettyprint();
}

```

```

public abstract class AbstractComposite implements Graphic {
    public void print() {
        accept(new PrintVisitor());
    }
    public void prettyprint() {
        accept(new PrettyPrintVisitor());
    }
    public abstract void accept(Visitor v);
}

```

```

class Ellipse extends AbstractComposite implements Graphic{
    public void accept(Visitor v){
        v.visit(this);
    }
}

```

```

class CompositeGraphic extends AbstractComposite implements Graphic {
    ArrayList<AbstractComposite> mChildGraphics = new ArrayList<AbstractComposite>();
    public void accept(Visitor v){
        v.visit(this);
    }
    public void add(AbstractComposite graphic) {
        mChildGraphics.add(graphic);
    }
    public void remove(AbstractComposite graphic) {
        mChildGraphics.remove(graphic);
    }
    ArrayList<AbstractComposite> getmChildGraphics () {
        return mChildGraphics;
    }
}

```

Figure 22: Visitor structure for Interface instead of Abstract Composite (data classes)

After doing the previous tasks, perform the base algorithm to reach the Visitor structure.

4.3.2 Visitor Program

The result program is shown by the figures 22 and 23.

4.3.3 Visitor→Composite Transformation

After performing the basic algorithm of back transformation (Fig. 10), change any use of the super-class type to the interface type (*Type Migration* in IntelliJ IDEA). Finally, delete the intermediate super-class.

4.4 Class Hierarchies with Several Levels

In this section we consider that the Composite class hierarchy has several levels (we add a subclass *ColoredEllipse* to *Ellipse*, which provides an overriding method for only one of the two business methods, see Fig. 24). The interest of this variant is that a subclass extends a composite and does not redefine all business methods. This subclass exists in different depth of hierarchy as the main composite class.

4.4.1 Composite→Visitor Transformation

Before performing the base algorithm of Fig. 7, apply the operation *pushDownNotRedefinedMethod* (see App. A.24) in order to push down the methods that exists in the composites but not redefined in the sub-classes. After that, the basic algorithm applies.

```

public class PrintVisitor extends Visitor{
    public void visit(CompositeGraphic compositeGraphic) {
        System.out.println("Composite:");
        for (AbstractComposite graphic : compositeGraphic.mChildGraphics) {
            graphic.accept(this);
        }
    }
    public void visit(Ellipse ellipse) {
        System.out.println("Ellipse :" + ellipse);
    }
}

```

```

public class PrettyPrintVisitor extends Visitor {

    public void visit(CompositeGraphic compositeGraphic) {
        System.out.println("Composite " + compositeGraphic + " composed of:");
        for (AbstractComposite graphic : compositeGraphic.mChildGraphics) {
            graphic.accept(this);
        }
        System.out.println("(end of composite)");
    }

    public void visit(Ellipse ellipse) {
        System.out.println("Ellipse corresponding to the object " + ellipse + ".");
    }
}

```

Figure 23: Visitor structure for Interface instead of Abstract Composite (visitor classes)

4.4.2 Visitor Program

The result program is shown by the figures 25 and 26.

4.4.3 Visitor→Composite Transformation

At the step 8 of the basic algorithm (see Fig. 10) use the operation *pushDownNotRedefinedMethod* in order to push down the auxiliary methods that exist in composites and are not redefined in their sub-classes.

```

abstract class Graphic {

    abstract public void print();
    abstract public void prettyprint();

}

```

```

class Ellipse extends Graphic{

    public void print() {
        System.out.println("Ellipse :" + this);
    }
    public void prettyprint(){
        System.out.println("Ellipse corresponding to the object " + this + ".");
    }
}

```

```

class ColoredEllipse extends Ellipse{
    int color;
    public void print() {
        System.out.println("Ellipse :" + color);
    }
}

```

```

class CompositeGraphic extends Graphic {
    private ArrayList<Graphic> mChildGraphics = new ArrayList<Graphic>();
    public void print() {
        System.out.println("Composite:");
        for (Graphic graphic : mChildGraphics) {
            graphic.print();
        }
    }
    public void prettyprint(){
        System.out.println("Composite " + this + " composed of:");
        for (Graphic graphic : mChildGraphics) {
            graphic.prettyprint();
        }
        System.out.println("(end of composite)");
    }
    public void add(Graphic graphic) {
        mChildGraphics.add(graphic);
    }
    public void remove(Graphic graphic) {
        mChildGraphics.remove(graphic);
    }
}

```

Figure 24: Composite with multiple hierarchical levels.

```

abstract class Graphic {
    public void print() {
        accept(new PrintVisitor());
    }
    public void prettyprint() {
        accept(new PrettyPrintVisitor());
    }
    public abstract void accept(Visitor v);
}

```

```

class Ellipse extends Graphic{
    public void accept(Visitor v) {
        v.visit(this);
    }
}

```

```

class ColoredEllipse extends Ellipse{
    int color;
    public void accept(Visitor v) {
        v.visit(this);
    }
}

```

```

class CompositeGraphic extends Graphic {
    ArrayList<Graphic> mChildGraphics = new ArrayList<Graphic>();
    public void add(Graphic graphic) {
        mChildGraphics.add(graphic);
    }
    public void remove(Graphic graphic) {
        mChildGraphics.remove(graphic);
    }
    ArrayList<Graphic> getmChildGraphics() {
        return mChildGraphics;
    }
    public void accept(Visitor v) {
        v.visit(this);
    }
}

```

Figure 25: Visitor with multiple hierarchical levels (data classes)

```

public class PrintVisitor extends Visitor {
    public void visit(CompositeGraphic compositeGraphic) {
        System.out.println("Composite:");
        for (Graphic graphic : compositeGraphic.mChildGraphics) {
            graphic.accept(this);
        }
    }
    public void visit(Ellipse ellipse) {
        System.out.println("Ellipse :" + ellipse);
    }
    public void visit(ColoredEllipse coloredEllipse) {
        System.out.println("Ellipse :" + coloredEllipse.color);
    }
}

```

```

public class PrettyPrintVisitor extends Visitor {
    public void visit(CompositeGraphic compositeGraphic) {
        System.out.println("Composite " + compositeGraphic + " composed of:");
        for (Graphic graphic : compositeGraphic.mChildGraphics) {
            graphic.accept(this);
        }
        System.out.println("(end of composite)");
    }
    public void visit(Ellipse ellipse) {
        System.out.println("Ellipse corresponding to the object " + ellipse + ".");
    }
    public void visit(ColoredEllipse coloredEllipse) {
        System.out.println("Ellipse :" + coloredEllipse.color);
    }
}

```

Figure 26: Visitor with multiple hierarchical levels (visitor classes)

5 Application to JHotDraw

To validate our transformation algorithms, we apply them to JHotDraw [GI].

To know on which classes to apply the transformation, we use a pattern detection tool. We have applied **pattern4** [TCSH06]: it reports a Composite structure with 6 operations and it reports the superclass and the subclass that implements the “container”. The operations are defined by overriding methods in about 12 classes of the class hierarchy.

The semi-automatic Composite→Visitor transformation applies successfully with the help of variations studied in Sec. 4 (and with the limitations explained in these variations).

It takes between 8 and 9 hours to apply the whole Composite→Visitor transformation interactively. Most of time is due to interaction (selection the entities to transform, selecting the refactoring operation and giving parameters). The automated version takes a few minutes. We are focusing on automating the whole reversible transformation on JhotDraw.

A second instance of the pattern is found but we have not transformed it since it has only one operation defined.

6 Related work

6.1 Refactoring to Patterns

Using chains of elementary refactoring operations to introduce design patterns into programs is not new. The idea is first proposed by Batory and Takuda [BT95].

Ó Cinnéide [OC00] give transformation to introduce several patterns but not the Visitor (he considers in [OC00] that automating the introduction of a visitor pattern is impractical).

Kerievsky [Ker04] proposes two sets of guidelines to introduce Visitor patterns. The first one is similar to the one from Mens and Tourwé [MT04] described in Sec. 2. The second one applies to an “external accumulation”: instead of transforming an operation defined by overriding methods in the class hierarchy, it applies to an operation defined outside of the class hierarchy by a switch on the type of an object with *instanceof* and type casts. Neither Mens and Tourwé [MT04] nor Kerievsky [Ker04] give the inverse transformation.

Hills et al. [HKVDSV11] have transformed a program based on a Visitor pattern to introduce a Visitor pattern instead (the Visitor pattern is similar to the Composite pattern). Their transformation is automated, with a few interactions

with the user. Since their transformation is dedicated to a specific program and is not abstractly described, it requires some work to be applied to other programs.

Jeaon et al. [JLB02] provide automatic inference of sequence of refactoring operations allowing to reach design pattern based versions of programs. Sudan et al. [PRSK10] provide an inference of a sequence of refactoring operations allowing to pass from a given version of a program to a second given version. Such tools could be used to infer variations of our transformation algorithms for variations in initial programs, or to infer transformations between other patterns.

6.2 Building Complex Refactoring Operations

The transformations we aim at can be seen as complex/composed refactoring operations. As each refactoring operation has specific preconditions, and as we use a large number of elementary transformations, assistance for building such transformations would be valuable. Several works provide languages to build or compose refactoring operations. Ó Cinnéide and Nixon [OCN00] show how to compose elementary refactoring operations with pre/post-conditions, as well as Kniesel and Koch [KK04].

Verbaere et al. propose a language dedicated to building refactoring operations [VEDM06], and Clint et al. propose a language dedicated to program manipulation [KSV09], which they have used to build the Visitor→Interpreter transformation [HKVDSV11].

6.3 Design Patterns Discovery

To provide a fully automated transformation, detection of the occurrences of the initial design pattern must be automated. Several work exist in that domain. Smith and Scott provide a tool that discovers variants of a design pattern in a given program [SS03]. Such tools can be used to automatically provide inputs to our transformations.

On the opposite, some tools detect pattern precursors, anti-patterns or code smells [RJ04, MGL06], but, in our approach, we consider that the initial program has already a good design.

7 Conclusion

In this report:

- We have shown how to use refactoring operations to transform a Java program conforming to the Composite pattern (or Interpreter pattern) into a program (still in Java) conforming to the Visitor pattern and vice versa.
- We have explained how to use some refactoring tools (IntelliJ IDEA and Eclipse) to perform these transformations. We have seen that some basic refactorings are not supported by these tools.
- We have discussed some variations in transformations to adapt to variations in the initial programs.

This work is a first step towards automation of these transformations so that the user does not have to perform each basic refactoring with a refactoring tool. On the example of the JHotDraw program, automation can reduce transformation time from 8 hours to a few minutes. This kind of automated transformation can be used to provide different versions of a same programs with different properties with respect to modularity [CDA12].

References

- [BT95] Don Batory and Lance Tokuda. Automated software evolution via design pattern transformations. Technical report, University of Texas at Austin, Austin, TX, USA, 1995.
- [CA13] Julien Cohen and Akram Ajouli. Practical use of static composition of refactoring operations. In *ACM Symposium On Applied Computing*, Portugal, March 2013.
- [CDA12] Julien Cohen, Rémi Douence, and Akram Ajouli. Invertible program restructurings for continuing modular maintenance. In *Soft. Maintenance and Reengineering (CSMR), 16th European Conf. on*, pages 347–352, 2012.
- [Fow99] Martin Fowler. *Refactoring: Improving the Design of Existing Code*. Addison-Wesley, 1999.
- [GHJV95] Erich Gamma, Richard Helm, Ralph Johnson, and John Vlissides. *Design patterns: elements of reusable object-oriented software*. Addison-Wesley Longman Publishing Co., Inc., Boston, MA, USA, 1995.
- [GI] Erich Gamma and IFA Informatik. JHotDraw as Open-Source Project. <http://www.jhotdraw.org/>.

- [HKVDSV11] Mark Hills, Paul Klint, Tijs Van Der Storm, and Jurgen Vinju. A case of visitor versus interpreter pattern. In *Proceedings of the 49th international conference on Objects, models, components, patterns*, TOOLS'11, pages 228–243, Berlin, Heidelberg, 2011. Springer-Verlag.
- [JLB02] Sang-Uk Jeon, Joon-Sang Lee, and Doo-Hwan Bae. An automated refactoring approach to design pattern-based program transformations in Java programs. In *Proceedings of the Ninth Asia-Pacific Software Engineering Conference*, APSEC '02, pages 337–, Washington, DC, USA, 2002. IEEE Computer Society.
- [Ker04] Joshua Kerievsky. *Refactoring to Patterns*. Pearson Higher Education, 2004.
- [KK04] Günter Kriesel and Helge Koch. Static composition of refactorings. *Science of Computer Programming*, 52(Issues 1-3):9–51, Aug. 2004. Special Issue on Program Transformation.
- [Koc02] Helge Koch. Ein refactoring-framework fr Java (in german). Diploma thesis, CS Dept. III, University of Bonn, Germany, April 2002.
- [KSV09] Paul Klint, Tijs van der Storm, and Jurgen Vinju. Rascal: A domain specific language for source code analysis and manipulation. In *Proceedings of the 2009 Ninth IEEE International Working Conference on Source Code Analysis and Manipulation*, SCAM '09, pages 168–177, Washington, DC, USA, 2009. IEEE Computer Society.
- [MGL06] Naouel Moha, Yann-Gael Gueheneuc, and Pierre Leduc. Automatic generation of detection algorithms for design defects. In *Proceedings of the 21st IEEE/ACM International Conference on Automated Software Engineering*, pages 297–300, Washington, DC, USA, 2006. IEEE Computer Society.
- [MT04] Tom Mens and Tom Tourwé. A survey of software refactoring. *IEEE Trans. Softw. Eng.*, 30:126–139, February 2004.
- [OC00] Mel Ó Cinnéide. *Automated Application of Design Patterns: A Refactoring Approach*. PhD thesis, Trinity College, Dublin, Oct. 2000.
- [OCN99] M. Ó Cinnéide and P. Nixon. A methodology for the automated introduction of design patterns. In *Proceedings of the IEEE International Conference on Software Maintenance*, ICSM '99, pages 463–, Washington, DC, USA, 1999. IEEE Computer Society.
- [OCN00] Mel Ó Cinnéide and Paddy Nixon. Composite refactorings for Java programs. In *Proc. of the Workshop on Formal Techniques for Java Programs*, ECOOP, 2000.
- [PRSK10] Kyle Prete, Napol Rachatasumrit, Nikita Sudan, and Miryung Kim. Template-based reconstruction of complex refactorings. In *IEEE International Conference on Software Maintenance (ICSM)*, Sept. 2010.
- [RJ04] J. Rajesh and D. Janakiram. Jiad: a tool to infer design patterns in refactoring. In *Proceedings of the 6th ACM SIGPLAN international conference on Principles and practice of declarative programming*, PPDP '04, pages 227–237, New York, NY, USA, 2004. ACM.
- [SS03] Jason M. Smith and David Stotts. SPQR: Flexible automated design pattern extraction from source code. In *18th IEEE Intl. Conf. on Automated Soft. Eng.*, pages 215–224. IEEE Computer Society Press, 2003.
- [TCSH06] Nikolaos Tsantalis, Alexander Chatzigeorgiou, George Stephanides, and Spyros T. Halkidis. Design pattern detection using similarity scoring. *IEEE Trans. Softw. Eng.*, 32:896–909, November 2006.
- [VEDM06] Mathieu Verbaere, Ran Ettinger, and Oege de Moor. Jungl: a scripting language for refactoring. In *Proceedings of the 28th international conference on Software engineering*, ICSE '06, pages 172–181, New York, NY, USA, 2006. ACM.

A Refactoring Operations

In this appendix, we define refactoring operations we use in our transformations. For each operation, we give an example to explain its behavior, and we tell how it is performed with IntelliJ IDEA or Eclipse. We give some preconditions when an operation applies only in a specific case. These preconditions are neither minimal (they can be refined into weaker conditions) nor complete (they are sufficient in our basic examples, but not in some situations we have not considered). Also, some preconditions dealing with name clashes are left implied.

The given *backward descriptions* are used for static composition of refactorings [KK04] (see App. B).

A.1 CreateEmptyClass

Overview: CreateEmptyClass (classname c): this operation is used to add a new class c.

Refactoring tools. new Class in Eclipse and IntelliJ IDEA.

Precondition.

($\neg \exists \text{existsType}(c)$)

Backward Description.

```

ExistsClass( $c$ )  $\mapsto \top$ 
ExistsType( $c$ )  $\mapsto \top$ 
IsAbstractClass( $c$ )  $\mapsto \perp$ 
ExistsMethodDefinition( $c, Y$ )  $\mapsto \perp$ 
ExistsMethodDefinitionWithParams( $c, Y, []$ )  $\mapsto \perp$ 
ExistsMethodDefinitionWithParams( $c, Y, [T1]$ )  $\mapsto \perp$ 
ExistsMethodDefinitionWithParams( $c, Y, [T1; T2]$ )  $\mapsto \perp$ 
ExistsMethodDefinitionWithParams( $c, Y, [T1; T2; T3]$ )  $\mapsto \perp$ 
ExistsMethodDefinitionWithParams( $c, Y, [T1; T2; T3; T4]$ )  $\mapsto \perp$ 
ExistsMethodDefinitionWithParams( $c, Y, [T1; T2; T3; T4; T5]$ )  $\mapsto \perp$ 
IsInheritedMethod( $c, Y$ )  $\mapsto \text{IsVisible}(\text{java.lang.Object}, Y, c)$ 
IsInheritedMethodWithParams( $c, Y, []$ )  $\mapsto \text{IsVisibleMethod}(\text{java.lang.Object}, Y, [], c)$ 
IsInheritedMethodWithParams( $c, Y, [T1]$ )  $\mapsto \text{IsVisibleMethod}(\text{java.lang.Object}, Y, [T1], c)$ 
IsInheritedMethodWithParams( $c, Y, [T1; T2]$ )  $\mapsto \text{IsVisibleMethod}(\text{java.lang.Object}, Y, [T1; T2], c)$ 
IsInheritedMethodWithParams( $c, Y, [T1; T2; T3]$ )  $\mapsto \text{IsVisibleMethod}(\text{java.lang.Object}, Y, [T1; T2; T3], c)$ 
IsInheritedMethodWithParams( $c, Y, [T1; T2; T3; T4]$ )  $\mapsto \text{IsVisibleMethod}(\text{java.lang.Object}, Y, [T1; T2; T3; T4], c)$ 
IsInheritedMethodWithParams( $c, Y, [T1; T2; T3; T4; T5]$ )  $\mapsto \text{IsVisibleMethod}(\text{java.lang.Object}, Y, [T1; T2; T3; T4; T5], c)$ 
IsSubType( $c, X$ )  $\mapsto \perp$  ( $X \neq \text{java.lang.Object}$ )
ExtendsDirectly( $c, X$ )  $\mapsto \perp$  ( $X \neq \text{java.lang.Object}$ )
ExistsMethodDefinitionWithParams( $B, Y, [c]$ )  $\mapsto \perp$ 
ExistsMethodDefinitionWithParams( $B, Y, [c; T1]$ )  $\mapsto \perp$ 
ExistsMethodDefinitionWithParams( $B, Y, [T1; c]$ )  $\mapsto \perp$ 
ExistsMethodDefinitionWithParams( $B, Y, [T1; T2; c]$ )  $\mapsto \perp$ 
ExistsMethodDefinitionWithParams( $B, Y, [T1; c; T2]$ )  $\mapsto \perp$ 
ExistsMethodDefinitionWithParams( $B, Y, [c; T1; T2]$ )  $\mapsto \perp$ 
IsInheritedMethodWithParams( $B, Y, [c]$ )  $\mapsto \perp$ 
IsInheritedMethodWithParams( $B, Y, [c; T1]$ )  $\mapsto \perp$ 
IsInheritedMethodWithParams( $B, Y, [T1; c]$ )  $\mapsto \perp$ 
IsInheritedMethodWithParams( $B, Y, [T1; T2; c]$ )  $\mapsto \perp$ 
IsInheritedMethodWithParams( $B, Y, [T1; c; T2]$ )  $\mapsto \perp$ 
IsInheritedMethodWithParams( $B, Y, [c; T1; T2]$ )  $\mapsto \perp$ 
ExistsParameterWithName( $B, Y, [c], P$ )  $\mapsto \perp$ 
ExistsParameterWithName( $B, Y, [c; T1], P$ )  $\mapsto \perp$ 
ExistsParameterWithName( $B, Y, [T1; c], P$ )  $\mapsto \perp$ 
ExistsParameterWithName( $B, Y, [T1; c; T2], P$ )  $\mapsto \perp$ 
ExistsParameterWithName( $B, Y, [T1; T2; c], P$ )  $\mapsto \perp$ 
ExistsParameterWithName( $B, Y, [c; T1; T2], P$ )  $\mapsto \perp$ 
ExistsParameterWithType( $B, Y, [c], P$ )  $\mapsto \perp$ 
ExistsParameterWithType( $B, Y, [c; T1], P$ )  $\mapsto \perp$ 
ExistsParameterWithType( $B, Y, [T1; c], P$ )  $\mapsto \perp$ 
ExistsParameterWithType( $B, Y, [T1; c; T2], P$ )  $\mapsto \perp$ 
ExistsParameterWithType( $B, Y, [T1; T2; c], P$ )  $\mapsto \perp$ 
ExistsParameterWithType( $B, Y, [c; T1; T2], P$ )  $\mapsto \perp$ 


```

$\text{IsUsedMethodIn}(c, B, Y) \mapsto \perp$
 $\text{IsUsedMethod}(c, B, [T1]) \mapsto \perp$
 $\text{IsUsedMethod}(c, B, [T1; T2]) \mapsto \perp$
 $\text{IsUsedMethod}(c, B, [T1; T2; T3]) \mapsto \perp$
 $\text{IsUsedMethod}(c, B, [T1; T2; T3; T4]) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(c, B, Y) \mapsto \perp$
 $\text{IsUsedConstructorAsInitializer}(c, B, Y) \mapsto \perp$
 $\text{IsUsedConstructorAsObjectReceiver}(c, B, Y) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(B, c, Y) \mapsto \perp$
 $\text{IsUsedConstructorAsInitializer}(B, c, Y) \mapsto \perp$
 $\text{IsUsedConstructorAsObjectReceiver}(B, c, Y) \mapsto \perp$
 $\text{IsSubType}(B, c) \mapsto \perp$
 $\text{ExtendsDirectly}(B, c) \mapsto \perp$
 $\text{MethodIsUsedWithType}(B, Y, [P], [c]) \mapsto \perp$
 $\text{MethodIsUsedWithType}(B, Y, [P], [c; T1]) \mapsto \perp$
 $\text{MethodIsUsedWithType}(B, Y, [P], [T1; c]) \mapsto \perp$
 $\text{MethodIsUsedWithType}(B, Y, [P], [T1; c; T2]) \mapsto \perp$
 $\text{MethodIsUsedWithType}(B, Y, [P], [T1; T2; c]) \mapsto \perp$
 $\text{AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC}(c, T1, T2, T3) \mapsto \perp$
 $\text{AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded}(c, T1, T2) \mapsto \perp$
 $\text{BoundVariableInMethodBody}(c, T1, T2) \mapsto \perp$
 $\text{ExistsField}(c, F) \mapsto \perp$
 $\text{ExistsMethodInvocation}(c, Y, T1, X) \mapsto \perp$
 $\text{ExistsAbstractMethod}(c, Y) \mapsto \perp$
 $\text{IsIndirectlyRecursive}(c, Y) \mapsto \perp$
 $\text{IsVisibleMethod}(c, Y, [T1], B) \mapsto \perp$
 $\text{IsVisibleMethod}(c, Y, [T1; T2], B) \mapsto \perp$
 $\text{IsVisibleMethod}(c, Y, [T1; T2; T3], B) \mapsto \perp$
 $\text{IsVisibleMethod}(B, Y, [B], c) \mapsto \perp$
 $\text{IsVisibleMethod}(B, Y, [B; T1], c) \mapsto \perp$
 $\text{IsVisibleMethod}(B, Y, [T1; B], c) \mapsto \perp$
 $\text{IsVisibleMethod}(B, Y, [T1; T2; B], c) \mapsto \perp$
 $\text{IsVisibleMethod}(B, Y, [T1; B; T2], c) \mapsto \perp$
 $\text{IsVisibleMethod}(B, Y, [B; T1; T2], c) \mapsto \perp$
 $\text{IsInverter}(c, Y, T1, T2) \mapsto \perp$
 $\text{IsDelegator}(c, Y, X) \mapsto \perp$
 $\text{IsAbstractClass}(c) \mapsto \perp$
 $\text{IsUsedMethodIn}(c, Y, B) \mapsto \perp$
 $\text{IsUsedMethodIn}(B, Y, c) \mapsto \perp$
 $\text{IsPrimitiveType}(c) \mapsto \perp$
 $\text{IsPublic}(c, Y) \mapsto \perp$
 $\text{IsProtected}(c, Y) \mapsto \perp$
 $\text{IsPrivate}(c, Y) \mapsto \perp$
 $\text{IsUsedAttributeInMethodBody}(c, X, Y) \mapsto \perp$
 $\text{IsGenericsSubtype}(c, [T1], B, [T2]) \mapsto \perp$
 $\text{IsGenericsSubtype}(c, [T1; T2], B, [T4; T3]) \mapsto \perp$
 $\text{IsGenericsSubtype}(c, [T1; T2; T3], B, [T4; T5; T6]) \mapsto \perp$
 $\text{IsInheritedField}(c, F) \mapsto \perp$
 $\text{IsOverridden}(c, Y) \mapsto \perp$
 $\text{IsOverloaded}(c, Y) \mapsto \perp$
 $\text{IsOverriding}(c, Y) \mapsto \perp$
 $\text{IsRecursiveMethod}(c, Y) \mapsto \perp$

$\text{IsRecursiveMethod}(c, Y) \mapsto \perp$
 $\text{HasReturnType}(c, Y, T1) \mapsto \perp$
 $\text{HasParameterType}(c, T1) \mapsto \perp$
 $\text{HasParameterType}(B, c) \mapsto \perp$
 $\text{MethodHasParameterType}(c, Y, T1) \mapsto \perp$
 $\text{AllSubclasses}(c, [C1; C2; C3]) \mapsto \perp$
 $\text{ExtendsDirectly}(c, \text{java.lang.Object}) \mapsto \top$

A.2 CreateIndirectionInSuperClass

Overview: CreateIndirectionInSuperclass (classname s, subclasses [a,b], methodname m, types [t,t'], returntype q, newname n) : this operation is used to create an indirection of the method s::m to the method n in all the hierarchy.



Refactoring tools. With IntelliJ IDEA:

- Use *Change Signature* on the method m in class s (select “delegate via overloading method”, specify the new name n, specify the desired visibility).

With Eclipse:

- Use *Change Method Signature* on the method m in class s (specify to “keep original method as delegate to changed method”, and specify the new name n).

Precondition.

$(\text{ExistsClass}(s) \wedge \text{IsAbstractClass}(s) \wedge \text{ExistsMethodDefinitionWithParams}(s, m, [t; t']) \wedge \text{ExistsAbstractMethod}(s, m) \wedge \neg \text{IsInheritedMethod}(s, n) \wedge \neg \text{IsInheritedMethodWithParams}(s, n, [t; t']) \wedge \neg \text{ExistsMethodDefinitionWithParams}(s, n, [t; t']) \wedge \text{AllSubclasses}(s, [a; b]) \wedge \text{HasReturnType}(s, m, q) \wedge \neg \text{IsPrivate}(s, m) \wedge \neg \text{IsPrivate}(a, m) \wedge \neg \text{IsPrivate}(b, m) \wedge \text{ExistsMethodDefinition}(s, m) \wedge \text{ExistsMethodDefinition}(a, m) \wedge \text{ExistsMethodDefinition}(b, m) \wedge \neg \text{ExistsMethodDefinition}(s, n) \wedge \neg \text{ExistsMethodDefinition}(a, n) \wedge \neg \text{ExistsMethodDefinition}(b, n))$

Backward Description.

$\text{ExistsAbstractMethod}(s, n) \mapsto \top$
 $\text{ExistsAbstractMethod}(s, m) \mapsto \perp$
 $\text{IsDelegator}(s, m, n) \mapsto \top$
 $\text{IsInheritedMethodWithParams}(s, n, [t; t']) \mapsto \perp$
 $\text{IsOverriding}(s, n) \mapsto \perp$
 $\text{HasReturnType}(s, n, q) \mapsto \text{HasReturnType}(s, m, q)$
 $\text{HasReturnType}(a, n, q) \mapsto \text{HasReturnType}(s, m, q)$
 $\text{HasReturnType}(b, n, q) \mapsto \text{HasReturnType}(s, m, q)$
 $\text{ExistsMethodDefinition}(s, n) \mapsto \text{ExistsMethodDefinition}(s, m)$
 $\text{ExistsMethodDefinition}(a, n) \mapsto \text{ExistsMethodDefinition}(a, m)$
 $\text{ExistsMethodDefinition}(b, n) \mapsto \text{ExistsMethodDefinition}(b, m)$
 $\text{ExistsMethodDefinitionWithParams}(s, n, [t; t']) \mapsto \top$
 $\text{ExistsMethodDefinitionWithParams}(a, n, [t; t']) \mapsto \top$
 $\text{ExistsMethodDefinitionWithParams}(b, n, [t; t']) \mapsto \top$
 $\text{ExistsMethodDefinitionWithParams}(s, n, [P1]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(a, n, [P1]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(b, n, [P1]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(s, n, [P1; P2]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(a, n, [P1; P2]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(b, n, [P1; P2]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(s, n, [P1; P2; P3]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(a, n, [P1; P2; P3]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(b, n, [P1; P2; P3]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(s, n, [P1; P2; P3; P4]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(a, n, [P1; P2; P3; P4]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(b, n, [P1; P2; P3; P4]) \mapsto \perp$
 $\text{ExistsParameterWithName}(s, n, [t; t'], N) \mapsto \perp$
 $\text{ExistsParameterWithName}(a, n, [t; t'], N) \mapsto \perp$
 $\text{ExistsParameterWithName}(b, n, [t; t'], N) \mapsto \perp$
 $\text{ExistsParameterWithName}(s, n, [P1], N) \mapsto \text{ExistsParameterWithName}(s, m, [P1], N)$
 $\text{ExistsParameterWithName}(a, n, [P1], N) \mapsto \text{ExistsParameterWithName}(a, m, [P1], N)$
 $\text{ExistsParameterWithName}(b, n, [P1], N) \mapsto \text{ExistsParameterWithName}(b, m, [P1], N)$
 $\text{ExistsMethodDefinition}(a, m) \mapsto \perp$
 $\text{ExistsMethodDefinition}(b, m) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(a, m, [t; t']) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(b, m, [t; t']) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(a, m, [P1]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(b, m, [P1]) \mapsto \perp$
 $\text{IsIndirectlyRecursive}(a, n) \mapsto \text{IsRecursiveMethod}(a, m)$
 $\text{IsIndirectlyRecursive}(b, n) \mapsto \text{IsRecursiveMethod}(b, m)$
 $\text{ExistsMethodInvocation}(a, n, s, m) \mapsto \text{IsRecursiveMethod}(a, m)$
 $\text{ExistsMethodInvocation}(b, n, s, m) \mapsto \text{IsRecursiveMethod}(b, m)$
 $\text{BoundVariableInMethodBody}(s, n, V) \mapsto \text{BoundVariableInMethodBody}(s, m, V)$
 $\text{BoundVariableInMethodBody}(a, n, V) \mapsto \text{BoundVariableInMethodBody}(a, m, V)$
 $\text{BoundVariableInMethodBody}(b, n, V) \mapsto \text{BoundVariableInMethodBody}(b, m, V)$
 $\text{IsOverloaded}(s, n) \mapsto \perp$
 $\text{IsOverloaded}(a, n) \mapsto \perp$
 $\text{IsOverloaded}(b, n) \mapsto \perp$
 $\text{IsOverridden}(s, n) \mapsto \perp$
 $\text{IsOverridden}(a, n) \mapsto \text{IsOverridden}(a, m)$
 $\text{IsOverridden}(b, n) \mapsto \text{IsOverridden}(b, m)$


$\text{IsOverriding}(a, n) \mapsto \text{IsOverriding}(a, m)$
 $\text{IsOverriding}(b, n) \mapsto \text{IsOverriding}(b, m)$
 $\text{IsRecursiveMethod}(s, n) \mapsto \perp$
 $\text{IsRecursiveMethod}(a, n) \mapsto \perp$
 $\text{IsRecursiveMethod}(b, n) \mapsto \perp$
 $\text{AllInvokedMethodsOnObject0InBody0fMAreDeclaredInC}(s, n, N, V) \mapsto$
 $\quad \quad \quad \text{AllInvokedMethodsOnObject0InBody0fMAreDeclaredInC}(s, m, N, V)$
 $\text{AllInvokedMethodsOnObject0InBody0fMAreDeclaredInC}(a, n, N, V) \mapsto$
 $\quad \quad \quad \text{AllInvokedMethodsOnObject0InBody0fMAreDeclaredInC}(a, m, N, V)$
 $\text{AllInvokedMethodsOnObject0InBody0fMAreDeclaredInC}(b, n, N, V) \mapsto$
 $\quad \quad \quad \text{AllInvokedMethodsOnObject0InBody0fMAreDeclaredInC}(b, m, N, V)$
 $\text{AllInvokedMethodsWithParameter0InBody0fMAreNotOverloaded}(s, n, N) \mapsto$
 $\quad \quad \quad \text{AllInvokedMethodsWithParameter0InBody0fMAreNotOverloaded}(s, m, N)$
 $\text{AllInvokedMethodsWithParameter0InBody0fMAreNotOverloaded}(a, n, N) \mapsto$
 $\quad \quad \quad \text{AllInvokedMethodsWithParameter0InBody0fMAreNotOverloaded}(a, m, N)$
 $\text{AllInvokedMethodsWithParameter0InBody0fMAreNotOverloaded}(b, n, N) \mapsto$
 $\quad \quad \quad \text{AllInvokedMethodsWithParameter0InBody0fMAreNotOverloaded}(b, m, N)$
 $\text{IsPublic}(s, n) \mapsto \text{IsPublic}(s, m)$
 $\text{IsPublic}(a, n) \mapsto \text{IsPublic}(a, m)$
 $\text{IsPublic}(b, n) \mapsto \text{IsPublic}(b, m)$
 $\text{IsProtected}(s, n) \mapsto \text{IsProtected}(s, m)$
 $\text{IsProtected}(a, n) \mapsto \text{IsProtected}(a, m)$
 $\text{IsProtected}(b, n) \mapsto \text{IsProtected}(b, m)$
 $\text{IsPrivate}(s, \text{attribut}) \mapsto \perp$
 $\text{IsPrivate}(a, \text{attribut}) \mapsto \perp$
 $\text{IsPrivate}(b, \text{attribut}) \mapsto \perp$
 $\text{IsPrivate}(s, n) \mapsto \perp$
 $\text{IsPrivate}(a, n) \mapsto \perp$
 $\text{IsPrivate}(b, n) \mapsto \perp$
 $\text{IsOverriding}(a, n) \mapsto \text{IsOverriding}(a, m)$
 $\text{IsOverriding}(b, n) \mapsto \text{IsOverriding}(b, m)$
 $\text{IsDelegator}(a, n, V) \mapsto \text{IsDelegator}(a, m, V)$
 $\text{IsDelegator}(b, n, V) \mapsto \text{IsDelegator}(b, m, V)$
 $\text{IsDelegator}(a, V, n) \mapsto \text{IsDelegator}(a, V, m)$
 $\text{IsDelegator}(b, V, n) \mapsto \text{IsDelegator}(b, V, m)$
 $\text{IsInheritedMethodWithParams}(a, n, [t; t']) \mapsto \text{IsVisibleMethod}(s, m, [t; t'], a)$
 $\text{IsInheritedMethodWithParams}(b, n, [t; t']) \mapsto \text{IsVisibleMethod}(s, m, [t; t'], b)$
 $\text{MethodIsUsedWithType}(a, n, [t; t'], [t; t']) \mapsto \text{MethodIsUsedWithType}(a, m, [t; t'], [t; t'])$
 $\text{MethodIsUsedWithType}(b, n, [t; t'], [t; t']) \mapsto \text{MethodIsUsedWithType}(b, m, [t; t'], [t; t'])$
 $\text{IsUsedMethod}(a, n, [t; t']) \mapsto \text{IsUsedMethod}(a, m, [t; t'])$
 $\text{IsUsedMethod}(b, n, [t; t']) \mapsto \text{IsUsedMethod}(b, m, [t; t'])$
 $\text{IsUsedMethodIn}(a, n, V) \mapsto \text{IsUsedMethodIn}(a, m, V)$
 $\text{IsUsedMethodIn}(b, n, V) \mapsto \text{IsUsedMethodIn}(b, m, V)$
 $\text{IsInverter}(a, n, V, V1) \mapsto \text{IsInverter}(a, m, V, V1)$
 $\text{IsInverter}(b, n, V, V1) \mapsto \text{IsInverter}(b, m, V, V1)$
 $\text{ExistsMethodInvocation}(a, V, V1, n) \mapsto \text{ExistsMethodInvocation}(a, V, V1, m)$
 $\text{ExistsMethodInvocation}(b, V, V1, n) \mapsto \text{ExistsMethodInvocation}(b, V, V1, m)$
 $\text{IsIndirectlyRecursive}(a, n) \mapsto \text{IsIndirectlyRecursive}(a, m)$
 $\text{IsIndirectlyRecursive}(b, n) \mapsto \text{IsIndirectlyRecursive}(b, m)$
 $\text{BoundVariableInMethodBody}(a, n, V) \mapsto \text{BoundVariableInMethodBody}(a, n, V)$
 $\text{BoundVariableInMethodBody}(b, n, V) \mapsto \text{BoundVariableInMethodBody}(b, n, V)$
 $\text{IsOverridden}(a, n) \mapsto \text{IsOverridden}(a, m)$
 $\text{IsOverridden}(b, n) \mapsto \text{IsOverridden}(b, m)$

A.3 AddParameter

(*Add Parameter* in Fowler [Fow99] et [Koc02])

AddParameter(class c, method m, parameterType t, parameterName n, defaultvalue e):

Add a parameter of type t to a method m in class c. In method invocations, use the expression e as new parameter.



Refactoring tools. *Change Method signature* in Eclipse tool and *Change Signature* in IntelliJ IDEA.

A.4 AddParameterWithReuse

Overview: **AddParameterWithReuse** (classname s,subclasses [a,b], methodname m,methodparameters [] ,paramType t, paramName p, usedvalueofparamType defaultvalue): this operation is used to add the parameter p of type t to the parameters of the method s::m, a::m and b::m. Same as **AddParameter**, but instead of adding a default value for the additional parameter in invocations, use any value with the specified type that is visible from the invocation site.

In IntelliJ IDEA, this is specified with the *Any Var* option in *Change Signature*. This is not supported by Eclipse.

Note that when several variables of the specified type are visible, the result is unspecified. In the example of use in this report, the type of the added parameter is a fresh type, and in recursive methods, the only variable of this type is the parameter being introduced so that there is no ambiguity.

Precondition.

$$\begin{aligned}
 & (\neg \text{BoundVariableInMethodBody}(s, m, p) \\
 & \wedge \text{ExistsClass}(s) \\
 & \wedge \text{ExistsMethodDefinition}(s, m) \\
 & \wedge \text{ExistsMethodDefinitionWithParams}(s, m, []) \\
 & \wedge \neg \text{ExistsMethodDefinitionWithParams}(s, m, [t]) \\
 & \wedge \neg \text{IsInheritedMethodWithParams}(s, m, [t]) \\
 & \wedge \neg \text{ExistsParameterWithName}(s, m, [], p) \\
 & \wedge \text{ExistsType}(t) \\
 & \wedge \text{AllSubclasses}(s, [a; b]))
 \end{aligned}$$

Backward Description.


$$\begin{aligned}
 & \text{ExistsMethodDefinitionWithParams}(s, m, []) \mapsto \perp \\
 & \text{ExistsMethodDefinitionWithParams}(s, m, [t]) \mapsto \top \\
 & \text{ExistsMethodDefinitionWithParams}(a, m, []) \mapsto \neg \text{ExistsMethodDefinitionWithParams}(a, m, []) \\
 & \text{ExistsMethodDefinitionWithParams}(b, m, []) \mapsto \neg \text{ExistsMethodDefinitionWithParams}(b, m, []) \\
 & \text{ExistsMethodDefinitionWithParams}(a, m, [t]) \mapsto \text{ExistsMethodDefinitionWithParams}(a, m, []) \\
 & \text{ExistsMethodDefinitionWithParams}(b, m, [t]) \mapsto \text{ExistsMethodDefinitionWithParams}(b, m, []) \\
 & \text{ExistsParameterWithName}(s, m, [t], p) \mapsto \top \\
 & \text{ExistsParameterWithName}(a, m, [t], p) \mapsto \top \\
 & \text{ExistsParameterWithName}(b, m, [t], p) \mapsto \top \\
 & \text{ExistsParameterWithType}(s, m, [t], t) \mapsto \top \\
 & \text{ExistsParameterWithType}(a, m, [t], t) \mapsto \top \\
 & \text{ExistsParameterWithType}(b, m, [t], t) \mapsto \top
 \end{aligned}$$

```


AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC(s, m, p, T) ↪ T
AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC(a, m, p, T) ↪ T
AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC(b, m, p, T) ↪ T
AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded(s, m, p) ↪
    (¬IsOverloaded(s, m) ∧ ¬IsOverloaded(a, m) ∧ ¬IsOverloaded(b, m))
AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded(a, m, p) ↪
    (¬IsOverloaded(s, m) ∧ ¬IsOverloaded(a, m) ∧ ¬IsOverloaded(b, m))
AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded(b, m, p) ↪
    (¬IsOverloaded(s, m) ∧ ¬IsOverloaded(a, m) ∧ ¬IsOverloaded(b, m))
IsUsedConstructorAsMethodParameter(t, s, m) ↪ T
IsUsedConstructorAsMethodParameter(t, a, m) ↪ T
IsUsedConstructorAsMethodParameter(t, b, m) ↪ T

```

A.5 AddParameterWithDelegate



A.6 MoveMethod




Refactoring tools. If the receiver object is not used in the body of the initial class, it will not be included as parameter in the destination class, so that you have to add it (see *AddParameter*).

A.7 MoveMethodWithDelegate

(*Move Method* in Fowler [Fow99])

Overview: *MoveMethodWithDelegate* (classname s,attributes [att1,att2], targetclass a,methodtobemoved m, parameterstypes [t,a], returntype q, movedmethod n, receivingobjectname o, newreceivingobjectname o'): this operation is used to move the method s::m to the class a and rename it as n.

Transform a method m of a class s into a delegator to a method n in an other class a. The code of m has been moved to n (and adapted).



Refactoring tools. *Move* in Eclipse tool. In IntelliJ IDEA, first introduce a local delegate (with *Change Signature*), then *Move*.

Precondition.

$(\text{ExistsClass}(s) \wedge \text{ExistsClass}(a) \wedge \text{ExistsMethodDefinitionWithParams}(s, m, [t; a]) \wedge \text{ExistsParameterWithType}(s, m, [t; a], a) \wedge \text{ExistsParameterWithName}(s, m, [t; a], o) \wedge \neg \text{ExistsMethodDefinitionWithParams}(a, n, [t; s]) \wedge \text{HasReturnType}(s, m, q) \wedge \neg \text{IsPrivate}(s, m) \wedge \neg \text{IsPrivate}(s, att1) \wedge \neg \text{IsPrivate}(s, att2))$


Backward Description.

$\text{ExistsMethodDefinition}(a, n) \mapsto \top$
 $\text{ExistsMethodDefinitionWithParams}(a, n, [t; s]) \mapsto \top$
 $\text{HasReturnType}(a, n, q) \mapsto \text{HasReturnType}(s, m, q)$
 $\text{ExistsParameterWithName}(a, n, [t; s], N) \mapsto \text{ExistsParameterWithName}(s, m, [t; a], N) \quad (N \neq o)$
 $\text{ExistsParameterWithName}(a, n, [t; s], o') \mapsto \perp$
 $\text{ExistsParameterWithName}(a, n, [t; s], o) \mapsto \perp$
 $\text{ExistsParameterWithType}(a, n, [t; s], s) \mapsto \top$
 $\text{ExistsParameterWithType}(a, n, [t; s], a) \mapsto \perp$
 $\text{ExistsParameterWithType}(a, n, [t; s], T) \mapsto \text{ExistsParameterWithType}(s, m, [t; a], T) \quad (T \neq a) \wedge (T \neq s)$
 $\text{ExistsMethodInvocation}(s, m, a, n) \mapsto \top$
 $\text{IsInverter}(s, m, a, q) \mapsto \top$
 $\text{IsPrivate}(s, att1) \mapsto \perp$
 $\text{IsPrivate}(s, att2) \mapsto \perp$
 $\text{IsUsedAttributeInMethodBody}(s, att1, m) \mapsto \perp$
 $\text{IsUsedAttributeInMethodBody}(s, att2, m) \mapsto \perp$

A.8 RenameMethod

(*Rename* in Fowler [Fow99] et [Koc02])

`RenameMethod(class c, method m, newname n):` Rename the method *m* of class *c* into *n*.



Refactoring tools. *Rename* in Eclipse and IntelliJ IDEA.

We have identified two types of this operation. The first one does not accept the overloading, the second one accepts overloading.

A.8.1 RenameInHierarchyNoOverloading

Overview RenameInHierarchyNoOverloading (class c, subclasses [a,b], method m ,types [t,t'], newname n) : this operation is used to rename the method (c,a,b)::m into n if n does not already exist with another signature in the hierarchy.

Precondition.

$$\begin{aligned}
 & (\text{ExistsClass}(c)) \\
 & \wedge \text{ExistsClass}(a) \\
 & \wedge \text{ExistsClass}(b) \\
 & \wedge \text{ExistsMethodDefinition}(c, m) \\
 & \wedge \text{ExistsMethodDefinitionWithParams}(c, m, [t; t']) \\
 & \wedge \text{AllSubclasses}(c, [a; b]) \\
 & \wedge \neg \text{ExistsMethodDefinition}(c, n) \\
 & \wedge \neg \text{ExistsMethodDefinition}(a, n) \\
 & \wedge \neg \text{ExistsMethodDefinition}(b, n) \\
 & \wedge \neg \text{ExistsMethodDefinitionWithParams}(c, n, [t; t']) \\
 & \wedge \neg \text{ExistsMethodDefinitionWithParams}(a, n, [t; t']) \\
 & \wedge \neg \text{ExistsMethodDefinitionWithParams}(b, n, [t; t']) \\
 & \wedge \neg \text{IsOverloaded}(c, m) \\
 & \wedge \neg \text{IsOverloaded}(a, m) \\
 & \wedge \neg \text{IsOverloaded}(b, m) \\
 & \wedge \neg \text{IsInheritedMethod}(c, n)
 \end{aligned}$$

Backward Description.

$$\begin{aligned}
 & \text{ExistsMethodDefinition}(c, n) \leftrightarrow \top \\
 & \text{ExistsMethodDefinitionWithParams}(c, n, [t; t']) \leftrightarrow \top \\
 & \text{ExistsMethodDefinition}(a, n) \leftrightarrow \text{ExistsMethodDefinition}(a, m) \\
 & \text{ExistsMethodDefinition}(b, n) \leftrightarrow \text{ExistsMethodDefinition}(b, m) \\
 & \text{ExistsMethodDefinition}(c, m) \leftrightarrow \perp \\
 & \text{ExistsMethodDefinition}(a, m) \leftrightarrow \perp \\
 & \text{ExistsMethodDefinition}(b, m) \leftrightarrow \perp \\
 & \text{ExistsMethodDefinitionWithParams}(a, n, [t; t']) \leftrightarrow \text{ExistsMethodDefinitionWithParams}(a, m, [t; t']) \\
 & \text{ExistsMethodDefinitionWithParams}(b, n, [t; t']) \leftrightarrow \text{ExistsMethodDefinitionWithParams}(b, m, [t; t']) \\
 & \text{ExistsMethodDefinitionWithParams}(c, m, [t; t']) \leftrightarrow \perp \\
 & \text{ExistsMethodDefinitionWithParams}(a, m, [t; t']) \leftrightarrow \perp \\
 & \text{ExistsMethodDefinitionWithParams}(b, m, [t; t']) \leftrightarrow \perp \\
 & \text{IsInheritedMethod}(a, n) \leftrightarrow \text{IsInheritedMethod}(a, m) \\
 & \text{IsInheritedMethod}(b, n) \leftrightarrow \text{IsInheritedMethod}(b, m) \\
 & \text{IsDelegator}(c, n, M) \leftrightarrow \text{IsDelegator}(c, m, M) \\
 & \text{IsDelegator}(a, n, M) \leftrightarrow \text{IsDelegator}(a, m, M) \\
 & \text{IsDelegator}(b, n, M) \leftrightarrow \text{IsDelegator}(b, m, M)
 \end{aligned}$$

A.8.2 RenameOverloadedMethodInHierarchy

Overview RenameOverloadedMethodInHierarchy (class c,subclasses [a,b],method m ,newname n, types [t]) : this operation is used to rename the method (c,a,b)::m into n nevertheless n will be overloaded or not.

Precondition.

(ExistsClass(c)
 \wedge ExistsMethodDefinitionWithParams($c, m, [t]$)
 $\wedge \neg$ IsInheritedMethodWithParams($c, n, [t]$)
 $\wedge \neg$ ExistsMethodDefinitionWithParams($c, n, [t]$)
 $\wedge \neg$ ExistsMethodDefinitionWithParams($a, n, [t]$)
 $\wedge \neg$ ExistsMethodDefinitionWithParams($b, n, [t]$)
 $\wedge \neg$ IsInheritedMethodWithParams($c, m, [t]$)
 \wedge AllSubclasses($c, [a; b]$))

Backward Description.

ExistsMethodDefinition(c, m) $\mapsto \perp$
 ExistsMethodDefinition(c, n) $\mapsto \top$
 IsOverriding(c, n) $\mapsto \perp$
 IsOverridden(c, n) $\mapsto \perp$
 IsPublic(c, n) \mapsto IsPublic(c, m)
 ExistsMethodDefinitionWithParams($c, n, [t]$) \mapsto ExistsMethodDefinitionWithParams($c, m, [t]$)
 ExistsMethodDefinitionWithParams($a, n, [t]$) \mapsto ExistsMethodDefinitionWithParams($a, m, [t]$)
 ExistsMethodDefinitionWithParams($b, n, [t]$) \mapsto ExistsMethodDefinitionWithParams($b, m, [t]$)
 ExistsMethodDefinition(a, n) $\mapsto \top$
 ExistsMethodDefinition(b, n) $\mapsto \top$
 ExistsMethodDefinitionWithParams($c, m, [t]$) $\mapsto \perp$
 ExistsMethodDefinitionWithParams($a, m, [t]$) $\mapsto \perp$
 ExistsMethodDefinitionWithParams($b, m, [t]$) $\mapsto \perp$
 ExistsMethodDefinition(a, m) $\mapsto \perp$
 ExistsMethodDefinition(b, m) $\mapsto \perp$
 isOverridingMethod($a, n, [t]$) \mapsto isOverridingMethod($a, m, [t]$)
 isOverridingMethod($b, n, [t]$) \mapsto isOverridingMethod($b, m, [t]$)
 ExistsParameterWithName($c, n, [t], V$) \mapsto ExistsParameterWithName($c, m, [t], V$)
 ExistsParameterWithName($a, n, [t], V$) \mapsto ExistsParameterWithName($a, m, [t], V$)
 ExistsParameterWithName($b, n, [t], V$) \mapsto ExistsParameterWithName($b, m, [t], V$)
 ExistsParameterWithType($c, n, [t], V$) \mapsto ExistsParameterWithType($c, m, [t], V$)
 ExistsParameterWithType($a, n, [t], V$) \mapsto ExistsParameterWithType($a, m, [t], V$)
 ExistsParameterWithType($b, n, [t], V$) \mapsto ExistsParameterWithType($b, m, [t], V$)
 IsDelegator(c, n, V) \mapsto IsDelegator(c, m, V)
 IsDelegator(a, n, V) \mapsto IsDelegator(a, m, V)
 IsDelegator(b, n, V) \mapsto IsDelegator(b, m, V)
 IsDelegator(c, V, n) \mapsto IsDelegator(c, V, m)
 IsDelegator(a, V, n) \mapsto IsDelegator(a, V, m)
 IsDelegator(b, V, n) \mapsto IsDelegator(b, V, m)
 IsRecursiveMethod(c, n) \mapsto IsRecursiveMethod(c, m)
 IsRecursiveMethod(a, n) \mapsto IsRecursiveMethod(a, m)
 IsRecursiveMethod(b, n) \mapsto IsRecursiveMethod(b, m)
 ExistsAbstractMethod(c, n) \mapsto ExistsAbstractMethod(c, m)
 ExistsAbstractMethod(a, n) \mapsto ExistsAbstractMethod(a, m)
 ExistsAbstractMethod(b, n) \mapsto ExistsAbstractMethod(b, m)
 IsInheritedMethodWithParams($a, n, [t]$) \mapsto IsVisibleMethod($c, m, [t], a$)
 IsInheritedMethodWithParams($b, n, [t]$) \mapsto IsVisibleMethod($c, m, [t], b$)

$\text{MethodIsUsedWithType}(c, n, [t], [t]) \mapsto \text{MethodIsUsedWithType}(c, m, [t], [t])$
 $\text{MethodIsUsedWithType}(a, n, [t], [t]) \mapsto \text{MethodIsUsedWithType}(a, m, [t], [t])$
 $\text{MethodIsUsedWithType}(b, n, [t], [t]) \mapsto \text{MethodIsUsedWithType}(b, m, [t], [t])$
 $\text{IsUsedMethod}(c, n, [t]) \mapsto \text{IsUsedMethod}(c, m, [t])$
 $\text{IsUsedMethod}(a, n, [t]) \mapsto \text{IsUsedMethod}(a, m, [t])$
 $\text{IsUsedMethod}(b, n, [t]) \mapsto \text{IsUsedMethod}(b, m, [t])$
 $\text{IsUsedMethodIn}(c, n, V) \mapsto \text{IsUsedMethodIn}(c, m, V)$
 $\text{IsUsedMethodIn}(a, n, V) \mapsto \text{IsUsedMethodIn}(a, m, V)$
 $\text{IsUsedMethodIn}(b, n, V) \mapsto \text{IsUsedMethodIn}(b, m, V)$
 $\text{HasReturnType}(c, n, V) \mapsto \text{HasReturnType}(c, m, V)$
 $\text{HasReturnType}(a, n, V) \mapsto \text{HasReturnType}(a, m, V)$
 $\text{HasReturnType}(b, n, V) \mapsto \text{HasReturnType}(b, m, V)$
 $\text{IsInverter}(c, n, V, V1) \mapsto \text{IsInverter}(c, m, V, V1)$
 $\text{IsInverter}(a, n, V, V1) \mapsto \text{IsInverter}(a, m, V, V1)$
 $\text{IsInverter}(b, n, V, V1) \mapsto \text{IsInverter}(b, m, V, V1)$
 $\text{ExistsMethodInvocation}(c, V, V1, n) \mapsto \text{ExistsMethodInvocation}(c, V, V1, m)$
 $\text{ExistsMethodInvocation}(a, V, V1, n) \mapsto \text{ExistsMethodInvocation}(a, V, V1, m)$
 $\text{ExistsMethodInvocation}(b, V, V1, n) \mapsto \text{ExistsMethodInvocation}(b, V, V1, m)$
 $\text{IsIndirectlyRecursive}(c, n) \mapsto \text{IsIndirectlyRecursive}(c, m)$
 $\text{IsIndirectlyRecursive}(a, n) \mapsto \text{IsIndirectlyRecursive}(a, m)$
 $\text{IsIndirectlyRecursive}(b, n) \mapsto \text{IsIndirectlyRecursive}(b, m)$
 $\text{BoundVariableInMethodBody}(c, n, V) \mapsto \text{BoundVariableInMethodBody}(c, n, V)$
 $\text{BoundVariableInMethodBody}(a, n, V) \mapsto \text{BoundVariableInMethodBody}(a, n, V)$
 $\text{BoundVariableInMethodBody}(b, n, V) \mapsto \text{BoundVariableInMethodBody}(b, n, V)$
 $\text{IsOverridden}(a, n) \mapsto \text{IsOverridden}(a, m)$
 $\text{IsOverridden}(b, n) \mapsto \text{IsOverridden}(b, m)$
 $\text{IsUsedConstructorAsMethodParameter}(V, c, m) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(V, a, m) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(V, b, m) \mapsto \perp$

A.8.3 RenameDelegatorWithOverloading

Overview `RenameDelegatorWithOverloading (classname s, subclasses [a,b], method m, paramtype t, paramName pn, super type-Ofparamtype t', newname n)` : this operation is used to rename the method (c,a,b)::m into n and accepts overloaded methods. This operation is an ad-hoc use of the operation `RenameOverloadedMethodInHierarchy` (we need in this use more details about the signature of the method to be renamed).

Precondition.

$(\text{ExistsClass}(s) \wedge \text{ExistsClass}(a) \wedge \text{ExistsClass}(b) \wedge \text{ExistsMethodDefinition}(s, m) \wedge \text{ExistsMethodDefinitionWithParams}(s, m, [t]) \wedge \text{AllSubclasses}(s, [a; b]) \wedge \neg \text{ExistsMethodDefinitionWithParams}(s, n, [t]) \wedge \neg \text{ExistsMethodDefinitionWithParams}(a, n, [t]) \wedge \neg \text{ExistsMethodDefinitionWithParams}(b, n, [t]) \wedge \neg \text{IsInheritedMethod}(s, n) \wedge \neg \text{ExistsMethodDefinitionWithParams}(s, n, [t]))$

Backward Description. $\text{ExistsMethodDefinition}(s, n) \mapsto \top$

$\text{ExistsMethodDefinitionWithParams}(s, n, [t]) \mapsto \top$

$\text{IsPublic}(s, n) \mapsto \text{IsPublic}(s, m)$


$\text{ExistsMethodDefinition}(s, m) \mapsto \perp$
 $\text{ExistsMethodDefinition}(a, m) \mapsto \perp$
 $\text{ExistsMethodDefinition}(b, m) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(s, m, [t]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(a, m, [t]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(b, m, [t]) \mapsto \perp$
 $\text{ExistsMethodDefinition}(a, n) \mapsto \text{ExistsMethodDefinition}(a, m)$
 $\text{ExistsMethodDefinition}(b, n) \mapsto \text{ExistsMethodDefinition}(b, m)$
 $\text{ExistsMethodDefinitionWithParams}(a, n, [t]) \mapsto \text{ExistsMethodDefinitionWithParams}(a, m, [t])$
 $\text{ExistsMethodDefinitionWithParams}(b, n, [t]) \mapsto \text{ExistsMethodDefinitionWithParams}(b, m, [t])$
 $\text{IsInheritedMethod}(a, n) \mapsto \text{IsInheritedMethod}(a, m)$
 $\text{IsInheritedMethod}(b, n) \mapsto \text{IsInheritedMethod}(b, m)$
 $\text{MethodIsUsedWithType}(s, n, [t], [t]) \mapsto \text{MethodIsUsedWithType}(s, m, [t], [t])$
 $\text{MethodIsUsedWithType}(a, n, [t], [t]) \mapsto \text{MethodIsUsedWithType}(a, m, [t], [t])$
 $\text{MethodIsUsedWithType}(b, n, [t], [t]) \mapsto \text{MethodIsUsedWithType}(b, m, [t], [t])$
 $\text{MethodIsUsedWithType}(s, m, [t], [t]) \mapsto \perp$
 $\text{MethodIsUsedWithType}(a, m, [t], [t]) \mapsto \perp$
 $\text{MethodIsUsedWithType}(b, m, [t], [t]) \mapsto \perp$
 $\text{ExistsParameterWithName}(s, n, [t], V) \mapsto \text{ExistsParameterWithName}(s, m, [t], V)$
 $\text{ExistsParameterWithName}(a, n, [t], V) \mapsto \text{ExistsParameterWithName}(a, m, [t], V)$
 $\text{ExistsParameterWithName}(b, n, [t], V) \mapsto \text{ExistsParameterWithName}(b, m, [t], V)$
 $\text{ExistsParameterWithType}(s, n, [t], V) \mapsto \text{ExistsParameterWithType}(s, m, [t], V)$
 $\text{ExistsParameterWithType}(a, n, [t], V) \mapsto \text{ExistsParameterWithType}(a, m, [t], V)$
 $\text{ExistsParameterWithType}(b, n, [t], V) \mapsto \text{ExistsParameterWithType}(b, m, [t], V)$
 $\text{ExistsMethodInvocation}(s, V1, V, n) \mapsto \text{ExistsMethodInvocation}(s, V1, V, m)$
 $\text{ExistsMethodInvocation}(a, V1, V, n) \mapsto \text{ExistsMethodInvocation}(a, V1, V, m)$
 $\text{ExistsMethodInvocation}(b, V1, V, n) \mapsto \text{ExistsMethodInvocation}(b, V1, V, m)$
 $\text{IsDelegator}(s, n, V) \mapsto \text{IsDelegator}(s, m, V)$
 $\text{IsDelegator}(a, n, V) \mapsto \text{IsDelegator}(a, m, V)$
 $\text{IsDelegator}(b, n, V) \mapsto \text{IsDelegator}(b, m, V)$
 $\text{IsDelegator}(s, V, n) \mapsto \text{IsDelegator}(s, V, m)$
 $\text{IsDelegator}(a, V, n) \mapsto \text{IsDelegator}(a, V, m)$
 $\text{IsDelegator}(b, V, n) \mapsto \text{IsDelegator}(b, V, m)$
 $\text{IsUsedMethod}(s, n, [t]) \mapsto \text{IsUsedMethod}(s, m, [t])$
 $\text{IsUsedMethod}(a, n, [t]) \mapsto \text{IsUsedMethod}(a, m, [t])$
 $\text{IsUsedMethod}(b, n, [t]) \mapsto \text{IsUsedMethod}(b, m, [t])$
 $\text{IsUsedMethodIn}(s, n, V) \mapsto \text{IsUsedMethodIn}(s, m, V)$
 $\text{IsUsedMethodIn}(a, n, V) \mapsto \text{IsUsedMethodIn}(a, m, V)$
 $\text{IsUsedMethodIn}(b, n, V) \mapsto \text{IsUsedMethodIn}(b, m, V)$
 $\text{HasReturnType}(s, n, V) \mapsto \text{HasReturnType}(s, m, V)$
 $\text{HasReturnType}(a, n, V) \mapsto \text{HasReturnType}(a, m, V)$
 $\text{HasReturnType}(b, n, V) \mapsto \text{HasReturnType}(b, m, V)$
 $\text{IsInverter}(s, n, V, V1) \mapsto \text{IsInverter}(s, m, V, V1)$
 $\text{IsInverter}(a, n, V, V1) \mapsto \text{IsInverter}(a, m, V, V1)$
 $\text{IsInverter}(b, n, V, V1) \mapsto \text{IsInverter}(b, m, V, V1)$
 $\text{IsIndirectlyRecursive}(s, n) \mapsto \text{IsIndirectlyRecursive}(s, m)$
 $\text{IsIndirectlyRecursive}(a, n) \mapsto \text{IsIndirectlyRecursive}(a, m)$
 $\text{IsIndirectlyRecursive}(b, n) \mapsto \text{IsIndirectlyRecursive}(b, m)$
 $\text{BoundVariableInMethodBody}(s, n, V) \mapsto \text{BoundVariableInMethodBody}(s, n, V)$
 $\text{BoundVariableInMethodBody}(a, n, V) \mapsto \text{BoundVariableInMethodBody}(a, n, V)$
 $\text{BoundVariableInMethodBody}(b, n, V) \mapsto \text{BoundVariableInMethodBody}(b, n, V)$
 $\text{IsOverridden}(a, n) \mapsto \text{IsOverridden}(a, m)$

$\text{IsOverridden}(b, n) \mapsto \text{IsOverridden}(b, m)$
 $\text{IsUsedConstructorAsMethodParameter}(V, s, m) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(V, a, m) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(V, b, m) \mapsto \perp$

A.9 ExtractSuperClass

(*Extract Super Class* in Fowler [Fow99] and [Koc02])

Overview: *ExtractSuperClass* (subclasses[a,b], superclass s, methodsOfsubclasses [m,n], returntype t): this operation is used to extract a super-class s from the classes a and b and make an abstract declaration of methods a::m, a::n, b::m and b::n in this new super-class.



Refactoring tools. *Extract Superclass* in Eclipse tool and IntelliJ IDEA. In IntelliJ IDEA, the *Extract Superclass* operation cannot be applied to several classes simultaneously, so we have maintain the code of this operation in order to run it on several classes.

Precondition.

$(\neg \text{existsType}(s))$
 $\wedge \text{ExistsClass}(a)$
 $\wedge \text{ExistsClass}(b)$
 $\wedge \text{ExtendsDirectly}(a, \text{java.lang.Object})$
 $\wedge \text{ExtendsDirectly}(b, \text{java.lang.Object})$
 $\wedge \text{HasReturnType}(a, m, t)$
 $\wedge \text{HasReturnType}(a, n, t)$
 $\wedge \text{HasReturnType}(b, m, t)$
 $\wedge \text{HasReturnType}(b, n, t))$

Backward Description.

$\text{IsAbstractClass}(s) \mapsto \top$
 $\text{ExistsClass}(s) \mapsto \top$
 $\text{ExistsType}(s) \mapsto \top$
 $\text{ExistsMethodDefinition}(s, X) \mapsto (\text{ExistsMethodDefinition}(a, X) \wedge \text{ExistsMethodDefinition}(b, X))$
 $\text{ExistsMethodDefinitionWithParams}(s, X, []) \mapsto (\text{ExistsMethodDefinitionWithParams}(a, X, []) \wedge \text{ExistsMethodDefinitionWithParams}(b, X, []))$
 $\text{ExistsMethodDefinitionWithParams}(s, X, [Y]) \mapsto (\text{ExistsMethodDefinitionWithParams}(a, X, [Y]) \wedge \text{ExistsMethodDefinitionWithParams}(b, X, [Y]))$
 $\text{IsUsedMethodIn}(s, X, Y) \mapsto \perp$

```

ExistsMethodDefinitionWithParams( $X, Y, [s]$ )  $\mapsto \perp$ 
IsUsedMethod( $s, X, [Y]$ )  $\mapsto \perp$ 
AllSubclasses( $s, [a; b]$ )  $\mapsto \top$ 
MethodIsUsedWithType( $X, Y, [Z], [s]$ )  $\mapsto \perp$ 
IsInheritedMethodWithParams( $X, Y, [s]$ )  $\mapsto \perp$ 
IsUsedConstructorAsMethodParameter( $s, X, Y$ )  $\mapsto \perp$ 
IsUsedConstructorAsInitializer( $s, X, Y$ )  $\mapsto \perp$ 
IsUsedConstructorAsObjectReceiver( $s, X, Y$ )  $\mapsto \perp$ 
IsPrimitiveType( $s$ )  $\mapsto \perp$ 
IsSubType( $a, s$ )  $\mapsto \top$ 
IsSubType( $b, s$ )  $\mapsto \top$ 
IsSubType( $X, s$ )  $\mapsto$  IsSubType( $X, a$ )
IsSubType( $X, s$ )  $\mapsto$  IsSubType( $X, b$ )
IsPublic( $s, m$ )  $\mapsto \top$ 
IsPublic( $s, n$ )  $\mapsto \top$ 
ExistsAbstractMethod( $s, m$ )  $\mapsto \top$ 
ExistsAbstractMethod( $s, n$ )  $\mapsto \top$ 
IsOverriding( $s, m$ )  $\mapsto \perp$ 
IsOverriding( $s, n$ )  $\mapsto \perp$ 
IsOverridden( $s, m$ )  $\mapsto \top$ 
IsOverridden( $s, n$ )  $\mapsto \top$ 
IsPrivate( $s, m$ )  $\mapsto \perp$ 
IsPrivate( $s, n$ )  $\mapsto \perp$ 

```

A.9.1 ExtractSuperClassWithoutPullUp

Overview: ExtractSuperClassWithoutPullUp (subclasses[a,b], superclass s): this operation is a specific variant of the operation extract super-class. It is simply used to extract a super-class without pull up the methods of sub-classes.

Precondition.


$$\begin{aligned} & (\neg \text{ExistsType}(s) \\ & \wedge \text{ExistsClass}(a) \\ & \wedge \text{ExistsClass}(b) \\ & \wedge \text{ExtendsDirectly}(a, \text{java.lang.Object}) \\ & \wedge \text{ExtendsDirectly}(b, \text{java.lang.Object})) \end{aligned}$$

Backward Description.

$$\begin{aligned} & \text{IsAbstractClass}(s) \mapsto \top \\ & \text{ExistsClass}(s) \mapsto \top \\ & \text{ExistsType}(s) \mapsto \top \\ & \text{AllSubclasses}(s, [a; b]) \mapsto \top \\ & \text{IsSubType}(a, s) \mapsto \top \\ & \text{IsSubType}(b, s) \mapsto \top \\ & \text{IsSubType}(X, s) \mapsto \text{IsSubType}(X, a) \\ & \text{IsSubType}(X, s) \mapsto \text{IsSubType}(X, b) \end{aligned}$$

A.10 GeneraliseParameter

Overview: GeneraliseParameter (classname s, subclasses [a,b], methodname m, paramName p, type t , supertype st): this operation is used to change the type t of the parameter p of the methods s::m, a::m and b::m into a super-type st. All the uses of the parameter which type is changed must be legal with the new type st (method invocations, object passed as parameter of other methods). The uses of the parameter which type is changed as parameter of methods must not result in a charge of the invoked code (static resolving of overloading).



Refactoring tools. *Change Method Signature* in Eclipse tool and *Type Migration* in IntelliJ IDEA (or *Change Signature*).

Precondition.

$$\begin{aligned}
& (\text{ExistsClass}(s) \\
& \wedge \text{ExistsClass}(a) \\
& \wedge \text{ExistsClass}(b) \\
& \wedge \text{ExistsMethodDefinition}(s, m) \\
& \wedge \text{ExistsMethodDefinition}(a, m) \\
& \wedge \text{ExistsMethodDefinition}(b, m) \\
& \wedge \text{IsSubType}(st, t) \\
& \wedge \text{AllSubclasses}(s, [a; b]) \\
& \wedge \text{IsLocalInvokedMethod}(s, m, p, t) \\
& \wedge \text{IsLocalInvokedMethod}(a, m, p, t) \\
& \wedge \text{IsLocalInvokedMethod}(b, m, p, t) \\
& \wedge \text{NotInvolvedInOverlaodingResolution}(s, m, p) \\
& \wedge \text{NotInvolvedInOverlaodingResolution}(a, m, p) \\
& \wedge \text{NotInvolvedInOverlaodingResolution}(b, m, p))
\end{aligned}$$

Backward Description.

$$\begin{aligned}
& \text{IsInverter}(s, m, t, V) \mapsto \text{IsInverter}(s, m, st, V) \\
& \text{IsInverter}(a, m, t, V) \mapsto \text{IsInverter}(a, m, st, V) \\
& \text{IsInverter}(b, m, t, V) \mapsto \text{IsInverter}(b, m, st, V) \\
& \text{ExistsMethodDefinitionWithParams}(s, m, [t]) \mapsto \text{ExistsMethodDefinitionWithParams}(s, m, [st]) \\
& \text{ExistsMethodDefinitionWithParams}(a, m, [t]) \mapsto \text{ExistsMethodDefinitionWithParams}(a, m, [st]) \\
& \text{ExistsMethodDefinitionWithParams}(b, m, [t]) \mapsto \text{ExistsMethodDefinitionWithParams}(b, m, [st]) \\
& \text{ExistsMethodDefinitionWithParams}(s, m, [st]) \mapsto \perp \\
& \text{ExistsMethodDefinitionWithParams}(a, m, [st]) \mapsto \perp \\
& \text{ExistsMethodDefinitionWithParams}(b, m, [st]) \mapsto \perp \\
& \text{IsInheritedMethodWithParams}(a, m, [t]) \mapsto \top \\
& \text{IsInheritedMethodWithParams}(b, m, [t]) \mapsto \top \\
& \text{IsUsedConstructorAsMethodParameter}(t, s, m) \mapsto \top \\
& \text{IsUsedConstructorAsMethodParameter}(t, a, m) \mapsto \top \\
& \text{IsUsedConstructorAsMethodParameter}(t, b, m) \mapsto \top \\
& \text{IsUsedConstructorAsMethodParameter}(st, s, m) \mapsto \perp \\
& \text{IsUsedConstructorAsMethodParameter}(st, a, m) \mapsto \perp \\
& \text{IsUsedConstructorAsMethodParameter}(st, b, m) \mapsto \perp \\
& \text{IsOverridden}(a, m) \mapsto \text{ExistsMethodDefinition}(a, m) \\
& \text{IsOverridden}(b, m) \mapsto \text{ExistsMethodDefinition}(b, m) \\
& \text{IsOverriding}(a, m) \mapsto \text{ExistsMethodDefinition}(a, m) \\
& \text{IsOverriding}(b, m) \mapsto \text{ExistsMethodDefinition}(b, m)
\end{aligned}$$

```

ExistsParameterWithName(s, m, [t], p) ↪ T
ExistsParameterWithName(a, m, [t], p) ↪ T
ExistsParameterWithName(b, m, [t], p) ↪ T
ExistsParameterWithType(s, m, [t], t) ↪ T
ExistsParameterWithType(a, m, [t], t) ↪ T
ExistsParameterWithType(b, m, [t], t) ↪ T

```

A.11 MergeDuplicateMethods


Overview MergeDuplicateMethods (classname c, subclasses [a,b],mergedmethods [m,n],newmethod m2, invertedtype t, returntype q): this operation is used to merge methods m and n existing in the hierarchy to a single method m2. The formal description of this operation is built on the formal description of five refactoring operations since it is composed of these operations.

Algorithm of the operation The operation MergeDuplicateMethods is based on four steps :

```

MergeDuplicateMethods (c,[a,b],[m,n],m2,t,q) =
1. ReplaceMethodcodeDuplicatesInverter (c, m, [n], t,q))
2. PullupConcreteDelegator(c, [a,b], n ,m))
3. InlineAndDelete(c,n))
4. RenamelnHierarchyNoOverloading (c, [a,b], m,[t], m2)

```



Refactoring tools. *Rename, Replace Method duplication, Extract Method, In-line* in Eclipse, *Rename, Replace Method Code Duplicates, Pull Up, Inline* in IntelliJ IDEA:

Notes.

- ReplaceCodeDuplicates introduces a delegation. After that, the code for m2 is the same in all the subclasses of c (a delegation). Then the pull-up can be done without changing the semantics, which allows to inline (and remove) m2 afterwards.
- After the first pull-up, the IntelliJ IDEA pull-up warns that some code already exists. The first time, when some code replaces the abstract declaration, the refactorer manages to remove the abstract declaration. The next times,

when a second code comes in addition of the first one, the refactorer prefers to leave the two versions (which are identical in this case), so that we have to use *safe delete* to remove one of them.

We could provide an extension of the *pull-up* operation with the customized behavior.

Preconditions:

- The two concerned methods bodies must be syntactically equals.
- The new name must not introduce an overloading.
- The two methods must not be overloaded.

A.12 ReplaceMethodcodeDuplicatesInverter

Overview ReplaceMethodcodeDuplicatesInverter (classname c, method m, copies [n,m1],invertedtype t,returntype q) : this operation is used to replace c::[n,m1] by c::m.

Precondition.

$$\begin{aligned} & (\text{ExistsClass}(c)) \\ & \wedge (\text{ExistsMethodDefinition}(c, m)) \\ & \wedge \text{ExistsMethodDefinition}(c, n) \\ & \wedge \text{ExistsMethodDefinition}(c, m1)) \\ & \wedge (\text{IsInverter}(c, m, t, q)) \\ & \wedge \text{IsInverter}(c, n, t, q) \\ & \wedge \text{IsInverter}(c, m1, t, q))) \end{aligned}$$

Backward Description.

$$\begin{aligned} & \text{IsDelegator}(c, n, m) \mapsto \top \\ & \text{IsDelegator}(c, m1, m) \mapsto \top \\ & \text{ExistsMethodInvocation}(c, n, c, m) \mapsto \perp \\ & \text{ExistsMethodInvocation}(c, m1, c, m) \mapsto \perp \\ & \text{IsRecursiveMethod}(c, n) \mapsto \perp \\ & \text{IsRecursiveMethod}(c, m1) \mapsto \perp \end{aligned}$$

A.13 SafeDeleteDelegatorOverriding

Overview SafeDeleteDelegatorOverriding (classname c, method m, superclass s, deleguee n) : this operations is used to remove useless overridings.

Precondition. ($\text{ExistsClass}(c)$
 $\wedge \text{ExistsClass}(s)$
 $\wedge \text{ExistsMethodDefinition}(c, m)$
 $\wedge \text{ExistsMethodDefinition}(s, m)$
 $\wedge \text{IsDelegator}(c, m, n)$
 $\wedge \text{IsDelegator}(s, m, n)$
 $\wedge \text{NotInvolvedInOverlaodingResolution}(c, m, this))$

Backward Description.

$$\begin{aligned} & \text{ExistsMethodDefinition}(c, m) \mapsto \perp \\ & \text{IsInheritedMethod}(c, m) \mapsto \top \\ & \text{AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC}(c, m, X, Y) \mapsto \perp \\ & \text{AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded}(c, m, X) \mapsto \perp \\ & \text{BoundVariableInMethodBody}(c, m, X) \mapsto \perp \\ & \text{ExistsParameterWithName}(c, m, [X], Y) \mapsto \perp \\ & \text{ExistsParameterWithType}(c, m, [X], Y) \mapsto \perp \\ & \text{ExistsMethodInvocation}(c, m, X, Y) \mapsto \perp \end{aligned}$$

```


ExistsMethodDefinitionWithParams( $c, m, [X]$ )  $\mapsto \perp$ 
IsInheritedMethodWithParams( $X, m, [Y]$ )  $\mapsto \perp$ 
IsIndirectlyRecursive( $c, m$ )  $\mapsto \perp$ 
IsVisibleMethod( $c, m, [X], Y$ )  $\mapsto \perp$ 
IsInverter( $c, m, X, Y$ )  $\mapsto \perp$ 
IsDelegator( $c, m, X$ )  $\mapsto \perp$ 
IsUsedMethod( $c, m, [X]$ )  $\mapsto \perp$ 
IsUsedMethodIn( $c, m, X$ )  $\mapsto \perp$ 
IsUsedConstructorAsMethodParameter( $X, c, m$ )  $\mapsto \perp$ 
IsUsedConstructorAsInitializer( $X, c, m$ )  $\mapsto \perp$ 
IsUsedConstructorAsObjectReceiver( $X, c, m$ )  $\mapsto \perp$ 
IsPublic( $c, m$ )  $\mapsto \perp$ 
IsProtected( $c, m$ )  $\mapsto \perp$ 
IsPrivate( $c, m$ )  $\mapsto \perp$ 
IsUsedAttributeInMethodBody( $c, X, m$ )  $\mapsto \perp$ 
IsOverridden( $c, m$ )  $\mapsto \perp$ 
IsOverloaded( $c, m$ )  $\mapsto \perp$ 
IsOverriding( $c, m$ )  $\mapsto \perp$ 
IsRecursiveMethod( $c, m$ )  $\mapsto \perp$ 
HasReturnType( $c, m, X$ )  $\mapsto \perp$ 
MethodHasParameterType( $c, m, X$ )  $\mapsto \perp$ 
MethodIsUsedWithType( $c, m, [X], [X]$ )  $\mapsto \perp$ 

```

A.14 PullUpAbstract

PullUpAbstract(set of classes C, method m, interface s)

Pull up a method implemented in a set of classes C to their superclass s: do not move the definitions, just declare the method abstract in s.




Refactoring tools. *Pull Up* in Eclipse tool and IntelliJ IDEA.

Preconditions:

- s is a superclass of each class in C.
- m is defined in all the classes of C

A.15 PullUpImplementation

Overview: PullupImplementation($a, [att1, att2], m, s$): this operation is used to pull up the definition of the method $a::m$ to s and delete it from a .



Refactoring tools. *Pull Up* in Eclipse tool and IntelliJ IDEA.

Precondition.

$$\begin{aligned}
 & (\text{ExistsClass}(a) \\
 & \wedge \text{ExistsClass}(s) \\
 & \wedge \text{IsAbstractClass}(s) \\
 & \wedge \text{ExistsMethodDefinition}(a, m) \\
 & \wedge \text{ExistsAbstractMethod}(s, m) \\
 & \wedge \text{AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC}(a, m, this, s) \\
 & \wedge \text{AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded}(a, m, this) \\
 & \wedge \neg \text{IsPrivate}(a, m) \\
 & \wedge \neg \text{IsUsedAttributeInMethodBody}(a, att1, m) \\
 & \wedge \neg \text{IsUsedAttributeInMethodBody}(a, att2, m))
 \end{aligned}$$


Backward Description.

$$\begin{aligned}
 & \text{ExistsMethodDefinition}(a, m) \mapsto \perp \\
 & \text{ExistsMethodDefinition}(s, m) \mapsto \top \\
 & \text{ExistsAbstractMethod}(s, m) \mapsto \perp \\
 & \text{IsDelegator}(s, m, X) \mapsto \text{IsDelegator}(a, m, X) \quad (m \neq X) \\
 & \text{ExistsMethodDefinitionWithParams}(a, m, [X]) \mapsto \perp \\
 & \text{ExistsMethodDefinitionWithParams}(s, m, [X]) \mapsto \top \\
 & \text{IsInheritedMethodWithParams}(a, m, [X]) \mapsto \top \\
 & \text{IsInheritedMethod}(a, m) \mapsto \top \\
 & \text{IsVisibleMethod}(s, m, [X], a) \mapsto \top \\
 & \text{IsPrivate}(a, m) \mapsto \perp \\
 & \text{IsOverridden}(a, m) \mapsto \perp \\
 & \text{IsOverriding}(a, m) \mapsto \perp \\
 & \text{IsVisible}(s, m, a) \mapsto \top \\
 & \text{IsOverloaded}(s, m) \mapsto \text{ExistsMethodDefinition}(s, m) \\
 & \text{IsUsedAttributeInMethodBody}(a, X, m) \mapsto \perp \\
 & \text{IsOverridden}(a, m) \mapsto \perp \\
 & \text{IsOverloaded}(a, m) \mapsto \perp \\
 & \text{IsRecursiveMethod}(a, m) \mapsto \perp \\
 & \text{HasReturnType}(a, m, X) \mapsto \perp
 \end{aligned}$$

$\text{MethodHasParameterType}(a, m, X) \mapsto \perp$
 $\text{MethodIsUsedWithType}(a, m, [X], [X]) \mapsto \perp$
 $\text{IsPrivate}(a, att1) \mapsto \perp$
 $\text{IsPrivate}(a, att2) \mapsto \perp$

A.16 PullUpWithGenerics

Overview: PullupWithGenerics (classname s, subclassname a, [att1,att2],methodname m,returntype RT ,parameterType T): this operation is used to pull up the method a::m to s and then creates the parameter type T to the class s (as shown in the following figure). After performing this operation a polymorphism is created in the hierarchy (Java Generic types).



Refactoring tools. We provide this operation as a plugin for IntelliJ IDEA (*Pull up method refactoring extension: http://plugins.intellij.net/plugin/?idea_ce&id=6889*).

Precondition.

$(\text{ExistsClass}(s))$
 $\wedge \text{IsAbstractClass}(s)$
 $\wedge \text{ExistsClass}(a)$
 $\wedge \text{IsSubType}(a, s)$
 $\wedge \neg \text{ExistsAbstractMethod}(s, m)$
 $\wedge \text{AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC}(a, m, this, s)$
 $\wedge \text{AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded}(a, m, this)$
 $\wedge \neg \text{IsPrimitiveType}(RT)$
 $\wedge \neg \text{HasParameterType}(a, RT)$
 $\wedge (\neg \text{IsUsedAttributeInMethodBody}(a, att1, m) \vee \neg \text{IsPrivate}(a, att1))$
 $\wedge (\neg \text{IsUsedAttributeInMethodBody}(a, att2, m) \vee \neg \text{IsPrivate}(a, att2))$

Backward Description.


$\text{ExistsAbstractMethod}(s, m) \mapsto \top$
 $\text{HasReturnType}(s, m, T) \mapsto \top$
 $\text{MethodHasParameterType}(s, m, T) \mapsto \top$
 $\text{HasParameterType}(s, T) \mapsto \top$

$\text{extendsFromParametricClass}(a, s, RT) \mapsto \top$
 $\text{IsGenericsSubtype}(a, [RT], s, [T]) \mapsto \top$
 $\text{IsPrivate}(a, m) \mapsto \perp$
 $\text{IsOverridden}(a, m) \mapsto \top$
 $\text{IsOverriding}(a, m) \mapsto \top$

A.17 InlineAndDelete

(*Inline Method* in [Fow99])

Overview: `InlineAndDelete (classname s,methodname m)`: this operation is used to replace one or all invocations of a given method by its body and delete it.



Refactoring tools. *In-line* in Eclipse tool and IntelliJ IDEA.

Precondition.

$(\text{ExistsClass}(c))$
 $\wedge \text{ExistsMethodDefinition}(c, m)$
 $\wedge \neg \text{IsOverriding}(c, m)$
 $\wedge \neg \text{IsOverridden}(c, m)$
 $\wedge \neg \text{IsRecursiveMethod}(c, m))$


Backward Description.

$\text{ExistsMethodDefinition}(s, m) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(s, m, []) \mapsto \perp$
 $\text{AllInvokedMethodsOnObjectInBodyOfMAreDeclaredInC}(s, m, X, Y) \mapsto \perp$
 $\text{AllInvokedMethodsWithParameterInBodyOfMAreNotOverloaded}(s, m, X) \mapsto \perp$
 $\text{BoundVariableInMethodBody}(s, m, X) \mapsto \perp$
 $\text{ExistsParameterWithName}(s, m, [X], Y) \mapsto \perp$
 $\text{ExistsParameterWithType}(s, m, [X], Y) \mapsto \perp$
 $\text{ExistsMethodInvocation}(s, m, X, Y) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(s, m, [X]) \mapsto \perp$
 $\text{IsInheritedMethodWithParams}(X, m, [Y]) \mapsto \perp$
 $\text{IsIndirectlyRecursive}(s, m) \mapsto \perp$
 $\text{IsVisibleMethod}(s, m, [X], Y) \mapsto \perp$
 $\text{IsInverter}(s, m, X, Y) \mapsto \perp$
 $\text{IsDelegator}(s, m, X) \mapsto \perp$
 $\text{IsUsedMethod}(s, m, [X]) \mapsto \perp$
 $\text{IsUsedMethodIn}(s, m, X) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(X, s, m) \mapsto \perp$
 $\text{IsUsedConstructorAsInitializer}(X, s, m) \mapsto \perp$

$\text{IsUsedConstructorAsObjectReceiver}(X, s, m) \mapsto \perp$
 $\text{IsPublic}(s, m) \mapsto \perp$
 $\text{IsProtected}(s, m) \mapsto \perp$
 $\text{IsPrivate}(s, m) \mapsto \perp$
 $\text{IsUsedAttributeInMethodBody}(s, X, m) \mapsto \perp$
 $\text{IsOverridden}(s, m) \mapsto \perp$
 $\text{IsOverloaded}(s, m) \mapsto \perp$
 $\text{IsOverriding}(s, m) \mapsto \perp$
 $\text{IsRecursiveMethod}(s, m) \mapsto \perp$
 $\text{HasReturnType}(s, m, X) \mapsto \perp$
 $\text{HasParameterType}(s, m) \mapsto \perp$
 $\text{MethodHasParameterType}(s, m, X) \mapsto \perp$
 $\text{MethodIsUsedWithType}(s, m, [X], [X]) \mapsto \perp$

A.18 InlineMethodInvocations

Overview: `InlineMethodInvocations(classname c,inlinedmethod m, classofinlinedmethod a, modifiedmethod n)`: this operation is used to in-line a method invocation of the method `c::m` inside the method `a::n`.



Refactoring tools. Inline in Eclipse and IntelliJ IDEA: select an invocation to inline and specify you want to inline only that one.

Precondition.


$(\text{ExistsClass}(c))$
 $\wedge \text{IsIndirectlyRecursive}(c, n)$
 $\wedge \text{ExistsMethodInvocation}(c, n, a, m)$
 $\wedge \text{ExistsMethodDefinition}(c, n))$

Backward Description.

$\text{ExistsMethodInvocation}(c, m, a, n) \mapsto \perp$
 $\text{IsRecursiveMethod}(c, m) \mapsto \text{ExistsMethodInvocation}(a, n, c, m)$
 $\text{IsIndirectlyRecursive}(c, m) \mapsto (\text{ExistsMethodInvocation}(a, n, C, X))$
 $\wedge \text{ExistsMethodInvocation}(C, X, c, m)) \quad (X \neq m)$
 $\text{IsUsedMethodIn}(a, n, m) \mapsto \perp$

A.19 AddSpecializedMethodInHierarchy (Composed)

Overview: `AddSpecializedMethodInHierarchy(class s, subclasses [a,b], methodname m, callermethods [n,o], inkovekmethods [p,q], paramtype t, paramname pn , subtypesOfparamtype [t1,t2],newtype t')`: this operation is used to get the method `s::m(t' pn)` instead of `s::m(t pn)`. This new duplication takes place in `s` and in all its subclasses that override `m`.



Algorithm of the operation The operation AddSpecializedMethodInHierarchy is based on three steps :

```
AddSpecializedMethodInHierarchy(class s, subclasses [a,b], methodname m, callermethods [n,o], inkovekmethods [p,q], param-type t, paramname pn , subtypesOfparamtype [t1,t2].newtype t') =
```

1. DuplicateMethodInHierarchy s [a,b] m [p,q] [n,o] temporaryName [t]
2. SpecialiseParameter s [a,b] temporaryName t pn [t1,t2] t';
3. RenameDelegatorWithOverloading (s, [a,b], temporaryName,t' , pn,t,m)

Refactoring tools. With IntelliJ IDEA:

1. Apply DuplicateMethodInHierarchy(c, m, temp-name) (see A.20 below).
2. Apply *Change Signature* on the method temp-name in the class s, to change the parameter type t into t' (this change is propagated into subclasses). Note that the behavior preservation is not guaranteed by this operation in general, but here we introduce a new method so the behavior is not changed. Note also, that here we cannot use the operation *Type Migration* of IntelliJ IDEA: replacing a parameter type by one of its subtypes is not safe in general.
3. Rename temp-name into m in s with *Rename*. That renaming introduces an overloading. In general, this could change the semantics of the program, but in the case of this particular chain, and provided the preconditions given below are satisfied, the behavior is preserved (the two methods have the same body; some invocations may be dispatched on the new method, but the external behavior is the same).

A.20 DuplicateMethodInHierarchy

Overview: DuplicateMethodInHierarchy(class s, subclasses [a,b], methodname m, callermethods [m1,m2], inkovekmethods [p,q],newname n ,paramType [t]) : this operation is used to create a duplicate of the method s::m with the name n. All overriding methods in subclasses are also duplicated in these classes.

Refactoring tools. With IntelliJ IDEA:

1. For each implementation of the method m in the subclasses of the class s, duplicate m by applying *Extract Method* on its body (give the new name, specify the desired visibility), then inline the invocation of method n that has replaced the method's body.
2. Use *Pull Members Up* to make the new method appear in classes where the initial method is declared abstract (specify that it must appear as abstract) (see *PullUpAbstract*).

Precondition.

(ExistsClass(s)
 \wedge ExistsMethodDefinitionWithParams(s, m, [t])
 \wedge ExistsMethodDefinition(s, m)
 $\wedge \neg$ ExistsMethodDefinitionWithParams(s, n, [t])

$$\begin{aligned}
& \wedge \neg \text{ExistsMethodDefinitionWithParams}(a, n, [t]) \\
& \wedge \neg \text{ExistsMethodDefinitionWithParams}(b, n, [t]) \\
& \wedge \neg \text{IsInheritedMethodWithParams}(s, n, [t]) \\
& \wedge \text{AllSubclasses}(s, [a; b]))
\end{aligned}$$


Backward Description.

$$\begin{aligned}
\text{ExistsMethodDefinition}(s, n) &\mapsto \top \\
\text{ExistsMethodDefinitionWithParams}(s, n, [t]) &\mapsto \top \\
\text{AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded}(s, n, V) &\mapsto \top \\
&\quad (\text{size}(\text{invokedmethodsInmethodName}) = 1) \\
\text{AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC}(s, n, V, V1) &\mapsto \\
&\quad \text{AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC}(s, m, V, V1) \\
\text{BoundVariableInMethodBody}(s, n, V) &\mapsto \text{BoundVariableInMethodBody}(s, m, V) \\
\text{IsPublic}(s, n) &\mapsto \text{IsPublic}(s, m) \\
\text{ExistsParameterWithName}(s, n, [t], V) &\mapsto \text{ExistsParameterWithName}(s, m, [t], V) \\
\text{ExistsParameterWithType}(s, n, [t], T) &\mapsto \text{ExistsParameterWithType}(s, m, [t], T) \\
\text{IsIndirectlyRecursive}(s, n) &\mapsto \text{IsIndirectlyRecursive}(s, m) \\
\text{IsRecursiveMethod}(s, n) &\mapsto \text{IsRecursiveMethod}(s, m) \\
\text{IsInverter}(s, n, T, V) &\mapsto \text{IsInverter}(s, m, T, V) \\
\text{IsUsedAttributeInMethodBody}(s, V, n) &\mapsto \text{IsUsedAttributeInMethodBody}(s, V, m) \\
\text{MethodHasParameterType}(s, n, V) &\mapsto \text{MethodHasParameterType}(s, m, V) \\
\text{ExistsMethodDefinitionWithParams}(a, n, [t]) &\mapsto \text{ExistsMethodDefinitionWithParams}(a, m, [t]) \\
\text{ExistsMethodDefinitionWithParams}(b, n, [t]) &\mapsto \text{ExistsMethodDefinitionWithParams}(b, m, [t]) \\
\text{IsDelegator}(s, n, p) &\mapsto \top \\
\text{IsDelegator}(s, n, q) &\mapsto \top \\
\text{IsDelegator}(a, n, p) &\mapsto \top \\
\text{IsDelegator}(a, n, q) &\mapsto \top \\
\text{IsDelegator}(b, n, p) &\mapsto \top \\
\text{IsDelegator}(b, n, q) &\mapsto \top \\
\text{ExistsMethodDefinition}(s, n) &\mapsto \top \\
\text{ExistsMethodDefinition}(a, n) &\mapsto \top \\
\text{ExistsMethodDefinition}(b, n) &\mapsto \top \\
\text{MethodIsUsedWithType}(s, n, [t], [t]) &\mapsto \perp \\
\text{MethodIsUsedWithType}(a, n, [t], [t]) &\mapsto \perp \\
\text{MethodIsUsedWithType}(b, n, [t], [t]) &\mapsto \perp \\
\text{MethodIsUsedWithType}(s, n, [t], [T]) &\mapsto \perp \\
\text{MethodIsUsedWithType}(a, n, [t], [T]) &\mapsto \perp \\
\text{MethodIsUsedWithType}(b, n, [t], [T]) &\mapsto \perp \\
\text{ExistsMethodInvocation}(s, m1, V, n) &\mapsto \top \\
\text{ExistsMethodInvocation}(s, m2, V, n) &\mapsto \top \\
\text{ExistsMethodInvocation}(a, m1, V, n) &\mapsto \top \\
\text{ExistsMethodInvocation}(a, m2, V, n) &\mapsto \top \\
\text{ExistsMethodInvocation}(b, m1, V, n) &\mapsto \top \\
\text{ExistsMethodInvocation}(b, m2, V, n) &\mapsto \top \\
\text{IsInheritedMethodWithParams}(a, n, [t]) &\mapsto \neg \text{ExistsMethodDefinitionWithParams}(a, m, [t]) \\
\text{IsInheritedMethodWithParams}(b, n, [t]) &\mapsto \neg \text{ExistsMethodDefinitionWithParams}(b, m, [t]) \\
\text{IsInheritedMethod}(a, n) &\mapsto \neg \text{ExistsMethodDefinition}(a, m) \\
\text{IsInheritedMethod}(b, n) &\mapsto \neg \text{ExistsMethodDefinition}(b, m) \\
\text{IsOverriding}(a, n) &\mapsto \neg \text{ExistsMethodDefinition}(a, m) \\
\text{IsOverriding}(b, n) &\mapsto \neg \text{ExistsMethodDefinition}(b, m) \\
\text{IsOverridden}(a, n) &\mapsto \neg \text{ExistsMethodDefinition}(a, m) \\
\text{IsOverridden}(b, n) &\mapsto \neg \text{ExistsMethodDefinition}(b, m)
\end{aligned}$$

A.21 DeleteMethodInHierarchy

(Delete Method in Fowler [Fow99] and [Koc02])

Overview: DeleteMethodInHierarchy (classname s, subclasses [a,b], method m, invokedmethodsInm [m1,m2], paramType t) : this operation is used to delete the method m from the hierarchy of classes s, a and b.



Refactoring tools. *Safe Delete* in IntelliJ IDEA and *Delete* in Eclipse.

Precondition.

$\exists \text{ExistsClass}(s)$
 $\wedge \exists \text{ExistsMethodDefinitionWithParams}(s, m, [t])$
 $\wedge \neg \text{MethodIsUsedWithType}(s, m, [t], [t])$
 $\wedge \neg \text{MethodIsUsedWithType}(a, m, [t], [t])$
 $\wedge \neg \text{MethodIsUsedWithType}(b, m, [t], [t])$
 $\wedge \text{AllSubclasses}(s, [a; b]))$

Backward Description.

$\text{ExistsParameterWithType}(s, m, [t], t) \mapsto \perp$
 $\text{ExistsParameterWithType}(a, m, [t], t) \mapsto \perp$
 $\text{ExistsParameterWithType}(b, m, [t], t) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(s, m, [t]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(a, m, [t]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(b, m, [t]) \mapsto \perp$
 $\text{ExistsMethodDefinition}(s, m) \mapsto \perp$
 $\text{ExistsMethodDefinition}(a, m) \mapsto \perp$
 $\text{ExistsMethodDefinition}(b, m) \mapsto \perp$
 $\text{IsUsedMethod}(s, m1, [V1]) \mapsto \perp$
 $\text{IsUsedMethod}(s, m2, [V1]) \mapsto \perp$
 $\text{IsUsedMethod}(a, m1, [V1]) \mapsto \perp$

$\text{IsUsedMethod}(a, m2, [V1]) \mapsto \perp$
 $\text{IsUsedMethod}(b, m1, [V1]) \mapsto \perp$
 $\text{IsUsedMethod}(b, m2, [V1]) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(V1, s, m) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(V1, a, m) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(V1, b, m) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(t, s, m) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(t, a, m) \mapsto \perp$
 $\text{IsUsedConstructorAsMethodParameter}(t, b, m) \mapsto \perp$
 $\text{IsUsedConstructorAsObjectReceiver}(t, s, m) \mapsto \perp$
 $\text{IsUsedConstructorAsObjectReceiver}(t, a, m) \mapsto \perp$
 $\text{IsUsedConstructorAsObjectReceiver}(t, b, m) \mapsto \perp$
 $\text{IsInheritedMethod}(a, m) \mapsto \perp$
 $\text{IsInheritedMethod}(b, m) \mapsto \perp$
 $\text{AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC}(s, m, V1, V2) \mapsto \perp$
 $\text{AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC}(a, m, V1, V2) \mapsto \perp$
 $\text{AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC}(b, m, V1, V2) \mapsto \perp$
 $\text{ExistsAbstractMethod}(s, m) \mapsto \perp$
 $\text{ExistsAbstractMethod}(a, m) \mapsto \perp$
 $\text{ExistsAbstractMethod}(b, m) \mapsto \perp$
 $\text{AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded}(s, m, V1) \mapsto \perp$
 $\text{AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded}(a, m, V1) \mapsto \perp$
 $\text{AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded}(b, m, V1) \mapsto \perp$
 $\text{BoundVariableInMethodBody}(s, m, V1) \mapsto \perp$
 $\text{BoundVariableInMethodBody}(a, m, V1) \mapsto \perp$
 $\text{BoundVariableInMethodBody}(b, m, V1) \mapsto \perp$
 $\text{ExistsParameterWithName}(s, m, [t], V1) \mapsto \perp$
 $\text{ExistsParameterWithName}(a, m, [t], V1) \mapsto \perp$
 $\text{ExistsParameterWithName}(b, m, [t], V1) \mapsto \perp$
 $\text{ExistsMethodInvocation}(s, m, V1, V2) \mapsto \perp$
 $\text{ExistsMethodInvocation}(a, m, V1, V2) \mapsto \perp$
 $\text{ExistsMethodInvocation}(b, m, V1, V2) \mapsto \perp$
 $\text{IsInheritedMethodWithParams}(a, m, [t]) \mapsto \perp$
 $\text{IsInheritedMethodWithParams}(b, m, [t]) \mapsto \perp$
 $\text{IsIndirectlyRecursive}(s, m) \mapsto \perp$
 $\text{IsIndirectlyRecursive}(a, m) \mapsto \perp$
 $\text{IsIndirectlyRecursive}(b, m) \mapsto \perp$
 $\text{IsVisibleMethod}(s, m, [t], V1) \mapsto \perp$
 $\text{IsVisibleMethod}(a, m, [t], V1) \mapsto \perp$
 $\text{IsVisibleMethod}(b, m, [t], V1) \mapsto \perp$
 $\text{IsInverter}(s, m, V1, V2) \mapsto \perp$
 $\text{IsInverter}(a, m, V1, V2) \mapsto \perp$
 $\text{IsInverter}(b, m, V1, V2) \mapsto \perp$
 $\text{IsDelegator}(s, V1, m) \mapsto \perp$
 $\text{IsDelegator}(a, V1, m) \mapsto \perp$
 $\text{IsDelegator}(b, V1, m) \mapsto \perp$
 $\text{IsUsedMethodIn}(s, m, V1) \mapsto \perp$
 $\text{IsUsedMethodIn}(a, m, V1) \mapsto \perp$
 $\text{IsUsedMethodIn}(b, m, V1) \mapsto \perp$
 $\text{IsUsedConstructorAsInitializer}(V1, s, m) \mapsto \perp$
 $\text{IsUsedConstructorAsInitializer}(V1, a, m) \mapsto \perp$
 $\text{IsUsedConstructorAsInitializer}(V1, b, m) \mapsto \perp$


```

IsUsedConstructorAsObjectReceiver(V1, s, m) ↪ ⊥
IsUsedConstructorAsObjectReceiver(V1, a, m) ↪ ⊥
IsUsedConstructorAsObjectReceiver(V1, b, m) ↪ ⊥
IsUsedAttributeInMethodBody(s, V1, m) ↪ ⊥
IsUsedAttributeInMethodBody(a, V1, m) ↪ ⊥
IsUsedAttributeInMethodBody(b, V1, m) ↪ ⊥
IsOverridden(a, m) ↪ ⊥
IsOverridden(b, m) ↪ ⊥
IsOverloaded(s, m) ↪ ⊥
IsOverloaded(a, m) ↪ ⊥
IsOverloaded(b, m) ↪ ⊥
IsOverriding(a, m) ↪ ⊥
IsOverriding(b, m) ↪ ⊥
IsRecursiveMethod(s, m) ↪ ⊥
IsRecursiveMethod(a, m) ↪ ⊥
IsRecursiveMethod(b, m) ↪ ⊥
HasReturnType(s, m, V1) ↪ ⊥
HasReturnType(a, m, V1) ↪ ⊥
HasReturnType(b, m, V1) ↪ ⊥
MethodHasParameterType(s, m, V1) ↪ ⊥
MethodHasParameterType(a, m, V1) ↪ ⊥
MethodHasParameterType(b, m, V1) ↪ ⊥
MethodIsUsedWithType(s, m, [t], [t]) ↪ ⊥
MethodIsUsedWithType(a, m, [t], [t]) ↪ ⊥
MethodIsUsedWithType(b, m, [t], [t]) ↪ ⊥


```

A.22 PushDownAll

Overview: PushDownAll (classname s, attributes [att1,att2], subclasses [a,b], method m,paramType [t]) : this operation is used to push down the method s::m to its subclasses and delete that method from s (in *Push Down Method* by Fowler [Fow99], methods are not necessarily pushed down to all the subclasses).



Variation for non-abstract methods:



Refactoring tools. *Push Down* or *Push member Down* in Eclipse tool and IntelliJ IDEA.

Precondition.

$(\text{ExistsClass}(s))$
 $\wedge \text{IsAbstractClass}(s)$
 $\wedge \text{ExistsMethodDefinitionWithParams}(s, m, [t])$
 $\wedge \neg \text{IsUsedMethod}(s, m, [t])$
 $\wedge \text{AllSubclasses}(s, [a; b])$
 $\wedge \neg \text{IsPrivate}(s, m)$
 $\wedge \text{ExistsMethodDefinitionWithParams}(s, m, [t])$
 $\wedge \text{ExistsMethodDefinitionWithParams}(s, m, [t])$
 $\wedge \neg \text{IsPrivate}(s, att1)$
 $\wedge \neg \text{IsPrivate}(s, att2))$

Backward Description.

$\text{ExistsMethodDefinitionWithParams}(s, m, [t]) \mapsto \perp$
 $\text{IsUsedMethodIn}(s, m, C) \mapsto \perp$
 $\text{ExistsMethodDefinition}(s, m) \mapsto \perp$
 $\text{ExistsAbstractMethod}(s, m) \mapsto \perp$
 $\text{IsDelegator}(s, m, V1) \mapsto \perp$
 $\text{HasReturnType}(s, m, V1) \mapsto \perp$
 $\text{AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC}(s, m, V1, V2) \mapsto \perp$
 $\text{AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded}(s, m, V1) \mapsto \perp$
 $\text{BoundVariableInMethodBody}(s, m, V1) \mapsto \perp$
 $\text{ExistsParameterWithName}(s, m, [t], V1) \mapsto \perp$
 $\text{ExistsParameterWithType}(s, m, [t], V1) \mapsto \perp$
 $\text{ExistsMethodInvocation}(s, m, V1, V2) \mapsto \perp$
 $\text{IsPublic}(s, m) \mapsto \perp$
 $\text{IsProtected}(s, m) \mapsto \perp$
 $\text{IsPrivate}(s, m) \mapsto \perp$
 $\text{IsOverloaded}(s, m) \mapsto \perp$
 $\text{IsUsedAttributeInMethodBody}(s, V1, m) \mapsto \perp$
 $\text{IsRecursiveMethod}(s, m) \mapsto \perp$
 $\text{IsIndirectlyRecursive}(s, m) \mapsto \perp$
 $\text{HasReturnType}(s, m, V1) \mapsto \perp$


```

MethodHasParameterType( $s, m, V1$ )  $\mapsto \perp$ 
MethodIsUsedWithType( $s, m, [t], [t]$ )  $\mapsto \perp$ 
IsUsedConstructorAsMethodParameter( $V1, s, m$ )  $\mapsto \perp$ 
IsUsedConstructorAsMethodParameter( $V1, s, m$ )  $\mapsto \perp$ 
IsUsedConstructorAsObjectReceiver( $V1, s, m$ )  $\mapsto \perp$ 
ExistsMethodDefinitionWithParams( $a, m, [t]$ )  $\mapsto \top$ 
ExistsMethodDefinitionWithParams( $b, m, [t]$ )  $\mapsto \top$ 
IsOverriding( $a, m$ )  $\mapsto \perp$ 
IsOverriding( $b, m$ )  $\mapsto \perp$ 
IsOverridden( $a, m$ )  $\mapsto \perp$ 
IsOverridden( $b, m$ )  $\mapsto \perp$ 
IsInheritedMethodWithParams( $a, m, [t]$ )  $\mapsto \perp$ 
IsInheritedMethodWithParams( $b, m, [t]$ )  $\mapsto \perp$ 
IsVisibleMethod( $s, m, [t], a$ )  $\mapsto \perp$ 
IsVisibleMethod( $s, m, [t], b$ )  $\mapsto \perp$ 
IsVisible( $s, m, a$ )  $\mapsto \perp$ 
IsVisible( $s, m, b$ )  $\mapsto \perp$ 
IsInheritedMethod( $a, m$ )  $\mapsto \perp$ 
IsInheritedMethod( $b, m$ )  $\mapsto \perp$ 
IsPrivate( $s, att1$ )  $\mapsto \perp$ 
IsPrivate( $s, att2$ )  $\mapsto \perp$ 

```

A.23 PushDownImplementation

Overview: PushDownImplementation (classname s , attributes $[att1, att2]$, subclasses $[a, b]$, method m , paramType $[t]$) : same as *PushDownAll* but keep the method abstract in the superclass.



Precondition.

```

(ExistsClass( $s$ )
 $\wedge$  ExistsMethodDefinition( $s, m$ )
 $\wedge$  ExistsMethodDefinitionWithParams( $s, m, [t]$ )
 $\wedge$   $\neg$ ExistsAbstractMethod( $s, m$ )
 $\wedge$  AllSubclasses( $s, [a; b]$ )
 $\wedge$   $\neg$ ExistsMethodDefinitionWithParams( $a, m, [t]$ )
 $\wedge$   $\neg$ ExistsMethodDefinitionWithParams( $b, m, [t]$ )
 $\wedge$   $\neg$ IsPrivate( $s, att1$ )

```

$\wedge \neg \text{IsPrivate}(s, att2))$


Backward Description.

$\text{ExistsAbstractMethod}(s, m) \mapsto \top$
 $\text{AllInvokedMethodsOnObjectInBodyOfMAreDeclaredInC}(s, m, V1, V2) \mapsto \perp$
 $\text{AllInvokedMethodsWithParameterInBodyOfMAreNotOverloaded}(s, m, V1) \mapsto \perp$
 $\text{BoundVariableInMethodBody}(s, m, V1) \mapsto \perp$
 $\text{ExistsMethodInvocation}(s, m, V1, V2) \mapsto \perp$
 $\text{IsInheritedMethodWithParams}(s, m, [t]) \mapsto \perp$
 $\text{IsIndirectlyRecursive}(s, m) \mapsto \perp$
 $\text{IsUsedConstructorAsInitializer}(V1, s, m) \mapsto \perp$
 $\text{IsUsedConstructorAsObjectReceiver}(V1, s, m) \mapsto \perp$
 $\text{IsPrivate}(s, m) \mapsto \perp$
 $\text{IsUsedAttributeInMethodBody}(s, V1, m) \mapsto \perp$
 $\text{IsOverridden}(s, m) \mapsto \perp$
 $\text{IsOverriding}(s, m) \mapsto \perp$
 $\text{IsRecursiveMethod}(s, m) \mapsto \perp$
 $\text{MethodHasParameterType}(s, m, V1) \mapsto \perp$
 $\text{MethodIsUsedWithType}(s, m, [t], [t]) \mapsto \perp$
 $\text{ExistsMethodDefinitionWithParams}(a, m, [t]) \mapsto \top$
 $\text{ExistsMethodDefinitionWithParams}(b, m, [t]) \mapsto \top$
 $\text{ExistsMethodDefinition}(a, m) \mapsto \top$
 $\text{ExistsMethodDefinition}(b, m) \mapsto \top$
 $\text{IsPrivate}(s, att1) \mapsto \perp$
 $\text{IsPrivate}(s, att2) \mapsto \perp$

A.24 PushDownNotRedefinedMethod

`pushDownNotRedefinedMethod(class c, method m)`


Duplicate the method `m` of class `c` into its subclasses.



Refactoring tools. Extract Method, Inline, Push Down, Rename in Eclipse and IntelliJ IDEA.

A.25 ReplaceMethodDuplication

Overview: ReplaceMethodDuplication (classname s, subclasses [a,b], method m,copy n, paramType [t]) : this operation is used to replace any occurrence of method s::m.



Refactoring tools. Replace Method Duplication in IntelliJ IDEA.

Precondition.

$$\begin{aligned}
 & (\text{ExistsClass}(s)) \\
 \wedge & \text{ExistsMethodDefinition}(s, m) \\
 \wedge & \text{ExistsMethodDefinition}(s, n) \\
 \wedge & \text{IsDelegator}(s, n, m) \\
 \wedge & \text{AllSubclasses}(s, [a; b])
 \end{aligned}$$

Backward Description. $\text{IsUsedMethod}(s, n, [t]) \mapsto \perp$

$$\begin{aligned}
 & \text{IsDelegator}(s, n, m) \mapsto \top \\
 & \text{ExistsMethodInvocation}(s, n, s, m) \mapsto \perp \\
 & \text{IsRecursiveMethod}(s, n) \mapsto \perp \\
 & \text{IsRecursiveMethod}(s, n) \mapsto \perp \\
 & \text{IsRecursiveMethod}(a, n) \mapsto \perp \\
 & \text{IsRecursiveMethod}(b, n) \mapsto \perp
 \end{aligned}$$

A.26 DeleteClass

DeleteClass(class c): Delete a class c which is not used.

Overview: DeleteClass (classname a, classnamesuperclass s ,allclasses [s,a,b], classnamemethods [m,m1],othermethods [m2,n]) : this operation is used to delete the class a which is supposed to be not used.

Refactoring tools. Safe Delete in IntelliJ IDEA, Delete in Eclipse.

Precondition.

$$\begin{aligned}
 & (\text{ExistsClass}(a)) \\
 \wedge & \neg \text{ExistsMethodDefinitionWithParams}(s, m2, [a]) \\
 \wedge & \neg \text{ExistsMethodDefinitionWithParams}(s, n, [a]) \\
 \wedge & \neg \text{ExistsMethodDefinitionWithParams}(b, m2, [a]) \\
 \wedge & \neg \text{ExistsMethodDefinitionWithParams}(b, n, [a]) \\
 \wedge & \neg \text{IsUsedMethodIn}(a, m, s) \\
 \wedge & \neg \text{IsUsedMethodIn}(a, m1, s) \\
 \wedge & \neg \text{IsUsedMethodIn}(a, m, b) \\
 \wedge & \neg \text{IsUsedMethodIn}(a, m1, b) \\
 \wedge & \neg \text{IsUsedConstructorAsMethodParameter}(a, a, s, m2) \\
 \wedge & \neg \text{IsUsedConstructorAsMethodParameter}(a, a, s, n) \\
 \wedge & \neg \text{IsUsedConstructorAsMethodParameter}(a, a, b, m2) \\
 \wedge & \neg \text{IsUsedConstructorAsMethodParameter}(a, a, b, n) \\
 \wedge & \neg \text{IsUsedConstructorAsInitializer}(a, a, s, m2) \\
 \wedge & \neg \text{IsUsedConstructorAsInitializer}(a, a, s, n)
 \end{aligned}$$

```

 $\wedge \neg \text{IsUsedConstructorAsInitializer}(a, a, b, m2)$ 
 $\wedge \neg \text{IsUsedConstructorAsInitializer}(a, a, b, n)$ 
 $\wedge \neg \text{IsUsedConstructorAsObjectReceiver}(a, a, s, m2)$ 
 $\wedge \neg \text{IsUsedConstructorAsObjectReceiver}(a, a, s, n)$ 
 $\wedge \neg \text{IsUsedConstructorAsObjectReceiver}(a, a, b, m2)$ 
 $\wedge \neg \text{IsUsedConstructorAsObjectReceiver}(a, a, b, n)$ 
 $\wedge \neg \text{IsSubType}(s, a)$ 
 $\wedge \neg \text{IsSubType}(b, a))$ 

```

Backward Description.

```

 $\text{ExistsType}(a) \mapsto \perp$ 
 $\text{IsSubType}(a, s) \mapsto \perp$ 
 $\text{AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC}(a, V1, V2, V3) \mapsto \perp$ 
 $\text{AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded}(a, V1, V2) \mapsto \perp$ 
 $\text{BoundVariableInMethodBody}(a, V1, V2) \mapsto \perp$ 
 $\text{ExistsParameterWithName}(a, V1, [V2], V3) \mapsto \perp$ 
 $\text{ExistsParameterWithType}(a, V1, [V2], V3) \mapsto \perp$ 
 $\text{ExistsField}(a, V1) \mapsto \perp$ 
 $\text{ExistsMethodInvocation}(a, V1, V2, V3) \mapsto \perp$ 
 $\text{ExistsMethodDefinitionWithParams}(a, V1, [V2]) \mapsto \perp$ 
 $\text{ExtendsDirectly}(a, s) \mapsto \perp$ 
 $\text{ExtendsDirectly}(V1, a) \mapsto \perp$ 
 $\text{ExistsAbstractMethod}(a, V1) \mapsto \perp$ 
 $\text{IsInheritedMethodWithParams}(a, V1, [V2]) \mapsto \perp$ 
 $\text{IsIndirectlyRecursive}(a, V1) \mapsto \perp$ 
 $\text{IsVisibleMethod}(a, V1, [V2], V3) \mapsto \perp$ 
 $\text{IsInverter}(a, V1, V2, V3) \mapsto \perp$ 
 $\text{IsDelegator}(a, V1, V2) \mapsto \perp$ 
 $\text{IsAbstractClass}(a) \mapsto \perp$ 
 $\text{IsUsedMethod}(a, V1, [V2]) \mapsto \perp$ 
 $\text{IsUsedMethodIn}(a, V1, V2) \mapsto \perp$ 
 $\text{IsUsedConstructorAsMethodParameter}(V1, a, V2) \mapsto \perp$ 
 $\text{IsUsedConstructorAsInitializer}(a, V1, V2) \mapsto \perp$ 
 $\text{IsUsedConstructorAsObjectReceiver}(a, V1, V2) \mapsto \perp$ 
 $\text{IsUsedConstructorAsInitializer}(V1, a, V2) \mapsto \perp$ 
 $\text{IsUsedConstructorAsObjectReceiver}(V1, a, V2) \mapsto \perp$ 
 $\text{IsPrimitiveType}(a) \mapsto \perp$ 
 $\text{IsPublic}(a, V1) \mapsto \perp$ 
 $\text{IsProtected}(a, V1) \mapsto \perp$ 
 $\text{IsPrivate}(a, V1) \mapsto \perp$ 
 $\text{IsUsedAttributeInMethodBody}(a, V1, V2) \mapsto \perp$ 
 $\text{IsGenericsSubtype}(a, [V1], s, [V2]) \mapsto \perp$ 
 $\text{IsGenericsSubtype}(V1, [V2], a, [V3]) \mapsto \perp$ 
 $\text{IsGenericsSubtype}(V1, [a], V2, [V3]) \mapsto \perp$ 
 $\text{IsInheritedField}(a, V1) \mapsto \perp$ 
 $\text{IsOverridden}(a, V1) \mapsto \perp$ 
 $\text{IsOverloaded}(a, V1) \mapsto \perp$ 
 $\text{IsOverriding}(a, V1) \mapsto \perp$ 
 $\text{IsRecursiveMethod}(a, V1) \mapsto \perp$ 
 $\text{IsRecursiveMethod}(a, V1) \mapsto \perp$ 
 $\text{HasReturnType}(a, V1, V2) \mapsto \perp$ 
 $\text{HasParameterType}(a, V1) \mapsto \perp$ 


```

```

HasParameterType( $V_1, a$ )  $\mapsto \perp$ 
MethodHasParameterType( $a, V_1, V_2$ )  $\mapsto \perp$ 
MethodIsUsedWithType( $a, V_1, [V_2], [V_3]$ )  $\mapsto \perp$ 
MethodIsUsedWithType( $V_1, V_2, [a], [a]$ )  $\mapsto \perp$ 
ExistsMethodDefinition( $a, m$ )  $\mapsto \perp$ 
ExistsMethodDefinition( $a, m_1$ )  $\mapsto \perp$ 
IsInheritedMethodWithParams( $V_1, m, [V_2]$ )  $\mapsto \perp$ 
IsInheritedMethodWithParams( $V_1, m_1, [V_2]$ )  $\mapsto \perp$ 

```

A.27 ExtractGeneralMethod



A.28 InlineClass

InlineClass(class c): Inline one or more references to a given class c.

Refactoring tools. *Inline* in Eclipse and IntelliJ IDEA.

A.29 SpecialiseParameter

Overview: SpecialiseParameter(classname s, subclasses [a,b], methodname m, paramType t ,paramName p, subtypes [st,q],new paramType st): this operation is used to change the type t of the parameter p of the methods s::m, a::m and b::m into one of its subtypes (st).

Precondition.

($\text{IsSubType}(st, t)$
 $\wedge \neg \text{MethodIsUsedWithType}(s, m, [t], [t])$
 $\wedge \neg \text{MethodIsUsedWithType}(a, m, [t], [t])$
 $\wedge \neg \text{MethodIsUsedWithType}(b, m, [t], [t])$
 $\wedge \text{ExistsClass}(s)$
 $\wedge \text{ExistsMethodDefinitionWithParams}(s, m, [t])$
 $\wedge \text{ExistsType}(t)$
 $\wedge \text{ExistsType}(st)$

$$\begin{aligned}
& \wedge \neg \text{ExistsMethodDefinitionWithParams}(s, m, [st]) \\
& \wedge \neg \text{IsInheritedMethodWithParams}(s, m, [st]) \\
& \wedge \text{AllSubclasses}(s, [a; b]) \\
& \wedge \text{AllInvokedMethodsWithParameter0InBody0fMAreNotOverloaded}(s, m, p) \\
& \wedge (\neg \text{MethodIsUsedWithType}(s, m, [t], [q]) \vee \text{ExistsMethodDefinitionWithParams}(s, m, [q]))
\end{aligned}$$

Backward Description.

$$\begin{aligned}
& \text{ExistsMethodDefinitionWithParams}(s, m, [st]) \mapsto \top \\
& \text{ExistsMethodDefinitionWithParams}(s, m, [t]) \mapsto \perp \\
& \text{ExistsMethodDefinitionWithParams}(a, m, [t]) \mapsto \perp \\
& \text{ExistsMethodDefinitionWithParams}(b, m, [t]) \mapsto \perp \\
& \text{ExistsMethodDefinitionWithParams}(a, m, [st]) \mapsto \text{ExistsMethodDefinitionWithParams}(a, m, [t]) \\
& \text{ExistsMethodDefinitionWithParams}(b, m, [st]) \mapsto \text{ExistsMethodDefinitionWithParams}(b, m, [t]) \\
& \text{MethodIsUsedWithType}(s, m, [t], [t]) \mapsto \perp \\
& \text{MethodIsUsedWithType}(a, m, [t], [t]) \mapsto \perp \\
& \text{MethodIsUsedWithType}(b, m, [t], [t]) \mapsto \perp \\
& \text{ExistsParameterWithName}(s, m, [st], p) \mapsto \top \\
& \text{ExistsParameterWithName}(a, m, [st], p) \mapsto \top \\
& \text{ExistsParameterWithName}(b, m, [st], p) \mapsto \top \\
& \text{ExistsParameterWithType}(s, m, [st], st) \mapsto \top \\
& \text{ExistsParameterWithType}(a, m, [st], st) \mapsto \top \\
& \text{ExistsParameterWithType}(b, m, [st], st) \mapsto \top \\
& \text{IsInverter}(s, m, st, V) \mapsto \text{IsInverter}(s, m, t, V) \\
& \text{IsInverter}(a, m, st, V) \mapsto \text{IsInverter}(a, m, t, V) \\
& \text{IsInverter}(b, m, st, V) \mapsto \text{IsInverter}(b, m, t, V) \\
& \text{IsInheritedMethodWithParams}(s, m, [st]) \mapsto \top \\
& \text{IsInheritedMethodWithParams}(a, m, [st]) \mapsto \top \\
& \text{IsInheritedMethodWithParams}(b, m, [st]) \mapsto \top \\
& \text{IsUsedConstructorAsMethodParameter}(st, s, m) \mapsto \top \\
& \text{IsUsedConstructorAsMethodParameter}(st, a, m) \mapsto \top \\
& \text{IsUsedConstructorAsMethodParameter}(st, b, m) \mapsto \top \\
& \text{IsUsedConstructorAsMethodParameter}(t, s, m) \mapsto \perp \\
& \text{IsUsedConstructorAsMethodParameter}(t, a, m) \mapsto \perp \\
& \text{IsUsedConstructorAsMethodParameter}(t, b, m) \mapsto \perp \\
& \text{IsOverridden}(a, m) \mapsto \text{ExistsMethodDefinition}(a, m) \\
& \text{IsOverridden}(b, m) \mapsto \text{ExistsMethodDefinition}(b, m) \\
& \text{IsOverriding}(a, m) \mapsto \text{ExistsMethodDefinition}(a, m) \\
& \text{IsOverriding}(b, m) \mapsto \text{ExistsMethodDefinition}(b, m)
\end{aligned}$$

B Preconditions composition

In this section, we apply a calculus of minimal precondition to the sequence of basic refactoring operations that compose our transformation. We apply the calculus of Kriesel and Koch [KK04], based on the *backward descriptions* given in the previous appendix. We use that calculus to compute a minimum precondition that ensures that the round-trip transformation succeeds, which means we determine a set of programs on which we can ensure that the preconditions of all the component refactoring operations will be satisfied when applying the *Composite*→*Visitor*→*Composite* transformation any number of time (as explained in [CA13]).

That computed precondition is given in Fig. 29. The chains taken into account for the computation are given in Figs. 27 and 28. The difference between these chains and the algorithms of previous sections are:

- We add some parameters to the operations that were not made explicit before (in previous sections, the *project* was an implicit parameter).

- Composite operations are replaced by their component operations (`MergeDuplicateMethods` in step 8 of the *Composite→Visitor* chain).
- We split some operations of the tool into several abstract operations when the behavior of an operation depends on the state of the program. In that case, each possible behavior is represented by a different abstract operation. For instance, we have two operations for method renaming, one for overloaded methods and one for not-overloaded methods.

1. `CreateEmptyClass(PrintVisitor)`
`CreateEmptyClass(PrettyprintVisitor)`
2. `CreateIndirectionInSuperClass(Graphic,[Ellipse;CompositeGraphic;], print, [], void, printTmpVC)`
`CreateIndirectionInSuperClass(Graphic, [Ellipse;CompositeGraphic;], prettyprint, [], void, prettyprintTmpVC)`
3. `InlineMethodInvocations(CompositeGraphic, printTmpVC, [], Graphic, print, [])`
`InlineMethodInvocations(CompositeGraphic, prettyprintTmpVC, [], Graphic, prettyprint, [])`
4. `AddParameterWithReuse(Graphic, [Ellipse;CompositeGraphic;], printTmpVC, [], PrintVisitor, v)`
`AddParameterWithReuse(Graphic, [Ellipse;CompositeGraphic;], prettyprintTmpVC, [], PrettyprintVisitor, v)`
5. `MoveMethodWithDelegate (Ellipse, [mChildGraphics;], PrintVisitor, printTmpVC, [PrintVisitor;], void, visit)`
`MoveMethodWithDelegate (CompositeGraphic, [mChildGraphics;], PrintVisitor, printTmpVC, [PrintVisitor;], void, visit)`
`MoveMethodWithDelegate (Ellipse, [mChildGraphics;], PrettyprintVisitor, prettyprintTmpVC, [PrettyprintVisitor;], void, visit)`
`MoveMethodWithDelegate (CompositeGraphic, [mChildGraphics;], PrettyprintVisitor, prettyprintTmpVC, [PrettyprintVisitor;], void, visit)`
6. `ExtractSuperClass ([PrintVisitor;PrettyprintVisitor;], Visitor, [visit;], void)`
7. `GeneraliseParameter (Graphic, [Ellipse;CompositeGraphic;], printTmpVC, v, PrintVisitor, Visitor)`
`GeneraliseParameter (Graphic, [Ellipse;CompositeGraphic;], prettyprintTmpVC, v, PrettyprintVisitor, Visitor)`
8. `ReplaceMethodcodeDuplicatesInverter (Ellipse, printTmpVC, [prettyprintTmpVC;], Visitor, void)`
`ReplaceMethodcodeDuplicatesInverter (CompositeGraphic, printTmpVC, [prettyprintTmpVC;], Visitor, void)`
`PullupConcreteDelegator (Ellipse, [mChildGraphics;], prettyprintTmpVC, Graphic)`
`SafeDeleteWithOverridden (CompositeGraphic, prettyprintTmpVC, Graphic)`
`InlineAndDelete (Graphic, prettyprintTmpVC)`
`RenameInHierarchyNoOverloading (Graphic, [Ellipse;CompositeGraphic;], printTmpVC, [Visitor;], accept)`

Figure 27: Chain of refactoring operations for *Composite→Visitor* transformation analysis

1. DuplicateMethodInHierarchy (Graphic, [Ellipse;CompositeGraphic;], accept,[visit;], [print;prettyprint;], acceptPrintVisitoraddspecializedMethodtmp, [Visitor;])
 - SpecialiseParameter (Graphic, [Ellipse;CompositeGraphic;], acceptPrintVisitoraddspecializedMethodtmp, Visitor, [PrintVisitor;PrettyprintVisitor;], PrintVisitor)
 - RenameDelegatorWithOverloading (Graphic, [Ellipse;CompositeGraphic;], acceptPrintVisitoraddspecializedMethodtmp, PrintVisitor, v, Visitor, accept)
 - DuplicateMethodInHierarchy (Graphic, [Ellipse;CompositeGraphic;], accept, [visit;], [print;prettyprint;], acceptPrettyprintVisitoraddsspecializedMethodtmp, [Visitor;])
 - SpecialiseParameter (Graphic, [Ellipse;CompositeGraphic;], acceptPrettyprintVisitoraddsspecializedMethodtmp, Visitor, [PrintVisitor;PrettyprintVisitor;], PrettyprintVisitor)
 - RenameDelegatorWithOverloading (Graphic, [Ellipse;CompositeGraphic;], acceptPrettyprintVisitoraddsspecializedMethodtmp, PrettyprintVisitor, v, Visitor, accept)
 - DeleteMethodInHierarchy (Graphic, [Ellipse;CompositeGraphic;], accept, [visit;], Visitor)
 - 2. PushDownAll (Visitor, [PrintVisitor;PrettyprintVisitor;], visit, [Ellipse;])
 - PushDownAll (Visitor, [PrintVisitor;PrettyprintVisitor;], visit, [CompositeGraphic;])
 - 3. InlineMethod (Ellipse, visit, PrintVisitor, accept)
 - InlineMethod (CompositeGraphic, visit, PrintVisitor, accept)
 - InlineMethod (Ellipse, visit, PrettyprintVisitor, accept)
 - InlineMethod (CompositeGraphic, visit, PrettyprintVisitor, accept)
 - 4. RenameOverloadedMethodInHierarchy (Graphic, [Ellipse;CompositeGraphic;], accept, printTmpVC, [PrintVisitor;])
 - RenameOverloadedMethodInHierarchy (Graphic, [Ellipse;CompositeGraphic;], accept, prettyprintTmpVC, [PrettyprintVisitor;])
 - 5. RemoveParameter (Graphic, [Ellipse;CompositeGraphic;], printTmpVC, [PrintVisitor;], PrintVisitor, v)
 - RemoveParameter (Graphic, [Ellipse;CompositeGraphic;], prettyprintTmpVC, [PrettyprintVisitor;], PrettyprintVisitor, v)
 - 6. ReplaceMethodDuplication (Graphic, [Ellipse;CompositeGraphic;], print, printTmpVC, [])
 - ReplaceMethodDuplication (Graphic, [Ellipse;CompositeGraphic;], prettyprint, prettyprintTmpVC, [])
 - 7. PushDownImplementation (Graphic, [], [Ellipse;CompositeGraphic;], print, [])
 - PushDownImplementation (Graphic, [], [Ellipse;CompositeGraphic;], prettyprint, [])
 - 8. PushDownAll (Graphic, [Ellipse;CompositeGraphic;], printTmpVC, [])
 - PushDownAll (Graphic, [Ellipse;CompositeGraphic;], prettyprintTmpVC, [])
 - 9. InlineAndDelete (Ellipse, printTmpVC)
 - InlineAndDelete (CompositeGraphic, printTmpVC)
 - InlineAndDelete (Ellipse, prettyprintTmpVC)
 - InlineAndDelete (CompositeGraphic, prettyprintTmpVC)
 - 10. DeleteClass (PrintVisitor, Visitor, [Ellipse;CompositeGraphic;PrintVisitor;PrettyprintVisitor;Visitor;Graphic;], [visit;], [accept;eval;show;])
 - DeleteClass (PrettyprintVisitor, Visitor, [Ellipse;CompositeGraphic;PrintVisitor;PrettyprintVisitor;Visitor;Graphic;], [visit;], [accept;eval;show;])
 - 11. DeleteClass (Visitor, java.lang.Object, [Ellipse;CompositeGraphic;PrintVisitor;PrettyprintVisitor;Visitor;Graphic;], [visit;], [accept;eval;show;])

Figure 28: Chain of refactoring operations of the back transformation analysis

```

(¬ExistsMethodDefinition(Graphic, accept)
 ∧ ¬ExistsMethodDefinition(Ellipse, accept)
 ∧ ¬ExistsMethodDefinition(CompositeGraphic, accept)
 ∧ ¬IsInheritedMethod(Graphic, accept)
 ∧ AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded(CompositeGraphic, prettyprint, this)
 ∧ AllInvokedMethodsOnObject0InBodyOfMAreDeclaredInC(Ellipse, prettyprint, this, Graphic)
 ∧ AllInvokedMethodsWithParameter0InBodyOfMAreNotOverloaded(Ellipse, prettyprint, this)
 ∧ ¬ExistsType(Visitor)
 ∧ ExistsClass(Ellipse)
 ∧ ¬BoundVariableInMethodBody(Graphic, prettyprint, v)
 ∧ ¬BoundVariableInMethodBody(Graphic, print, v)
 ∧ IsRecursiveMethod(CompositeGraphic, prettyprint)
 ∧ ExistsClass(CompositeGraphic)
 ∧ IsRecursiveMethod(CompositeGraphic, print)
 ∧ ExistsMethodDefinitionWithParams(Graphic, prettyprint, [])
 ∧ ExistsAbstractMethod(Graphic, prettyprint)
 ∧ ¬IsInheritedMethod(Graphic, prettyprintTmpVC)
 ∧ ¬IsInheritedMethodWithParams(Graphic, prettyprintTmpVC, [])
 ∧ ¬ExistsMethodDefinitionWithParams(Graphic, prettyprintTmpVC, [])
 ∧ HasReturnType(Graphic, prettyprint, void)
 ∧ ExistsMethodDefinition(Graphic, prettyprint)
 ∧ ExistsMethodDefinition(Ellipse, prettyprint)
 ∧ ExistsMethodDefinition(CompositeGraphic, prettyprint)
 ∧ ¬ExistsMethodDefinition(Graphic, prettyprintTmpVC)
 ∧ ¬ExistsMethodDefinition(Ellipse, prettyprintTmpVC)
 ∧ ¬ExistsMethodDefinition(CompositeGraphic, prettyprintTmpVC)
 ∧ ExistsClass(Graphic)
 ∧ IsAbstractClass(Graphic)
 ∧ ExistsMethodDefinitionWithParams(Graphic, print, [])
 ∧ ExistsAbstractMethod(Graphic, print)
 ∧ ¬IsInheritedMethod(Graphic, printTmpVC)
 ∧ ¬IsInheritedMethodWithParams(Graphic, printTmpVC, [])
 ∧ ¬ExistsMethodDefinitionWithParams(Graphic, printTmpVC, [])
 ∧ AllSubclasses(Graphic, [Ellipse; CompositeGraphic])
 ∧ HasReturnType(Graphic, print, void)
 ∧ ¬IsPrivate(Graphic, print)
 ∧ ¬IsPrivate(Ellipse, print)
 ∧ ¬IsPrivate(CompositeGraphic, print)
 ∧ ExistsMethodDefinition(Graphic, print)
 ∧ ExistsMethodDefinition(Ellipse, print)
 ∧ ExistsMethodDefinition(CompositeGraphic, print)
 ∧ ¬ExistsMethodDefinition(Graphic, printTmpVC)
 ∧ ¬ExistsMethodDefinition(Ellipse, printTmpVC)
 ∧ ¬ExistsMethodDefinition(CompositeGraphic, printTmpVC)
 ∧ ¬ExistsType(PrettyprintVisitor)
 ∧ ¬ExistsType(PrintVisitor))

```

Figure 29: Computed precondition for the round-trip transformation