



HAL
open science

Some Numerical and Mechanical Issues When Using Intrinsic Cohesive Approaches

Nawfal Blal, Loïc Daridon, Yann Monerie, Stéphane Pagano

► **To cite this version:**

Nawfal Blal, Loïc Daridon, Yann Monerie, Stéphane Pagano. Some Numerical and Mechanical Issues When Using Intrinsic Cohesive Approaches. European Solid Mechanics Conference (ESMC), Jul 2012, Austria. hal-00665936

HAL Id: hal-00665936

<https://hal.science/hal-00665936>

Submitted on 3 Feb 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Some Numerical and Mechanical Issues When Using Intrinsic Cohesive Approaches

BLAL Nawfal^{†,‡,‡}, DARIDON Loïc^{†,‡}, MONERIE Yann^{‡,‡}, PAGANO Stéphane^{†‡}

[†]Laboratoire de Mécanique et Génie Civil, Université Montpellier 2, CNRS, CC 048 Place Eugène Bataillon, 34095 Montpellier cedex, France. {nawfal.blal, loic.daridon, stephane.pagano}@univ-montp2.fr

[‡]Institut de Radioprotection et de Sûreté Nucléaire, Bat. 702, CE Cadarache, BP3-13115 St. Paul-lez-Durance Cedex, France. yann.monerie@irsn.fr

[‡]Laboratoire de Micromécanique et d'Intégrité des Structures, MIST Laboratory, IRSN-CNRS-Université Montpellier 2

ABSTRACT

Since the pioneering works of [1, 2], cohesive zone models are extensively used in failure and damage mechanics. Nevertheless, their numerical implementation as well as the development of micro-mechanical damage model using cohesive approaches are still important issues of concern. This work aims at determining a micromechanical model for elastoplastic materials using intrinsic cohesive approaches in numerical simulations, e.g. the Cohesive-Volumetric Finite Element Method. The idea, first proposed by [3] and recently used by [4], consists in replacing the cohesive-volumetric discretization by an equivalent 'matrix-inclusions' composite: the continuous matrix has the same behavior as bulk elements whereas inclusions correspond to the edges of the underlying mesh (see Figure 1).




Figure 1: From cohesive-volumetric discretization to the equivalent 'matrix-inclusions' composite.

The overall behavior of such composite is asymptotically obtained using variational homogenization estimate [5, 6, 7]. The case of isotropic elastic media with bilinear cohesive law is firstly proposed. An elliptic micromechanical damage model is thus derived for brittle materials. Then the extension of the model to plastic media is considered. The main interests of this work are:

1. The overall elastic loss due to intrinsic models is *a priori* estimated and a criteria on cohesive stiffness is proposed.

2. The local damageable parameters are linked to (i) the overall properties of the relevant material and to (ii) the mesh parameters. Such calibration allow to derive an overall *mesh-independent* behavior.
3. The proposed model is available whatever the mesh type and the triaxiality loading rate contrary to previous results available in the literature.

References

- [1] G. I. Barenblatt. The mathematical theory of equilibrium cracks in brittle fractures. *Advances In Applied Mechanics*, 7:55–129, 1962.
- [2] D.S. Dugdale. Yielding of steel sheets containing slits. *Journal of Mechanics and Physics of Solids*, 8:100–104, 1960.
- [3] V. Acary and Y. Monerie. Nonsmooth fracture dynamics using a cohesive zone approach. Technical Report RR-6032, Institut National de Recherche en Informatique et en Automatique, 2006.
- [4] N. Blal, L. Daridon, Y. Monerie, and S. Pagano. Criteria on the artificial compliance inherent to the intrinsic cohesive zone. *Comptes Rendus de Mécanique*, 339:789–795, 2011.
- [5] Z. Hashin and S. Shtrikman. A variational approach to the theory of the elastic behaviour of multiphase materials. *Journal of the Mechanics and Physics of Solids*, 11:127–140, 1963.
- [6] P. Suquet. Overall properties of nonlinear composites : Secant moduli theory and its link with Ponte Castaneda’s variational procedure. *Comptes Rendus de l’Académie des Sciences*, 320:563–571, 1995.
- [7] P. Ponte Castañeda. The effective mechanical properties of nonlinear isotropic composites. *Journal of the Mechanics and Physics of Solids*, 39:45–71, 1991.