



HAL
open science

Automatic estimation of asymmetry for gradient-based alignment of noisy images on Lie group

Jean-Baptiste Authesserre, Rémi Megret, Yannick Berthoumieu

► **To cite this version:**

Jean-Baptiste Authesserre, Rémi Megret, Yannick Berthoumieu. Automatic estimation of asymmetry for gradient-based alignment of noisy images on Lie group. *Pattern Recognition Letters*, 2011, 32 (10), pp.1480-1492. 10.1016/j.patrec.2011.04.001 . hal-00669813

HAL Id: hal-00669813

<https://hal.science/hal-00669813>

Submitted on 13 Feb 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Automatic Estimation of Asymmetry for Gradient-Based Alignment of Noisy Images on Lie Group

Jean-Baptiste Authesserre^{a,*}, Rémi Mégret^a, Yannick Berthoumieu^a

^a*Signal and Image Processing Group, IMS, UMR 5218 CNRS, University of Bordeaux,
351 Cours de la Libération F-33405 TALENCE CEDEX, France. E-mail :
jean-baptiste.authesserre@ims-bordeaux.fr, remi.megret@ims-bordeaux.fr,
yannick.berthoumieu@ims-bordeaux.fr*

Abstract

Many parametric image alignment approaches assume equality of the images to register up to motion compensation. In presence of noise this assumption does not hold. In particular, for gradient-based approaches, which rely on the optimization of an error functional with gradient descent methods, the performances depend on the amount of noise in each image. We propose in this paper to use the Asymmetric Composition on Lie Groups (ACL) formulation of the alignment problem to improve the robustness in presence of asymmetric levels of noise. The ACL formulation, generalizing state-of-the-art gradient-based image alignment, introduces a parameter to weight the influence of the images during the optimization. Three new methods are presented to estimate this asymmetry parameter: one supervised (MVACL) and two fully automatic (AAVL and GACL). Theoretical results and experimental validation show how the new algorithms improve robustness in presence of noise. Finally, we illustrate the interest of the new approaches for object tracking under low-light conditions.

Keywords: Asymmetric image alignment, noisy images, parametric motion estimation, gradient methods, Lie Groups.

1. Introduction

2 Parametric motion estimation is a fundamental task of many vision ap-
3 plications such as object tracking, image mosaicking, video compression and

4 augmented reality. To recover the motion parameters, direct image align-
5 ment works by optimizing a pixel-based error measure between a moving
6 image and a fixed-image called template. Gradient-based alignment uses
7 more specifically a local optimization relying on the gradients of the error
8 measure with respect to the motion parameters, usually applied in an it-
9 erative scheme. These gradients in turn depend on the gradients of the
10 images themselves. Also known as template matching, this method was first
11 introduced for optical-flow computation (Lucas and Kanade, 1981). Since
12 then, many related approaches were proposed. Baker and Matthews (2004)
13 summarized four main classes of algorithms as Forwards Additive, Forwards
14 Compositional, Inverse Additive, and Inverse Compositional.

15 M egret et al. (2008) extended this taxonomy of the methods in order to
16 take into account recent approaches: the Efficient Second-order Minimization
17 (ESM) algorithm (Benhimane and Malis, 2007) and the Symmetric Gradient
18 Method (SGM) (Keller and Averbuch, 2004). These methods symmetrically
19 weight the gradients of both images when estimating the update of motion
20 parameters, which yields faster convergence and improved robustness. An-
21 other contribution of Benhimane and Malis (2007) was to introduce Lie group
22 parameterization in image alignment, which is a natural and efficient way to
23 parameterize motion (Vercauteren et al., 2009), especially for rigid motion
24 estimation.

25 The approaches using symmetrically weighted gradients have been shown
26 to be more robust (Keller and Averbuch, 2004; Benhimane and Malis, 2007)
27 than the forwards and inverse approaches. Those methods rely implicitly
28 on the assumption that the gradients of both images are equally reliable. In
29 presence of images of different *SNR* (Signal to Noise Ratio), this assumption
30 does not hold. To improve the robustness of alignment algorithms in that case,
31 Authesserre et al. (2009) introduced the Asymmetric Compositional method
32 as an extension of the ESM approach. This approach is based on the opti-
33 mization of a closed-form error measure that leads to weighting the gradients
34 of both images asymmetrically according to a free parameter α that tunes
35 the level of asymmetry. Tuning this α parameter produces a family of ap-
36 proaches which can yield better performance than the conventional methods.
37 However the automatic computation of α was not provided.

38 In this paper, we propose new approaches relying on an Asymmetric
39 Compositional on Lie Group (ACL) formulation of image alignment. The
40 new approaches provide an adaptive computation of α to handle asymmetric
41 levels of noise. The paper is organized as follows :

- 42 • In Section 2, we formalize the image alignment problem as a parameter optimization procedure on a Lie Algebra. We introduce the ACL formulation as a generalization of existing algorithms.
- 43
- 44
- 45 • In section 3, we provide a theoretical analysis of the ACL objective function.
- 46
- 47 – Its relationship with the ESM (Benhimane and Malis (2007)) optimization procedure and the effect of noise are highlighted.
- 48
- 49 – A first algorithm, the MVACL is introduced in the context of a Gauss-Newton optimization of the ACL objective function. This approach focus on the amount of noise only and computes α subject to the knowledge of the relative variance of noise in the two images (section 3.2).
- 50
- 51
- 52
- 53
- 54 • In section 4, we introduce new algorithms to compute α :
- 55 – The GACL and AACL approaches propose more general heuristics to compute α automatically (sections 4.1 and 4.2).
- 56
- 57 – To relieve the overhead for the computation of α , fast approximations of those methods are also proposed (section 4.3).
- 58
- 59 • In section 5 the state-of-the art and the new approaches performance in the context of image alignment under various noise conditions are evaluated.
- 60
- 61
- 62 • In section 6, we illustrate the interest of the new approaches for object tracking under low-light conditions.
- 63

64 2. Image alignment

65 2.1. Lie group parameterization of motion

66 Rigid motion models such as non degenerate affine motion for the Euclidian plane $\mathbf{x} \in \mathbb{R}^2$ and homography for the projective plane $\mathbf{x} \in \mathbb{P}^2$
67 (Bayro-Corrochano and Ortegón-Aguilar, 2007) can be parameterized using Lie Group. A Lie group \mathcal{P} is a differentiable manifold structured by the
68 composition operation (\circ). To any finite dimensional Lie Group is associated a Lie algebra \mathfrak{P} whose underlying finite dimensional vector space is the
69 tangent space to \mathcal{P} at the neutral element $\mathbf{0}$. Locally an increment $\delta\boldsymbol{\mu} \in \mathcal{P}$
70
71
72

73 around $\mathbf{0}$ can be bijectively reparameterized by an increment $\mathbf{v} \in \mathfrak{P}$ using
 74 the exponential map:

$$\delta\boldsymbol{\mu}(\mathbf{v}) = \exp(\mathbf{v}), \quad (1)$$

75 with the following properties:

$$\exp(-\mathbf{v}) = \exp(\mathbf{v})^{-1}, \quad (2)$$

$$\exp(\alpha\mathbf{v}) \circ \exp(\beta\mathbf{v}) = \exp((\alpha + \beta)\mathbf{v}), \quad (3)$$

76 for all $\alpha, \beta \in \mathbb{R}$.

77 With such a mapping we can solve for parameters in the algebra and
 78 get the corresponding element of interest $\delta\boldsymbol{\mu}$ using eq. (1). This ensures
 79 to obtain $\delta\boldsymbol{\mu}$ inside the group without having to enforce explicit constraints
 80 (Vercauteren et al., 2009), as opposed to using the more classic vector space
 81 embedding $\mathcal{P} \in \mathbb{R}^p$, where p is the number of parameters to estimate in the
 82 vector $\delta\boldsymbol{\mu}$.

83 In the following, as in (Bayro-Corrochano and Ortégón-Aguilar, 2007;
 84 Benhimane and Malis, 2007; Vercauteren et al., 2009), we assume that the
 85 parameter space \mathcal{P} forms a Lie group, which acts on image coordinates \mathbf{x}
 86 through \mathbf{W} . Moreover, we assume that the motion model satisfies group
 87 action properties (Miller and Younes, 2001). This action has the following
 88 properties, which are related respectively to composition (\circ), inversion ($^{-1}$)
 89 and parameters of the identity transformation $\mathbf{0}$:

$$\mathbf{W}(\boldsymbol{\mu}^k \circ \delta\boldsymbol{\mu}, \mathbf{x}) = \mathbf{W}(\boldsymbol{\mu}^k, \mathbf{W}(\delta\boldsymbol{\mu}, \mathbf{x})), \quad (4)$$

$$\mathbf{y} = \mathbf{W}(\boldsymbol{\mu}^{-1}, \mathbf{x}) \Leftrightarrow \mathbf{x} = \mathbf{W}(\boldsymbol{\mu}, \mathbf{y}), \quad (5)$$

$$\mathbf{W}(\mathbf{0}, \mathbf{x}) = \mathbf{x}. \quad (6)$$

90 Explicit expressions of the group action \mathbf{W} and of the exponential map
 91 \exp are provided in Appendix B for the case of homography, which will be
 92 used in the experiments.

93 2.2. Asymmetric image alignment on Lie Group

94 The goal of the algorithms presented in this paper is to align a template
 95 image $T(\mathbf{x})$ to an input image $I(\mathbf{x})$, where $\mathbf{x} = (x, y)^T$ is a column vector
 96 containing the pixel coordinates. The alignment problem is solved iteratively.

97 We assume that we know at step k a coarse estimation of the warp parameters
 98 $\boldsymbol{\mu}^k$. Aligning two images on Lie group is formalized (Authesserre et al., 2009)
 99 as estimating the vector $\mathbf{v} \in \mathfrak{P}$ such that the following discrepancy error is
 100 minimal:

$$E_\alpha(\mathbf{v}) = \sum_{i \in 1..N} |e_{\alpha,i}(\mathbf{v})|^2 \quad (7)$$

101 where $e_{\alpha,i}$ represents the error at each pixel \mathbf{x}_i belonging to a region of interest
 102 $R = (\mathbf{x}_1, \dots, \mathbf{x}_N)$:

$$e_{\alpha,i}(\mathbf{v}) = I(\mathbf{W}(\boldsymbol{\mu}^k \circ \exp((1 - \alpha)\mathbf{v}), \mathbf{x}_i)) - T(\mathbf{W}(\exp(-\alpha\mathbf{v}), \mathbf{x}_i)). \quad (8)$$

103 The particularity of eq. (8) is to introduce a tuning parameter $\alpha \in [0, 1]$ cor-
 104 responding to an asymmetric constraint imposed on the alignment process.

105 The α coefficient allows us to formulate existing approaches generically:
 106 the particular cases $\alpha = 0$ and $\alpha = 1$ correspond to extending the classical
 107 approaches (Forwards Compositional (Shum and Szeliski, 2000) and Inverse
 108 Compositional (Baker and Matthews, 2004)) to Lie Group parameterization.
 109 We call these extensions FCL (Forward Compositional Lie) and ICL (Inverse
 110 Compositional Lie). The FCL approach has already been introduced under
 111 the name LIEMANIFOLD approach in Guangwei et al. (2008). The case
 112 $\alpha = 0.5$ corresponds to the ESM (Efficient Second-order Minimization) algo-
 113 rithm presented by Benhimane and Malis (2007) under conditions discussed
 114 in (Mégret et al., 2008; Authesserre et al., 2009). Thus the asymmetric
 115 method consists in generalizing previous approaches to any $\alpha \in [0, 1]$. Fol-
 116 lowing this naming scheme we will denote in the sequel ACL (Asymmetric
 117 Compositional Lie) the asymmetric approach where α is arbitrarily set a
 118 priori.

119 Aligning two images consists in optimizing locally the error defined by
 120 eq. (7) and (8) at step k with respect to \mathbf{v} . Once \mathbf{v} is computed, the update
 121 rule provides a new estimation of the motion parameters:

$$\boldsymbol{\mu}^{k+1} = \boldsymbol{\mu}^k \circ \exp(\mathbf{v}). \quad (9)$$

122 Baker and Matthews (2004) showed that the Gauss-Newton (GN) opti-
 123 mization has efficient convergence properties and a reasonable computational

124 cost. Following most authors (Lucas and Kanade, 1981; Shum and Szeliski,
 125 2000; Keller and Averbuch, 2004; Vercauteren et al., 2009), we will use this
 126 approach. In the sequel we denote by $\mathbf{e}_\alpha = (e_{\alpha,i})_{i=1..N}$ the vector obtained
 127 by concatenating the pixel-wise errors $e_{\alpha,i}$. The Gauss-Newton optimization
 128 of the error function (7) yields:

$$\hat{\mathbf{v}}_\alpha = -(\mathbf{J}_\alpha(\mathbf{0}))^\dagger \mathbf{e}_\alpha(\mathbf{0}) = -(\mathbf{J}_\alpha(\mathbf{0})^t \mathbf{J}_\alpha(\mathbf{0}))^{-1} \mathbf{J}_\alpha(\mathbf{0})^t \mathbf{e}_\alpha(\mathbf{0}), \quad (10)$$

129 where t is the transpose operator and $(\mathbf{J}_\alpha(\mathbf{v}_0))^\dagger$ is the pseudo-inverse of the
 130 jacobian matrix of the error vector \mathbf{e} at $\mathbf{0}$. The jacobian matrix is defined as:

$$\mathbf{J}_\alpha(\mathbf{w}) = \left. \frac{\partial \mathbf{e}_\alpha(\mathbf{v})}{\partial \mathbf{v}} \right|_{\mathbf{v}=\mathbf{w}} \quad (11)$$

131 This matrix can be expressed as the concatenation of the gradients $\mathbf{J}_{\alpha,i}(\mathbf{w})$
 132 of the pixelwise errors $e_{\alpha,i}$: $\mathbf{J}_\alpha(\mathbf{w}) = [\mathbf{J}_{\alpha,1}(\mathbf{w})^t, \dots, \mathbf{J}_{\alpha,N}(\mathbf{w})^t]^t$ with

$$\mathbf{J}_{\alpha,i}(\mathbf{w}) = (1 - \alpha) \mathbf{J}_{I,i}((1 - \alpha)\mathbf{w}) + \alpha \mathbf{J}_{T,i}(-\alpha\mathbf{w}), \quad (12)$$

133 where $\mathbf{J}_{I,i}$ and $\mathbf{J}_{T,i}$ are the jacobian matrices defined as:

$$\mathbf{J}_{I,i}(\mathbf{w}) = \left. \frac{\partial I(\mathbf{W}(\boldsymbol{\mu}^k \circ \exp(\mathbf{v}), \mathbf{x}_i))}{\partial \mathbf{v}} \right|_{\mathbf{v}=\mathbf{w}}, \quad (13)$$

$$\mathbf{J}_{T,i}(\mathbf{w}) = \left. \frac{\partial T(\mathbf{W}(\exp(\mathbf{v}), \mathbf{x}_i))}{\partial \mathbf{v}} \right|_{\mathbf{v}=\mathbf{w}}. \quad (14)$$

134 3. Theoretical analysis of the ACL objective function

135 We now introduce a theoretical study showing the usefulness of the generic
 136 ACL formulation to provide new insights into existing gradient-based ap-
 137 proaches and the effect of noise. Considering successively the noiseless and
 138 the noisy cases, second-order expansion of the error function $\mathbf{e}_\alpha(\mathbf{v})$ is per-
 139 formed. This allows us to highlight in section 3.2 the trade-off that needs
 140 to be done between the minimization of both second-order structural terms
 141 and noise variance terms.

142 Let us consider two images corrupted by independant additive noises
 143 characterized by respective variances σ_I^2 and σ_T^2 :

$$I = I_{nf} + \epsilon_I \quad \text{and} \quad T = T_{nf} + \epsilon_T, \quad (15)$$

144 where the indice nf indicates noise-free values. This yields the noisy jaco-
 145 bians:

$$\mathbf{J}_I(\mathbf{w}) = \mathbf{J}_I^{nf}(\mathbf{w}) + \mathbf{J}_{\epsilon_I}(\mathbf{w}) \quad \text{and} \quad \mathbf{J}_T(\mathbf{w}) = \mathbf{J}_T^{nf}(\mathbf{w}) + \mathbf{J}_{\epsilon_T}(\mathbf{w}), \quad (16)$$

146 where $\mathbf{J}_{\epsilon_I}(\mathbf{w})$ and $\mathbf{J}_{\epsilon_T}(\mathbf{w})$ are the jacobian matrices obtained by concatenat-
 147 ing the pixelwise gradients:

$$\mathbf{J}_{\epsilon_I, i}(\mathbf{w}) = \left. \frac{\partial \epsilon_I(\mathbf{W}(\boldsymbol{\mu}^k \circ \exp(\mathbf{v}), \mathbf{x}_i))}{\partial \mathbf{v}} \right|_{\mathbf{v}=\mathbf{w}}, \quad \text{and} \quad (17)$$

$$\mathbf{J}_{\epsilon_T, i}(\mathbf{w}) = \left. \frac{\partial \epsilon_T(\mathbf{W}(\exp(\mathbf{v}), \mathbf{x}_i))}{\partial \mathbf{v}} \right|_{\mathbf{v}=\mathbf{w}}. \quad (18)$$

148 3.1. Noise-free case

149 In this section we consider that the noise-free images are identical up to
 150 the true motion parameter vector \mathbf{v}^* :

$$\forall \mathbf{x} \quad I^{nf}(\mathbf{W}(\boldsymbol{\mu}^k \circ \exp((1 - \alpha)\mathbf{v}^*), \mathbf{x})) = I^{nf}(\mathbf{W}(\exp(-\alpha\mathbf{v}^*), \mathbf{x})), \quad (19)$$

151 which yields:

$$\mathbf{e}_\alpha^{nf}(\mathbf{v}^*) = \mathbf{0}. \quad (20)$$

152 Under this assumption we can show that:

153 **Theorem 1** (Second-order expansion under noise-free conditions at optimum
 154 \mathbf{v}^*). For any α :

$$\mathbf{e}_\alpha^{nf}(\mathbf{v}^*) = \mathbf{e}_\alpha^{nf}(\mathbf{0}) + \frac{1}{2}(\mathbf{J}_I^{nf}(\mathbf{0}) + \mathbf{J}_T^{nf}(\mathbf{0}))\mathbf{v}^* + O(\|\mathbf{v}^*\|^3). \quad (21)$$

155 *Proof.* We use here the lemmas presented in Appendix A. According to
 156 (A.1), we have to second-order:

$$\mathbf{e}_\alpha^{nf}(\mathbf{v}) = \mathbf{e}_\alpha^{nf}(\mathbf{0}) + \frac{1}{2}(\mathbf{J}_\alpha^{nf}(\mathbf{0}) + \mathbf{J}_\alpha^{nf}(\mathbf{v}))\mathbf{v} + O(\|\mathbf{v}\|^3). \quad (22)$$

157 Moreover, for the true parameter \mathbf{v}^* , and using (A.13), we have:

$$(\mathbf{J}_\alpha^{nf}(\mathbf{0}) + \mathbf{J}_\alpha^{nf}(\mathbf{v}^*))\mathbf{v}^* = (\mathbf{J}_I^{nf}(\mathbf{0}) + \mathbf{J}_T^{nf}(\mathbf{0}))\mathbf{v}^* + O(\|\mathbf{v}^*\|^3) \quad (23)$$

158 Plugging (23) into (22) yields (21). \square

159 Note that $\mathbf{e}_\alpha(\mathbf{0})$ is independent of α . Benhimane and Malis (2007) ini-
 160 tially proposed the ESM procedure consisting in plugging the jacobian \mathbf{J}_{ESM}
 161 into the equation (10) as a second-order minimization of the forward objec-
 162 tive function ($\alpha = 0$ in (8)) where:

$$\mathbf{J}_{\text{ESM}} = \frac{1}{2}(\mathbf{J}_I(\mathbf{0}) + \mathbf{J}_T(\mathbf{0})). \quad (24)$$

163 Their proof was based on the assumption (19). Under the same assumption,
 164 equation (21) generalizes this result by revealing that the ESM optimization
 165 yields in fact a second-order minimization of any ACL objective function,
 166 with FCL and ICL objective functions as special cases.

167 3.2. In presence of noise

168 Under noisy conditions eq. (23) cannot be applied on the noisy jacobian
 169 \mathbf{J}_α and holds only for the noise-free part \mathbf{J}_α^{nf} . Furthermore, during the op-
 170 timization procedure we have only access to the noisy image jacobian $\mathbf{J}_I(\mathbf{0})$
 171 and $\mathbf{J}_T(\mathbf{0})$. Thus, we are looking for the α value that produces a jacobian
 172 $\mathbf{J}_\alpha(\mathbf{0})$ as close as possible to the jacobian $\mathbf{J}_{\text{ESM}}^{nf}$.

Theorem 2 (Discrepancy between $\mathbf{J}_\alpha(\mathbf{0})$ and the ideal jacobian $\mathbf{J}_{\text{ESM}}^{nf}$).

$$\mathbf{J}_{\text{ESM}}^{nf} = \mathbf{J}_\alpha(\mathbf{0}) - (\mathbf{A}_\alpha + \mathbf{B}_\alpha), \quad (25)$$

173 with:

$$\begin{aligned} \mathbf{A}_\alpha &= \left(\frac{1}{2} - \alpha\right)\mathbf{J}_\ominus^{nf}(\mathbf{0}), \\ \mathbf{B}_\alpha &= (1 - \alpha)\mathbf{J}_{\epsilon_I}(\mathbf{0}) + \alpha\mathbf{J}_{\epsilon_T}(\mathbf{0}), \end{aligned} \quad (26)$$

174 where :

$$\mathbf{J}_\ominus^{nf}(\mathbf{0}) = \mathbf{J}_I^{nf}(\mathbf{0}) - \mathbf{J}_T^{nf}(\mathbf{0}). \quad (27)$$

Proof.

$$\begin{aligned} \mathbf{J}_{\text{ESM}}^{nf} &= \mathbf{J}_\alpha^{nf}(\mathbf{0}) - \left(\frac{1}{2} - \alpha\right)\mathbf{J}_\ominus^{nf}(\mathbf{0}) \\ &= \mathbf{J}_\alpha(\mathbf{0}) - \left(\frac{1}{2} - \alpha\right)\mathbf{J}_\ominus^{nf}(\mathbf{0}) - ((1 - \alpha)\mathbf{J}_{\epsilon_I}(\mathbf{0}) + \alpha\mathbf{J}_{\epsilon_T}(\mathbf{0})) \end{aligned} \quad (28)$$

175 □

176 Equation (25) highlights the presence of two kinds of corrupting terms $\mathbf{A}_\alpha\mathbf{v}^*$
 177 and $\mathbf{B}_\alpha\mathbf{v}^*$ when plugged into eq. (21).

178 *Term of structure.* The term $\mathbf{A}_\alpha \mathbf{v}^*$ corresponds to second-order terms of the
 179 noise-free error $\mathbf{e}_\alpha^{nf}(\mathbf{v}^*)$ at optimum as it can be shown by plugging (A.13)
 180 into (A.4):

$$\mathbf{J}_\ominus^{nf}(\mathbf{0})\mathbf{v}^* = (\mathbf{J}_I^{nf}(\mathbf{0}) - \mathbf{J}_I^{nf}(\mathbf{v}^*))\mathbf{v}^* \stackrel{(A.4)}{=} O(\|\mathbf{v}^*\|^2). \quad (29)$$

181 Using the ESM algorithm allows us to compensate them and therefore reach
 182 a second-order approximation in the noise-free case.

183 *Term of noise.* The term $\mathbf{B}_\alpha \mathbf{v}^*$ corresponds to first-order contribution of
 184 noise. Assuming the noises on I and T are independant of respective variance
 185 σ_I^2 and σ_T^2 and of zero mean, the total variance of $\mathbf{B}_\alpha \mathbf{v}^*$ is proportional to:

$$\text{var}(\mathbf{B}_\alpha \mathbf{v}^*) \propto (1 - \alpha)^2 \sigma_I^2 + \alpha^2 \sigma_T^2 \quad (30)$$

186 Minimizing (30) with respect to α defines a new Minimal Variance ACL
 187 approach denoted MVACL:

$$\alpha^{\text{MVACL}} = \frac{\sigma_I^2}{\sigma_I^2 + \sigma_T^2}. \quad (31)$$

188 This α value has the following properties: it yields an ESM behaviour
 189 for symmetric amount of noise ($\sigma_I = \sigma_T$) and unidirectional FCL behaviour
 190 (resp. ICL behaviour) when $\sigma_I \ll \sigma_T$ (resp. $\sigma_I \gg \sigma_T$).

191 Several typical cases can be considered:

- 192 • The SNR is high and the initialization is close to the optimum ($\|\mathbf{v}^*\|^2 \ll$
 193 $\|\mathbf{v}^*\|$): the terms \mathbf{A}_α and \mathbf{B}_α are small and do not influence the align-
 194 ment process, the FCL, ICL, ESM and MVACL perform equivalently.
- 195 • The SNR (signal to noise ratio) is high and the initialization is far
 196 from the optimum ($\|\mathbf{v}^*\|$ is large): the term \mathbf{A}_α dominates \mathbf{B}_α and the
 197 optimal α is near 0.5, as used by the ESM.
- 198 • The SNR is low, but the noise is symmetrically distributed ($\sigma_I \approx \sigma_T$)
 199 on I and T , then the variance of $\mathbf{B}_\alpha \mathbf{v}^*$ is also minimum for $\alpha = 0.5$,
 200 which is used by both the ESM and the MVACL algorithms.
- 201 • The SNR is low and asymmetrically distributed $\sigma_I \gg \sigma_T$ (resp. $\sigma_I \ll$
 202 σ_T) and the initialization is close to the optimum : \mathbf{B}_α dominates \mathbf{A}_α ,
 203 and the optimal α is the one that minimizes the variance of \mathbf{B}_α as

| | Term of structure $\mathbf{A}_\alpha \mathbf{v}^*$ | Term of noise $\mathbf{B}_\alpha \mathbf{v}^*$ | Recommended approach |
|--|---|---|--------------------------------------|
| Noiseless or low noise with close initialization | negligible | negligible | FCL, ICL, ESM, MVACL |
| Noiseless or low noise with far initialization | X | negligible | ESM |
| Symmetric noise | X | X | MVACL, ESM |
| Near initialization with strong asymmetric noise | negligible | X | MVACL |
| Far initialization with strong asymmetric noise | X | X | proposed heuristics AACL and GACL |

Table 1: Summary of methods fitness to several typical situations of alignment. Noiseless or low noise : σ_I, σ_T are negligible. Strong noise : σ_I or/and σ_T are high values. Symmetric noise : $\sigma_I \approx \sigma_T$. Near initialization : the motion to estimate $\|\mathbf{v}^*\|$ is close to 0. Far initialization : the motion to estimate $\|\mathbf{v}^*\|$ is large.

204 estimated by the MVACL. For very asymmetric noise levels, one of the
205 images is far more corrupted than the other. The optimal α value can
206 reach the bounds 0 if T is the image strongly corrupted (resp. 1 if I is
207 the image strongly corrupted), which is used by the FCL (resp. ICL)
208 approach.

- 209 • The SNR is low and the initialization is far from the optimum : both
210 terms \mathbf{A}_α and \mathbf{B}_α are not negligible and should be taken care of. In that
211 case it is difficult to predict which algorithm is more efficient between
212 the MVACL and the ESM.

213 It follows from the previous analysis that the ESM and the MVACL
214 provide the same result for symmetrical levels of noise, but that in other
215 cases, each one assumes one of terms \mathbf{A}_α or \mathbf{B}_α is negligible. Those remarks
216 are summarized in table 1 and will be discussed further in the experimental
217 section 5.2. The MVACL furthermore requires the knowledge of the noise
218 variances. We propose in the next section to take a different perspective
219 on this problem by using a geometrically motivated solution for the fully-
220 automatic estimation of α .

221 4. Fully-automatic estimation of α

222 Authesserre et al. (2009) have shown that the asymmetric approach can
223 outperform other approaches in terms of robustness to noise by choosing

224 an appropriate α . In the robotic community Marey and Chaumette (2008)
 225 propose a similar approach for designing command law in visual servoing. In
 226 both cases no rule was presented to compute the α -value. In this section we
 227 propose two methods based on an automatic computation of this coefficient.

228 *4.1. Method 1 : Geometric ACL (GACL)*

229 In the following, we denote by F_α the affine subspace passing through
 230 $\mathbf{e}_\alpha(\mathbf{0})$ and parallel to the span of the columns of $\mathbf{J}_\alpha(\mathbf{0})$. The elements of F_α
 231 can be obtained by the linearized error:

$$\tilde{\mathbf{e}}_\alpha(\mathbf{v}) = \mathbf{e}_\alpha(\mathbf{0}) + \mathbf{J}_\alpha(\mathbf{0})\mathbf{v}. \quad (32)$$

232 We also denote by $\hat{\mathbf{v}}_\alpha$ the Lie algebra increment estimated by plugging $\mathbf{J}_\alpha(\mathbf{0})$
 233 into eq. (10).

234 The geometric interpretation of the Gauss-Newton algorithm is that the
 235 increment $\hat{\mathbf{v}}_\alpha$ is chosen such that $\hat{\mathbf{e}}_\alpha = \tilde{\mathbf{e}}_\alpha(\hat{\mathbf{v}}_\alpha)$ corresponds to the orthogonal
 236 projection of the origin \mathbf{O} of the error space onto the affine subspace F_α .
 237 Thus, the different ACL methods can be distinguished by the choice of the
 238 subspace F_α onto which \mathbf{O} is projected. This is illustrated in fig. 1 for the
 239 case of a motion model with one degree of freedom.




Figure 1: Geometric interpretation of the different approaches using a Gauss-Newton optimization for one parameter motion: \mathbf{O} is projected orthogonally onto a particular affine subspace F_α (in this case, affine line for a model of $p = 1$ parameter). The projection of \mathbf{O} onto F_α is noted $\hat{\mathbf{e}}_\alpha$.

240 The α value of the ACL approach can be seen as a confidence value on the
 241 directions (in the error space), of the subspaces F_0 and F_1 . It should favor

242 the directions that lead closer to the origin \mathbf{O} of the error space. We propose
 243 to compute α by using the distances of \mathbf{O} to both subspaces F_0 and F_1 .
 244 Considering the plane passing through the points $\hat{\mathbf{e}}_0$, $\hat{\mathbf{e}}_1$ and \mathbf{O} (see fig. 2),
 245 we denote by \mathbf{P} the orthogonal projection of \mathbf{O} onto the line passing through
 246 $\hat{\mathbf{e}}_1$ and $\hat{\mathbf{e}}_0$, by l the distance between $\hat{\mathbf{e}}_1$ and $\hat{\mathbf{e}}_0$ and by d_1 (respectively d_0)
 247 the distance between \mathbf{O} and $\hat{\mathbf{e}}_1$ (respectively $\hat{\mathbf{e}}_0$). Using the Pythagorean
 248 theorem in $(\mathbf{O}, \mathbf{P}, \hat{\mathbf{e}}_0)$ and in $(\mathbf{O}, \mathbf{P}, \hat{\mathbf{e}}_1)$, we obtain:

$$\alpha^{\text{GACL}} = \frac{d_0^2 - d_1^2}{2l^2} + \frac{1}{2} = \frac{\langle \hat{\mathbf{e}}_0 | (\hat{\mathbf{e}}_0 - \hat{\mathbf{e}}_1) \rangle}{\|(\hat{\mathbf{e}}_0 - \hat{\mathbf{e}}_1)\|^2}, \quad (33)$$

249 where $\langle . | . \rangle$ (respectively $\|.\|$) stands for the regular scalar product (re-
 250 spectively the Euclidean vector norm) in \mathbb{R}^N .




Figure 2: Generic interpretation of the α^{GACL} value: The distances between the point \mathbf{O} and the subspaces F_0 and F_1 are estimated. Then α^{GACL} is chosen to favor the nearest subspace to \mathbf{O} .

251 The α^{GACL} value favors the subspace nearest to \mathbf{O} . If both subspaces are
 252 equally near to \mathbf{O} , the α^{GACL} value is equal to 0.5, and the behaviour of the
 253 ESM approach occurs. This method in its simplest form requires computing
 254 both $\hat{\mathbf{e}}_0$ and $\hat{\mathbf{e}}_1$ to estimate α^{GACL} which is quite costly.

255 4.2. Method 2 : Analytic ACL (AACL)

256 The AACL algorithm considers the linearization of the pixelwise residual
 257 eq. (8) around $\mathbf{v} = \mathbf{0}$ (cf. eq. (32)). An approximation of the complete
 258 residual error is obtained by plugging eq. (32) into eq. (7):

$$E_\alpha(\mathbf{v}) \approx \|\mathbf{e}_\alpha(\mathbf{0}) + \mathbf{J}_I(\mathbf{0})\mathbf{v}\|^2 - 2\alpha(\mathbf{e}_\alpha(\mathbf{0}) + \mathbf{J}_I(\mathbf{0})\mathbf{v})^T \mathbf{J}_\Theta(\mathbf{0})\mathbf{v} + \alpha^2 \|\mathbf{J}_\Theta(\mathbf{0})\mathbf{v}\|^2, \quad (34)$$

259 where $\mathbf{J}_\ominus = \mathbf{J}^I(\mathbf{0}) - \mathbf{J}^T(\mathbf{0})$.

260 Minimizing this residual with respect to α for a fixed $\hat{\mathbf{v}}$ yields the confi-
 261 dence value used by the AACL algorithm:

$$\alpha^{\text{AACL}}(\hat{\mathbf{v}}) = \frac{\langle \tilde{\mathbf{e}}_0(\hat{\mathbf{v}}) | (\tilde{\mathbf{e}}_0(\hat{\mathbf{v}}) - \tilde{\mathbf{e}}_1(\hat{\mathbf{v}})) \rangle}{\|\tilde{\mathbf{e}}_0(\hat{\mathbf{v}}) - \tilde{\mathbf{e}}_1(\hat{\mathbf{v}})\|^2}, \quad (35)$$

262 where $\tilde{\mathbf{e}}_\alpha(\hat{\mathbf{v}})$ is defined by equation (32).

263 Notice the similarity between the expressions (33) and (35). In the first
 264 case, α is obtained by projecting \mathbf{O} orthogonally onto the affine line $(\hat{\mathbf{e}}_0, \hat{\mathbf{e}}_1)$.
 265 In the second one, \mathbf{O} is projected orthogonally onto the line $(\tilde{\mathbf{e}}_0(\hat{\mathbf{v}}), \tilde{\mathbf{e}}_1(\hat{\mathbf{v}}))$
 266 instead. For the AACL method, a fixed $\hat{\mathbf{v}}$ has to be set before using eq.
 267 (35). In the sequel, we note AACL^M the analytic AACL approach using the
 268 method M for computing $\hat{\mathbf{v}}$, where M can be the FCL approach ($\alpha = 0$),
 269 the ICL approach ($\alpha = 1$) or the ESM approach ($\alpha = 0.5$).

270 4.3. Summary of the algorithms and fast approximations

271 The state-of-the-art gradient-based approaches and the new ones can be
 272 seen as particular cases of the ACL formulation using different values of α
 273 for the computation of the jacobian matrix eq. (12). The different methods
 274 considered in this paper are summarized in the table 2. The main steps of
 the algorithm scheme is summarized in table 3.

| ACL Methods | | | | | | |
|-----------------------|-----|-----|-----|-------------------------------------|------------------------------------|--|
| Non-adaptive to noise | | | | Adaptive to noise | | |
| Fixed- α | | | | Supervised- α | Automatic- α | |
| | FCL | ICL | ESM | MVACL | GACL | AACL^M |
| α | 0 | 1 | 0.5 | α^{MVACL} eq. (31) | α^{GACL} eq. (33) | $\alpha^{\text{AACL}}(\hat{\mathbf{v}})$ eq. (35) |

Table 2: The different asymmetric approaches. For the AACL approach, M stands for the method (FCL, ICL or ESM approach) used to set $\hat{\mathbf{v}}$ in equation (35).

275
 276 For step 2b), if the automatically computed α is such that $\alpha > 1$ (resp. is
 277 such that $\alpha < 0$), we arbitrarily set it to 1 (resp. 0) yielding the behaviour of
 278 the ICL (resp. FCL) approach. All approaches are based on the computation
 279 of the Jacobian matrices \mathbf{J}_I and \mathbf{J}_T . Implementation issues are tackled in
 280 appendix Appendix C.

281 As noted by Baker and Matthews (2004), steps 2a, 2b and 2c can be
 282 skipped for the ICL approach ($\alpha = 1$). Moreover, for this method, the

Iterative scheme of the ACL approaches

| |
|--|
| <ol style="list-style-type: none"> 1. Precomputation: <ol style="list-style-type: none"> (a) Compute the template jacobian $\mathbf{J}_T(\mathbf{0})$ (eq. (14)), (b) Estimate α for the MVACL, F-GACL and F-AACL (eq. (31), (33) and (35)). 2. Iterate until convergence: <ol style="list-style-type: none"> (a) Compute the current error $\mathbf{e}_\alpha(\mathbf{0})$ (eq. (8)) and the image jacobian $\mathbf{J}_I(\mathbf{0})$ (eq. (13)), (b) Only for AACL and GACL approaches, compute α (eq. (35) or (33)), (c) Compute the asymmetric jacobian $\mathbf{J}_\alpha(\mathbf{0})$ (eq. (12)), (d) Solve for \mathbf{v} (eq. (10)), (e) Update parameters $\boldsymbol{\mu}^{k+1}$ (eq. (9)). |
|--|

Table 3: Unified presentation of the algorithm scheme of the ACL approaches.

283 pseudo-inverse of the jacobian $\mathbf{J}_{\alpha=1}(\mathbf{0}) = \mathbf{J}_T(\mathbf{0})$ can be precomputed. The
 284 ICL algorithm is thus the most efficient of the ACL approaches in terms of
 285 computational time per iteration.

286 The AACL and GACL algorithms may introduce a significant overhead
 287 in terms of computational time for the computation of α (step 2b) if they
 288 are run on a sequential processor. To improve the efficiency, we propose
 289 estimating α only once during the first iteration. This yields an approxima-
 290 tion of the AACL and GACL denoted F -GACL (Fast-GACL) and F -AACL
 291 (Fast-AACL). The fast new approaches only introduce an additional compu-
 292 tational effort for computing α during the first iteration compared with fixed
 293 α -ACL approaches (except for the ICL approach).

294 This computational cost is called E-CC (for Extra Computational Cost)
 295 in the sequel. Moreover, we denote by P-CC (Pre-Computational Cost) the
 296 computational effort induced each time the image used as the template T
 297 changes (step 1) in table 3) and by I-CC (iterative computational cost) the
 298 standard cost of each iteration of a fixed- α -ACL algorithm (step 2a), 2c)
 299 and 2d) in table 3). The table 4 summarizes the computational time of the
 300 different approaches obtained with a Matlab implementation on a Intel(R)
 301 Core(TM)2 duo CPU 3.0 GHz with 4 GB of RAM. The number of pixels N
 302 of the template is 10000. The number of parameters for the homography is
 303 $p = 8$.

| Methods | P-CC | E-CC | I-CC |
|--------------------------------|------|------|------|
| FCL | 4.22 | 0 | 7.00 |
| ICL | 7.60 | 0 | 4.53 |
| ESM | 6.73 | 0 | 7.16 |
| AACL ^{ESM} | 6.38 | 0 | 9.08 |
| $F - \text{AACL}^{\text{ESM}}$ | 6.40 | 1.33 | 7.15 |
| GACL | 7.57 | 0 | 8.99 |
| $F - \text{GACL}$ | 7.61 | 1.25 | 7.15 |

Table 4: Computational time (in ms) of the different approaches. Three steps are distinguished : the precomputation for the template T (P-CC), the extra computation performed by the fast new approaches each time a new image I has to be processed (E-CC), and the per iteration cost performed by each algorithm (I-CC).

304 The E-CC for the fast approaches takes approximately a fifth of the compu-
305 tational time of one iteration of the ESM. Thus the additional computational
306 cost for computing α with the fast approximations of the GACL and AACL
307 is very small when several iterations are required for convergence. The next
308 section will show in which situations this cost is counterbalanced by an in-
309 creased robustness of the estimation.

310 5. Experimental validation

311 The performance assessment uses a methodology inspired by the bench-
312 mark proposed by Baker and Matthews (2004). Random homographies are
313 generated by adding spatial Gaussian noise of standard deviation σ_p (called
314 Point Sigma) to four canonical point locations in a reference image I_{ref} . The
315 new locations are called test points. Using these homographies, the image
316 I_{ref} is warped onto the template image T_{ref} . I_{ref} (resp. T_{ref}) is then cor-
317 rupted with additive gaussian noise: $I = I_{ref} + \epsilon_I$ (resp. $T = T_{ref} + \epsilon_T$).
318 Noise level is characterized by the SNR (Signal to Noise ratio) between the
319 noise-free image and the image of noise: $SNR_{dB} = 10 \log_{10} \left(\frac{E(I^2)}{Var(\epsilon)} \right)$. The
320 RMS point error is defined as the root mean square error between the test
321 points and the point locations obtained from the motion parameter estimated
322 by an alignment algorithm in the reference image coordinates.

323 We will consider two main performance criteria defined by Baker and
324 Matthews (2004):

- 325 - Average frequency of convergence: percentage of tests where an algo-
326 rithm converged to the correct estimate (RMS Point Error < 1 pixel),




Figure 3: Images used for the experiments. First row: The noise-free image (left) is used for extracting the template image. Image I is then obtained by adding gaussian noise to the noise free image. The noisy images (right) are shown with respective SNR : 15 dB, 10 dB and 5 dB. Second row: other images used for the experimentations. Images A and E come from the INRIA Learning and Recognition in Vision (LEAR) dataset (<http://lear.inrialpes.fr/data>). Images B and C come from the benchmark of Baker and Matthews (2004). Image D was synthesized using an OpenGL implementation.

327 - Average rates of convergence: for tests that converge for all methods, the
 328 average RMS point error is plotted against the algorithm iteration number.

329 In the sequel, the results are obtained by averaging the performances
 330 obtained on the five images [A-E] shown in figure 3. The motion model
 331 is a homography parameterized as in Appendix B: a 3×3 homography
 332 matrix \mathbf{H} which belongs to the Lie group \mathcal{P} of matrices with $\det(\mathbf{H}) = 1$. Its
 333 associated Lie algebra \mathfrak{P} is the vector space of matrices with null trace. For
 334 each algorithm and each test, 30 iterations are done. For average frequency of
 335 convergence, 500 tests are done per image and per Point Sigma. For average
 336 rates of convergence, 100 tests which converge are averaged per image.

337 5.1. ACL algorithms behavior in presence of noise

338 Figure 4 shows the behaviours of the ACL approaches, using a fixed value
 339 for α , in terms of frequency of convergence with respect to image SNR , when
 340 aligning an almost noise free template to a noisy image. As mentioned by
 341 Authesserre et al. (2009), the best performance is obtained by a compromise
 342 between the use of the gradients of both T and I , and the weighting of the
 343 influence of noise. Thus, when the images are noise free (high SNR), the
 344 FCL ($\alpha = 0$) and the ICL ($\alpha = 1$) provide identical results and the ESM
 345 ($\alpha = 0.5$) outperforms these two methods. However, when the noise level
 346 increases on I , the performance of the ESM decreases. When the SNR of I

347 becomes too low, the ICL provides the best results. Between these two cases
 348 the best robustness is obtained using an intermediate α value.




Figure 4: Average frequency of convergence of fixed- α ACL approaches with respect to image SNR for a Point Sigma equal to 12 pixels. A SNR of 100 dB was used on the template. The image is corrupted using a SNR varying from -15 dB to 30 dB.

349 5.2. Influence of the noise asymmetry

350 To simulate controled noise asymmetry, noise is parameterized by a total
 351 variance σ^2 , and an asymmetry coefficient $\beta \in [0,1]$. The total variance σ^2 is
 352 computed from a given global SNR in order to average results with images
 353 (figure 3) of the same quality. The amount of noise is allocated to I and T
 354 as follows:

$$\sigma_I^2 = (1 - \beta)\sigma^2, \quad \sigma_T^2 = \beta\sigma^2, \quad \text{with } \beta \in [0, 1]. \quad (36)$$

355 where σ_I (resp. σ_T) is used as noise standard deviation to corrupt the image
 356 I (resp. the template T) with an additive centered white Gaussian noise.

357 Six configurations are considered to evaluate the comparative perfor-
358 mances for various typical situations:

- 359 • Exp.0 : near initialization (Point Sigma σ_p equal to 6 pixels) and high
360 SNR (Total SNR=15 dB)
- 361 • Exp.1 : near initialization (Point Sigma σ_p equal to 6 pixels) and
362 medium SNR (Total SNR=10 dB)
- 363 • Exp.2 : near initialization (Point Sigma σ_p equal to 6 pixels) and low
364 SNR (Total SNR=5 dB)
- 365 • Exp.3 : far initialization (Point Sigma σ_p equal to 12 pixels) and high
366 SNR (Total SNR=15 dB)
- 367 • Exp.4 : far initialization (Point Sigma σ_p equal to 12 pixels) and
368 medium SNR (Total SNR=10 dB)
- 369 • Exp.5 : far initialization (Point Sigma σ_p equal to 12 pixels) and low
370 SNR (Total SNR=5 dB)

371 The results of the experiments 0-5 are shown on figure 5 and discussed in the
372 sequel.

373 5.2.1. Conventional algorithms

374 The first column of the figure 5 shows the results of the FCL, ICL, ESM
375 and MVACL algorithms. As mentioned in the theoretical analysis (section
376 3.1), the ESM provides better results when β is near 0.5 (see exp. 0-5), or
377 when the total SNR is high (Exp. 0 and 3). By using only the gradients of
378 I (resp. T), the FCL (resp. ICL) yields only the best performance for β near
379 1 (resp. 0) or when the image T (resp. I) is sufficiently corrupted (Exp. 2,
380 low SNR).

381 5.2.2. MVACL approach

382 As it can be seen on the first column of the figure 5, the MVACL provides
383 performance similar to ICL for $\beta = 0$ that evolves smoothly to be similar to
384 ESM for $\beta = 0.5$ and to FCL for $\beta = 1$. On the one hand, the MVACL yields
385 a better behaviour than the standard approaches under low SNR conditions
386 (Exp.2 and 5) because in that case the MVACL appropriately averages the
387 term of noise \mathbf{B}_α of the equation (25). On the other hand, this approach

388 is outperformed by the ESM under high SNR conditions (Exp. 0 and 3).
389 Indeed, by only taking into account the noise variance for computing α , the
390 MVACL optimally weights noise-jacobian terms at the expense of taking into
391 consideration the term \mathbf{A}_α , which is in that case not negligible compared to
392 the term of noise \mathbf{B}_α .




Figure 5: Average frequency of convergence with respect to noise asymmetry for the different approaches. Exp. 0: $\sigma_p = 6$ pixels, SNR=15 dB. Exp. 1: $\sigma_p = 6$ pixels, SNR=10 dB. Exp. 2: $\sigma_p = 6$ pixels, SNR=5 dB. Exp. 3: $\sigma_p = 12$ pixels, SNR=15 dB. Exp. 4: $\sigma_p = 12$ pixels, SNR=10 dB. Exp. 5: $\sigma_p = 12$ pixels, SNR=5 dB. Corresponding numerical values for characteristic β values are presented in table 5.

| Conditions | Exp.0 | | | Exp.1 | | | Exp.2 | | | Exp.3 | | | Exp.4 | | | Exp.5 | | |
|--------------------------------|------------------------------------|-------------|-------------|------------------------------------|-------------|-------------|-----------------------------------|-------------|-------------|-------------------------------------|-------------|-------------|-------------------------------------|-------------|-------------|------------------------------------|-------------|-------------|
| | $\sigma_p = 6$ pixels SNR=15 dB | | | $\sigma_p = 6$ pixels SNR=10 dB | | | $\sigma_p = 6$ pixels SNR=5 dB | | | $\sigma_p = 12$ pixels SNR=15 dB | | | $\sigma_p = 12$ pixels SNR=10 dB | | | $\sigma_p = 12$ pixels SNR=5 dB | | |
| β | 0 | 0.2 | 0.5 | 0 | 0.2 | 0.5 | 0 | 0.2 | 0.5 | 0 | 0.2 | 0.5 | 0 | 0.2 | 0.5 | 0 | 0.2 | 0.5 |
| FCL | 83.6 | 85.7 | 88.2 | 53.6 | 62.7 | 75.0 | 13.6 | 18.2 | 30.6 | 32.8 | 37.3 | 43.2 | 10.2 | 13.6 | 23.3 | 0.8 | 1.6 | 4.8 |
| ICL | 92.4 | 91.2 | 88.9 | <u>92.4</u> | 87.4 | 75.7 | <u>90.4</u> | 63.6 | 32.0 | 54.4 | 49.9 | 42.8 | <u>53.6</u> | 40.2 | 24.4 | <u>52.7</u> | 18.2 | 4.5 |
| ESM | <u>95.2</u> | <u>95.0</u> | <u>95.4</u> | 91.0 | 91.3 | 91.7 | 59.4 | <u>63.9</u> | <u>67.3</u> | <u>67.4</u> | 67.2 | 67.4 | 52.2 | <u>52.4</u> | <u>52.3</u> | 18.6 | <u>19.7</u> | 20.7 |
| MVACL | 92.4 | 94.0 | 95.4 | 92.4 | 92.2 | 91.7 | 90.4 | 76.0 | 67.3 | 54.4 | 63.4 | 67.4 | 53.6 | 54.2 | 52.3 | 52.7 | 29.0 | 20.7 |
| GACL | 95.1 | 95.0 | 95.1 | 94.4 | 92.5 | 91.4 | 90.5 | 73.3 | 67.6 | 68.5 | 67.4 | 66.4 | 63.6 | 56.0 | 52.2 | 55.4 | 27.5 | 20.5 |
| AAACL ^{FCL} | 94.5 | 94.3 | 94.6 | 90.7 | 89.7 | 90.2 | 51.6 | 49.9 | 58.2 | 65.1 | 64.4 | 64.5 | 54.4 | 51.2 | 50.1 | 20.3 | 17.1 | 17.4 |
| AAACL ^{ICL} | 94.4 | 94.2 | 94.3 | 93.7 | 92.4 | 90.0 | 91.6 | 74.3 | 58.1 | 65.3 | 65.1 | 64.0 | 61.5 | 54.8 | 50.3 | 56.8 | 28.6 | 18.0 |
| AAACL ^{ESM} | 95.3 | 95.1 | 95.2 | 94.4 | 92.9 | 91.6 | 86.4 | 73.3 | 67.8 | 68.9 | 68.0 | 67.1 | 63.9 | 56.6 | 52.6 | 51.5 | 28.0 | 20.6 |
| <i>F</i> -GACL | 95.0 | <u>94.8</u> | 95.0 | <u>94.1</u> | 92.4 | <u>90.6</u> | <u>89.1</u> | 73.0 | 63.6 | 67.4 | 66.4 | 65.1 | 61.8 | 53.7 | 48.7 | <u>50.0</u> | 24.0 | 17.0 |
| <i>F</i> -AAACL ^{ESM} | <u>95.2</u> | <u>94.8</u> | <u>95.1</u> | 94.0 | <u>92.5</u> | <u>90.6</u> | 86.3 | 74.4 | <u>64.2</u> | <u>68.0</u> | <u>67.0</u> | <u>66.1</u> | <u>62.6</u> | 54.6 | <u>50.1</u> | 44.7 | <u>26.7</u> | <u>18.6</u> |

Table 5: Average frequency of convergence with respect to noise for the different approaches for characteristic β values. Best overall method is in bold, best methods in each category are underlined.

393 *5.2.3. Influence of the choice of $\hat{\mathbf{v}}$ for the AACL approaches*

394 In the following we evaluate the new approaches. The second column of
395 figure 5 shows the different behaviors of the AACL^{FCL}, AACL^{ICL}, AACL^{ESM}
396 and the GACL algorithms in terms of frequency of convergence with respect
397 to image noise asymmetry. The ESM performances are also plotted as refer-
398 ence. We observe that:

- 399 • For any Point Sigma and Total SNR and for any β , the AACL^M ap-
400 proach using the method M to initialize $\hat{\mathbf{v}}$ in (35) always provides at
401 least as good results as the method M itself (Exp.0-5).
- 402 • The performance of the AACL^M is correlated to the performance of the
403 method M itself. Thus, for situations where the FCL (resp. ICL) works
404 well, such as in Exp.2 and and in Exp.5 for β near 1 (resp. near 0), the
405 AACL^{FCL} provides better results than the conventional methods and
406 other AACL approaches by improving the performances of the FCL
407 (resp. ICL) approach. In all other cases, the AACL^{ESM} provides better
408 results.

409 *5.2.4. AACL vs GACL*

410 For any β value and for any global SNR , the GACL and AACL^{ESM} yield
411 similar results. Moreover, they always provide the best results (Exp. 0, 1, 3
412 and 4) or near the best results (Exp. 2 and 5). The AACL^{FCL} and AACL^{ICL}
413 are only more robust in very asymmetric cases (Exp.2 and 5) where the noisy
414 image is not the one used for computing the gradients allowing the estimation
415 of $\hat{\mathbf{v}}$. For all these reasons, we consider in the sequel only the GACL and
416 AACL^{ESM} approaches.

417 *5.3. Performance of the fast approximations*

418 The figure (5), third column shows the different behaviors of the ESM,
419 F -AACL^{ESM} and F -GACL algorithms in terms of frequency of convergence
420 with respect to image noise asymmetry. It can be seen that the fast ap-
421 proximations produce the same behaviors as the exact AACL and GACL
422 approaches. However, the fast approximations provide slightly worse results
423 than the exact approaches, particularly for quasi symmetric amount of noise
424 (β between 0.35 and 0.65) where they are outperformed by the ESM ap-
425 proach (see Exp. 2, 4 and 5). The fast approaches are thus a good choice for
426 aligning a noisy image to another noisy image, but of greater quality (which

427 in practice takes place for example in image mosaicking (Pham et al., 2005)
 428 where a noisy image is aligned to the current mosaic).

429 To illustrate this, fig. 6 shows the average rate of convergence (Point
 430 Sigma σ_p equal to 6 pixels) and average frequency of convergence with re-
 431 spect to σ_p for a noisy image ($SNR_I = 10$ dB) and a high quality template
 432 ($SNR_T = 100$ dB). For legibility, only the fast approximations and the state-
 433 of-the-art approaches are plotted.




Figure 6: Average Frequency of convergence and average Convergence Rate for the ESM, ICL, FCL, $F - AAAL^{ESM}$, $F - GACL$ algorithms in presence of image noise. A SNR of 10 dB has been used on the image and 100 dB on the template.

434 The fast new approaches outperform the state-of-the-art approaches in
 435 terms of frequency of convergence and convergence rate. The improvement
 436 in convergence rate counter-balances the E-CC introduced by the computa-
 437 tion of α during the first iteration. Thus, the new approaches are at least
 438 as efficient as the best reference algorithms while better handling noisy im-
 439 ages. Thus, for an equivalent computational complexity and according to the
 440 repartition of noise on images we can provide the following recommendation:

- 441 • In quasi noiseless condition or in symmetric noise condition ($SNR_I \approx$
 442 SNR_T), the ESM algorithm would provide the best results among the
 443 studied approaches.
- 444 • In very asymmetric noise condition $SNR_I \gg SNR_T$ (resp. $SNR_I \ll$
 445 SNR_T), the FCL algorithm (resp. ICL) would provide the best results
 446 among the studied approaches.

- 447
448
449
450
 • In the other cases, the AACL^{ESM} and GACL would be preferred if the best robustness is required. Trading off for computational performance, the $F\text{-AACL}^{\text{ESM}}$ or $F\text{-GACL}$ would be chosen in presence of strong corruption with asymmetric noise levels.

451 6. Object tracking under low-light conditions

452
453
454
455
456
457
 In low-light conditions, an optical imaging system produces bad quality images (cf. figure 7) that can be modeled according to Alter et al. (2006) : the observed number of photons at one pixel is drawn from a Poisson distribution whose parameter is proportional to the average received intensity. Thus, tracking an object using gradient-based approach becomes a challenging task because the Poisson noise can severely corrupt the gradients of the images.

458
459
460
461
462
 In order to improve the tracking performance for this kind of data, one would try to lower the noise on the template by averaging several registered frames. This approach yields an asymmetric image alignment problem where the current image I is registered to the template T of higher quality. We now evaluate the usefulness of the proposed algorithms in such a context.

463 6.1. Corpus and ground truth design

464
465
466
467
468
469
 We considered two sequences of 40 and 32 images captured with the same imaging device (samples are presented on figure 7). In the first sequence one object of interest is selected and three are selected in the second sequence. This yields 136 independent observations of real shot noise associated to low-light imaging. For each sequence and object, a ground-truth is generated by using the following protocol:




Figure 7: Samples of low-light image.

- 470 • the object of interest is selected in the frame 1 of the sequence (which
471 plays the role of the template image T) through the use of a rectangular
472 bounding-box. This location defines the true parameter $\bar{\boldsymbol{\mu}}(1)$ of the
473 position of the object in the first image.
- 474 • The ESM algorithm is run to align image $t+1$ and image 1 by initializing
475 alignment parameter with $\bar{\boldsymbol{\mu}}(t)$ and by using 200 iterations which allows
476 the algorithm to estimate parameter $\bar{\boldsymbol{\mu}}(t+1)$. The ESM algorithm is
477 used here because it has been shown to be the more efficient in presence
478 of symmetric noise. The motion model used is 2D translation. We
479 checked manually frame by frame that the ESM produced reasonable
480 motion parameters.

481 The generated ground-truth $\bar{\boldsymbol{\mu}}$ is approximative. We will not use it to do
482 accuracy evaluation. However, we can use it to evaluate convergence rate
483 and frequency of convergence of the different algorithms with a sufficiently
484 large error threshold.

485 6.2. Evaluation methodology

486 The following results are obtained by averaging performance obtained for
487 many different motion initializations for each image and for each object of
488 interest. In order to do this, we use a benchmark similar to the one presented
489 in section 5. First, the corners associated to the object of interest in the cur-
490 rent image t are computed by using the parameters $\bar{\boldsymbol{\mu}}(t)$. A perturbation $\delta\mathbf{x}$
491 drawn randomly from a zero-mean normal distribution of standard deviation
492 $\sigma_p = 10$ is added to the spatial location \mathbf{x} of each corner. The new locations
493 of the corners yield the initial parameters $\boldsymbol{\mu}_i^0(t)$ used to initialize the different
494 alignment algorithms.

495 Two setups are studied here :

- 496 • Exp.6 : the algorithms are run using only the first image as a template.
497 The level of noise is thus symmetric.
- 498 • Exp.7 : each algorithm generates its template by averaging the five
499 first frames of the video, after compensating the images in the same
500 coordinate frame by using the estimated motion parameters.

501 For each frame, 20 different motion initializations are generated which
502 yield more than 2000 tests for each setup.

503 *6.3. Results*

504 Figures 8 show the performance of the different algorithms in terms of
505 mean RMS Point Error and frequency of convergence as a function of the
506 iteration number for the Exp.6 and 7. The mean RMS Point Error corre-
507 sponds to the mean euclidean distance between the four corners of the region
508 of interest predicted by the tested algorithm and those of the ground truth.
509 For the frequency of convergence, the convergence threshold is 4 pixels in
510 terms of RMS Point Error.




Figure 8: Convergence rate in terms of mean RMS Point error relatively to the iteration number and frequency of convergence relatively to the iteration number on a sequence of real images corrupted by shot noise. A threshold of 4 pixels on the RMS Point Error is used to check the convergence of an approach. Left : only the first frame is used as a template (Exp.6). Right : The five first frames are used to generate the template after motion compensation (Exp.7).

511 The ESM algorithm and the new approaches ACL provide better results
512 than the more conventional approaches FCL and ICL for the Exp.6 which
513 confirms on real data the good behavior of such approaches under symmet-
514 rical level of noise.

515 The use of an averaged template (Exp.7) improves the performance of
516 all approaches that use the gradients of T . This improvement yields the
517 approaches AACL, GACL and their fast approximations to outperform the
518 other approaches in terms of convergence rate and frequency of convergence.

519 *Remark on the accuracy of the approaches.* In figure 8, after convergence,
520 using only the first frame as the template (Exp. 6) has lower RMS point
521 error than generating the template with the first five frames (Exp.7). The
522 difference in accuracy observed under symmetric or asymmetric conditions
523 are around 0.5 pixel. Because the images are very corrupted, it is difficult to
524 check manually that the ground truth provides the position of the object with
525 such a precision. Thus, there are two possible explanations for the difference
526 in RMS Point Error at convergence :

- 527 1. By reducing the noise injected to the system in the Exp.7, averaging
528 yields results which are more accurate than without the averaging (in-
529 accurate ground-truth).
- 530 2. Because of a non perfect motion estimation, frame averaging in Exp.7
531 introduces a slight blur on the template which yields a decrease of the
532 accuracy of the approaches (blurred template).

533 This analysis reveals that, when averaging frames, a trade off has to be made
534 between noise and blur reduction.

535 The averaging process was only introduced to illustrate the potential of
536 the ACL formulation to register images in presence of noise level asymmetry.
537 The study of using many frames to generate a high quality template is an
538 interesting perspective, which is out of the scope of this paper.

539 In both Exp.6 and Exp.7 the automatic-ACL approaches provide as ac-
540 curate results as the best of the state-of-the art approach, while improving
541 robustness and convergence rate under asymmetric conditions, thus showing
542 their ability to estimate a relevant α on such real datasets.

543 6.4. Illustration of tracking

544 To illustrate the principle of tracking using an average template, figure 9
545 presents the results of the approaches FCL, ICL, ESM and F -AACL^{ESM} (the

546 different heuristics AACL, GACL, F -AACL^{ESM} and F -GACL^{ESM} approaches
547 provide similar results on those data) under real tracking conditions. As
548 in Exp.7, each algorithm generates its template by averaging the five first
549 frames of the video, after compensating the images in the same coordinate
550 frame by using the estimated motion parameters. The motion parameters
551 are initialized in each frame by those estimated in the previous frame. Each
552 algorithm performs 30 iterations per image. The FCL approach fails to track
553 the object of interest. The approach ESM loses the object of interest after
554 the frame 20. The ICL approach accumulates tracking error and fails to track
555 after the frame 25. The F -AACL^{ESM} approach is able to track the object
556 during the whole sequence.

557 Such an illustration shows under a realist context, the potentiality of the
558 new Asymmetric approaches.

559 7. Conclusion

560 In this paper we used the Asymmetric Composition on Lie Group (ACL)
561 formulation proposed by Authesserre et al. (2009) to provide new gradient-
562 based image alignment methods that compute automatically the asymmetry
563 parameter α . A theoretical analysis allowed us to identify that in presence
564 of noise, the role of the asymmetry parameter α is to perform a trade-off
565 involving two terms : the deterministic structural term and the random
566 noise term. Three new approaches have been proposed, i.e. the MVACL,
567 GACL and AACL. The MVACL approach is more of a theoretical interest
568 as it ignores the structural term completely, in favor of the minimization of
569 noise variance. The two other approaches GACL and AACL are heuristics
570 based on a geometrical and an analytical interpretation of the problem, which
571 were shown to estimate relevant values of α , yielding improvement in the
572 robustness to asymmetric noise. Those heuristics have practical interest,
573 since they are fully automatic and reach comparable performance as the
574 MVACL for asymmetric noise, even though the later requires the knowledge
575 of noise variances. An interesting perspective for a future work, would be to
576 take into account this information to further improve the performances.

577 The new methods introduce a computational overhead because of the
578 need to compute α . To alleviate the computational burden, fast approxi-
579 mations of the new methods have been introduced, which have comparable
580 computational complexity as fixed- α state-of-the-art methods, but with bet-
581 ter robustness in case of asymmetric noise levels.

















| Frame | FCL | ICL | ESM | $F\text{-AACL}^{\text{ESM}}$ |
|-------|---|---|--|---|
| 1 |  |  |  |  |
| 10 |  |  |  |  |
| 20 |  |  |  |  |
| 30 |  |  |  |  |

Figure 9: Tracking performance of the FCL, ICL, ESM and $F\text{-AACL}^{\text{ESM}}$ approaches on a video captured under low-light conditions. The first five images are used to build an average template. The dashed line rectangle corresponds to the ground truth location of the object. The solid line rectangle corresponds to the tracking results of the different algorithms after 30 iterations.

582 The benefits of the new methods were studied in the case of image align-
583 ment with L2 pixelwise errors. As done by Brooks and Arbel (2009) for the
584 inverse compositional and the ESM methods, the proposed approach could
585 be extended to more generic error metrics and motion models to fit particu-
586 lar needs in various applications. We think their properties could be useful
587 in applications where a slightly noisy template would be aligned to a highly
588 noisy image under low-light condition (Alter et al., 2006).

589 In this paper, we focused on the problem of noise related asymmetry. In
590 applications such as super-resolution (Dijk et al., 2008), where the images
591 to align can have different resolutions, the derivatives of the low-resolution
592 frame is less reliable than the derivatives of the high resolution estimate. This
593 problem of resolution asymmetry has been thoroughly discussed in (Dedeoglu
594 et al., 2007) in term of bias on the estimation of the warp. However, the
595 problem of the reliability of the image derivatives has not been tackled. We
596 think that it is an interesting perspective for future developments, to merge
597 those two sources of asymmetry in a single formulation.

598 Acknowledgement

599 The authors would like to thank M. Grossetete of Thales Avionics corp.
600 for providing the real low light images used in the experimental section.

601 Appendix A. Second-order approximation of the ACL objective 602 function

603 In the following we present the main properties used for the derivation of
604 the second-order approximation of the ACL objective function (cf. eq. (21))
605 under noise-free conditions.

Lemma (Second-order linearization of the ACL objective function).

$$\mathbf{e}_\alpha(\mathbf{v}) = \mathbf{e}_\alpha(\mathbf{0}) + \frac{1}{2}(\mathbf{J}_\alpha(\mathbf{0}) + \mathbf{J}_\alpha(\mathbf{v}))\mathbf{v} + O(\|\mathbf{v}\|^3) \quad (\text{A.1})$$

606 *Proof.* By developing (8) to second-order around $\mathbf{v} = \mathbf{0}$, we have at each
607 pixel \mathbf{x}_i :

$$\mathbf{e}_{\alpha,i}(\mathbf{v}) = \mathbf{e}_{\alpha,i}(\mathbf{0}) + \mathbf{J}_{\alpha,i}(\mathbf{0})\mathbf{v} + \frac{1}{2}\mathbf{v}^t\mathbf{H}_{\alpha,i}(\mathbf{0})\mathbf{v} + O(\|\mathbf{v}\|^3) \quad (\text{A.2})$$

with $\mathbf{J}_{\alpha,i}(\mathbf{0})$ the jacobian matrix and $\mathbf{H}_{\alpha,i}(\mathbf{0})$ the Hessian matrix of $e_{\alpha,i}$ at $\mathbf{0}$:

$$\mathbf{H}_{\alpha,i}(\mathbf{w}) = \left. \frac{\partial^2 \mathbf{e}_{\alpha,i}(\mathbf{v})}{\partial \mathbf{v}^2} \right|_{\mathbf{w}} \quad (\text{A.3})$$

608 We also have:

$$\mathbf{J}_{\alpha,i}(\mathbf{v}) = \mathbf{J}_{\alpha,i}(\mathbf{0}) + \mathbf{v}^t \mathbf{H}_{\alpha,i}(\mathbf{0}) + O(\|\mathbf{v}\|^2) \quad (\text{A.4})$$

609 Thus, by plugging (A.4) into (A.2), we obtain (A.1). This linearization is
610 valid in noise-free as well as in noisy cases. \square

Lemma (Jacobian equivalence along \mathbf{v}^*).

$$\mathbf{J}_I^{nf}((1-\alpha)\mathbf{v}^*)\mathbf{v}^* = \mathbf{J}_T^{nf}(-\alpha\mathbf{v}^*)\mathbf{v}^* \quad (\text{A.5})$$

611 *Proof.* Using directional derivative along \mathbf{v}^* , the assumption (20) and the
612 exponential map properties (2) and (3), we have:

$$\begin{aligned} & \mathbf{J}_{I,i}^{nf}((1-\alpha)\mathbf{v}^*)\mathbf{v}^* \\ &= \left. \frac{\partial I^{nf}(\mathbf{W}(\boldsymbol{\mu}^k \circ \exp((1-\alpha)\mathbf{v}^* + t\mathbf{v}^*), \mathbf{x}_i))}{\partial t} \right|_{t=0} \\ &= \left. \frac{\partial T^{nf}(\mathbf{W}(\exp(-\alpha\mathbf{v}^* + t\mathbf{v}^*), \mathbf{x}_i))}{\partial t} \right|_{t=0} \quad (\text{A.6}) \\ &= \mathbf{J}_{T,i}^{nf}(-\alpha\mathbf{v}^*) \left. \frac{\partial(-\alpha\mathbf{v}^* + t\mathbf{v}^*)}{\partial t} \right|_{t=0} \\ &= \mathbf{J}_T^{nf}(-\alpha\mathbf{v}^*)\mathbf{v}^* \end{aligned}$$

613 \square

Corollary.

$$\mathbf{J}_\alpha^{nf}(\mathbf{v}^*)\mathbf{v}^* = \mathbf{J}_I^{nf}((1-\alpha)\mathbf{v}^*)\mathbf{v}^* = \mathbf{J}_T^{nf}(-\alpha\mathbf{v}^*)\mathbf{v}^* \quad (\text{A.7})$$

614

615 with the special cases:

$$\mathbf{J}_I^{nf}(\mathbf{v}^*)\mathbf{v}^* = \mathbf{J}_T^{nf}(\mathbf{0})\mathbf{v}^* \quad (\text{A.8})$$

$$\mathbf{J}_T^{nf}(-\mathbf{v}^*)\mathbf{v}^* = \mathbf{J}_I^{nf}(\mathbf{0})\mathbf{v}^* \quad (\text{A.9})$$

616 *Proof.* We have:

$$\mathbf{J}_\alpha^{nf}(\mathbf{v}^*)\mathbf{v}^* = (1 - \alpha)\mathbf{J}_I^{nf}((1 - \alpha)\mathbf{v}^*)\mathbf{v}^* + \alpha\mathbf{J}_T^{nf}(-\alpha\mathbf{v}^*)\mathbf{v}^*. \quad (\text{A.10})$$

617 Using lemma A.5 into the previous equation to replace $\mathbf{J}_{nf}^T(-\alpha\mathbf{v}^*)\mathbf{v}^*$ yields
 618 (A.7). The special cases are obtained for $\alpha = 0$ and $\alpha = 1$. \square

619 Note that we generalize here the proof of (A.8) proposed by Benhimane
 620 and Malis (2007) to the generic ACL jacobian.

621 **Lemma** (Linear approximation of the image jacobian).

622 For $\gamma \in [0, 1]$

$$\mathbf{J}_I(\gamma\mathbf{v}) = \mathbf{J}_I(\mathbf{0}) + \gamma(\mathbf{J}_I(\mathbf{v}) - \mathbf{J}_I(\mathbf{0})) + O(\|\mathbf{v}\|^2) \quad (\text{A.11})$$

623 *Proof.* By expanding $\mathbf{J}_{I,i}(\gamma\mathbf{v})$ to first-order around $\mathbf{0}$ we have:

$$\mathbf{J}_{I,i}(\gamma\mathbf{v}) - \mathbf{J}_{I,i}(\mathbf{0}) = \gamma\mathbf{v}^t \frac{\partial^2 I(\mathbf{W}(\boldsymbol{\mu}^k \circ \exp(\mathbf{v}), x_i))}{\partial \mathbf{v}^2} \Big|_{\mathbf{v}=\mathbf{0}} + O(\|\gamma\mathbf{v}\|^2) \quad (\text{A.12})$$

624

\square

Lemma (Linear approximation of the α -ACL jacobian).

$$\mathbf{J}_\alpha^{nf}(\mathbf{v}^*)\mathbf{v}^* = (\alpha\mathbf{J}_I^{nf}(\mathbf{0}) + (1 - \alpha)\mathbf{J}_T^{nf}(\mathbf{0}))\mathbf{v}^* + O(\|\mathbf{v}^*\|^3) \quad (\text{A.13})$$

Proof.

$$\begin{aligned} \mathbf{J}_\alpha^{nf}(\mathbf{v}^*)\mathbf{v}^* &\stackrel{(\text{A.7})}{=} \mathbf{J}_I^{nf}((1 - \alpha)\mathbf{v}^*)\mathbf{v}^* \\ &\stackrel{(\text{A.11})}{=} (\mathbf{J}_I^{nf}(\mathbf{0}) + (1 - \alpha)(\mathbf{J}_I^{nf}(\mathbf{v}^*) - \mathbf{J}_I^{nf}(\mathbf{0})))\mathbf{v}^* + O(\|\mathbf{v}^*\|^3) \\ &\stackrel{(\text{A.8})}{=} (\alpha\mathbf{J}_I^{nf}(\mathbf{0}) + (1 - \alpha)\mathbf{J}_T^{nf}(\mathbf{0}))\mathbf{v}^* + O(\|\mathbf{v}^*\|^3) \end{aligned} \quad (\text{A.14})$$

625

\square

626 **Appendix B. Parametrization of homography**

627 In this section we present the homography parameterization of motion
 628 used in the experimental section.

A 2D Homography is a transformation in the projective image plane \mathbb{P}^2 . A homography can be represented by a 3×3 matrix \mathbf{H} :

$$\mathbf{H} = \begin{pmatrix} 1 + \mu_1 & \mu_2 & \mu_3 \\ \mu_4 & 1 + \mu_5 & \mu_6 \\ \mu_7 & \mu_8 & 1 + \mu_9 \end{pmatrix}. \quad (\text{B.1})$$

629 with $\boldsymbol{\mu} = [\mu_1 \ \mu_2 \ \mu_3 \ \mu_4 \ \mu_5 \ \mu_6 \ \mu_7 \ \mu_8 \ \mu_9]^T$ in \mathcal{P} , which is isomor-
 630 phic to $\text{SL}(3)$, the Special Linear Group of dimension 3 (Benhimane and
 631 Malis, 2007) satisfying $\det(\mathbf{H}) = 1$.

A group action \mathbf{W} , fulfilling equations (4), (5) and (6) can be defined from $\text{SL}(3)$ to \mathbb{P}^2 . For $\mathbf{H} \in \text{SL}(3)$ and $\mathbf{x} = [x \ y \ 1]^T \in \mathbb{P}$, we have:

$$\mathbf{W} : \text{SL}(3) \times \mathbb{P}^2 \mapsto \mathbb{P}^2$$

$$(\mathbf{H}, \mathbf{x}) \mapsto \begin{pmatrix} \frac{\mu_1 x + \mu_2 y + \mu_3}{\mu_7 x + \mu_8 y + \mu_9} \\ \frac{\mu_4 x + \mu_5 y + \mu_6}{\mu_7 x + \mu_8 y + \mu_9} \\ 1 \end{pmatrix} \quad (\text{B.2})$$

Lie Algebra local reparameterization. For \mathbf{H} around identity, \mathbf{H} can be reparameterized using the matrix exponential map:

$$\mathbf{H}(\mathbf{v}) = \text{expm}\left(\sum_{m=1}^8 v_m \mathbf{G}_m\right) \quad (\text{B.3})$$

with for any matrix \mathbf{X} :

$$\text{expm}(\mathbf{X}) = \sum_{m=0}^{\infty} \frac{1}{m!} (\mathbf{X}^m) \quad (\text{B.4})$$

and $\mathbf{v} = [v_1 \ v_2 \ v_3 \ v_4 \ v_5 \ v_6 \ v_7 \ v_8]^T$ in the Lie Algebra \mathfrak{P} associated to \mathcal{P} . $\{\mathbf{G}_m\}_{m=1..8}$ are 3×3 matrix called Lie algebra generators. Under the condition $\det(\mathbf{H}) = 1$, the generators must satisfy:

$$\forall m, \quad \text{Tr}(\mathbf{G}_m) = 0 \quad (\text{B.5})$$

632 where Tr is the trace of a matrix. The \mathbf{G}_m are the vector basis of the tangent
633 space to the Lie Group manifold around the identity parameter $\boldsymbol{\mu} = \mathbf{0}$.

The \mathbf{G}_m are chosen such that they convey a geometrical meaning. The generators associated to translations are :

$$\mathbf{G}_1 = \begin{pmatrix} 0 & 0 & 1 \\ 0 & 0 & 0 \\ 0 & 0 & 0 \end{pmatrix} \quad \mathbf{G}_2 = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 0 & 1 \\ 0 & 0 & 0 \end{pmatrix}. \quad (\text{B.6})$$

Indeed, by applying (B.4) to \mathbf{G}_1 (resp. \mathbf{G}_2) we obtain the standard 3×3 matrix of a translation along the x-axis (resp. y-axis). The generators associated respectively to isotropic dilation about the origin and rotation about the origin are:

$$\mathbf{G}_3 = \begin{pmatrix} \frac{1}{2} & 0 & 0 \\ 0 & \frac{1}{2} & 0 \\ 0 & 0 & -1 \end{pmatrix} \quad \mathbf{G}_4 = \begin{pmatrix} 0 & -1 & 0 \\ 1 & 0 & 0 \\ 0 & 0 & 0 \end{pmatrix}. \quad (\text{B.7})$$

The generators associated to shear at 0 and 45 degrees are :

$$\mathbf{G}_5 = \begin{pmatrix} 1 & 0 & 0 \\ 0 & -1 & 0 \\ 0 & 0 & 0 \end{pmatrix} \quad \mathbf{G}_6 = \begin{pmatrix} 0 & 1 & 0 \\ 1 & 0 & 0 \\ 0 & 0 & 0 \end{pmatrix}. \quad (\text{B.8})$$

The generators corresponding to the projective transformations induced by the parameters of the line at infinity are :

$$\mathbf{G}_7 = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 1 & 0 & 0 \end{pmatrix} \quad \mathbf{G}_8 = \begin{pmatrix} 0 & 0 & 0 \\ 0 & 0 & 0 \\ 0 & 1 & 0 \end{pmatrix}. \quad (\text{B.9})$$

634 Appendix C. Images Jacobian computation

635 In this section we tackle implementation issues about the Jacobian matrix
636 associated to an image.

The Jacobian Matrix associated to I and T are

$$\mathbf{J}_{I,i}(\mathbf{0}) = \left. \frac{\partial I(\mathbf{W}(\boldsymbol{\mu}^k \circ \exp(\mathbf{v})), \mathbf{x}_i)}{\partial \mathbf{v}} \right|_{\mathbf{v}=\mathbf{0}} \quad (\text{C.1})$$

and

$$\mathbf{J}_{T,i}(\mathbf{0}) = \left. \frac{\partial T(\mathbf{W}(\exp(\mathbf{v}), \mathbf{x}_i))}{\partial \mathbf{v}} \right|_{\mathbf{v}=\mathbf{0}}. \quad (\text{C.2})$$

Using chain-rule, we can decompose these Jacobians as

$$\mathbf{J}_{I,i}(\mathbf{0}) = \mathcal{M}_I \mathcal{M}_{\mathbf{W}} \mathcal{M}_L \quad \text{and} \quad \mathbf{J}_{T,i}(\mathbf{0}) = \mathcal{M}_T \mathcal{M}_{\mathbf{W}} \mathcal{M}_L. \quad (\text{C.3})$$

1. \mathcal{M}_I (resp. \mathcal{M}_T) is a 1×3 matrix corresponding to the gradient of the warped image I (resp. T) with parameters $\boldsymbol{\mu}^k$ (resp. $\mathbf{0}$):

$$\mathcal{M}_I = \left. \frac{\partial I(\mathbf{W}(\boldsymbol{\mu}^k, \mathbf{x}))}{\partial \mathbf{x}} \right|_{\mathbf{x}_i} \quad \text{and} \quad \mathcal{M}_T = \left. \frac{\partial T(\mathbf{x})}{\partial \mathbf{x}} \right|_{\mathbf{x}_i} \quad (\text{C.4})$$

637 Those gradients can be implemented using the Söbel operator.

2. $\mathcal{M}_{\mathbf{W}}$ is a matrix corresponding to the Jacobian of the warp:

$$\mathcal{M}_{\mathbf{W}} = \left. \frac{\partial \mathbf{W}(\boldsymbol{\mu}, \mathbf{x}_i)}{\partial \boldsymbol{\mu}} \right|_{\mathbf{0}} \quad (\text{C.5})$$

3. \mathcal{M}_L corresponds to the Jacobian of the Lie algebra reparameterization:

$$\mathcal{M}_L = \left. \frac{\partial \exp(\mathbf{v})}{\partial \mathbf{v}} \right|_{\mathbf{0}} \quad (\text{C.6})$$

638 $\mathcal{M}_{\mathbf{W}}$ and \mathcal{M}_L can be precomputed before running the alignment algorithm.
 639 \mathcal{M}_T can also be precomputed. That is why the inverse approach using only
 640 gradient of the template is computationally the most efficient of the ACL
 641 approaches. \mathcal{M}_I (and consequently $\mathbf{J}_{I,i}(\mathbf{0})$) has to be computed at each
 642 iteration.

Particular case of homography. For the homography model

$$\mathcal{M}_{\mathbf{W}} = \begin{pmatrix} \mathbf{x}_i^T & \mathbf{0} & -x_i \mathbf{x}_i^T \\ \mathbf{0} & \mathbf{x}_i^T & -y_i \mathbf{x}_i^T \\ \mathbf{0} & \mathbf{0} & \mathbf{0} \end{pmatrix} \in \mathbb{R}_{3 \times 9} \quad (\text{C.7})$$

$$\mathcal{M}_L = [[\mathbf{G}_1]_v \quad \dots \quad [\mathbf{G}_8]_v] \in \mathbb{R}_{9 \times 8} \quad (\text{C.8})$$

643 where $[\mathbf{G}_m]_v$ is the matrix \mathbf{G}_m reshaped as a vector (in row major order) and
 644 \mathbf{x}_i are homogeneous image coordinates $\mathbf{x}_i = [x_i \quad y_i \quad 1]^T \in \mathbb{P}^2$.

645 **References**

- 646 Alter, F., Matsushita, Y., Tang, X., 2006. An intensity similarity measure in
647 low-light conditions. In: European Conference on Computer Vision. Vol.
648 3954. pp. 267–280.
- 649 Authesserre, J.-B., Mégret, R., Berthoumieu, Y., April 2009. Asymmetric
650 gradient-based image alignment. In: IEEE International Conference on
651 Acoustics, Speech and Signal Processing. pp. 981–984.
- 652 Baker, S., Matthews, I., 2004. Lucas-Kanade 20 years on: A unifying frame-
653 work. *International Journal of Computer Vision* 56 (3), 221–255.
- 654 Bayro-Corrochano, E., Ortegón-Aguilar, J., 2007. Lie algebra approach for
655 tracking and 3d motion estimation using monocular vision. *Image and
656 Vision Computing* 25, 907–921.
- 657 Benhimane, S., Malis, E., July 2007. Homography-based 2d visual tracking
658 and servoing. *International Journal of Robotics Research* 26 (7), 661–676.
- 659 Brooks, R., Arbel, T., 2009. Generalizing inverse compositional and ESM
660 image alignment. *International Journal of Computer Vision* 87 (3), 191–
661 212.
- 662 Dedeoglu, G., Kanade, T., Baker, S., May 2007. The asymmetry of image
663 registration and its application to face tracking. *IEEE Transactions on
664 Pattern Analysis and Machine Intelligence* 29 (5), 607–623.
- 665 Dijk, J., van Eekeren, A. W. M., Schutte, K., de Lange, D. J., van Vliet, L. J.,
666 2008. Superresolution reconstruction for moving point target detection.
667 *Optical Engineering* 47 (9).
- 668 Guangwei, L., Yunpeng, L., Jian, Y., Zelin, S., 2008. Optimization on lie
669 manifolds and projective tracking. In: IEEE International Conference on
670 Computer Science and Software Engineering. Vol. 1. Los Alamitos, CA,
671 USA, pp. 768–771.
- 672 Keller, Y., Averbuch, A., August 2004. Fast motion estimation using bi-
673 directional gradient methods. *IEEE Transactions on Image Processing*
674 13 (8), 1042 – 1054.

- 675 Lucas, B., Kanade, T., 1981. An iterative image registration technique with
676 an application to stereo vision. In: proc. International Joint Conferences
677 on Artificial Intelligence. pp. 674–679.
- 678 Marey, M., Chaumette, F., May 2008. Analysis of classical and new visual
679 servoing control laws. In: proc. IEEE International Conference on Robotics
680 and Automation. Pasadena, California, pp. 3244–3249.
- 681 Mégret, R., Authesserre, J.-B., Berthoumieu, Y., 2008. The bi-directional
682 framework for unifying parametric image alignment approaches. In: proc.
683 European Conference on Computer Vision. pp. 400–411.
- 684 Miller, M. I., Younes, L., 2001. Group actions, homeomorphisms, and match-
685 ing: A general framework. *International Journal of Computer Vision* 41 (2),
686 61 – 84.
- 687 Pham, T. Q., Bezuijen, M., van Vliet, L. J., Schutte, K., Luengo Hendriks,
688 C. L., May 2005. Performance of optimal registration estimators. Vol. 5817
689 of proc. Society of Photo-Optical Instrumentation Engineers (SPIE) Con-
690 ference. pp. 133–144.
- 691 Shum, H.-Y., Szeliski, R., 2000. Construction of panoramic image mosaics
692 with global and local alignment. *International Journal of Computer Vision*
693 36 (2), 101–130.
- 694 Vercauteren, T., Pennec, X., Perchant, A., Ayache, N., 2009. Diffeomorphic
695 demons: Efficient non-parametric image registration. *NeuroImage* 45 (2),
696 561–572.