

Derivation of a merging condition for two interacting streamers in air

Zdenek Bonaventura, Max Duarte, Anne Bourdon, Marc Massot

▶ To cite this version:

Zdenek Bonaventura, Max Duarte, Anne Bourdon, Marc Massot. Derivation of a merging condition for two interacting streamers in air. Plasma Sources Science and Technology, 2012, pp.1-10. hal-00697691v1

HAL Id: hal-00697691 https://hal.science/hal-00697691v1

Submitted on 15 May 2012 (v1), last revised 31 Jul 2012 (v2)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Derivation of a merging condition for two interacting streamers in air

Zdeněk Bonaventura¹, Max Duarte², Anne Bourdon^{3,4}, Marc Massot^{3,4,5}

 1 Department of Physical Electronics, Faculty of Science, Masaryk University, Kotlářská 2, 611 37 Brno, Czech Republic

 2 Laboratoire J.-A. Dieudonné – UMR CNRS 6621, Université de Nice – Sophia Antipolis, Parc Valrose, 06108 Nice Cedex 02, France

³ CNRS, UPR 288 "Laboratoire d'Energétique Moléculaire et Macroscopique, Combustion", Grande voie des vignes, 92295 Châtenay-Malabry, France

⁴ Ecole Centrale Paris, Grande voie des vignes, 92295 Châtenay-Malabry, France
 ⁵ Center for Turbulence Research, Stanford University, Building 500, 488 Escondido
 Mall, Stanford CA 94305-3035, USA

E-mail: zbona@physics.muni.cz

Abstract. The simulation of the interaction of two simultaneously propagating air streamers of the same polarity is presented. A parametric study has been carried out using an accurate numerical method which ensures a time-space error control of the solution. For mutual separation of both streamers smaller or comparable to the longest characteristic absorption length of photoionization in air, we have found that streamers tend to merge if the ratio between their radii and their mutual distance is about 0.35 for positive streamers, and 0.4 for negative ones. Moreover it is demonstrated that these ratios are practically independent of the applied electric field, the initial seed configuration, and the pressure.

PACS numbers: 52.80.Mg, 52.65.-y, 51.50.+v, 47.11.St

Electrical breakdown in air gaps often involves the development of fast ionizing waves that take the form of thin filaments called streamers [1]. These complex and highly nonlinear phenomena precede the formation of sparks and leaders. Similar filamentary structures are observed in sprites: large-scale discharges which appear at low pressure in the altitude range of about 40 to 90 km above large thunderstorms [2, 3].Streamers often form branches. Then the individual streamer heads carry charges of the same polarity, and thus they are electrostatically repelling each other. However, careful observations show also the opposite behavior: streamers may even merge or reconnect [4, 5, 6]. So far, only few numerical studies have been carried out on streamer interactions. First, the impact of charges of numerous positive streamers, propagating simultaneously, on the electric field and on the velocity of one single positive streamer was studied in [7] for a 2D configuration. Later on it was shown in [8] that the electrodynamics of a 2D array of negative streamers substantially differs from the one of a single streamer due to their electrostatic interaction. Recently, the interaction of two streamer discharges in air and other oxygen-nitrogen mixtures has been studied for a 3D cylindrical configuration in [9]. These authors showed that two competing mechanisms have to be considered: attraction due to nonlocal photoionization between streamers and electrostatic repulsion of streamer heads due to their space charges of same polarity. Qualitatively, they concluded that streamer merging is favored if the distance between streamers is smaller or comparable to the streamer radius and to the longest absorption length of photoionization. However, a more precise or even quantitative description of streamer merging remains an open problem.

In this work, we simulate the interaction of two streamers of the same polarity by means of an accurate numerical method which ensures a time-space error control of the solution. The study is carried out in a Cartesian 2D geometry which significantly reduces computational costs with respect to fully 3D simulations, and thus allows us to perform an extended parametric analysis. In agreement with [8, 10], we consider that the main characteristics of the dynamics of the interacting streamers in two dimensions, as described below, will be similar in three dimensions. The main goal of this work is to provide quantitative information and hence a more precise physical description of the conditions of streamer merging. In practice we aim at defining geometrical parameters independent of the multivariable complex physical settings and thus a simple characterization that may be extended to more general configurations.

We consider the classical fluid model for air given by drift-diffusion equations selfconsistently coupled with Poisson's equation [11, 12]:

$$\left. \begin{array}{l} \partial_t n_{\rm e} - \partial_{\mathbf{x}} \cdot n_{\rm e} \, \mathbf{v}_{\rm e} - \partial_{\mathbf{x}} \cdot (D_{\rm e} \, \partial_{\mathbf{x}} n_{\rm e}) = \\ n_{\rm e} \alpha |\mathbf{v}_{\rm e}| - n_{\rm e} \eta |\mathbf{v}_{\rm e}| - n_{\rm e} n_{\rm p} \beta_{\rm ep} + n_{\rm n} \gamma + S_{\rm ph}, \\ \partial_t n_{\rm p} + \partial_{\mathbf{x}} \cdot n_{\rm p} \mathbf{v}_{\rm p} - \partial_{\mathbf{x}} \cdot (D_{\rm p} \, \partial_{\mathbf{x}} n_{\rm p}) = \\ n_{\rm e} \alpha |\mathbf{v}_{\rm e}| - n_{\rm e} n_{\rm p} \beta_{\rm ep} - n_{\rm n} n_{\rm p} \beta_{\rm np} + S_{\rm ph}, \\ \partial_t n_{\rm n} - \partial_{\mathbf{x}} \cdot n_{\rm n} \mathbf{v}_{\rm n} - \partial_{\mathbf{x}} \cdot (D_{\rm n} \, \partial_{\mathbf{x}} n_{\rm n}) = \\ n_{\rm e} \eta |\mathbf{v}_{\rm e}| - n_{\rm n} n_{\rm p} \beta_{\rm np} - n_{\rm n} \gamma, \end{array} \right\}$$

$$(1)$$

Derivation of a merging condition for two interacting streamers in air

$$\varepsilon_0 \partial_{\mathbf{x}} \cdot \mathbf{E} = -q_{\rm e}(n_{\rm p} - n_{\rm n} - n_{\rm e}), \quad \mathbf{E} = -\partial_{\mathbf{x}} V,$$
(2)

where $\mathbf{x} \in \mathbb{R}^d$, n_i is the density of charged species *i* (e: electrons, p: positive ions, n: negative ions), V and \mathbf{E} stand, respectively, for the electric potential and field, and $\mathbf{v}_i = \mu_i \mathbf{E}$ is the drift velocity. We denote by D_i and μ_i the diffusion coefficient and the absolute value of the mobility of charged species i, q_e is the absolute value of the electron charge, and ε_0 is the permittivity of free space. Moreover α is the impact ionization coefficient, η stands for the electron attachment coefficient, $\beta_{\rm ep}$ and β_{np} are, respectively, the electron-positive ion and negative-positive ion recombination coefficients, and γ is the detachment coefficient. All these coefficients depend on the local reduced electric field E/N, and thus vary in time and space, where $E = |\mathbf{E}|$ is the electric field magnitude, and N is the air neutral density. Further details are given in [15]. For $S_{\rm ph}$, the photoionization source term for air, we use the 3-Group SP₃ model derived in [13] with Larsen's boundary conditions [14]. In this model, three equivalent absorption lengths are used to model the wavelength dependence of the photoionization source term in air. At ground pressure these absorption lengths are $(\lambda_1 p_{O_2})^{-1} = 0.1408 \,\mathrm{cm}$, $(\lambda_2 p_{O_2})^{-1} = 0.0561 \,\mathrm{cm}$, and $(\lambda_3 p_{O_2})^{-1} = 0.0105 \,\mathrm{cm}$, where $p_{O_2} = 158.9 \,\mathrm{Torr}$ is the partial pressure of molecular oxygen in air.

To handle the stiff modeling equations, we have recently developed in [15] a numerical scheme for multi-scale streamer discharge simulations for general Cartesian multi-dimensional geometries. The strategy is based on a second order time adaptive integration with a splitting technique and dedicated solvers, and space finite volume multiresolution for dynamic grid adaptation. These features involve important efficiency gains in terms of CPU time and memory space while ensuring a time-space error control of the solution. Poisson's equation and Helmholtz equations issued by the photoionization model are considered on the adapted grid, and the resulting sparse linear systems are solved with MUMPS [16, 17]. We set in what follows a time-space accuracy tolerance of 10^{-4} for a space resolution equivalent to 7680×4096 points in a domain of $[-1.5, 1.5] \times [-0.8, 0.8]$ cm. The choice guarantees a sufficiently fine time-space representation of the physics, and numerical results disclosing practically the same physical behavior for higher spatial resolutions and tighter accuracy tolerances. The domain size is carefully chosen for the various configurations such that no interference of the boundaries is evidenced.

In order to preserve similarity constraints at different pressures (corresponding to discharges at different altitudes), all variables are scaled by an appropriate power of the ratio of the air density at ground pressure N_0 , and the air density N at the given pressure [18]. For example, the space dimensions scale as $\mathbf{x} = \mathbf{x}_0 N_0/N$, the charge densities as $n = n_0 N^2/N_0^2$, the electric field as $E = E_0 N/N_0$, and the time as $t = t_0 N_0/N$, where the subscript "0" refers to the values at ground pressure. Our reference (ground) density for air is $N_0 = 2.688 \times 10^{19} \,\mathrm{cm}^{-3}$ at a temperature of 273 K.

We study two separate discharge filaments initiated by placing two identical Gaussian plasma clouds into a homogeneous background electric field generated by two remote electrodes. The pressure, streamer polarity, applied electric field, and the



Figure 1. (color online) Time evolution of the net charge density for two positive streamers at ground pressure $(N/N_0 = 1.0)$ for an applied electric field $E_{\rm a} = 1.5E_{\rm bd}$ and two Gaussian seeds with $y_0 = 0.2 N_0/N \,\mathrm{cm}$, $n_{\rm max} = 10^{13} N^2/N_0^2 \,\mathrm{cm}^{-3}$, and $\sigma = 0.02N_0/N \,\mathrm{cm}$. (a) $t = 5.0 \,\mathrm{ns}$: well-developed streamers repulsing each other, (b) $t = t_{\rm tr} = 6.3 \,\mathrm{ns}$: transition between repulsion and merging, (c) $t = 8.0 \,\mathrm{ns}$: propagation of a single discharge. Black solid line: trajectory of the maximum electric field.

configuration parameters of the initial Gaussian seeds (the width σ , the maximum density n_{max} , and the mutual separation y_0) are varied in order to derive a condition for the merging of both streamers.

Figures 1(a)–(c) show snapshots of different phases of the evolution of the net charge density ($\rho = n_{\rm p} - n_{\rm e} - n_{\rm n}$) for two simultaneously propagating positive discharge filaments at ground pressure ($N/N_0 = 1.0$) for an initial seed separation of $y_0 = 0.2 N_0/N$ cm, a maximum density of $n_{\rm max} = 10^{13} N^2/N_0^2$ cm⁻³, a width $\sigma = 0.02N_0/N$ cm, and an applied electric field $E_{\rm a} = 1.5E_{\rm bd}$, where $E_{\rm bd} = 32 N/N_0$ kV cm⁻¹ is the breakdown electric field in air. The complete trajectory of the maximum electric field is also shown. Following this trajectory, the transition time $t_{\rm tr}$, between the streamer repulsion and the beginning of their merging, is defined as the instant when the separation of the two trajectories starts to decrease. For the condition of Figure 1, we have $t_{\rm tr} = 6.3$ ns. Figure 2(a) shows at this time the distribution of the net charge density. We define in Figure 2(b) the *mutual distance of both filaments* δ by the separation of the maximum net density $\rho_{\rm max}$ in each head and, the *streamer head diameter* \mathcal{D} as the cross section, in the direction perpendicular to the applied electric field $\mathbf{E}_{\rm a}$, where the charge density is locally higher than half the maximum net density: $\rho \geq \rho_{\rm max}/2$.

We have found that the merging condition for two streamers in air could be



Figure 2. (color online) (a) Net charge density and (b) Region where the net charge density is higher than half the maximum net charge density at $t = t_{tr}$ for the same condition as in Figure 1(b). Definition of the *streamer head diameter* \mathcal{D} and the *mutual distance of both filaments* δ .

represented by the value of the ratio \mathcal{D}/δ which appears to be very stable for a given polarity of discharges. For instance, for the same parameters of the seeds as in Figure 1 $(n_{\text{max}} = 10^{13} N^2/N_0^2 \text{ cm}^{-3}, y_0 = 0.2 N_0/N \text{ cm}, \text{ and } \sigma = 0.02 N_0/N \text{ cm})$ we have performed a set of simulations with an applied electric field E_a varying from $1.5E_{\text{bd}}$ to $2.5E_{\text{bd}}$ at ground pressure. Figure 3 shows that the resulting values of \mathcal{D}/δ for merging streamers are roughly constant and of about 0.35 for positive polarity discharges, and approximatively 0.4 for negative ones. Hence \mathcal{D}/δ is independent of the applied electric field E_a for both streamer polarities. Similarly, Figure 4 shows the dependence of \mathcal{D}/δ on n_{max} , the maximum density of seeds, for a fixed applied electric field $E_a = 1.5E_{\text{bd}}$. Same previous ratios are obtained whereas \mathcal{D}/δ is slightly decreasing as n_{max} involves only a variation of about 15% of \mathcal{D}/δ . Figure 5 shows the variation of \mathcal{D}/δ with altitude. We have considered altitudes ranging from the ground up to 80 km (corresponding to 1.5×10^{-5} atm). As shown in Figure 5, the \mathcal{D}/δ is independent of altitude and then of pressure in the range studied.

We have performed simulations to study the influence of the initial seed separation y_0 on \mathcal{D}/δ . Figure 6 shows the dependence of \mathcal{D}/δ for $y_0 \leq 0.2 N_0/N$ cm. Two sets



Figure 3. (color online) Ratios \mathcal{D}/δ for positive and negative streamers for different values of the applied electric field $E_{\rm a}/E_{\rm bd}$. Other parameters are similar to Figure 1.



Figure 4. (color online) Ratios \mathcal{D}/δ for positive and negative streamers for different values of the maximum density n_{\max} of seeds. Other parameters are similar to Figure 1.



Figure 5. (color online) Ratios \mathcal{D}/δ for positive and negative streamers for different altitudes and corresponding values of N/N_0 . Other parameters are similar to Figure 1.



Figure 6. (color online) Ratios \mathcal{D}/δ for positive and negative streamers for different initial seed distances y_0 , with (a) $n_{\rm max} = 10^{13} N^2/N_0^2 \,\mathrm{cm}$, $E = 1.5 E_{\rm bd}$, $\sigma = 0.02 N_0/N \,\mathrm{cm}$; (b) $n_{\rm max} = 10^{10} N^2/N_0^2 \,\mathrm{cm}$, $E = 2.5 E_{\rm bd}$, $\sigma = 0.00736 N_0/N \,\mathrm{cm}$. Absorption lengths for photoionization at ground pressure are shown.

of seed parameters were considered: (a) for $y_0 > 0.1 N_0/N$ cm: $n_{\rm max} = 10^{13} N^2/N_0^2$ cm, $\sigma = 0.02 N_0 / N \text{ cm}$, and $E = 1.5 E_{\text{bd}}$; (b) for $y_0 < 0.1 N_0 / N \text{ cm}$: $n_{\text{max}} = 10^{10} N^2 / N_0^2 \text{ cm}$, $\sigma = 0.00736 N_0/N \,\mathrm{cm}$, and $E = 2.5 E_{\mathrm{bd}}$. The first set corresponds to the reference condition used for Figure 1. The second set was chosen to be close to the conditions used in [9], and is characterized by a high value of the applied electric field, comparable to typical values of the electric field in streamer heads, and small initial seed width and separation. Because of the small seed width of the second set, the computations were performed for a space resolution equivalent to 15360×8192 points in a domain of $[-1.5, 1.5] \times [-0.8, 0.8]$ cm. Figure 6 shows that for positive streamers with $y_0 \geq 1$ $0.04 N_0/N$ cm, the value of the ratio \mathcal{D}/δ for the second set is slightly less than the reference value of 0.35 for the first set, which can be explained by the small dependence of \mathcal{D}/δ on $n_{\rm max}$, as seen in Figure 4. For negative streamers, Figure 6 shows that for $y_0 \ge 0.04 N_0/N$ cm, the ratio \mathcal{D}/δ is independent of the value of y_0 . For initial separation of streamers smaller than $y_0 < 0.04 N_0/N$ cm the transition between repulsion and merging is occurring very close to the initial Gaussian seeds and therefore the region where $\rho \geq \rho_{\rm max}/2$ is indistinguishably joined with the charge lobes, typically observed near the initial germs (shown in Figure 2). In this case, the streamer head appears to be significantly wider, and consequently the ratio \mathcal{D}/δ increases as shown in Figure 6. It is interesting to note that in the two sets used for Figure 6, very different values of σ have been used. We have carried out additional simulations to verify that the value of σ has a negligible influence on the ratio \mathcal{D}/δ .

In this work, we have carried out a parametric study on the interaction of streamers in air using numerical simulations based on an accurate numerical method which ensures a time-space error control of the solution. From the simulations performed we have deduced a stable value for the ratio \mathcal{D}/δ as merging condition for streamers. We have thus shown that simultaneously propagating streamers tend to merge when the ratio between their radii and their mutual distance is about 0.35 for positive streamers, and 0.4 for negative ones. These ratios are independent of the applied field, the initial seed configuration, and pressure. This quantitative analysis is valid for a mutual distance between streamers smaller or comparable to the longest characteristic absorption length of photoionization $(0.1408N_0/N \text{ cm})$. These results clearly illustrate the significant role of photoionization on streamer merging. We have also carried out simulations for larger values of y_0 , but it was not possible to derive simple conclusions on streamer interactions from the analysis of the value of the ratio \mathcal{D}/δ . Further studies are therefore required to find the key parameters to characterize streamer interactions when y_0 is much larger than the longest photoionization absorption length.

Acknowledgments

This research was supported by a fundamental project grant from ANR (French National Research Agency): Séchelles (ANR-09-BLAN-0075-01, PI. S. Descombes), and by a DIGITEO RTRA project: MUSE (PI. M. M.). Z. B. acknowledges support by project CZ.1.05/2.1.00/03.0086 funded by European Regional Development Fund and support of Ecole Centrale Paris.

References

- [1] Raizer Y P 1991 Gas Discharge Physics (Springer-Verlag, Berlin Heidelberg, 1991)
- [2] Sentman D D, Wescott E M, Osborne D L, Hampton D L, and Heavner M J 1995 Geophys. Res. Lett. 22 1205–8
- [3] Pasko V P 2007 Plasma Sources Sci. Technol. 16 S13–S29
- [4] Briels T M P, Kos J, van Veldhuizen E M and Ebert U 2006 J. Phys. D: Appl. Phys. 39 5201-10
- [5] Cummer S A, Jaugey N, Li J, Lyons W A, Nelson T E and Gerken E A 2006 Geophys. Res. Lett. 33 L04104
- [6] Nijdam S, Geurts C G C, van Veldhuizen E M and Ebert U 2009 J. Phys. D: Appl. Phys. 42 045201
- [7] Naidis G V 1996 J. Phys. D: Appl. Phys. 29 779–83
- [8] Luque A, Brau F and Ebert U 2008 Phys. Rev. E 78 016206
- [9] Luque A, Ebert U and Hundsdorfer W 2008 Phys. Rev. Lett. 101 075005
- [10] Brau F, Luque A, Meulenbroek B, Ebert U, and Schäfer L 2008 Phys. Rev. E 77 026219
- [11] Babaeva N Y and Naidis G V 1996 J. Phys. D: Appl. Phys. 29 2423-31
- [12] Kulikovsky A A 1998 Phys. Rev. E 57 7066–74
- [13] Bourdon A, Pasko V P, Liu N Y, Celestin S, Segur P and Marode E 2007 Plasma Sources Sci. Technol. 16 3 656–78
- [14] Liu N Y, Celestin S, Bourdon A, Pasko V P, Segur P and Marode E 2007 Appl. Phys. Lett. 91 21 211501
- [15] Duarte M, Bonaventura Z, Massot M, Bourdon A, Descombes S and Dumont T 2012 J. Comput. Phys. 231 3 1002–19
- [16] Amestoy P R, Duff I S, Koster J and L'Excellent J-Y 2001 SIAM J. Matrix Anal. Appl. 23 1 15-41
- [17] Amestoy P R, Guermouche A, L'Excellent J-Y and Pralet S 2006 Parallel Computing 32 2 136–56
- [18] Liu N and Pasko V P 2006 J. Phys. D: Appl. Phys. 39 327-34