



HAL
open science

Analysing eye movement data using Point Process models

Simon Barthelme

► **To cite this version:**

Simon Barthelme. Analysing eye movement data using Point Process models. 1ères Rencontres R, Jul 2012, Bordeaux, France. hal-00717555

HAL Id: hal-00717555

<https://hal.science/hal-00717555>

Submitted on 13 Jul 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Analysing eye movement data using Point Process models

Simon Barthelmé^a, Hans Trukenbrod^b, Ralf Engbert^b, Felix Wichmann^c

^aComputer Science
Technical University and Bernstein Center for Computational Neuroscience
Franklinstr. 28-29, 10487 Berlin
simon.barthelme@bccn-berlin.de

^bPsychology
University of Potsdam
Karl-Liebknecht-Str. 24/25, 14476 Potsdam OT Golm, Germany
{ralf,hans}.{engbert,trukenbrod}@uni-potsdam.de

^cComputer Science
University of Tübingen
Institute for Computer Sciences, Eberhard Karls University, 72076 Tübingen Germany
felix.wichmann@uni-tuebingen.de

Keywords: point processes, eye movements, spatial statistics

The measure and analysis of eye movements is crucial to neuroscience and psychology [10]. Eye movements are extremely useful from a methodological point of view - among other things, it is relatively easy to train animals to respond using eye movements, and the neurophysiological pathways involved are relatively well understood [6]. Eye movements are also tremendously interesting as an object of study in their own right, because they are the most immediate means we have to explore our visual environment.

In humans, the eyes do not move constantly but rather alternate between periods of relative stability, called fixations, and periods of movement. Very often the analysis is not concerned with movements but rather with fixations, and most especially where fixations occur. For example, in so-called “free-viewing” experiments, subjects view natural images, with no specific instructions - they are free to look wherever they like. Where they choose to fixate is far from random: subjects focus on similar locations, and exactly why they do that is an old debate in neuroscience and psychology [11, 8].

Some authors have argued that eye movements are controlled by a cortical *saliency map* [5], which represents interesting locations in the visual field, and that “interestingness” is computed very

early in the visual cortex using local image information. Following these ideas, models have been developed that seek to predict fixations from local image features [4]. Exactly what is being predicted and how is a source of some confusion in the literature, and many different methods have been proposed, with no unifying framework so far [12].

We argue that the right framework is to be found in the tools of spatial statistics [2]. A set of fixations is in essence spatial data - a set of points in space. For such data, appropriate statistical models are known as point processes: a point process is a probability distribution over finite subsets of a spatial domain. There is an extensive literature on how point process models can be used to analyse point patterns, reviewed for example in [3] and [7].

While the literature on point processes focuses mostly on studying the outcome of one point process, fixation data is better thought of as arising from many related point processes - for example, one process per image, or one process per subject, etc. The interesting questions often have to do with how fixation patterns vary (across subjects, across images) and whether they are common factors. We have developed a R package called **mpp**, for “multiple point processes”, which aims to facilitate Bayesian inference for such problems. It builds on the **spatstat** package [1] and uses **INLA** for approximate inference [9]. We will show how **mpp** can be used to explore some simple hierarchical point process models applied to fixation locations.

Acknowledgements

This work has benefited from funding from the BMBF (Foerderkennzeichen 01GQ1001B).

References

- [1] Adrian Baddeley and Rolf Turner. *Spatstat: an R package for analyzing spatial point patterns*. *Journal of Statistical Software*, 12(6):1–42, 2005. ISSN 1548-7660.
- [2] Peter J. Diggle. *Statistical Analysis of Spatial Point Patterns*. Hodder Education Publishers, 2 edition.
- [3] Janine Illian, Antti Penttinen, Helga Stoyan, and Dietrich Stoyan. *Statistical Analysis and Modelling of Spatial Point Patterns (Statistics in Practice)*. Wiley-Interscience, 1 edition, March 2008.
- [4] L. Itti and C. Koch. Computational modelling of visual attention. *Nature reviews. Neuroscience*, 2(3):194–203, March 2001.
- [5] C. Koch and S. Ullman. Shifts in selective visual attention: towards the underlying neural circuitry. *Human neurobiology*, 4(4):219–227, 1985.
- [6] Richard J. Krauzlis. The control of voluntary eye movements: New perspectives. *The Neuroscientist*, 11(2):124–137, April 2005.
- [7] Jesper Møller and Rasmus P. Waagepetersen. Modern statistics for spatial point processes*. *Scandinavian Journal of Statistics*, 34(4):643–684, December 2007.

- [8] Antje Nuthmann and John M. Henderson. Object-based attentional selection in scene viewing. *Journal of vision*, 10(8), 2010.
- [9] Håvard Rue, Sara Martino, and Nicolas Chopin. Approximate bayesian inference for latent gaussian models by using integrated nested laplace approximations. *Journal of the Royal Statistical Society: Series B (Statistical Methodology)*, 71(2):319–392, 2009.
- [10] Alexander C. Schütz, Doris I. Braun, and Karl R. Gegenfurtner. Eye movements and perception: A selective review. *Journal of vision*, 11(5), 2011.
- [11] Benjamin W. Tatler, Mary M. Hayhoe, Michael F. Land, and Dana H. Ballard. Eye guidance in natural vision: Reinterpreting salience. *Journal of Vision*, 11(5), May 2011.
- [12] Niklas Wilming, Torsten Betz, Tim C. Kietzmann, and Peter König. Measures and limits of models of fixation selection. *PLoS ONE*, 6(9):e24038+, September 2011.