



**HAL**  
open science

## Technical Report: CSVM format for scientific tabular data

Gérôme Beyries, Frédéric Rodriguez

► **To cite this version:**

Gérôme Beyries, Frédéric Rodriguez. Technical Report: CSVM format for scientific tabular data. 2012. hal-00720153v1

**HAL Id: hal-00720153**

**<https://hal.science/hal-00720153v1>**

Preprint submitted on 24 Jul 2012 (v1), last revised 24 Jul 2012 (v2)

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Technical Report: CSV format for scientific tabular data

CSV specification v.1.0 (CSV-1): concept and design, guidelines for the implementation of APIs (Perl, Python).

Gérôme Beyries<sup>a,b,c</sup>, Frédéric Rodriguez<sup>a,b,\*</sup>

<sup>a</sup> CNRS, Laboratoire de Synthèse et Physico-Chimie de Molécules d'Intérêt Biologique, LSPCMIB, UMR-5068, 118 Route de Narbonne, F-31062 Toulouse Cedex 9, France.

<sup>b</sup> Université de Toulouse, UPS, Laboratoire de Synthèse et Physico-Chimie de Molécules d'Intérêt Biologique, LSPCMIB, 118 route de Narbonne, F-31062 Toulouse Cedex 9, France.

<sup>c</sup> Work completed at locations<sup>a,b</sup>.

## Abstract

The CSV (CSV with metadata data) is issued from CSV format and used for storing experimental data, models, specifications. CSV allows the storage of tabular data with a limited but extensible amount of metadata. This increases the exchange and long term use of RAW data because all information needed to use subsequently the data are included in the CSV file. Basic CSV files are readable by current tools (i.e. spreadsheets) for handling tables. Using full possibilities of concept, it is possible to deviate from a strict table and annotate also inside the data block. CSV file are pure ASCII files and could provide a template for implementing best practices in handling raw data at a laboratory level, in exchange between data sources, in long term resources, or in collaborative processes particularly when different scientific fields are implied. In this document we describe the first (CSV-1) release of CSV format.

## Keywords

Open format; CSV; CSV; Tabular data; Perl; Python; Specification; RAW data; Data exchange; Open Data.

## Status

This document is a recommendation for a file format and some guidelines for the design of corresponding APIs. The design principles and concepts defined in this document are non-normative. This format if fully documented and publicly available, it can be used as an Open format.

---

\* *Corresponding authors.*

CNRS, Laboratoire de Synthèse et Physico-Chimie de Molécules d'Intérêt Biologique, LSPCMIB, UMR-5068, 118 Route de Narbonne, F-31062 Toulouse Cedex 9, France.

Tel.: þ33 (0) 5 61556486; fax: þ33 (0) 5 61556011.

E-mail address: *Frederic.Rodriguez@univ-tlse3.fr* (F. Rodriguez).

## 1. W&H of CSVM File format

The CSVM format is derived from CSV, the main goal behind CSVM is to have a simple data format usable in a generic manner, as closest as possible from CSV. Why and How is explained in this section.

### 1.1. CSV file format

CSV (Comma Separated Values) is a de facto industry standard to exchange tabular data from spreadsheets or databases. A CSV file is constituted from a header line (first line, for column identification) and data lines. Each column is separated by a character not used in data, i.e. a TAB or a comma. A example of CSV tabular data (separators not shown) below:

Table 1. - CSV table of vehicles.

---

"ID"	"MODEL"	"TYPE"	"MANUFACTURER"
24	Xsara	VTS	Citroen
#12	Civic	Type R	Honda
38	Clio	RS	Renault
12	Coupé	16VT	Fiat
45	306	S16	Peugeot

Each column is separated by a particular character, i.e. a TAB. To have a more rich content, some conventions must be used in CSV files <sup>1</sup> (using Unicode characters, XML bindings ...).

### 1.2. History of CSVM design

Collaborative scientific projects (PEVS<sup>2</sup>, GIS-ECOBAG P2 : Zone Atelier Adour-Garonne, LTERs<sup>3</sup> ...) in environmental science, for the period 1998-2002, have shown that this kind format was missing. For us, the main issue was not data modeling or RDBMS conception but 1) how we could aggregate raw data in collaborative projects with actors of different scientific fields and 2) how we could ensure a raw data storage on long term without losing information.

We were involved in some working packages and we found that 80% of data was tabular data (one or  $n$  independent tables). To exploit, later, this information (i.e. integrating in RDBMS) we needed to store data in a convenient manner, but in the same time we collected data.

A classical dialog exists between people which make databases (and need data to do a modeling work) and people which collect data (and expect to use database to store data in the same time). But the scope of our work was not Agile database techniques, because we worked on directly on RAW data.

RAW data is an extended ensemble relative to data itself. Data sets (i.e. in a RDBMS) are designed and populated to answer a scientific question. On the contrary, RAW data could contain a lot of information without interest for the current scientific work, but nobody could say if this information will be used later.

So we wanted to get out database paradigms and work directly on RAW data. We design methods and file formats able to produce a view of RAW data in response of a scientific stimulus. This view (table(s) or a collection) should be directly usable to produce or populate RDBMS.

We wanted also to support collective intelligence needed by collaborative projects. These processes involve sharing RAW data of different scientific fields and entities, in the same time. This was the main issue; we expected that if RAW data was correctly annotated and if these annotations were understood by all actors (scientific field vs. scientific field and scientist vs. IT developers) much of the process could be achieved and implemented.

---

<sup>1</sup> For some proposals: <http://www.python.org/dev/peps/pep-0305/> (CSV file API) - <http://www.creativyst.com/Doc/Articles/CSV/CSV01.htm>

<sup>2</sup> Programme Environnement Vie et Sociétés du CNRS (PEVS).

<sup>3</sup> Long Term Ecological Research (LTER).

A solution in our context was to add metadata to data tables. The metadata to be written should be as generic as possible, so we excluded data descriptors related to a scientific field, descriptors should be related to data itself with nearly no modeling of data. The metadata to be written should be also as short as possible, if writers made a big supplementary work to annotate, the aim could not be reached. The ensemble (data + metadata) should be compatible with current tools used by scientists, engineers, or technicians to write data. We placed the metadata block at the bottom of the file after the data block, so the data table could be edited on a spreadsheet, text editor and we retained a CSV (comma separated values) like format. Additional planned features were:

- to embed limited but extensible metadata.
- to be an ASCII format.
- to be the closest as possible from CSV. One user, using the same spreadsheet or text editor, may easily modify CSV data to produce CSV data or use only the CSV part of CSV data.
- to be used for experimental data , but also for data description, specifications ... in other ways store in a same format : the data, the results, the model.
- to be an alternative for tabular data stored in XML files.
- to be loadable by our applications without implementing a specific parser code.
- to be usable for relational databases import/export as an intermediate format.

In the period 2002-2004 the concept was in place, we made the design of format itself and we implemented the first API written in Perl Language. We began also to apply this file format outside environmental sciences (chemistry, enzymology) in order to have a proof of concept with respect of genericity.

In the period 2004-2010 we worked on a Python API and made full applications in scientific fields such as medicinal chemistry, structural bioinformatics.

In the recent period (2010- ) we worked on extension of CSV. Work is carried out to release a new version (CSV-2) which some improvements such as support of recursive and embedded data.

### 1.3. CSV and XML

CSV is not designed to be a substitute of XML or CSV. But if needed, CSV could offer a full XML interface, the idea is to serialize XML file, and code XML tree topology as a particular CSV column. In fact, the result of an XML DOM parser is very near from a serialized XML structure stored in CSV flat file. The binding of CSV vs. XML is out of the scope of this document.

### 1.4. CSV by example

The CSV data of *Table1* is rewritten in CSV and shown below:

*Table 2. - CSV table of vehicles.*

24	Xsara	VTS	Citroen
#12	Civic	Type R	Honda
38	Clio	-	Renault
12	Coupé	16VT	Fiat
45	306	S16	Peugeot

#TITLE	Vehicle data			
#HEADER	ID	MODEL	TYPE	MANUFACTURER
#TYPE	NUMERIC	TEXT	TEXT	TEXT
#WIDTH	50	50	50	50

The header line is removed and a metadata block (blue, red, green text) is appended at the end of data (orange text). The metadata block is signed by keywords and lines beginning by a # character (blue, red text). The column titles of CSV file, are now found in a metadata line beginning by keyword #HEADER. After, the keyword, the order of columns in metadata block, is the same as found in data block, with one cell for the keyword (red, blue text).

## Delimiters, empty cells, empty rows, remarks :

Each cell in data block or metadata block is separated by same delimiters as CSV files, i.e. a TAB or another character. Only the colored cells need to be separated by a given delimiter.

An empty cell is defined, as in a CSV file, by two consecutive delimiters. If any char is found (including a SPACE) the cell is not empty. A good practice is to use a specific character to mark empty cells. In the previous example the character ‘-’ is used to mark an empty cell, then it will be more easy to use a text editor rather than a spreadsheet program.

## A true CSV file

The CSV file accepts empty rows between the data and metadata (purple) blocks, or inside data block (after Clio model). Rows in data block beginning by # are not read by a CSV parser, but could be embedded in the CSV file (red row). Now we show the same CSV data but with a ‘!’ character as delimiter and as it could be written in a real file.

Table 3a. - CSV file of vehicles.

---

```
24!Xsara!VTS!Citroen
#12!Civic!Type R!Honda
38!Clio!-!Renault

12!Coupé!16VT!Fiat
45!306!S16!Peugeot

#TITLE!Vehicle data
#HEADER!ID!MODEL!TYPE!MANUFACTURER
#TYPE!NUMERIC!TEXT!TEXT!TEXT
#WIDTH!50!50!50!50
```

## Annotation of data

The previous file shows that a particular row marked by a # symbol (first character) could be masked to the parser. But it is also possible to use this strategy to add information on a row, given the same example with green rows:

Table 3b. - CSV file of vehicles.

---

```
24!Xsara!VTS!Citroen
#12!Civic!Type R!Honda
38!Clio!-!Renault
# This model is discontinued
# See http://en.wikipedia.org/wiki/Fiat\_Coup%C3%A9 for information
12!Coupé!16VT!Fiat
45!306!S16!Peugeot
```

So CSV admits two levels of annotation: 1) the *metadata block* and 2) *remarks*: insertion of rows marked by # characters in data block. The *metadata* block is compatible with spreadsheets, *remarks* are not. We stop the development of *remarks* at this level, because this could lead to conceive generic descriptors.

## 2. CSVM-1 specifications

Here some specifications describing the flat file format in the first version. The later versions will not change anything on this but will add some #TYPES (links, images), guidelines for inserting ASCII data in fields, inserting binary objects, inserting tables in cells to provide a tree like structure.

### 2.1. Metadata keywords

The #TITLE, #HEADER and #TYPE keywords, must be always integrated in a CSVM file. These keywords are the support of genericity.

Table 4. - Metadata keywords.

---

Keyword	Explanation
#TITLE	The title of the table/sheet
#HEADER	Columns identifiers/titles
#TYPE	Data type of columns
#WIDTH	An indicator of quantity of text typically contained in column.

We have also introduced the #META keyword to add something to the metadata block. This keyword is optional. Parsing CSVM file with our API needs only the four previous keywords and will process #META if this keyword is found in the CSVM file.

### 2.2 The #TITLE keyword

This record is used to store general information about the table and uses one field and one row, typically the title of the table. But the string used as a value for this keyword could be used for anything you want.

If this row is used with a secondary separator to store other column metadata than #HEADER and #TYPE, we recommend to use optional #META keyword rather than #TITLE.

### 2.3 The #HEADER keyword

It is obvious than the #HEADER is the title of a column, as we found in some CSV files with this kind of information. Each #HEADER keyword doesn't need to be surrounded by a delimiter such as simple quote or double quote.

### 2.4. The #TYPE keyword

This keyword is used to give the data types for each column. Giving a CSV file for environmental data:

Table 5. - Working CSV example (some rows are deleted).

---

Diameter	Density	Nature
15	3	Perchis
20	4	Perchis
...	...	...
55	2	Fut
60	1	Fut

In this example, the data of columns Diameter et Density (diameter, density) are number, so numerical data , in the other hand, the column Nature (nature) are textual, in fact character strings, and are tagged as text data. The different data types supported are resumed in the following table:

Table 6. - Values usable with a #TYPE keyword.

---

Sub value	Type
NUMERIC	Numerical data (float or integers).
TEXT	character strings (unlimited length)

DATE	Date, at format DD/MM/YYYY or MM/DD/YYYY
BOOLEAN	Two state data.

### Case of BOOLEAN columns

In the case of BOOLEAN column, the corresponding data in data block must be codes using 0 (false) or 1 (true). But it is possible to code the same values in a TEXT row as 'y' or 'n' or any string.

### Case of NUMERIC columns

The NUMERIC data is used to store numeric values (as text value) but without making a signature on a float or integer values. We expect that after the CSVSM parser as loaded all data, the application could check using the #HEADER value the good numeric format.

If not, alternative exists in CSVSM to use INTEGER or FLOAT values for #TYPE keywords. But, remember that a CSVSM file is loaded by the parser as a string, a matrix of string, a CSVSM object embedding a matrix of string. So for a CSVSM specification, the value used in #TYPE is not related to a specific processing, all must be done by the application. The value which can be affected to #TYPE keyword is only at programmer's charge, but we recommend to use only very generic types (NUMERIC, INT, INTEGER, FLOAT, REAL, TEXT; STRING etc).

So the question how to handle diversity if two programmer's use different #TYPE values ? Why not to store them in a CSVSM file ? This file could be used as a conversion tool. We have defined a specific CSVSM dictionary concept for such purposes. This that we don't need to specify a lot of sub values for #TYPE keyword.

All of these values must be integrated in a cell after #TYPE keyword, in the same order than data columns. In the case of previous example, we get:

*Table 7. - Working CSVSM example (char | used as separator).*

```
15|3|Perchis|
...|...|...|
60|1|Fut|
#TITLE|Foret du boila
#HEADER|Diameter|Density|Nature
#TYPE|NUMERIC|NUMERIC|TEXT
#WIDTH|50|50|100
```

## 2.5. The #WIDTH keyword

This keyword is used in transformations of CSVSM files to other formats usable on web pages, to display tabular data (i.e.: Javascript tables, Javascript lists). In other cases, the entire #WIDTH line can be forgotten or, better, filled with values (0, 10, 50 ..) :

*Table 8. - Unused #WIDTH line(filled with zero values).*

```
#WIDTH|0|0|0
```

The unit (the values) used by #WITH is an arbitrary unit, formerly corresponding to a width of column expressed in pixels. In fact, consider that it is an approximation of the maximum quantity of data (string lengths) contained in column for all lines of the CSVSM table (see example below):

*Table 9. - Using #WITH to control fields/columns widths.*

```
...|...|...
John-Andrews Howard-Smith|1|yes

#TITLE|Who was here table
#HEADER|name|was_here|Oral communication
#TYPE|TEXT|BOOLEAN|BOOLEANYN
#WIDTH|100|10|10
```

If you use the same CSV file with without correct proportions (dummy values or zeros) of #WIDTH, it could be a signal for parser to calculate the accurate values from column contents. But in all cases for using or not #WIDTH, this row must be found in CSV file.

## 2.6 The #META keyword by example

The following table is used to encode a small collection of molecules with specific values of #TYPE (IMAGE, LINK). The table uses TAB separator (red arrows) and the columns where #TYPE=LINK uses a secondary separator (the | char). The left part of this cell is used to store the location of URL and the right part a name of this URL.

Figure 1. – A small collection of chemicals (enzyme inhibitors).

```
inh>glccerase → sketch/mol-22.png → IFM · 5-hydroxymethyl-3,4-dihydroxypiperidine ·
isofagomine · inhibiteur · BglA, · 1OIF → sketch/mol-22.skc|mol-22.skc
inh>glccerase → sketch/mol-23.png → NOJ · 1-deoxynojirimycin · inhibiteur · BglA, · 1OIM →
sketch/mol-23.skc|mol-23.skc
inh>glccerase → sketch/mol-24.png → G2F · 2-deoxy-2-fluoro-glucose · substrat · BglA, · 1OIN ·
Forme · substrat · (libère · dinitrophénol) · présent · sous · forme · d'intermédiaire · réactionnel ·
(F-Glucose:GLU351) → sketch/mol-24.skc|mol-24.skc
inh>glccerase → sketch/mol-25.png → IFL · isofagomine · lactam · inhibiteur · BglA, · 1UZ1 →
sketch/mol-25.skc|mol-25.skc → lig/ifl.pdb|ifl.pdb
inh>glccerase → sketch/mol-26.png → OXZ · tetrahydrooxazine · inhibiteur · BglA, · 1W3J →
sketch/mol-26.skc|mol-26.skc → lig/oxz.pdb|oxz.pdb
inh>glccerase → sketch/mol-27.png → CTS · castanospermine · inhibiteur · BglA, · 2CBU →
sketch/mol-27.skc|mol-27.skc → lig/cts.pdb|cts.pdb
inh>glccerase → sketch/mol-28.png → CGB · calystegine · B2 · inhibiteur · BglA, · 2CBV →
sketch/mol-28.skc|mol-28.skc → lig/cgb.pdb|cgb.pdb
inh>glccerase → sketch/mol-29.png → GIM · glucoimidazole · inhibiteur · BglA, · 2CES →
sketch/mol-29.skc|mol-29.skc → lig/gim.pdb|gim.pdb
inh>glccerase → sketch/mol-30.png → PGI · pyridine-6,7,8-triol · inhibiteur · BglA, · 2CET →
sketch/mol-30.skc|mol-30.skc → lig/pgi.pdb|pgi.pdb

#TITLE → buildez.org · small · molecules
#HEADER → TYPE → SECTOR → IMG → NAME → SKETCH → MOL
#TYPE → TEXT → TEXT → IMAGE → TEXT → LINK → LINK
#WIDTH → 50 → 50 → 50 → 50 → 50 → 50
#META → yes · no · yes · yes · yes · yes
```

This table will be processed in a workflow and displayed as a dynamic Javascript table, showing images of molecules, and reactive hyperlinks:

Figure 2. – JavaScript dynamic table issued from the previous CSV file.

TYPE	IMG	NAME	SKETCH	MOL
inh		IFM 5-hydroxymethyl-3,4-dihydroxypiperidine isofagomine inhibiteur BglA, 1OIF	<a href="#">mol-22.skc</a>	<a href="#">ifm.pdb</a>
inh		NOJ 1-deoxynojirimycin inhibiteur BglA, 1OIM	<a href="#">mol-23.skc</a>	<a href="#">noj.pdb</a>
inh		G2F 2-deoxy-2-fluoro-glucose substrat BglA, 1OIN Forme substrat (libère dinitrophénol) présent sous forme d'intermédiaire réactionnel (F-Glucose:GLU351)	<a href="#">mol-24.skc</a>	<a href="#">g2f.pdb</a>

Please remark that in this output the column in which #HEADER=SECTOR has disappeared. This particular behavior is coded in #META field of CSV: 'yes' string is used if column must be displayed and 'no' if not. A SPACE is used as secondary field separator.

This is an example of #META use, this keyword is very often used for storing external reference of data table (i.e. URL, bibliographic references etc).



## 2.7. CSV Guidelines

Please read carefully information related to CSV format (i.e.: the two links given in first section), CSV guidelines are simplest that CSV.

### Classical delimiters

Classically, the characters used as CSV delimiters are (in brackets) [, ; : SPACE TAB | !]. Please, take in account that some of these characters can be found in data. So it is better to use delimiter not found in data: as TABs, or rare characters as § (also ALT-245 on PC/Windows). We prefer to avoid some characters found in OS syntax as /\| or characters such as < >.

### Composite text delimiters

The DOUBLE COTE or SIMPLE COTE characters (" or ') are often used to delimit text data including characters usable also as delimiters (COMMA, SPACES, POINTS ..). The following table gives some examples:

Table 10. - Using composite text delimiters in CSV files.

Data	Delimiter	Number of columns
"Bonjour, dit'il", c'est pour aujourd'hui ou demain ?	,	2
Bonjour, dit'il, c'est pour aujourd'hui ou demain ?	,	3
Bonjour, dit'il, c'est pour aujourd'hui ou demain ?	'	4
"Bonjour, dit'il" c'est pour aujourd'hui ou demain ?	'	4

Take in account, as shown here, that the corresponding number of columns can be slightly different from one case to other. In order to specify the simplest rules as possible, the CSV specification don't make use of composite text delimiters ' and ". You must use an adequate column delimiter to keep composite data in each column. A way is to use TABs or '§' character, as shown below:

Table 11. - CSV's approach.

Data	Delimiter	Number of columns
Bonjour, dit'il§c'est pour aujourd'hui ou demain ?	§	2

### Exporting CSV from a spreadsheet

After data and metadata integration, you need to export CSV. This is the same as exporting Text CSV data. If the spreadsheet uses more than one sheet, you cannot export the sheets in the same CSV file, but each sheet in a separate CSV file.

- Classical 'save as' command.
- On file requester widget, select the CSV format..
- Perhaps you have fields to complete (depending on software):
- Character set must be Occidental Europa.
- Field separator must be TAB or § character if you can feed this field.
- Do not use text separator as " « ' or another character.

Successfully CSV export has been done from Open Office and Microsoft software.


### Changing delimiters in CSV/CSV files

Use a text editor or a word processor and use the Find/Replace tool, CSV API must provide functions to do this kind of task.

### 3. Using CSVM with Perl language

The following scheme explains in 3 main layers, how we could use CSVM data. The bottom layer is the CSVM file itself, the CSVM API is used to read the file and convert data in a CSVM object including a data matrix (or a data matrix directly). Then the upper layer (at application level) uses the CSVM object.

Figure 3. - CSVM model.



In Perl language, the CSVM data structure, used as a `$csvm_ptr` object is defined in `build::csvm` package and is constituted of the following fields:

Figure 3. – Perl CSVM structure.

Field	Type	Init	Information
SOURCE	String	= undef;	CSV/CSVM file name
CSV	String	= undef;	CSV or CSVM (CSV filetype)
HEADER_N	Integer	= 0;	Value of c+1
HEADER	Array [0..c] of String	= [];	CSVM #HEADER fields list
TITLE_N	Integer	= 0;	Typically 1, let for future use
TITLE	String	= undef;	CSVM title
TYPE_N	Integer	= 0;	Value of c+1
TYPE	Array [0..c] of String	= [];	CSVM #TYPE fields list
WIDTH_N	Integer	= 0;	Value of c+1
WIDTH	Array [0..c] of String	= [];	CSVM #WIDTH fields list
DATA_R	Integer	= 0;	r+1, number of CSVM data rows
DATA_C	Integer	= 0;	c+1, number of CSVM data columns
DATA	Matrix [0..r][0..c] of String	= [];	CSVM data matrix
META	String	= undef;	CSVM #META field string

Here is a short explanation on how it is possible to parse a CSVM file, first of all you need to import the `build::csvm` Perl package :

```
use build::csvm;
```

After you need to define a `csvm` object, implemented as a pointer to a CSVM structure :

```
my $in_ptr = &csvm_ptr_new; ## pointer to csvm structure
```

At least you can parse a CSVM file in a CSVM structure, the string `$in_file_path.$in_file_name` is the path and name of CSVM file appended:

```
$in_ptr->csvm_ptr_read_csvm($in_file_path,$in_file_name);
```

If field delimiters are not TABs, you can use the method `csvm_ptr_read_extended_csvm` to load file with field (`$sep` value) specification:

```
$csvm_ptr->csvm_ptr_read_extended_csvm($fsep);
```

You can also load a file in a string (`$s`) transform the string and import the string in CSVM structure knowing line separator (`$lsep`) and field separator (`$fsep`) using the method `csvm_ptr_get_csvm`.

```
$csvm_ptr->csvm_ptr_get_csvm($s, $lsep , $fsep);
```

You can now apply some methods or access and transform each field of structure:

```
$in_ptr->csvm_ptr_dump(0,0); # echoes structure
$in_ptr->{'TITLE'} = "Modified title."; # change field title
print "[".$self->{'DATA'}->[$i][$j]."]"."\\n";
```

In order to clean memory after all operations, we recommend the following sequence :

```
$in_ptr->csvm_ptr_clear;
undef $in_ptr;
```

It is possible to access to CSVM data without using a CSVM object, a subroutine is provided in `build::csvm` which returns a string matrix from CSVM file (the file contents are stored in a string `$s`):

```
my @matrix = &csvm_matrix_data($s, $lsep , $fsep , $fields_n);
```

In which `$lsep` and `$fsep` are the row and fields separators. Note that no analysis of CSVM string is done before parsing data in CSVM structure. In this case you need to provide the number of columns wanted in the resulting matrix (must see `build::csvm` & `csvm_matrix_data` for more information).

*Today (2012 first edition of this document) the CSVM Perl API (created 2002-2004) and restricted in a core of basic functionality common to Python API.*

## 4. Using CSVm with Python language

The following lines are part of definition of `csvm_ptr` object defined in `build.parsers.csvm` package, with nearly the same fields found in Perl version :

Figure 4. –Python CSVm object.

```
class csvm_ptr:
    """
    Follows CSVm specs (v:1.x) for contents of data structure. Standard column
    types are NUMERIC,TEXT,DATE,BOOLEAN. Some of us, use also INTEGER, FLOAT
    for numeric types. Some of us, use also NODE, LINK, IMAGE for web data
    embedded in CSVm files. WIDTHs (10,50 if not set) are for Javascript tables
    and can be omitted.
    *** 1.01/080304/fred
    """
    def __init__(self):
        self.SOURCE = ""           # path/file name of readed CSVm file
        self.CSV = ""             # CSVm or CSV depending of file contents
        self.TITLE_N = 0          #Titles of CSVm file (let for future, only one string used today)
        self.TITLE = ""           # Title of CSVm file
        self.HEADER_N = 0         # Number of data columns titles
        self.HEADER = []          # List of data column titles
        self.TYPE_N = 0           # Number of data columns types (= self.HEADER_N)
        self.TYPE = []            # List of data column types
        self.WIDTH_N = 0          # Number of data columns widths (= self.HEADER_N)
        self.WIDTH = []           # List of data column widths
        self.DATA_R = 0           # Number of data rows
        self.DATA_C = 0           # Number of data columns (= self.HEADER_N)
        self.DATA = []            # String matrix containing data
        self.META = ""            # Meta string
```

### 4.1 Using the CSVm API

The description of CSVm APIs is out of scope of this document but it could be useful to provide an example to understand how a CSVm file could be used. Given the following pieces of code in Python, first we use a blank CSVm object :

```
print """ A new blank CSVm structure"""
c = csvm_ptr()
print """ Print the empty structure ... """
c.csvm_ptr_dump(0,0)
print "=> Is the empty structure is a CSVm object = ", csvm_iscsvm(c)
print "=> Is self.DATA matrix is a CSVm object = ", csvm_iscsvm(c.DATA)
```

Which gives :

```
*** A new blank CSVm structure
*** Print the empty structure ...

DUMP: CSVm info {
SOURCE
CSV
META      []
TITLE_N 0
TITLE
HEADER_N      0
TYPE_N 0
WIDTH_N 0
DATA_R 0
DATA_C 0
        -1      -1
}
done

=> Is the empty structure is a CSVm object = True
=> Is self.DATA matrix is a CSVm object = False
```

Now we will to load a CSV file, dumps it, dump a row :

```
print """ Read test.csvm and fills the structure ... """
c = csvm_ptr_read_extended_csvm(c,"test/test1.csvm","\t")
print """ Dump all ... """
c.csvm_ptr_dump(0,0)
print
print """ Print as string the second row (numbered as 1 in CSVm) ... """
s = c.csvm_ptr_str_dump(2,0)
print s
```

The dump methods, printouts all metadata, for all the rows :

```
*** Read test.csvm and fills the structure ...
*** Dump all ...

DUMP: CSVm info {
SOURCE test/test1.csvm
CSV CSVm
META [Test of|meta|fields|use]
TITLE_N 1
TITLE CSV File [ test\test.csv ]
HEADER_N 15
TYPE_N 15
WIDTH_N 15
0 50 NUMERIC {numero}
1 50 TEXT {fichier_mol}
2 50 TEXT {nom}
3 50 NUMERIC {vrac}
4 50 TEXT {plaque}
5 50 TEXT {chimiste}
6 50 TEXT {observations}
7 50 TEXT {ref_produit}
8 50 TEXT {ref_cahier}
9 50 TEXT {code_labo}
10 50 TEXT {no_equipe}
11 50 TEXT {no_boite}
12 50 TEXT {droits}
13 50 TEXT {let_ligne_boite}
14 50 TEXT {no_col_boite}
DATA_R 6
DATA_C 15
6 15
0 [1][af01.mol][Tyrosine][10][oui][M.Dupont][existe sous forme de sel de
sodium][af01][C1][CCC][1][1][L][A][1]
1 [5][af02.mol][Histidine][20][oui][J.Smith][][af02][C1][CCC][1][1][L][B][1]
2 [2][af03.mol][Tryptophane][20][oui][nous][][af03][C1][CCC][1][1][L][C][1]
3 [3][af04.mol][Proline][12][non][eux][][af04][C2][][][][][][]
4 [4][af05.mol][Adenosine][0][oui][elle@ici][Plus de produit
disponible][af05][C1][CCC][1][1][L][F][3]
5 [6][af06.mol][Phosphatidyl Choline][300][non][lui@labas][Purifié a partir de jaune
d'oeuf][af06][D2][][][][][][]
}
done
```

Or one particular row :

```
*** Print as string the second row (numbered as 1 in CSVm) ...
```

```
DUMP: CSVm info {SOURCE test/test1.csvm
CSV CSVm
META [Test of|meta|fields|use]
TITLE_N 1
TITLE CSV File [ test\test.csv ]
HEADER_N 15
TYPE_N 15
WIDTH_N 15
0 50 NUMERIC {numero}
1 50 TEXT {fichier_mol}
2 50 TEXT {nom}
3 50 NUMERIC {vrac}
4 50 TEXT {plaque}
5 50 TEXT {chimiste}
6 50 TEXT {observations}
7 50 TEXT {ref_produit}
8 50 TEXT {ref_cahier}
```





## 5. The CSVM parser

We have defined fuzzy data types such as TEXT or NUMERIC as a signal to users and code designers, because from our point of view, CSVM format (particularly #TYPE row) must not be constrained by a data type interpretation and a normative list of allowed types.

Reading the previous examples, it is obvious that the CSVM parser doesn't interpret the data using #TYPE keyword: all is parsed as strings (scalar, lists and matrix) in memory. The parser is uncoupled from data, this gives the ability to use any kind of data type in the CSVM file, and let the application layer interpret the information depending on the metadata stored in the CSVM file.

Remember that a CSVM file (A) with very particular types can be documented by another CSVM file (B), in example for the B-file:

```
CONCENTRATION    Mol/L    NUMERIC    FLOAT
MOL_CONC         MOL/L    NUMERIC    FLOAT
MASSIC_CONC      G/L      NUMERIC    FLOAT
MOLECULE_ID      -        NUMERIC    INTEGER
NAME             -        TEXT       STRING
FORMULA          -        TEXT       SMILES
FORMIMG          -        IMAGE      URL_SMALL|URL_IMAGE

#TITLE    Small types table
#HEADER  NAME UNIT CSVM_TYPE REAL TYPE
#TYPE    TEXT TEXT TEXT TEXT
#WIDTH  10  10  10  10
#META    Version 1.1 (Jule 12 2011) by [John]
```

In this file, we store the #HEADER values of file A, eventually the units, and a real type to be used by application. If some coworkers had used the same information in CSVM files, but with different names (i.e. CONCENTRATION vs. MOL\_CONC) or different units (MASSIC\_CONC vs. MOL\_CONC) the data of B-File could be used to restore initial information or normalize data.

Some less obvious types can be defined (i.e. a molecular formula expressed with SMILES<sup>4</sup> format). Composite format can also be define, in the last row an image is defined by an URL for the reduced picture and another for the full picture.

With the same parser and the same format we can read the two CSVM files, the one(s) with data and the one with information on the previous. This kind of approach can be used also to define conversion of metadata/data (typically units, names, types ...) between CSVM files. For such purposes we have defined a first extension of CSVM files (readable with the same parser) and called it CSVM dictionaries.

## 6. Open Format

Due to metadata block added to CSV block, CSVM is not RFC4180<sup>5</sup> compliant.

CSVM is as an Open Format following the definition proposed by the Linux Information Project <sup>6</sup> (any format that is published for anyone to read and study but which MAY OR MAY NOT BE encumbered by patents, copyrights or other restrictions on use). We expect that CSVM could be a Free Format (IS NOT encumbered by any copyrights, patents, trademarks or other restrictions) after a running time.

---

<sup>4</sup> Chemical File Format [Wikipedia] - [http://en.wikipedia.org/wiki/Chemical\\_file\\_format](http://en.wikipedia.org/wiki/Chemical_file_format)

<sup>5</sup> Y. Shafranovich (2005), Common Format and MIME Type for Comma-Separated Values (CSV) Files, RFC 4180, The Internet Society - <http://tools.ietf.org/html/rfc4180>

<sup>6</sup> Open Format [Wikipedia] - [http://en.wikipedia.org/wiki/Open\\_format](http://en.wikipedia.org/wiki/Open_format)



## 7. Conclusion and perspectives

At this date, different fields of science (environmental sciences, chemistry, enzyme kinetics, structural bioinformatics, rational drug design) were sampled, and computer scientists have used CSV files for a range of current tasks needed by laboratory's activities:

- Pure tabular data;
- Indexes, collection of files;
- External parameters files for software components (wrappers, converters, filters ...);
- Aggregation of tables;
- Conversion of table data (dictionaries);
- Mixed file for data, parameters, results (short times series);
- Driver for software pipes (linear, parallel);
- Phenomenological Model's or EDO systems specification and storage;
- Key / value(s) files and dictionaries
- Database schema and tables
- Trees

We expect that this list is not exhaustive, because the typical range of CSV files is from 1-1000, 5000 rows and 1-20, 30 columns, about the same range than a current spreadsheet file.

But not the same use, CSV is useful to store data in long term and to be included in software pipes, particularly with automation written in Python.

CSV is not a substitute for formats in use to handle mass data (HF5, NetCDF ...) with ASCII or binary storage. CSV is not also a substitute of XML, because it is focused on tabular data, and a same generic parser could be used for all kind of data and data types. CSV is a light format designed to handle complexity of small data islands handled everyday at laboratory<sup>7</sup>.

CSV was mainly used in Microsoft environments, but conceived to be independent of Operating System, so a validation phase targeting Unix/Linux systems is planned. Other topics are treated like extending conversion with other tabular formats and spreadsheets.

But the main effort is focused on extension of CSV leading to CSV-2 specification. We want take in account a lot of requirements not easy fulfilled by other light data formats, particularly: 1) to embed ASCII or binary data in the same ASCII table, 2) to embed CSV data inside a CSV cell and make rooted trees of mixed CSV tables and single CSV cells.

## References

- G. Beyries. Composants logiciels génériques pour les collections de données. Mémoire ingénieur Ecole des Techniques du Génie Logiciel (2004).
- G. Beyries, F. Rodriguez. Quels outils informatiques pour les collections de données ? Restitution Programme ECOBAG P1, Agen (2004).
- Software design and components for enzymology, S.Gavalda, F.Rodriguez, G.Beyries, C.Blonski. 21<sup>ème</sup> CBSO, Ax-Les-Thermes (2006).
- M. Gerino et coll. Bilan et dynamique de la matière organique et des contaminants au sein d'une discontinuité ex de la retenue de Malause. Restitution des travaux scientifiques du projet de recherche Ecobag P2 (2006).
- S. Gau, F. Rodriguez, C. Lherbet, C. Menendez, M. Baltas. Approches interdisciplinaires pour la conception rationnelle d'inhibiteurs. RECOB 13, Aussois (2010).

---

<sup>7</sup> Additional Supporting Information may be found at <http://buildblog.buildez.net/>

## Acknowledgments

We are grateful to Professor Pierre Tisnes (LSPCMIB, UMR 5068 CNRS-Toulouse University) and Dr. Philippe Vervier (CNRS-Toulouse University and GIS ECOBAG) for supporting this first phase of work.

We thank Pr. Magali Gerino (ECOLAB, UMR 5245 CNRS-Toulouse University) and collaborators for advices and helpful discussions about this work.

We would like to thank the CNRS, the “Université Paul Sabatier” and GIS ECOBAG (2002-2004) for their financial support.

We thank all collaborators in different laboratories which shared data with us and helped us to develop the format's usage