

Flow-induced pruning of branched systems and brittle reconfiguration

Diego Lopez, Sébastien Michelin, Emmanuel de Langre

▶ To cite this version:

Diego Lopez, Sébastien Michelin, Emmanuel de Langre. Flow-induced pruning of branched systems and brittle reconfiguration. Journal of Theoretical Biology, 2011, 284 (1), pp.117. 10.1016/j.jtbi.2011.06.027 . hal-00720860

HAL Id: hal-00720860 https://hal.science/hal-00720860

Submitted on 26 Jul 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Author's Accepted Manuscript

Flow-induced pruning of branched systems and brittle reconfiguration

Diego Lopez, Sébastien Michelin, Emmanuel de Langre

PII:	\$0022-5193(11)00332-8
DOI:	doi:10.1016/j.jtbi.2011.06.027
Reference:	YJTBI 6529

To appear in: Journal of Theoretical Biology

Received date:29 March 2011Revised date:7 June 2011Accepted date:22 June 2011



www.elsevier.com/locate/yjtbi

Cite this article as: Diego Lopez, Sébastien Michelin and Emmanuel de Langre, Flowinduced pruning of branched systems and brittle reconfiguration, *Journal of Theoretical Biology*, doi:10.1016/j.jtbi.2011.06.027

This is a PDF file of an unedited manuscript that has been accepted for publication. As a service to our customers we are providing this early version of the manuscript. The manuscript will undergo copyediting, typesetting, and review of the resulting galley proof before it is published in its final citable form. Please note that during the production process errors may be discovered which could affect the content, and all legal disclaimers that apply to the journal pertain.

Flow-induced pruning of branched systems and brittle reconfiguration

Diego Lopez^a, Sébastien Michelin^a, Emmanuel de Langre^{a,*}

^aDepartment of Mechanics, LadHyX Ecole Polytechnique-CNRS 91128 Palaiseau, France

Abstract

Whereas most plants are flexible structures that undergo large deformations under flow, another process can occur when the plant is broken by heavy fluidloading. We investigate here the mechanism of such possible breakage, focusing on the flow-induced pruning that can be observed in plants or aquatic vegetation when parts of the structure break under flow. By computation on an actual tree geometry, a 20-yr-old walnut tree (*Juglans Regia L.*) and comparison with simple models, we analyze the influence of geometrical and physical parameters on the occurrence of branch breakage and on the successive breaking events occurring in a tree-like structure when the flow velocity is increased. We show that both the branching pattern and the slenderness exponent, defining the branch taper, play a major role in the breakage scenario. We identify a criterion for branch breakage to occur before breakage of the trunk. In that case, we show that the successive breakage of peripheral branches allows the plant to sustain higher flow forces.

*Corresponding author

Email addresses: lopez@ladhyx.polytechnique.fr (Diego Lopez), sebastien.michelin@ladhyx.polytechnique.fr (Sébastien Michelin), delangre@ladhyx.polytechnique.fr (Emmanuel de Langre)

Preprint submitted to Journal of Theoretical Biology

June 27, 2011

This mechanism is therefore similar to elastic reconfiguration, and can be seen as a second strategy to overcome critical events, possibly a widespread solution in plants and benthic organisms.

Keywords: Wind-loading, Allometry, Tree-like structure, Bending stress, Branch breakage

1 1. Introduction

2 Most living systems are surrounded by a fluid, be it air or water. When this 3 fluid flows, it generates mechanical forces, that may have major consequences on 4 growth as well as on reproduction or survival [1, 2, 3]. Typical cases are trees 5 subjected to wind or corals subjected to water currents. In terms of flow-induced deformations, two typical behaviors can be pointed out. In the most common one, 6 7 the solid undergoes large elastic deformations, for instance in crops or aquatic 8 vegetation. In the second type, the system breaks before any significant deforma-9 tion can occur; this will be referred to as brittle behavior in the following. The 10 former has been abundantly studied, a key result being that of load reduction by elastic reconfiguration [4, 5]. The latter has already been described in trees or 11 12 corals [6, 7], but to the best of our knowledge the effect of branching has never 13 been studied theoretically. Therefore, we shall focus hereafter on brittle branched 14 slender systems, which are ubiquitous in nature: trees [8], bushes, algae [6], corals 15 [9] and corallines [10], to list a few. In the following we refer mainly to trees un-16 der wind loading, with the understanding that these results are also applicable to 17 a large variety of other biological systems under fluid-loading.

For a brittle branched system attached to a support, breakage under flow may occur in three distinct types: (i) base breakage, Fig. 1a, when the attachment to

the ground is broken, as in uprooting, (ii) trunk breakage, Fig. 1b, when the main
element is broken, and (iii) branch breakage, Fig. 1c, when an upper element
breaks, as in flow-induced pruning.

[Figure 1 about here.]

23

24 In fact, the distinction between trunk and branch breakage has a biological 25 relevance, since breakage of the trunk is likely to be fatal, while re-growth is often 26 possible after branch breakage. Moreover branch breakage does reduce loads 27 on the trunk and the attachment, as in elastic reconfiguration, thereby delaying 28 their breakage [6, 11]. Finally, branch breakage can also be part of the asexual 29 reproduction process by propagation. This is observed in terrestrial plants such 30 as willows and poplars [12], and in stony corals such as Acropora Cervicornis or 31 Acropora Palmata [13, 14].

32 Breakage is the consequence of an unacceptable stress level; it is therefore 33 directly related to the stress state in the structure [11, 15]. In particular, the issue 34 of whether the stress level is uniform or not in the tree is crucial, as breakage is 35 expected to occur at the point of maximal stress. For instance, Niklas and Spatz 36 [11] showed that in a cherry tree the stress level varies by one to two orders of 37 magnitude within the tree and has a local maximum in the branches. On the other 38 hand, Bejan et al. showed that the flow-induced stress is uniform for a tapered 39 trunk when the taper is linear [16]. In fact the stem taper is an important parameter 40 regarding the stress distribution; see the discussion in [17].

41 Several questions remain however regarding the flow-induced breakage of 42 tree-like structures: (i) what are the effects of the geometrical and physical pa-43 rameters on the occurrence of branch breakage? (ii) How do the breaking events

occur successively as the flow is increased? (iii) Assuming that branch break-44 45 age is favorable in biological terms, is it compatible with other constraints on the 46 geometry? The aim of this paper is to address these questions, using simple nu-47 merical and analytical models for the mechanical behavior of slender and brittle 48 structures. The modeling assumptions and framework used throughout the paper 49 are first presented in Section 2. In Section 3, we compute the stress distribution and successive breaking events in a complex tree, using the geometry of an ac-50 51 tual walnut tree. Using an idealized branched system, we derive conditions for 52 branch breakage in Section 4. These are further analyzed for a tapered beam, here 53 referred to as the slender cone model, in Section 5. The corresponding three ge-54 ometries are sketched in Fig. 2. Finally a general discussion and conclusion are 55 given in Section 6.

[Figure 2 about here.]

57 2. Mechanical model and parameters

56

Throughout the paper, we consider a cross flow over the entire structure, uniform, as the dependence of the stress on the wind velocity profile was shown to be small [11]. Also, only static loads are taken into account, and the corresponding fluid force magnitude f per unit length reads

$$f = \frac{1}{2}\rho C_D D U^2,\tag{1}$$

58 where *U* is the free stream velocity, ρ its density, *D* the local branch diameter and 59 C_D the drag coefficient [3, 18]. The direction is assumed to be that of the flow 60 velocity. The fluid load is here computed on a leafless branch, and the influence 61 of leaves will be discussed in Section 6.

This load is applied on the whole branched system, which is held by a perfect clamping at the base. Because of the high slenderness of the system, we use a standard linear beam theory to derive the stress state, essentially the bending moment *M*. The maximum stress in the cross-section resulting from this bending moment is the skin stress, defined as $\Sigma = 32M/\pi D^3$ [19, 20].

The brittle behavior is introduced as follows: (i) the deformations are assumed to be negligible, so the stress state is computed on the initial configuration, without elastic reconfiguration, (ii) when increasing the flow velocity U, breakage occurs when and where the local skin stress Σ reaches a critical value, Σ_c . Then, the broken branch is removed, and this results in a new flow-induced stress state. Flow velocity may then be further increased until a new breaking event occurs.

Throughout the paper, the relevant dimensionless number to scale the fluidloading $\rho C_D U^2$ with respect to the critical stress Σ_c is the Cauchy number, defined as

$$C_Y = \frac{\rho C_D U^2}{\Sigma_c} G,$$
 (2)

where *G* is a geometrical factor introduced for comparison purpose and defined such that $\Sigma = \Sigma_c$ at the base of the intact structure when $C_Y = 1$. Note that this Cauchy number is similar in principle but differs from that used in the analysis of flow-induced elastic deformation, namely $C_Y = \rho C_D U^2 / E$ [3, 5]; the critical stress Σ_c simply replaces here the Young modulus *E*.

The non-dimensional stress is defined as $\sigma = \Sigma/\Sigma_c$ and the non-dimensional bending moment as $m = M/M_c$, with $M_c = \Sigma_c \pi D_B^3/32$, D_B being the base diameter [19]. This latter scaling is chosen so that failure occurs at the base of the trunk when m = 1. The non-dimensional vertical coordinate z is defined using H, the height of the structure, as a reference length scale.

83 **3.** Flow-induced pruning of a walnut tree

92

84 The geometry of the branched system is expected to have a large influence 85 on the stress state and thus on the location and timing of breaking events. We 86 therefore first apply the procedure described above using the digitized geometry of 87 an actual 20-yr-old walnut tree (Juglans Regia L.) described in [21] (Fig. 2a). This 88 tree is 7.9 m high, 18 cm in diameter at breast height (dbh), and has a sympodial 89 branching pattern [22] and about eight orders of branching. The stress state under 90 flow is computed using a standard finite element software (CASTEM v. 3M [23]), 91 and is presented in Fig. 3b for four different branching paths.

[Figure 3 about here.]

93 We observe that the stress level is not uniform but shows a maximum located 94 in the branches, which is consistent with the results of Niklas and Spatz [11] which 95 are sketched in Fig. 3a. Note that since σ varies linearly with the fluid-loading C_{γ} , 96 one needs only to focus on the critical situation where $\sigma = 1$ is first reached in 97 the structure. In this tree, the criterion for breakage is satisfied first in a branch 98 and not in the trunk. This corresponds to the mechanism of branch breakage, as 99 defined in Section 1. If the fluid-loading is further increased after removal of the 100 broken parts, successive breaking events are observed, in a flow-induced pruning 101 sequence: Fig. 4a shows three states of the tree at increasing Cauchy number with 102 branches progressively removed as they break off.

During the sequence of breakage, the bending moment at the base of the tree, m_b , evolves significantly with the Cauchy number, Fig. 4b. Up to the first breakage, the moment is proportional to the fluid-loading C_Y (zone I in Fig. 4b). Then, in a small range of load increase (zone II), all large branches are broken at an inter-

107 mediate level, resulting in a significant decrease of the bending moment. Breakage 108 then continues but to a much smaller extent (zone III), while the moment increases 109 almost linearly up to the value $m_{\rm b} = 1$ when the trunk breaks. Note that the benefit 110 of this sequence of breaking events is that the critical value of the base moment $m_{\rm b} = 1$ is reached only at $C_Y \simeq 10$ instead of $C_Y = 1$ if there was no branch break-111 112 age. This corresponds to more than a factor of 3 on the acceptable fluid velocity. 113 For instance, for a critical stress $\Sigma_c = 40$ MPa, which is the order of magnitude of 114 maximum acceptable bending stresses measured in trees [12, 24], the maximum 115 sustainable fluid velocity before trunk breakage is increased from $U \simeq 30 \text{ m.s}^{-1}$ without branch breakage to $U \simeq 100 \text{ m.s}^{-1}$ with branch breakage. 116

To summarize, this set of computations clearly shows that branch breakage can occur prior to trunk breakage, and that the sequence of flow-induced pruning results in a significant reduction in the load applied on the base of the tree, or equivalently, an increase in the sustainable fluid velocity. To further analyze this process, we turn to a simple model in the next section.

123 **4. The ideal tree model**

124 4.1. Infinite branched tree

125

[Figure 5 about here.]

To establish the relation between the parameters of the system and the flowinduced pruning process, we simplify the problem to its essential elements: the branched geometry and the slenderness of branches; we disregard here the effect of branch orientation relative to the flow. Similarly to [25], we consider first

an infinitely iterated sympodial tree made of cylindrical branches (Fig. 5). Two parameters only are needed to describe this ideal tree: (i) the branching ratio λ , giving the reduction of diameter through branching, and (ii) the slenderness exponent β , giving the relationship between length and diameter in branch segments of the tree, so that

$$\lambda = \left(\frac{D_{k+1}}{D_k}\right)^2, \quad \frac{D_{k+1}}{D_k} = \left(\frac{L_{k+1}}{L_k}\right)^{\beta},\tag{3}$$

where D_k and L_k are the diameter and length of a branch segment of order k, see Fig. 5a [25]. Typical values of these parameters are $\lambda < 1$ and $1 < \beta < 2$. Note that the number of branches emerging from a branching point is typically equal to $1/\lambda$ [26].

We use now a scaling argument similar to that of [25] for the dynamics of trees. On the ideal infinitely branched system of Fig. 5a, we can compare the stress level in branch k = 1 (the trunk) and in branch k = 2. The sub-tree labeled II in Fig. 5a is identical to the full tree, I, but for a change in length and diameter scales. All diameters (resp. lengths) in II are reduced by a factor $\lambda^{1/2}$ (resp. $\lambda^{1/2\beta}$). Let Σ_1 be the maximum skin stress in the trunk (k = 1) under a given fluid-loading U, and Σ_2 the maximum skin stress in the branch k = 2. The relations between the flow velocity and Σ_1 or Σ_2 are identical, but for the change of diameter and length scales. The dependence of the stress on diameter and length is the following: (i) Σ varies as M/D^3 , where M is the bending moment, (ii) M varies as fL^2 , where f is the norm of the local fluid force, Eq. (1), (iii) f varies as $\rho U^2 D$. Hence Σ varies as $\rho U^2 (L/D)^2$. We therefore may state that

$$\frac{\Sigma_2}{\Sigma_1} = \left(\frac{L_2}{D_2}\right)^2 \left(\frac{D_1}{L_1}\right)^2 = \lambda^{\frac{1-\beta}{\beta}}.$$
(4)

Since $\lambda < 1$, the condition for the stress to be higher in branches than in the trunk becomes

$$\beta > 1. \tag{5}$$

Here the only parameter controlling the possibility of branch breakage is the slenderness exponent, a classical parameter in the allometry of trees. As β is typically greater than 1 for trees, branch breakage is expected to occur. This simplistic approach now deserves to be improved, as the assumption of an infinite number of branching levels is very strong, and may not be compatible with the constraint that the tree area has to be finite.

136 4.2. Finite branched tree

Let us consider now the same idealized tree, but with a finite number of branching iterations (Fig. 5b). This structure has N levels, which are labeled in this section from the top to the bottom. Note that n = N - k + 1, where n is the label of the previous section from the base of the tree. The trunk corresponds now to the last level, N. At each level n, we define the branch diameter D_n and length L_n , which can be expressed as a function of the trunk diameter and length D_N and L_N as

$$D_n = \lambda^{\frac{N-n}{2}} D_N, \quad L_n = \lambda^{\frac{N-n}{2\beta}} L_N.$$
(6)

By a simple integration of the fluid force on the branches, the moment at the base of a branch of order n may be derived, as well as the corresponding skin stress, which is obtained in non-dimensional form as

$$\sigma_n = C_Y \lambda^{\frac{1-\beta}{\beta}N} \left(A \lambda^{\frac{\beta-1}{\beta}n} + B \lambda^{\frac{n}{2}} + C \lambda^{\frac{\beta-1}{2\beta}n} \right), \tag{7}$$

where the Cauchy number C_Y is defined as

$$C_Y = \left[\frac{8}{\pi} \left(\frac{L_N}{D_N}\right)^2\right] \frac{\rho C_D U^2}{\Sigma_c},\tag{8}$$

and *A*, *B* and *C* are functions of β and λ only. The detailed derivation of Eq. (7) as well as the expression of *A*, *B* and *C* can be found in Appendix A.

139 A systematic numerical exploration of the (λ, β) parameter space shows that 140 when $\beta < 1$ the stress always increases from top to bottom. Conversely, for $\beta > 1$, 141 the stress reaches a maximum at branch level n_c and then decreases from top to 142 bottom, provided that $N > n_c$, where n_c depends on λ and β . This dependence is 143 given in Fig. 6. This analysis with a finite tree model gives a criterion consistent 144 with that of the infinite tree model, namely $\beta > 1$. Moreover, the other parameter, 145 λ , is found to affect only the location of possible breakage. This suggests that 146 branching is not a key factor in the occurrence of branch or trunk breakage. In the 147 next section we explore a simpler model of the slenderness effect.

148

[Figure 6 about here.]

149 5. The slender cone model

150 5.1. Flow-induced stress

The simplest model that allows one to take into account a relation between diameters and lengths through a slenderness exponent is a cone. This formulation is related to MacMahon and Kronauer's equivalent geometry of a tree, a tapered beam with a rectangular cross-section of dimensions varying as power laws of height [8, 27].

The geometry considered here is a slender cone with a circular cross-section, Fig. 7a, and we follow the same mechanical approach as for the previous geometries. Let *H* be the cone height, $d_H = D_H/H$ the dimensionless diameter at the base and *z* the vertical coordinate which is orientated downwards in this section. The cone dimensionless diameter is given by

$$d(z) = d_H z^{\beta}. \tag{9}$$

[Figure 7 about here.]

Using the same formulation as in the previous section, the stress state along the cone is obtained as

$$\sigma(z) = C_Y z^{2(1-\beta)},\tag{10}$$

where the Cauchy number is defined here as

$$C_Y = \left[\frac{16}{(1+\beta)(2+\beta)\pi d_H^2}\right] \frac{\rho C_D U^2}{\Sigma_c}.$$
 (11)

From Eq. (10), we readily observe that: (i) for $\beta = 1$, the constant stress case of Bejan et al. [16] is found; (ii) for $\beta < 1$ the stress increases with z and is therefore maximum at the base, Fig. 7a; (iii) for $\beta > 1$ the stress decreases with z, and the maximum, discussed further, is not at the base, Fig. 7b-c. These results are consistent with the condition for branch breakage in the previous section.

To avoid the singular case of infinite stress at z = 0 for $\beta > 1$, we use a cone truncated at $z = z_0$, Fig. 7c. The truncation z_0 corresponds to the first breakage occurring as soon as $U \neq 0$, and its value is chosen arbitrarily. The corresponding stress state is then

$$\frac{\sigma(z)}{C_Y} = z^{2(1-\beta)} - (2+\beta)z_0^{1+\beta}z^{1-3\beta} + (1+\beta)z_0^{2+\beta}z^{-3\beta},$$
(12)

11

156

which reduces to Eq. (10) when $z_0 = 0$. The detailed derivation of this equation is given in Appendix B. For $\beta > 1$, the stress shows a maximum before decreasing downwards, as illustrated in Fig. 7c. The limit case $z_0 = 0$ is in fact equivalent, in the ideal tree model of Section 4, to the limit as N goes towards infinity, which would lead to a vanishing diameter at the tip. There is therefore an analogy between the cone truncation and the ideal tree with a finite number of branching levels.

169 5.2. Sequence of breaking events

170 Considering now the generic case of the truncated cone, Fig. 7c, we analyze 171 the sequence of breaking events resulting from an increasing fluid-loading C_{Y} . 172 The stress σ increases linearly with C_Y up to the point where its maximum value 173 reaches the limit of breakage, $\sigma = 1$. This defines the first breaking event at $C_Y = C_Y^1$ occurring at $z = z_1$. It results in a new truncated cone, and the process is 174 repeated as C_Y is further increased. Eventually, when the cone becomes truncated 175 176 close to the base, the maximum stress may be reached at the base itself, resulting 177 finally in base breakage.

178 This sequence of breaking events may be analyzed in terms of the maximum 179 fluid-loading C_v^{max} that the cone can support before breaking at the base. As illus-180 trated in Fig. 8, this is strongly dependent on β . When $\beta < 1$, the first breaking event is at the base so that $C_{y}^{\text{max}} = 1$. Conversely when $\beta > 1$, breaking occurs 181 progressively as C_Y is increased, and the base breakage is delayed, $C_Y^{\text{max}} > 1$. The 182 183 precise value of C_Y where the base breaks depends on the initial truncation z_0 , but 184 is always higher than a lower bound that can be computed from Eq. (12), which is 185 shown in Fig. 8. We observe a significant increase of the ability of the system to 186 sustain fluid-loading when $\beta > 1$.

[Figure 8 about here.]

188 In terms of base moment, the sequence of breaking events can be easily com-189 puted, Fig. 9. For $\beta < 1$ the base moment increases linearly with C_{γ} until base 190 breakage occurs, $m_b = 1$ for $C_Y = 1$. For $\beta > 1$ the sequence of breaking events 191 results in sudden drops in base moment followed by linear increase up to the next 192 breaking, as illustrated in Fig. 9. Since the sequence of breaking events is a dis-193 crete process that depends on the initial truncation z_0 , there exists, for a given 194 Cauchy number C_Y , a wide range of acceptable cone heights and thereby a wide 195 range of corresponding base moments. In practice, for all possible values of z_0 , 196 the evolution of $m_{\rm b}$ remains bounded between its values for the shortest and high-197 est cone that can exist at each Cauchy number. This is represented by the shaded 198 region in Fig. 9.

199 [Figure 9 about here.]

These results show that the simple cone model contains the key elements to understand the effect of geometry on (i) the stress profile, (ii) the sequence of breaking events and (iii) the consequences on the evolution of base load when the fluid velocity is increased. Here again, the essential criterion concerns the slenderness exponent β .

205 **6. Discussion and conclusions**

187

Starting from the case of a full walnut tree geometry, we have used models of increasing simplicity. This allowed us to point out the role of various parameters on the process of breakage under fluid-loading. The first issue that had to be addressed was that of the flow-induced stress distribution. As noted by other

authors, the stress is not necessarily maximum at the base [11, 16]. In fact in the walnut tree of Section 3, the stress has a local maximum at about mid height. Using the ideal tree model in Section 4, we have shown that the existence of this maximum is related to the value of the slenderness exponent, β , being larger than one: in fact this allometry parameter is about 1.37 for this particular walnut tree [25]. Following Bejan et al. [16], we recover the critical value of $\beta = 1$ in the simplest model, that of a cone in Section 5.

217 Actually, some refinement is needed here to understand the precise location 218 of the maximum of stress. We have shown in Section 4 that the location of this 219 maximum was also dependent on the branching parameter λ , in the form of the 220 parameter n_c , which is the number of branching levels from the top to this maxi-221 mum point. For our walnut tree, where $\lambda \simeq 0.25$, we obtain $n_c = 6$ using Fig. 6. 222 This is smaller than the total number of branching levels in the walnut tree which 223 is about 8 [21]. A local maximum of stress is therefore expected in the branches, 224 and is actually observed in Fig. 3.

225 The second issue was that of the sequence of breaking events occurring when 226 the fluid-loading C_{Y} is increased. Using a brittle fracture model for the walnut tree 227 in Section 3, we have shown that most large branches broke in a short range of 228 flow velocity, and that breakage of the trunk occurred much later. The large size 229 of broken branches can be explained by the value of $n_c = 6$ found above. All large 230 branches do not break exactly at the same value of the Cauchy number. This is 231 due among other reasons to some variability in the allometry parameters λ and β 232 within the tree. Once all large branches are broken, the remaining tree shape, C in 233 Fig. 4a, does not have enough branching levels to have a local maximum, and the 234 next breaking event occurs at the base of the trunk. Note that the process of branch

breakage in the walnut tree allowed the tree to have a much larger acceptable Cauchy number before breakage of the trunk. This can also be analyzed using the cone model as in Section 5, where the critical Cauchy number for base breakage is clearly dependent on β (Fig. 8).

239 The third issue was that of the evolution of the load at the base of the tree. For 240 the walnut tree, Fig. 4b, the sequence of successive breakage of the large branches 241 results in a significant decrease of the drag-induced moment at the base. This can 242 be understood using the cone model, where the sequence of breaking event and 243 corresponding drops of base moment can be tracked, Fig. 9. We may therefore 244 state that the essential characteristics of branch breakage and corresponding load 245 evolution in the walnut tree can be understood using our simple ideal tree model and cone model. 246

247 The analytical results of Sections 4 and 5 were obtained considering that all 248 parameters have self-similar variations. However, this was not the case for the 249 walnut tree computations of Section 3, which suggests that the behaviors pointed 250 out in this study can be generalized to structures that do not necessarily have self-251 similar variations of their parameters. Moreover, the ideal tree and cone models 252 can be easily extended to incorporate other features of the problem, such as a de-253 pendence of all parameters with z: the flow velocity U, the material properties 254 through the critical parameter Σ_c , and even the drag coefficient C_D , which allows 255 one to take easily into account the additional drag of leaves. Preliminary results, 256 not shown here for the sake of brevity, showed that the criterion for branch break-257 age takes the same form, but involves both β and the corresponding parameter 258 related to the additional z-dependence. Taking into account a significant elastic 259 deformation before load fracture, or incorporating dynamical effects, would be

260 much more complex.

261

[Table 1 about here.]

262 Considering the simplicity of the criterion that we have found for branch 263 breakage, we can test whether it is generally satisfied. MacMahon and Kronauer 264 [27] have noted that β is usually larger than 1 and typically around 1.5, while λ 265 is typically close to 0.25. This leads to a maximum stress located at a branching 266 level $n_c = 5$ counting from top down. This is clearly in the branches as trees gen-267 erally have more than 5 orders of branching. We may therefore state that branch 268 breakage can be expected in most sympodial trees. This is illustrated in Table 1, where the values of parameters are given for several trees. 269

270 Clearly the possibility of branch breakage is favorable in terms of survival of 271 an individual tree in the face of extreme fluid-loading. It may also be favorable in 272 terms of tree development by removing the less vigorous branches. The question 273 then arises as to whether this implies new constraints on the geometry of the tree. 274 It appears from our results that the constraint $\beta > 1$ is not incompatible with 275 other constraints such as the optimal resistance to buckling under gravity, which 276 requires $\beta = 3/2$ [8]. The same result was obtained considering the wind effect on 277 trees but for an overcrowded tree canopy [17]. Similarly $\beta > 1$ is compatible with 278 a constraint for optimal dissipation [25, 28], that modal frequencies have a ratio 279 of less than two, requiring that $\beta > 1$ for $\lambda = 0.25$.

280 The particular case of branched corals [9, 13, 14] is somewhat different. The 281 segments are similar in length and diameter, so that $\lambda \approx 1$ and $\beta \approx 1$ in our 282 variables, but with a number of branches emerging from one branching not equal 283 to $1/\lambda$. An analysis similar to that of Section 4 shows that breakage is expected at 284 the bottom. This is the case in most isolated corals.

285 More generally we may place these results in the overall context of reconfig-286 uration, as introduced by Vogel [4]. This originally referred to the reduction of 287 loading made possible by elastic deformation. For a plant, it is a crucial mecha-288 nism to survive heavy fluid-loading. But plant tissues are not all very elastic, and 289 plant parts are not all very flexible. Our results on the role of branch breakage in 290 reducing loading show that, in parallel with elastic reconfiguration, there exists a 291 mechanism of brittle reconfiguration. There are therefore two distinct strategies to 292 overcome critical events. The first is evidently reversible in the short term by elas-293 ticity. The second is also reversible by re-growth, but only in the long term. Thus 294 flow-induced pruning is possibly a widespread mechanism in plants or benthic 295 organisms that support heavy loading by the surrounding fluid environment.

296 Acknowledgements

The authors gratefully acknowledge the help of Chris Bertram, from the University of Sydney, for stimulating discussions and useful corrections on the manuscript. The authors also acknowledge the interesting comments and useful suggestions from the anonymous reviewers. The first author was funded by the PhD scholarship program "AMX" at Ecole Polytechnique.

302 Appendix A. Stress derivation in finite branched tree model

In order to compute the stress along the finite ideal tree, we introduce f_n the fluid force per unit length at level n, $f_n = \frac{1}{2}\rho C_D U^2 D_n$, with the same notations as Eq. (1). At each level n, we consider two force components: (i) the shear force τ_n in the flow direction and (ii) the bending moment M_n in the direction normal to

the flow. Due to the free condition at the top, $\tau_0 = 0$ and $M_0 = 0$, and for $n \ge 1$

$$\tau_n = f_n L_n + p \tau_{n-1}, \tag{A.1}$$

$$M_n = \frac{1}{2} f_n L_n^2 + p \left(M_{n-1} + L_n \tau_{n-1} \right), \qquad (A.2)$$

where *p* is the number of branches emerging from one at a branching point ($p = 1/\lambda$). The non-dimensional stress σ_n at level *n* reads

$$\sigma_n = \frac{32M_n}{\pi\Sigma_c D_n^3} \tag{A.3}$$

By integration of Eqs. (A.1) and (A.2), the stress at each level can be obtained,

$$\sigma_n = C_Y \lambda^{\frac{1-\beta}{\beta}N} \left(A \lambda^{\frac{\beta-1}{\beta}n} + B \lambda^{\frac{n}{2}} + C \lambda^{\frac{\beta-1}{2\beta}n} \right), \tag{A.4}$$

with

$$C_Y = \left[\frac{8}{\pi} \left(\frac{L_N}{D_N}\right)^2\right] \frac{\rho C_D U^2}{\Sigma_c},\tag{A.5}$$

and

$$= \frac{\lambda^{\frac{1-\beta}{2\beta}} + 1}{\left(\lambda^{\frac{1-\beta}{2\beta}} - 1\right)\left(\lambda^{\frac{2-\beta}{2\beta}} - 1\right)},$$
(A.6)

$$B = \frac{\lambda^{\frac{2\beta}{2\beta}} + 1}{\left(\lambda^{\frac{2-\beta}{2\beta}} - 1\right)\left(\lambda^{\frac{1}{2\beta}} - 1\right)},$$
 (A.7)

$$B = \frac{\lambda^{\frac{1}{2\beta}} + 1}{\left(\lambda^{\frac{2-\beta}{2\beta}} - 1\right)\left(\lambda^{\frac{1}{2\beta}} - 1\right)},$$

$$C = \frac{-2}{\left(\lambda^{\frac{1-\beta}{2\beta}} - 1\right)\left(\lambda^{\frac{1}{2\beta}} - 1\right)}.$$
(A.7)
(A.7)

303 Appendix B. Stress derivation in the slender cone model

The stress state for the slender cone model is obtained by direct integration of the fluid force defined in Eq. (1), using Eq. (9) for the diameter. The shear force

and resulting bending moment read

$$\tau(z) = \int_{z_0}^{z} f(z') dz', \quad M(z) = \int_{z_0}^{z} \tau(z') dz', \quad (B.1)$$

with $z_0 \ge 0$. The local non-dimensional skin stress reads

$$\sigma(z) = \frac{32M(z)}{\pi\Sigma_c d(z)^3}.$$
(B.2)

304 The integration of these equations give Eq. (10) and Eq. (12) depending on z_0 .

305 **References**

- 306 [1] B. Moulia, C. Coutand, C. Lenne, Posture control and skeletal mechanical
 307 acclimation in terrestrial plants: implications for mechanical modeling of
 308 plant architecture, Am. J. Bot. 93 (2006) 1477–1489.
- 309 [2] M. A. R. Koehl, W. K. Silk, H. Liang, L. Mahadevan, How kelp produce
 310 blade shapes suited to different flow regimes: A new wrinkle, Integr. Comp.
 311 Biol. 48 (2008) 834 –851.
- 312 [3] E. de Langre, Effects of wind on plants, Annu. Rev. Fluid Mech. 40 (2008)
 313 141–168.
- [4] S. Vogel, Drag and reconfiguration of broad leaves in high winds, J. Exp.
 Bot. 40 (1989) 941 –948.
- 316 [5] F. Gosselin, E. de Langre, B. A. Machado-Almeida, Drag reduction of flex317 ible plates by reconfiguration, J. Fluid Mech. 650 (2010) 319–341.
- [6] M. A. R. Koehl, How do benthic organisms withstand moving water?, Am.
 Zool. 24 (1984) 57 –70.

- [7] K. J. Niklas, H. Spatz, Methods for calculating factors of safety for plant
 stems, J. Exp. Biol. 202 (1999) 3273–3280.
- 322 [8] T. A. McMahon, The mechanical design of trees, Sci. Am. 233 (1975) 93–
 323 102.
- J. S. Madin, Mechanical limitations of reef corals during hydrodynamic disturbances, Coral Reefs 24 (2005) 630–635.
- [10] P. T. Martone, M. W. Denny, To break a coralline: mechanical constraints
 on the size and survival of a wave-swept seaweed, J. Exp. Biol. 211 (2008)
 3433–3441.
- [11] K. J. Niklas, H. C. Spatz, Wind-induced stresses in cherry trees: evidence
 against the hypothesis of constant stress levels, Trees 14 (2000) 0230–0237.
- [12] H. Beismann, H. Wilhelmi, H. Baillères, H. C. Spatz, A. Bogenrieder,
 T. Speck, Brittleness of twig bases in the genus *Salix*: fracture mechanics
 and ecological relevance, J. Exp. Bot. 51 (2000) 617–633.
- [13] V. Tunnicliffe, Breakage and propagation of the stony coral acropora cervicornis, Proc. Natl. Acad. Sci. U.S.A. 78 (1981) 2427 –2431.
- 336 [14] R. C. Highsmith, Reproduction by fragmentation in corals, Mar. Ecol. Prog.
 337 Ser. 7 (1982) 207–226.
- 338 [15] B. A. Gardiner, C. P. Quine, Management of forests to reduce the risk of
 abiotic damage a review with particular reference to the effects of strong
 winds, For. Ecol. Manag. 135 (2000) 261 277.

- 341 [16] A. Bejan, S. Lorente, J. Lee, Unifying constructal theory of tree roots,
 342 canopies and forests, J. Theor. Biol. 254 (2008) 529 540.
- [17] M. Larjavaara, Maintenance cost, toppling risk and size of trees in a selfthinning stand, J. Theor. Biol. 265 (2010) 63 67.
- [18] J. S. Madin, S. R. Connolly, Ecological consequences of major hydrodynamic disturbances on coral reefs, Nature 444 (2006) 477–480.
- K. J. Niklas, Plant biomechanics: an engineering approach to plant form and
 function, University of Chicago Press, Chicago, Illinois, USA, 1992.
- 349 [20] J. M. Gere, S. P. Timoshenko, Mechanics of Materials, PWS-KENT, Boston,
 350 Massachusetts, USA, 1990.
- [21] H. Sinoquet, P. Rivet, C. Godin, Assessment of the three-dimensional architecture of walnut trees using digitizing, Silva Fenn. 31 (1997) 265–273.
- [22] D. Barthelemy, Y. Caraglio, Plant Architecture: A Dynamic, Multilevel and
 Comprehensive Approach to Plant Form, Structure and Ontogeny, Ann. Bot.
 99 (2007) 375–407.
- [23] P. Verpeaux, T. Charras, A. Millard, Castem 2000, une approche moderne du
 calcul des structures, in: J. M. Fouet, P. Ladevèze, R. Ohayon (Eds.), Calcul
 des structures et intelligence artificielle, Pluralis, Paris, France, 1988, pp.
 261–271.
- [24] T. Lundström, T. Jonas, A. Volkwein, Analysing the mechanical performance and growth adaptation of norway spruce using a non-linear finiteelement model and experimental data, J. Exp. Bot. 59 (2008) 2513–2528.

- 363 [25] M. Rodriguez, E. de Langre, B. Moulia, A scaling law for the effects of ar-
- 364 chitecture and allometry on tree vibration modes suggests a biological tuning
- 365 to modal compartmentalization, Am. J. Bot. 95 (2008) 1523–1537.
- 366 [26] A. Lindenmayer, P. Prusinkiewicz, The algorithmic beauty of plants, 367 Springer-Verlag, 1996.
- 368 [27] T. A. McMahon, R. E. Kronauer, Tree structures: Deducing the principle of mechanical design, J. Theor. Biol. 59 (1976) 443-466. 369
- 370 [28] B. Theckes, E. de Langre, X. Boutillon, Modal energy transfer from geomet-
- 371 rical nonlinearities in a tree-like structure, Proceedings of the 7th European
- 372 Nonlinear Dynamics Conference (Accepted) (2011).

373 List of Figures

374	1	Schematic view of breakage process in a branched brittle system	
375		under flow. (a) Base breakage, (b) Trunk breakage, (c) Branch	
376		breakage	25
377	2	Geometries of the models used in the paper: (a) Section 3: Walnut	
378		tree, as in [21]; (b) Section 4: Idealized branched system, as in	
379		[25]; (c) Section 5: Tapered beam, as in [8, 16]	25
380	3	Non-dimensional stress profile σ in a tree under cross-flow. (a)	
381		Schematic view of the stress profiles given by Niklas and Spatz	
382		[11] for cherry trees, showing a local maximum near the top.	
383		(b) Computed stress profiles along four branching paths, A (×),	
384		B (\Box), C (\triangle) and D (\circ) in the digitized tree geometry shown in (c).	26
385	4	Computed sequence of branch breakage in the walnut tree: (a) A:	
386		initial tree for $C_Y \leq 0.67$; B: after breakage in large branches,	
387		$C_Y = 1.7$; C: just before trunk breakage, $C_Y = 10.7$. (b) Corre-	
388		sponding evolution of the bending moment at the base of the tree	
389		$m_{\rm b}$, in three distinct ranges. The dashed line shows the moment	
390		that would exist without breakage. The dotted line shows the crit-	
391		ical value m_b that causes trunk breakage	26
392	5	Idealized branched system. (a) Infinite iterated tree. The sub-	
393		tree II is equivalent to the whole tree I but for a change of scales.	
394		(b) Finite iterated tree and corresponding notations	27

395	6	Location of the maximum of stress under cross-flow in an ideal-	
396		ized tree model, as a function of the slenderness exponent β and	
397		the branching parameter λ . The location is given in the form of	
398		the number of branching levels counted from the top of the tree,	
399		Fig. 5b. For $\beta \leq 1$, the breakage is directly at the base of trunk	27
400	7	The slender cone model: geometry and stress profile under uni-	
401		form cross flow. (a) cone with $\beta < 1$ (here 0.75), showing a max-	
402		imum of stress at the base; (b) cone with $\beta > 1$ (here 2), showing	
403		a maximum at the top; (c) cone truncated arbitrarily at $z_0 = 0.3$	
404		showing a local maximum.	28
405	8	Maximum fluid load that the cone can support as a function of the	
406		slenderness exponent. Note that for $\beta > 1$ the curve is the lower	
407		bound of all possible evolutions.	28
408	9	Moment at the base of the cone as the fluid-loading is increased. (-	
409) direct base breakage occurring when $\beta < 1$; (—) progressive	
410		breaking for $\beta > 1$ (here $\beta = 2$). The shaded region shows all	
411		possible values depending on the initial truncation z_0 . The cone	
412		state is shown for three values of C_Y	29
		-67	

413 List of Tables

414	1	Predicted breakage type using the results of Section 4. Branch	
415		breakage is predicted when $n_c \leq N$	30



Figure 1: Schematic view of breakage process in a branched brittle system under flow. (a) Base breakage, (b) Trunk breakage, (c) Branch breakage.



Figure 2: Geometries of the models used in the paper: (a) Section 3: Walnut tree, as in [21]; (b) Section 4: Idealized branched system, as in [25]; (c) Section 5: Tapered beam, as in [8, 16].





Figure 3: Non-dimensional stress profile σ in a tree under cross-flow. (a) Schematic view of the stress profiles given by Niklas and Spatz [11] for cherry trees, showing a local maximum near the top. (b) Computed stress profiles along four branching paths, A (×), B (\Box), C (Δ) and D (\circ) in the digitized tree geometry shown in (c).



Figure 4: Computed sequence of branch breakage in the walnut tree: (a) A: initial tree for $C_Y \le 0.67$; B: after breakage in large branches, $C_Y = 1.7$; C: just before trunk breakage, $C_Y = 10.7$. (b) Corresponding evolution of the bending moment at the base of the tree m_b , in three distinct ranges. The dashed line shows the moment that would exist without breakage. The dotted line shows the critical value m_b that causes trunk breakage.



Figure 5: Idealized branched system. (a) Infinite iterated tree. The sub-tree II is equivalent to the whole tree I but for a change of scales. (b) Finite iterated tree and corresponding notations.



Figure 6: Location of the maximum of stress under cross-flow in an idealized tree model, as a function of the slenderness exponent β and the branching parameter λ . The location is given in the form of the number of branching levels counted from the top of the tree, Fig. 5b. For $\beta \le 1$, the breakage is directly at the base of trunk.



Figure 7: The slender cone model: geometry and stress profile under uniform cross flow. (a) cone with $\beta < 1$ (here 0.75), showing a maximum of stress at the base; (b) cone with $\beta > 1$ (here 2), showing a maximum at the top; (c) cone truncated arbitrarily at $z_0 = 0.3$ showing a local maximum.



Figure 8: Maximum fluid load that the cone can support as a function of the slenderness exponent. Note that for $\beta > 1$ the curve is the lower bound of all possible evolutions.



Figure 9: Moment at the base of the cone as the fluid-loading is increased. (- -) direct base breakage occurring when $\beta < 1$; (—) progressive breaking for $\beta > 1$ (here $\beta = 2$). The shaded region shows all possible values depending on the initial truncation z_0 . The cone state is shown for three values of C_Y .

Accer

	Ref.	Tree	Slenderness exponent β	Branching parameter λ	Total orders of branching N	Predicted branch breakage level n _c	Predicted breakage type
	[21, 25]	Walnut Tree Juglans Regia L.	1.37	0.25	> 8	6	Branch
	[27]	Red Oak Quercus Rubra	1.51	0.41	> 6	7	Branch or Trunk
		White Oak 1 Quercus Alba	1.41	0.28	> 6	6	Branch
		White Oak 2 Quercus Alba	1.66	0.29	> 6	5	Branch
		Poplar Tree Populus Tremoloides	1.5 (estimated)	0.29	> 6	5	Branch
		Pin Cherry Prunus Pensylvanica	1.5	0.24	> 4	5	Branch or Trunk
		White Pine Pinus Strobus	1.37	0.24	> 5	5	Branch
Table 1 $n_c \leq N$ 425	: Predict	ed breakage typ	e using the	e results of	Section 4. E	Branch breaka	ge is predicted

Table 1: Predicted breakage type using the results of Section 4. Branch breakage is predicted when

- Flow-induced pruning of branched systems may be predicted from of usual allometry parameters
- > Flow-induced pruning is strongly beneficial to a living branched system
- The condition for flow-induced pruning is compatible with other constraints on growth.

Accepted manuscript