

Problem D: Is the Name of This Problem

Source file: `quine.{c, cpp, java}`

Input file: `quine.in`

The philosopher Willard Van Orman Quine (1908–2000) described a novel method of constructing a sentence in order to illustrate the contradictions that can arise from self-reference. This operation takes as input a single phrase and produces a sentence from that phrase. (The author Douglas R. Hofstadter refers to this process as *to Quine a phrase*.) We can define the Quine operation like so:

$$\text{Quine}(A) = "A" A$$

In other words, if A is a phrase, then $\text{Quine}(A)$ is A enclosed in quotes (`"`), followed by a space, followed by A . For example:

$$\text{Quine}(\text{HELLO WORLD}) = \text{"HELLO WORLD" HELLO WORLD}$$

Below are some other examples of sentences that can be created by the Quine operation. Note that Quining allows sentences to be indirectly self-referential, such as the last sentence below.

```
"IS A SENTENCE FRAGMENT" IS A SENTENCE FRAGMENT
"IS THE NAME OF THIS PROBLEM" IS THE NAME OF THIS PROBLEM
"YIELDS FALSEHOOD WHEN QUINED" YIELDS FALSEHOOD WHEN QUINED
```

Your goal for this problem is to take a sentence and decide whether the sentence is the result of a Quine operation.

Input: The input will consist of a sequence of sentences, one sentence per line, ending with a line that has the single word, **END**. Each sentence will contain only uppercase letters, spaces, and quotation marks. Each sentence will contain between 1 and 80 characters and will not have any leading, trailing, or consecutive spaces.

You must decide whether each sentence is the result of a Quine operation. To be a Quine, a sentence must match the following pattern *exactly*:

1. A quotation mark
2. Any nonempty sequence of letters and spaces (call this phrase A)
3. A quotation mark
4. A space
5. Phrase A —exactly as it appeared in (2)

If it matches this pattern, the sentence is a Quine of the phrase A . Note that phrase A must contain the exact same sequence of characters both times it appears.

Output: There will be one line of output for each sentence in the data set. If the sentence is the result of a Quine operation, your output should be of the form, $\text{Quine}(A)$, where A is the phrase to Quine to create the sentence.

If the sentence is not the result of a Quine operation, your output should be the phrase, **not a quine**.

Example input:	Example output:
<pre>"HELLO WORLD" HELLO WORLD "IS A SENTENCE FRAGMENT" IS A SENTENCE FRAGMENT "IS THE NAME OF THIS PROBLEM" IS THE NAME OF THIS PROBLEM "YIELDS FALSEHOOD WHEN QUINED" YIELDS FALSEHOOD WHEN QUINED "HELLO" I SAID WHAT ABOUT "WHAT ABOUT" " NO EXTRA SPACES " NO EXTRA SPACES "NO"QUOTES" NO"QUOTES "" END</pre>	<pre>Quine(HELLO WORLD) Quine(IS A SENTENCE FRAGMENT) Quine(IS THE NAME OF THIS PROBLEM) Quine(YIELDS FALSEHOOD WHEN QUINED) not a quine not a quine not a quine not a quine not a quine</pre>

A review of quotation marks in strings: As a reminder, the quotation mark character is a regular character, and can be referred to in C, C++, and Java using the standard single-quote notation, like so:

```
' ''
```

However, to place a quotation mark inside a double-quoted string in C, C++, and Java, you must place a backslash (\) in front of it. If you do not it will be interpreted as the end of the string, causing syntax errors. For example:

```
"This quotation mark \" is inside the string"
"\" "
"\"SAID SHE\" SAID SHE"
```