



## H • Maximum in the Cycle of 1

If  $P$  is a permutation of the integers  $1, \dots, n$ , the *maximum in the cycle of 1* is the maximum of the values  $P(1)$ ,  $P(P(1))$ ,  $P(P(P(1)))$ , etc. For example, if  $P$  is the permutation:

```
| 1 2 3 4 5 6 7 8 |  
| 3 2 5 4 1 7 8 6 |
```

we have:

$$P(1) = 3$$
$$P(P(1)) = P(3) = 5$$

and

$$P(P(P(1))) = P(5) = 1$$

so the maximum in the cycle of 1 is 5.

For this problem, you will write a program which takes as input integers  $n$ , ( $n > 0$ ) and  $k$  ( $1 \leq k \leq n$ ), and returns the number of permutations of the integers  $1, \dots, n$ , for which the maximum in the cycle of 1 is  $k$ .

### Input

The first line of input contains a single integer  $P$ , ( $1 \leq P \leq 1000$ ), which is the number of data sets that follow. Each data set is a single line that contains the three space separated decimal integer values. The first value is the data set number,  $N$ . The second value is the size of the permutation,  $n$  where ( $1 \leq n \leq 20$ ), and the third value is the desired maximum in the cycle of 1,  $k$  where ( $1 \leq k \leq n$ ).

### Output

For each data set there is one line of output. It contains the data set number ( $N$ ) followed by a single space, followed by a double precision floating point whole value which is the number of permutations of the integers  $1, \dots, n$ , for which the maximum in the cycle of 1 is  $k$ .



Greater New York  
Programming Contest  
Adelphi University  
Garden City, NY



Sample Input	Sample Output
4	1 6
1 4 1	2 168
2 7 3	3 86400
3 10 5	4 1158524765798400
4 20 7	