



B • The Rascal Triangle

The *Rascal Triangle* definition is similar to that of the *Pascal Triangle*. The rows are numbered from the top starting with 0. Each row n contains $n+1$ numbers indexed from 0 to n . Using $R(n, m)$ to indicate the index m item in the index n row:


$$R(n, m) = 0 \text{ for } n < 0 \text{ OR } m < 0 \text{ OR } m > n$$

The first and last numbers in each row (which are the same in the top row) are 1:

$$R(n, 0) = R(n, n) = 1$$

The interior values are determined by $(UpLeftEntry * UpRightEntry + 1) / UpEntry$ (see the parallelogram in the array below):

$$R(n+1, m+1) = (R(n, m) * R(n, m+1) + 1) / R(n-1, m)$$



Write a program which computes $R(n, m)$ the m^{th} element of the n^{th} row of the *Rascal Triangle*.

Input

The first line of input contains a single integer P , ($1 \leq P \leq 1000$), which is the number of data sets that follow. Each data set is a single line of input consisting of 3 space separated decimal integers. The first integer is data set number, N . The second integer is row number n , and the third integer is the index m within the row of the entry for which you are to find $R(n, m)$ the *Rascal Triangle* entry ($0 \leq m \leq n \leq 50000$).



Greater New York
Programming Contest
Adelphi University
Garden City, NY



Output

For each data set there is one line of output. It contains the data set number, n , followed by a single space which is then followed by the *Rascal Triangle* entry $R(n, m)$ accurate to the nearest integer value.

| Sample Input | Sample Output |
|---------------|---------------|
| 5 | 1 1 |
| 1 4 0 | 2 5 |
| 2 4 2 | 3 411495886 |
| 3 45678 12345 | 4 24383845 |
| 4 12345 9876 | 5 264080263 |
| 5 34567 11398 | |