



## Czech ACM Student Chapter

Charles University in Prague  
Slovak University of Technology  
University of Žilina  
Matej Bel University in Banská Bystrica

## Czech Technical University in Prague

Technical University of Ostrava  
Pavol Jozef Šafárik University in Košice  
Masaryk University  
University of West Bohemia



# CTU Open Contest 2012

---

## Software Bugs

bugs.c, bugs.cpp, Bugs.java



Not all bugs are insects. There are also certain kinds of bugs that may become a real nightmare for software developers. You definitely know the situation when a user calls to say “Hey, I’ve found a bug in your program.” Once you have located and removed the bug, another one appears immediately. It is a hard and never-ending process.

Recently, there appeared a promising open-source initiative called the *Bug Preprocessor*. The preprocessor is a program able to find all bugs in your source code and mark them, so they are relatively easy to remove. Your task is to write a program that will remove all marked bugs from the preprocessed source code.

### Input Specification

The input contains several test cases. Each test case starts with a line containing one integer number  $T$  ( $0 \leq T \leq 100\,000$ ), one space and a string  $B$  used by the preprocessor to mark all bugs. The next  $T$  lines then contain the preprocessed source code. All bugs are represented by a case-sensitive string  $B$ .

Each line of the input will be between 0 and 2000000 characters long. The bug marker  $B$  consists of at least 1 and at most 1000 uppercase letters (“A” through “Z”).

### Output Specification

Your program must remove all of the bugs and produce the same result as if the first occurrence of  $B$  on each line was removed repeatedly, until there is no other existing occurrence of  $B$ . Nothing else may be removed, not even spaces.

### Sample Input

```
7 BUG
print "No bugs here..."

void hello() {
BUGBUG
    printfBUG("Hello, world!\n");
}

1 ERR
wriERRERRtelERRn("Hello E-R-R");
```

### Output for Sample Input

```
print "No bugs here..."

void hello() {
    printf("Hello, world!\n");
}

writeln("Hello E-R-R");
```

*(This problem has been adapted from SWERC archives.)*