



HAL
open science

Laboratory dielectric constant determination for planetary surface characterization

Yann Brouet, Anny Chantal Levasseur-Regourd, P. Encrenaz, M. Gheudin, G.
Ruffié, S. Gulkis

► **To cite this version:**

Yann Brouet, Anny Chantal Levasseur-Regourd, P. Encrenaz, M. Gheudin, G. Ruffié, et al.. Laboratory dielectric constant determination for planetary surface characterization. EPSC-DPS Joint Meeting 2011, Oct 2011, Nantes, France. 6, pp.EPSC-DPS2011-1083-1. hal-00790863

HAL Id: hal-00790863

<https://hal.science/hal-00790863>

Submitted on 10 Jun 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Laboratory dielectric constant determination for planetary surface characterization

Y. Brouet (1), A.C. Levasseur-Regourd (2), P. Encrenaz (1), M. Gheudin (1), G. Ruffié (3), S. Gulikis (4) and the MIRO Team. (1) Observatoire de Paris / LERMA, Paris, France (yann.brouet@obspm.fr); (2) UPMC (Univ. Paris 6) / LATMOS, Paris, France; (3) IMS, Bordeaux, France; (4) JPL, Pasadena, USA.

Abstract

A program of dielectric constant determination on various analogues, over a large range of frequencies and porosities, is under development in relation with the interpretation of Rosetta spacecraft observations. The analogues are meteoritic samples (compact and powdered), likely to be representative of the asteroids that have already been flown-by and of the cometary nucleus that is to be encountered. First results have already been obtained for asteroid Steins.

1. Introduction and motivation

On board the ESA Rosetta spacecraft, which is to rendezvous comet 67P/Churyumov-Gerasimenko in mid-2014, the MIRO (Microwave Instrument for The Rosetta Orbiter) and CONSERT (Comet Nucleus Sounding Experiment by Radiowave Transmission) experiments will allow the characterization, respectively of the cometary nucleus sub-surface and of its internal structure. MIRO is a dual-frequency radiometer, with one continuum channel at 190 GHz (1.6 mm) and another one at 562 GHz (0.5 mm) [1]. CONSERT is a new type of experiment, aimed at investigating the deep interior of the nucleus through radio-waves at 90 MHz, transmitted from the orbiter and returned from the lander [2]. MIRO has already observed the two asteroids that were flown by Rosetta, (2867) Steins in 2008 and (21) Lutetia in 2010. MIRO results have shown that (2867) Steins surface has a relatively high thermal inertia of $110 JK^{-1}m^{-2}s^{-0.5}$, whereas (21) Lutetia surface has a low thermal inertia less than $30 JK^{-1}m^{-2}s^{-0.5}$, suggesting a lunar-type regolith [3, 4].

We propose to provide complementary results by comparing MIRO (and later also CONSERT) observations with measurements in the laboratory of the dielectric constants of samples of meteoritic analogues for both asteroids and for the cometary nucleus. Laboratory measurements of the dielectric constant on meteoritic

analogues will allow for better constraining the properties of the asteroids and of the nucleus. Associated with a shape model of these small bodies, dielectric constant determination (real part and imaginary part) on meteoritic analogues should lead to the prediction of emissivity of these objects, as a function of the solar phase angle.

2. Laboratory experiments

Such measurements on meteoritic analogues are to be obtained on a large range of frequencies (for the sub-millimeter up to possibly the meter domains) and porosities, taking into account the formation of layers of regolith on the surface, with different ranges of size distribution and compaction degree (possibly related to the gravity of the asteroids and of the nucleus). Table 1 lists the spectral domain of the instruments that are available for such measurements, at LERMA in Paris, as well as at IMS (Laboratoire de l'Intégration du Matériau au Système) in Bordeaux.

Table 1: Spectral domain of available laboratory experiments for permittivity measurements.

Experiment (laboratory)	Spectral domain
Impedance analyzer (IMS)	100 MHz
Coaxial sensor (IMS)	0.5-6 GHz
Resonant cavities (IMS)	1.2-13.4 GHz
Millimeter benches (IMS and LERMA)	30-550 GHz

It should be added that, as far as atmosphere-less bodies are considered, the properties of the regolithic surfaces are also approached by remote polarimetric observations (see e.g., [5]). Light scattering laboratory measurements (in the visible and near-infrared domains) on meteoritic analogues with the PROGRA2 experiment (operating in the laboratory or during parabolic flights to reduce the gravity) can indeed be

used to establish whether the analogue is appropriate or not and to estimate the size distribution of the dust particles.

3. Samples and preliminary results

Dielectric constant measurements for different frequencies have already been obtained on an aubrite, an enstatite achondrite meteorite, which is considered as a good analogue for Steins (and other E-type asteroids) surface [6]. Dielectric constant values are systematically smaller than those derived by MIRO measurements: 6 for the real part and 0.1 for the imaginary part for the aubrite, instead of 7.2 and 0.3 respectively for Steins [3], suggesting that the complexity of Steins surface needs to be studied through complementary measurements. Meanwhile, polarimetric measurements have shown that aubrite powders and Allende meteorite powders could represent good analogues for the surface light scattering properties of respectively Steins and Lutetia [7, 8].

Acknowledgements

Support from CNES is acknowledged

References

- [1] Gulkis, S., et al.: MIRO, microwave instrument for the Rosetta orbiter, *Space Sci. Rev.*, 128, 561-597, 2007.
- [2] Kofman, W. et al.: The Comet Nucleus Sounding Experiment by Radiowave Transmission (CONSERT), *Space Sci. Rev.*, 128, 413-432, 2007.
- [3] Gulkis et al.: Millimeter and sub-millimeter measurements of asteroid (2867) Steins during the Rosetta fly-by, *Planet. Space Sci.*, 58, 1077-1087, 2010.
- [4] Gulkis, S., et al.: Continuum observations of asteroids (2867) Steins and (21) Lutetia with the MIRO millimeter and sub-millimeter instrument on the ESA Rosetta spacecraft, EPSC Congress, 20-24 Sept. 2010, Rome, Italy, 2010.
- [5] Levasseur-Regourd, A.C.: Inferring properties of dust within solar system bodies through observations and simulations of the linear polarization of scattered solar light, In *Polarimetric detection, characterization, and remote sensing* (M.I. Mischchenko, Y.S. Yatskiv, V.K. Rosenbush and G. Videen eds.), NATO Science Series, Springer, 295-312, 2011.
- [6] McFadden, L.A. et al.: Coordinated laboratory studies of meteorites supporting Rosetta mission's asteroid flyby target: 2867 Steins, 40th LPSC, 2887, 2009.
- [7] Hadamcik, E., et al.: Polarimetric observations and laboratory simulations of asteroidal surfaces: the case of 21-Lutetia, *J. Quant. Spectros. Radiat. Transfer*, in press, 2011.
- [8] Levasseur-Regourd, A.C. et al.: Clues to links between aubrites and (2867) Steins, from comparisons between polarimetric laboratory measurements on meteoritic samples and observations, *Planet. Space Sci.*, submitted, 2011.