

Discussion on: "Time-Delay Model-Based Control of the Glucose-Insulin System, by Means of a State Observer"

Olivier Sename, Corentin Briat

▶ To cite this version:

Olivier Sename, Corentin Briat. Discussion on: "Time-Delay Model-Based Control of the Glucose-Insulin System, by Means of a State Observer". European Journal of Control, 2012, 18 (6), pp.607-609. hal-00795550

HAL Id: hal-00795550

https://hal.science/hal-00795550

Submitted on 28 Feb 2013

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Discussion on the article "Time-delay model-based control of the glucose-insulin system, by means of a state observer"

Olivier Sename[†] and Corentin Briat[‡]

I. Introduction

Time-delay systems are ubiquitous in nature and engineering. Delays account for transmission, diffusion and migration phenomena as well as maturation and aging in physical, biological, ecological, epidemiological and population systems. Lotka-Volterra models describing prey-predator models or Pearl-Verhulst equations for population dynamics are instances of deterministic models aiming to describe population evolution. These models do not account for aging/maturation of the population and this is the reason why refinement of the models have been proposed [1].

Delays in epidemiological models [1] may account for incubation time, time for recovery, time for the vaccine to become active or time to be susceptible again after recovering. Models referred to as compartmental models [2], comprising SIR, SIS, SEIS models, and so on. The following simple delay-SIR model has been proposed in [3]

$$\begin{array}{lcl} \dot{S}(t) & = & -\beta S(t)I(t) \\ \dot{I}(t) & = & \beta S(t)I(t) - \beta \int_h^\infty \gamma(\tau)S(t-\tau)I(t-\tau)d\tau \\ \dot{R}(t) & = & \beta \int_h^\infty \gamma(\tau)S(t-\tau)I(t-\tau)d\tau \end{array}$$

where S,I and R represent the population of susceptible, infectious and recovered people, respectively. The delay is distributed in this model and describes the time spent being sick. The distributed delay kernel $\gamma:[h,\infty)\to\mathbb{R}_+$ satisfies the condition $\int_h^\infty \gamma(\tau)d\tau=1$ and can be seen as a probability distribution. An optimal vaccination strategy has been applied on this model for controlling the disease outbreak.

Delay equations have also found applications in ecology [4], [5] where the following neutral delay model [6] for forest evolution based on Pearl-Verhulst equation has been proposed:

$$\dot{x}(t) = rx(t) \left[1 - \frac{x(t-\tau) + c\dot{x}(t-\tau)}{K} \right]$$

where x,r and K are the tree population, the intrinsic growth rate and the environmental carrying capacity. The additional term $c\dot{x}(t-\tau)$ to the usual logistic equation is introduced to account for soil depletion and erosion.

†Control Systems dpt, GIPSA-lab, UMR CNRS-InPG-UJF 5216, 11 rue des Mathématiques, BP 46, F-38402 GRENOBLE Cedex, France, olivier.sename@gipsa-lab.fr; † Department of Biosystems Science and Engineering, Swiss Federal Institute of Technology - Zürich (ETHZ), Mattenstrasse 26, 4058 Basel, SWITZERLAND, corentin@briat.info, www.briat.info.

The paper [7] addresses the control of the glucose-insulin system

$$\dot{G}(t) = -K_{xgi}G(t)I(t) + \frac{T_{gh}}{V_G}
\dot{I}(t) = -K_{xi}I(t) + \frac{T_{iGmax}}{V_I}f(G(t - \tau_g)) + u(t)$$
(1)

which takes the form of a positive nonlinear system with constant discrete-delay. Above G and I denote plasma glycemia and insulinemia, respectively. The control input u is the exogenous intra-venous insulin delivery rate.

The current paper [7] addresses the design of an observer-based control law, where the controller is taken back from [8] by the same authors. The observer is designed with the assumption that only the plasma glycemia, i.e. G(t), is measured. The observer design relies on the computation of a constant matrix W, which multiplied by the inverse of the Jacobian matrix of the observability matrix (which is nonsingular except at (0,0)), yields the observer-gain, see e.g. [9]. The local stability of the closed-loop system is finally proved by looking at the asymptotic stability of the origin of the linear time-varying system

$$\dot{\hat{e}}(t) = H\hat{e}(t) + WC\xi(t)
\dot{\xi}(t) = \hat{H}\xi(t) + Br_0(t)\xi(t) + r_1(t)BC\xi(t - \tau_g).$$
(2)

A Lyapunov argument is used to infer stability of the above LTV system and the matrix gain W is designed according to some results in [10] pertaining on delay-independent robust stability of uncertain polytopic time-delay systems.

II. TOWARDS AN LPV APPROACH FOR BIOLOGICAL SYSTEMS

A. A first extension to LPV observers

The framework developed in the paper [7], i.e. delay and time-varying parametric uncertainties, is completely compatible with the LPV framework which assumes knowledge of the varying parameters r_1 and r_2 . Note that these parameters are functions of the state of the systems.

Along these lines, we can therefore imagine the following extensions:

• The observer structure may be extended to incorporate additional terms (ans gains), notably to take into account delayed information. This may lead to a more accurate estimation of the state and better convergence properties. The exact knowledge of the delay value is critical here and may be the main limitation of observer including delays. Memory-resilient observers should be a suitable solution, see e.g. [11], [12] for memory resilient controllers.

 System (2) can be viewed as an LPV system involving two varying parameters r₀ and r₁. Some of the results developed in [13], [14] may be used to design an LPV observer involving a parameter-dependent gain W(r₁, r₂) in order to improve performance of the overall observation process.

B. Design of gain scheduled LPV controllers

The design of gain-scheduled control laws is also one of the objectives of the LPV framework. By rewriting system (1) as a quasi-LPV system of the form

$$\dot{G}(t) = (K_{xgi}\rho(t))I(t) + \frac{T_{gh}}{V_G}
\dot{I}(t) = \alpha(t)G(t-\tau_g) - K_{xi}I(t) + u(t)$$
(3)

where $\rho(t) = G(t)$ and

$$\alpha(t) = \frac{T_{iGmax}}{V_I} \cdot f'(\rho(t - \tau_g)). \tag{4}$$

The above system is an LPV time-delay system that has been extensively studied in [15], [16], see also references therein. Based on this formulation, gain-scheduled controllers can easily be derived.

REFERENCES

- J. D. Murray, Mathematical Biology Part I. An Introduction. 3rd Edition. Springer-Verlag Berlin Heidelberg, 2002.
- [2] W. M. Haddad, V. Chellaboina, and Q. Hui, Nonnegative and compartmental dynamical systems. 41 William Street, Princeton, New Jersey, USA: Princeton University Press, 2010.
- [3] C. Briat and E. Verriest, "A new delay-SIR model for pulse vaccination," *Biomedical signal processing and control*, vol. 4(4), pp. 272– 277, 2009.
- [4] E. C. Pielou, Mathematical Ecology. New York, USA: Wiley Interscience, 1977.
- [5] K. Gopalsamy and B. G. Zhang, "On a neutral delay-logistic equation," Dynamics and stability of systems, vol. 2, pp. 183–195, 1988.
- [6] E. I. Verriest and P. Pepe, "Time optimal and optimal impulsive control for coupled differential difference point delay systems with an application in forestry," in *IFAC Workshop on time-delay systems*, Nantes, France, 2007.
- [7] P. Palumbo, P. Pepe, S. Panunzi, and A. D. Gaetano, "Time-delay model-based control of the glucose-insulin system, by means of a state observer," *European Journal of Control*, vol. 18, no. 6, 2012.
- [8] —, "Robust closed-loop control of plasma glycemia: A discretedelay model approach," DISCRETE AND CONTINUOUS DYNAMI-CAL SYSTEMS SERIES B, vol. 12, no. 2, p. 455468, Sept. 2009.
- [9] A. Germani and P. Pepe, "A State Observer for a Class of Nonlinear Systems with Multiple Discrete and Distributed Time Delays," *Euro*pean Journal of Contro, vol. 11(3), pp. 196–205, 2005.
- [10] K. Gu, V. L. Kharitonov, and J. Chen, Stability of Time-Delay Systems. Birkhäuser, Boston, 2003.
- [11] C. Briat, O. Sename, and J. Lafay, "Memory resilient gain-scheduled state-feedback control of time-delay systems with time-varying delays," in *ROCOND'09*, Haifa, Israel, 2009.
- [12] —, "Memory resilient gain-scheduled state-feedback control of uncertain LTI/LPV systems with time-varying delays," Systems & Control Letters, vol. 59, pp. 451–459, 2010.
- [13] C. Briat, "Robust control and observation of LPV time-delay systems," Ph.D. dissertation, Grenoble Institute of Technology, GIPSAlab/Control Systems dpt, 2008.
- [14] C. Briat, O. Sename, and J.-F. Lafay, "Design of lpv observers for lpv time-delay systems: an algebraic approach," *International Journal of Control*, vol. 84, no. 9, pp. 1533–1542, 2011.
- [15] C. Briat, "Control and observation of LPV time-delay systems," Ph.D. dissertation, Grenoble-INP, 2008. [Online]. Available: http://www.briat.info/thesis/PhDThesis.pdf

[16] R. Zope, J. Mohammadpour, K. Grigoriadis, and M. Franchek, "Delay-dependent h_∞ control for lpv systems with fast-varying time delays," in 2012 American Control Conference, Montral, Canada June 27-June 29, 2012, 2012.