

Biomechanical response of varicose veins to elastic compression: A numerical study.

Pierre-Yves Rohan, Pierre Badel, Bertrand Lun, Didier Rastel, Stéphane Avril

▶ To cite this version:

Pierre-Yves Rohan, Pierre Badel, Bertrand Lun, Didier Rastel, Stéphane Avril. Biomechanical response of varicose veins to elastic compression: A numerical study. Journal of Biomechanics, 2013, 46 (3), pp.599-603. 10.1016/j.jbiomech.2012.10.043. hal-00801291

HAL Id: hal-00801291

https://hal.science/hal-00801291

Submitted on 15 Mar 2013

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

4

2 Biomechanical response of varicose veins to

elastic compression: a numerical study

Rohan C.P-Y.¹, Badel P.¹, Lun B.², Rastel D.³, Avril S.¹ 5 6 ¹ Ecole Nationale Supérieure des Mines de Saint-Etienne, CIS-EMSE, CNRS:UMR5307, LGF, F-42023 Saint 7 Etienne, France 8 ² Sigvaris Research and Development Center, Saint-Just-Saint-Rambert, France 9 ³ Vascular physician, Grenoble, France 10 11 Corresponding author: 12 Christian Pierre-Yves Rohan 13 Center for Health Engineering 14 Ecole Nationale Supérieure des Mines 15 158 cours Fauriel 16 42023 SAINT-ETIENNE CEDEX 2 France 17 Phone: +33477426609 18 Fax: +33477499755 19 Email: rohan@emse.fr 20 21 Keywords: Varicose veins; trans-mural pressure; Finite Element Updating; Medical Compression 22 Stockings 23 24 Word count (introduction through conclusion): 1 988

26 Abstract

A patient-specific Finite-Element (FE) model of the human leg is developed to model the stress distribution in and around a vein wall in order to determine the biomechanical response of varicose veins to compression treatment. The aim is to investigate the relationship between the local pressure on (the) soft tissues induced by wearing the compression garment and the development and evolution of varicose veins and various skin-related diseases such as varicose veins and ulcers. Because experimental data on the mechanical properties of healthy superficial veins and varicose veins are scarce in literature, ultrasound images of *in vivo* varicose veins are acquired and analysed to extract the material constants using Finite Element Model Updating. The decrease in trans-mural pressure, which conditions the effectiveness of compressive treatments, is computed from the simulation results. This constitutes the original added value of the developed model as decreases in trans-mural pressures cannot be assessed experimentally by any other means. Results show that external compression is effective in decreasing the trans-mural pressure, thereby having a positive effect in the control and treatment of vein-related diseases.

41 Introduction

56

42 Compression therapy by Medical Compression Stockings (MCS), which is considered as the "gold 43 standard" therapy for venous insufficiency, has been a topic of important research for 30 years. The 44 following effects or actions of MCS have gained a special interest: 45 - hemodynamic effects: (Mayberry et al., 1991), (Ibegbuna et al., 2003), (Guesdon et al., 2007), (Downie et 46 al., 2008) and (Wang et al., 2012), in continuation of pioneer studies on collapsible tubes: (Katz et al., 47 1969), (Moreno et al., 1970) and (Kamm and Shapiro, 1979); - clinical and post-surgery effects: (Nehler et al., 1992), (Nehler et al., 1993)(Kern et al., 2007), 48 49 (Villavicencio, 2009) and (Hamel-Desnos et al., 2010); 50 - skin and deep tissue compression: (Wildin et al., 1998), (Agu et al., 1999), (Best et al., 2000), , (Yeung et 51 al., 2004), (Liu et al., 2005), (Gaied et al., 2006), (Liu et al., 2006), (Dai et al., 2007), (Lee and Han, 2010), 52 (Martinez et al., 2010), (Avril et al., 2010) and (Dubuis et al., 2012). 53 54 However, some of the mechanisms by which MCS act(s) are still not clearly understood. The present study 55 aims at addressing the effect of MCS on varicose veins by adopting a finite-element modelling approach.

Materials and methods

58	-1- Imaging methods
59	Images are acquired on the calf of a 50 year old male patient with a varicose vein:
60	- Magnetic resonance imaging is applied with a two dimensional T1 TSE modality on a Siemens 1.5T
61	scanner using (()pixel resolution: 0.7813×0.7813 mm2, slice thickness: 3.9 mm()).
62	- Echography is applied for obtaining images with a better spatial resolution in the region of the varicose
63	vein. The ultrasound images are acquired with and without 15-20 mmHg MCS (AFNOR, 1986) both in the
64	standing and supine position (Fig 1).
65	
66	-2- Finite Element Model
67	Finite element mesh
68	The geometry is reconstructed from both MRI (deep tissues) and ultrasound scans (vein). The meshing
69	tools available in ABAQUS® are used to generate the computational mesh of the reconstructed geometry
70	(Fig. 2). Continuum plane strain elements with a hybrid formulation are used for the muscle, fat and vein
71	wall. A 2-D model is used since (Avril et al., 2010) showed that the 2-D approach predicts a similar
72	pressure distribution in the calf tissues as a full 3-D model.
73	A hybrid formulation is preferred because the soft tissues are defined as quasi-incompressible (Poisson's
74	ratio > 0.475). Truss elements are used for the discretisation of the muscular aponeurosis, the skin and the
75	MCS. A relatively finer discretisation is used around the vein. The models contain about 13 600 elements
76	and 33 800 degrees of freedom (including the Lagrange multiplier variables). A mesh convergence study
77	was conducted showing that further mesh refinement produces a negligible change in the solution.
78	
79	Internal blood pressure in the vein
80	The intravascular pressure is accounted for by a constant pressure applied on the inner surface of the vein
81	wall. The pressure imposed is 15mmHg in the supine position and 90mmHg in the standing position. This
82	pressure is responsible for an initial pre-stress of the vein wall before applying compression, which is
83	considered by applying an initial circumferential pre-stress on the vein wall to counterbalance this
84	pressure. The value of the circumferential pre-stress in each element of the vein wall is determined by

85 applying the Laplace law. A 1 kPa pre-stress is also defined on the skin in the circumferential direction 86 (Flynn et al., 2011). 87 88 Boundary conditions 89 The tibia and fibula are fixed in this model. 90 91 Contact pressure on the skin. 92 The interaction between the skin and the sock is enforced using the default ABAQUS® parameters in the 93 normal direction (Tab. 1) and using a penalty method in the tangential direction. A skin-to-textile friction 94 coefficient of 0.3 is used for the tangential direction, as reported in the literature (Gerhardt et al., 2009). 95 96 Constitutive equations 97 A summary is given in Tab 2. A linearized model is preferred for the vein because (i) the developed 98 biomechanical model is used to simulate the deformation of the leg between two states of loading 99 (compressed and uncompressed) which are very close one to the other, and (ii) we do not need to know 100 the stress-free state of our leg as (it) is the case with nonlinear material behaviour models. The Poisson's 101 ratio is fixed (to) at 0.49 (Wells and Liang, 2011) and two different stiffness values are identified, in supine 102 and standing positions respectively, as the diameter reduction of the vein lumen, due to a 15-20 mmHg 103 class compression sock, is (of) 10% in the supine and (of) 3% in the standing position. 104 105 Analysis procedure 106 Simulation is divided into 3 steps as previously described: 107 Step 1 Initial stress on vein wall and skin and blood pressure loading 108 Step 2 Inflate sock and activate the contact conditions between the skin and the sock 109 Step 3 Release the MCS and calculate the equilibrium position 110 111 The resolution is performed via an implicit scheme. The default convergence criteria in ABAQUS/Standard 112 are used (Tab. 1).

113

114 Results

140

-1- Mechanical properties of the vein wall and fat 115 The FE model is calibrated against the echographic images of compressed and uncompressed legs 116 117 acquired in the standing and supine positions. The identified Young's moduli for the vein wall are 100 kPa 118 in the supine position and 836 kPa in the standing position. The identified C₁₀ constant for the fat, 119 characterizing the shear modulus in the Neo-Hookean strain energy function, is 5 kPa. 120 -2- Parametric study 121 122 Simulations are run corresponding to the supine and standing positions. Salient quantitative results of each simulation are reported in the Appendix through Table A1 to A7, where the influence of the 123 124 following parameters is reported: 125 [a] Ratio of adipose tissue to leg size (Table A1); 126 [b] Position on the leg contour (Table A2); 127 [c] Vein lumen size (Table A3); [d] Depth of vein in adipose tissue (Table A4); 128 129 [e] Effect of the applied external compression (Table A5); 130 [f] Influence of the "type" of fat (Table A6 for the influence of the stiffness and Table A7 for the 131 influence of the incompressibility parameter). 132 133 Based on the results, it can be summarized that the biomechanical response of veins is subject to three 134 main mechanical factors: the vein size, the local radius of curvature and the fat stiffness. This highlights 135 the strong patient-specific response of the leg to external compression. 136 137 Parametric studies were also (run about) carried out on the element types, the type of contact and the 138 type of material behaviour. Results (Tables A8 through A12) show that the modelling assumptions do not 139 affect the trends (about) of the three main mechanical factors.

Discussion

-1- Material properties

The stiffness properties of the fat and of the vessel wall are identified by Finite Element Model Updating. The obtained values are consistent with values reported in the literature. In a study to determine the *in vitro* elastic properties of human saphenous vein segments, (Wesly et al., 1975) reported that the *in vitro* saphenous tangent modulus in the circumferential direction is considerably smaller at pressure ranges corresponding to the supine position (30 kPa and 65 kPa at 10 mmHg and 25 mmHg of pressure respectively) but is similar to carotid values at pressures similar to those encountered *in vivo* in the standing position (990 kPa and 1.5 MPa at 75 mmHg and 100 mmHg of pressure respectively). This is consistent with other studies, conducted both *in vivo* and *in vitro*, showing that veins exhibit a non-linear mechanical behaviour and become stiffer as (it) they deform(s)(Buhs et al., 1999) (Zhao et al., 2007). More recently, based on the material parameters reported by (Chuong and Fung, 1986), Han estimated the Young's modulus of blood vessels to be 100 kPa (Han, 2011). Material parameters of the Fung exponential strain energy function have also been reported for the human saphenous vein (Zhao et al., 2007) and for porcine jugular veins (Lee and Han, 2010). They are all comparable with the elastic properties found in our approach.

The material parameter identified for the fat lies within the range of values reported (by) in a study involving six patients. (Dubuis et al., 2012)

The fact that the narrowing of the vein is less pronounced in the standing position, for a given level of external compression, may also be due to the fact that the applied external pressure has to work against a higher internal blood pressure (Partsch and Partsch, 2005), (Partsch, 2007).

-2- Main trends

The results obtained using the proposed model show that hydrostatic pressure in fat is (i) (is) effectively increased and (ii) by an order of magnitude comparable to the mean contact pressure exerted by the MCS on the skin.

The computed hydrostatic pressure in the fat is essential to understanding how the pressure is transmited through the superficial soft tissues. Moreover the increase in tissue pressure is regarded as a crucial mechanism (to the) in compressive treatments (Bergan, 2007). Clearly, appreciating how geometric and material parameters affect the transmission of pressure is an important step to understanding both the modes of action of EC treatment and the rationales behind its efficacy.

Other research teams have reported satisfactory results for the measurement of vein deformation under compression (Partsch et al., 2010) but have not used these results for quantifying the trans-mural pressures. The results of our model indicate that 15-20 mmHg MCS are effective in decreasing the transmural pressure on vein walls. The values predicted are twice as high in the standing position than in the supine position. This trend corroborates that reported *in vitro* by (Gardon-Mollard and Ramel, 2008).

-3- Clinical relevance

From a clinical perspective, an increase of the trans-mural pressure on varicose vein walls exacerbates the disease and the underlying Chronic Venous Insufficiency (CVI). The goal of compression therapy is to restore a trans-mural pressure which is as normal as possible, by increasing the perivenous tissue pressure (Gardon-Mollard and Ramel, 2008). The results reported here confirm the idea that MCS work towards reducing the trans-mural pressure. In addition, trans-mural pressure is known to be related to the tension of the vein wall according to the Laplace law (Gusic et al., 2005). Reduction of the tension implies a smaller number of alterations in the vein wall associated with various pathologies. Another consequence is a greater stability with respect to axial buckling and tortuosity development (Han, 2007)(Han, 2009)(Han, 2012).

The action of MCS may also affect the remodelling of the vein. (Travers et al., 1996) (have) observed that varicose saphenous veins contained significantly higher amounts of collagen in all layers of the vein wall and that these collagen fibres were seen to invade and break up regular muscle layers of the media in varicosis. Reduction of the tension in the vein wall under the action of MCS is prone to hinder these effects.

Another important clinical (important) aspect concerns the evolution of CVI more generally: because CVI is both progressive and irreversible, clinical symptoms associated with venous insufficiency increase in severity with time (Suzuki et al., 2009). Important efforts are still necessary to predict numerically the long-term action of MCS in preventing the progression of venous stasis and the apparition of associated symptoms such as oedema, pigmentation, and ulcers on the skin.

205 Conclusion

In this study, a FE model of a human leg with a varicose vein has been developed to compute the stress
distribution in and around the vein wall and analyse the biomechanical response of varicose veins to
external compression in terms of trans-mural pressures. Experimental data on the mechanical properties
of healthy superficial veins and varicose veins being scarce in literature, ultrasound images of in vivo
varicose veins have been acquired and analysed to extract the material constants of the vein wall and tha
of the fat, using Finite Element Model Updating.
The model (brings)provides a new insight on MCS mechanical action and its possible benefits. The results
confirm the idea that MCS work towards reducing (the) trans-mural pressure and are effective in
narrowing leg veins, which is important for the clinical consequences.
Future developments include a validation of the proposed approach and of its medical outcomes using

Acknowledgement

221 None

clinical studies.

Conflict of interest

223 None

225 References

- AFNOR, 1986. NF G30-102. Article de bonneterie Détermination de la pression de contention.
- Agu, O., Hamilton, G., Baker, D., 1999. Graduated compression stockings in the prevention of venous
- thromboembolism. British Journal of Surgery 86, 992–1004.
- Avril, S., Bouten, L., Dubuis, L., Drapier, S., Pouget, J.-F., 2010. Mixed Experimental and Numerical Approach
- 230 for Characterizing the Biomechanical Response of the Human Leg Under Elastic Compression. Journal of
- Biomechanical Engineering 132, 31006–31014.
- Bergan, J.J., 2007. The Vein Book. Academic Press.
- Best, A.J., Williams, S., Crozier, A., Bhatt, R., Gregg, P.J., Hui, A.C.W., 2000. Graded compression stockings in
- elective orthopaedic surgery. J Bone Joint Surg Br 82-B, 116–118.
- Buhs, C.L., Bendick, P.J., Glover, J.L., 1999. The effect of graded compression elastic stockings on the lower
- leg venous system during daily activity. Journal of Vascular Surgery 30, 830–835.
- 237 Chuong, C.J., Fung, Y.C., 1986. On Residual Stresses in Arteries. Journal of Biomechanical Engineering 108,
- 238 189–192.
- Dai, X., Liu, R., Li, Y., Zhang, M., Kwok, Y., 2007. Computational Textile, in: Studies in Computational
- Intelligence. Springer Berlin / Heidelberg, pp. 301–309.
- Downie, S.P., Raynor, S.M., Firmin, D.N., Wood, N.B., Thom, S.A., Hughes, A.D., Parker, K.H., Wolfe, J.H.N., Xu,
- 242 X.Y., 2008. Effects of Elastic Compression Stockings on Wall Shear Stress in Deep and Superficial Veins of
- the Calf. Am J Physiol Heart Circ Physiol 294, H2112–H2120.
- Dubuis, L., Avril, S., Debayle, J., Badel, P., 2012. Identification of the material parameters of soft tissues in
- the compressed leg. Computer Methods in Biomechanics and Biomedical Engineering 15, 3–11.
- Flynn, C., Taberner, A., Nielsen, P., 2011. Mechanical characterisation of in vivo human skin using a 3D
- 247 force-sensitive micro-robot and finite element analysis. Biomechanics and Modeling in Mechanobiology
- **248** 10, 27–38.
- Gaied, I., Drapier, S., Lun, B., 2006. Experimental assessment and analytical 2D predictions of the stocking
- pressures induced on a model leg by Medical Compressive Stockings. Journal of Biomechanics 39, 3017–
- **251** 3025.
- 252 Gardon-Mollard, Ramel, 2008. La compression médicale. Elsevier Masson.
- 253 Gerhardt, L. -c, Lenz, A., Spencer, N.D., Münzer, T., Derler, S., 2009. Skin-textile friction and skin elasticity
- in young and aged persons. Skin Research and Technology 15, 288–298.
- Guesdon, P., Fullana, J.-M., Flaud, P., 2007. Experimental study of muscular draining. Comptes Rendus
- 256 Mécanique 335, 207–212.
- Gusic, R.J., Petko, M., Myung, R., William Gaynor, J., Gooch, K.J., 2005. Mechanical properties of native and
- ex vivo remodeled porcine saphenous veins. Journal of Biomechanics 38, 1770–1779.
- Hamel-Desnos, C.M., Guias, B.J., Desnos, P.R., Mesgard, A., 2010. Foam Sclerotherapy of the Saphenous
- 260 Veins: Randomised Controlled Trial with or without Compression. European Journal of Vascular and
- 261 Endovascular Surgery 39, 500–507.

- Han, H.-C., 2007. A biomechanical model of artery buckling. Journal of Biomechanics 40, 3672–3678.
- 263 Han, H.-C., 2009. Blood vessel buckling within soft surrounding tissue generates tortuosity. Journal of
- 264 Biomechanics 42, 2797–2801.
- Han, H.-C., 2011. Determination of the Critical Buckling Pressure of Blood Vessels Using the Energy
- 266 Approach. Ann Biomed Eng 39, 1032–1040.
- lbegbuna, V., Delis, K.T., Nicolaides, A.N., Aina, O., 2003. Effect of elastic compression stockings on venous
- hemodynamics during walking. Journal of Vascular Surgery 37, 420–425.
- 269 Kamm, R.D., Shapiro, A.H., 1979. Unsteady Flow in a Collapsible Tube Subjected to External Pressure or
- Body Forces. Journal of Fluid Mechanics 95, 1–78.
- 271 Katz, A.I., Chen, Y., Moreno, A.H., 1969. Flow through a Collapsible Tube: Experimental Analysis and
- 272 Mathematical Model. Biophysical Journal 9, 1261–1279.
- Kern, P., Ramelet, A.-A., Wütschert, R., Hayoz, D., 2007. Compression after sclerotherapy for telangiectasias
- and reticular leg veins: A randomized controlled study. Journal of Vascular Surgery 45, 1212–1216.
- Lee, A., Han, H.-C., 2010. A Nonlinear Thin-Wall Model for Vein Buckling. Cardiovascular Engineering and
- 276 Technology 1, 282–289.
- Liu, R., Kwok, Y.-L., Li, Y., Lao, T.-T., Zhang, X., Dai, X., 2006. A three-dimensional biomechanical model for
- 278 numerical simulation of dynamic pressure functional performances of graduated compression stocking
- **279** (GCS). Fibers and Polymers 7, 389–397.
- Liu, R., Kwok, Y.L., Li, Y., Lao, T.T.H., Zhang, X., Dai, X.Q., 2005. Objective Evaluation of Skin Pressure
- Distribution of Graduated Elastic Compression Stockings. Dermatologic Surgery 31, 615–624.
- Martinez, R., Fierro, C., Shireman, P., Han, H.-C., 2010. Mechanical Buckling of Veins Under Internal
- Pressure. Annals of Biomedical Engineering 38, 1345–1353.
- Mayberry, J.C., Moneta, G.L., De Frang, R.D., Porter, J.M., 1991. The influence of elastic compression
- stockings on deep venous hemodynamics. Journal of Vascular Surgery 13, 91–100.
- Moreno, A.H., Katz, A.I., Gold, L.D., Reddy, R.V., 1970. Mechanics of Distension of Dog Veins and Other Very
- Thin-Walled Tubular Structures. Circulation Research 27, 1069–1080.
- Nehler, M.R., Moneta, G.L., Chitwood, R.W., Porter, J.M., 1992. The Lower Extremity Venous System Part III:
- Nonoperative Treatment of Chronic Venous Insufficiency. PERSPECT VASC SURG ENDOVASC THER 5,
- 290 100-114.
- Nehler, M.R., Moneta, G.L., Woodard, D.M., Defrang, R.D., Harker, C.T., Taylor Jr., L.M., Porter, J.M., 1993.
- 292 Perimalleolar subcutaneous tissue pressure effects of elastic compression stockings. Journal of Vascular
- 293 Surgery 18, 783–788.
- Partsch, B., Partsch, H., 2005. Calf compression pressure required to achieve venous closure from supine
- to standing positions. Journal of Vascular Surgery 42, 734–738.
- 296 Partsch, H., 2007. Chapter 10 Mechanism and effects of compression therapy, in: The Vein Book.
- 297 Academic Press, Burlington, pp. 103–109.
- 298 Partsch, H., Mosti, G., Mosti, F., 2010. Narrowing of leg veins under compression demonstrated by
- 299 magnetic resonance imaging (MRI). Int Angiol 29, 408–410.

- 300 Suzuki, M., Unno, N., Yamamoto, N., Nishiyama, M., Sagara, D., Tanaka, H., Mano, Y., Konno, H., 2009.
- 301 Impaired lymphatic function recovered after great saphenous vein stripping in patients with varicose
- vein: Venodynamic and lymphodynamic results. Journal of Vascular Surgery 50, 1085–1091.
- Travers, J.P., Brookes, C.E., Evans, J., Baker, D.M., Kent, C., Makin, G.S., Mayhew, T.M., 1996. Assessment of
- 304 wall structure and composition of varicose veins with reference to collagen, elastin and smooth muscle
- content. European Journal of Vascular and Endovascular Surgery 11, 230–237.
- 306 Villavicencio, J., 2009. Sclerotherapy in the management of varicose veins of the extremities., in: Handbook
- of Venous Disorders: Guidelines of the American Venous Forum. Gloviczki, P. and Yao J., London, pp. 366–
- 308 379.
- Wang, Y., Pierce, I., Gatehouse, P., Wood, N., Firmin, D., Xu, X.Y., 2012. Analysis of flow and wall shear stress
- in the peroneal veins under external compression based on real-time MR images. Medical Engineering &
- 311 Physics 34, 17–27.
- Wells, P.N.T., Liang, H.-D., 2011. Medical Ultrasound: Imaging of Soft Tissue Strain and Elasticity. J. R. Soc.
- 313 Interface 8, 1521–1549.
- Wesly, R.L., Vaishnav, R.N., Fuchs, J.C., Patel, D.J., Greenfield, J.C., 1975. Static Linear and Nonlinear Elastic
- Properties of Normal and Arterialized Venous Tissue in Dog and Man. Circulation Research 37, 509–520.
- 316 Wildin, C.J., Hui, A.C.W., Esler, C.N.A., Gregg, P.J., 1998. In vivo pressure profiles of thigh-length graduated
- 317 compression stockings. British Journal of Surgery 85, 1228–1231.
- 318 Yeung, K.W., Li, Y., Zhang, X., 2004. A 3D Biomechanical Human Model for Numerical Simulation of
- 319 Garment–Body Dynamic Mechanical Interactions During Wear. Journal of the Textile Institute 95, 59–79.
- 320 Zhao, J., Jesper Andreasen, J., Yang, J., Steen Rasmussen, B., Liao, D., Gregersen, H., 2007. Manual pressure
- 321 distension of the human saphenous vein changes its biomechanical properties—implication for coronary
- artery bypass grafting. Journal of Biomechanics 40, 2268–2276.

List of figures

Figure 1	Acquisition of Echographic images both in the standing and supine position (1a and 1b). A special precaution was taken as illustrated in figure 1c.
Figure 2	Finite element mesh of the 2D patient specific mesh. It consists of continuum plane strain elements for the muscle, fat and vein wall and truss elements for the muscular aponeurosis, skin and MCS. A relatively finer discretisation is used in the vicinity of the vein wall. The thickness-to-radius ratio of the vein is taken as 0.1, as reported in the literature.

List of tables

Table 1	Material properties of the different constitutive parts of the model
Table 2	Default ABAQUS parameters used for the simulation (Hibbitt, 2009)

Table A1	Influence of the ratio of adipose tissue to leg size. The thickness of the adipose tissue has been modified during the segmentation step to account for different morphologies of subcutaneous adipose tissue (Reference configuration and geometries 1, 2 and 3 hereunder). The results show that the amount of adipose tissue has a negligible influence both on the decrease in the vein cross-section and on the decrease in trans-mural pressure.
Table A2	Influence of the position of the vein on the leg contour. The vein is placed at different positions on the leg contour (Reference configuration and geometries 1, 2 and 3 hereunder). The maximum values of decrease in trans-mural pressure, percentage circumferential stretch ratio and increase in hydrostatic pressure in fat, are obtained when the radius of curvature is the smallest. These results confirm that the performance of the MCS is correlated to the local radius of curvature of the leg.
Table A3	Influence of the cross-sectional area of the vein. Different veins are generated from the segmented geometry of the vein in vivo by doing a dilation of the semi-minor and semi-major axes respectively. The centre of dilation is taken as the centre of the vein and the scaling factor as 0.7, 0.5 and 0.2 respectively (Reference configuration and geometries 1, 2 and 3 hereunder). The results show that MCS have a slightly more important effect as the cross section decreases, but overall the numerical values are very close. A more pronounced effect is obtained in the supine position.
Table A4	Influence of the depth of the vein in the adipose tissue. New geometries are obtained by translating the vein in the direction of the skin or, on the contrary, closer to the muscular aponeurosis (Reference configuration and geometries 1, 2 and 3 hereunder). Almost no effect is obtained in the supine position. In the standing position, however, the benefit on the decrease in trans-mural pressure due to external compression, slightly but steadily increases (as) when the vein is closer to the skin.
Table A5	Influence of the external compression applied. The stiffness of the sock used in the reference model is multiplied by a constant of proportionality (i.e. 1, 2 and 3). The mean contact pressure delivered for each case is reported below. Results show a fine linear relationship between the mean contact pressure and the response of the leg. We observe moreover that the response is different in the standing and supine position, except for the mean increase in hydrostatic pressure in fat.
Table A6	Influence of the stiffness of the fat. Different "types" of fat are modelled by changing C_{10} . The values are taken in the range 3-8 kPa C_{10} . Results are reported hereunder. The main result is the significant influence of this parameter on the percentage compression of the vein in the supine position and the quasi-insignificant influence in the standing position.
Table A7	Influence of the compressibility of the fat. Different "types" of fat are modelled by changing D_1 . The values are taken in the range $0.005\text{-}10~\text{MPa}^{-1}$. Results are reported hereunder. Almost no effect is obtained either in the supine or standing positions.
Table A8	Influence of the constitutive behaviour law used to model the vein wall. Two types of behaviour laws were compared (i) bi-linear elastic and (ii) Neo-Hookean hyperelastic material model. Only weak differences are observed in the results.
Table A9	Influence of the element type used for the Finite Element mesh. Three aspects were considered (i) hybrid formulation of the elements (ii) reduced integration of these and (iii) geometric order (linear/quadratic). Results show that the choice of element formulation does not affect key conclusions of the study derived from the modelling

	results.
Table A10	Influence of the contact formulation for the Fat/Vein interface (Fat/Vein). Two aspects of the contact specifications were considered: (i) normal and (ii) tangential behaviour of the contact interaction properties. Both "hard" and "soft" constraint methods were investigated for enforcing the contact pressure-overclosure relationship (normal direction). Furthermore, a tie constraint (each node on the slave surface is constrained to have the same motion as the point on the master surface to which it is closest) was also investigated in place of the contact interaction. Results show minor changes.
Table A11	Influence of the contact formulation for the Fat/Muscle interface (Fat/Muscle). The same contact conditions were investigated. Very little change was observed.
Table A12	Influence of the contact formulation for the Skin/MCS interface (Skin/MCS). Results show that the "softened" contact algorithms available in ABAQUS/Standard (and subsequently retained as a constraint method for enforcing the contact pressure-overclosure relationship) performed better than the "hard" contact algorithms. The main advantage of the "softened" contact algorithms is that clearance is calculated from surface to surface instead of from node to surface. As a consequence, the contact load is evenly distributed along the interacting surfaces.




Figure 1. Acquisition of echographic images both in the standing and supine position (a and b). A special precaution was taken as illustrated in panel c.




Figure 2: Finite element mesh of the 2D patient specific mesh. It consists of continuum plane strain elements for the muscle, fat and vein wall and truss elements for the muscular aponeurosis, skin and MCS. A relatively finer discretisation is used in the vicinity of the vein wall. The thickness-to-radius ratio of the vein is taken as 0.1, as reported in the literature.

Simulation element	ABAQUS parameters used									
Truss elements	Truss cross-sectional area = 1.0 mm ²									
Contact pairs (for surfaces in contact)	Contact algorithm: pure master-slave contact									
	Tangential Behaviour:									
	Friction formulation=PENALTY,									
	Behaviour independent of slip rate, pressure and temperature,									
	riction coefficient = 0.3									
	Normal Behaviour :									
Contact between	Contact pressure-overclosure relationship= EXPONENTIAL (SOFT),									
Skin and textile	This means that the contact pressure transmitted between the two									
	interacting surfaces increases exponentially as the clearance between them,									
	measured in the contact (normal) direction, diminishes (starting from a user-									
	defined threshold value).									
	eparation of the surfaces is not allowed									
	Constraint Enforcement Method= PENALTY									
	Tangential Behaviour : FRICTIONLESS									
	Normal Behaviour:									
Contact fat-muscle	Contact pressure-overclosure relationship= EXPONENTIAL									
	Separation of the surfaces is not allowed									
	Constraint enforcement method= AUGMENTED_LAGRANGE									
Constraint between										
surfaces :-	Type of constraint : TIE									
-1- Bone-Fat	Tie constraint means that each node on the slave surface is constrained to									
-2- Bone-Muscle	have the same motion as the point on the master surface to which it is closest									
-3- Fat-Vein	Slave surfaces are adjusted so that surfaces are in contact									
-4- Aponeurosis-Muscle	Rotational DOF are also tied									
-5- Skin-Fat										
	Implicit resolution									
	Maximum number of steps allowed = 100									
	Initial increment time step size = 1.0s									
	Minimum increment time step size = 1e-5s									
Steps of the FE analysis	Maximum increment time step size = 1.0s									
(steps 1 to 3)	Nlgeom=ON									
	Solution technique = Full Newton									
	Equation solver = Direct (i.e. the solver finds the exact solution (up to									
	machine precision) of the set of linear equations obtained at each iteration of									
	the Newton method. It uses a sparse, direct, Gauss elimination method)									

Table 1: Default ABAQUS parameters used for the simulation (Hibbitt, 2009).

Material	Model	Material parameters	Source
Fat	Hyper-elastic Neo-Hookean	$C_{10} = 0.005 \text{ MPa}$ $D_1 = 0.14 \text{ MPa}^{-1}$	Inverse identification (Dubuis et al., 2011) (Avril et al., 2010)
Muscle	Hyper-elastic Neo-Hookean	$C_{10} = 0.003 \text{ MPa}$ $D_1 = 0.14 \text{MPa}^{-1}$	(Dubuis et al., 2011) (Avril et al., 2010)
Skin	Hyper-elastic Neo-Hookean	$C_{10} = 0.1 \text{ MPa}$ $D_1 = 0.14 \text{ MPa}^{-1}$	(Iivarinen et al., 2011) (Hendriks et al., 2006)
Muscular aponeurosis	Hyper-elastic Neo-Hookean	$C_{10} = 10 \text{ MPa}$ $D_1 = 80 \text{ MPa}^{-1}$	(Wu, 2007)
Vein wall	Linearized (in standing and resting positions respectively)	ν = 0.49 (fixed)	Inverse identification
MCS	Linear elastic	E = 0.39 v = 0.49	SIGVARIS tensile test on 15- 20 mmHg MCS and based on the French norm NF- G30-102 (AFNOR, 1986)

Table 2: Material properties of the different constitutive parts of the model.

Morphology of adipose tissue		C	0							6							
Note: all pressures given in mmHg	Referen	ce config			Geomet	ry1			Geomet	ry2			Geometry3				
	Supine		Standin	g	Supine		Standin	ıg	Supine		Standin	g	Supine	Standing			
Percentage circumferential reduction of the vein lumen	10.0		3.2		10.1		3.3		10.2		3.3		10.3		3.3		
Average contact pressure at skin-sock interface	17.3	±5.3	17.4	±5.8	17.3	±5.4	17.3	±6.0	17.4	±5.8	17.4	±6.1	17.4	±5.5	17.4	±6.0	
Mean trans-mural pressure in vein wall before EC	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.1	±5.5	11.0	±1.1	67.1	±5.7	11.0	±1.1	67.1	±6.0	
Mean decrease of trans-mural pressure in vein wall due to EC	4.8	±2.5	12.3	±11.1	4.8	±2.7	12.2	±11.7	5.0	±2.5	12.6	±11.0	4.9	±2.6	12.5	±11.3	
Mean increase in hydrostatic pressure in fat due to EC	19.8	±3.7	19.9	±6.6	19.7	±3.7	19.5	±6.4	19.6	±3.6	19.8	±5.8	19.2	±3.5	19.5	±5.7	
Maximum hydrostatic pressure in fat	29.0		39.3		32.8		44.0		41.2		43.8		29.9		39.3		

Table A1: Ratio of adipose tissue to leg size

Position of the vein on the leg contour		C				C				6								
Note : all pressures given in mmHg	Referen	Geomet	ry1			Geomet	ry2			Geometry3								
	Supine		Standin	g	Supine		Standin	g	Supine		Standin	g	Supine			Standing		
Percentage circumferential reduction of the vein lumen	10.0		3.2		11.0		3.5		12.3		4.0		10.7		4.0			
Average contact pressure at skin-sock interface	17.3	±5.3	17.4	±5.8	17.3	±5.4	17.3	±6.0	17.4	±5.8	17.4	±6.1	17.5	±5.5	17.4	±6.1		
Mean trans-mural pressure in vein wall before EC	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.1	±5.4	11.0	±1.1	67.2	±5.6	11.0	±1.1	67.2	±5.6		
Mean decrease of trans-mural pressure in vein wall due to EC	4.8	±2.5	12.3	±11.1	5.3	±2.1	13.2	±11.2	6.0	±3.5	14.9	±12.0	5.1	±2.9	14.9	±12.0		
Mean increase in hydrostatic pressure in fat due to EC	19.8	±3.7	19.9	±6.6	21.4	±4.8	20.6	±7.0	23.1	±5.9	22.2	±7.1	21.1	±4.7	22.2	±7.1		
Maximum hydrostatic pressure in fat	29.0		39.3		48.0		48.0		42.9		54.9		42.7		54.9			

Table A2: Position on the leg contour

		9		0		0		0									
Initial vein c/s of vein lumen (in mm2)	21.9				11.2				5.9				1.0				
Note: all pressures given in mmHg	Referen	ce confi	guration		Geomet	ry1			Geomet	ry2			Geometry3				
	Supine Standing			Supine		Standing	3	Supine		Standing	g	Supine Standing					
Percentage circumferential reduction of the vein lumen	10.0		3.2		10.3		3.4		10.4		3.5		10.6		3.6		
Average contact pressure at skin-sock interface	17.3	±5.3	17.4	±5.8	17.3	±5.5	17.4	±5.7	17.3	±5.6	17.3	±5.8	17.3	±5.7	17.3	±5.7	
Mean trans-mural pressure in vein wall before EC	11.0	±1.1	67.2	±5.4	8.8	±0.7	63.5	±4.6	7.5	±0.6	61.2	±4.3	5.5	±0.4	57.6	±4.1	
Mean decrease of trans-mural pressure in vein wall due to EC	4.8	±2.5	12.3	±11.1	5.3	±2.3	12.4	±9.7	5.6	±2.3	12.4	±8.9	5.9	±2.6	12.4	±8.5	
Mean increase in hydrostatic pressure in fat due to EC	19.8	±3.7	19.9	±6.6	20.5	±3.7	20.5	±5.6	20.6	±3.8	20.9	±5.2	20.8	±3.5	21.1	±4.0	
Maximum hydrostatic pressure in fat	29.0		39.3		29.7		36.3		33.4		36.2		33.6		34.1		

Table A3: Vein lumen size




Table A4: Depth of vein in adipose tissue

Mean external compression applied on skin (mmHg)	17.4				34.7				52.0				69.4			
Note: all pressures given in mmHg	Reference configuration			Configu			Configu	ration 2			Configuration 3					
	Supine		Standin	g	Supine		Standir	ıg	Supine Standing			g	Supine		Standing	
Percentage circumferential																
reduction of the vein lumen	10.0		3.2		16.8		5.7		22.4		7.9		27.4		10.0	
Average contact pressure at skin-sock interface	17.3	±5.3	17.4	±5.8	34.7	±9.3	34.7	±9.8	52.0	±12.9	52.0	±13.4	69.3	±16.6	69.4	±17.2
Mean trans-mural pressure in vein wall before EC	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.2	±5.4
Mean decrease of trans-mural pressure in vein wall due to EC	4.8	±2.5	12.3	±11.1	10.1	±4.5	23.7	±10.3	16.0	±8.3	34.8	±9.3	22.1	±14.4	45.8	±8.6
Mean increase in hydrostatic pressure in fat due to EC	19.8	±3.7	19.9	±6.6	37.2	±6.3	38.3	±7.7	54.3	±9.2	56.2	±8.6	71.2	±12.8	73.7	±9.7
Maximum hydrostatic pressure in fat	29.0		39.3		57.6		59.8		91.0		91.1		123.7		119.9	

Table A5: Effect of the applied external compression

C ₁₀ Fat (kPa)	3				5				6				7.5			
Note : all pressures given in mmHg	Configuration 1			Referen	ce config	guration		Configu	ration 2			Configuration 3				
	Supine		Standin	g	Supine		Standin	ıg	Supine		Standin	g	Supine		Standin	g
Percentage circumferential																
reduction of the vein lumen	12.2		3.3		10.0		3.2		9.2		3.1		8.3		3.0	
Average contact pressure at																
skin-sock interface	17.3	±4.9	28.7	±10.0	17.3	±5.3	17.4	±5.8	17.4	±5.5	17.4	±5.9	17.4	±5.7	17.3	±6.2
Mean trans-mural pressure in																
vein wall before EC	11.0	±1.1	67.3	±5.4	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.2	±5.4
Mean decrease of trans-mural pressure in vein wall due to																
EC EC	6.4	±2.4	12.9	±10.9	4.8	±2.5	12.3	±11.1	4.3	±2.6	11.9	±11.1	3.7	±2.6	11.4	±11.2
Mean increase in hydrostatic																
pressure in fat due to EC	18.7	±3.0	19.1	±5.9	19.8	±3.7	19.9	±6.6	20.3	±4.1	20.2	±6.8	20.9	±4.7	20.5	±7.1
Maximum hydrostatic																
pressure in fat	27.6		36.1		29.0		39.3		29.9		40.4		32.1		42.4	

Table A6: Influence of the "type" of fat for the stiffness

D ₁ Fat (MPa ⁻¹)	0.005				0.14				1				10			
Note : all pressures given in mmHg	Configuration 1			Referen	ce config	guration		Configu	ration 2			Configuration 3				
	Supine		Standin	g	Supine		Standin	ıg	Supine		Standin	g	Supine		Standin	g
Percentage circumferential																
reduction of the vein lumen	10.0		3.2		10.0		3.2		10.0		3.2		10.0		3.2	
Average contact pressure at																
skin-sock interface	17.4	±5.4	17.4	±5.9	17.3	±5.3	17.4	±5.8	17.4	±5.4	17.3	±5.8	17.3	±5.3	17.3	±5.4
Mean trans-mural pressure in																
vein wall before EC	11.0	±1.1	67.4	±5.4	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.2	±5.4
Mean decrease of trans-mural pressure in vein wall due to																
EC EC	4.8	±2.5	12.2	±11.1	4.8	±2.5	12.3	±11.1	4.8	±2.5	12.3	±11.1	4.7	±2.7	12.0	±11.2
Mean increase in hydrostatic																
pressure in fat due to EC	19.8	±3.8	19.9	±6.6	19.8	±3.7	19.9	±6.6	19.6	±3.7	19.8	±6.6	18.4	±3.6	18.4	±6.1
Maximum hydrostatic																
pressure in fat	29.1		39.1		29.0		39.3		28.5		38.9		26.4		36.1	

Table A7: Influence of the "type" of fat for the incompressibility parameter

Constitutive behaviour law for the vein wall	Bi-linea	r elastic	model		Neo-Hookean material behaviour law						
Note: all pressures given in mmHg	Referen	ce config	guration								
	Supine		Standin	ıg	Supine		Standing				
Percentage circumferential											
reduction of the vein lumen	10.0		3.2		9.8		3.2				
Average contact pressure at skin-sock interface	17.3	±5.3	17.4	±5.8	17.3	±5.3	17.3	±5.8			
Mean trans-mural pressure in vein wall before EC	11.0	±1.1	67.2	±5.4	11.0	±1.3	67.1	±6.6			
Mean decrease of trans-mural pressure in vein wall due to EC	4.8	±2.5	12.3	±11.1	5.3	±2.7	12.2	±12.4			
Mean increase in hydrostatic pressure in fat due to EC	19.8	±3.7	19.9	±6.6	19.8	±3.7	19.9	±6.5			
Maximum hydrostatic pressure in fat	29.0		39.3		29.0		39.2				

Table 8A:

Element type used for the FE mesh	Normal (CPE4, (Reduce (CPE4R			Hybrid f reduced (CPE4R)	integra		I)	Geometric order: Quadratic elements used instead of linear elements (CPE8, CPE6, T2D3)						
Note : all pressures given in mmHg	Supine	Standin					Referen	ce confi	guration Standin	g	Supine		Standin	g		
Percentage circumferential reduction of the vein lumen	10.0		3.2		10.0		3.2		10.0		3.2		10.0		3.2	
Average contact pressure at skin-sock interface	17.3	±5.3	17.3	±5.8	17.3	±5.3	17.3	±5.8	17.3	±5.3	17.4	±5.8	17.6	±6.0	17.6	±6.4
Mean trans-mural pressure in vein wall before EC	10.9	±1.1	67.1	±5.8	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.2	±5.4	14.5	±1.2	88.3	±6.7
Mean decrease of trans-mural pressure in vein wall due to EC	5.9	±2.7	14.8	±13.1	4.8	±2.5	12.3	±11.1	4.8	±2.5	12.3	±11.1	6.3	±3.1	16.1	±13.0
Mean increase in hydrostatic pressure in fat due to EC	19.8	±3.8	19.9	±6.6	19.8	±3.7	19.9	±6.6	19.8	±3.7	19.9	±6.6	20.6	±16.6	20.4	±17.6
Maximum hydrostatic pressure in fat	29.2		39.6		29.1		39.2		29.0		39.3		286.0		285.7	

Table A9

Contact formulation for the interface Fat/Vein								contact	pressur	" contact e-overclo		Friction - Exponential ("Soft") contact pressure-overclosure relationship				
	Tie cons	straint			Friction			relation	ship							
Note: all pressures given in mmHg	Referen	ce confi	guration													
	Supine		Standin	g	Supine		Standin	g	Supine		Standin	g	Supine		Standin	g
Percentage circumferential reduction of the vein lumen	9.9		3.1		10.1		3.2		10.1		3.1		10.1		3.2	
Average contact pressure at skin-sock interface	17.3	±5.3	17.4	±5.8	17.3	±5.3	17.4	±5.8	17.3	±5.3	17.4	±5.8	17.3	±5.3	17.4	±5.8
Mean trans-mural pressure in vein wall before EC	11.0	±1.1	67.2	±5.4	10.8	±1.1	67.2	±5.4	10.9	±1.1	67.2	±5.4	9.8	±0.9	64.6	±5.1
Mean decrease of trans-mural pressure in vein wall due to EC	4.7	±2.5	12.0	±11.0	5.2	±2.3	12.8	±12.0	5.1	±1.9	12.4	±11.3	5.6	±1.6	12.7	±10.6
Mean increase in hydrostatic pressure in fat due to EC	19.5	±3.7	19.7	±6.5	19.9	±4.8	20.0	±4.9	19.8	±4.5	19.8	±5.5	20.0	±4.6	20.1	±5.6
Maximum hydrostatic pressure in fat	36.5		39.4		35.2		35.6		34.9		37.0		29.8		38.0	

Table A10

Contact formulation for the interface Fat/Muscle	Tie cons		Friction	ıless				pressur	' contact e-overclo		Friction - Exponential ("Soft") contact pressure-overclosure relationship					
Note: all pressures given in mmHg													Reference configuration			
	Supine	Standin	Supine		Standin	g	Supine		Standin	ıg	Supine		Standing			
Percentage circumferential reduction of the vein lumen	9.9		3.2		10.0		3.0		9.9		3.1		10.0		3.2	
Average contact pressure at skin-sock interface	17.3	±5.3	17.4	±5.8	17.3	±5.3	17.4	±5.8	17.3	±5.3	17.4	±5.8	17.3	±5.3	17.4	±5.8
Mean trans-mural pressure in vein wall before EC	11.0	±1.1	67.3	±5.4	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.2	±5.4
Mean decrease of trans-mural pressure in vein wall due to EC	4.8	±2.5	12.3	±11.1	4.6	±2.6	11.1	±11.2	4.7	±2.5	12.0	±11.0	4.8	±2.5	12.3	±11.1
Mean increase in hydrostatic pressure in fat due to EC	19.6	±4.3	20.0	±7.0	19.4	±3.6	18.7	±6.4	19.5	±3.7	19.7	±6.5	19.8	±3.7	19.9	±6.6
Maximum hydrostatic pressure in fat	39.7		39.5		31.8		38.8		36.5		39.4		29.0		39.3	

Table A11

Contact formulation for the interface Skin/MCS	Tie constraint			pressure	' contact e-overclo	sure	Friction - Exponential ("Soft") contact pressure-overclosure relationship							
Note : all pressures given in mmHg											Reference configuration			
	Supine	Standing	Supine		Standin	ıg	Supine		Standing		Supine		Standin	g
Percentage circumferential reduction of the vein lumen			10.0		3.0		9.9		3.1		10.0		3.2	
Average contact pressure at skin-sock interface			17.3	±5.3	17.4	±5.8	18.8	±23.3	18.8	±23.5	17.3	±5.3	17.4	±5.8
Mean trans-mural pressure in vein wall before EC	Not relevant be the leg is done the contact bet	-	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.2	±5.4	11.0	±1.1	67.2	±5.4
Mean decrease of trans-mural pressure in vein wall due to EC	and the skin		4.6	±2.6	11.1	±11.2	4.7	±2.5	12.0	±11.0	4.8	±2.5	12.3	±11.1
Mean increase in hydrostatic pressure in fat due to EC			19.4	±3.6	18.7	±6.4	19.5	±3.7	19.7	±6.5	19.8	±3.7	19.9	±6.6
Maximum hydrostatic pressure in fat			31.8		38.8		36.5		39.4		29.0		39.3	

Table A12