



Vibro-acoustic simulation of a car window

Christophe Barras

► To cite this version:

Christophe Barras. Vibro-acoustic simulation of a car window. Acoustics 2012, Apr 2012, Nantes, France. hal-00810759

HAL Id: hal-00810759

<https://hal.science/hal-00810759>

Submitted on 23 Apr 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



ACOUSTICS 2012

Vibro-acoustic simulation of a car window

C. Barras


Hutchinson Centre de Recherche, rue Gustave Nourry, BP 31, 45120 Chalette-Sur-Loing,
France
christophe.barras@cdr.hutchinson.fr



Teaming **up** for comfort and safety®

CONTENT

- Introduction
- Acoustic transparency phenomenon
- 3D finite elements model
 - Acoustic excitation
 - Power evaluation
- Parameter study
- Conclusions

HUTCHINSON





Acoustic excitation

Diffused field :
- same probability for every directions of plane waves

incidence (θ)	number of azimuthal waves (q)	weighting of wave
0	1	0.2704
17.5	6	0.3095
35	10	0.3311
52.5	15	0.3180
70	18	0.3159

Total waves | 50

HUTCHINSON

Acoustic excitation

Diffused field :
- same probability for every directions of place waves



Real life measurement :
- truncation of some waves (wall proximity)



Glass thickness of 3.85 mm

Legend: Ondes planes tronquées à 70° (Blue line with crosses), Champ diffus (Black line with dots), Mesures (Green line with triangles).

→ Truncation of waves gives higher TL

HUTCHINSON





Teaming up for comfort and safety®

KEY POINTS

1. 3D finer mesh
2. Representative excitation
3. Computed of transmitted power at 10cm above glass

CONCLUSION

Validated and reliable model that can be used for:

- sensitivity studies on parameters such as thickness of the glass, design of the glass run channel
- comparison and ranking of different designs by simulation, allowing less prototypes and measurements

HUTCHINSON 