



Nonlinear ultrasound parameter measurement for clay suspended particles characterization

Hicham Jakjoud, Ahmed Chitnalah, Noureddine Aouzale, Hanane Soucrati

► To cite this version:

Hicham Jakjoud, Ahmed Chitnalah, Noureddine Aouzale, Hanane Soucrati. Nonlinear ultrasound parameter measurement for clay suspended particles characterization. Acoustics 2012, Apr 2012, Nantes, France. hal-00811345

HAL Id: hal-00811345

<https://hal.science/hal-00811345>

Submitted on 23 Apr 2012

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



ACOUSTICS 2012

Nonlinear ultrasound parameter measurement for clay suspended particles characterization

H. Jakjoud, A. Chitnalah, N. Aouzale and H. Soucrati

Laboratory of Electrical Sciences and Technology, Faculty of Sciences and Technology, 40000
Marrakech, Morocco
hicham.jakjoud@gmail.com

Nonlinear ultrasound parameter measurement for clay suspended particles characterization

H. Jakjoud, A. Chitnalah, N. Aouzale, H. Soucouri

Laboratoire des Systèmes Electriques et Télécommunications

Université Cadi Ayyad Marrakech

Finite amplitude insert substitution method is used to measure the nonlinear ultrasound parameter in clay particles suspended in water. The analytical expressions of the fundamental and the second harmonic are obtained by integrating the KZK equation in multilayer structure using the quasi-linear assumption and a set of Gaussian beams. In order to validate the technique, measurements are performed in methanol and Glycerol. The results fit well with literature ones. Then we used this technique to investigate a sample of water with clay particles. The sample is filled out into a slice layer and inserted into a well known medium orthogonally to the propagation direction. The concentration of particles ranges from 10g/l to 50g/l. The celerity, the absorption and the nonlinear coefficient are measured. We noted that the nonlinear ultrasound parameter shows a linear variation within the clay's particles concentration and it shows a good sensibility.