



Fiber-based broadband black-light source

Thibaut Sylvestre, Min Won Lee, A. R. Raguer, Birgit Stiller, Gil Fanjoux, B. Barviau, Arnaud Mussot, Alexandre Kudlinski

► To cite this version:

Thibaut Sylvestre, Min Won Lee, A. R. Raguer, Birgit Stiller, Gil Fanjoux, et al.. Fiber-based broadband black-light source. The 7th International conference on Photonics and Applications (ICPA-7), Jan 2012, Vietnam. pp.A - 41. hal-00833003

HAL Id: hal-00833003

<https://hal.science/hal-00833003>

Submitted on 11 Jun 2013

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Fibre-Based Broadband Black Light Source

(Invited paper)

T. Sylvestre¹, M. W. Lee¹, A. R. Ragheb¹, B. Stiller¹, G. Fanjoux¹,
B. Barviau², A. Mussot² and A. Kudlinski²

¹ FEMTO-ST Institute, CNRS 6174, Université de Franche-Comté, Besançon, France

² PhLAM, Université de Lille 1, CNRS 8523, IRCICA, Villeneuve d'Ascq, France

Email address: thibaut.sylvestre@univ-fcomte.fr

Abstract.

Black-Light or Wood's lamp refers to sources that emit long-wavelength ultraviolet radiation (UV-A) from 315 nm and little visible light till 410 nm (blue). In this paper, we present a new fibre-based source of "black light", a source that emits broadband ultraviolet radiation but only small amounts of visible light and no infrared light. We made this source by pumping a specially designed silica photonic crystal fibre (PCF) with 355 nm light pulses from a Q-switched frequency-tripled Nd:YAG laser. Four-wave mixing and cascaded Raman generation combine in the fibre to provide a supercontinuum output that spans from around 350 nm to 390-470 nm, with the exact spectral width dependent on the pump power, as shown in Fig. 1. This broadband black-light source can find potential applications for diagnostic and therapeutic uses in medicine and in dermatology, for the detection of substances tagged with fluorescents and minerals, for counterfeit money, for absorption spectroscopy, and for military applications [1,2].




Fig. 1. Output spectra for increasing input power from 0.5 to 4 mW showing black-light continuum generation from 350 nm up to the blue at 470 nm in a 30 m-long silica PCF pumped at 355-nm with 300-ps Q-switched pulses. The inset shows the optical mode output.

References

- [1] T. Sylvestre *et al.* "Black-light continuum generation in a silica-core photonic crystal fiber," Opt. Lett. **37**, 130-132 (2012).
- [2] O. Graydon, Nature Photonics **6**, 138 (2012).