

The problem of detecting corrosion by an electric measurement revisited

Mourad Choulli, Aymen Jbalia

▶ To cite this version:

Mourad Choulli, Aymen Jbalia. The problem of detecting corrosion by an electric measurement revisited. 2013. hal-00864869v2

HAL Id: hal-00864869 https://hal.science/hal-00864869v2

Preprint submitted on 15 Apr 2014 (v2), last revised 22 Sep 2015 (v3)

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

THE PROBLEM OF DETECTING CORROSION BY AN ELECTRIC MEASUREMENT REVISITED

†MOURAD CHOULLI AND ‡AYMEN JBALIA

ABSTRACT. We establish a logarithmic stability estimate for the problem of detecting corrosion by a single electric measurement. We give a proof based on an adaptation of the method initiated in [BCJ] for solving the inverse problem of recovering the surface impedance of an obstacle from the scattering amplitude. The key idea consists in estimating accurately a lower bound of the L^2 -norm, locally at the boundary, of the solution of the boundary value problem used in modeling the problem of detection corrosion by an electric measurement.

Key words: Logarithmic stability estimate, detecting corrosion, boundary measurement.

MSC: 35R30.

1. INTRODUCTION

Let Ω be a C^n -smooth bounded domain of \mathbb{R}^n , n = 2, 3. We denote its boundary by Γ and we consider the following boundary value problem (abbreviated to BVP in the sequel)

(1.1)
$$\begin{cases} \Delta u = 0 & \text{in } \Omega, \\ \partial_{\nu} u + q(x)u = g & \text{on } \Gamma. \end{cases}$$

We assume in the sequel that $g \in H^{n-3/2}(\Gamma)$ and g is non identically equal to zero.

For $s \in \mathbb{R}$ and $1 \leq r \leq \infty$, we introduce the vector space

$$B_{s,r}(\mathbb{R}^{n-1}) := \{ w \in \mathscr{S}'(\mathbb{R}^{n-1}); \ (1+|\xi|^2)^{s/2} \widehat{w} \in L^r(\mathbb{R}^{n-1}) \},\$$

where $\mathscr{S}'(\mathbb{R}^{n-1})$ is the space of temperate distributions on \mathbb{R}^{n-1} and \hat{w} is the Fourier transform of w. Equipped with its natural norm

$$||w||_{B_{s,r}(\mathbb{R}^{n-1})} := ||(1+|\xi|^2)^{s/2} \widehat{w}||_{L^r(\mathbb{R}^{n-1})},$$

 $B_{s,r}(\mathbb{R}^{n-1})$ is a Banach space (it is noted that $B_{s,2}(\mathbb{R}^{n-1})$ is merely the usual Sobolev space $H^s(\mathbb{R}^{n-1})$). By using local charts and a partition of unity, we construct $B_{s,r}(\Gamma)$ from $B_{s,r}(\mathbb{R}^{n-1})$ similarly as $H^s(\Gamma)$ is built from $H^s(\mathbb{R}^{n-1})$.

To carry out our analysis, we need solutions of the BVP (1.1) with some smoothness. In order to give sufficient conditions on the coefficient q guaranteeing this smoothness, we set

 $\mathcal{Q} = \{ q \in B_{n-1/2,1}(\Gamma); \ q \ge 0 \text{ and } q \not\equiv 0 \}$

and

$$\mathscr{Q}_M = \{ q \in \mathscr{Q}; \ \|q\|_{B_{n-1/2,1}(\Gamma)} \le M \},$$

where M > 0 is a given constant.

By Theorem 2.3 in [Ch1], observing that $B_{n-1/2,1}(\Gamma)$ is continuously embedded in $B_{n-3/2,1}(\Gamma)$, we obtain that, for any $q \in \mathcal{Q}$, the BVP (1.1) has a unique solution $u_q \in H^n(\Omega)$. Moreover,

(1.2)
$$\|u_q\|_{H^n(\Omega)} \le C \text{ for all } q \in \mathcal{Q}_M.$$

The constant C above can depend only on Ω , g and M.

Usually, in a BVP modeling the problem of detecting corrosion damage by electric measurements the boundary Γ consists in two parts: $\Gamma = \overline{\Gamma_a \cup \Gamma_i}$, Γ_a and Γ_i being two disjoint open subsets of Γ . Γ_a corresponds to the part of the boundary accessible to measurements and Γ_i is the inaccessible part of the boundary where the corrosion damage can occur.

Henceforth, we assume that the current flux g satisfies $\operatorname{supp}(g) \subset \Gamma_a$. The function q in (1.1) is known as the corrosion coefficient and it is naturally supported on Γ_i . This motivate the introduction of the following subset of \mathcal{Q}_M :

$$\mathscr{Q}_M^0 = \{ q \in \mathscr{Q}_M; \operatorname{supp}(q) \subset \Gamma_i \}.$$

We are interested in the stability issue for the problem consisting in the determination of the boundary coefficient q from the boundary measurement $u_{q|\gamma}$, where γ is an open subset of the accessible sub-boundary Γ_a . In the sequel, we assume that γ does not meet supp(g):

$$\gamma \subset \Gamma_a \setminus \operatorname{supp}(g).$$

We need to extend the usual notion of a starshaped domain. We say that D is mutiply-starshaped if there exists a finite number of points in D, say x_1, \ldots, x_k , such that

(i) $\cup_{i=1}^{k-1} [x_i, x_{i+1}] \subset D$,

(ii) any point in D can be connected by a line segment to at least one of the points x_i .

In this case, any two points in D can be connected by a broken line consisting of at most k + 1 line segments. Obviously, the case k = 1 corresponds to the usual definition of a starshaped domain.

Even if it is not always necessary, we assume in all of this text that Ω is multiplystarshaped and, for each $\tilde{x} \in \Gamma$, Γ is locally located at one side of the tangent plane $T_{\tilde{x}}$ to Γ at \tilde{x} . Precisely, to each $\tilde{x} \in \Gamma$, there is a neighborhood V of \tilde{x} such that

$$\Gamma \cap V \subset \{ x \in \mathbb{R}^n; \ (x - \widetilde{x}) \cdot \nu(\widetilde{x}) \le 0 \}.$$

The later definition means that Γ is convex at each of its points (corresponding to the definition in chapter 13, page 95 of [Th]). We notice that the convexity of Γ implies the convexity at each of its points, but the converse is not true in general.

We aim in the present work to prove the following theorem.

Theorem 1.1. There are three positive constants A, B and σ satisfying: for any $q \in \mathscr{Q}_{M}^{0} \cap C^{\alpha}(\Gamma)$, we find $\epsilon = \epsilon(q)$ so that for all $\tilde{q} \in \mathscr{Q}_{M}^{0} \cap C^{\alpha}(\Gamma)$ such that $\|q - \tilde{q}\|_{L^{\infty}(\Gamma_{i})} \leq \epsilon$,

$$\|q - \widetilde{q}\|_{L^{\infty}(\Gamma)} \le \frac{A}{\left|\ln\left|\ln\left(B\|u - \widetilde{u}\|_{L^{2}(\gamma)}\right)\right|\right|^{\sigma}}$$

with $u = u_q$ and $\tilde{u} = u_{\tilde{q}}$.

Theorem 1.1 can be seen as a completion of the results established in [CCL] in dimension two and in [BCC] in dimensions two and three. We note that in the above mentioned works the difference of $q - \tilde{q}$ is only estimated in a compact subset of $\{x \in \Gamma_i; u_q(x) \neq 0\}$. However, there is a counterpart in estimating $q - \tilde{q}$ in the whole Γ . The stability estimates in [CCL] and [BCC] are of single logarithmic type, while the estimate in Theorem 1.1 is of double logarithmic type.

There is a wide literature treating the problem of detecting corrosion by electric measurements. We refer to [ADR, CFJL, CJ, CCY, Ch2, Ch3, FI, In, Si2] where various type of stability estimate are given. We just quote these few references, but of course there are many others. A neighbor problem is the one consisting in the determination of the surface impedance of an obstacle from the scattering amplitude (e.g [ASV, BCJ, Si1] and the reference therein).

The rest of this text consists in two sections. In section 2 we estimate accurately a lower bound of the L^2 -norm, locally at the boundary, of the solution of the BVP (1.1). We show, step by step, how we adapt the method in [BCJ] to the present problem. Section 3 is devoted the proof of Theorem 1.1.

Unless otherwise specified, all the constants we use in the sequel depend only on data.

2. Lower bound for L^2 -norm at the boundary

We prove the following theorem.

Theorem 2.1. Let M > 0, there is c > 0 so that: for all $q \in \mathscr{Q}_M^0$ and $\widetilde{x} \in \Gamma$,

$$e^{-ce\,\overline{r}} \le \|u_q\|_{L^2(B(\widetilde{x},r)\cap\Gamma)}, \ 0 < r \le r^*,$$

where r^* is a constant that can depend on q.

We need some preliminary results before proving Theorem 2.1.

For sake of simplicity, we assume in the sequel that Ω is in addition starshaped. From the proof of Proposition 2.1 below, one can see that the extension to the case where Ω is multiply-starshaped is obvious.

For $\delta > 0$, we set

$$\Omega^{\delta} = \{ x \in \Omega; \, \operatorname{dist}(x, \Gamma) > \delta \}$$

and we recall the following useful three sphere inequality.

Lemma 2.1. There exist C > 0 and 0 < s < 1 so that: for all $u \in H^1(\Omega)$ satisfying $\Delta u = 0$ in Ω , $y \in \Omega$ and $0 < r < \frac{1}{3} dist(y, \Gamma)$,

$$\|u\|_{H^1(B(y,2r))} \le C \|u\|_{H^1(B(y,r))}^s \|u\|_{H^1(B(y,3r))}^{1-s}$$

Proposition 2.1. We assume that Ω is starshaped with respect to $x^* \in \Omega$ and we choose $\delta > 0$ such that $x^* \in \Omega^{\delta}$. Let M > 0, there are two constants c > 0 and $r_{\delta} > 0$ so that: for all $u \in H^1(\Omega)$ satisfying $\Delta u = 0$, $||u||_{H^1(\Omega)} \leq M$ and, $x, y \in \Omega^{\delta}$, we have

 $e^{-ce^{\frac{c}{r}}} \|u\|_{H^1(B(x,r))} \le \|u\|_{H^1(B(y,4r))}, \ 0 < r < r_{\delta}.$

¹We refer to [BCJ] for a proof. The case of a general divergence form operator is detailed in [CT].

Proof. We set

$$d_1 = |x - x^*|, \ \eta = \frac{x^* - x}{|x^* - x|}$$

and we consider the sequence, where $0 < 2r < d_1$,

$$x_k = x^* - k(2r)\eta, \quad k \ge 1.$$

Clearly,

$$|x_k - x| = d_1 - k(2r)$$

Let N_1 be the smallest integer such that $d_1 - N_1(2r) \leq r$, or equivalently

$$\frac{d_1}{2r} - \frac{1}{2} \le N_1 < \frac{d_1}{2r} + \frac{1}{2}$$

By Lemma 2.1, it follows that

(2.1)
$$\widetilde{C}r^t ||u||_{H^1(B(x_{N_1},2r))} \le ||u||_{H^1(B(y^*,2r))}^{s^{N_1}} \text{ with } t = \frac{1}{1-s}$$

Since $|y_{N_1} - x| = d_1 - N_1(2r) \le r$, $B(x_0, r) \subset B(y_{N_1}, 2r)$. Whence (2.1) entails

(2.2)
$$Cr^{t} \|u\|_{H^{1}(B(x,r))} \leq \|u\|_{H^{1}(B(x^{*},2r))}^{s^{N_{1}}}$$

The same argument between x^* and y gives

(2.3)
$$Cr^{t} \|u\|_{H^{1}(B(x^{*},r))} \leq \|u\|_{H^{1}(B(y,2r))}^{s^{N_{2}}}.$$

Here N_2 is defined by the relation

$$\frac{d_2}{2r} - \frac{1}{2} \le N_2 < \frac{d_2}{2r} + \frac{1}{2} \text{ with } d_2 = |y - x^*|.$$

A combination of (2.2) and (2.3) implies

$$(Cr)^{1+s^{N_1}} \|u\|_{H^1(B(x,r))} \le \|u\|_{H^1(B(y,4r))}^{s^{N_1+N_2}}.$$

Or equivalently

(2.4)
$$(Cr)^{\kappa} \|u\|_{H^1(B(x,r))} \le \|u\|_{H^1(B(y,4r))}$$

with

$$\kappa = \frac{1+s^{N_1}}{s^{N_1+N_2}}.$$

Henceforth, we assume that r is sufficiently small in such a way that Cr < 1 in (2.4). Letting $D = \operatorname{diam}(\Omega)$, we obtain by a direct computation

$$\kappa \le (1 + s^{-1/2})e^{\frac{2D|\ln s|}{r}}.$$

This estimate in (2.4) yields

$$e^{-ce\frac{\overline{r}}{r}} \|u\|_{H^1(B(x,r))} \le \|u\|_{H^1(B(y,4r))}$$

as it is the expected.

We recall that according to Caccioppoli's inequality, for all $u \in H^1(\Omega)$ satisfying $\Delta u = 0$ in Ω and $x \in \Omega$,

$$\|\nabla u\|_{L^2(B(x,r))^n} \le Cr^{-1} \|u\|_{L^2(B(x,2r))}$$

for a sufficiently small r.

Therefore the following corollary is immediate from Proposition 2.1.

4

Corollary 2.1. Under the assumptions of Proposition 2.1 and for M > 0, there are two constants c > 0 and $r_{\delta} > 0$ so that: for all $u \in H^1(\Omega)$ satisfying $\Delta u = 0$, $||u||_{H^1(\Omega)} \leq M$ and $x, y \in \Omega^{\delta}$,

$$e^{-cer} \|u\|_{H^1(B(x,r))} \le \|u\|_{L^2(B(y,8r))}, \quad 0 < r < r_{\delta}.$$

By an elementary continuity argument, we get from this corollary

Corollary 2.2. We fix $\eta > 0$ and M > 0. There is c > 0 with the property that, to any $u \in H^1(\Omega)$, satisfying

 $\Delta u = 0$, $\|u\|_{H^1(\Omega)} \leq M$ and there is $\hat{x} \in \Gamma$ such that $u \in C(B(\hat{x}, \hat{r}) \cap \Omega)$, for some $\hat{r} > 0$, and $|u(\hat{x})| \geq \eta$,

corresponds $\delta > 0$ and $r_{\delta} > 0$ for which, for all $y \in \Omega^{\delta}$,

$$e^{-ce^{\frac{c}{r}}} \le ||u||_{L^2(B(y,r))}, \ 0 < r < r_{\delta}.$$

Note here that δ and r_{δ} may depend also on u.

Now, because Γ is convex at each of its points and bearing in mind that Ω is located at one side of Γ , Ω has the uniform exterior ball property. That is, there is $\rho > 0$ so that, for all $\tilde{x} \in \Gamma$, we find $x' \in \mathbb{R}^n \setminus \overline{\Omega}$ such that

$$B(x',\rho) \cap \Omega = \emptyset$$
 and $\overline{B}(x',\rho) \cap \overline{\Omega} = \{\widetilde{x}\}.$

Let

(2.5)
$$\mathcal{B}(\widetilde{x},r) = B(x',\rho+r), \quad \widetilde{x} \in \Gamma.$$

Then, as a peculiar case of Corollary 3.1 in [BCJ], we have

Proposition 2.2. There exist two constants C > 0 and $0 < \gamma < 1/2$ so that, for any $0 < r \le D$ and $u \in H^2(\Omega)$ satisfying $\Delta u = 0$, the following estimate holds true (2.6) $Cr^2 \|u\|_{H^1(\mathcal{B}(\tilde{x}, \frac{r}{4})\cap\Omega)} \le \|u\|_{H^2(\Omega)}^{1-\gamma} (\|u\|_{L^2(\mathcal{B}(\tilde{x}, r)\cap\Gamma)} + \|\nabla u\|_{L^2(\mathcal{B}(\tilde{x}, r)\cap\Gamma)^n})^{\gamma}.$

As Ω is C^n -smooth, it has also the uniform interior cone property: there are R > 0 and $\theta \in]0, 2\pi[$ satisfying, for all $\tilde{x} \in \Gamma$, we find $\xi \in \mathbb{R}^n$ such that $|\xi| = 1$ and

 $\mathcal{C}(\widetilde{x}) = \{ x \in \mathbb{R}^n; \ |x - \widetilde{x}| < R \text{ and } (x - \widetilde{x}) \cdot \xi > |x - \widetilde{x}| \cos \theta \} \subset \Omega.$

We note that ξ can be chosen in the following form

$$\xi = \frac{\widetilde{x} - x'}{|\widetilde{x} - x'|},$$

where x' is the same as in the definition of uniform exterior ball property.

In other words, following the definition in [BCJ], Ω possesses the uniform exterior ball-interior cone property. Then a slight modification of the first part of the proof of Theorem 4.1 in [BCJ] yields

Proposition 2.3. We pick $\tilde{x} \in \Gamma$. Then, for sufficiently small r, we can choose $x_0 \in \Omega, y_0 \in \Omega$ two points in the line segment passing through \tilde{x} and directed by ξ such that $B(x_0, r/2) \subset \mathcal{B}(\tilde{x}, r) \cap \Omega$ and $B(y_0, \kappa r) \subset \Omega^{R/2}$, where κ is constant depending only on θ . Let M > 0, there are C > 0, $\eta > 1$, and $r^* > 0$, not depending on x_0 and y_0 , such that for all $u \in H^1(\Omega)$ satisfying $\Delta u = 0$ in Ω and $\|u\|_{H^1(\Omega)} \leq M$,

$$e^{-\frac{C}{r^{\eta}}} \|u\|_{H^{1}(B(y_{0},\kappa r))} \le \|u\|_{H^{1}(B(x_{0},r))}, \quad 0 < r \le r^{*}.$$

A combination of Corollary 2.2, Proposition 2.2 and Proposition 2.3 gives

Theorem 2.2. Let $\eta > 0$, M > 0 and $\hat{x} \in \Gamma$. There is a constant c > 0 such that for all $u \in H^2(\Omega)$ satisfying $\Delta u = 0$ in Ω , $|u(\hat{x})| \ge \eta$, $||u||_{H^2(\Omega)} \le M$ and $\tilde{x} \in \Gamma$,

$$e^{-ce\,\overline{\tau}} \le \|u\|_{H^1(\mathcal{B}(\widetilde{x},r)\cap\Gamma)} + \|\partial_\nu u\|_{L^2(\mathcal{B}(\widetilde{x},r)\cap\Gamma)}, \quad 0 < r \le r^*,$$

where r^* can depend on u.

For $\tilde{x} \in \Gamma$, pick $\psi \in C_0^{\infty}(\mathcal{B}(\tilde{x}, 2r))$ satisfying $\psi = 1$ in a neighborhood of $\mathcal{B}(\tilde{x}, r)$ and $|\partial^{\beta}\psi| \leq Cr^{-|\beta|}$ for any $\beta \in \mathbb{R}^n$, $|\beta| \leq 2$. Let $u \in H^2(\Omega)$. Using the interpolation inequality

$$\|\psi u\|_{H^{1}(\Gamma)} \leq C \|\psi u\|_{H^{3/2}(\Gamma)}^{2/3} \|\psi u\|_{L^{2}(\Gamma)}^{1/3}$$

together with the properties of ψ and the continuity of the trace operator $v \in H^2(\Omega) \to v_{|\Gamma} \in H^{3/2}(\Gamma)$, we get in a straightforward manner

(2.7)
$$\|u\|_{H^1(\mathcal{B}(\tilde{x},r)\cap\Gamma)} \leq Cr^{-4/3} \|u\|_{H^2(\Omega)}^{2/3} \|u\|_{L^2(\mathcal{B}(\tilde{x},2r)\cap\Gamma)}^{1/3}.$$

On the other hand, we claim that

(2.8)
$$\mathcal{B}(\widetilde{x},r) \cap \Gamma \subset B(\widetilde{x},2\rho r) \cap \Gamma.$$

Here $\mathcal{B}(\tilde{x}, r)$ is defined by (2.5).

Indeed, under a rigid transformation, it is enough to prove this inclusion when $\tilde{x} = 0, x' = (0, -\rho) \in \mathbb{R}^{n-1} \times \mathbb{R}, T_{\tilde{x}} = \{x_n = 0\}$ and Γ is located locally in $\{x_n \ge 0\}$. In that case, by an elementary calculation, we get

$$B(x', \rho + r) \cap \{x_n \ge 0\} \subset B(0, 2\rho r) \cap \{x_n \ge 0\}.$$

Clearly, this inclusion entails the following one

$$B(x', \rho + r) \cap \Gamma \subset B(0, 2\rho r) \cap \Gamma.$$

Therefore, in light of (2.7) and (2.8), a direct consequence of Theorem 2.2 is the following corollary.

Corollary 2.3. Let $\eta > 0$, M > 0 and $\hat{x} \in \Gamma$. There is a constant c > 0 so that for all $u \in H^2(\Omega)$ satisfying $\Delta u = 0$ in Ω , $|u(\hat{x})| \ge \eta$, $||u||_{H^2(\Omega)} \le M$ and $\tilde{x} \in \Gamma$,

$$e^{-ce\,\overline{r}} \le \|u\|_{L^2(B(\tilde{x},r)\cap\Gamma)} + \|\partial_{\nu}u\|_{L^2(B(\tilde{x},r)\cap\Gamma)}, \ 0 < r \le r^*,$$

where r^* can depend on u.

Moreover, if $|\partial_{\nu}u| \leq N|u|$ on Γ , for some constant N, then

$$e^{-ce\,\overline{r}} \le \|u\|_{L^2(B(\widetilde{x},r)\cap\Gamma)}, \quad 0 < r \le r^*.$$

We are now able to complete the proof of Theorem 2.1.

Proof of Theorem 2.1. We need to prove that there are $\hat{x} \in \Gamma$ and $\eta > 0$ for which $|u_q(\hat{x})| \geq \eta$ for any $q \in \mathscr{Q}_M^0$.

We fix Γ_0 an arbitrary nonempty open subset of $\Gamma \setminus \text{supp}(g)$. By Corollary 1 in [Bo], there is a constant A > 0 such that, for all $u \in H^2(\Omega)$ satisfying $\Delta u = 0$ and $\|u\|_{H^2(\Omega)} \leq M$, we have

(2.9)
$$||u||_{H^1(\Omega)} \le \frac{A}{\left|\ln(M^{-1}\delta)\right|^{1/2}},$$

where $\delta = ||u||_{H^1(\Gamma_0)} + ||\partial_{\nu}u||_{L^2(\Gamma_0)}.^2$

²Note that the smallness condition on δ in Corollary 1 in [Bo] can be easily removed.

Let Γ_1 be an open subset of Γ satisfying $\operatorname{supp}(g) \subset \Gamma_1 \Subset \Gamma$. Proceeding as before, we deduce from an usual interpolation inequality

$$\begin{aligned} \|g\|_{L^{2}(\Gamma_{a})} &= \|\partial_{\nu}u_{q}\|_{L^{2}(\Gamma_{1})} \leq C \|\partial_{\nu}u_{q}\|_{H^{-1/2}(\Gamma)}^{1/2} \|\partial_{\nu}u_{q}\|_{H^{1/2}(\Gamma)}^{1/2} \\ &\leq C \|u_{q}\|_{H^{1}(\Omega)}^{1/2} \|u_{q}\|_{H^{2}(\Omega)}^{1/2} \\ &\leq C \|u_{q}\|_{H^{1}(\Omega)}^{1/2}. \end{aligned}$$

This and (2.9) imply

$$||g||_{L^2(\Gamma_a)} \le \frac{C}{\left|\ln(M^{-1}\delta)\right|^{1/4}}, \text{ with } \delta = ||u_q||_{H^1(\Gamma_0)} + ||\partial_{\nu}u_q||_{L^2(\Gamma_0)},$$

or equivalently

$$\widetilde{\eta} = M e^{-C^4 \|g\|_{L^2(\Gamma_a)}^4} \le \|u_q\|_{H^1(\Gamma_0)} + \|\partial_{\nu} u_q\|_{L^2(\Gamma_0)}$$

Replacing Γ_0 by a smaller subset and proceeding as in the proof of Corollary 2.3, we get

(2.10)
$$\widetilde{\eta} = M e^{-c^4 \|g\|_{L^2(\Gamma_1)}^{-4}} \le \|u_q\|_{L^2(\Gamma_0)}.$$

Now since $H^n(\Omega)$ is continuously embedded in $C(\overline{\Omega})$, we derive from (2.10)

$$\eta = \widetilde{\eta} |\Gamma_0|^{-1/2} \le |u_q(\widehat{x})| = \max_{\overline{\Gamma_0}} |u_q|.$$

3. Proof of the stability estimate

First, we mimick the proof of Proposition 4.1 in [BCJ] to get that there are B > 0and $\sigma > 0$ satisfying: for any $q \in \mathscr{Q}_M^0$, we find $\epsilon(q) > 0$ so that, for any $f \in C^{\alpha}(\Gamma)$ with

$$[f]_{\alpha} = \sup\{|f(x) - f(y)| | x - y|^{-\alpha}; \ x, y \in \Gamma, \ x \neq y\} \le M$$

and $||f||_{L^{\infty}(\Gamma)} \leq \epsilon(q)$,

(3.1)
$$||f||_{L^{\infty}(\Gamma)} \leq \frac{B}{\left|\ln ||fu_q||_{L^{\infty}(\Gamma)}\right|^{\sigma}}$$

Proof of Theorem 1.1. Let $v = \tilde{u} - u$. Since $\Delta v = 0$, the same argument as in the proof of Theorem 2.1 yields

$$\|\partial_{\nu}v\|_{L^{2}(\Gamma)} \leq C \|v\|_{H^{1}(\Omega)}^{1/2}.$$

Hence,

(3.2)
$$\|v\|_{L^{2}(\Gamma)} + \|\partial_{\nu}v\|_{L^{2}(\Gamma)} \le C \|v\|_{H^{1}(\Omega)}^{1/2}$$

Let $\gamma_0 \Subset \gamma$. Again, by Corollary 1 in [Bo], there is a constant A > 0 for which

(3.3)
$$\|v\|_{H^1(\Omega)} \le \frac{A}{\left|\ln((2M)^{-1}\delta)\right|^{1/2}}$$

with $\delta = \|v\|_{H^1(\gamma_0)} + \|\partial_{\nu}v\|_{L^2(\gamma_0)}.$

As previously, we get by applying an interpolation inequality

$$\|v\|_{H^1(\gamma_0)} \le C \|v\|_{L^2(\gamma)}^{1/3},$$

and since $\partial_{\nu} v = 0$ on γ , (3.3) implies

(3.4)
$$\|v\|_{H^1(\Omega)} \le \frac{A}{\left|\ln(B\|v\|_{L^2(\gamma)})\right|^{1/2}}$$

In light of (3.2), (3.4) leads

(3.5)
$$\|v\|_{L^{2}(\Gamma)} + \|\partial_{\nu}v\|_{L^{2}(\Gamma)} \leq \frac{A}{\left|\ln(B\|v\|_{L^{2}(\gamma)})\right|^{1/4}},$$

Let $f = (q - \tilde{q})u$. We fix θ satisfying $2/3 < \theta < 1$ if n = 2 and $3/5 < \theta < 1$ if n = 3 and set $s = 3\theta/2$ for n = 2 and $s = 5\theta/2$ for n = 3. By this peculiar choice of s, $H^s(\Gamma)$ is continuously embedded in $L^{\infty}(\Gamma)$. Therefore, using the interpolation inequalities

$$\begin{split} \|f\|_{H^{s}(\Gamma)} &\leq C \|f\|_{H^{3/2}(\Gamma)}^{\theta} \|f\|_{L^{2}(\Gamma)}^{1-\theta} & \text{if } n = 2, \\ \|f\|_{H^{s}(\Gamma)} &\leq C \|f\|_{H^{5/2}(\Gamma)}^{\theta} \|f\|_{L^{2}(\Gamma)}^{1-\theta} & \text{if } n = 3, \end{split}$$

we obtain

$$\begin{split} \|f\|_{L^{\infty}(\Gamma)} &\leq C \|f\|_{H^{3/2}(\Gamma)}^{\theta} \|f\|_{L^{2}(\Gamma)}^{1-\theta} & \text{if } n = 2, \\ \|f\|_{L^{\infty}(\Gamma)} &\leq C \|f\|_{H^{5/2}(\Gamma)}^{\theta} \|f\|_{L^{2}(\Gamma)}^{1-\theta} & \text{if } n = 3, \end{split}$$

Or

$$\|f\|_{H^{n-1/2}(\Gamma)} = \|(q-\tilde{q})u\|_{H^{n-1/2}(\Gamma)} \le C \|q-\tilde{q}\|_{B_{n-1/2,1}(\Gamma)} \|u\|_{H^{n-1/2}(\Gamma)}.$$

Consequently,

(2, 0)

(3.6)
$$\|(q-\widetilde{q})u\|_{L^{\infty}(\Gamma)} \leq C \|(q-\widetilde{q})u\|_{L^{2}(\Gamma)}^{1-\theta}.$$

But

(3.7)
$$(q - \tilde{q})u = \partial_{\nu}v + \tilde{q}v.$$

Then a combination of (3.5), (3.6) and (3.7) yields

(3.8)
$$\|(q - \tilde{q})u\|_{L^{\infty}(\Gamma)} \le \frac{A}{\left|\ln(B\|v\|_{L^{2}(\gamma)})\right|^{(1-\theta)/4}},$$

In light of (3.1), we end up getting

$$\|q - \widetilde{q}\|_{L^{\infty}(\Gamma)} \leq \frac{A}{\left|\ln \left|\ln \left(B\|u - \widetilde{u}\|_{L^{2}(\gamma)}\right)\right|\right|^{\sigma}}.$$

References

- [ADR] G. ALESSANDRINI, L. DEL PIERO AND L. RONDI, Stable determination of corrosion by a single electrostatic boundary measurement, Inverse problems, 19 (4) (2003), 973-984.
- [ASV] G. ALESSANDRINI, E. SINCICH AND S. VESSELLA Stable determination of surface impedance on a rough obstacle by far field data, Inverse Problems and Imaging, 7 (2) (2013), 341-351.
- [BCJ] M. BELLASSOUED, M. CHOULLI and A. JBALIA, Stability of the determination of the surface impedance of an obstacle from the scattering amplitude, Math. Methods Appl. Sci. 36 (18) (2013) 2429-2448.
- [BCC] M. BELLASSOUED, J. CHENG and M. CHOULLI, Stability estimate for an inverse boundary coefficient problem in thermal imaging, J. Math Anal. Appl. 343 (2008) 328-336.
- [Bo] L. BOURGEOIS, About stability and regularization of ill-posed elliptic Cauchy problems: the case of C^{1,1} domains, Math. Model. Numer. Anal. 44 (4) (2010), 715-735.

- [CFJL] S. CHAABANE, I. FELLAH, M. JAOUA and J. LEBLOND, Logarithmic stability estimates for a robin coefficient in two-dimensional Laplace inverse problems, Inverse Problems 20, (2004), 47-59.
- [CJ] S. CHAABANE and M. JAOUA, Identification of Robin coefficients by means of boundary measurements, Inverse Problems 15, (1999), 1425-1438.
- [CCL] J. CHENG, M. CHOULLI and J. LIN, Stable determination of a boundary coefficient in an elliptic equation, M3AS 18 (1) (2008) 107-123.
- [CCY] J. CHENG, M. CHOULLI and X. YANG, An iterative BEM for the inverse problem of detecting corrosion in a pipe, Numer. Math. J. Chinese Univ. 14 (3) (2005) 252-266.
- [Ch1] M. CHOULLI, Stability estimates for an inverse elliptic problem, J. Inverse Ill-Posed Probl. 10 (6) (2002), 601-610.
- [Ch2] M. CHOULLI, An inverse problem in corrosion detection: stability estimates, J. Inverse Ill-Posed Probl. 12 (4) (2004), 349-367.
- [Ch3] M. CHOULLI, Une introduction aux problèmes inverses elliptiques et paraboliques, SMAI-Springer, Berlin, 2009.
- [CT] M. CHOULLI and F. TRIKI, On an inverse medium problem with internal data, preprint
- [FI] D. FASINO AND G. INGLESE, An inverse Robin problem for Laplaces's equation: theoretical and numerical methods, Inverse Problems 15 (1999), 41-48.
- [In] G. INGLESE, An inverse problem in corrosion detection, Inverse Problems 13 (1997), 977-994.
 [Si1] SINCICH, Stable determination of the surface impedance of an obstacle by far field measure
 - ments, SIAM J. Math. Anal., 38 (2) (2006), 434-451.
- [Si2] E. SINCICH, Lipschitz stability for the inverse Robin problem, Inverse Problems 23 (2007), 1311-1326.
- [Th] J. A. THORPE, Elementary topics in differential geometry, Springer-Velag, Belin, 1979.

†Institut Élie Cartan de Lorraine, UMR CNRS 7502, Université de Lorraine-Metz, Ile du Saulcy, F-57045 Metz cedex 1, France

E-mail address: mourad.choulli@univ-lorraine.fr

‡Faculté des Sciences de Bizerte, Département des Mathématiques, 7021 Jarzouna Bizerte, Tunisie

E-mail address: jbalia.aymen@yahoo.fr