

# **NOI 2013 – solutions to contest tasks.**

School of Computing  
National University of Singapore

Chang Ee-Chien

16 March 2013

# Scientific Committee

Chang Ee-Chien (chair)

Chin Zhan Xiong

Steven Halim

Harta Wijaya

Martin Henz

Raymond Kang

Ooi Wei Tsang

Frank Stephan

Wing-Kin Sung

Trinh Tuan Phuong

## Changes from previous years

- 1) Many subtasks. Constrains on each subtask explicitly stated.
- 2) Realtime feedback. “Realistic” input/output samples provided.

**TASK 1: GLOBAL WARMING**  
**TASK 2: TRUCKING DIESEL\***  
**TASK 3: FERRIES**


\* Task 2 has a mistake and its solution will not be presented here.




# **Task 1: GLOBAL WARMING**

# Problem


Given the altitude at each location, compute the max possible number of islands.




# Problem



# Problem



# Problem



# Partial solution

Try all sea levels, starting from 0.5, 1.5, 2.5, 3.5, ..., (highest\_point - 0.5).

At each sea level, scan the whole array to count the number of islands.

Running time  $O(\text{highest\_point} \times n)$

*Able to solve subtask 2.*

# Partial solution

Try sea levels at just below or above altitude at each *location*. Trying

$$h_n \quad h_n + 0.5 .$$

Running time  $O( n^2 )$

*Able to solve subtask 1.*

# Partial solution

Try sea levels at just below or above altitude at each *location*. Trying

$$h_1 - 0.5, \quad h_2 - 0.5, \quad \dots, \quad h_n - 0.5 .$$


Running time  $O( n^2 )$


*Able to solve subtask 1.*



## **Solution (idea):**

- Flood the world; lower the sea level and count the number of island.
- Do not lower the sea level slowly, jump to the local peaks or local valleys.
- Do not scan the whole array to count the islands. At each new sealevel, the number of islands can be differed by at most one.







March 16, 2010

2013 NOI


15

# encounter peak (+)







# encounter peak (+)



# encounter peak (+)





# encounter valley (-)






# encounter peak (+)






# encounter valley (-)

2



# encounter valley (-)



March 16, 2010


2013 NOI


24

Running time  $O(n \log n)$

*Able to solve input all subtasks.  
Unable to solve subtasks 1,2,5 if  
handle a special case wrongly.*

# Special cases: Handling peaks and valleys at same altitude






## **Task 3: FERRIES**




# Problem

Shortest path (in term of cost).




# Problem

Shortest path (in term of cost).



# Problem


The weights of outgoing edges may be swapped. For each combination of swap, we can determine the cost of shortest path. Among all combinations, what is the maximum?



# Problem


Shortest path (in term of cost).

combination 1



shortest : 3


combination 2




shortest: 8


Among the 12 combinations, 8 is the max.

# Subtask 1: Bipartite Graph






shortest: 8



shortest: 15

among the 120 combinations (matchings), 15 is the max



# Solution (subtask 1)

- Sort A in increasing order.
- Sort B in decreasing order.
- Output  $\min( A[i] + B[i] )$  among all  $i$ 's.


Running time: Depend on the sorting algo.

$$O(n \log n)$$

Correctness: Why?



# Correctness:



+	0	1	5	6	8
3					11
7				13	
10			15		
11		12			
15	15				

**Claim:** *The answer must appear in the diagonal of the above table.*

<b>+</b>	<b><math>a_1</math></b>	<b><math>a_2</math></b>	<b><math>a_3</math></b>	<b><math>a_4</math></b>	<b><math>a_5</math></b>
<b><math>b_1</math></b>					
<b><math>b_2</math></b>					
<b><math>b_3</math></b>					
<b><math>b_4</math></b>					
<b><math>b_5</math></b>					


$a_i$  and  $b_i$  are sort increasing.

**Claim:** *The answer must appear in the diagonal of the above table.*

**proof**

+	$a_1$	$a_2$	$a_3$	$a_4$	$a_5$
$b_1$					
$b_2$					
$b_3$					
$b_4$					
$b_5$					

The answer cannot appear only in the lower triangle, for e.g  $a_5 + b_3$ . Suppose so, let us consider the matching that gives  $a_5 + b_3$ . Note that elements in  $\{a_1, a_2, a_3, a_4\}$  must not match with elements in  $\{b_1, b_2\}$ , as this give a value smaller than  $a_5 + b_3$ . So  $\{a_1, a_2, a_3, a_4\}$  must match with  $\{b_4, b_5\}$ . It is impossible to match 4 items to 2 items (contradiction).

<b>+</b>	<b><math>a_1</math></b>	<b><math>a_2</math></b>	<b><math>a_3</math></b>	<b><math>a_4</math></b>	<b><math>a_5</math></b>
$b_1$					
$b_2$					
$b_3$					
$b_4$					
$b_5$					

The answer cannot appear only in the upper triangle.


Suppose the answer appear only in  $b_2 + a_3$ .

Case 1: both  $a_1 + b_5$  and  $a_2 + b_4$  are larger then  $(b_2 + a_3)$ . This is impossible as we can find a matching whose min is larger than  $(b_2 + a_3)$


Case 2:  $a_1 + b_5$  is smaller than  $(b_2 + a_3)$ . Impossible, because any matching will take one element from the leftmost column.

Case 3:  $a_2 + b_4$  is smaller than  $(b_2 + a_3)$ . Also impossible...

# Subtask 2



# Subtask 2 – reduce it to subtask 1




## Subtask 3


- Slight modification of Dijkstra's algorithm.
- Reverse the graph (by reversing the direction of the edge). Find the shortest path from the destination to the source.
- Modify the Dijkstra's algorithm.




# The original Dijkstra's algo: find the shortest path from source to destination.




# Extract the min, update neighbours




# Extract the min




# Extract the min, update neighbours




# Extract the min,



# Extract the min, update neighbours



# Extract the min. Done.



Let  $G = (V, E, c)$  be a weighted directed graph.  
Let  $N_{in}(v)$  be the set of incoming neighbors of  $v$ .  
Let  $N_{out}(v)$  be the set of outgoing neighbors of  $v$ .  
Let  $c(u, v)$  be the cost of the edge from  $u$  to  $v$ .

---

```
1: for all  $u \in V$  do
2:    $d(u) \leftarrow \infty$ 
3:   mark  $u$  as unvisited
4: end for
5:  $d(source) \leftarrow 0$ 
6:  $Q \leftarrow \{source\}$ 
7: while  $Q \neq \phi$  do
8:    $v \leftarrow \arg \min_{x \in Q} d(x)$ 
9:    $Q \leftarrow Q \setminus \{v\}$ 
10:  mark  $v$  as visited
11:  for all  $u \in N_{out}(v)$  do
12:    if  $d(u) < c(v, u) + d(v)$  then
13:       $d(u) \leftarrow c(v, u) + d(v)$ 
14:       $Q \leftarrow Q \cup \{u\}$ 
15:    end if
16:  end for
17: end while
18: return  $d(destination)$ 
```

---



# **Solution (subtask 3)**

- Modify the Dijkstra's algorithm.

Dijkstra's

Let  $G = (V, E, c)$  be a weighted directed graph.  
Let  $C(v)$  be the multiset of unassigned costs of incoming edges to  $v$ .  
Let  $N_{in}(v)$  be the set of incoming neighbors of  $v$ .  
Let  $N_{out}(v)$  be the set of outgoing neighbors of  $v$ .

---

```


1: for all  $u \in V$  do
2:    $d(u) \leftarrow \infty$ 
3:   mark  $u$  as unvisited
4: end for
5:  $d(source) \leftarrow 0$ 
6:  $Q \leftarrow \{source\}$ 
7: while  $Q \neq \emptyset$  do
8:    $v \leftarrow \arg \min_{x \in Q} d(x)$ 
9:    $Q \leftarrow Q \setminus \{v\}$ 
10:  mark  $v$  as visited
11:  for all  $u \in N_{out}(v)$  do
12:     $m \leftarrow \max\{x \mid x \in C(u)\}$ 
13:     $\tilde{c}(v, u) \leftarrow m$ 
14:     $C(u) \leftarrow C(u) \setminus m$ 
15:    if  $d(u) < \tilde{c}(v, u) + d(v)$  then
16:       $d(u) \leftarrow \tilde{c}(v, u) + d(v)$ 
17:       $Q \leftarrow Q \cup \{u\}$ 
18:    end if
19:  end for
20: end while
21: return  $d(destination)$ 

```


---

insert line  
12, 13, 14.


# Modified Dijkstra's algo.




# Extract min




# Extract min, update neighbours




# Extract min, update neighbours



# Extract min, update neighbours




# Extract min,







# Extract min, update neighbours




# Extract min




# Extract min, update neighbours



# Extract min, update neighbours



# Extract min, done.



Ans: 8

That's great. Why it is correct?

See attached pdf file for proof.

## Subtask 4: graph contain cycle

Need a special check. Such check also required in the original Dijkstra's algorithm.

For simplicity, let us consider the original Dijkstra's algorithm. If the graph contains a cycle, a vertex may get added to the queue  $Q$  twice. Need an extra "if" statement to prevent that.

# The original Dijkstra's algo.

