

Integrative biomechanics for tree ecology: beyond wood density and strength

Mériem Fournier, Jana Dlouha, Gaëlle Jaouen, Tancrède Almeras

► To cite this version:

Mériem Fournier, Jana Dlouha, Gaëlle Jaouen, Tancrède Almeras. Integrative biomechanics for tree ecology: beyond wood density and strength. Journal of Experimental Botany, 2013, 60 (15), pp.4397-4410. 10.1093/jxb/ert279. hal-00909904

HAL Id: hal-00909904 https://hal.science/hal-00909904v1

Submitted on 27 Nov 2013

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers. L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

This is a preprint version of a published article:

Fournier M, Dlouha J, Jaouen G, Alméras T (2013) Integrative biomechanics for tree ecology: beyond wood density and strength. Journal of experimental botany 64(15):4793-815 DOI: 10.1093/jxb/ert279

To get the original article, write to: tancrede.almeras@univ-montp2.fr

.....

Integrative biomechanics for tree ecology: beyond wood density and strength

M. Fournier^{1,2}, J. Dlouhá^{2,1}, G. Jaouen³, T. Almeras⁴

1. AgroParisTech, UMR 1092 LERFOB, 54000 Nancy, France

- 2. INRA, UMR 1092 LERFOB, 54280 Champenoux, France
- 3. AgroParisTech, UMR "Ecologie des Forêts de Guyane", 97387 Kourou Cedex, France

4. CNRS, Université de Montpellier 2, Laboratoire de Mécanique et Génie Civil, 34095 Montpellier, France

Corresponding author

M. Fournier: <u>meriem.fournier@agroparistech.fr</u>, UMR 1092 LERFOB, AgroParisTech, 14 rue Girardet, 54000 Nancy, France. Tel.: +33 (0)3 83 39 68 00; Fax: +33 (0)3 83 32 73 81.

Other authors:

jana.dlouha@nancy.inra.fr gaelle.jaouen@ecofog.gf tancrede.almeras@univ-montp2.fr

Date of submission: 18 may 2013

Number of tables: 3

Number of figures: 5

Total word count: 13340

Supplementary material: one file in .xlsx format (SBcalculation.xlsx)

Abstract

Functional ecology has long considered the support function as important, but its biomechanical complexity is only just being elucidated. We show here that it can be described on the basis of four biomechanical traits, two safety traits against winds (SW) and self-buckling (SB), and two motricity traits involved in sustaining an upright position, tropic motion velocity (MV) and posture control (PC). All these traits are integrated at the tree scale, combining tree size and shape together with wood properties. The assumption of trait constancy has been used to derive allometric scaling laws, but it was more recently found that observing their variations among environments and functional groups, or during ontogeny, provides more insights into adaptive syndromes of tree shape and wood properties. However, over-simplified expressions have often been used, possibly concealing key adaptive drivers. An extreme case of over-simplification is the use of wood basic density as a proxy for safety. Actually, since wood density is involved in stiffness, loads and construction costs, the impact of its variations on safety is non-trivial. Moreover, other wood features, especially the microfibril angle (MFA), are also involved. Furthermore, wood is not only stiff and strong, but it also acts as a motor for MV and PC. The relevant wood trait for that is maturation strain asymmetry. Maturation strains vary with cell wall characteristics such as MFA, rather than with wood density. Finally, the need for further studies about the ecological relevance of branching patterns, motricity traits and growth responses to mechanical loads is discussed.

Keywords

Biomechanics, Ecological strategy, Gravitropism, Shape, Size, Trees, Wood

1 Introduction

2 The mechanical design of trees as achieved by Nature, in particular, the perennial self-3 supporting habit of extremely slender stems, is both fascinating and complex (Rowe and 4 Speck, 2005), and understanding how tree and wood traits involved in this design are or are 5 not adapted to the environment is a major challenge in functional ecology. Many physical 6 models have been developed in the past to increase our understanding of why tree design 7 works so efficiently (Niklas, 1992; Moulia and Fournier-Djimbi, 1997; Niklas et al., 2006b). 8 These models are still used to address some questions that exist in plant ecology today such 9 as the maximum height that trees can reach (Niklas, 2007; Banin et al., 2012), self-thinning 10 rules (Larjavaara, 2010), biomass partitioning within tree organs (Taneda and Tateno, 11 2004), and developmental, phylogenetic and environmental wood variations (Watt et al., 2006; Lachenbruch et al., 2011; Zhang et al., 2011). Indeed, in all of these questions, an 12 13 understanding of how a given design leads to tree mechanical performance first requires an 14 integrative mechanical framework that lays the groundwork for a dedicated mechanical 15 model (Niklas, 1992). In such a modelling approach, the mechanical design of a tree is 16 specified by wood mechanical properties and morphological characteristics that make it 17 possible to resist forces and control strains, as well as by their interaction with loads from 18 external factors (wind flows and gravity) and internal factors (supported fresh biomass, 19 crown area, lever arms, etc.). Mathematical expressions can then be derived to explicitly 20 link the tree mechanical performance in terms of strains, stresses and safety margins, to 21 the design variables such as tissue properties and tree size and shape. However, this 22 modelling phase is only a very preliminary step towards understanding how tree and wood 23 traits are or are not ecologically adapted to the environment. From this point of view, most 24 ecologists who speak of biomechanics have actually been focusing on design safety associated with survival (Read and Stokes, 2006). The two most frequently discussed design 25 26 features are wood mechanical properties (Chave et al., 2009) and optimal allometries 27 between height and diameter that maintain a given safety margin against mechanical 28 failure (see Niklas (1994) and Moulia and Fournier-Djimbi (1997) for a review of related studies, and Niklas et al. (2006a) for a recent case study). 29 30 Moreover, as developed by Moulia and co-workers (Moulia et al., 2006), plant

- 31 biomechanical performance must continually adapt during growth, implying that a
- 32 developmental plasticity rather than a genetically-fixed design was probably selected in

33 most environments. Generally speaking, phenotypic plasticity and more accurately 34 ontogenetic plasticity (*i.e.* variation in the ontogenetic trajectory induced by environment) 35 are nowadays widely debated by plant ecologists (Sultan 2002, Wright and McConnaughay 36 2002, Herault et al. 2012). Biomechanical ontogenetic plasticity has been widely observed, 37 especially on woody climbers (e.g. Menard et al. 2009, Rowe and Speck 2006). It is based on 38 mechanosensing that triggers specific growth responses to mechanical signals (Moulia et 39 al., 2011). Analysing these responses has led to the identification of two different 40 components of the support function: (i) a skeletal design based on stem thickness and taper together with the strength and stiffness of wood (Niklas, 1992); and (ii) a motricity design 41 42 involving active movements generated by mechanical auto-stresses. It has been shown that 43 motricity is required to control the posture of the tree (Moulia et al., 2006) and to explore 44 its aerial environment (Martone et al., 2010). So far, advances in plant biomechanics 45 dealing with the involvement of motricity in tree habit and its consequences in terms of 46 mechanical design have been poorly studied in ecology. It is still assumed that plants 47 support mechanical stresses but do not actively generate them (see, for example, how tree 48 biomechanics and reaction wood are presented in Turner, 2001). In their review about 49 biomechanics and plant ecology, Read and Stokes (2006) mentioned ontogenetic variations 50 of mechanical traits due to development constraints as well as stem-righting movements, 51 but biomechanical traits have not integrated such sensing or moving processes up until now 52 (see Chave et al. (2009) about wood traits, and King et al. (2006; 2009) about tree 53 mechanical performance). By the same token, plant signalling is an active field of research 54 in ecology (Givnish, 2002), but mechanical signals have been much less considered than 55 chemical signals, for example. 56 In this paper, we propose concepts and methods that make it possible to better integrate,

- 57 from an ecological point of view, the way trees mechanically explore their aerial
- 58 environment "without muscle" (Martone *et al.*, 2010). Since we emphasize developmental
- 59 biomechanics during growth, we show that safety against wind damages or against self-
- 60 buckling is a necessary but not a sufficient condition for the adaptive success of tree habits.
- 61 We propose a new view of biomechanical performance, describing the biomechanical
- 62 framework for studying "motricity", i.e., the ability to slowly but actively control the
- 63 orientation of stems (Moulia et al., 2006) by monitoring stem lean and curvature (Bastien et
- 64 *<u>al., 2013</u>*) and generating bending forces that actively compensate for the effect of
- 65 increasing self-loads (Almeras and Fournier, <u>2009</u>). The way this biomechanical framework

has been and could be used in tree ecology at species and community levels is reviewedand discussed.

68 Before beginning this review, we would like to justify why we focused uniquely on trees. 69 Obviously, the previous arguments concern not only trees but all land plants as well (see, 70 for example, Moulia et al., 2006). However, the long-term adaptation of mechanical design 71 is particularly emblematic in tall and long-living trees. Indeed, during their ontogeny, trees 72 always experiment with a wide range of changing mechanical loads: they increase their 73 mass by up to 10^5 or more during their lifetime. Moreover, cambial growth, although it is 74 not a feature specific to trees (Lens et al., 2012), has specific implications regarding 75 biomechanics. Contrary to herbaceous plants in which living cells have a significant share in 76 mechanical functions, the bulk of the tree body consists of dead cells that are almost 77 unmodified after their death. Only the very thin living cambiumenables through the 78 secondary growth the continuous adaptation of stem mechanical design parameters such 79 as flexural stiffness or orientation over the years. Although the biomechanical comparative 80 analysis of different plant forms is a promising domain (see Rowe and Speck, 2005), we 81 have limited our discussion to woody trees. Moreover, we have primarily focused on forest 82 trees and limited development to the biomechanical performance of aerial support systems 83 mainly focusing on trunks. It is suggested that the reader consults Tobin et al. (2007), 84 Stokes (2000) and Ennos (2000) for some insights into root biomechanics. In this review, 85 trees are defined as self-supporting plants where cambial indeterminate growth enables a 86 large and reactive increase of thickness.

87 This review is organized as follows. After introducing briefly the concepts of functional 88 biomechanical traits, we will develop usual mechanical models of strength and safety, and 89 less usual models of motricity, in order to define integrative traits of biomechanical 90 performance at the tree level that combine load characteristics, stem morphology and 91 wood properties. Figure 1 summarizes the mechanical constraints and processes covered. 92 We will discuss how these integrative traits can be estimated by sets of measured traits 93 (obtained by usual or unusual metrologies). Then we will emphasize the interests and limits 94 of scaling laws that link together measured traits under hypotheses of constant 95 biomechanical performance. A specific section will deal with this question of scaling laws 96 along ontogenetic trajectories. Subsequently, we will put stress on wood properties in 97 order to disentangle the different meanings of wood density, a soft trait widely used in 98 ecology, and provide biomechanical interpretations of how wood structure at different

99 level (from tissue to cell wall) could be evolutionarily or physiologically driven. The

100 conclusion will return to general issues, suggesting future research challenges.

Symbols are not systematically defined in the text, but can be found in the list of
abbreviations at the end. For a better understanding of formulas, readers unfamiliar with
biomechanical terms are invited to report to this glossary. General definitions of stresses,
strains or auto-stresses are not restated, readers are referred to general reviews (Niklas
1992, or Boudaoud 2010), to the general glossary of Moulia (2013), or to definitions (Box 1)
of Baskin and Jensen (2013).

107

108 Functional biomechanical traits at the tree level

109 Ecological strategies specify the different ways in which organisms and species secure 110 carbon profit during vegetative growth and ensure gene transmission in the environment 111 where they grow in order to maintain their fitness (Westoby et al., 2002). To characterise 112 the different strategies, plant ecologists measure functional traits, i.e., "any morphological, 113 physiological or phenological feature measurable at the individual level, from the cell to the 114 whole-organism level, and that impacts fitness indirectly, without explicit reference to 115 environment" (Violle et al., 2007). Strategies are inferred from the analysis of the 116 relationships between these traits. A major challenge for plant ecology is then: (i) to define 117 consistent sets of measurable traits; and (ii) to develop extensive databases from the 118 recording of these sets of traits in order to quantify ecological strategies of species along 119 environmental gradients (Violle et al., 2007). These databases are then analysed through 120 multidimensional analysis, revealing syndromes of traits that separate different functional 121 strategies, i.e., clustering of plants among the huge diversity of species and traits, and 122 among the wide range of environments. By doing so, plant ecologists have found only a few 123 basic contrasted strategies (Westoby et al., 2002; Grime, 2001). Interest has focused on 124 tropical forests since they provide a tremendous diversity of tree species to study 125 strategies. Although a greater number of tree strategies have been discussed for a long 126 time (Turner, 2001; Delcamp et al., 2008; Fortunel et al., 2012), tropical species have often 127 been opposed along one single predominant axis that expresses growth vs. survival. This 128 axis can be equally interpreted as opposing shade-avoidant or pioneer species vs. shade-129 tolerant species or dryads (Turner, 2001). Generally speaking, the question is how traits 130 associated with particular functions such as carbon storage, sap ascent, etc., or mechanical

support, are more or less closely linked to this axis. As pointed out by Wright et al. (2004), a 131 132 further question concerns the direct or indirect causality of correlations observed between 133 traits. On the basis of the leaf economics spectrum of Wright et al. (2004), Chave et al. 134 (2009) reviewed variations of wood properties across large biogeographic gradients and 135 showed that (i) wood basic density ρ is a good proxy for the predominant growth-survival 136 axis, and that (ii) since wood mechanical properties are positively correlated to ρ , a high 137 degree of wood stiffness and strength is also associated with survival. However, the 138 biomechanical causality behind these relationships requires a cautious analysis, bringing us 139 to the issue of mechanical design and the biomechanical modelling of the support function 140 of trees in their environment. Actually, the causality between high wood density and high 141 biomechanical performance is not self-evident and will be widely discussed in further 142 sections.

143 In the following sections, we (i) propose four tree-level integrative traits that characterise 144 the support function and that synthesize the literature on the topic, and (ii) develop a set of 145 biomechanical models that clarifies how wood properties and tree morphology interact 146 with loads to define these integrated traits at the tree level. Indeed, mechanics leads to 147 quite complex geometrical effects compared, for example, to gas exchanges or sap 148 conduction. Whereas the latter are mainly based on fluxes through surfaces, the former 149 involve the transmission of forces through lever arms and second moments of area, leading 150 to geometry-dependent amplifications (Gordon 1978). We show that using integrative 151 models could rebut some intuitive assumptions often made by ecologists such as, for 152 example, "the greater the wood strength is, the greater the safety will be" Indeed, 153 ecologists need to develop a better understanding of integrative biomechanical models that 154 underlie the definition of wood and tree traits: if biomechanical models are designed by 155 physicists alone, there is a risk that they may build only general "first order" models, not 156 adapted to the diversity of life nor to adaptations or responses to specific environments. 157 We show, for example, that shape factors (such as taper or biomass distribution along the 158 stem) have been neglected in the past, despite the fact that their effects on mechanical 159 safety could be important.

160

161 Common traits of strength and safety

162 *Risk of wind damage and tree strength*

163 In trees, wind loading may lead to the most commonly experienced mechanical abiotic risk 164 (Read and Stokes, 2006). Safety factors against risk are the ratio of the load capability to the 165 actual load (Niklas, 2000). The higher they are, the higher the margin of safety against the 166 risk will be.

167 Obviously, both wind velocity and air density are environmental factors. In order to define a 168 tree-level trait for wind firmness without any reference to environment, we propose estimating tree safety (SW) as a critical wind drag pressure $\rho_{air} U_w^2$ that makes the trunk 169 170 break. The usual dimensionless safety factor (Fig. 2, Niklas 2000), can then be obtained as 171 the ratio of our SW trait to the current wind drag pressure, according to specific wind 172 climates. This dimensionless safety factor remains the relevant parameter for discussing the 173 ecological significance of an observed tree design, since the same design could be highly 174 risky in windy conditions and very safe in other ones. Several different mechanistic models 175 have been developed to calculate SW (Gardiner et al., 2008; Schindler et al., 2012), all 176 based on the following steps: i) estimating the drag force from interactions between wind 177 and crown properties, ii) converting this drag force into bending moments adding the lever 178 arm to any cross-section of the trunk, iii) distributing bending moments in local forces per 179 area unit, namely bending stresses, across the woody cross-section, iv) comparing these 180 stresses due to wind to the maximal stress wood can support, namely wood strength. The 181 stem breaks down if bending stresses exceed wood strength, if not the tree is safe. Then, 182 the critical wind pressure is the one that causes bending stresses just at the limit of wood 183 strength.

Quite simple engineering models based on both empirical measurements and physical laws are commonly used by forest managers (see synthesis of Gardiner *et al.* (2008)) for wind risk assessment. These models overlook the dynamic effects of turbulent flows (de Langre, 2008) and tree vibrations (James *et al.*, 2006), including them through a corrective "gust factor" by which the meteorological *U_w* is multiplied (<u>Gardiner *et al.*</u>, 2008).

189 Concerning the steps (i) and (ii), wind is assumed to act as a static bending moment190 calculated at the height X as:

191
$$M_w(X) = 0.5 c_d \rho_{air} A_w U_w^{-2} (H_w - X) F_w$$
(1)

192 This frequently used formulation is more relevant for isolated trees but has also been

validated in forestry and included in wind risk management tools (<u>Gardiner *et al.*, 2008</u>).

- 194 In such tools, parameters that cannot be directly measured in managed forests are
- 195 calibrated. A_w , which is the streamlined projected area of the stem and crown against
- 196 which the wind acts, is estimated from basic tree dimensions (*H*, *D*, crown dimensions).
- 197 The shape factor F_w in (1) represents both the interaction between the wind and crown
- 198 profiles, and the relationship between the wind around the tree (that is usually not
- assessed) and the meteorological data that are available.
- 200 Then, according to step (iii), the bending moment in (1) is distributed across the cross-
- section of the trunk into bending stress $\sigma_w(X)$. Bending stress is locally perceived as forces
- 202 per area unit along the trunk axis. The maximum tensile stress is developed on the
- 203 windward side whereas maximum compressive stress is located on the opposite leeward
- side. Then (step iv), $\sigma_w(X)$ is compared to the wood critical limit for plastic behaviour or for
- rupture, $\sigma_c(X)$, measured by bending tests in the laboratory (see general concepts in Niklas
- 206 1992 and example of available data in <u>Chave *et al.*, 2009</u>).
- 207 To calculate the tree safety, the location X_w of the weakest cross-section (i.e. the height X_w
- where damage should occur first) must be estimated. X_w minimises the safety factor
- 209 $\sigma_c(X)/\sigma_w(X)$ along the height X. The function $\sigma_c(X)/\sigma_w(X)$ varies along stems with complex
- patterns (Niklas, 2000, Fig.2). Actually, a constant stress $\sigma_w(X)$ along the stem is a quite old
- and frequently used assumption (e.g. Dean and Long 1986, see Moulia and Fournier-Djimbi,
- 212 1997, for a review). Such a constant stress design should constrain the variations of
- 213 diameter and wood properties along the stem. However, as claimed by Niklas and Spatz
- 214 (2000), such a design agrees neither with empirical observation nor biomechanical theory.
- Then, as in Niklas (2000), we suggest carefully checking where the minimum safety factor, $\sigma_c(X)/\sigma_w(X)$ is located. Actually, Figure 2 illustrates a case of complex patterns of variations of safety with height. Nevertheless, in usual forest trees made of a single and welldifferentiated trunk, safety is usually minimal near the stem base (Gardiner *et al.*, 2008; Sterck and Bongers, 1998). The critical wind pressure SW is then calculated at the stem base as:

$$SW = \frac{\pi \sigma_c D^3}{16 c_d A_w H k_w F_w}$$

SW (Safety against Wind) increases with wood strength σ_c and stem thickness *D*. It decreases with the drag coefficient c_d , the wind-exposed surface area A_w , and the height of the centre of pressure Hk_w . In the case of a non-circular cross section, the criterion can be easily modified by adding a cross-section shape factor.

226

227 Are there theoretical limits to the self-supporting habit?

228 Self-buckling is the mechanical situation where an erect and slender tree is no longer self-229 supporting, since supported weights exceed a critical limit and make it bend dramatically. 230 This has been identified as another major mechanical constraint on tree stability (Greenhill 231 1881, Niklas, 1992). Safety against self-buckling is independent of the actual environment 232 since it relies only on the biomass and stiffness characteristics of the tree, without any 233 external factor except gravity acceleration g, whose variations are negligible. Safety against 234 self-buckling is based on the calculation of critical dimensions that the tree mechanical 235 design cannot exceed. According to our previous definition of safety, self-buckling load 236 capability is thus defined as the maximum height a tree can reach before buckling, when 237 other parameters involved in the self-bending loads are kept constant. Then, safety against 238 buckling is the ratio of this maximum height to the actual one.

239

240 Models of self-buckling safety, calculated as the ratio of the real dimension to the

241 theoretical limit

242 Such a theoretical concept has led to many different models (see the synthesis in Holbrook 243 and Putz, 1989, and Jaouen et al., 2007), all based on the use of two independent 244 dimensions among the thickness D, the height H or the volume V. The simplest one 245 assumes a cylindrical pole loaded with wood weight alone. More complex ones add a 246 power-law taper (Greenhill, 1881), an additional weight at the top of the pole to take leaves 247 and branches into account (King and Loucks, 1978), or a distributed mass along the pole 248 (Holbrook and Putz, 1989). The ratio between the real dimension and the theoretical critical 249 one then gives a dimensionless safety factor against self-buckling (SB), which usually 250 exceeds 1 for normally self-supporting trees. Choosing a parsimonious but accurate model 251 for SB calculation requires experimental validations. Whereas Holbrook and Putz (1989) and 252 Jaouen et al. (2007) showed wide discrepancies between different models and discussed 253 their reliability on the basis of observations of trees at the self-supporting limit, most 254 authors trusted the simplest cylindrical pole formula without any discussion (see Sterck and 255 Bongers, 1998; Osunkoya et al., 2007 and Read et al., 2011, among others). Both Jaouen et

256 al. (2007) and Holbrook and Putz (1989) showed that in the tree sapling samples they 257 studied, the simplest cylinder formula fits well with more realistic models that account for 258 trunk shape and load distribution. Figure 3 illustrates this result since the safety factor of 259 the crowned stem (iv) is better approximated by the cylinder (ii) than by the tapered stem 260 (iii). Actually, the additional weight gained by considering a cylinder roughly compensates 261 for the weight of branches and leaves, disregarded in the tapered stem model. However, in 262 many works that focused on self-buckling through the cylindrical pole model, crown 263 morphology was considered as an important tree functional trait (Sterck and Bongers, 264 1998; Osunkoya et al., 2007). Since results pointed out that branches and leaves should 265 have different weights from one species to another, it was unfortunate that the crown 266 morphology could not have been integrated into calculations of self-buckling safety. 267 Indeed, Jaouen et al. (2007) demonstrated that both the stem taper and the height of the 268 tree centre of mass explain a larger part of the variation of the critical self-buckling height 269 than, for example, the wood modulus of elasticity. Thus, the soundness of a general 270 cylinder pole model, which is the least physically relevant, is questionable.

271 More generally, should other additional weights (such as ice, rainfalls or snow, epiphytes, 272 animals, etc.) be included in the calculation of the critical self-buckling height? Obviously, as 273 it is generally implicitly assumed since Greenhill (1881), they can be considered as random 274 events, associated with an oversized design to face uncertainties. That is why a safety factor 275 SB that is too close to 1 is not viable, whereas an optimal SB would be probably a bit larger 276 than 1 (King et al. 2009). For additional accuracy, an estimation of these additional weights 277 could be included in critical height calculations (Holbrook and Putz 1989, King and Loucks 278 1978). When comparing ecological situations of different regimes of rainfalls or of variable 279 abundance of epiphytes or lianas, such detailed approaches would make it possible to 280 quantify how much more safety is required in the most constrained environments. Actually, 281 the height of the centre of mass - m parameter – may have been substantially 282 underestimated, as well as the load factor, when abusively neglecting epiphytes, ice or 283 snow. In Fig. 3, models of increasing complexity have been used to calculate SB on a tree of 284 a given diameter and height, assuming less and less uncertainty concerning loads (practical 285 formulas are given above, inputs are developed in the legend). Figure 3 demonstrates that 286 additional weights (case (v)) could have an impact on SB on the same order of magnitude as 287 taper or crown load.

In any case, the magnitude of the safety factor bears important ecological information in
itself: a low safety factor (close to 1) indicates a real risk, whereas a high safety factor

instead suggests that the constraint is not ecologically relevant or improperly calculated
since important drivers have been neglected. Then, as reported by Niklas and Spatz (2004),
it is really problematic to assume that the tree biomechanical design is driven by a constant
and high safety factor. Therefore, each time a high safety factor (higher than 5 to 10, for
example) is observed, both the relevancy of the biomechanical constraint (is buckling a real
risk?) and the method used for calculation (are loads, shape or wood properties properly
assessed?) must be questioned.

297

The critical self-buckling height refers to different dimensional limits, depending on environmental drivers

300 As effectively pointed out by Holbrook and Putz (1989), calculating critical dimensions 301 addresses a last but sensitive question: should we calculate the critical minimum diameter 302 with a fixed height of the tree? Alternately, should the basal diameter be maintained 303 constant to calculate the critical maximum height? This choice must be discussed from an 304 ecological perspective. Buckling is a great limiting mechanical constraint when the intense 305 competition for light foraging is the main environmental force at play, suggesting that 306 investment capability in the support function is limiting. Maximum height for a given 307 support tissue volume (or biomass) would then be meaningful, as assumed by Jaouen et al. 308 (2007) and Holbrook and Putz (1989) when dealing with understorey trees, where trees are 309 sheltered from winds but allocate comparatively more biomass to height growth than to 310 diameter increment. On the other hand, when comparing canopy trees of similar height, 311 minimising the diameter or the volume of support tissue for a given height, as done by King 312 et al. (2009), is also relevant.

313 Whereas the above-mentioned authors carefully rewrote Greenhill's criterion to argue their 314 choice of critical self-buckling dimensions, most authors use the formula based on a 315 constant diameter without any ecological justification (e.g., Sterck and Bongers, 1998, 316 among others). Maximising height at a forced constant diameter can be the relevant 317 criterion to compare plants from a wide variety of biological types or plants, including 318 species that lack perennial secondary growth (Niklas, 1992). However, among trees 319 characterised by indefinite growth in thickness, using a fixed diameter seems difficult to 320 justify.

322 Practical criteria to estimate the safety margin against self-buckling

The following section gives practical equations (provided as supplementary material in a .xlsx file) to compute safety against self-buckling, adapted to populations of varying heights based on the maximum height achievable with a constant support tissue volume. By reformulating Greenhill's model (<u>1881</u>) and revisiting Jaouen's formula (2007), the critical self-buckling height is:

328 $H_c = 0.88 V^{1/4} E^{1/4} (\rho_T g)^{-1/4} F_b^{1/2}$

345

The density of the carried load ρ_{T} is significantly higher than the fresh density of wood alone ρ_{green} , or than the wood basic density ρ , sometimes improperly extended to SB calculations (<u>Sterck and Bongers, 1998</u>). The shape factor F_{b} is 1 when the tree is represented by a cylindrical pole loaded by its own mass alone, as recently assumed by most authors. In other situations, it is a function of biomass and diameter profiles along the stem:

$$F_b = 0.1785 (|m-4n+2|) \cdot (2n+1) \int_{\frac{4n-1}{m-4n+2}}^{-1} (0)$$

The parameters *n* and *m* are defined by $D(X) = D\left(\frac{H-X}{H}\right)^n$, and $M(X) = \rho_T V\left(\frac{H-X}{H}\right)^m$, 336 where D(X) is the diameter at height X and M(X) is the biomass supported above height X. 337 338 The higher *n* is, the higher the taper will be (n=0 is a cylinder). The higher the value of *m* is, 339 the nearer to the base of the tree the biomass is concentrated. m+1 is the ratio of the total 340 height to the height of the centre of mass H_q (Fig. 1). The Bessel function first root $J_{\frac{4\pi-1}{2}}^{-1}(0)$ can be practically solved with an adapted computing software programme or by 341 using the linear regressions fitted by Jaouen et al. (2007). The safety factor SB is then 342 defined as the ratio H_c/H . Since the volume V is $\pi HD^2/(4(2n+1))$ (Jaouen et al., 2007), SB is 343 344 given by the following equation:

$$SB = 0.836 H^{-2/4} D^{1/2} E^{1/4} (\rho_T g)^{-1/4} (2n+1)^{-1/4} F_b^{1/2}$$

Safety against self-buckling increases with wood stiffness *E*, the amount of support tissue *V* or the diameter *D*, and decreases with height *H* and specific mass ρ_T .

348 It can be observed that for a cylinder (n=0, $F_b = 1$), this SB based on constant volume is a

349 power of ¾ of the widely used safety factor **0.792** $H^{-1} D^{2/3} E^{1/3} (\rho_T g)^{-1/3}$, based on a

350 constant diameter (which is then higher, as shown in Fig. 3). Actually, the three safety 351 factors calculated from (i) a minimum diameter at constant height, (ii) a maximum height at 352 constant diameter, or (iii) a maximum height at constant volume, are closely related. Due to 353 the multiplicative relationships linking H_c , H, D and V, they are powers of each other. 354 Therefore, they can be used indifferently for comparing safety between trees, regardless of 355 the ecological conditions. Moreover, the limit for the self-supporting habit is always 1, and 356 the optimal allometry between H and D that leads to constant safety during growth (assuming that the other parameters are constant) is also $H^{2/3}$, regardless of the criterion. 357

358

359 Including motricity in functional biomechanical traits

360 Motricity of lignified stems: what enables trunks to actively curve?

361 Although trees have been idealised as perfectly vertical structures when calculating SW or 362 SB traits, real trees always lean, at least slightly. Without any gravitropism, trees could not 363 maintain a vertical orientation because their increasing weight would always bend them 364 towards the ground. As highlighted by Darwin and Darwin (1880), gravitropism is a major 365 growth process that takes part in light foraging strategies and is achieved through local 366 curving along stems and auto-stressing systems (Archer and Wilson, 1973; Hejnowicz, 1997). Curving stiff, thick and lignified tree stems requires a specific source of energy, 367 368 supplied by an internal straining process, leading to asymmetric auto-stresses (Martone et 369 al., 2010). In radially growing stems and differentiating wood, this process, namely the 370 maturation strain induction, occurs at the end of cell formation, and the asymmetry is 371 achieved through the differentiation of reaction wood (Scurfield, 1973). After reviewing 372 traits of the skeletal design, we now formalise which tree features characterise the 373 motricity design.

Following the work of Fournier *et al.* (<u>1994a</u>), Almeras and Fournier (<u>2009</u>) modelled the
bending curvature of a growing stem due to auto-stresses as:

$$\frac{dC_m}{dD}(X) = -4\frac{F_m(X)\,\Delta\alpha(X)}{D(X)^2}$$

This minimal model expressed the basic limits and drivers of the movement: tropisms require growth, so the model represents a rate of curvature per unit of radial growth in diameter (dC/dD). The thinner the stem is, the easier the bending will be and, moreover,

381 noticed by Collet et al. (2011) or Jaouen (2007) studying saplings, and then carefully 382 discussed by Dassot et al. (2012) on beech stands of different tree density or by Almeras et 383 al. (2004) on branches. The difference in maturation strain $\Delta \alpha$ from one side to the other is 384 the main driving force that generates an asymmetry of pre-stresses. Radial growth 385 asymmetry is an additional way to generate such an asymmetry from the mean value $\vec{\alpha}$: 386 stems curve by making more straining wood and/or more wood of the same quality on one 387 side. The shape factor F_m represents the radial growth asymmetry motor as 388 $F_m = 1 + 2k_m \bar{\alpha} / \Delta \alpha$, where k_m is the asymmetry of radial growth, $k_m = (R_+ - R_-)/(R_+ + R_-)$. Actually, Almeras et al. (2005) showed that except in 389

the rate of curvature is proportional to D^{-2} . Motricity is then less constrained in thin axes, as

extreme eccentric growth, the second motor is less efficient, so F_m can be taken as 1 in

391 many cases. At a second order, this basic motor process is also catalysed by radial variations

392 of the modulus of elasticity *E*.

393

380

394 Moving as fast as possible: the curvature rate as a first trait of motricity

Curvature velocity $\frac{dC_m}{dt}(X)$ could therefore be a good candidate for describing stem 395 396 motricity. As reported by Moulia and Fournier (2009), curvature, which is the relevant 397 variable to describe stem movement, follows complex spatial patterns along the stem. 398 Although these spatial patterns by themselves contain information (Bastien et al., 2013), a 399 first approach, focused on time variations, retained curvature velocity near the base (for 400 example, at breast height, which is the usual height of forest measurements) to describe 401 tree motricity, since the bending of the base is essential to move the whole stem (Dassot et 402 al., 2012).

When the lean has been disturbed, trees have to react as fast as possible to recover an
adapted posture to avoid loosing competition for height growth and light foraging (Fournier *et al.*, 2006). A first motricity trait is therefore defined as tropic Motion Velocity (MV), i.e.,
the curvature rate near the base due to radial growth and maturation strains:

$$MV = \frac{dC_m}{dt}(0) = -4 \frac{F_m \Delta \alpha}{D^2} \frac{dD}{dt}$$

408 *MV* is the way the trunk is able to react to disturbances of the trunk lean from its set-point
 409 angle by generating asymmetric pre-stresses at the stem periphery. The trunk set-point

- 410 angle is driven by the environment. It is generally vertical, leading to negative
- 411 orthogravitropism, but becomes oblique on slopes (<u>Matsuzaki *et al.*, 2006</u>; <u>Lang *et al.*,</u>
- 412 <u>2010</u>), or during regeneration stages in shade conditions (<u>Collet *et al.*, 2011</u>), due to
- 413 interactions with phototropism.
- 414

415 Competition for light, slenderness and long-term stability

416 As a founder of biomechanics, Gordon (1978) stated that Nature seems to have accepted 417 stiffness quite reluctantly, except in trees that must be both light and rigid. However the 418 incredibly low stiffness of a slender young sapling tree competing for light would puzzle any 419 civil engineer responsible for design of such a tall, heavy and durable structure exposed to 420 winds and other loads, as a tree should be. Then, since trees are very common elements of 421 our landscapes, a question of more ecological relevance is how such a design can grow and 422 remain upright for such a long time (Moulia et al., 2006). Actually, wood produced at the 423 tree stem periphery is not only a rigid and strong perennial material, as it is in wood houses 424 built by humans, but the tissue of a smart thickening process as well. This process enables 425 the physiological acclimation of the support system to changing mechanical constraints and 426 increasing supported masses, but requires a tremendous coordination between growth in 427 diameter and height (or biomass), on the one hand, and growth and wood properties, 428 especially maturation strains, on the other. According to Grime's strategies (Grime, 2001), 429 in environments with low wind stress and disturbance (low chronic winds, no storms, no 430 sudden changes of wind sheltering such as forest understories not disturbed by large gaps), 431 trees should develop a high efficiency to compete for the light resource, at a low cost to 432 support tissue. Since stems become very slender and close to the non-self-supporting habit 433 in such conditions, a first above-mentioned criterion of biomechanical performance is 434 safety against self-buckling. It is a necessary condition but not a sufficient one. As soon as a 435 tree is slightly disturbed from perfect verticality and symmetry, further growth in biomass 436 makes it bend downwards so that motricity must be activated to control a safe posture 437 over time.

438

439 Maintaining an erect habit: moving to compensate gravitational bending

The biomechanical performance of erect trees is thus based on the way trunks are able tomaintain the trunk set-point angle by the above-mentioned active curving. Almeras and

442 Fournier (2009) suggested defining such a biomechanical performance as follows:

443 i) Growth in biomass induces a curvature rate due to the continuous change of
444 biomass in a growing tree (near the stem base, *X*=0). It can be calculated as:

$$\frac{dC_g}{dD} = 16(1+b)\mathbf{F}_g \sin\varphi \frac{\rho_T g}{E} \frac{H^2}{D^3}$$

The higher the load ρ_T , the lever arm *H* and the lean φ are, and the lower the stem thickness *D* and the wood stiffness *E* are, the higher the flexibility $\frac{dC_g}{dD}$ will be. The form factor F_g is 1 in a cylindrical pole (*n*=0 and *m*=1), and in other situations, for a given total biomass (fixed by ρ_T , *H* and *D*), the higher the centre of mass is, the higher F_g will be. Through the allometric exponent *b*, the bending under self-weight also increases when relative growth in height compared to relative growth in diameter is more rapid.

452 ii) Therefore, the performance of posture control (also called gravitropic performance 453 by Almeras and Fournier, 2009) is the ratio of the value of the reaction, i.e., the 454 tropic motion rate per unit of radial growth $\frac{dC_m}{dD}$, to the gravitational curvature

455 rate
$$\frac{dC_g}{dD}$$
:

$$PC = \frac{-dC_m}{dC_g} = \frac{E\,\Delta\alpha}{4(1+b)\,\rho_T g\,\sin\varphi} \frac{F_m}{F_g} \frac{D}{H^2}$$

457 Like previous biomechanical integrative traits, PC is the balance between a load action 458 independent of environmental factors, in this case, $F_a \rho_T g \sin \varphi$, and a tree reaction, in this case, $F_m E\Delta \alpha$. Size and shape interacts with these latter actions and reactions, with an 459 460 immediate effect of size through D and H. PC=0 means that the tree is not able to react any 461 longer. Therefore, it will bend more and more under its self-weight. PC=1 is the situation 462 where a given posture is maintained when no more bending, upward by reaction or 463 downward by gravity, occurs. When PC>1, the tree is righting itself, whereas when PC<1, it 464 is sagging down.

465

466 Functional diversity and variations of motricity traits

467 When dealing with the diversity of tree functional traits, ecologists have exclusively 468 considered stem biomechanical properties as a way to understand how the tree design 469 either avoids or tolerates failure risk. Data collected concerning tree morphology and wood 470 properties are therefore analysed from this standpoint. With this in mind, the assumptions 471 tested were the following: (i) Are high wood strength and stiffness associated with a 472 survival strategy against mechanical constraints and, as a result, with high SB and SW (Read 473 et al., 2011); (ii) Is tree design based on low but optimised stem safety SB or SW that 474 maximises survival and minimises the stem construction costs (Kooyman and Westoby, 475 2009; King et al., 2006); (iii) How can the association between wood density and the 476 growth-survival axis be explained (van Gelder et al., 2006) or disturbed (Read et al., 2011) 477 by biomechanical requirements? We argue that such a view is restrictive and that motricity 478 could also be an important component of tree strategy. Surprisingly, although tropisms are 479 widely investigated via their physiology, their ecological significance has received less 480 attention (lino, 2006). The two previous motricity traits have been designed to quantify 481 these movements with their different components. PC has been specifically designed as an 482 efficiency trait that should be linked to high survival at low construction costs. Using data 483 from Jaouen (2007), Duchateau (2008) and Delcamp et al. (2008), Figure 4 illustrates the 484 use of PC among functional groups in tropical tree communities to investigate relationships 485 between the motricity traits and the demographic ones. PC is variable among species and 486 functional groups, and negatively associated with mortality rate. Actually, the functional 487 response groups defined from species demography, independently of any biomechanical 488 considerations (Favrichon, 1994; Delcamp et al., 2008), appear here to be more 489 discriminated by PC than by SB, which is the usual biomechanical trait of ecologists in such 490 conditions.

491 In addition to PC associated with competition, MV is proposed as an adaptive trait to 492 disturbance. Disturbances such as windstorms, avalanches and landslides immediately refer 493 to the previous biomechanical traits of safety against the abiotic mechanical constraints. 494 However, a general biomechanical view of disturbance should include not only mechanical 495 strength but resilience as well. Thus, a better understanding of how plants explore and 496 colonise space and compete over time in a changing environment is required (Read and 497 Stokes, 2006). Hamilton et al. (1985) described the switching from a shade-tolerant to a 498 sun-adapted design after gap opening, which is a very common situation of forest 499 community dynamics. Although they were not focused on tropisms and biomechanics, they 500 mentioned righting movements as important morphological adaptations to such a

501 disturbance. Actually, in such situations, the question is no longer how to maintain a given 502 angle to offset the increase of weight (this performance is associated to PC), but mainly to 503 make large and fast movements, described by MV. For instance, in their work on natural 504 regeneration of mixed hardwood forests, <u>Collet *et al.* (2011)</u> used MV to discuss how the 505 immediate radial growth after gap opening, that speeds up MV, contributed to explain the 506 success of pre-existing advanced regeneration. Actually, an immediate allocation of carbon 507 to cambial growth (which increases motricity and stiffness) with delayed primary growth 508 and crown development (which increase weight) is a strong necessity to avoid long-term 509 mechanical instability.

510

511 Four integrative traits of tree stem biomechanical performance obtained by 512 combining size, wood and shape traits

- Four integrative biomechanical traits, SW, SB, MV and PC, directly interpretable as
 properties of the organism, were defined in the previous section. They are linked to the
 performance or safety of the tree support functions in these two components, the skeleton
 and the motricity design. We will therefore concentrate on how to use them in ecological
 studies. First, they must be measurable on great numbers of individuals among the tree
 diversity and along environmental gradients
- 519 Measuring integrative biomechanical traits directly at the whole tree level
- 520 The direct measurements of SW and SB traits at the tree level are usually cumbersome. SW
- 521 can be assessed from wind tunnel experiments (<u>Cao *et al.*, 2012</u>) or by mimicking wind by
- 522 pulling tests (<u>Achim *et al.*, 2005</u>). To enable direct estimation of SB,one needs to define SB
- 523 as the ratio of the critical load weight to the current one as an increase of tree dimensions
- 524 up to the critical height or diameter is not feasible. Then, SB may be estimated from
- 525 artificial loading, adding weights to the tree until it buckles (<u>Tateno, 1991</u>).
- 526 The tropic motion velocity MV has been directly assessed through curvature
- 527 measurements, assuming that the observed changes of curvature are mainly due to the
- 528 active reaction, neglecting bending under self-weight (Collet *et al.*, 2011). However,
- 529 observed changes of curvatures always superimpose motricity and bending under
- 530 increasing weights. On the basis of theoretical models, the two processes can be
- 531 distinguished from each other through additional measurements, as proposed by Almeras

532 et al. (2009) and Huang et al. (2010) to analyse gravitropic movements in leaning stems,

533 where the bending under self-weight could no longer be ignored.

534

Assessing integrative biomechanical traits from independent measurements of size, shape
and wood properties as components of load and resistance

537 Practically speaking, the four biomechanical traits defined are simple products of wood, size 538 and shape traits (adding a crown property, the drag coefficient c_d , in SW) that could be 539 measured independently. Indeed, some of these dissociated traits are already available in 540 extensive/broad databases: height, diameter and growth rate of H and D are measured in 541 permanent forest plots (Pretzsch, 2009); wood properties such as the modulus of elasticity 542 *E* or the critical stress σ_c are available in technological databases (<u>Chave *et al.*, 2009</u>). The 543 different dissociated traits are of two types: resistance (compared to motricity) traits 544 describe how the tree resists (compared to reacts) to mechanical constraints, whereas load 545 factors (k, c_d , A_w in SW; ρ_T in SB; or φ in PC) describe how the external environment, i.e., 546 gravity or wind, interacts with the tree structure to transmit forces. In a particular 547 environment, trees can in fact increase their performances by adapting resistance or 548 motricity traits, or can limit the constraint by adapting load factors. Table 1 classifies these 549 components according to their meaning in each integrative trait.

550

551 The particular case of maturation strains

552 Maturation strain α is not commonly measured in tree ecology. It can be assessed 553 experimentally (i) by measurements of curvature repeated over time, reversing the model to measure $F_m \Delta \alpha$ (Almeras et al., 2009; Sierra-De-Grado et al., 2008; Coutand et al., 2007, 554 in seedlings and greenhouse experiments; Huang et al., 2010, in relation to branches; and 555 556 Collet et al., 2011, concerning natural forest regeneration), (ii) by indicators of maturation 557 strains at the stem periphery (Almeras et al., 2005), developed by wood technologists and 558 measured by different stress-releasing techniques (Fournier et al., 1994b; Yoshida and 559 Okuyama, 2002), and (iii) by going back in time from spatial mapping of reaction wood 560 occurrence, using calibrated relationships between reaction wood and maturation strain 561 indicators (Dassot et al., 2012). This last method allows retrospective growth analysis using 562 wood as a marker of past events, as is currently done in dendrochronological approaches.

564 Scaling or not scaling: how trees follow or evade simple rules derived from 565 constant biomechanical performance

566 One major theoretical interest of integrative traits is the possibility of using them to discuss 567 scaling laws at constant biomechanical performance. The four integrative traits presented 568 above are based on products of dissociated traits, as size parameters – height, diameter, 569 volume, growth rate and wind surface area -, that interact with wood, load, and shape 570 features. Then, a constant performance (i.e. a constant integrative trait) results in 571 allometric laws that link dissociated traits.

572

573 Allometric laws between H and D as null hypotheses to test the effect of other variables

574 Implicitly assuming that size parameters are more variable, theoretical works investigated 575 how height *H* and diameter *D* should be coordinated to maintain a constant biomechanical 576 performance, if all the other properties were kept constant. Slenderness laws that maintain 577 a constant safety (SB or SW) have been widely discussed (e.g. King and Loucks (1978), Mac 578 Mahon 1973, Dean and Long 1986, see Chapter 3 of Niklas (1994) and Moulia and Fournier-579 Djimbi (1997) for a review). Almeras and Fournier (2009) have derived a similar law for the 580 long-term stability, i.e. a constant posture control (PC). The associated allometric 581 relationships are summarized in Table 1. These scaling laws between size variables provide 582 null hypotheses to investigate how other components of shape, load factor or wood 583 properties could vary with size in order to limit or enhance the size constraints on 584 biomechanical performance.

585

586 Null hypotheses to be rejected

587 We would then like to emphasize that the use of integrative biomechanical traits to study 588 how trees adapt to specific environments should not be limited to the "automatic checking 589 of predetermined allometric law between *H* and *D*". Actually, more exciting results occur 590 when such allometries fail. Dean and Long (1986) emphasized that to maintain a constant 591 SW among trees, a constant $\underline{D}^3 H^1 A_w^{-1}$, rather than a simple constant D^3/H , is required.

592 More recently, the possibility that wood variations could compensate for the effect of size 593 variables become a quite active field of research for tree biomechanics (Niklas, 1997; 594 Waghorn and Watt, 2013; van Gelder et al., 2006). The reader can also refer to the section 595 below on ontogenetic changes. Moreover, a constant biomechanical performance agrees 596 with neither biomechanical nor ecological theories. Indeed, environmental conditions 597 orient the value of biomechanical performance and, subsequently, its variation as well as its 598 ecological relevance. For example, SW in an environment sheltered from the wind is 599 probably very high (except if this safe environment has been recently changed at the time 600 scale of evolution or tree development so that trees remain adapted or acclimated to a high 601 risk). Thus, under such condition, SW is likely to be of little interest. On the contrary, in an 602 environment where wind is the main constraint SW is meaningful and should be carefully 603 determined. Actually, in such condition, SW should not rely only on H, D and A_w 604 adaptations, but also on less studied traits such as drag coefficient or wind pressure area 605 and the crown reconfiguration with increasing wind velocity (see the theoretical work of 606 Lopez et al., 2011; and the comprehensive experimental study of Butler et al., 2012). Then, 607 a "wind avoidance" strategy based on optimised values of SW should be much more 608 complex than simple relationships between H, D and A_w. With regard to self-buckling 609 safety, mature isolated trees are usually very safe, making allometries derived from 610 optimised SB factors meaningless (Niklas and Spatz, 2004). However, self-buckling is 611 adjusted at a minimal level in understories where several saplings are no longer self-612 supporting (Jaouen et al., 2007).

613

614 Weak wood can make strong trees

Many previous works assumed that the higher the wood strength σ_c (or stiffness E) is, the 615 616 higher the tree biomechanical performance SW (or SB) will be (e.g. Chave et al., 2009; 617 Swenson and Enquist, 2007). However, since biomechanical performances are related to 618 combinations of traits, it is very easy to make a strong trunk with weak wood by just 619 increasing the diameter. Indeed, as developed by Larjavaara an Muller Landau (2010), due to the scaling of SW (expressed as $\sigma_{\sigma} D^{B}$), decreasing the wood strength by 30% could be 620 easily offset by increasing the diameter by 10% ($\sqrt[1]{1.3}$ =1.09). Therefore, to address the 621 622 question of how increasing wood mechanical properties changes the biomechanical 623 performance, we must take account of how other components of the integrative trait, 624 especially those such as diameter that considerably vary among trees, scale with wood

625 properties. For example, some authors observed a significant increase in E with slenderness 626 H^3/D^2 (Waghorn and Watt, 2013, in *Pinus radiata*). Waghorn and Watt (2013) discussed the 627 way trees regulated E to maintain a viable level of safety SB at high slenderness, probably 628 using mechanoperception of sways. However, they also concluded that slenderness 629 remains the first driver of SB, so that a higher wood performance E is associated with a 630 lower performance SB. Therefore, only if wood properties are independent of other traits, 631 and if other traits do not vary too much, will the tree biomechanical safety increase 632 significantly with wood strength or stiffness.

633

634 Scaling laws are based on the assumption of constant integrative traits, that involves

635 ecology rather than biomechanics

636 Biomechanical scaling laws proved to be very popular (e.g. McMahon, 1973), although they 637 are based on complex and cumbersome mechanical models which are not easily 638 understandable by biologists. Therefore, ecologists may think that mechanical theories are 639 the convincing basis of scaling laws. Indeed, when analysing the contribution of size, wood 640 or shape to biomechanical performance, the preliminary mechanical analysis provides 641 answers about the way all the parameters involved interact to generate, transmit or resist 642 forces. However, mechanics cannot say which parameters are constant. First, as above-643 mentioned, the principle of a constant performance is relative to a tree population in a 644 given environment. Secondly, modelling always uses over-simplifications and neglects 645 parameters. When mechanical integrative modelling is used to derive scaling laws, 646 neglected parameters are implicitly kept constant. Ecology studies which load, 647 morphological and wood traits are variable in tree populations, according to 648 environmental, phylogenetic or physiological limits and drivers. Mechanics can provide help 649 to check by integrative modelling and sensitivity analysis whether these variations impact 650 biomechanical performance. Then, to discuss adaptations of tree biomechanical 651 performance to environment, it would be valid to use comprehensive expressions of 652 integrative biomechanical traits, as proposed in Table 1. For example, in addition to how 653 wood strength σ_c , D and H scale with each other, SW addresses the question of how the 654 load parameters – crown area A_w , lever arm $H k_w$ - could also vary with D, H and σ_c . 655 Similarly, on the basis of a more detailed representation of SB, it follows that taper n and 656 biomass distribution m along the stem should also scale with other traits. Indeed, in tropical 657 forests, weak vs. strong wood, cylindrical vs. tapered stem form, poorly vs. highly

developed branching, and a single layer of leaves in the highest parts vs. multi-layered
crowns, are associated traits that oppose growth to survival (synthesis in <u>Turner, 2001;</u>
Jaouen, 2007). As reported by (<u>Niklas and Spatz, 2010</u>), the challenge for biologists is to
explore the whole complexity of environmental contexts and tree adaptations of shape and
wood properties.

663

664 That little tree will grow big!

665 Are ontogenetic changes of wood properties and shape functionally significant?

666 In long-lived organisms such as trees, understanding how observed strong ontogenetic 667 changes in demographic rates could be explained by functional traits is a major issue for 668 ecology (Herault et al., 2011). From a biomechanical point of view, the increase in size is a 669 major constraint during ontogeny. Therefore, now that we have assessed how functional 670 traits vary with size as well as the above-mentioned null hypotheses on optimal allometries 671 between basic size components, we would like to address the following questions: (i) What 672 are the general variations of wood, shape and load during tree development? (ii) Can these 673 variations and relationships be interpreted by their functional biomechanical role?

674 The variations in mechanical safety as forest trees grow are intriguing since some stages of 675 growth are especially critical, particularly sapling stages exposed to self-buckling in dense 676 understories (Jaouen et al., 2007), and the oldest stages of canopy trees exposed to wind 677 throws (Turner, 2001). Some authors have attempted to study how safety factors change 678 with size and ontogeny (see Sterck and Bongers, 1998; Osunkoya et al., 2007; van Gelder et 679 al., 2006). They used expressions of SB based on a constant D, underestimating the load 680 factor ρ_{T} (taken as ρ) and ignoring shape factors, i.e., the taper and the height of the center 681 of mass, although they did observe variations in crown characteristics. Indeed, their results 682 concerning safety must be considered with caution.

683

684 Could ontogenetic trajectories of wood properties and shape compensate for size effects?

685 Using the comprehensive expression of integrative traits as a product of separated traits *T*

at power v_{τ} , the functional significance of simultaneous ontogenetic variations of wood and

shape could be analysed using the following general method. For the purpose of clarity, we
have illustrated the method by re-analysing some data from Jaouen *et al.* (2007) concerning
SB.

690 The population of 23 individuals of Oxandra asbeckii (Pulle) R.E. Fries (Annonaceae) 691 measured by Jaouen et al. (2007) are assumed to represent an ontogenetic trajectory (i.e. 692 the different sizes are supposed to represent the same individual at different stages of 693 growth). We have fitted an allometric relationship to estimate the relationship between 694 any trait T (i.e., the size V, the modulus of elasticity E, the shape factor F_b and the load factor ρ_T and the integrative SB; data from Jaouen *et al.*, 2007) and the height *H* as $T \sim H^{TT}$. 695 Since H is assumed to follow the ontogenetic trajectory, τ_{T} is the ontogenetic trend of the 696 697 variation of T. The ontogenetic trend of SB is therefore the sum of the ontogenetic trends τ_T 698 of all the isolated traits T multiplied by their power exponent v_{T} . Table 2 gives the results 699 for the particular sample of Oxandra asbeckii: (i) safety against self-buckling decreases with 700 height at a power of -0.23; (ii) if we had studied safety only on the basis of the two size 701 factors H and V, as was done by other authors in the past, we would have concluded that 702 safety decreases with a higher power of -0.32; (iii) additional shape and load factors slightly 703 compensate for size, with a power of +0.02 and +0.06, respectively; (iv) no ontogenetic 704 change was found for the modulus of elasticity. In this particular case, size (i.e., the 705 variations of H, and D or V) remains a constraint, not strongly offset by variations in other 706 features. This general method can apply every time that an integrative trait is a product of 707 dissociated traits.

708

709 The biomechanical significance of wood properties variations

710 The way wood properties variations can compensate for size effects during growth is 711 undoubtedly a challenging research question. Analysing black locust trees (Robinia 712 pseudoacacia), Niklas (1997) estimated that ontogenetic variation of wood properties could 713 maintain SB at a constant level when a tree grows in size. Considering the motricity MV trait that scales with D^{-2} when other parameters are kept constant, Dassot *et al.* (2012) 714 715 investigated how adjustments of reaction wood formation would compensate for the highly 716 limiting effect of *D* during growth in beech (*Fagus sylvatica* L.). Due to the higher content of 717 reaction wood in juvenile wood, they found a high level of stabilisation of motricity during 718 the first young stages that is no longer maintained after ten years of growth. Thus, the

719 relationship between MV and D was no longer a power law, and decreased faster than the expected D^{-2} . This study of Dassot *et al.* (2012) gave a functional meaning to typical, very 720 721 frequently reported radial patterns of reaction wood (synthesis in Lachenbruch et al., 722 2011). Generally speaking, wood radial variations (of density or mechanical properties) are 723 studied in-depth for wood quality assessment in the area of forest science. In a recent 724 comprehensive review, Lachenbruch et al. (2011) suggested that adaptation to changing 725 mechanical constraints could explain some typical observed patterns. To test these 726 hypotheses, a first modelling approach would be to assess how the basic integrative traits 727 SB, SW or PC vary with wood radial variations according to simultaneous changes of other 728 dissociated traits (size, shape, load) during growth. As already stated above in relation to 729 scaling with size, inadequate attention has been accorded to shape (such as stem taper and 730 distribution of mass along the stem) and load factor (the total mass per unit of trunk 731 volume or the wind force per unit of crown surface). Indeed, they are as ontogenetically 732 plastic as wood properties. Thus, the ontogenetic change of shape, size, wood and load 733 properties cannot be studied separately. Foresters design forest growth models coupled 734 with wood quality models (Makela et al., 2010; Auclair and Nepveu, 2012). Since some of 735 these tools simulate simultaneous changes of height, diameter, stem profile, crown 736 expansion and wood variations, they could provide valuable support to investigate how 737 biomechanical performance varies with growth.

738

739 A general overview of biomechanical wood traits

The previous section ended with wood variations since they are likely to have an impact on
the ontogenetic trends of biomechanical traits. A general aspect of ecological strategies
concerns the way the different properties of wood are related to each other, and the
impact of these relationships on the whole organism performance.

744

745 Wood densities? Simple measurements for a set of distinct functions

Wood basic density is widely used as a key functional trait indicative of the tree life history
and biomechanical and physiological strategies (Chave *et al.*, 2009). In contrast with wood

- rangineering studies where properties of wood with partially dried cell walls are considered,
- cell walls in the living tree are fully saturated. Water bound within hydrophilic cell walls
- 750 causes swelling and modifies the cell wall mechanical properties (Siau, 1984). Conversely,

water present in cell lumens, also called free water, does not play any mechanical role except for the special case of parenchyma cells (<u>Niklas, 1988</u>; <u>Chapotin *et al.*, 2006</u>). It is therefore essential to distinguish between fresh wood density (ρ_{green}) representative of the load (ignoring branches and leaves), and basic density (ρ) representative of the wood mechanical properties (<u>Larjavaara and Muller-Landau, 2010</u>). Assuming that cell lumens are fully saturated in a living tree and that the density of cell wall material is 1500 kg m⁻³ (Kellogg and Wangaard, 1969), fresh density in kg m⁻³ can be approximated by:

$$\rho_{green} = 1000 + \frac{\rho}{2}$$
 (2)

However, the degree of cell lumen saturation may differ between trees or species, making fresh density a less reliable predictor of interspecific variability of mechanical properties. Basic density ρ is therefore the only appropriate parameter to use as an indicator of wood tissue properties (Larjavaara and Muller-Landau, 2012). The modulus of elasticity of green wood can be predicted from ρ (Fournier *et al.* 2006) as:

764
$$E = 10400 \left(\frac{\rho}{530}\right)^{1.03}$$
 (3)

765

766 Stiff, heavy and costly high-density wood. Does it make trees more or less safe?

767 Larjavaara and Muller-Landau (2010) demonstrated that "the lower the wood density is, 768 the greater SW will be". Such a result sounds surprising. In reality, wood basic density is not 769 only an indicator of wood strength but also of stem construction costs (approximated by 770 the dried biomass) per unit of volume. Therefore, with a given biomass, decreasing wood 771 density will increase the stem thickness. The question is then how the biomechanical 772 performance scales to wood density with a constant dry biomass, that involves a trade-off 773 between wood mechanical properties and stem thickness. Assuming a constant dry 774 biomass of the cross-section actually equals to fix ρD^2 . Then, as SW is proportional to $\sigma_n D^3$, if σ_{σ} varies linearly with ρ (as observed by wood scientists and reported by Chave *et al.*, 775 2009), the safety SW scales as $\rho^{-0.5}$ thus increases with decreasing density (Larjavaara and 776 777 Muller Landau, 2010). The problem becomes increasingly intricate when the biomechanical 778 performance studied is the safety against self-buckling (SB). In fact, wood basic density 779 becomes not only a proxy for mechanical stiffness E and a component of the construction cost ρ_{v} , but also a large part of the load since ρ_{τ} is the sum of (i) wood basic density, (ii) 780

781 stem water content per unit of trunk volume, and (iii) fresh biomass of leaves and branches 782 per unit of trunk volume. On the basis of a study of tropical trees of 8–25 cm in D (at breast 783 height), and carefully assuming relationships between loads (components of $\rho_{\rm r}$) and basic density ρ , King *et al.* (2006) inferred that SB varied slightly, in proportion to $\rho^{0.27}$. Actually, 784 our own simulations presented in Fig. 3 found a similar scaling of SB, between $\rho^{0.22}$ to $\rho^{0.26}$. 785 786 More recently, Anten and Schieving (2010) studied more generally how the cost to make a 787 trunk of given height and mechanical stability varies with wood basic density. They used the 788 two criterions SW and SB and concluded that a higher density would only result in a slight 789 increase in the safety margin.

790

791 Theoretical wood variations due to wood structure: ρ and MFA as key structural features

792 As mentioned above, the stiffness E and strength σ_c of wood tissues are usually assumed to 793 vary quite linearly with wood basic density (Chave et al., 2009; Fournier et al., 2006). This is 794 a general character of honeycomb cellular materials made of elongated cells, when cell wall 795 properties are constant (Gibson and Ashby, 1997). Since the density of cell wall material 796 does not significantly differ among wood species, wood basic density represents the 797 relative quantity of the cell wall in a given volume of wood made up of cells and lumens. 798 The quantity of the cell wall material naturally affects the wood tissue properties but 799 cannot explain all of the variability because cell wall stiffness and strength are neither 800 constant nor isotropic. Wood anatomical elements primarily responsible for load carrying 801 are generally aligned with the axis of elongation of the plant organ, which makes wood 802 much stiffer along this direction. Moreover, these load-bearing elements (fibres in 803 angiosperms and tracheids in gymnosperms) exhibit a multi-layered composite cell wall. 804 Some 75% to 85% of the total cell wall thickness consists of a so-called S2 layer made up of 805 a soft viscoelastic matrix that envelops stiff cellulose microfibrils. The latter are organised in 806 spirals that form an angle of typically 10–30°, referred to as the microfibril angle (MFA), 807 with the longitudinal fibre/tracheid axis (Fengel and Wegener, 1984), and are responsible 808 for most of the stiffness of the cell wall. Stiffness of wood tissues may therefore be 809 expressed as a function of basic density, MFA and cell wall stiffness as follows (Xu and Liu, 810 2004):

$$\frac{E}{\rho} = \frac{E_{cw}}{\rho_{cw}} \cos^4 MFA$$

where *E* is the elastic modulus or stiffness and the index *cw* stands for the cell wall material. Since ρ_{ew} is constant, the ratio E/ρ varies with the stiffness of the cell wall along the cell axis, which is primarily determined by the MFA and secondarily by the E_{ew} variations (Salmen and Burgert, 2009).

816 Concerning other wood properties, strength σ_c is similarly linked to the basic density and 817 MFA (Evans and Ilic, 2001; Lachenbruch et al., 2010; Read et al., 2011), whereas the 818 amount of strain generated during cell maturation α is quite independent of wood density 819 but related to the MFA (Clair et al., 2011). Recalling that stem motricity relies on the 820 asymmetry $\Delta \alpha$, the asymmetry $\Delta \alpha$ in hardwoods is the result of the differentiation of 821 tension wood on the upper side, whereas in softwoods, compression wood on the lower 822 side causes the asymmetry. Tension wood is more cellulosic with a low MFA, whereas 823 compression wood is more lignified with a high MFA.

824

825 Adapting stiffness in the 3D space of basic density, MFA and cell wall stiffness

826 When observed along wide biogeographic gradients, the correlation between basic density 827 ρ and the modulus of elasticity E (<u>Chave et al., 2009</u>) has a strong physical determinism, 828 usually interpreted as a trade-off between construction cost and wood performance. In 829 fact, along a wide range of variations of wood density, neither the MFA nor the cell wall 830 stiffness $E_{\sigma w}$ can offset the fact that "the more the better". The MFA is generally 831 considered in wood science to be intrinsically independent of basic density (Yang and 832 Evans, 2003; Boiffin, 2008; Donaldson, 2008). Theoretically, a tree can therefore "choose" 833 to vary one or both properties to adapt its tissues for different loading scenarios, using dense tissues with a low MFA to maximise stiffness E and strength σ_c , low-density tissues 834 835 with a high MFA to enhance the tissue flexibility (low E), and high-density tissues with a high MFA to enhance the energy absorbed before fracture (called toughness) (Burgert et 836 837 al., 2004; Burgert, 2006; Jungnikl et al., 2009). 838 Typical patterns of association between the three determinants of wood stiffness emerge 839 from the motor function: in softwoods, the high MFA and highly lignified cell walls of

- 840 compression wood are associated with lower *E*, with a trade-off between stem safety SB
- and stem motricity MV (<u>Almeras *et al.*, 2005</u>). Moreover, since the product $E\Delta\alpha$ is involved
- in postural control, this lower E could weaken the ability of a stem to maintain a given
- angle. In hardwoods, motricity is associated with a higher *E* and there is no trade-off but,

844 instead, a positive association between the performances of both skeletal and motricity845 function.

846

847 Some co-variations of ρ and MFA among species are ecologically driven

848 Studies on interspecific variations of the MFA in ecological contexts are rare since the MFA 849 has mainly been investigated in view of understanding variations in mechanical properties 850 of commercial species in terms of growth conditions (Saren et al., 2004; Medhurst et al., 851 2012) and possible wood quality improvement (Baltunis et al., 2007). In their pioneer 852 studies, Read *et al.* (2011) and Boiffin (2008) observed the diversity of the MFA, E and ρ 853 among some rainforest species. While Read et al. (2011) aimed at understanding how high 854 winds in New Caledonia constrained wood properties among 15 species of different sizes 855 and habits, Boiffin (2008) observed 22 species in French Guiana with a very low wind 856 constraint in understorey saplings from different functional groups of species along a light 857 demand gradient. In both samples, E is closely correlated to ρ (Table 3). In contrast to 858 Boiffin's observations, Read and co-workers (2011) reported that this relationship was not 859 related to the usual growth-survival trade-off in their sample. Indeed, relationships 860 between E and ρ have a strong physical determinism, regardless of the reason why species 861 with low and high wood densities coexist. Moreover, as shown in Table 3, whereas 862 \cos^4 (MFA) and ρ are independent among Boiffin's species (2008), they are closely linked in 863 Read et al. (2011), suggesting a strong differentiation of species along a stiffness axis in 864 these high wind conditions. The mean value of the cell wall stiffness, estimated as the average of $E/(\rho \cos^4(MFA))$, is higher in Read *et al.* (2011) (with a value of 23.9 GPa) than in 865 Boiffin (2008) (with a value of 21.2 GPa), also suggesting a greater stiffness of the cell wall. 866 867 Read et al. (2011) raised the question as to why such an opposition between stiff and not 868 stiff wood have been filtered in cyclone-prone environments. Indeed, French Guianese 869 species structured along the light demand gradient make it possible to explore wider 870 possibilities of associations between the MFA and ρ . Read *et al.* (2011) suggested further 871 studies of the ecological significance of the MFA. Actually, since the MFA is a key feature of 872 motricity, the low mean MFA of some angiosperm species (or high ones of some 873 gymnosperms) could indicate a higher occurrence of reaction wood and, therefore, a higher 874 motricity or postural control. We think that including motricity traits in such investigations 875 will bring new insights into the question of trade-offs or associations between ρ and the 876 MFA.

878 Beyond the skeleton: including maturation asymmetry $\Delta \alpha$ in wood databases

879 Studies of the evolutionary significance of PC or MV are in their infancy since they require 880 measurements of $\Delta \alpha$, which are not the usually collected data in ecological studies. $\Delta \alpha$ is 881 related to reaction wood formation, which has been widely studied in wood anatomy. 882 Wood anatomy is strongly linked to evolutionary ecology (Carlquist, 2001). Would it be 883 possible to use wood anatomical traits as a proxy for $\Delta \alpha$? Indeed, using wood anatomy 884 databases to infer functional traits is becoming a common practice in ecology (Martínez-885 Cabrera *et al.*, 2011). However, translating these anatomical observations into $\Delta \alpha$ is an 886 unsolved problem, since $\Delta \alpha$ is more closely related to cell wall properties like MFA than to 887 cellular characteristics usually observed in wood taxonomy. Normal anatomical 888 observations related to reaction wood, for example concerning the occurrence of the G 889 layer among tree species, are not useful to assess variations in motricity (Clair et al., 2006) 890 because different cellular traits associated with different patterns of reaction wood have 891 converged to the same functionality of motricity traits (Scurfield, 1973). 892 Measurements of α through growth strain indicators (GSI) are now a standard method for

893 wood scientists (see the large database on European Beech in Jullien et al., 2013). In order 894 to enhance high throughput and non-destructive assessment with the sampling methods 895 commonly used in field ecology, these standards should be used to calibrate indirect 896 methods using the empirical correlation between GSI and the tangential diameter of an 897 increment core (Ferrand, 1982), or, in a more reliable way, the relationship between GSI 898 and MFA (Yang et al., 2006). New tools such as Silviscan have made extensive 899 measurements of MFA easier (Read et al., 2011), making it possible to interpret their 900 variations both as wood stiffness and strength variations related to SB and SW, and as $\Delta \alpha$

901 and PC or MV variations.

902 Once the appropriate metrology has been selected, the conditions in which maturation 903 strains are characterised (i.e., the sampling methods) when comparing PC or MV among 904 species along environmental gradients should also be carefully assessed. When $\Delta \alpha$ was 905 measured as a righting capacity under controlled conditions of lean disturbance, it was 906 found to be highly genetically determined (see Almeras *et al.*, 2009, or Sierra-De-Grado *et* 907 *al.*, 2008). However, in natural conditions, $\Delta \alpha$ has a high phenotypical plasticity (Fournier *et* 908 *al.*, 1994b) since it rapidly acclimates to lean disturbances.

910 Challenges for future research in ecological biomechanics

911 Definition and integration of biomechanical crown traits

912 In the current definition of integrative traits (SW, SB, PC, MV), branching patterns are 913 included only through the load parameters (m, A_w , c_d , ρ_T). However, trees are complex 914 fractal structure (Plucinski et al., 2008). The guestion of relevant traits that capture the 915 biomechanical parts of branching patterns must therefore be addressed. Indeed, the 916 branching structure of the crown has been shown to play a significant role in wind failure 917 through resonant and structural damping behaviours (James et al., 2006). When studying 918 plant adaptation to the environment, ecology deals with a large number of plants and 919 environments, roughly described at the infra-individual level. Standard biomechanical 920 models based on numerical simulations in which each specific situation is described 921 through a large dataset of variables describing one single tree (e.g., Sellier and Fourcaud, 922 <u>2009</u>) are thus not appropriate. However, alternative biomechanical studies use 923 parsimonious representations to address questions about the impact of branching patterns 924 on mechanical safety (Plucinski et al., 2008; Rodriguez et al., 2008; Eloy, 2011; Lopez et al., 925 2011). In several models, a simple characterization of branching through two parameters 926 has been found to be sufficient: (i) the branching ratio, which is the reduction of diameter 927 through branching, and (ii) the slenderness exponent, which is the relationship between 928 length and diameter in branch segments (Rodriguez et al., 2008; Eloy, 2011;, Lopez et al., 929 2011). For example, using these two branching parameters, Lopez et al. (2011) investigated 930 the brittle reconfiguration of the crown, i.e., the way some branches preferentially break 931 under wind flows acting as mechanical "safety fuses". They proposed an elegant model 932 based on the scaling of the fluid-loading with respect to the critical stress (a criterion similar 933 to SW). Similarly, Eloy (2011) demonstrated that Leonardo's rule (i.e., the total cross-934 section of branches is conserved across branching nodes) can be a mechanical adaptation 935 to winds. In our opinion, although such models seem very simplistic at first glance, they 936 represent a great potential for ecological studies since they are based on very few 937 parameters of load, size and shape, similarly to popular seminal works such as that of 938 Greenhill (1881).

939

940 Assessing the evolutionary importance of motricity

941 As already mentioned above, studies of ecological significance of the variability of motricity 942 traits PC or MV require data about $\Delta \alpha$, which are not as common and available as other 943 wood traits. Using measurements of all other traits of PC, Jaouen (2007) demonstrated the 944 importance of $\Delta \alpha$ varations in sapling growth strategy by *reductio ad absurdum* arguments. 945 She simulated the successive curvatures and leans of saplings under the assumption of $\Delta \alpha$ 946 =0 (and, therefore, PC=0) for different species competing in a tropical rainforest 947 understorey, under the assumption that the lean has been slightly disturbed at an early 948 stage of growth (Fig. 5). With no capacity of reaction, plants should bend more and more 949 since gravitational curvature acts alone. Then, due to their extreme slenderness and quite 950 high centre of mass, trees would achieve high tilt angles that are even not viable in some 951 species (such as Vm in Fig. 5). Moreover, since stiffness and loads strongly differ between 952 species, this theoretical tilt angle would be highly variable between species. Indeed, such 953 leans and lean variations between species are not observed (Fig.5), demonstrating that 954 motricity is active and that motricity traits necessarily differ between species, as already 955 shown in Fig. 4.

956 However, in nature, trees experience successive disturbances, and the way an observed 957 lean is reached at a given time depends on the whole history of growth and disturbances. In 958 such a context, the success of the righting and straightening process relies on how MV can 959 rapidly adapt after the disturbance. As reported by Almeras et al. (2002) who studied the 960 bending of apricot tree shoots, and as shown in theoretical simulations of Fig. 5, even a 961 small difference in stem form at oblique stages before disturbance and in growth rates in 962 response to disturbance could lead, through the reciprocal dependencies between form 963 and growth, to a considerable divergence in its later development. In particular, the timing, 964 size and frequencies of the disturbances should be considered using conceptual approaches 965 of the ecology of disturbances (Johnson and Miyanishi, 2007). Formalising these problems 966 in changing environments along growth trajectories could deeply modify our 967 representation of motricity in natural forests, so far focused on reaction wood formation 968 (Dassot et al., 2012). Indeed, features other than the maturation strain asymmetry 969 $(\Delta \alpha)$, such as the relative timing of growth in height, thickness and leaf biomass, may be of 970 greater importance (Almeras et al., 2004). When observing buttress morphology in 971 rainforest species, Chapman et al. (1998) concluded that most buttresses are opportunistic 972 organs, the efficiency of which lies in their adaptability to respond to development crises 973 such as gap openings. Actually, as buttresses act as mechanical guy ropes (Clair et al., 974 2003), their formation cause an efficient posture control, without any reaction wood. By

975 the same token, modelling MV or PC in thick and rigid stems of lianas or palm trees, which

976 do not grow in thickness from concentric rings, remains an open question.

977 From a practical point of view, all these studies should use extensive measurements of lean

978 using simple methods (Collet et al., 2011), or new digitising techniques such as T-LIDAR,

- 979 whose uses are expanding in the areas of ecology and forestry (<u>Dassot *et al.*, 2011</u>).
- 980

981 Towards greater communication between sensory mechanobiology and tree ecology

982 It is now widely accepted that plants are sensitive to environmental signals, and that signal983 driven responses explain a large part of the phenotypical plasticity (<u>Givnish, 2002</u>). Plants

984 are, in particular, extremely sensitive to wind-induced deformations (Moulia et al., 2011),

as well as to leaning (Moulia and Fournier, 2009), and the thigmomorphogenetic and

986 gravitropic responses are likely to be adaptive in many situations (Jaouen et al., 2010).

987 However, these responses have been widely ignored in tree ecology.

988 This may be due to the fact that thigmomorphogenesis and gravitropism have long been 989 investigated by plant physiologists in particular, leading to very detailed descriptions at the 990 cellular and molecular level. However, the situation has changed over the last decade. Just 991 as for motricity, parsimonious and generic integrative models have been developed for 992 wind mechanosensing (the S3m model of Moulia et al., 2011) and for postural control (the 993 AC model of Bastien et al., 2013), both of which have been validated on a large set of 994 species and plant habits. These models allow for simple but relevant traits to be defined. 995 For example, Bastien et al. (2013) showed that the mechanosensitive control of posture 996 depends on a single dimensionless parameter B, which is the ratio between the 997 gravisensitivity to lean and the proprioceptive sensitivity of curvature. Moreover, this ratio 998 can be accurately estimated by taking photos at two stages after a leaning disturbance. 999 Finally, these approaches have also revealed genetic markers that may be used as traits of 1000 mechanosensitivity (Chevolot et al., 2011; Moulia et al., 2011). There is still a significant 1001 amount of work to be done before we can define simple sensory mechanobiological 1002 measurements for tree ecology. In particular, a major challenge will be to integrate these 1003 models over much longer periods of time such as the life span of trees or even climatic 1004 changes. Nevertheless, we think that the conditions are now favourable to promote better 1005 and more fruitful communication between sensory mechanobiology and biomechanical 1006 ecology.

1008 Glossary of abbreviations and symbols: list (alphabetical order) and definition

- *A_w*: wind surface area that creates an obstruction to wind flow, depending on crown
- 1010 dimensions (m²).
- *b*: ratio of relative height growth to relative diameter growth (d*H*/*H*)/(d*D*/*D*), i.e., exponent
- 1012 of the relation $H^{\sim}D^{b}$ (dimensionless).
- c_d : drag coefficient (dimensionless).
- 1014 D: diameter of the cross-section at the stem base (m).
- D(X): diameter of the stem cross-section at X-level (m).
- dC_g/dD : rate of gravitational curvature (downward and positive when weight increases) per
- 1017 unit of radial growth in diameter near the base (m^{-2}) .
- dC_m/dD or $dC_m/dD(X)$: rate of reaction curvature (upward and negative in the case of
- 1019 gravitropism) due to maturation per unit of diameter growth, at the stem base or at X-level 1020 (m^{-2}) .
- 1021 dD/dt: radial growth velocity, usually expressed in mm/year; dD/dt is then twice the annual
- tree ring width.
- dR_+ : tree ring width on one side + (m).
- 1024 d*R*.: tree ring width on the opposite side (m).
- *E*: modulus of elasticity (also called Young's modulus) (N m^{-2}).
- E_{cw} : modulus of elasticity of cell wall material (N m⁻²).
- F_b : self-buckling form factor, $F_b = 0.1785(|m-4n+2|).(2n+1)J_{\frac{4n-4}{m-4n+2}}^{-1}(0)$
- 1028 (dimensionless).

 F_g : growing weight form factor, $F_g = \frac{2}{(m+1)(2n+1)}$ (dimensionless).

 F_m : interaction between maturation strains and radial growth asymmetry, which enhances

- 1031 the motricity (dimensionless).
- F_w : wind form factor that represents the interaction between crown shape and wind
- 1033 profiles (dimensionless).
- 1034 g: gravity acceleration (N kg⁻¹).
- *H*: total height of the tree (m).
- *H_c*: critical self-buckling height (m).
- H_g : height of the centre of mass (m).
- H_w : height of the centre of wind drag pressure (m).
- *I*: second moment of area of the cross-section (m⁴).

- 1040 k_m : eccentricity of radial growth, $k = (R_r R_l)/(R_r + R_l)$ between -1 and 1
- 1041 (dimensionless).
- 1042 k_w : ratio H_w/H , smaller than 1 (dimensionless).

1043 *m*: biomass profile distribution, defined by $M(x) = \rho_T V \left(\frac{H-X}{H}\right)^m$, dimensionless. *m*

- 1044 represents the relative height of the centre of mass as $m+1 = H/H_q$.
- 1045 *M*(*X*): biomass supported above X-level (kg).
- 1046 MV: tropic Motion Velocity. Capability of a new peripheral wood to induce a curvature from
- 1047 the maturation of a new peripheral layer of wood during one unit of time. MV is a
- 1048 curvature rate ($m^{-1}s^{-1}$).
- 1049 $M_w(X)$: bending moment induced by wind at X-level (N m).

1050 *n*: taper, defined as $D(x) = D\left(\frac{H-X}{H}\right)^n$, dimensionless. Note that *n* can be estimated easily

- 1051 from the form factor $\frac{V}{D^2 H}$ of volume equations of forestry as $\frac{\pi}{4(2n+1)} = \frac{V}{D^2 H}$
- 1052 PC: Posture Control. Ratio of reaction curvature to gravitational curvature (dimensionless).
- 1053 SB: tree Safety factor against self-Buckling. Ratio of the maximum height the tree can reach
- 1054 (while remaining self-supporting with other parameters kept constant), to its actual height
- 1055 (dimensionless).
- 1056 SW: Safety against Wind. Tree resistance to wind calculated as the critical pressure $\rho_{air} g$
- 1057 U_w^2 (N m⁻²).
- 1058 T: general symbol for a trait T.
- 1059 U_w : wind velocity (m s⁻¹).
- 1060 V: volume of the trunk (m^3).
- 1061 $\Delta \alpha \text{ or } \Delta \alpha(X)$: contrast of maturation strain in the new ring of wood of a growing stem, at
- 1062 the stem base or X-level (dimensionless).
- 1063 φ : mean lean of the stem, angle from the vertical (radian).
- 1064 v_{T} : general power of a dissociated T in the expression of an integrative trait.
- 1065 ρ : wood basic density, which is the mass of dried wood per unit of fresh volume (kg m⁻³).
- 1066 ρ_{air} : density of air in kg m⁻³. ρ_{air} can be calculated from temperature, air relative humidity
- 1067 and elevation. For 15°C, 60% of relative humidity, ρ_{air} =1.21 kg m⁻³ at sea level.
- 1068 ρ_{cw} : basic density of the cell wall material, ρ_{cw} =1500 kg m⁻³.
- 1069 ρ_{green} : density of green wood in the living tree, ratio of fresh mass (dry matter and water) to
- 1070 fresh volume, in (kg m^{-3}) .
- 1071 ρ_{T} : total fresh biomass supported, including leaves, trunk and branches, per unit of trunk 1072 volume (kg m⁻³).

1073 σ_w or $\sigma_w(X)$: bending stress induced by wind forces, at the stem base or at X-level (N m⁻²).

1074 σ_c or $\sigma_c(X)$: wood critical stress usually measured by bending tests (as the standard MOR),

1075 at the stem base or at X-level (N m^{-2}).

1076 τ_{τ} : ontogenetic trend of a dissociated trait T.

1077

1078 Supplementary material

1079 Supplementary file: SBcalculation.xls (in .xls format, Microsoft[®]). This tool makes it possible

1080 to recalculate the safety factors SB of Fig. 3. It can be applied for further assessments of SB,

avoiding the use of two simple formulas (trees of constant diameter, cylindrical, with no

1082 crown and water load, no taper, etc.).

1083

1084 Acknowledgements

- 1085 This work was supported by the French National Research Agency (ANR) through the
- 1086 Laboratory of Excellence ARBRE (ANR-12- LABXARBRE-01). Some re-analysed data came
- 1087 from the WOODIVERSITY project of the ANR "Biodiversity" programme (2006-2009). We
- 1088 thank Juliette Boiffin and Emmanuel Duchateau, both Master's students in 2008, who
- 1089 contributed to the reflection on this study, and Bruno Ferry who helped to find the
- 1090 demographic traits in Fig. 4. We are also grateful to Gail Wagman who improved the
- 1091 English, and to an anonymous reviewer for stimulating comments.

References

Achim A, Ruel JC, Gardiner BA, Laflamme G, Meunier S. 2005. Modelling the vulnerability of balsam fir forests to wind damage. *Forest Ecology and Management* **204**, 35-50.

Almeras T, Costes E, Salles JC. 2004. Identification of biomechanical factors involved in stem shape variability between apricot-tree varieties. *Annals of Botany* **93**, 1-14.

Almeras T, Derycke M, Jaouen G, Beauchene J, Fournier M. 2009. Functional diversity in gravitropic reaction among tropical seedlings in relation to ecological and developmental traits. *Journal of Experimental Botany* **60**, 4397-4410.

Almeras T, Fournier M. 2009. Biomechanical design and long-term stability of trees: Morphological and wood traits involved in the balance between weight increase and the gravitropic reaction. *Journal of Theoretical Biology* **256**, 370-381.

Almeras T, Gril J, Costes E. 2002. Bending of apricot tree branches under the weight of axillary growth : test of a mechanical model with experimental data. *Trees-Structure and function* **16**, 5-15.

Almeras T, Thibaut A, Gril J. 2005. Effect of circumferential heterogeneity of wood maturation strain, modulus of elasticity and radial growth on the regulation of stem orientation in trees. *Trees-Structure and function* **19**, 457-467.

Anten NPR, Schieving F. 2010. The role of wood mass density and mechanical constraints in the economy of tree architecture. *American Naturalist* **175**, 250-260.

Archer RR, Wilson BF. 1973. Mechanics of the compression wood response II. On the location, action, and distribution of compression wood formation. *Plant physiology* **51**, 777-782.

Auclair D, Nepveu G. 2012. The CAQ network in France: 15 years of brainstorming and cooperative work to connect forest resources and wood quality through modelling approaches and simulation software. *Annals of Forest Science* **69**, 119-123.

Baltunis BS, Wu HX, Powell MB. 2007. Inheritance of density, microfibril angle, and modulus of elasticity in juvenile wood of *Pinus radiata* at two locations in Australia. *Canadian Journal of Forest Research-Revue Canadienne De Recherche Forestiere* **37**, 2164-2174.

Banin L, Feldpausch TR, Phillips OL, Baker TR, Lloyd J, Affum-Baffoe K, Arets EJMM, Berry NJ, Bradford M, Brienen RJW, Davies S, Drescher M, Higuchi N, Hilbert DW, Hladik A, Iida Y, Abu Salim K, Kassim AR, King DA, Lopez-Gonzalez G, Metcalfe D, Nilus R, Peh KSH, Reitsma JM, Sonke B, Taedoumg H, Tan S, White L, Woell H, Lewis SL. 2012. What controls tropical forest architecture? Testing environmental, structural and floristic drivers. *Global Ecology and Biogeography* **21**, 1179-1190.

Baskin TI, Jensen OE. 2013. On the role of stress anisotropy in the growth of stems. *Journal of Experimental Botany*. 64 (15), XXXX-XXXX.

Bastien R, Bohr T, Moulia B, Douady S. 2013. Unifying model of shoot gravitropism reveals proprioception as a central feature of posture control in plants. *Proceedings of the National Academy of Sciences of the United States of America* 110, 755-760.

Boiffin J. 2008. Variabilité de traits anatomiques, mécaniques et hydrauliques ches les juvéniles de vingt-deux espèces d'arbres de sous-bois en forêt tropicales humide. Master thesis, Université Henri Poincaré, Nancy, France.

Boudaoud A. 2010. An introduction to the mechanics of morphogenesis for plant biologists. *Trends in Plant Science*. 15(6):353-60.

Burgert I. 2006. Exploring the micromechanical design of plant cell walls. *American journal of botany* **93**, 1391-1401.

Burgert I, Frühmann K, Keckes J, Fratzl P, Stanzl-Tschegg S. 2004. Structure-function relationships of four compression wood types: micromechanical properties at the tissue and fibre. *Trees-Structure and function* **18**, 480-485.

Butler DW, Gleason SM, Davidson I, Onoda Y, Westoby M. 2012. Safety and streamlining of woody shoots in wind: an empirical study across 39 species in tropical Australia. *New Phytologist* **193**, 137-149.

Cao J, Tamura Y, Yoshida A. 2012. Wind tunnel study on aerodynamic characteristics of shrubby specimens of three tree species. *Urban Forestry & Urban Greening* **11**, 465-476.

Carlquist S. 2001. *Comparative wood anatomy: systematic, ecological, and evolutionary aspects of dicotyledon wood*. Berlin: Springer.

Chapman CA, Kaufman L, Chapman LJ. 1998. Buttress formation and directional stress experienced during critical phases of tree development. *Journal of Tropical Ecology* **14**, 341-349.

Chapotin SM, Razanameharizaka JH, Holbrook NM. 2006. Abiomechanical perspective on the role of large stem volume and high water content in baobab trees (*Adansonia* spp.; Bombacaceae). *American Journal of Botany* **93**, 1251-1264.

Chave J, Coomes D, Jansen S, Lewis SL, Swenson NG, Zanne AE. 2009. Towards a worldwide wood economics spectrum. *Ecology Letters* **12**, 351-366.

Chevolot M, Louisanna E, Azri W, Leblanc-Fournier N, Roeckel-Drevet P, Scotti-Saintagne C, Scotti I. 2011. Isolation of primers for candidate genes for mechano-sensing in five Neotropical tree species. *Tree Genetics & Genomes* **7**, 655-661.

Clair B, Almeras T, Pilate G, Jullien D, Sugiyama J, Riekel C. 2011. Maturation stress generation in poplar tension wood studied by synchrotron radiation microdiffraction. *Plant Physiology* **155**, 562-570.

Clair B, Almeras T, Ruelle J, Fournier M. 2006. Reaction mechanisms for the shape control in angiosperms tension wood : diversity, efficiency, limits and alternatives *Proceedings of the fifth plant biomechanics conference, August 28th-september 1st, 2006, Stockholm, Sweden.* Stockholm, Suède: STFI-Packforsk AB, 467-472.

Clair B, Fournier M, Prévost MF, Beauchêne J, Bardet S. 2003. Biomechanics of buttressed trees : bending strains and stresses. *American journal of botany* **90**, 1349-1356.

Collet C, Fournier M, Ningre F, Hounzandji API, Constant T. 2011. Growth and posture control strategies in Fagus sylvatica and Acer pseudoplatanus saplings in response to canopy disturbance. *Annals of Botany* **107**, 1345-1353.

Coutand C, Fournier M, Moulia B. 2007. The gravitropic response of poplar trunks: key roles of prestressed wood regulation and the relative kinetics of cambial growth versus wood maturation. *Plant physiology* **144**, 1166-1180.

Darwin C, Darwin FE. 1880. The Power of movement in plants. London: Murray.

Dassot M, Constant T, Fournier M. 2011. The use of terrestrial LiDAR technology in forest science: application fields, benefits and challenges. *Annals of Forest Science* **68**, 959-974.

Dassot M, Fournier M, Ningre F, Constant T. 2012. Effect of tree size and competition on tension wood production over time in beech plantations and assessing relative gravitropic response with a biomechanical model. *American Journal of Botany* **99**, 1427-1435.

Dean TJ, Long JN. 1986. Validity of constant stress and elastic-principles of stem formation in *Pinus contorta* and *Trifolium pratense*. *Annals of Botany* **58**, 833-740.

de Langre E. 2008. Effects of wind on plants. Annual Review of Fluid Mechanics 40, 141-168.

Delcamp M, Gourlet-Fleury S, Flores O, Gamier E. 2008. Can functional classification of tropical trees predict population dynamics after disturbance? *Journal of Vegetation Science* **19**, 209-220.

Donaldson L. 2008. Microfibril angle: measurement, variation and relationship - a review. *IAWA Bulletin* **29**, 345-386.

Duchateau E. 2008. Diversité des capacités de réaction gravitropique de jeunes arbres en forêt tropicale humide. Master thesis, Université Henri Poincaré, Nancy, France.

Eloy C. 2011. Leonardo's rule, self-similarity, and wind-induced stresses in trees. *Physical Review Letters* **107**.

Ennos AR. 2000. The mechanics of root anchorage. *Advances in Botanical Research Incorporating Advances in Plant Pathology***33**, 133-157.

Evans R, Ilic J. 2001. Rapid prediction of wood stiffness from microfibril angle and density. *Forest products journal* **51**, 53 - 57.

Fengel D, Wegener G. 1984. *Wood. Chemistry, ultrastructure, reactions*. Berlin/New York: de Gruyter.

Ferrand JC. 1982. Study of growth stresses:1. Measurement method on increment cores. *Annales Des Sciences Forestieres* **39**, 109-142.

Fortunel C, Fine PVA, Baraloto C. 2012. Leaf, stem and root tissue strategies across 758 Neotropical tree species. *Functional Ecology* **26**, 1153-1161.

Fournier M, Baillères H, Chanson B. 1994a. Tree biomechanics : growth, cumulative prestresses, and reorientations. *Biomimetics* **2**, 229-251.

Fournier M, Chanson B, Thibaut B, Guitard D. 1994b. Measurement of residual growth strains at the stem surface. Observations on different species. *Annales Des Sciences Forestieres* **51**, 249-266.

Fournier M, Stokes A, Coutand C, Fourcaud T, Moulia B. 2006. Tree biomechanics and growth strategies in the context of forest functional ecology . In: Herrel A, Speck T, Rowe N, eds. *Ecology and biomechanics: a mechanical approach to the ecology of animals and plants*. Boca Raton, Florida, USA: CRC Press, 1-34.

Gardiner B, Byrne K, Hale S, Kamimura K, Mitchell SJ, Peltola H, Ruel J-C. 2008. A review of mechanistic modelling of wind damage risk to forests. *Forestry* **81**, 447-463.

Gibson LJ, Ashby MF. 1997. *Cellular solids. Structure and properties*. Cambridge: Cambridge University Press.

Givnish TJ. 2002. Ecological constraints on the evolution of plasticity in plants. *Evolutionary Ecology* **16**, 213-242.

Gordon JE. 1978. *Structures or why things do not fall down*. Harmondsworth, Penquin Books Ltd.

Greenhill A. 1881. Determination of the greatest height consistent with stability that a vertical pole or mast can be made, and of the greatest height to which a tree of given proportions can grow. *Proceedings of the Cambridge Philosophical Society*, Vol. 4, 65-73.

Grime JP. 2001. *Plant strategies, vegetation processes, and ecosystem properties*. Chichester; UK: John Wiley & Sons Ltd.

Hamilton JR, Thomas CK, Carvell KL. 1985. Tension wood formation following release of upland oak advance reproduction. *Wood and fiber science* **17**, 382-390.

Hejnowicz Z. 1997. Graviresponses in herbs and trees: A major role for the redistribution of tissue and growth stresses. *Planta* **203**, S136-S146.

Herault B, Bachelot B, Poorter L, Rossi V, Bongers F, Chave J, Paine CET, Wagner F, Baraloto C. 2011. Functional traits shape ontogenetic growth trajectories of rain forest tree species. *Journal of Ecology* **99**, 1431-1440.

Holbrook NM, Putz FE. 1989. Influence of neighbors on tree form : effects of lateral shade and prevention of sway on the allometry of *Liquidambar styraciflua* (sweet gum). *American journal of botany* **76**, 1740-1749.

Huang YS, Hung LF, Kuo-Huang LL. 2010. Biomechanical modeling of gravitropic response of branches: roles of asymmetric periphery growth strain versus self-weight bending effect. *Trees-Structure and Function* **24**, 1151-1161.

lino M. 2006. Toward understanding the ecological functions of tropisms: interactions among and effects of light on tropisms. *Current Opinion in Plant Biology* **9**, 89-93.

James KR, Haritos N, Ades PK. 2006. Mechanical stability of trees under dynamic loads. *American journal of Botany* 93, 1522-1530.

Jaouen G. 2007. Etude des stratégies biomécaniques de croissance des jeunes arbres en peuplement hétérogène tropical humide. *Thèse de doctorat, Université Henri Poincaré, Nancy, France*. 201p.

Jaouen G, Almeras T, Coutand C, Fournier M. 2007. How to determine sapling buckling risk with only a few measurements. *American Journal of Botany* **94**, 1583-1593.

Jaouen G, Fournier M, Almeras T. 2010. Thigmomorphogenesis versus light in biomechanical growth strategies of saplings of two tropical rain forest tree species. *Annals of Forest Science* 67, 211.

Johnson EA, Miyanishi K. 2007. *Plant disturbance ecology: the process and the response*. Academic Press.

Jullien D, Widmann R, Loup C, Thibaut B. 2013. Relationship between tree morphology and growth stress in mature European beech stands. *Annals of Forest Science* **70**, 133-142.

Jungnikl K, Goebbels J, Burgert I, Fratzl P. 2009. The role of material properties for the mechanical adaptation at branch junctions. *Trees-Structure and Function* 23, 605-610.

Kellogg RM, Wangaard FF. 1969. Variation in the cell-wall density of wood. *Wood and Fiber Science* **1**, 180-204.

King D, Loucks OL. 1978. Theory of tree bole and branch form. *Radiation and Environmental Biophysics* **15**, 141-165.

King DA, Davies SJ, Tan S, Noor NSM. 2006. The role of wood density and stem support costs in the growth and mortality of tropical trees. *Journal of Ecology* **94**, 670-680.

King DA, Davies SJ, Tan S, Noor NSM. 2009. Trees approach gravitational limits to height in tall lowland forests of Malaysia. *Functional Ecology* **23**, 284-291.

Kooyman RM, Westoby M. 2009. Costs of height gain in rainforest saplings: main-stem scaling, functional traits and strategy variation across 75 species. *Annals of Botany* **104**, 987-993.

Lachenbruch B, Johnson GR, Downes GM, Evans R. 2010. Relationships of density, microfibril angle, and sound velocity with stiffness and strength in mature wood of Douglas-fir. *Canadian Journal of Forest Research-Revue Canadienne De Recherche Forestiere* **40**, 55-64.

Lachenbruch B, Moore JR, Evans R. 2011. Radial variation in wood structure and function in woody plants, and hypotheses for its occurrence. In: Meinzer FC, Lachenbruch B, Dawson TE, eds. *Size-and age-related changes in tree structure and function*. Netherlands: Springer, 121-164.

Lang AC, Haerdtle W, Bruelheide H, Geissler C, Nadrowski K, Schuldt A, Yu M, von Oheimb G. 2010. Tree morphology responds to neighbourhood competition and slope in speciesrich forests of subtropical China. *Forest Ecology and Management* **260**, 1708-1715.

Larjavaara M. 2010. Maintenance cost, toppling risk and size of trees in a self-thinning stand. *Journal of Theoretical Biology* **265**, 63-67.

Larjavaara M, Muller-Landau HC. 2010. Rethinking the value of high wood density. *Functional Ecology* **24**, 701-705.

Larjavaara M, Muller-Landau HC. 2012. Still rethinking the value of high wood density. *American Journal of Botany* **99**, 165-168.

Lens F, Smets E, Melzer S. 2012. Stem anatomy supports *Arabidopsis thaliana* as a model for insular woodiness. *New Phytologist* **193**, 12-17.

Lopez D, Michelin S, de Langre E. 2011. Flow-induced pruning of branched systems and brittle reconfiguration. *Journal of Theoretical Biology* **284**, 117-124.

McMahon, TA. 1973. Size and shape in biology. Science 179, 1202–1204.

Makela A, Grace JC, Deckmyn G, Kantola A, Campioli M. 2010. Simulating wood quality in forest management models. *Forest Systems* **19**, 48-68.

Martínez-Cabrera HI, Schenk HJ, Cevallos-Ferriz SRS, Jones CS. 2011. Integration of vessel traits, wood density, and height in angiosperm shrubs and trees. *American Journal of Botany* **98**, 915-922.

Martone PT, Boller M, Burgert I, Dumais J, Edwards J, Mach K, Rowe N, Rueggeberg M, Seidel R, Speck T. 2010. Mechanics without muscle: Biomechanical inspiration from the plant world. *Integrative and Comparative Biology* **50**, 888-907.

Matsuzaki J, Masumori M, Tange T. 2006. Stem phototropism of trees: A possible significant factor in determining stem inclination on forest slopes. *Annals of Botany* **98**, 573-581.

Medhurst J, Downes G, Ottenschlaeger M, Harwood C, Evans R, Beadle C. 2012. Intraspecific competition and the radial development of wood density, microfibril angle and modulus of elasticity in plantation-grown *Eucalyptus nitens*. *Trees-Structure and Function* **26**, 1771-1780.

Menard L, McKey D, Rowe, N. (2009) Developmental plasticity and biomechanics of treelets and lianas in *Manihot aff. quinquepartita* (Euphorbiaceae): a branch-angle climber of French Guiana. *Annals of Botany* **103,** 1249-1259.

Moulia B. 2013 Plant biomechanics and mechanobiology are convergent paths to flourishing interdisciplinary research . *Journal of Experimental Botany* 64 (15), XXXX-XXXX.

Moulia B, Coutand C, Lenne C. 2006. Posture control and skeletal mechanical acclimation in terrestrial plants: implications for mechanical modeling of plant architecture. *American Journal of Botany* **93**, 1477-1489.

Moulia B, Fournier-Djimbi M. 1997. Optimal mechanical design of plant stems: the models behind the allometric power laws. In: *Proceedings of the First Plant Biomechanics Conference*. Reading, Centre for Biomimetics, Vincent JFV and Jeronimidis G (Eds).

Moulia B, Fournier M. 2009. The power and control of gravitropic movements in plants: a biomechanical and systems biology view. *Journal of Experimental Botany* **60**, 461-486.

Moulia B, Der Loughian C, Bastien R, Martin O, Rodríguez M, Gourcilleau D, Barbacci A, Badel E, Franchel G, Lenne C, Roeckel-Drevet P, Allain JM, Frachisse JM, Langre E, Coutand C, Fournier-Leblanc N, Julien JL. 2011. Integrative mechanobiology of growth and architectural development in changing mechanical environments. In: Wojtaszek P, ed. *Mechanical Integration of Plant Cells and Plants,* Springer Berlin Heidelberg. **9**, 269-302.

Niklas KJ. 1988. Dependency of the tensile modulus on transverse dimensions, water potential, and cell number of pith parenchyma. *American Journal of Botany* **75**, 1286-1292.

Niklas KJ. 1992. *Plant biomechanics An engineering approach to plant form and function*. Chicago: University of Chicago Press.

Niklas KJ. 1994. *Plant allometry. The scaling of form and process*. Chicago: University of Chicago Press.

Niklas KJ. 1997. Mechanical properties of Black Locust (*Robinia pseudoacacia* L.) wood. Size- and age-dependent variations in sap- and heartwood. *Annals of botany* **79**, 265-272.

Niklas KJ. 2000. Computing factors of safety against wind-induced tree stem damage. *Journal of Experimental Botany* **51**, 797-806.

Niklas KJ. 2007. Maximum plant height and the biophysical factors that limit it. *Tree Physiology* **27**, 433-440.

Niklas KJ, Cobb ED, Marler T. 2006a. A comparison between the record height-to-stem diameter allometries of pachycaulis and leptocaulis species. *Annals of Botany* **97**, 79-83.

Niklas KJ, Spatz H-C. 2000. Response to Klaus Mattheck's letter. *Trees-Structure and Function* **15**, 64-65.

Niklas KJ, Spatz HC. 2004. Growth and hydraulic (not mechanical) constraints govern the scaling of tree height and mass. *Proceedings of the National Academy of Sciences of the United States of America* **101**, 15661-15663.

Niklas KJ, Spatz HC. 2010. Worldwide correlations of mechanical properties and green wood density. *American Journal of Botany* 97, 1587-1594.

Niklas KJ, Spatz HC, Vincent J. 2006b. Plant biomechanics: an overview and prospectus. *American journal of botany* **93**, 1369-1378.

Osunkoya OO, Omar-Ali K, Amit N, Dayan J, Daud DS, Sheng TK. 2007. Comparative heightcrown allometry and mechanical design in 22 tree species of Kuala Belalong rainforest, Brunei, Borneo. *American Journal of Botany* **94**, 1951-1962.

Plucinski M, Plucinski S, Rodriguez-Iturbe I. 2008. Consequences of the fractal architecture of trees on their structural measures. *Journal of Theoretical Biology* **251**, 82-92.

Read J, Evans R, Sanson GD, Kerr S, Jaffre T. 2011. Wood properties and trunk allometry of co-occurring rainforest canopy trees in a cyclone-prone environment. *American Journal of Botany* **98**, 1762-1772.

Read J, Stokes A. 2006. Plant biomechanics in an ecological context. *American Journal of Botany* **93**, 1546-1565.

Rodriguez M, Langre Ed, Moulia B. 2008. A scaling law for the effects of architecture and allometry on tree vibration modes suggests a biological tuning to modal compartmentalization. *American Journal of Botany* **95**, 1523-1537.

Rowe N, Speck T. 2005. Plant growth forms: an ecological and evolutionary perspective. *New phytologist* **166**, 61-72.

Salmen L, Burgert I. 2009. Cell wall features with regard to mechanical performance. A review COST Action E35 2004-2008: Wood machining - micromechanics and fracture. *Holzforschung* **63**, 121-129.

Saren MP, Serimaa R, Andersson S, Saranpaa P, Keckes J, Fratzl P. 2004. Effect of growth rate on mean microfibril angle and cross-sectional shape of tracheids of Norway spruce. *Trees-Structure and Function* **18**, 354-362.

Schindler D, Bauhus J, Mayer H. 2012. Wind effects on trees. *European Journal of Forest Research* **131**, 159-163.

Scurfield G. 1973. Reaction wood: Its structure and function. Science 179, 647-655.

Sellier D, Fourcaud T. 2009. Crown structure and wood properties: Influence on tree sway and response to high winds. *American Journal of Botany* **96**, 885-896.

Siau JF. 1984. Transport processes in wood. Berlin Heidelberg: Springer.

Sierra-De-Grado R, Pando V, Martinez-Zurimendi P, Penalvo A, Bascones E, Moulia B. 2008. Biomechanical differences in the stem straightening process among *Pinus pinaster* provenances. A new approach for early selection of stem straightness. *Tree Physiology* **28**, 835-846.

Sterck FJ, Bongers F. 1998. Ontogenetic changes in size, allometry, and mechanical design of tropical rain forest trees. *American Journal of Botany* **85**, 266-272.

Stokes A. 2000. *The supporting roots of trees and woody plants: form, function and physiology*. Dordrecht, Netherlands: Kluwer Academic Publishers.

Swenson NG, Enquist BJ. 2007. Ecological and evolutionary determinants of a key plant functional trait: Wood density and its community-wide variation across latitude and elevation. *American Journal of Botany* **94**, 451-459.

Taneda H, Tateno M. 2004. The criteria for biomass partitioning of the current shoot: Water transport versus mechanical support. *American Journal of Botany* **91**, 1949-1959.

Tateno M. 1991. Increase in lodging safety factor on thigmomorphogenetically dwarfed shoots of mulberry tree. *Physiologia Plantarum* **81**, 239-243.

Tobin B, Cermak J, Chiatante D, Danjon F, Di Iorio A, Dupuy L, Eshel A, Jourdan C, Kalliokoski T, Laiho R, Nadezhdina N, Nicoll B, Pages L, Silva J, Spanos I. 2007. Towards developmental modelling of tree root systems. *Plant Biosystems* **141**, 481-501.

Turner IM. 2001. *The ecology of trees in the tropical rain forest*. Cambridge: Cambridge UniversityPress.

van Gelder HA, Poorter L, Sterck FJ. 2006. Wood mechanics, allometry, and life-history variation in a tropical rain forest tree community. *New Phytologist* **171**, 367-378.

Violle C, Navas M-L, Vile D, Kazakou E, Fortunel C, Hummel I, Garnier E. 2007. Let the concept of trait be functional! *Oikos* **116**, 882-892.

Waghorn MJ, Watt MS. 2013. Stand variation in Pinus radiata and its relationship with allometric scaling and critical buckling height. *Annals of Botany* **111**, 675-680.

Watt MS, Moore JR, Facon J-P, Downes GM, Clinton PW, Coker G, Davis MR, Simcock R, Parfitt RL, Dando J, Mason EG, Bown HE. 2006. Modelling environmental variation in Young's modulus for Pinus radiata and implications for determination of critical buckling height. *Annals of Botany* **98**, 765-775.

Westoby M, Falster DS, Moles AT, Vesk PA, Wright IJ. 2002. Plant ecological strategies: Some leading dimensions of variation between species. *Annual Review of Ecology and Systematics* **33**, 125-159.

Wright IJ, Reich PB, Westoby M, Ackerly DD, Baruch Z, Bongers F, Cavender-Bares J, Chapin T, Cornelissen JHC, Diemer M, Flexas J, Garnier E, Groom PK, Gulias J, Hikosaka K, Lamont BB, Lee T, Lee W, Lusk C, Midgley JJ, Navas ML, Niinemets U, Oleksyn J, Osada N, Poorter H, Poot P, Prior L, Pyankov VI, Roumet C, Thomas SC, Tjoelker MG, Veneklaas EJ, Villar R. 2004. The worldwide leaf economics spectrum. *Nature* **428**, 821-827.

Wright SD, McConnaughay KDM. 2012. Interpreting phenotypic plasticity: the importance of ontogeny. *Plant Species Biology* **17**: 119-131.

Sultan SE. 2000. Phenotypic plasticity for plant development, function and life history. *Trends in Plant Science* **5**, 537-542.

Xu P, Liu H. 2004. Models of microfibril elastic modulus parallel to the cell axis. *Wood Science and Technology* **38**, 363-374.

Yang JL, Bailleres H, Evans R, Downes G. 2006. Evaluating growth strain of Eucalyptus globulus Labill. from SilviScan measurements. *Holzforschung* **60**, 574-579.

Yang JL, Evans R. 2003. Prediction of MOE of eucalypt wood from microfibril angle and density. *Holz als Roh und Werkstoff* **61**, 449-452.

Yoshida M, Okuyama T. 2002. Techniques for measuring growth stress on the xylem surface using strain and dial gauges. *Holzforschung* **56**, 461-467.

Zhang S-B, Slik JWF, Zhang J-L, Cao K-F. 2011. Spatial patterns of wood traits in China are controlled by phylogeny and the environment. *Global Ecology and Biogeography* **20**, 241-250.

Legends of tables

Table 1: Synthesis of the four traits: Safety against Wind (SW) as the critical wind pressure, Safety against Self-Buckling (SB) as the ratio of critical buckling height for the same trunk volume, to current height, Motricity (MV) as the active gravitropic curvature rate during radial growth, Posture Control performance (PC) as the ratio of the gravitropic curvature to the gravitational one, at a given angle φ (the limit 1 is the long-term stable regime where the tree maintains a constant lean φ). For each trait, the table summarizes the way to calculate it as a combination of dissociated variables, the types of the different variables involved (size, shape, wood, load), and the allometric scaling laws between size variables that maintain a constant value.

Table 2: General method for assessing ontogenetic trends on an integrative trait from a sampling of trees that represent an ontogenetic trajectory (case study: safety against self-buckling of a sample of *Oxandra asbeckii* at the sapling stage, re-analysing data from Jaouen *et al.* (2007)). The first two lines provide the mean values and the coefficient of variation for each component T. The third line τ_T is the power exponent (ontogenetic trend) from fitting the trait T to the developmental variable H. The fourth v_T gives the power of T in the integrative trait SB. In the last line, the sum of products $\tau_T v_T$ gives the ontogenetic trend of the integrative trait (SB in this case), broken down into trends for each component.

Table 3: Scaling of E with ρ and cos⁴(MFA) using data from Read *et al.* (2011) and Boiffin (2008). Wood characteristics were measured on increment cores and silviscan (X-ray tomography and diffraction) in Read *et al.* (2011), whereas Boiffin (2008) measured E of entire stems in a universal testing machine (bending test), and MFA by X-ray diffraction.

Table 1 (erratum : ligne 2 trait SB remplacer 2+1 par 2n+1)

Trait	Expression as a function of size, wood, load and	Size	Resulting scaling	Shape	Wood	Load factors
	shape variables	variables	laws between	factors	resistance or	
			size variables to		motor	
			maintain a		properties	
			stable trait			
			(everything else			
			being constant)			
SW	$\pi\sigma_c D^3$	D, A_w, H	$D^3 \sim A_w H$	k_w, F_w	σ_{c}	$c_{d}, k_{w}, F_{w}, A_{w}$
	$16 c_d A_w H k_w F_w$					
SB	$0.88 H^{-1} V^{1/4} E^{1/4} (\rho_T g)^{-1/4} F_b^{1/2}$	H,VorD	$H \sim V^{1/4}$	F _b	Е	ρ_T
	or		or			
	$0.83 H^{-3/4} D^{1/2} E^{1/4} (\rho_{\pi} q)^{-1/4} (2+1)^{-1/4} F_{\rm b}^{1/2}$		$H \sim D^{2/3}$			
MV	$F_m \Delta \alpha \ dD$	dD	dD p2	-	Δα	-
	$\frac{-4}{D^2} \frac{dt}{dt}$	dt'	$\frac{dt}{dt} \sim D^{-}$			
РС	$E \Delta \alpha \qquad F_m D$	H, D	$H \sim D^{1/2}$	b, F _g	$E,\Delta\alpha$	ρ _T ,sinφ
	$\frac{4(1+b)\rho_T g \sin\varphi}{F_g} \frac{F_g}{H^2}$			_		

Table 2

Trait T	H (m)	V (m ³)	ρ_T (g/cm ³)	F _b	E (MPa)	SB
Mean value	7.0	7.5 10 ⁻³	1.6	2.2	14200	1.41
Coefficient of variation (%)	40%	155%	22%	18%	10%	18%
Ontogenetic trends, τ_T (T \approx H $^{\tau_T}$)	1	2.726	-0.097	0.128	-0.018	-0.235
Power of T in SB formula, v_T	-1	0.25	-0.25	0.5	0.25	-
$v_T \tau_T$: Contribution of T to SB	-1	0.68	0.024	0.065	-0.005	-0.235

Table 3

Wood trait T	ρ	cos ⁴ (MFA)	E
Mean value			
Boiffin	0.64	MFA=15°	12.2 GPa
Read	0.66	MFA=12°	14.3 GPa
Pearson coefficient of LogE vs. LogT			
Boiffin	0.78	0.25	1
Read	0.79	0.83	1
Pearson coefficient of Logp vs. LogT			
Boiffin	1	0.08	0.78
Read	1	0.75	0.79

Legends of figures

Figure 1: The four different processes of biomechanical traits with graphical representations of geometrical traits.

Figure 2: Reproduced from Niklas (2000). Safety against wind inside one wild cherry tree as a function of distance from top of tree (H-X). The safety factor here is the dimensionless quotient of the critical wind pressure to the wind drag pressure experienced at the stem element level (83 segments of the same tree were used in the numerical computation). The tree safety is then characterised by a set of safety factors along the the tree height X. Three different wind speeds (10, 20 and 50 m/s) are simulated, leading to three different safety factors for the same stem element design. The single safety factor SW defined in the text can be calculated from the minimum values of Niklas's safety factor along the height, at different wind speeds, as $\rho_{air} U_w^2 \min(U_w)$. On the right side, tree silhouette and measured wind speed profiles.

Figure 3: Variations of safety factors against self-buckling SB as a function of wood basic density ρ , independently of size and slenderness. SB was calculated for a tree of constant D=20 cm and H=20 m: (i) Cylinder made of dry wood: safety factor calculated from the maximum height at a constant diameter (as done in Sterck and Bongers, 1998); (ii) Cylinder made of fresh wood: safety factor calculated from the maximum height at a constant wood volume; (iii) Tapered stem: everything else similar to (ii); (iv) Crowned stem, which is the (iii) situation with additional loads of branches; and (v) Crowned tree carrying epiphytes, i.e., (iv) where a quite small mass but with a high centre of mass has been added. Wood modulus of elasticity E is linked to wood basic density (equation 3). The density ρ_T is given by ρ in (i), wood fresh density given by equation (2) in (ii) and (iii), a mean value of 1400 kg/m³ in (iv) (mean value of Jaouen *et al.*, 2007), a mean value of 1540 kg/m³ in (v) assuming the biomass of epiphytes is 10% of the tree biomass. Except for cylinders (i) and (ii) where n=0, the taper n is 0.6 (mean value observed by Jaouen *et al.*, 2007). The biomass profile distribution is m= 2n+1 for the tapered stem (iii), m=1.5 (mean value observed by Jaouen *et al.*, 2007) for the crowned stem (iv), and m=1.27 in (v), which means that the centre of mass of epiphytes is located at 80% of the total tree height. SB is constant with ρ in (i), scales as $\rho^{0.22}$ in (ii) and (iii), and as $\rho^{0.26}$ in (iv) and (v).

Figure 4: Relationships between mortality rate and biomechanical traits PC and SB at sapling stages on a set of tropical species. Spearman correlation coefficients are R=-0.55 (p=0.07) for PC and R=-0.47 (p=0.14) for SB. Observations from the experimental plots of Paracou in French Guiana (Jaouen *et al.*, 2007; Delcamp *et al.*, 2008). Mortality rates are those of Delcamp *et al.* (2008) for control (not harvested) plots. Functional groups are also developed in Delcamp *et al.* (2008): ST = strongly shade-tolerant species, small to medium size; T = shade-tolerant species, medium size; MT = mid shade-tolerant species,

emergent; H = long-lived heliophilous species of the canopy. The species biomechanical traits were calculated as in Jaouen *et al.* (2007), on 1370 saplings for morphological data (H, D, b and φ) and sub-sampling for other variables (m, n, ρ_T , E, $\Delta \alpha$). All data comes from Jaouen (2007) except $\Delta \alpha$ in PC. $\Delta \alpha$ data come from the Wood Diversity project (Duchateau, 2008). Since Duchateau (2008) presented results on only nine species, unpublished data on *Eperua falcata* and *Pradosia cochlearia* has been added.

Figure 5: Basal (between 0 and 2 m) leans on a community of tropical saplings. Plain lines represent leans simulated under the assumption of no motricity (PC=0), along growth trajectories, from an initial disturbance of 8 degrees at an initial diameter (at 1 m in height) of 1 cm. Simulations used the equation of the gravitational curvature rate $\frac{dC_g}{dD}$ and mean traits measured on each species, as developed in Jaouen (2007). Dots are observed leans for the whole

set of trees and species (adapted from Jaouen, 2007).

Figure 1



Figure 2



Figure3



Figure 4





