



**HAL**  
open science

## Use of the C4.5 machine learning algorithm to test a clinical guideline-based decision support system.

Jean-Baptiste Lamy, Anis Ellini, Vahid Ebrahimiinia, Jean-Daniel Zucker, Hector Falcoff, Alain Venot

### ► To cite this version:

Jean-Baptiste Lamy, Anis Ellini, Vahid Ebrahimiinia, Jean-Daniel Zucker, Hector Falcoff, et al.. Use of the C4.5 machine learning algorithm to test a clinical guideline-based decision support system.. Studies in Health Technology and Informatics, 2008, 136, pp.223-8. hal-00912885

**HAL Id: hal-00912885**

**<https://hal.science/hal-00912885>**

Submitted on 2 Dec 2013

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Use of the C4.5 machine learning algorithm to test a clinical guideline-based decision support system

Jean-Baptiste LAMY <sup>a,1</sup>, Anis ELLINI <sup>a</sup>, Vahid EBRAHIMINIA <sup>a</sup>  
Jean-Daniel ZUCKER <sup>a</sup>, Hector FALCOFF <sup>b</sup> and Alain VENOT <sup>a</sup>

<sup>a</sup> *Laboratoire d'Informatique Médicale et de Bio-informatique (LIM&BIO), UFR SMBH, Université Paris 13, Bobigny, France*

<sup>b</sup> *Société de Formation Thérapeutique du Généraliste (SFTG), Paris, France*

**Abstract.** Well-designed medical decision support system (DSS) have been shown to improve health care quality. However, before they can be used in real clinical situations, these systems must be extensively tested, to ensure that they conform to the clinical guidelines (CG) on which they are based. Existing methods cannot be used for the systematic testing of all possible test cases.

We describe here a new exhaustive dynamic verification method. In this method, the DSS is considered to be a black box, and the Quinlan C4.5 algorithm is used to build a decision tree from an exhaustive set of DSS input vectors and outputs. This method was successfully used for the testing of a medical DSS relating to chronic diseases: the ASTI critiquing module for type 2 diabetes.

**Keywords.** Knowledge-based systems, Expert systems, Evidence-based guidelines, Decision support, Assessment-evaluation, Type 2 diabetes, Machine learning

## Introduction

Clinical Guidelines (CG) are useful for physicians [1]. However, guidelines printed on paper are difficult to use efficiently during medical consultation [2]. This has led to the development of decision support systems (DSS) based on the CG [3]. The ASTI project in France provides an example of such a system. This DSS aims to improve therapeutic care for patients with chronic diseases, by helping physicians to take into account the recommendations expressed in CG [4]. ASTI includes a critiquing module — a rule-based system composed of a knowledge base and an inference engine [5, 6]. This module is automatically activated when the physician writes a drug prescription; it compares the treatment proposed by the physician with that recommended by the CG, and issues an alert if they differ. ASTI has been applied to several chronic diseases, including type 2 diabetes.

---

<sup>1</sup>Corresponding Author: Jean-Baptiste Lamy, LIMBIO, UFR SMBH, Université Paris 13, 74 rue Marcel Cachin, 93017 Bobigny cedex, France; E-mail: jibalamy@free.fr.

Before their use in real clinical situations, DSS such as ASTI must be extensively tested to ensure their medical validity. Errors may be encountered at various levels: in the knowledge base, in the inference engine or in the system specifications. Few papers on the testing of medical DSS have been published, although knowledge-based system verification has been widely studied outside the medical domain. Preece [7, 8] distinguishes between two types of verification method. *Static methods* do not require the DSS to be run. They involve the inspection of the knowledge base by an expert, or checking for syntactic errors, logical errors (*e.g.* unsatisfiable conditions) or semantic errors (*e.g.* a male patient being pregnant) in the knowledge base [9]. These methods may identify errors, but cannot ensure the total absence of errors [7, 10].

*Dynamic methods* involve the running of the DSS with a test base. The test base may be written manually, or using automatic methods aiming to identify the “most relevant” test cases [10, 11]. The intervention of a human expert is required to determine whether the responses of the DSS are satisfactory. These methods therefore cannot be used for the systematic testing of all possible test cases, as there are generally too many such cases for manual review by an expert.

We aimed to check the conformity of the ASTI critiquing module to the CG used to design it — the French CG for type 2 diabetes [12]. We present a new dynamic verification method for “rebuilding” the knowledge contained in the CG from an exhaustive set of test cases, using machine learning techniques to construct a decision tree. We applied this method to the ASTI critiquing module for type 2 diabetes, and present the results of a comparison, by an expert, of the generated decision tree with the original CG. Finally, we discuss the potential value of such a method and possibilities of applying this method to other DSS.

## 1 Methods

We propose a general verification method with three steps: (1) generation of an exhaustive set of possible input vectors for the DSS, and running of the DSS to determine the output for each input vector, (2) extraction of knowledge from the set of (input vector, output result) pairs by applying learning or generalization algorithms, and (3) comparison, by an expert, of the knowledge extracted in step 2 with the original source of knowledge (here, the CG).

### 1.1 Generating Input Vectors and Outputs

It is possible to generate an exhaustive (or almost exhaustive) set of input vectors by considering a set of variables expressing the various elements of input for the DSS, and generating all possible combinations of the variables' values. Continuous variables (*e.g.* glycosylated haemoglobin) are limited to a few values, corresponding, for example, to the threshold values expressed in the CG. Finally, the output associated with each input vector is obtained by running the DSS.

### 1.2 Building the Decision Tree

A decision tree is built from the input vectors and the associated outputs, using C4.5 [13], a reference algorithm in machine learning. Pruning must be disabled, to ensure

0% error in the tree. Factorization rules are applied to reduce the size of the tree: (1) if all the children of a given node include the same element of a recommendation (*e.g.* a recommended drug treatment), this element of information can be included in the node and removed from its children, (2) if a variable can take several values leading to the same recommendations, the largest set of such values can be grouped together as “<other>”.

### 1.3 Comparing the Decision Tree with Clinical Guidelines

Finally, the decision tree is compared with the CG by experts. These experts should be medical experts briefly trained in the evaluation method and the reading of the decision tree. The experts must check that the treatments recommended by the tree conform to the CG, and should check the CG to ensure that none of the recommendations included in the CG are missing from the tree.

## 2 Results

The general method presented above was applied to the ASTI critiquing module for type 2 diabetes.

### 2.1 Generating Input Vectors

The inputs of the ASTI critiquing module are related to (a) the patient's clinical condition, (b) the patient's treatment history, (c) the new treatment proposed by the physician, and (d) efficiency and the tolerance of the current treatment. For type 2 diabetes, these inputs correspond to the variables shown in Table 1. Doses were taken into account, using the following rule: if the treatment proposed is the same as the current treatment, the dose is understood to be modified: reduced if the problem identified was poor tolerance, and increased if the problem identified was low efficiency. A few rules were used to eliminate unrealistic combinations. For example, if the current treatment is diet, there cannot be drug intolerance.

Combinations of the values given in Table 1 generated an almost exhaustive set of input vectors. Only cases in which the patient had more than one drug intolerance, and cases involving quadritherapies (which are never recommended by the CG) were excluded. This approach yielded 147,680 input vectors.

### 2.2 Building the Decision Tree

The data were initially processed so that the list of valid treatments was used as the classifying variable, rather than the critiquing module's output (*i.e.* conform, not optimal or non conform). The decision tree was then built using the C4.5 algorithm. Before the factorization rules described in the methods section were applied, the decision tree included 87 nodes. After the application of these rules, the final tree included only 60 nodes (see Figure 1).

For a patient with a BMI of 25 kg/m<sup>2</sup> and an HbA1c level of 7%, with a current treatment of diet plus metformin shown to be inefficient, the decision tree recommends a first-line treatment of diet + metformin (with a higher dose of metformin as the

Variable	Definition	Retained values
Diabetes discovery	Was diabetes discovered at an early or late stage ?	Early, late
BMI	Body mass index	$\leq 27 \text{ kg/m}^2$ , $> 27 \text{ kg/m}^2$
HbA1c	Glycosylated hemoglobin levels	$\leq 6.5\%$ , $> 6.5\%$ (*)
Current type of treatment	The type of the treatment currently administered	No treatment, diet only, monotherapy, bitherapy, tritherapy, single daily insulin treatment, fractioned insulin treatment
Current treatment	Treatment currently administered	19 possible values, <i>e.g.</i> : no treatment, diet, diet+metformin
Problem	The medical problem preventing the continuation of current treatment	Low efficiency, poor tolerance
Efficiency	Level of efficiency of the current treatment (meaningful only if the problem is low efficiency)	Partial, null
Poorly tolerated drug	The drug in the current treatment responsible for intolerance (meaningful only if the problem is poor tolerance)	Metformin, sulfonamide, glinide, alpha-glucosidase inhibitors, glitazone, very slow-acting insulin, delayed-action insulin
Proposed treatment	The new treatment proposed by the physician, which may or may not conform to the CG	(As for current treatment)

**Table 1:** The list of variables considered for type 2 diabetes, and the values retained. (\*) Only two values were considered, as ASTI makes use of treatment efficiency to determine whether the treatment should be strengthened.

recommended treatment is the same as the current treatment, see section 3.1), diet + glinide, diet + sulfonamide, diet + metformin + glinide or diet + metformin + sulfonamide, and a second-line treatment of diet + glinide + alphaglucoSIDaseinhibitors (AGI), diet + metformin + AGI, diet + sulfonamide + AGI, diet + metformin + glinide, diet + metformin + sulfonamide or diet + metformin + glitazone.

For a patient with a BMI of  $29 \text{ kg/m}^2$  and an HbA1c level of 6.8%, with a current treatment of diet plus metformin, and who does not tolerate the metformin, the decision tree recommends a first-line treatment of diet + AGI, and a second-line treatment of diet + glinide or diet + sulfonamide. However, decreasing the dose of the metformin is not recommended.

### 2.3 Comparing the Decision Tree with Clinical Guidelines

We asked two physicians to compare the decision tree with the original CG. The experts found the decision tree to be easily readable, although one of them was at first confused by the use of only two levels of treatment intention on the tree. The experts searched the tree for the therapeutic recommendations expressed in the CG, and found that none of them was missing. They also ensured that the various branches of the tree lead to the same prescription that the CG. Consequently, the experts considered the tree to conform to the CG.



*e.g.* a DSS using the k-nearest neighbours algorithm), which includes most of medical knowledge based DSS. To apply our testing method, one should first identify the DSS inputs, generate an almost exhaustive set of input vectors, and run the DSS for each of them. Then, one should extract knowledge from the input vectors and output data, using C4.5 or another learning algorithm. Finally, one should ask a human expert to compare the extracted knowledge to the knowledge that was used to build the DSS.

Three problems might be encountered when applying this method. First, it can be difficult to generate an almost exhaustive set of the DSS's input vectors, in particular when the number of variables is very high, *e.g.* for hypertension CG, or when there are many continuous variables. However medical recommendations usually define threshold values that allow to discretize continuous variable easily, as we have done for diabetes type 2. Second, it might be impossible to generate in a reasonable time the outputs for all input vectors (DSS too slow or too many vectors). Third, learning algorithms might be unadapted to the knowledge used by the DSS. For example, rule conditions such as "if the patient has two or more risk factors from a given list..." cannot be learnt by C4.5. To solve this problem, one can use more sophisticated learning algorithms, *e.g.* based on description logic, or derive input variables from the other variables, *e.g.* the number of risk factors could be added as an input variable.

In conclusion, the ASTI critiquing module for type 2 diabetes was almost exhaustively tested in this study, using an original black-box dynamic verification method. This method appears generic and therefore applicable to other medical DSS.

## References

- [1] J.M. Grimshaw and I.T. Russel. Effect of clinical guidelines on medical practice: a systematic review of rigorous evaluations. *Lancet*, **342**(8883):1317–22, 1993.
- [2] J.C. Dufour, J. Bouvenot, P. Ambrosi, D. Fieschi, and M. Fieschi. Textual Guidelines versus Computable Guidelines: A Comparative Study in the Framework of the PRESQUID Project in Order to Appreciate the Impact of Guideline Format on Physician Compliance. In proceedings of the AMIA Annual Symposium, pages 219–223, Washington, DC, 2006.
- [3] P.A. De Clercq, J.A. Blom, H.H.M. Korsten, and A. Hasman. Approaches for creating computer-interpretable guidelines that facilitate decision support. *Artificial intelligence in medicine*, **31**:1–27, 2004.
- [4] B. Seroussi, J. Bouaud, H. Dreau, H. Falcoff, C. Riou, M. Joubert, C. Simon, G. Simon, and A. Venot. ASTI: a guideline-based drug-ordering system for primary care. In *Medinfo*, volume 10, pages 528–32, the Netherlands, 2001.
- [5] V. Ebrahiminia, C. Riou, B. Seroussi, J. Bouaud, S. Dubois, H. Falcoff, and A. Venot. Design of a decision support system for chronic diseases coupling generic therapeutic algorithms with guideline-based specific rules. *Studies in Health Technology and Informatics*, **124**:483–488, 2006.
- [6] V. Ebrahiminia, C. Duclos, M.E. Toussi, C. Riou, R. Cohen, and A. Venot. Representing the patient's therapeutic history in medical records and in guideline recommendations for chronic diseases using a unique model. *Studies in Health Technology and Informatics*, **116**:101–6, 2005.
- [7] A. Preece. Micro-level knowledge management, chapter Evaluating verification and validation methods in knowledge engineering, pages 123–145. Morgan-Kaufman, 2001.
- [8] A. Preece. Validation of knowledge-based systems: The state-of-the-art in north america. *Journal of communication and cognition - Artificial intelligence*, **11**:381–413, 1994.
- [9] G. Duftschmid and S. Miksch. Knowledge-based verification of clinical guidelines by detection of anomalies. *Artificial intelligence in medicine*, **22**:23–41, 2001.
- [10] M. Shwe, S.W. Tu, and L.M. Fagan. Validating the knowledge base of a therapy-planning system. *Methods of Information in Medicine*, **28**(1):36–50, 1988.
- [11] A. Ellini, V. Ebrahiminia, A. Venot, and J. Nobécourt. Une expérience originale de test automatisé d'un système d'aide à la décision clinique basé sur les guides de bonnes pratiques. In *IC'2007*, 2007.
- [12] HAS. Traitement médicamenteux du diabète de type 2. Available at [http://www.has-sante.fr/portail/display.jsp?id=c\\_459266](http://www.has-sante.fr/portail/display.jsp?id=c_459266), November 2006.
- [13] J. R. Quinlan. *C4.5: Programs for Machine Learning*. Morgan Kaufmann, 1993.