## Auxiliary Material: Determination of total amount of adsorbed fluid


We follow the procedure described by Ottiger et al. [2006]. Total sorption  $n_T$  [mol/g] can be approximated as the summation of excess sorption  $n_{ex}$  [mol/g] and the fluid mass not-in-excess in the volume of the adsorbed phase, proportional to the volume of the adsorbed phase per unit mass of coal  $V_{ads}/m_{coal}$  [cm<sup>3</sup>/g] and the bulk mass density of the fluid  $\rho_b$ [mol/cm<sup>3</sup>]:

$$n_T = n_{ex} + \frac{V_{ads}}{m_{coal}}\rho_b$$

If  $n_T$  is assumed to follow a Langmuir trend (reasonable for low-medium pressure), then,  $n_{ex}$  can be fitted with three parameters  $n_u$ ,  $P_{Lu}$ , and  $V_{ads}/m_{coal}$ :

$$n_{ex} = n_u \frac{p}{p + P_{Lu}} - \frac{V_{ads}}{m_{coal}} \rho_b$$

The following figure shows the three parameter fitting of the experimental data presented by *Gensterblum et al.* [2010] for Brzeszcze coal. The fitting permits recovering an estimate of the adsorbed phase volume per unit mass of coal  $V_{ads}/m_{coal} = 0.055 \text{ cm}^3/\text{g}$ , which can be used to estimate the total sorption amount  $n_T$ .



Determination of total adsorption amount for coal immersed in the adsorbate (unjacketed) at 45°C. (a) Excess sorption [mmol/g] measured for Brzeszcze coal by different laboratories (symbols - *Gensterblum et al.* [2010]) and 3-parameter Langmuir fitted model. (b) Total sorption amount adding the mass of fluid ( $V_{ads}/m_{coal}$ )  $\rho_b$  (CO<sub>2</sub> bulk mass density computed from EOS *Span* and Wagner [1996]). (c) Total adsorption amount per unit volume of undeformed specimen [mol/L] obtained with  $\rho_{coal} = 1343 \text{ kg/m}^3$ .