

Original and accurate polynomial interpolation method to determine the surface currents with a minimum of known points in the case of diffraction and radiating problems.

> J.P. Damiano, J.Y. Dauvignac LEAT, UNSA-CNRS, Valbonne, France

P. Dubois, C. Dedeban, P.Y. Garel France Télécom R&D, La Turbie, France

> J.P. Zolesio CNRS-INRIA, Valbonne, France



# OUTLINE

✓Introduction

- Technical modeling
  - Analysis
  - Interpolation

✓Results

✓Conclusion





The report Solving electromagnetic scattering and radiation problems is time consuming.


Our aim

To determine the values of the current flow over a large frequency band using a very few number of frequency samples.



To develop an accurate method based on the formal knowledge of the derivatives of the current flow.

To associate an interpolation method.



ICEAA'03

#### 



## **TECHNICAL MODELING > Analysis**

# Current flows and its derivatives known at some frequency samples. Choice of an interpolation method > polynomial function (degree 5). Critical points.



Interpolation method

Some test functions to choice the optimal interpolation method.

Influence of the number of sampling points.


Applications to various geometries.



# The optimized and adaptive SR3D code



### **TECHNICAL MODELING > Interpolation**





## **TECHNICAL MODELING > Interpolation**


#### Case 1 : Only the values of the function are known


Least-square method. Polynomial and trigonometric functions. Taylor series and Chebyshev approximations. Piecewise polynomial functions. Splines, cubic splines, B-splines functions. Rational functions. Padé approximations. Thiele interpolations. *and so on.* 


#### Case 2 : The values of the function and its derivatives are known

Splines, cubic splines, B-splines functions. Piecewise polynomial functions

We compared various methods







ICEAA'03




## RESULTS

- A line slotted patch antenna
  - The quadratic error
  - The radiation patterns
- □ A circular waveguide
  - The VSWR
- Optimized computing time




A line slotted patch antenna : 4.5 - 6.5 GHz


#### Variations of the quadratic error





A line slotted patch antenna : 5.1 GHz






ICEAA'03



## Optimized computing time





# CONCLUSION

An original and accurate optimization technique.

An efficient model based on the formal derivatives of the current flow.

Very good and promising results.

✓A true time-saving

Thank you for your attention

Grazie mille per la vostra pazienza