



**HAL**  
open science

# Stochastic uncertainty quantification of the eddy current in human body by using polynomial chaos decomposition

Gaignaire Roman, Riccardo Scorretti, Ruth V. Sabariego, Christophe Geuzaine

## ► To cite this version:

Gaignaire Roman, Riccardo Scorretti, Ruth V. Sabariego, Christophe Geuzaine. Stochastic uncertainty quantification of the eddy current in human body by using polynomial chaos decomposition. IEEE Transactions on Magnetics, 2012, 48 (2), pp.451 - 454. 10.1109/TMAG.2011.2171925. hal-00934420

**HAL Id: hal-00934420**

**<https://hal.science/hal-00934420>**

Submitted on 22 Jan 2014

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

# Stochastic uncertainty quantification of the eddy current in human body by using polynomial chaos decomposition

Roman Gaignaire✱, Riccardo Scorretti♡, Ruth V. Sabariego✱ and Christophe Geuzaine✱

The finite element method can be used to compute the electromagnetic fields induced in the human body by environmental extremely low frequency (ELF) fields. However, the electric properties of tissues are not precisely known and may vary depending on the individual, his/her age and other physiological parameters. In this paper, we account for the uncertainties on the conductivities of the brain tissues and spread them out to the induced fields by means of a non-intrusive approach based on the chaos Hermite polynomial with the finite element method as a black box [1], [2]. After showing the convergence of the method, we compute the probability to be over the thresholds define by the norms.

*Index Terms*—Non-intrusive methods, polynomial chaos decomposition, stochastic methods

## I. INTRODUCTION

THE uncertainty in electrical parameters, as well as the variability of the human body between different individuals, is a major problem in numerical dosimetry. Determining the conductivities of the human tissues is since years subject of research [3]. Tissues are highly heterogeneous “materials” and possibly anisotropic [4]. The properties of tissues change rather quickly after death [5], so that measurements performed *in vitro* on excised tissues may not be representative. Besides for ethical reasons, most of *in vivo* measurements have been performed on animals. Moreover, the age [6] and the physiological condition [7] may also significantly alter these properties. Obtaining data for characterising a foetus is even harder [8]. At ELF frequencies, the measurements are performed either by identifying an equivalent RC circuit, or by a four-point measurement. At those frequencies, electrode polarization is (another) major source of errors. Some tentatives have been performed [7], [9] for numerically estimating the conductivity and permittivity by modeling tissues as porous media, with a limit success. Gabriel *et al* have done a huge work [10]–[12] by collecting most of the existing data, and building a tissue database, which is currently the reference for dosimetric computations [13]. In a recent work [14], new measurements have shown large differences with respect to previously published data: the new values of conductivities are often higher and muscle-type tissues are found to be much less anisotropic. More recently, several techniques based on the magnetic resonance (MR) have been proposed. MR electric impedance tomography (MREIT) methods are based on the detection of the shielding effect of electrical currents on the magnetic field; these electrical currents may be either induced by the MR device itself, by a third external coil [15], or injected into the body through electrodes [16]. Diffusion tensor MREIT methods are based on the proportionality between water diffusion tensor and electrical conductivity. These last techniques are particularly interesting when dealing with brain [17], because the diffusion signal in this organ is strong enough, while other MREIT techniques are not applicable due to the high resistivity of the skull. Moreover, this technique provides information about the anisotropy of tissues. Using this technique, Sekino *et al*

found higher conductivity values [18] than those reported by Gabriel in [10]. All MRI based techniques share the enormous advantage to be applicable *in vivo* in humans beings. In spite of the amount of work accomplished, the dielectric properties of human tissues are still poorly known: e.g. at 50 Hz the conductivities of the white and grey matter in [11] and [19] span, respectively, within [0.0753 ; 0.5155] and [0.0533 ; 0.302] S/m. Therefore, it is crucial to quantify the effect of this uncertainty on the electromagnetic fields computed in the human body. One could use a extremely time-consuming Monte-Carlo (MC) simulation to statistically characterise the induced fields (some weeks in our model). In this paper, we use a chaos polynomial (CP) approach, the so-called *non intrusive probabilistic algorithms*, which assumes that the variances of conductivities are finite [1], [2] and allows to completely characterise the induced field in the probabilistic dimension with a much lower computational cost (a few hours).

## II. INCORPORATION OF STOCHASTIC UNCERTAINTY

### A. Deterministic framework

The fields induced in the human body are computed by the finite element (FE) method using a  $\phi$  – formulation. Details of this formulation and the phantom used (Fig. 1) can be found in [20]. We simulate the exposure to the field generated by an infinite cable (current  $I = 1000$  A at 50 Hz) placed at a few centimeters from the left side of the head. In the literature on protection against ELF fields, three global quantities are generally computed for each organ from the current density  $\mathbf{j}$ : the (spatial) average  $j_{Avg}$ , the maximum value  $j_{max}$ , and the 99% percentile  $j_{99-perc}$  [21]. Similar definitions exist for the electric field  $\mathbf{e}$ . The basic restriction of the 1998 edition of ICNIRP’s recommendations [22] is based on  $j_{max}$ , while the 2010 edition [23] focus on  $e_{99-perc}$ . In particular, for a 50 Hz occupational exposure the threshold values in the central nervous system (CNS) recommended by the ICNIRP are  $j_{max} < 10$  mA/m<sup>2</sup> and  $e_{99-perc} < 100$  mV/m.

### B. Uncertainties

In this paper, we focus on the fields induced in the brain. The conductivities of the white matter  $\sigma_W(\omega)$  and of the grey matter  $\sigma_G(\omega)$  are modeled within a probabilistic framework<sup>1</sup>,

Manuscript received July 1, 2011. Corresponding authors: R. Gaignaire, C. Geuzaine (e-mail: rgaignaire@gmail.com, cgeuzaine@ulg.ac.be).

<sup>1</sup>The notation:  $x(\omega)$  means that  $x$  is a random variable.




Fig. 1. a) Mesh of whole head; b) grey matter; c) and white matter.

by assuming that they are random variables defined on a probabilistic space  $\Theta, F, P$ . Therefore  $j_{Avg}, j_{max}, j_{99-perc}, e_{Avg}, e_{max}$  and  $e_{99-perc}$  turn out to be random as well. In particular, by using the maximum entropy principle [24] we model (arbitrarily)  $\sigma_G(\omega)$  and  $\sigma_W(\omega)$  as independent random variables, uniformly distributed:

$$\sigma_G(\omega) \sim U([0.0753 ; 0.5155]) \text{ (S/m)} \quad (1)$$

$$\sigma_W(\omega) \sim U([0.0533 ; 0.3020]) \text{ (S/m)} \quad (2)$$

### C. The non intrusive approach

As the conductivities of the brain and the cerebellum are two independent random variables of finite variance, we can expand them as a truncated series of order  $p_{in}$  in the bi-dimensional Hermite polynomials of a random gaussian vector  $\xi(\omega) = (\xi_1(\omega), \xi_2(\omega))$ , known as *Hermite chaos polynomials* [2]:

$$\sigma_G(\omega) \approx \sum_{i=0}^{P_{in}} \sigma_{G_i} \psi_i(\xi(\omega)) \quad (3)$$

$$\sigma_W(\omega) \approx \sum_{i=0}^{P_{in}} \sigma_{W_i} \psi_i(\xi(\omega)) \quad (4)$$

where  $\sigma_{G_i}$  and  $\sigma_{W_i}$  are scalar values that depend on the probabilistic law of the conductivities,  $P_{in} = C_{2+p_{in}}^{p_{in}}$  is the number of bi-dimensional polynomials of order less than  $p_{in}$ , and  $\psi_i$  is the  $i^{th}$  bi-dimensional polynomial of Hermite. To solve the stochastic problem, we use an approach based on a CP decomposition of both the conductivity and the induced fields [2]. We assume the conductivities to be of finite variance, with no assumption on the shape of the probabilistic distribution.

The values of those induced fields –the average current density in the brain  $\mathbf{j}_{Avg}(\omega) = \mathbf{j}_{Avg}(\xi(\omega))$ – are computed by the FEM from any couple of values  $(\sigma_G(\xi(\omega)), \sigma_W(\xi(\omega)))$ . The average density belongs to a space that can be spanned by the polynomials  $\psi(\xi(\omega))$  and thus written as a truncated

series to an order  $p_{out}$ :

$$\mathbf{j}_{Avg}(\omega) = \sum_{m=0}^{P_{out}} \mathbf{j}_{Avg_m} \psi_m(\xi(\omega)). \quad (5)$$

To compute the value of the unknown real coefficients  $\mathbf{j}_{Avg_m}$ , we use the orthogonality properties of the Hermite polynomials:

$$\mathbf{j}_{Avg_m} = \frac{E[\mathbf{j}_{Avg}(\omega) \psi_m(\xi(\omega))]}{E[\psi_m(\xi(\omega))^2]}, \quad (6)$$

where  $E[\cdot]$  is the mathematical expectation. The denominator can be computed analytically. The integral in the numerator is computed by means of a Hermite Gauss integration scheme with  $d$  integration points [2]:

$$E[\mathbf{j}_{Avg}(\omega) \psi_m(\xi(\omega))] \approx \sum_{i=1}^d \dots \sum_{j=1}^d w_{i,j} (\mathbf{j}_{Avg}((t_1, t_2)_{i,j})) \psi_m((t_1, t_2)_{i,j}), \quad (7)$$

with  $(t_1, t_2)_{i,j}$  the  $i, j$ -th Gauss point and  $w_{i,j}$  the associated weight in the bi-dimensional Cartesian rule. The deterministic problem must thus be computed  $d^2$  times, with the conductivity evaluated through (3) and  $(\xi_1(\omega), \xi_2(\omega)) = (t_1, t_2)_{i,j}$ ,  $i, j = 1, \dots, d$ .

## III. RESULTS AND DISCUSSION

The non intrusive method is governed by three parameters:  $p_{in}$ ,  $p_{out}$  and  $d$ ;  $p_{in}$  is linked to the precision on the approximation made on the input random variables  $\sigma_G(\omega)$  and  $\sigma_W(\omega)$ ,  $p_{out}$  is the order of truncation of the studied global quantities ( $j_{Avg}, j_{max}, j_{99-perc}$  and the corresponding quantities for the electric field) and  $d$  is the number of quadrature points. Herein, we have chosen  $p_{in} = 16$ , while  $p_{out}$  and  $d$  vary. For the sake of conciseness, we deal with the white and grey matter (though the method could handle other tissues during the same computation as well).

### A. Influence of the input parameters

The probabilistic density (PD) of  $e_{99-perc}$  in the grey matter obtained with  $p_{out} = 8$ ,  $p_{in} = 16$  and different values of  $d$  is shown in Fig. 2. The curves of the PD obtained with  $d = 10$  and  $d = 16$  are nearly superposed, what proofs the convergence of the method with increasing values of  $d$ . Concerning dispersion parameters as the mean and the standard deviation, the convergence is reached as soon as  $d \geq 4$  (mean:  $0.0487V/M$ , standard deviation:  $0.07$  when  $d = 2$  to  $0.0044$  as soon as  $d = 6$ ).

The PD of  $j_{max}$  in the white matter obtained with  $d = 16$ ,  $p_{in} = 16$  and different values of  $p_{out}$  are plotted in Fig. 3. Again, one observes that convergence is achieved as  $p_{out}$  increases. The value of  $p_{out}$  has a minor influence on the central dispersion parameters (mean and variance): the mean is constant and equal to  $13.1$  mA/m, and the standard deviation converges with  $p_{out} \geq 3$  to  $3.4$  mA/m. It can be observed that the support of the PD is bounded to  $21$  mA/m for  $p_{out} \geq 4$  (that is, most likely  $j_{max} < 21$  mA/m): conversely,  $p_{out} = 2$  would lead to the wrong conclusion that  $j_{max}$  may exceed  $21$  mA/m with a non negligible probability.




Fig. 2. Probabilistic density of  $e_{99-perc}$  in the grey matter for  $p_{out} = 8$ ,  $p_{in} = 16$  and  $d = 6$  (blue),  $d = 10$  (red),  $d = 16$  (green).




Fig. 4. Density of probability (in  $A/m^2$ ) of  $j_{Avg}$  (blue),  $j_{99-perc}$  (red) and  $j_{max}$  (green) in the grey matter ( $p_{in} = 16$ ,  $d = 16$ ).




Fig. 3. Density of probability of  $j_{max}$  ( $A/m^2$ ) in the white matter for  $d = 16$ ,  $p_{in} = 16$  and  $p_{out} = 2$  (black),  $p_{out} = 4$  (red),  $p_{out} = 6$  (green),  $p_{out} = 8$  (blue).

### B. Analysis of the results

The PD of  $j_{Avg}$ ,  $j_{99-perc}$  and  $j_{max}$  linked to the induced current density in the grey matter are represented in Fig. 4 for  $p_{out} = 4$  and  $p_{out} = 8$ . For  $p_{out} = 6$ , the curves are very close to those for  $p_{out} = 8$  so the method has converged. One observes that while  $j_{Avg}$  is always under to  $10 A/m^2$ , this does not hold for  $j_{99-perc}$  and  $J_{max}$ , which are likely to exceed this hazardous limit — the exact probability is computed hereafter.

The PD of  $e_{Avg}$ ,  $e_{99-perc}$  and  $e_{max}$  related to the electric field in the white matter are depicted in Fig. 5 for  $p_{out} = 4$  and  $p_{out} = 8$ . The curves for  $p_{out} = 4$  and  $p_{out} = 8$  are much more similar than in the previous case. These PDs are more peaked than those corresponding to the current density, i.e. they are less dispersed around their means. Moreover, the area under these curves for  $\|e\| > 100 mV/m$  equals 0 for  $e_{Avg}$  and  $e_{99-perc}$  and nearly 0 for  $e_{max}$ .




Fig. 5. Density of probability (in  $V/m$ ) of  $e_{Avg}$  (blue),  $e_{99-perc}$  (red) and  $e_{max}$  (green) in the white matter ( $p_{in} = 16$ ,  $d = 16$ ).

In order to avoid health hazards, ICNIRP recommends that in the central nervous system  $j_{max} \leq 10 mA/m^2$  [22] or  $e_{99-perc} \leq 100 mV/m$  [23]. As these global quantities are available as a polynomial expansion like (5), we can estimate the probability  $-p-$  that these recommendations are not fulfilled —thus, in the case of [22],  $p$  is:  $\mathcal{P}\{j_{max} \leq 10 mA/m^2\}$ . To this aim, a large number  $n$  of couples of independent values following a normal variable  $(\xi_{1i}, \xi_{2i})_{1 \leq i \leq 10^4}$  are sampled. The polynomial expansion (5) is evaluated for each pair of values and the number of occurrences (i.e. the number of pairs) for which the basic restriction is exceeded are counted. The probability  $p$  and the confident interval  $CI$  are estimated by means of the central limit theorem as:

$$p = \frac{\text{Number of occurrences}}{n} \quad (8)$$

$$CI = z_{.05/2} \sqrt{\frac{p(1-p)}{n}} \quad (9)$$

where  $z_{.05/2}$  is the confidence interval of 97.5% of a normal random variable. The cost of this computation is negligible

with regard to the coefficient evaluation via (6).

The probability that each of the global quantities exceeds the basic restriction for the simulated exposure has been computed with  $n = 10^5$  and the obtained values are reported in Table I. For instance, the third line in Table I reads: the probability for  $e_{max} > 100 \text{ mV/m}$  is of  $80\% \pm 0.27\%$  with a risk of  $5\%^2$ . According to most recent recommendations [23], the basic

TABLE I

PROBABILITY TO EXCEED THE THRESHOLD DEFINED BY THE NORMS.

Field	Probability in Grey matter	in white matter
$e_{avg}$	$0 \pm 0$	$0 \pm 0$
$e_{99-perc}$	$0 \pm 0$	$0 \pm 0$
$e_{max}$	$0.8 \pm 2.7 \times 10^{-3}$	$0.14 \pm 2.2 \times 10^{-3}$
$j_{avg}$	$0 \pm 0$	$0 \pm 0$
$j_{99-perc}$	$0.73 \pm 2.8 \times 10^{-3}$	$0.16 \pm 2.3 \times 10^{-3}$
$j_{max}$	$1 \pm 0$	$0.80 \pm 2.5 \times 10^{-3}$

restriction  $e_{99-perc} \leq 100 \text{ mV/m}$  is most likely fulfilled – it would not have been the case if we consider  $e_{max}$  instead of  $e_{99-perc}$ . Concerning the 1998 recommendations [22], the restriction  $j_{max} \leq 10 \text{ mA/m}^2$  is clearly not fulfilled for the grey matter (see also Fig. 4), while for the white matter the probability for  $j_{max}$  to exceed  $10 \text{ mA/m}^2$  is of 80%. These probabilities decrease respectively to 73% and 16% when dealing with  $j_{99-perc}$  instead of  $j_{max}$ .

IV. CONCLUSION

The proposed recommendations for avoiding health issues due to over-exposure to ELF radiations may require to evaluate the induced fields in the human body by dosimetric methods.

Unfortunately, these computations are largely affected by the uncertainty on the conductivities of human tissues. Indeed, an arbitrary security factor 3 is considered in [23] in order to account for “dosimetric uncertainties”.

We propose an effective method for quantifying the uncertainty on some relevant quantities (notably  $j_{max}$  and  $e_{99-perc}$ ), provided that a characterisation of the statistical distribution of the conductivities is available. Our simulations suggest that latest 2010 ICNIRP recommendations are more permissive than those in the former edition. However, it has to be pointed out that in our computations we use a quite pessimistic statistical law for the conductivities, and also that other sources of uncertainty (posture, physiognomy...) are disregarded.

ACKNOWLEDGMENT

This work has been supported by the Belgian French Community (ARC 09/14-02) and the Belgian Science Policy (IAP P6/21).

REFERENCES

[1] R. Gaignaire, G. Crevecoeur, L. Dupré, R. Sabariego, P. Dular, and C. Geuzaine, “Stochastic uncertainty quantification of the conductivity in eeg source analysis by using polynomial chaos decomposition,” *IEEE Trans. Mag.*, vol. 46, no. 8, pp. 3457–3460, 2010.

<sup>2</sup>i.e. the risk that the real probability is inferior to 79.23% or superior to 80.27% equals 5%.

[2] R. Gaignaire, O. Moreau, B. Sudret, and S. Clénet, “Propagation d’incertitudes en électromagnétisme statique par chaos polynomial et résolution non intrusive,” in *NUMELEC 2006, Lille*, 2006.

[3] L. Geddes and L. Baker, “The specific resistance of biological material—a compendium of data for the biomedical engineer and physiologist,” *Medical and Biological Engineering and Computing*, vol. 5, no. 3, pp. 271–293, 1967.

[4] F. Sachse, M. Wolf, C. Werner, and K. Meyer-Waarden, “Extension of anatomical models of the human body: Three-dimensional interpolation of muscle fiber orientation based on restrictions,” *Journal of Comp. Inf. Tech.*, vol. 6, no. 1, pp. 95–101, 1998.

[5] D. Haemmerich, O. Ozkan, J. Tsai, S. Staelin, S. Tungjitkusolmun, D. Mahvi, and J. Webster, “Changes in electrical resistivity of swine liver after occlusion and postmortem,” *Medical and Biological Engineering and Computing*, vol. 40, no. 1, pp. 29–33, 2002.

[6] C. Gabriel, “Dielectric properties of biological tissue: variation with age,” *Bioelectromagnetics*, vol. 26, no. S7, pp. S12–S18, 2005.

[7] C. Peratta, A. Peratta, J. Hand *et al.*, “Modelling the human body exposure to elf electric fields,” *Medical Physics*, vol. 37, p. 5561, 2010.

[8] R. Cech, N. Leitgeb, and M. Padiaditis, “Fetal exposure to low frequency electric and magnetic fields,” *Phys. Med. Biol.*, vol. 52, p. 879, 2007.

[9] S. W. Smye, C. J. Evans, M. P. Robinson, and B. D. Sleeman, “Modelling the electrical properties of tissue as a porous medium,” *Phys. Med. Biol.*, vol. 52, no. 23, pp. 7007–22, Dec. 2007.

[10] C. Gabriel, S. Gabriel, and E. Corthout, “The dielectric properties of biological tissues: I. Literature survey,” *Phys. Med. Biol.*, vol. 41, no. 11, pp. 2231–49, Nov. 1996.

[11] S. Gabriel, R. W. Lau, and C. Gabriel, “The dielectric properties of biological tissues: II. Measurements in the frequency range 10 Hz to 20 GHz,” *Phys. Med. Biol.*, vol. 41, no. 11, pp. 2251–69, Nov. 1996.

[12] —, “The dielectric properties of biological tissues: III. Parametric models for the dielectric spectrum of tissues,” *Phys. Med. Biol.*, vol. 41, no. 11, pp. 2271–93, Nov. 1996.

[13] R. F. D. Andreuccetti, “An internet resource for the calculation of the dielectric properties of body tissues,” <http://niremf.ifac.cnr.it/tissprop>.

[14] C. Gabriel, a Peyman, and E. H. Grant, “Electrical conductivity of tissue at frequencies below 1 MHz,” *Phys. Med. Biol.*, vol. 54, no. 16, pp. 4863–4878, 2009.

[15] S. Ueno and N. Iriguchi, “Impedance magnetic resonance imaging: a method for imaging of impedance distributions based on magnetic resonance imaging,” *J. appl. phys.*, vol. 83, p. 6450, 1998.

[16] H. J. Kim, Y. T. Kim, A. S. Minhas, W. C. Jeong, E. J. Woo, J. K. Seo, and O. J. Kwon, “In vivo high-resolution conductivity imaging of the human leg using MREIT: the first human experiment,” *IEEE Trans. Med. Imag.*, vol. 28, no. 11, pp. 1681–1687, 2009.

[17] M. Sekino, Y. Inoue, and S. Ueno, “Magnetic resonance imaging of electrical conductivity in the human brain,” *Magnetics, IEEE Transactions on*, vol. 41, no. 10, pp. 4203–4205, 2005.

[18] M. Sekino, H. Ohsaki, S. Yamaguchi-Sekino, N. Iriguchi, and S. Ueno, “Low-frequency conductivity tensor of rat brain tissues inferred from diffusion mri,” *Bioelectromagnetics*, vol. 30, no. 6, pp. 489–499, 2009.

[19] J. Latikka, T. Kuurne, and H. Eskola, “Conductivity of living intracranial tissues,” *Phys. Med. Biol.*, vol. 46, p. 1611, 2001.

[20] R. Scorretti, R. Sabariego, L. Morel, C. Geuzaine, N. Burais, and L. Nicolas, “Computation of induced fields into the human body by dual finite element formulations,” *submitted to IEEE Trans. Mag.*, 2011.

[21] P. J. Dimbylow, “Induced current densities from low-frequency magnetic fields in a 2 mm resolution, anatomically realistic model of the body,” *Phys. Med. Biol.*, vol. 43, no. 2, pp. 221–230, Feb. 1998.

[22] ICNIRP, “Guidelines for limiting exposure to time-varying electric, magnetic, and electromagnetic fields (up to 300 ghz),” *Health Phys*, vol. 74, no. 4, pp. 494–522, 1998.

[23] —, “Guidelines for limiting exposure to time-varying electric and magnetic fields (1 Hz to 100 kHz),” *Health physics*, vol. 99, no. 6, pp. 818–836, 2010.

[24] E. Jaynes, “Information theory and statistical mechanics,” *Phys. rev.*, vol. 108, no. 2, p. 171, 1957.