



HAL
open science

Femtosecond laser material processing with nondiffracting light

François Courvoisier, Amaury Mathis, Jinggui Zhang, Luc Froehly, Luca Furfaro, Maxime Jacquot, Remo Giust, Pierre-Ambroise Lacourt, John Michael Dudley

► **To cite this version:**

François Courvoisier, Amaury Mathis, Jinggui Zhang, Luc Froehly, Luca Furfaro, et al.. Femtosecond laser material processing with nondiffracting light. European congress and Exhibition on Advanced Materials and Processes (EUROMAT) 2013, Jan 2013, Spain. pp.A1I-I/K-TH-PM2-1. hal-00938936

HAL Id: hal-00938936

<https://hal.science/hal-00938936>

Submitted on 29 Jan 2014

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

Femtosecond Laser Material Processing with nondiffracting light

F. Courvoisier*, A. Mathis, J. Zhang, L. Froehly, L. Furfaro, M. Jacquot,
R. Giust, P.A. Lacourt, and J.M. Dudley

Département d'Optique P.M. Duffieux, Institut FEMTO-ST,
UMR 6174 CNRS Université de Franche-Comté, 25030 Besancon Cedex, France


francois.courvoisier@femto-st.fr

Although versatile and widely used, femtosecond laser micro-nanomachining faces a challenge for the fabrication of high aspect ratio or deep structures. The control of the profile along the longitudinal dimension is extremely difficult. In this context, our approach is based on controlling the direction of light rather than shaping the intensity pattern in one plane. Here we review our recent work in this field using Bessel beams and accelerating beams.

In Bessel beams, light propagates along the generatrix of a cone, with a fixed radial wavevector. Contrary to Gaussian beams, the femtosecond filamentation regime of Bessel beams can be stationary, and can generate extended plasma tracks in dielectrics. This allowed us to generate nanochannels in glass with aspect ratio up to 100:1 [1]. Numerical simulations of the nonlinear propagation in this regime show the importance of the conical structure in generating extremely dense plasmas [2].

Airy beams and more generally accelerating beams constitute another family of beams that possess quasi-nondiffracting behaviour and their nonlinear propagation can also be stationary. Their primary intensity lobe propagates along a curved trajectory that can be arbitrarily shaped even in the nonparaxial regime. Since this lobe is adjacent to a region where no light propagates, accelerating beams can be used for direct curved edge profiling and trench processing in transparent and opaque materials [3,4].

Our results show that controlling the linear and nonlinear propagation of ultrashort femtosecond laser pulses by nondiffracting beams is a key new technological approach for laser processing.



(a) Intensity distribution of a circularly accelerating beam. (b) Edge profiling on silicon and diamond.

References

- [1] M. K. Bhuyan et al, "High aspect ratio nanochannel machining using single shot femtosecond Bessel beams," *Appl. Phys. Lett.* **97**, 081102 (2010).
- [2] F. Courvoisier et al "Applications of femtosecond Bessel beams to laser ablation," *Appl. Phys. A*, DOI10.1007/s00339-012-7201-2, Online First (2012)
- [3] A. Mathis et al, "Micromachining along a curve: Femtosecond laser micromachining of curved profiles in diamond and silicon using accelerating beams", *Appl. Phys. Lett.* **101**,071110 (2012)
- [4] A. Mathis et al, "Direct machining of curved trenches in silicon with femtosecond accelerating beams", to be published in *J. Eur. Opt. Soc, Rapid Publ.* (2013)